

Appendix B

Highest Test Plots

Table of Contents

1. 2.4G Body-worn 0mm SAR 3

1. 2.4G Body-worn 0mm SAR

Date: 21.09.2026

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q26083136-2E dongle

Serial: S26083136-008

Communication System: UID 0, Bluetooth (0); Communication System Band: BLE; Frequency: 2478 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005
Medium parameters used (interpolated): $f = 2478\text{ MHz}$; $\sigma = 1.787\text{ S/m}$; $\epsilon_r = 37.977$; $\rho = 1000\text{ kg/m}^3$
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.91, 7.91, 7.91) @ 2478 MHz; Calibrated: 22.06.2026
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 22.06.2026
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP.1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/right side SRD2M 2478 MHz/Area Scan (9x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 0.0507 W/kg

Configuration/right side SRD2M 2478 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 5.717 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.0660 W/kg
SAR(1 g) = 0.040 W/kg; SAR(10 g) = 0.021 W/kg
Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 15 mm)
Ratio of SAR at M2 to SAR at M1 = 61.3%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.0566 W/kg

