



RADIO TEST REPORT

Applicant	:	Harman International Industries, Inc.
Address of Applicant	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Manufacturer	:	Harman International Industries, Inc.
Address of Manufacturer	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	3.1 CHANNEL SOUNDBAR WITH DOLBY ATMOS® AND WIRELESS SUBWOOFER
FCC Model No.	:	CINEMA SB580MK2 SUB, CINEMA SB581MK2 SUB, CINEMA SB582MK2 SUB, CINEMA SB583MK2 SUB, CINEMA SB584MK2 SUB, CINEMA SB585MK2 SUB, CINEMA SB586MK2 SUB, CINEMA SB587MK2 SUB, CINEMA SB588MK2 SUB, CINEMA SB589MK2 SUB, CINEMA SB590MK2 SUB, CINEMA SB591MK2 SUB, CINEMA SB592MK2 SUB, CINEMA SB593MK2 SUB, CINEMA SB594MK2 SUB, CINEMA SB596MK2 SUB, CINEMA SB597MK2 SUB, CINEMA SB598MK2 SUB, CINEMA SB599MK2 SUB, CINEMA SB540MK2 SUB, CINEMA SB541MK2 SUB, CINEMA SB542MK2 SUB, CINEMA SB543MK2 SUB, CINEMA SB544MK2 SUB, CINEMA SB545MK2 SUB, CINEMA SB546MK2 SUB, CINEMA SB547MK2 SUB, CINEMA SB548MK2 SUB, CINEMA SB549MK2 SUB
IC Model No.	:	CINEMA SB580MK2 SUB
FCC ID	:	APISB580SW2
IC	:	6132A-SB580SW2
HVIN	:	SB580SWMK2
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020, RSS-247 Issue 4 July 24, 2025, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021), ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
Report No.	:	DDT-RE26031216-2E10
Issue Date	:	2026/06/04
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2 nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	10
2.4.	Decision of final test mode	10
2.5.	Deviations of test standard	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	11
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	6 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result.....	14
4.5.	Test graphs	15
5.	99% Bandwidth	17
5.1.	Block diagram of test setup	17
5.2.	Limits	17
5.3.	Test procedure	17
5.4.	Test result.....	18
5.5.	Test graphs	19
6.	Maximum Peak Output Power.....	21
6.1.	Block diagram of test setup	21
6.2.	Limits	21
6.3.	Test procedure	21
6.4.	Test result.....	22
6.5.	Test graphs	23
7.	Power Spectral Density	25
7.1.	Block diagram of test setup	25
7.2.	Limits	25
7.3.	Test procedure	25
7.4.	Test result.....	26
7.5.	Test graphs	27
8.	Band Edge Compliance (Conducted Method)	29

8.1.	Block diagram of test setup	29
8.2.	Limits	29
8.3.	Test procedure	29
8.4.	Test result.....	30
8.5.	Test graphs	31
9.	RF Conducted Spurious Emissions.....	33
9.1.	Block diagram of test setup	33
9.2.	Limits	33
9.3.	Test procedure	33
9.4.	Test result.....	34
9.5.	Test graphs	35
10.	Duty Cycle	41
10.1.	Block diagram of test setup	41
10.2.	Limit	41
10.3.	Test procedure	41
10.4.	Test result.....	42
10.5.	Test graphs	43
11.	Antenna Requirements.....	45
11.1.	Limit.....	45
11.2.	Result	45
12.	Radiated Emission	46
12.1.	Test equipment.....	46
12.2.	Block diagram of test setup	47
12.3.	Limits	49
12.4.	Assistant equipment used for test	50
12.5.	Test procedure	50
12.6.	Test result.....	52
12.7.	Test data	53
13.	Band Edge Compliance.....	69
13.1.	Test equipment.....	69
13.2.	Block diagram of test setup	70
13.3.	Limits	70
13.4.	Assistant equipment used for test	70
13.5.	Test procedure	70
13.6.	Test result.....	70
13.7.	Test data	71
14.	Power Line Conducted Emissions.....	79
14.1.	Test equipment.....	79

14.2. Block diagram of test setup79

14.3. Limits80

14.4. Assistant equipment used for test80

14.5. Test procedure80

14.6. Test result.....81

14.7. Test data82

15. Test Setup Photograph86

16. Photos of the EUT88

Test Report Declare

Applicant	:	Harman International Industries, Inc.
Address of Applicant	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	3.1 CHANNEL SOUNDBAR WITH DOLBY ATMOS® AND WIRELESS SUBWOOFER
FCC Model No.	:	CINEMA SB580MK2 SUB, CINEMA SB581MK2 SUB, CINEMA SB582MK2 SUB, CINEMA SB583MK2 SUB, CINEMA SB584MK2 SUB, CINEMA SB585MK2 SUB, CINEMA SB586MK2 SUB, CINEMA SB587MK2 SUB, CINEMA SB588MK2 SUB, CINEMA SB589MK2 SUB, CINEMA SB590MK2 SUB, CINEMA SB591MK2 SUB, CINEMA SB592MK2 SUB, CINEMA SB593MK2 SUB, CINEMA SB594MK2 SUB, CINEMA SB596MK2 SUB, CINEMA SB597MK2 SUB, CINEMA SB598MK2 SUB, CINEMA SB599MK2 SUB, CINEMA SB540MK2 SUB, CINEMA SB541MK2 SUB, CINEMA SB542MK2 SUB, CINEMA SB543MK2 SUB, CINEMA SB544MK2 SUB, CINEMA SB545MK2 SUB, CINEMA SB546MK2 SUB, CINEMA SB547MK2 SUB, CINEMA SB548MK2 SUB, CINEMA SB549MK2 SUB
IC Model No.	:	CINEMA SB580MK2 SUB
Manufacturer	:	Harman International Industries, Inc.
Address of Manufacturer	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,

ANSI C63.10-2020,

RSS-247 Issue 4 July 24, 2025,

RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021),

ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26031216-2E10		
Date of Receipt:	2026/03/16	Date of Test:	2026/03/16 - 2026/05/18

Created: Jacky Huang	Reviewed: Johnson Huang	Approved: Ella Gong
		
2026/05/19	2026/06/04	2026/06/04

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/06/04	Ella Gong

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2), RSS-247 clause 6.3.1, RSS-Gen clause 6.7	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3), RSS-247 clause 6.3.2	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e), RSS-247 clause 6.3.1	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d), RSS-247 clause 6.6	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203, RSS-Gen clause 6.8	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a), RSS-Gen clause 8.8	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: 3.1 CHANNEL SOUNDBAR WITH DOLBY ATMOS® AND WIRELESS SUBWOOFER
FCC Model Number	: CINEMA SB580MK2 SUB, CINEMA SB581MK2 SUB, CINEMA SB582MK2 SUB, CINEMA SB583MK2 SUB, CINEMA SB584MK2 SUB, CINEMA SB585MK2 SUB, CINEMA SB586MK2 SUB, CINEMA SB587MK2 SUB, CINEMA SB588MK2 SUB, CINEMA SB589MK2 SUB, CINEMA SB590MK2 SUB, CINEMA SB591MK2 SUB, CINEMA SB592MK2 SUB, CINEMA SB593MK2 SUB, CINEMA SB594MK2 SUB, CINEMA SB596MK2 SUB, CINEMA SB597MK2 SUB, CINEMA SB598MK2 SUB, CINEMA SB599MK2 SUB, CINEMA SB540MK2 SUB, CINEMA SB541MK2 SUB, CINEMA SB542MK2 SUB, CINEMA SB543MK2 SUB, CINEMA SB544MK2 SUB, CINEMA SB545MK2 SUB, CINEMA SB546MK2 SUB, CINEMA SB547MK2 SUB, CINEMA SB548MK2 SUB, CINEMA SB549MK2 SUB
IC Model Number	: CINEMA SB580MK2 SUB
Difference of model number	: Above models are identical in schematic and structure, only the model number are different, therefore the test performed on the model: CINEMA SB580MK2 SUB
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 100-240V~ 50/60Hz 25W
Antenna Type	: PCB antenna
Max Antenna Gain (dBi)	: 2.43
Radio Specification	: Bluetooth LE
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK

Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478


11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		
Bluetooth LE 2Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	
13	2428	27	2456	/	
The channels denoted with the grey background are excluded, because they are primary advertising channel only for the Bluetooth LE 1Mbps according to the Bluetooth Core Specification.					

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
AC cable	Harman	N/A	Length: 1.5m

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: FCC_Tool_V3.0

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Mode	Setting Tx Power	Channel	Frequency (MHz)
BLE 1M	11	CH0	2402
	11	CH19	2440
	11	CH39	2480
BLE2M	11	CH1	2404
	11	CH19	2440
	11	CH38	2478

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9 \text{ kHz} \leq f < 7 \text{ GHz}$);
	3.31 dB ($7 \text{ GHz} \leq f < 40 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.14 dB (Antenna Polarize: H)
	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
Uncertainty for Power line conduction emission test	4.58 dB (18 GHz - 40 GHz)
	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	Cal. Interval
☒ RF Connected Test (RF Measurement System 1#)					
SIGNAL ANALYZER	R&S	FSQ26	101272	2027/02/28	1 Year
Wideband Radio Communication Tester	R&S	CMW500	117491	2027/02/28	1 Year
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY59100192	2027/02/28	1 Year
MXG Vector Signal Generator	Agilent	N5182A	MY19060405	2027/02/28	1 Year
RF Control Unit	Tonscend	JS0806-2	158060010	2027/02/28	1 Year
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/02/28	1 Year
Test Software	Tonscend	JS1120-3	V3.6.21	N/A	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW: 100 kHz

VBW: $\geq [3 \times \text{RBW}]$

Detector Mode: Peak

Sweep time: Auto

Trace mode: Max hold


- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.


4.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 1#
Ambient Condition:	26.6℃, 40.1%RH	Test Date:	2026.04.01
Test Power Supply:	AC 120V	Sample Number:	S2026031216-003

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.70	2401.64	2402.34	0.5	PASS
		2440	0.71	2439.64	2440.35	0.5	PASS
		2480	0.70	2479.64	2480.34	0.5	PASS
BLE_2M	Ant1	2404	1.16	2403.42	2404.58	0.5	PASS
		2440	1.16	2439.41	2440.58	0.5	PASS
		2478	1.16	2477.41	2478.58	0.5	PASS


4.5. Test graphs





5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW: 1% to 5% of the OBW

VBW: approximately three times RBW

Span: between 1.5 times and 5.0 times the OBW

Detector Mode: Peak

Sweep time: Auto

Trace mode: Max hold


- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 1#
Ambient Condition:	26.6℃,40.1%RH	Test Date:	2026.04.01
Test Power Supply:	AC 120V	Sample Number:	S2026031216-003

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	1.0280	2401.4760	2402.5040	---	---
		2440	1.0320	2439.4760	2440.5080	---	---
		2480	1.0280	2479.4760	2480.5040	---	---
BLE_2M	Ant1	2404	1.9860	2403.0040	2404.9900	---	---
		2440	1.9860	2439.0040	2440.9900	---	---
		2478	1.9860	2477.0040	2478.9900	---	---


5.5. Test graphs





6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.1.1.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW: $\geq$ DTS bandwidth

VBW: $\geq 3 \times$ RBW

Span: $\geq 3 \times$ RBW

Detector Mode: Peak

Sweep time: Auto

Trace mode: Max hold

- (5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.

6.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 1#
Ambient Condition:	26.6℃, 40.1%RH	Test Date:	2026.04.01
Test Power Supply:	AC 120V	Sample Number:	S2026031216-003

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
BLE_1M	Ant1	2402	11.23	≤30	13.66	≤36	PASS
		2440	10.82	≤30	13.25	≤36	PASS
		2480	10.88	≤30	13.31	≤36	PASS
BLE_2M	Ant1	2404	11.30	≤30	13.73	≤36	PASS
		2440	10.83	≤30	13.26	≤36	PASS
		2478	11.00	≤30	13.43	≤36	PASS


6.5. Test graphs





7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{ RBW}$
Span:	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.


If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 1#
Ambient Condition:	26.6℃, 40.1%RH	Test Date:	2026.04.01
Test Power Supply:	AC 120V	Sample Number:	S2026031216-003

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-4.66	≤8.00	PASS
		2440	-5.07	≤8.00	PASS
		2480	-5.25	≤8.00	PASS
BLE_2M	Ant1	2404	-7.91	≤8.00	PASS
		2440	-8.29	≤8.00	PASS
		2478	-8.37	≤8.00	PASS


7.5. Test graphs





8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span:	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.


(4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 1#
Ambient Condition:	26.6℃, 40.1%RH	Test Date:	2026.04.01
Test Power Supply:	AC 120V	Sample Number:	S2026031216-003

Mode	Frequency [MHz]	Measured Range	Verdict
BLE 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass
BLE 2M	2404	2.310 GHz - 2.410 GHz	Pass
	2478	2.470 GHz - 2.500 GHz	Pass


8.5. Test graphs





9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency:	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span:	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span:	Encompass frequency range to be measured
Number of measurement points:	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 1#
Ambient Condition:	26.6℃,40.1%RH	Test Date:	2026.04.01
Test Power Supply:	AC 120V	Sample Number:	S2026031216-003

Mode	Frequency [MHz]	Verdict
BLE1M	2402	Pass
	2440	Pass
	2480	Pass
BLE 2M	2404	Pass
	2440	Pass
	2478	Pass

9.5. Test graphs

