

**FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 Issue 4**

TEST REPORT

For

BLUETOOTH HEADSET

MODEL NUMBER: TUNE FLEX 3

REPORT NUMBER: 4792137414-1-RF-2

ISSUE DATE: June 17, 2026

**FCC ID: APITUNEFLEX3
IC: 6132A-TUNEFLEX3**

Prepared for

**HARMAN INTERNATIONAL INDUSTRIES INC
8500 Balboa Blvd Nothridge CA 91325, UNITED STATES**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

**Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	June 17, 2026	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	N/A
Conducted Output Power	ANSI C63.10-2020, Clause 11.9.1.2	FCC Part 15.247 (b)(3) RSS-247 Clause 6.3.2	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020, Clause 11.8.1 & 6.9.3	FCC Part 15.247 (a)(2) RSS-247 Clause 6.3.1 (a) RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2020, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 6.3.1 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2020, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 6.6	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020, Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 6.6 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

Note:

1. For FCC&ISED, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 standards.
2. "N/A" means not applicable in this report.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <FCC 47 CFR PART 15 SUBPART C ISED RSS-247 Issue 4> when <Simple Acceptance> decision rule is applied. Decision rule for statement of conformity: The measurement uncertainty is not taken into account for statement of conformity.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. CHANNEL LIST	9
5.3. MAXIMUM POWER	10
5.4. TEST CHANNEL CONFIGURATION.....	10
5.5. THE WORSE CASE POWER SETTING PARAMETER	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	11
5.7. SUPPORT UNITS FOR SYSTEM TEST	12
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	13
7. ANTENNA PORT TEST RESULTS	16
7.1. CONDUCTED OUTPUT POWER	16
7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	17
7.3. POWER SPECTRAL DENSITY	19
7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	20
7.5. DUTY CYCLE	22
8. RADIATED TEST RESULTS.....	23
8.1. RESTRICTED BANDEDGE-LEFT	31
8.2. RESTRICTED BANDEDGE-RIGHT	36
8.3. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-LEFT	41
8.4. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-RIGHT	47
8.5. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-LEFT	53
8.6. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-RIGHT	65
8.7. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-LEFT.....	77
8.8. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-RIGHT	80
8.9. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-LEFT.....	83
8.10. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-RIGHT	85

8.11.	SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-LEFT	87
8.12.	SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-RIGHT	89
9.	ANTENNA REQUIREMENT	91
10.	TEST DATA.....	92
10.1.	APPENDIX A: DTS BANDWIDTH.....	92
10.1.1.	Test Result-Left.....	92
10.1.2.	Test Graphs-Left	93
10.1.3.	Test Result-Right	95
10.1.4.	Test Graphs-Right.....	96
10.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....	98
10.2.1.	Test Result-Left.....	98
10.2.2.	Test Graphs-Left	99
10.2.3.	Test Result-Right	101
10.2.4.	Test Graphs-Right.....	102
10.3.	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....	104
10.3.1.	Test Result-Left.....	104
10.3.2.	Test Result-Right	104
10.4.	APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY.....	105
10.4.1.	Test Result-Left.....	105
10.4.2.	Test Result-Right	105
10.4.3.	Test Graphs-Right.....	106
10.4.1.	Test Graphs-Left.....	108
10.5.	APPENDIX E: BAND EDGE MEASUREMENTS.....	110
10.5.1.	Test Result-Left.....	110
10.5.2.	Test Result-Right	110
10.5.3.	Test Graphs-Left	111
10.5.4.	Test Graphs-Right.....	113
10.6.	APPENDIX F: CONDUCTED SPURIOUS EMISSION	115
10.6.1.	Test Result-Left.....	115
10.6.2.	Test Result-Right	115
10.6.3.	Test Graphs-Left.....	116
10.6.4.	Test Graphs-Right.....	122
10.7.	APPENDIX G: DUTY CYCLE.....	128
10.7.1.	Test Result-Left.....	128
10.7.2.	Test Graphs-Left	128
10.7.3.	Test Result-Right	129
10.7.4.	Test Graphs-Right.....	129

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: HARMAN INTERNATIONAL INDUSTRIES INC
Address: 8500 Balboa Blvd Nothridge CA 91325, UNITED STATES

Manufacturer Information

Company Name: HARMAN INTERNATIONAL INDUSTRIES INC
Address: 8500 Balboa Blvd Nothridge CA 91325, UNITED STATES

EUT Information

EUT Name: BLUETOOTH HEADSET
Model: TUNE FLEX 3
Brand: JBL
Sample Received Date: May 9, 2026
Sample Status: Normal
Sample ID: 9724933
Date of Tested: May 18, 2026 to June 17, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR PART 15 SUBPART C ISED RSS-247 Issue 4	Pass


Prepared By:



Johnson Liu

Laboratory Engineer Associate

Checked By:



Kebo Zhang

Operations Leader

Approved By:



Stephen Guo

Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC 47 CFR PART 15 SUBPART C ISED RSS-247 Issue 4, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, FCC 47 CFR Part 2, ANSI C63.10-2020, ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	4.36 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.47 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.65 dB (1 GHz ~ 18 GHz)
	4.73 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

Remark: For Radiated Emission measurements (200 MHz - 18 GHz), the EUT support table is made of Expanded Polystyrene (EPS). This material is characterized by a low dielectric constant, as recognized in CISPR 16-1-4, to minimize its influence on field strength measurements. This influence has been considered in the uncertainty budget.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	BLUETOOTH HEADSET
Model	TUNE FLEX 3

Frequency Range:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Data Rates:	1Mbps/2Mbps
Ratings	DC 3.7V via Battery

5.2. CHANNEL LIST

BLE 1M:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2466	/	/

BLE 2M:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2404	11	2424	21	2444	31	2464
2	2406	/	/	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	/	/
10	2422	20	2442	30	2462	/	/

5.3. MAXIMUM POWER

Left:

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
LE 1M	2402 ~ 2480	0-39[40]	10.62
LE 2M	2404 ~ 2478	1-11[11] 13-38[26]	10.64

Right:

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
LE 1M	2402 ~ 2480	0-39[40]	9.71
LE 2M	2404 ~ 2478	1-11[11] 13-38[26]	9.79

Note:

- Maximum peak output power = measured value + cable loss (provided by UL)

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 1(Low Channel), CH 19(MID Channel), CH 38(High Channel)	2404 MHz, 2440 MHz, 2478 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software Version		BQB.exe		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		LCH	MCH	HCH
GFSK(1Mbps)	Left & Right	default	default	default
GFSK(2Mbps)	Left & Right	default	default	default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
Left	2402 ~ 2480	LDS	-2.54
Right	2402 ~ 2480	LDS	-0.60

Note: The antenna gain is provided by clients.

Test Mode	Transmit and Receive Mode	Description
LE 1M	☒ 1TX, 1RX	Antenna Left or Right can be used as transmitting/receiving antenna.
LE 2M	☒ 1TX, 1RX	Antenna Left or Right can be used as transmitting/receiving antenna.

5.7. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E14	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.26,2025	Dec.25,2026
Vector Signal Generator	R&S	SMBV100A	261637	Sep.12, 2025	Sep.11, 2026
Signal Generator	R&S	SMB100A	178553	Sep.12, 2025	Sep.11, 2026
Signal Analyzer	R&S	FSV40	101118	Sep.12, 2025	Sep.11, 2026
Software					
Description		Manufacturer	Name	Version	
For R&S TS 8997 Test System		Rohde & Schwarz	EMC 32	10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.12, 2025	Sep.11, 2026
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.12, 2025	Sep.11, 2026
DC power supply	TSSTAKASAGO	ZX-400L	409150160137	Sep.12, 2025	Sep.11, 2026
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.12, 2025	Sep.11, 2026
Attenuator	Aglient	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.26,2025	Dec.25,2026
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Radiated Emissions(Below 1G)					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.12, 2025	Sep.11, 2026
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.12, 2025	Sep.11, 2026
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions(Above 1G)					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Signal Analyzer	R&S	FSV40	101117	Sep.12, 2025	Sep.11, 2026
Preamplifier	TDK	PA-02-001-3000	TRS-302-00051	Sep.12, 2025	Sep.11, 2026
Horn Antenna	ETS-Lindgren	3117	00213191	Jan.29,2026	Jan.28,2029
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.12, 2025	Sep.11, 2026
High Gain Horn Antenna	Schwarzbeck	BBHA-9170	697	Jun. 30, 2024	Jun. 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00002	Sep.12, 2025	Sep.11, 2026
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.12, 2025	Sep.11, 2026
Highpass Filter	Wainwright	WHKX10-2700-3000-1800-40SS	24	Sep.12, 2025	Sep.11, 2026
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.12, 2025	Sep.11, 2026
Software					
Description		Manufacturer	Name		Version
Test Software for Radiated Emission		Tonscend	JS32-RE		5.0.0
Test Software for Radiated Emissions		Farad	EZ-EMC		Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Sep.16, 2025	Sep.15, 2026
Barometer	Yiyi	Baro	N/A	Sep.19, 2025	Sep.18, 2026
Attenuator	Agilent	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(b)(3) ISED RSS-247 6.3.2	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	59.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	May 22, 2026	Test By	Eason He
-----------	--------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(a)(2) ISED RSS-247 6.3.1(a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 1 % to 5 % of the OBW but not less than 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.3℃	Relative Humidity	59.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	May 22, 2026	Test By	Eason He
-----------	--------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR §15.247 (e) ISED RSS-247 6.3.1 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.10.2.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$> 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	59.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	May 22, 2026	Test By	Eason He
-----------	--------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
FCC 47 CFR §15.247 (d) ISED RSS-247 6.6	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.11.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$\geq 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span/RBW}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.3℃	Relative Humidity	59.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	May 22, 2026	Test By	Eason He
-----------	--------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.3°C	Relative Humidity	59.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	May 22, 2026	Test By	Eason He
-----------	--------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to FCC 47 CFR §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit ($\mu\text{V/m}$) at 3 m	Field Strength Limit (dB $\mu\text{V/m}$) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) ($\mu\text{A/m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.6
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC 47 CFR §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT


Temperature	23.2°C	Relative Humidity	54%
Atmosphere Pressure	101kPa	Test Voltage	

TEST DATE / ENGINEER

Test Date	May 26, 2026	Test By	Leslie Xie
-----------	--------------	---------	------------


TEST RESULTS

8.1. RESTRICTED BANDEDGE-LEFT




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2376.83	40.78	49.30	8.52	74.00	24.70	PK	Horizontal	PASS
2	2390.00	39.75	48.45	8.70	74.00	25.55	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2376.08	41.05	49.56	8.51	74.00	24.44	PK	Vertical	PASS
2	2390.00	39.65	48.35	8.70	74.00	25.65	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2483.50	37.94	47.93	9.99	74.00	26.07	PK	Horizontal	PASS
2	2491.22	40.45	50.54	10.09	74.00	23.46	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2376.13	40.08	48.59	8.51	74.00	25.41	PK	Horizontal	PASS
2	2390.00	38.16	46.86	8.70	74.00	27.14	PK	Horizontal	PASS


Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2483.50	38.10	48.09	9.99	74.00	25.91	PK	Horizontal	PASS
2	2490.23	40.09	50.17	10.08	74.00	23.83	PK	Horizontal	PASS


Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

8.2. RESTRICTED BANDEDGE-RIGHT




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2378.38	40.31	48.85	8.54	74.00	25.15	PK	Horizontal	PASS
2	2390.00	39.17	47.87	8.70	74.00	26.13	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2378.13	40.75	49.29	8.54	74.00	24.71	PK	Vertical	PASS
2	2390.00	39.03	47.73	8.70	74.00	26.27	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2483.50	37.94	47.93	9.99	74.00	26.07	PK	Horizontal	PASS
2	2489.44	40.44	50.51	10.07	74.00	23.49	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2376.23	40.18	48.69	8.51	74.00	25.31	PK	Horizontal	PASS
2	2390.00	38.68	47.38	8.70	74.00	26.62	PK	Horizontal	PASS


Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2483.50	37.54	47.53	9.99	74.00	26.47	PK	Horizontal	PASS
2	2490.98	40.14	50.23	10.09	74.00	23.77	PK	Horizontal	PASS


Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

8.3. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-LEFT




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1173.09	57.73	33.09	-24.64	74.00	40.91	PK	Horizontal	PASS
2	1575.29	57.49	33.48	-24.01	74.00	40.52	PK	Horizontal	PASS
3	1934.47	56.61	35.79	-20.82	74.00	38.21	PK	Horizontal	PASS
4	2260.63	57.35	37.66	-19.69	74.00	36.34	PK	Horizontal	PASS
5	2583.79	58.10	38.61	-19.49	74.00	35.39	PK	Horizontal	PASS
6	2888.94	56.98	37.91	-19.07	74.00	36.09	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1107.05	57.36	32.58	-24.78	74.00	41.42	PK	Vertical	PASS
2	1367.18	56.50	31.87	-24.63	74.00	42.13	PK	Vertical	PASS
3	1687.34	56.82	33.68	-23.14	74.00	40.32	PK	Vertical	PASS
4	2041.52	57.14	37.11	-20.03	74.00	36.89	PK	Vertical	PASS
5	2382.69	56.89	37.26	-19.63	74.00	36.74	PK	Vertical	PASS
6	2812.91	57.06	37.94	-19.12	74.00	36.06	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1163.08	56.12	31.46	-24.66	74.00	42.54	PK	Horizontal	PASS
2	1505.25	56.76	32.19	-24.57	74.00	41.81	PK	Horizontal	PASS
3	1919.46	56.99	36.01	-20.98	74.00	37.99	PK	Horizontal	PASS
4	2249.62	58.27	38.57	-19.70	74.00	35.43	PK	Horizontal	PASS
5	2622.81	57.13	37.70	-19.43	74.00	36.30	PK	Horizontal	PASS
6	2879.94	57.19	38.12	-19.07	74.00	35.88	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1068.03	58.40	33.55	-24.85	74.00	40.45	PK	Vertical	PASS
2	1453.23	56.82	32.21	-24.61	74.00	41.79	PK	Vertical	PASS
3	1782.39	56.72	34.32	-22.40	74.00	39.68	PK	Vertical	PASS
4	2091.55	57.47	37.54	-19.93	74.00	36.46	PK	Vertical	PASS
5	2512.76	57.80	38.20	-19.60	74.00	35.80	PK	Vertical	PASS
6	2856.93	57.12	38.03	-19.09	74.00	35.97	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1133.07	57.24	32.52	-24.72	74.00	41.48	PK	Horizontal	PASS
2	1470.24	56.26	31.65	-24.61	74.00	42.35	PK	Horizontal	PASS
3	1808.40	56.92	34.74	-22.18	74.00	39.26	PK	Horizontal	PASS
4	2179.59	56.81	37.05	-19.76	74.00	36.95	PK	Horizontal	PASS
5	2480.74	55.52	35.89	-19.63	74.00	33.01	PK	Horizontal	PASS
6	2859.93	57.58	38.49	-19.09	74.00	35.51	PK	Horizontal	PASS


Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1089.04	57.61	32.80	-24.81	74.00	41.20	PK	Vertical	PASS
2	1481.24	56.66	32.06	-24.60	74.00	41.94	PK	Vertical	PASS
3	1915.46	57.24	36.22	-21.02	74.00	37.78	PK	Vertical	PASS
4	2327.66	57.14	37.47	-19.67	74.00	36.53	PK	Vertical	PASS
5	2713.86	57.37	38.10	-19.27	74.00	35.90	PK	Vertical	PASS
6	2940.97	57.72	38.68	-19.04	74.00	35.32	PK	Vertical	PASS


Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

8.4. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-RIGHT




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1116.06	56.86	32.10	-24.76	74.00	41.90	PK	Horizontal	PASS
2	1332.17	56.80	32.19	-24.61	74.00	41.81	PK	Horizontal	PASS
3	1570.29	57.19	33.15	-24.04	74.00	40.85	PK	Horizontal	PASS
4	1932.47	57.50	36.67	-20.83	74.00	37.33	PK	Horizontal	PASS
5	2324.66	56.72	37.06	-19.66	74.00	36.94	PK	Horizontal	PASS
6	2639.82	57.39	37.99	-19.40	74.00	36.01	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1131.07	56.80	32.08	-24.72	74.00	41.92	PK	Vertical	PASS
2	1515.26	57.91	33.43	-24.48	74.00	40.57	PK	Vertical	PASS
3	1883.44	57.00	35.63	-21.37	74.00	38.37	PK	Vertical	PASS
4	2216.61	57.60	37.88	-19.72	74.00	36.12	PK	Vertical	PASS
5	2553.78	58.23	38.70	-19.53	74.00	35.30	PK	Vertical	PASS
6	2857.93	58.17	39.08	-19.09	74.00	34.92	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1170.09	57.33	32.68	-24.65	74.00	41.32	PK	Horizontal	PASS
2	1539.27	57.50	33.21	-24.29	74.00	40.79	PK	Horizontal	PASS
3	1880.44	57.12	35.72	-21.40	74.00	38.28	PK	Horizontal	PASS
4	2268.63	57.79	38.09	-19.70	74.00	35.91	PK	Horizontal	PASS
5	2617.81	58.44	39.00	-19.44	74.00	35.00	PK	Horizontal	PASS
6	2958.98	57.77	38.74	-19.03	74.00	35.26	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1092.05	57.27	32.48	-24.79	74.00	41.52	PK	Vertical	PASS
2	1420.21	57.57	32.94	-24.63	74.00	41.06	PK	Vertical	PASS
3	1886.44	57.45	36.11	-21.34	74.00	37.89	PK	Vertical	PASS
4	2212.61	57.25	37.54	-19.71	74.00	36.46	PK	Vertical	PASS
5	2557.78	57.53	38.00	-19.53	74.00	36.00	PK	Vertical	PASS
6	2890.95	57.24	38.17	-19.07	74.00	35.83	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1092.05	58.13	33.34	-24.79	74.00	40.66	PK	Horizontal	PASS
2	1439.22	58.02	33.40	-24.62	74.00	40.60	PK	Horizontal	PASS
3	1796.40	56.45	34.15	-22.30	74.00	39.85	PK	Horizontal	PASS
4	2152.58	57.40	37.59	-19.81	74.00	36.41	PK	Horizontal	PASS
5	2449.72	57.03	37.40	-19.63	74.00	36.60	PK	Horizontal	PASS
6	2847.92	56.64	37.54	-19.10	74.00	36.46	PK	Horizontal	PASS


Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1133.07	57.01	32.29	-24.72	74.00	41.71	PK	Vertical	PASS
2	1442.22	56.55	31.94	-24.61	74.00	42.06	PK	Vertical	PASS
3	1763.38	58.78	36.23	-22.55	74.00	37.77	PK	Vertical	PASS
4	2068.53	56.86	36.88	-19.98	74.00	37.12	PK	Vertical	PASS
5	2395.70	56.35	36.72	-19.63	74.00	37.28	PK	Vertical	PASS
6	2735.87	57.94	38.70	-19.24	74.00	35.30	PK	Vertical	PASS


Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level

8.5. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-LEFT




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4283.14	56.90	39.21	-17.69	74.00	34.79	PK	Horizontal	PASS
2	8350.18	52.97	40.05	-12.92	74.00	33.95	PK	Horizontal	PASS
3	10676.34	50.19	40.84	-9.35	74.00	33.16	PK	Horizontal	PASS
4	12154.58	50.71	40.98	-9.73	74.00	33.02	PK	Horizontal	PASS
5	14908.45	51.03	41.45	-9.58	74.00	32.55	PK	Horizontal	PASS
6	17782.39	48.16	43.06	-5.10	74.00	30.94	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4943.47	56.34	38.53	-17.81	74.00	35.47	PK	Vertical	PASS
2	7809.90	55.27	40.43	-14.84	74.00	33.57	PK	Vertical	PASS
3	10736.37	50.20	40.96	-9.24	74.00	33.04	PK	Vertical	PASS
4	12222.11	50.90	40.99	-9.91	74.00	33.01	PK	Vertical	PASS
5	15583.79	51.22	41.70	-9.52	74.00	32.30	PK	Vertical	PASS
6	17594.80	48.14	43.07	-5.07	74.00	30.93	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4268.13	56.96	39.30	-17.66	74.00	34.70	PK	Horizontal	PASS
2	7307.15	56.06	40.88	-15.18	74.00	33.12	PK	Horizontal	PASS
3	10083.54	52.30	41.37	-10.93	74.00	32.63	PK	Horizontal	PASS
4	13340.17	52.55	41.39	-11.16	74.00	32.61	PK	Horizontal	PASS
5	15658.83	51.79	42.12	-9.67	74.00	31.88	PK	Horizontal	PASS
6	17744.87	48.74	43.65	-5.09	74.00	30.35	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4253.13	56.68	39.05	-17.63	74.00	34.95	PK	Vertical	PASS
2	7277.14	54.70	39.50	-15.20	74.00	34.50	PK	Vertical	PASS
3	10458.73	51.10	41.51	-9.59	74.00	32.49	PK	Vertical	PASS
4	12192.10	51.10	41.35	-9.75	74.00	32.65	PK	Vertical	PASS
5	14938.47	50.54	41.06	-9.48	74.00	32.94	PK	Vertical	PASS
6	17789.89	48.86	43.75	-5.11	74.00	30.25	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4275.64	57.35	39.67	-17.68	74.00	34.33	PK	Horizontal	PASS
2	7817.41	54.81	39.96	-14.85	74.00	34.04	PK	Horizontal	PASS
3	10398.70	50.10	40.46	-9.64	74.00	33.54	PK	Horizontal	PASS
4	11704.35	51.07	41.61	-9.46	74.00	32.39	PK	Horizontal	PASS
5	14998.50	51.37	42.13	-9.24	74.00	31.87	PK	Horizontal	PASS
6	17602.30	49.45	44.45	-5.00	74.00	29.55	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4388.19	57.10	39.17	-17.93	74.00	34.83	PK	Vertical	PASS
2	7322.16	56.13	40.95	-15.18	74.00	33.05	PK	Vertical	PASS
3	10151.08	52.23	41.07	-11.16	74.00	32.93	PK	Vertical	PASS
4	13220.11	53.22	42.34	-10.88	74.00	31.66	PK	Vertical	PASS
5	16004.00	50.78	42.56	-8.22	74.00	31.44	PK	Vertical	PASS
6	17609.80	48.33	43.33	-5.00	74.00	30.67	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4238.12	57.10	39.52	-17.58	74.00	34.48	PK	Horizontal	PASS
2	8335.17	54.65	41.59	-13.06	74.00	32.41	PK	Horizontal	PASS
3	10091.05	52.25	41.29	-10.96	74.00	32.71	PK	Horizontal	PASS
4	12049.52	50.68	41.03	-9.65	74.00	32.97	PK	Horizontal	PASS
5	14991.00	50.98	41.70	-9.28	74.00	32.30	PK	Horizontal	PASS
6	17519.76	49.06	42.88	-6.18	74.00	31.12	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4245.62	57.48	39.87	-17.61	74.00	34.13	PK	Vertical	PASS
2	7712.36	55.40	40.22	-15.18	74.00	33.78	PK	Vertical	PASS
3	9805.90	52.77	40.80	-11.97	74.00	33.20	PK	Vertical	PASS
4	13152.58	52.40	41.40	-11.00	74.00	32.60	PK	Vertical	PASS
5	16664.33	49.62	41.96	-7.66	74.00	32.04	PK	Vertical	PASS
6	17849.92	48.91	43.60	-5.31	74.00	30.40	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4283.14	58.22	40.53	-17.69	74.00	33.47	PK	Horizontal	PASS
2	8372.69	52.88	40.17	-12.71	74.00	33.83	PK	Horizontal	PASS
3	11711.86	50.35	40.82	-9.53	74.00	33.18	PK	Horizontal	PASS
4	13302.65	52.35	41.28	-11.07	74.00	32.72	PK	Horizontal	PASS
5	15006.00	50.80	41.53	-9.27	74.00	32.47	PK	Horizontal	PASS
6	17602.30	47.94	42.94	-5.00	74.00	31.06	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4260.63	57.02	39.37	-17.65	74.00	34.63	PK	Vertical	PASS
2	7074.54	54.89	39.91	-14.98	74.00	34.09	PK	Vertical	PASS
3	10076.04	51.16	40.26	-10.90	74.00	33.74	PK	Vertical	PASS
4	13145.07	52.23	41.19	-11.04	74.00	32.81	PK	Vertical	PASS
5	14968.48	51.26	41.90	-9.36	74.00	32.10	PK	Vertical	PASS
6	17624.81	48.70	43.68	-5.02	74.00	30.32	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4260.63	56.75	39.10	-17.65	74.00	34.90	PK	Horizontal	PASS
2	7809.90	54.97	40.13	-14.84	74.00	33.87	PK	Horizontal	PASS
3	10331.17	51.42	41.20	-10.22	74.00	32.80	PK	Horizontal	PASS
4	12177.09	50.93	41.19	-9.74	74.00	32.81	PK	Horizontal	PASS
5	15096.05	51.55	41.78	-9.77	74.00	32.22	PK	Horizontal	PASS
6	17902.45	48.58	43.08	-5.50	74.00	30.92	PK	Horizontal	PASS


Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4253.13	57.43	39.80	-17.63	74.00	34.20	PK	Vertical	PASS
2	8357.68	53.13	40.28	-12.85	74.00	33.72	PK	Vertical	PASS
3	10548.77	50.34	40.80	-9.54	74.00	33.20	PK	Vertical	PASS
4	12229.61	51.91	41.96	-9.95	74.00	32.04	PK	Vertical	PASS
5	14991.00	51.19	41.91	-9.28	74.00	32.09	PK	Vertical	PASS
6	17602.30	47.62	42.62	-5.00	74.00	31.38	PK	Vertical	PASS


Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

8.6. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-RIGHT




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4253.13	56.97	39.34	-17.63	74.00	34.66	PK	Horizontal	PASS
2	6969.48	54.98	40.03	-14.95	74.00	33.97	PK	Horizontal	PASS
3	9963.48	51.39	40.49	-10.90	74.00	33.51	PK	Horizontal	PASS
4	12109.55	51.35	41.65	-9.70	74.00	32.35	PK	Horizontal	PASS
5	14983.49	50.73	41.43	-9.30	74.00	32.57	PK	Horizontal	PASS
6	17534.77	49.28	43.32	-5.96	74.00	30.68	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4575.79	57.56	39.28	-18.28	74.00	34.72	PK	Vertical	PASS
2	7419.71	55.75	40.57	-15.18	74.00	33.43	PK	Vertical	PASS
3	10533.77	50.87	41.33	-9.54	74.00	32.67	PK	Vertical	PASS
4	13265.13	52.24	41.26	-10.98	74.00	32.74	PK	Vertical	PASS
5	14975.99	50.41	41.09	-9.32	74.00	32.91	PK	Vertical	PASS
6	17684.84	47.97	42.92	-5.05	74.00	31.08	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4260.63	56.97	39.32	-17.65	74.00	34.68	PK	Horizontal	PASS
2	7209.60	56.29	41.05	-15.24	74.00	32.95	PK	Horizontal	PASS
3	10398.70	50.47	40.83	-9.64	74.00	33.17	PK	Horizontal	PASS
4	11959.48	51.88	42.13	-9.75	74.00	31.87	PK	Horizontal	PASS
5	14983.49	50.47	41.17	-9.30	74.00	32.83	PK	Horizontal	PASS
6	17677.34	48.53	43.48	-5.05	74.00	30.52	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4238.12	56.81	39.23	-17.58	74.00	34.77	PK	Vertical	PASS
2	7209.60	57.13	41.89	-15.24	74.00	32.11	PK	Vertical	PASS
3	10421.21	51.05	41.43	-9.62	74.00	32.57	PK	Vertical	PASS
4	13175.09	53.23	42.31	-10.92	74.00	31.69	PK	Vertical	PASS
5	16581.79	49.83	42.24	-7.59	74.00	31.76	PK	Vertical	PASS
6	17789.89	47.70	42.59	-5.11	74.00	31.41	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4253.13	57.73	40.10	-17.63	74.00	33.90	PK	Horizontal	PASS
2	7937.47	55.06	40.10	-14.96	74.00	33.90	PK	Horizontal	PASS
3	11201.60	49.43	40.80	-8.63	74.00	33.20	PK	Horizontal	PASS
4	13040.02	53.13	41.70	-11.43	74.00	32.30	PK	Horizontal	PASS
5	15328.66	51.35	41.74	-9.61	74.00	32.26	PK	Horizontal	PASS
6	17789.89	48.95	43.84	-5.11	74.00	30.16	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4253.13	56.68	39.05	-17.63	74.00	34.95	PK	Vertical	PASS
2	7022.01	54.88	40.01	-14.87	74.00	33.99	PK	Vertical	PASS
3	10346.17	51.61	41.53	-10.08	74.00	32.47	PK	Vertical	PASS
4	13557.78	53.23	41.02	-12.21	74.00	32.98	PK	Vertical	PASS
5	14998.50	51.24	42.00	-9.24	74.00	32.00	PK	Vertical	PASS
6	17849.92	48.91	43.60	-5.31	74.00	30.40	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4155.58	57.66	39.69	-17.97	74.00	34.31	PK	Horizontal	PASS
2	6174.09	56.41	40.05	-16.36	74.00	33.95	PK	Horizontal	PASS
3	8327.66	53.27	40.14	-13.13	74.00	33.86	PK	Horizontal	PASS
4	12214.61	51.43	41.58	-9.85	74.00	32.42	PK	Horizontal	PASS
5	14983.49	51.31	42.01	-9.30	74.00	31.99	PK	Horizontal	PASS
6	17654.83	48.12	43.09	-5.03	74.00	30.91	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4148.07	57.20	39.16	-18.04	74.00	34.84	PK	Vertical	PASS
2	6166.58	56.07	39.68	-16.39	74.00	34.32	PK	Vertical	PASS
3	9903.45	51.83	40.52	-11.31	74.00	33.48	PK	Vertical	PASS
4	13370.19	52.40	41.16	-11.24	74.00	32.84	PK	Vertical	PASS
5	15388.69	50.81	41.54	-9.27	74.00	32.46	PK	Vertical	PASS
6	17609.80	48.27	43.27	-5.00	74.00	30.73	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4260.63	58.38	40.73	-17.65	74.00	33.27	PK	Horizontal	PASS
2	7344.67	55.54	40.39	-15.15	74.00	33.61	PK	Horizontal	PASS
3	10436.22	50.79	41.19	-9.60	74.00	32.81	PK	Horizontal	PASS
4	13790.40	54.07	41.73	-12.34	74.00	32.27	PK	Horizontal	PASS
5	16056.53	50.76	42.42	-8.34	74.00	31.58	PK	Horizontal	PASS
6	17789.89	48.29	43.18	-5.11	74.00	30.82	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4268.13	56.92	39.26	-17.66	74.00	34.74	PK	Vertical	PASS
2	7937.47	55.64	40.68	-14.96	74.00	33.32	PK	Vertical	PASS
3	10308.65	52.14	41.74	-10.40	74.00	32.26	PK	Vertical	PASS
4	12214.61	51.27	41.42	-9.85	74.00	32.58	PK	Vertical	PASS
5	15651.33	52.18	42.52	-9.66	74.00	31.48	PK	Vertical	PASS
6	17842.42	48.06	42.79	-5.27	74.00	31.21	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5063.53	57.90	40.14	-17.76	74.00	33.86	PK	Horizontal	PASS
2	7104.55	54.83	39.79	-15.04	74.00	34.21	PK	Horizontal	PASS
3	10316.16	51.56	41.22	-10.34	74.00	32.78	PK	Horizontal	PASS
4	13242.62	52.45	41.53	-10.92	74.00	32.47	PK	Horizontal	PASS
5	14960.98	51.37	41.98	-9.39	74.00	32.02	PK	Horizontal	PASS
6	17782.39	48.06	42.96	-5.10	74.00	31.04	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4275.64	57.49	39.81	-17.68	74.00	34.19	PK	Vertical	PASS
2	6436.72	56.44	40.16	-16.28	74.00	33.84	PK	Vertical	PASS
3	8380.19	53.30	40.65	-12.65	74.00	33.35	PK	Vertical	PASS
4	10526.26	51.42	41.87	-9.55	74.00	32.13	PK	Vertical	PASS
5	13302.65	52.55	41.48	-11.07	74.00	32.52	PK	Vertical	PASS
6	17084.54	50.09	42.95	-7.14	74.00	31.05	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


8.7. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-LEFT

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	76.85	-101.40	-24.55	47.60	-76.05	-3.90	-72.15	peak
2	0.0160	70.91	-101.37	-30.46	43.52	-81.96	-7.98	-73.98	peak
3	0.0280	66.29	-101.38	-35.09	38.66	-86.59	-12.84	-73.75	peak
4	0.0502	61.96	-101.48	-39.52	33.59	-91.02	-17.91	-73.11	peak
5	0.0825	59.83	-101.65	-41.82	29.27	-93.32	-22.23	-71.09	peak
6	0.1063	59.12	-101.78	-42.66	27.07	-94.16	-24.43	-69.73	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1585	75.72	-101.65	-25.93	23.60	-77.43	-27.90	-49.53	peak
2	0.1942	68.81	-101.70	-32.89	21.84	-84.39	-29.66	-54.73	peak
3	0.2300	64.53	-101.77	-37.24	20.37	-88.74	-31.13	-57.61	peak
4	0.3163	61.70	-101.87	-40.17	17.60	-91.67	-33.90	-57.77	peak
5	0.3780	59.78	-101.94	-42.16	16.05	-93.66	-35.45	-58.21	peak
6	0.4761	56.89	-102.04	-45.15	14.05	-96.65	-37.45	-59.20	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.6298	63.67	-62.09	1.58	31.62	-49.92	-19.88	-30.04	peak
2	1.1687	58.72	-62.19	-3.47	26.25	-54.97	-25.25	-29.72	peak
3	2.9222	55.42	-61.60	-6.18	29.54	-57.68	-21.96	-35.72	peak
4	8.9001	52.91	-60.95	-8.04	29.54	-59.54	-21.96	-37.58	peak
5	17.3107	54.04	-60.93	-6.89	29.54	-58.39	-21.96	-36.43	peak
6	26.8424	52.72	-60.27	-7.55	29.54	-59.05	-21.96	-37.09	peak


8.8. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-RIGHT

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0108	73.51	-101.39	-27.88	46.93	-79.38	-4.57	-74.81	peak
2	0.0188	70.14	-101.35	-31.21	42.12	-82.71	-9.38	-73.33	peak
3	0.0279	67.17	-101.38	-34.21	38.69	-85.71	-12.81	-72.90	peak
4	0.0514	61.18	-101.48	-40.30	33.38	-91.80	-18.12	-73.68	peak
5	0.0911	58.11	-101.72	-43.61	28.41	-95.11	-23.09	-72.02	peak
6	0.1297	57.13	-101.70	-44.57	25.35	-96.07	-26.15	-69.92	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1590	74.82	-101.65	-26.83	23.57	-78.33	-27.93	-50.40	peak
2	0.1817	70.03	-101.68	-31.65	22.42	-83.15	-29.08	-54.07	peak
3	0.2348	65.93	-101.77	-35.84	20.19	-87.34	-31.31	-56.03	peak
4	0.2827	63.60	-101.83	-38.23	18.58	-89.73	-32.92	-56.81	peak
5	0.3573	60.08	-101.91	-41.83	16.54	-93.33	-34.96	-58.37	peak
6	0.4364	58.36	-101.99	-43.63	14.80	-95.13	-36.70	-58.43	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5785	63.40	-62.08	1.32	32.36	-50.18	-19.14	-31.04	peak
2	1.3810	58.47	-62.10	-3.63	24.80	-55.13	-26.70	-28.43	peak
3	2.8803	55.34	-61.60	-6.26	29.54	-57.76	-21.96	-35.80	peak
4	6.9230	54.13	-61.22	-7.09	29.54	-58.59	-21.96	-36.63	peak
5	13.8871	54.60	-60.97	-6.37	29.54	-57.87	-21.96	-35.91	peak
6	26.8719	53.04	-60.27	-7.23	29.54	-58.73	-21.96	-36.77	peak


8.9. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-LEFT

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18760.000	50.34	-5.42	44.92	74.00	-29.08	peak
2	20016.000	49.56	-5.47	44.09	74.00	-29.91	peak
3	21248.000	49.79	-4.77	45.02	74.00	-28.98	peak
4	23200.000	48.65	-3.38	45.27	74.00	-28.73	peak
5	24768.000	46.36	-2.31	44.05	74.00	-29.95	peak
6	25512.000	45.80	-1.73	44.07	74.00	-29.93	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18112.000	51.46	-5.47	45.99	74.00	-28.01	peak
2	19064.000	49.78	-5.31	44.47	74.00	-29.53	peak
3	21272.000	48.75	-4.76	43.99	74.00	-30.01	peak
4	23088.000	46.52	-3.41	43.11	74.00	-30.89	peak
5	24584.000	46.37	-2.31	44.06	74.00	-29.94	peak
6	25688.000	44.81	-0.90	43.91	74.00	-30.09	peak


8.10. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-RIGHT

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18848.000	49.35	-5.35	44.00	74.00	-30.00	peak
2	20728.000	49.66	-5.14	44.52	74.00	-29.48	peak
3	22320.000	47.79	-4.13	43.66	74.00	-30.34	peak
4	23584.000	47.42	-3.15	44.27	74.00	-29.73	peak
5	24544.000	46.44	-2.32	44.12	74.00	-29.88	peak
6	25832.000	46.22	-0.76	45.46	74.00	-28.54	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18496.000	50.25	-5.25	45.00	74.00	-29.00	peak
2	19840.000	49.32	-5.32	44.00	74.00	-30.00	peak
3	21928.000	48.55	-4.43	44.12	74.00	-29.88	peak
4	23736.000	46.69	-3.19	43.50	74.00	-30.50	peak
5	24720.000	46.22	-2.33	43.89	74.00	-30.11	peak
6	25856.000	44.79	-0.80	43.99	74.00	-30.01	peak


8.11. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-LEFT

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	55.2200	31.25	-15.55	15.70	40.00	-24.30	peak
2	150.2800	26.64	-13.14	13.50	43.50	-30.00	peak
3	302.5700	38.07	-10.96	27.11	46.00	-18.89	peak
4	482.9900	27.08	-6.97	20.11	46.00	-25.89	peak
5	759.4400	25.20	-2.13	23.07	46.00	-22.93	peak
6	870.9900	28.50	-1.65	26.85	46.00	-19.15	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	46.4900	35.41	-15.14	20.27	40.00	-19.73	peak
2	199.7500	26.51	-11.95	14.56	43.50	-28.94	peak
3	359.8000	24.91	-9.14	15.77	46.00	-30.23	peak
4	496.5700	25.93	-6.64	19.29	46.00	-26.71	peak
5	664.3800	27.18	-5.00	22.18	46.00	-23.82	peak
6	889.4200	27.18	-1.24	25.94	46.00	-20.06	peak


8.12. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-RIGHT

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	54.2500	32.52	-15.51	17.01	40.00	-22.99	peak
2	199.7500	26.02	-11.95	14.07	43.50	-29.43	peak
3	302.5700	35.94	-10.96	24.98	46.00	-21.02	peak
4	401.5100	30.17	-9.31	20.86	46.00	-25.14	peak
5	625.5800	24.01	-5.45	18.56	46.00	-27.44	peak
6	780.7800	26.56	-2.23	24.33	46.00	-21.67	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	46.4900	36.06	-15.14	20.92	40.00	-19.08	peak
2	217.2100	27.36	-12.74	14.62	46.00	-31.38	peak
3	250.1900	33.31	-14.60	18.71	46.00	-27.29	peak
4	544.1000	26.30	-6.40	19.90	46.00	-26.10	peak
5	736.1599	28.53	-2.58	25.95	46.00	-20.05	peak
6	873.9000	27.40	-1.58	25.82	46.00	-20.18	peak

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass


10. TEST DATA

10.1. APPENDIX A: DTS BANDWIDTH

10.1.1. Test Result-Left

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant L	2402	0.70	2401.64	2402.34	≥ 0.5	PASS
		2440	0.69	2439.64	2440.33	≥ 0.5	PASS
		2480	0.69	2479.64	2480.33	≥ 0.5	PASS
BLE_2M	Ant L	2404	1.17	2403.41	2404.58	≥ 0.5	PASS
		2440	1.17	2439.41	2440.58	≥ 0.5	PASS
		2478	1.17	2477.40	2478.58	≥ 0.5	PASS

10.1.2. Test Graphs-Left






BLE_2M_Ant L_2404



BLE_2M_Ant L_2440




BLE_2M_Ant L_2478

10.1.3. Test Result-Right

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant R	2402	0.69	2401.64	2402.33	≥ 0.5	PASS
		2440	0.68	2439.65	2440.33	≥ 0.5	PASS
		2480	0.69	2479.65	2480.34	≥ 0.5	PASS
BLE_2M	Ant R	2404	1.18	2403.40	2404.58	≥ 0.5	PASS
		2440	1.16	2439.42	2440.58	≥ 0.5	PASS
		2478	1.17	2477.41	2478.58	≥ 0.5	PASS

10.1.4. Test Graphs-Right





BLE_2M_Ant R_2404



BLE_2M_Ant R_2440





BLE_2M_Ant R_2478

10.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH**10.2.1. Test Result-Left**


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant L	2402	1.0211	2401.4874	2402.5086	PASS
		2440	1.0210	2439.4872	2440.5082	PASS
		2480	1.0196	2479.4878	2480.5074	PASS
BLE_2M	Ant L	2404	2.0210	2402.9994	2405.0205	PASS
		2440	2.0229	2438.9998	2441.0227	PASS
		2478	2.0119	2477.0018	2479.0136	PASS

10.2.2. Test Graphs-Left






BLE_2M_Ant L_2404



BLE_2M_Ant L_2440




BLE_2M_Ant L_2478

10.2.3. Test Result-Right


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant R	2402	1.0178	2401.4916	2402.5094	PASS
		2440	1.0175	2439.4911	2440.5086	PASS
		2480	1.0179	2479.4911	2480.5090	PASS
BLE_2M	Ant R	2404	2.0016	2403.0047	2405.0063	PASS
		2440	2.0056	2439.0056	2441.0112	PASS
		2478	2.0040	2477.0059	2479.0099	PASS

10.2.4. Test Graphs-Right






BLE_2M_Ant R_2404



BLE_2M_Ant R_2440



BLE_2M_Ant R_2478

10.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER**10.3.1. Test Result-Left**

Test Mode	Antenna	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant L	2402	10.43	≤30	PASS
		2440	10.62	≤30	PASS
		2480	10.09	≤30	PASS
BLE_2M	Ant L	2404	10.38	≤30	PASS
		2440	10.64	≤30	PASS
		2478	10.20	≤30	PASS

10.3.2. Test Result-Right

Test Mode	Antenna	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant R	2402	9.21	≤30	PASS
		2440	9.71	≤30	PASS
		2480	9.47	≤30	PASS
BLE_2M	Ant R	2404	9.28	≤30	PASS
		2440	9.79	≤30	PASS
		2478	9.62	≤30	PASS


10.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY**10.4.1. Test Result-Left**


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant L	2402	-5.07	≤8.00	PASS
		2440	-4.67	≤8.00	PASS
		2480	-5.14	≤8.00	PASS
BLE_2M	Ant L	2404	-8.44	≤8.00	PASS
		2440	-8.13	≤8.00	PASS
		2478	-9.04	≤8.00	PASS

10.4.2. Test Result-Right


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant R	2402	-6.32	≤8.00	PASS
		2440	-5.87	≤8.00	PASS
		2480	-5.93	≤8.00	PASS
BLE_2M	Ant R	2404	-10.23	≤8.00	PASS
		2440	-9.90	≤8.00	PASS
		2478	-9.87	≤8.00	PASS

10.4.3. Test Graphs-Right






BLE_2M_Ant R_2404





BLE_2M_Ant R_2440




BLE_2M_Ant R_2478

10.4.1. Test Graphs-Left






BLE_2M_Ant L_2404



BLE_2M_Ant L_2440



BLE_2M_Ant L_2478

10.5. APPENDIX E: BAND EDGE MEASUREMENTS

10.5.1. Test Result-Left


Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant L	Low	2402	9.56	-48.63	≤ -10.44	PASS
		High	2480	9.54	-52.31	≤ -10.46	PASS
BLE_2M	Ant L	Low	2404	9.58	-54.45	≤ -10.42	PASS
		High	2478	9.57	-52.69	≤ -10.43	PASS

10.5.2. Test Result-Right

Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant R	Low	2402	8.22	-47.2	≤ -11.78	PASS
		High	2480	8.67	-48.03	≤ -11.33	PASS
BLE_2M	Ant R	Low	2404	8.17	-48.29	≤ -11.83	PASS
		High	2478	8.65	-33.63	≤ -11.35	PASS


10.5.3. Test Graphs-Left





10.5.4. Test Graphs-Right





10.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION


10.6.1. Test Result-Left


Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant L	2402	Reference	9.58	---	PASS
			30~1000	-56.57	≤-10.42	PASS
			1000~26500	-45.58	≤-10.42	PASS
		2440	Reference	10.07	---	PASS
			30~1000	-56.46	≤-9.93	PASS
			1000~26500	-45.94	≤-9.93	PASS
		2480	Reference	9.62	---	PASS
			30~1000	-56.88	≤-10.38	PASS
			1000~26500	-46.16	≤-10.38	PASS
BLE_2M	Ant L	2404	Reference	9.56	---	PASS
			30~1000	-56.61	≤-10.44	PASS
			1000~26500	-46.58	≤-10.44	PASS
		2440	Reference	10.07	---	PASS
			30~1000	-56.97	≤-9.93	PASS
			1000~26500	-46.42	≤-9.93	PASS
		2478	Reference	9.65	---	PASS
			30~1000	-57.35	≤-10.35	PASS
			1000~26500	-46.42	≤-10.35	PASS

10.6.2. Test Result-Right


Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant R	2402	Reference	8.26	---	PASS
			30~1000	-56.97	≤-11.74	PASS
			1000~26500	-46.21	≤-11.74	PASS
		2440	Reference	8.77	---	PASS
			30~1000	-56.77	≤-11.23	PASS
			1000~26500	-40.01	≤-11.23	PASS
		2480	Reference	8.69	---	PASS
			30~1000	-56.72	≤-11.31	PASS
			1000~26500	-45.74	≤-11.31	PASS
BLE_2M	Ant R	2404	Reference	8.18	---	PASS
			30~1000	-57.13	≤-11.82	PASS
			1000~26500	-42	≤-11.82	PASS
		2440	Reference	8.69	---	PASS
			30~1000	-56.99	≤-11.31	PASS
			1000~26500	-46.12	≤-11.31	PASS
		2478	Reference	8.73	---	PASS
			30~1000	-56.97	≤-11.27	PASS
			1000~26500	-46.09	≤-11.27	PASS

10.6.3. Test Graphs-Left







BLE_1M_Ant L_2440_0-Reference




BLE_1M_Ant L_2440_30-1000




BLE_1M_Ant L_2440_1000-26500




BLE_1M_Ant L_2480_0-Reference




BLE_1M_Ant L_2480_30-1000




BLE_1M_Ant L_2480_1000-26500




BLE_2M_Ant L_2404_0-Reference




BLE_2M_Ant L_2404_30-1000




BLE_2M_Ant L_2404_1000-26500




BLE_2M_Ant L_2440_0-Reference




BLE_2M_Ant L_2440_30-1000




BLE_2M_Ant L_2440_1000-26500



BLE_2M_Ant L_2478_0-Reference





BLE_2M_Ant L_2478_30-1000




BLE_2M_Ant L_2478_1000-26500

10.6.4. Test Graphs-Right







BLE_1M_Ant R_2440_0-Reference




BLE_1M_Ant R_2440_30-1000




BLE_1M_Ant R_2440_1000-26500




BLE_1M_Ant R_2480_0-Reference




BLE_1M_Ant R_2480_30-1000




BLE_1M_Ant R_2480_1000-26500




BLE_2M_Ant R_2404_0-Reference




BLE_2M_Ant R_2404_30-1000




BLE_2M_Ant R_2404_1000-26500




BLE_2M_Ant R_2440_0-Reference




BLE_2M_Ant R_2440_30-1000




BLE_2M_Ant R_2440_1000-26500



BLE_2M_Ant R_2478_0-Reference



BLE_2M_Ant R_2478_30-1000



BLE_2M_Ant R_2478_1000-26500

10.7. APPENDIX G: DUTY CYCLE

10.7.1. Test Result-Left

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.38	0.62	0.6129	61.29	2.13	2.63	3
BLE_2M	1.06	1.88	0.5638	56.38	2.49	0.94	1

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

10.7.2. Test Graphs-Left



10.7.3. Test Result-Right

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.38	0.62	0.6129	61.29	2.13	2.63	3
BLE_2M	1.06	1.86	0.5699	56.99	2.44	0.94	1

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

10.7.4. Test Graphs-Right



END OF REPORT