



Product Service

**Choose certainty.
Add value.**

Report On

Specific Absorption Rate Testing of the
Sharp CDMA SHX12 Dual-band CDMA (BC0,BC6) and Tri-band GSM
(GSM900/DCS1800/PCS1900) Dual mode Cellular Phone with
Bluetooth, Felica, WLAN and GPS

COMMERCIAL-IN-CONFIDENCE

FCC ID: APYHRO00162

Document 75915934 Report 14 Issue 2

December 2011



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuvps.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

Specific Absorption Rate Testing of the
Sharp CDMA SHX12 Dual-band CDMA (BC0,BC6) and Tri-band
GSM (GSM900/DCS1800/PCS1900) Dual mode Cellular Phone with
Bluetooth, Felica, WLAN and GPS

Document 75915934 Report 14 Issue 2

December 2011

PREPARED FOR

Sharp Communication Compliance Ltd
Azure House
Bagshot Road
Bracknell
Berkshire
RG12 7QY

PREPARED BY

N Bennett
Senior Administrator

APPROVED BY

M J Hardy
Authorised Signatory

DATED

05 January 2012

This report has been up issued to include missing PCS 1900 Conducted Power results





CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Test Results Summary 5
1.4	Product Information 8
1.5	FCC Power Measurements 11
2	TEST DETAILS 13
2.1	SARA 2 SAR Measurement System 14
2.2	CDMA 2000 Head SAR Test Results and Course Area Scans – 2D 20
2.3	CDMA 2000 835 MHz Body SAR Test Results and Course Area Scans – 2D 24
2.4	GSM 1900 MHz Head SAR Test Results and Course Area Scans – 2D 26
2.5	GSM 1900 MHz Body SAR Test Results and Course Area Scans – 2D 30
2.6	WLAN 802.11b 2450 MHz Head SAR Test Results and Course Area Scans – 2D 32
2.7	WLAN 802.11b 2450 MHz Body SAR Test Results and Course Area Scans – 2D 36
3	TEST EQUIPMENT USED 38
3.1	Test Equipment Used 39
3.2	Test Software 40
3.3	Dielectric Properties of Simulant Liquids 41
3.4	Test Conditions 42
3.5	Measurement Uncertainty 43
4	PHOTOGRAPHS 45
4.1	Test Positional Photographs 46
4.2	Photographs of Equipment Under Test (EUT) 49
5	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 51
5.1	Accreditation, Disclaimers and Copyright 52
ANNEX A	Probe Calibration Report A.2



Product Service

SECTION 1

REPORT SUMMARY

Specific Absorption Rate Testing of the
Sharp CDMA SHX12 Dual-band CDMA (BC0,BC6) and Tri-band GSM
(GSM900/DCS1800/PCS1900) Dual mode Cellular Phone with Bluetooth, Felica, WLAN and
GPS enabled Mobile Handset



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Specific Absorption Rate Testing of the Sharp CDMA SHX12 Dual-band CDMA (BC0,BC6) and Tri-band GSM (GSM900/DCS1800/PCS1900) Dual mode Cellular Phone with Bluetooth, Felica, WLAN and GPS enabled Mobile Handset to the requirements of EN 50360: 2001.

Objective	To perform Specific Absorption Rate Testing to determine the Equipment Under Test's (EUT's) compliance with the requirements specified of EN 50360: 2001, for the series of tests carried out.
Applicant	Sharp Communication Compliance Ltd
Manufacturer	Sharp Corporation
Manufacturing Description	Mobile Handset
Model Number	CDMA SHX12
Power Class	GSM 850 MHz Class 4 PCS 1900 MHz Class 1
IMEI Number(s)	004401113640987 (GSM 850) 004401113634311 (PCS 1900) 004401113638320 (WLAN)
Hardware Version	PP1
Software Version	A9140G
Battery Cell Manufacturer	Sharp Corporation
Battery Model Number	SHX12UAA
Test Specification/Issue/Date	OET Bulletin 65 Supplement C Edition 01-01
Start of Test	28 November 2011
Finish of Test	06 December 2011
Related Document(s)	FCC 47CFR 2.1093 KDB 248227 – v01r02 (Rev 1.2) KDB 450824 – D01 v01r01(Rev 1.1) KDB 450824 – D02 v01 KDB 648474 – D01 v01r05 KDB 941225 – D01 v02 KDB 941225 – D03 v01 IEEE 1528-2003
Name of Engineer(s)	Gary Bridle



Product Service

1.2 BRIEF SUMMARY OF RESULTS

The measurements shown in this report were made in accordance with the procedures specified OET 65(C) – 2001.

The maximum 1g volume averaged SAR found during this Assessment

Max 1g SAR (W/kg)	0.629
The maximum 1g volume averaged SAR level measured for all the tests performed did not exceed the limits for General Population/Uncontrolled Exposure (W/kg) Partial Body of 1.6 W/kg. Level defined in Supplement C (Edition 01-01) to OET Bulletin 65 (97-01).	

1.3 TEST RESULTS SUMMARY

1.3.1 System Performance / Validation Check Results

Prior to formal testing being performed a System Check was performed in accordance with OET 65(C) – 2001 and the results were compared against published data in Standard IEEE 1528-2003. The following results were obtained: -

System performance / Validation results

Date	Dipole Used	Frequency (MHz)	Max 1g SAR (W/kg)*	Percentage Drift on Reference	Max 10g SAR (W/kg)*	Percentage Drift on Reference
28/11/2011	850	844.4	9.62	-10.94%	6.39	-7.46%
06/12/2011	1900	1883.6	41.74	9.56%	22.05	7.58%
01/12/2011	2450	2450.0	48.17	21.34%	22.23	8.46%

*Normalised to a forward power of 1W



1.3.2 Results Summary Tables

CDMA 2000 850 MHz Head Specific Absorption Rate (Maximum SAR) 1g & 10g Results for the Sharp CDMA SHX12.

Position		Channel Number	Frequency (MHz)	Max Spot SAR (W/kg)	Max 1g SAR (W/kg)	Max 10g SAR (W/kg)	SAR Drift (%)	Area scan (Figure number)
Ear	Head							
Left	Cheek	1013	824.07	0.680	0.535	0.424	-2.590	Figure 8
Left	15°	1013	824.07	0.530	0.458	0.306	0.010	Figure 9
Right	Cheek	1013	824.07	0.610	0.575	0.433	-1.570	Figure 10
Right	15°	1013	824.07	0.440	0.417	0.310	1.010	Figure 11
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) & 2.0 W/kg (10g)								

CDMA 2000 850 MHz Body Specific Absorption Rate (Maximum SAR) 1g & 10g Results for the Sharp CDMA SHX12.

Position		Channel Number	Frequency (MHz)	Max Spot SAR (W/kg)	Max 1g SAR (W/kg)	Max 10g SAR (W/kg)	SAR Drift (%)	Area scan (Figure number)
Spacing	Direction							
15mm	Front Facing	189	836.4	0.230	0.163	0.111	-3.180	Figure 12
15mm	Rear Facing	189	836.4	0.390	0.413	0.194	-6.430	Figure 13
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) & 2.0 W/kg (10g)								

GSM 1900 MHz Head Specific Absorption Rate (Maximum SAR) 1g & 10g Results for the Sharp CDMA SHX12.

Position		Channel Number	Frequency (MHz)	Max Spot SAR (W/kg)	Max 1g SAR (W/kg)	Max 10g SAR (W/kg)	SAR Drift (%)	Area scan (Figure number)
Ear	Head							
Left	Cheek	661	1880	0.260	0.234	0.147	-0.040	Figure 14
Left	15°	661	1880	0.140	0.132	0.076	-2.250	Figure 15
Right	Cheek	661	1880	0.410	0.401	0.245	-0.710	Figure 16
Right	15°	661	1880	0.110	0.103	0.063	-2.290	Figure 17
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) & 2.0 W/kg (10g)								



Product Service

GSM 1900 MHz Body Specific Absorption Rate (Maximum SAR) 1g & 10g Results for the Sharp CDMA SHX12.

Position		Channel Number	Frequency (MHz)	Max Spot SAR (W/kg)	Max 1g SAR (W/kg)	Max 10g SAR (W/kg)	SAR Drift (%)	Area scan (Figure number)
Spacing	Direction							
15mm	Front Facing	661	1880	0.470	0.582	0.370	9.000	Figure 18
15mm	Rear Facing	661	1880	0.510	0.629	0.397	-5.670	Figure 19
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) & 2.0 W/kg (10g)								

WLAN 802.11b 2450 MHz Head Specific Absorption Rate (Maximum SAR) 1g & 10g Results for the Sharp CDMA SHX12.

Position		Channel Number	Frequency (MHz)	Max Spot SAR (W/kg)	Max 1g SAR (W/kg)	Max 10g SAR (W/kg)	SAR Drift (%)	Area scan (Figure number)
Ear	Head							
Left	Cheek	6	2437.0	0.150	0.136	0.073	1.220	Figure 20
Left	15°	6	2437.0	0.140	0.117	0.062	1.610	Figure 21
Right	Cheek	6	2437.0	0.060	0.058	0.037	0.100	Figure 22
Right	15°	6	2437.0	0.050	0.051	0.032	0.910	Figure 23
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) & 2.0 W/kg (10g)								

WLAN 802.11b 2450 MHz Body Specific Absorption Rate (Maximum SAR) 1g & 10g Results for the Sharp CDMA SHX12.

Position		Channel Number	Frequency (MHz)	Max Spot SAR (W/kg)	Max 1g SAR (W/kg)	Max 10g SAR (W/kg)	SAR Drift (%)	Area scan (Figure number)
Spacing	Direction							
15mm	Front Facing	6	2437.0	0.010	0.017	0.012	0.000	Figure 24
15mm	Rear Facing	6	2437.0	0.020	0.019	0.013	0.000	Figure 25
Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g) & 2.0 W/kg (10g)								



1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The equipment under test (EUT) was a Sharp CDMA SHX12 Dual-band CDMA (BC0,BC6) and Tri-band GSM (GSM900/DCS1800/PCS1900) Dual mode Cellular Phone with Bluetooth, Felica, WLAN and GPS enabled Mobile Handset. A full technical description can be found in the manufacturer's documentation.

1.4.2 Test Configuration and Modes of Operation

The testing was performed with standard batteries supplied and manufactured by Sharp Corporation. Each battery was fully charged before each measurement and there were no external connections.

For head SAR assessment, testing was performed with the device in the declared normal position of operation for Cellular CDMA 2000 GSM 850 MHz and PCS 1900 MHz and WLAN 2450 MHz frequency bands at maximum power. The device was placed against a Specific Anthropomorphic Mannequin (SAM) phantom as specified in the OET 65(C) - 2001. The phantom was filled with simulant liquid appropriate to the frequency band. The dielectric properties were measured and found to be in accordance with the requirements for the dielectric properties specified in OET 65(C) – 2001 testing was performed at both the left and right ear of the phantom at both handset positions stated in the applied specification.

For body SAR assessment, the device was tested for typical body-worn operation in accordance with the requirements of OET65(c) with the exception of SAR limits applied, these were obtained from ICNIRP (1998). Flat phantom dimensions are 210mmx210mmx210mm and with a sidewall thickness of 3.0mm. The phantom was filled to a depth of 150mm with the appropriate body simulant liquid. The dielectric properties were in accordance with the requirements specified in Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01). SAR testing was performed with the body of the device placed at 15.0mm separation from the phantom.

Conducted power measurements were carried out on the device in Voice and GPRS modes. The channel that yielded the highest SAR for each mode was used to make SAR measurements.

Testing was performed in each position at the frequency that gave the highest output power for each band. No SAR level was found to be within -3dB of the applicable limit (-3dB equates to ≤ 0.802 W/kg in this instance) therefore no additional testing was required at the remaining frequencies / channels of the bands



Simultaneous transmission SAR testing for Head/Body for CDMA2000 850MHz and PCS1900 was not required because the sum of the max 1-g SAR levels obtained is less than 1.6W/kg. Simultaneous transmission SAR testing for Head/Body for PCS1900 and BT was not required because the antenna separation distance is greater than 5cm and the Bluetooth conducted output power is less than 24mW. Simultaneous transmission SAR testing for Head/Body for PCS1900 and WLAN was not required because the Bluetooth conducted output power is less than 24mW. Simultaneous transmission SAR testing for Head/Body for CDMA2000 800MHz and WLAN was not required because the antenna separation distance is greater than 5cm and the maximum SAR levels obtained for both transmitters is less than 0.8W/kg. Simultaneous transmission SAR testing for Head/Body for CDMA2000 800MHz and BT was not required because the antenna separation distance is greater than 5cm and the Bluetooth conducted output power is less than 24mW. Simultaneous transmission SAR testing for Head/Body for WLAN and BT was not required because the antenna separation distance is less than 2.5cm and the Bluetooth conducted output power is less than 24mW. Stand alone SAR testing for Bluetooth was not required due to the output power being less than the threshold.

Testing was performed using a Universal Radio Communications test set. WLAN testing was achieved using the devices internal software, customer supplied software and settings supplied by the customer. The worse case data rate for WLAN testing was obtained from data provided by TUV Product Service determined by the testing of the handset to ETSI EN 300 328. The worst case was deemed as the data rate which produced the highest level of conducted average power. This was 11Mbps for 802.11b.

Due to the inability to make conducted power measurements on the WLAN SAR sample the following technique was used to make power measurements and ascertain what testing was required and which channel yielded the highest power. Due to limiting factors of the radiated test setup the radiated measurements were made in maximum peak only as maximum average measurements could not be made. Measurements were made on the conducted sample in maximum peak and maximum average. On a channel by channel basis the ratio between maximum peak and maximum average was worked out, this ratio was then applied to the radiated maximum peak measurements that were taken on the radiated sample.

Testing is not required on 802.11g/n when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels.

HEAD SAR CDMA2000:

SAR for the head exposure configurations is measured in RC3 with the EUT configured to transmit at full rate using Loopback Service Option SO55.

SAR for RC1 is not required when the maximum average output of each channel is less than 0.25dB higher than that measured in RC3. If SAR for RC1 is required, then SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

BODY SAR CDMA2000:

SAR for the body exposure configuration is measured in RC3 with the EUT configured using TDSO32, to transmit at full rate on FCH with all other code channels disabled.

SAR for multiple code channels (FCH + SCH) is not required when the maximum average output of each RF channel is less than 0.25dB higher than that measured with FCH only. If SAR for multiple code channels is required then SAR is measured on the maximum output channel (FCH + SCHn) with FCH at full rate and SCH0 enabled at 9600bps, using the exposure configuration that results in the highest SAR with FCH only for that channel. When multiple code channels are enabled, the DUT may shift by more than 0.5dB and lead to higher SAR drifts and SCH dropouts.



Product Service

Body SAR in RC1 is not required when the maximum average output of each channel is less than 0.25dB higher than that measured in RC3. If SAR for RC1 is required, then SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR that channel in RC3.

Included in this report are descriptions of the test method; the equipment used and an analysis of the test uncertainties applicable and diagrams indicating the locations of maximum SAR for each test position along with photographs indicating the positioning of the handset against the body as appropriate.



1.5 FCC POWER MEASUREMENTS

1.5.1 Method

Conducted power measurements were made using a power meter.

1.5.2 Conducted Power Measurements

Head

Serial No.	Mode	Modulation	Frequency	Conducted Carrier Power (dBm)	
				Average	Peak
SSHFL000935	S055, RC1	64-RAY Orthogonal	824.70	23.69	28.8
			836.52	23.44	28.1
			848.27	23.47	29.24

Serial No.	Mode	Modulation	Frequency	Conducted Carrier Power (dBm)	
				Average	
SSHFL000935	S055, RC3	64-RAY Orthogonal	824.70	23.43	
			838.52	23.42	
			848.37	23.37	

Body

Serial No.	Mode	Modulation	Frequency	Conducted Carrier Power (dBm)	
				Average	Peak
SSHFL000935	TDS032,	BPSK	824.70	23.51	28.74
	FCH		838.52	23.42	28.60
	RC3		848.37	23.54	28.78

Serial No.	Mode	Modulation	Frequency	Conducted Carrier Power (dBm)	
				Average	
SSHFL000935	TDS032,	BPSK	824.70	23.67	
	FCH +SCH		838.52	23.51	
	RC3		848.37	23.53	

**WLAN**

Mode	Modulation	Frequency	Conducted Carrier Power (dBm) IMEI 004401113357913	Radiated Carrier Power(dBm) IMEI 004401113358119	Peak to Average Ratio (dB)	Corrected Radiated Carrier Power for SAR Report (dBm)
802.11b 2Mbps	DQPSK	2412	18.74	16.8	3.64	13.16
		2437	19.32	17.4	3.45	13.95
		2462	18.83	17.1	3.69	13.41

Mode	Modulation	Frequency	Conducted Carrier Power (dBm) IMEI 004401113357913	Radiated Carrier Power(dBm) IMEI 004401113358119	Peak to Average Ratio (dB)	Corrected Radiated Carrier Power for SAR Report (dBm)
802.11g 6Mbps	BPSK	2412	22.52	18.76	9.64	9.12
		2437	22.61	20.51	9.55	10.96
		2462	23.12	22.30	9.66	12.64

Mode	Modulation	Frequency	Conducted Carrier Power (dBm) IMEI 004401113357913	Radiated Carrier Power(dBm) IMEI 004401113358119	Peak to Average Ratio (dB)	Corrected Radiated Carrier Power for SAR Report (dBm)
802.11n 6.5Mbps	BPSK	2412	21.80	21.10	10.02	11.08
		2437	21.89	22.31	10.05	12.26
		2462	22.33	23.94	10.04	13.90

PCS 1900

IMEI	Modulation	Frequency	Conducted Carrier Power (dBm)
004401113634311	GMSK	1850.2	30.01
		1800.0	30.07
		1909.8	30.05



Product Service

SECTION 2

TEST DETAILS

Specific Absorption Rate Testing of the
Sharp CDMA SHX12 Dual-band CDMA (BC0,BC6) and Tri-band GSM
(GSM900/DCS1800/PCS1900) Dual mode Cellular Phone with Bluetooth, Felica, WLAN and
GPS enabled Mobile Handset.



2.1 SARA 2 SAR MEASUREMENT SYSTEM

2.1.1 Robot System Specification

The SAR measurement system being used is the IndexSAR SARA2 system, which consists of a Mitsubishi RV-E2 6-axis robot arm and controller, IndexSAR probe and amplifier and SAM phantom Head Shape. The robot is used to articulate the probe to programmed positions inside the phantom head to obtain the SAR readings from the DUT.

Schematic diagram of the SAR measurement system




Figure 1

The system is controlled remotely from a PC, which contains the software to control the robot and data acquisition equipment. The software also displays the data obtained from test scans.

The position and digitised shape of the phantom heads are made available to the software for accurate positioning of the probe and reduction of set-up time.

The SAM phantom heads are individually digitised using a Mitutoyo CMM machine to a precision of 0.001mm. The data is then converted into a shape format for the software, providing an accurate description of the phantom shell.

In operation, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom. When the maximum SAR point has been found, the system will then carry out a 3D scan centred at that point to determine volume averaged SAR level.



2.1.2 Probe and Amplifier Specification

IXP-050 IndexSAR isotropic immersible SAR probe

The probes are constructed using three orthogonal dipole sensors arranged on an interlocking, triangular prism core. The probes have built-in shielding against static charges and are contained within a PEEK cylindrical enclosure material at the tip. Probe calibration is described in the following section.

IFA-010 Fast Amplifier

Technical description of IndexSAR IFA-010 Fast probe amplifier

A block diagram of the fast probe amplifier electronics is shown below.

Block diagram of the fast probe amplifier electronic




Figure 2

This amplifier has a time constant of approx. 50µs, which is much faster than the SAR probe response time. The overall system time constant is therefore that of the probe (<1ms) and reading sets for all three channels (simultaneously) are returned every 2ms to the PC. The conversion period is approx. 1 µs at the start of each 2ms period. This enables the probe to follow pulse modulated signals of periods >>2ms. The PC software applies the linearisation procedure separately to each reading, so no linearisation corrections for the averaging of modulated signals are needed in this case. It is important to ensure that the probe reading frequency and the pulse period are not synchronised and the behaviour with pulses of short duration in comparison with the measurement interval need additional consideration.

Phantoms

The Flat phantom used is a rectangular Perspex Box IndexSAR item IXB-070. Dimensions 210w 210d 210h (mm). This phantom is used with IndexSAR side bench IXM-030.

The Specific Anthropomorphic Mannequin (SAM) Upright Phantom is fabricated using moulds generated from the CAD files as specified by CENELEC EN 62209-1: 2006. It is mounted via a rotation base to a supporting table, which also holds the robotic positioner. The phantom and robot alignment is assured by both mechanical and laser registration systems.



2.1.3 SAR Measurement Procedure

Principal components of the SAR measurement test bench



Figure 3




Figure 4

The major components of the test bench are shown in the pictures above. A test set and dipole antenna control the handset via an air link and a low-mass phone holder can position the phone at either ear. Graduated scales are provided to set the phone in the 15 degree position. The upright phantom head holds approx. 7 litres of simulant liquid. The phantom is filled and emptied through a 45mm diameter penetration hole in the top of the head.

After an area scan has been done at a fixed distance of 8mm from the surface of the phantom on the source side, a 3D scan is set up around the location of the maximum spot SAR. First, a point within the scan area is visited by the probe and a SAR reading taken at the start of testing. At the end of testing, the probe is returned to the same point and a second reading is taken. Comparison between these start and end readings enables the power drift during measurement to be assessed.

SARA2 Interpolation and Extrapolation schemes

SARA2 software contains support for both 2D cubic B-spline interpolation as well as 3D cubic B-spline interpolation. In addition, for extrapolation purposes, a general n^{th} order polynomial fitting routine is implemented following a singular value decomposition algorithm presented in [4]. A 4th order polynomial fit is used by default for data extrapolation, but a linear-logarithmic fitting function can be selected as an option. The polynomial fitting procedures have been tested by comparing the fitting coefficients generated by the SARA2 procedures with those obtained using the polynomial fit functions of Microsoft Excel when applied to the same test input data.



Interpolation of 2D area scan

The 2D cubic B-spline interpolation is used after the initial area scan at fixed distance from the phantom shell wall. The initial scan data are collected with approx. 115mm spatial resolution and spline interpolation is used to find the location of the local maximum to within a 1mm resolution for positioning the subsequent 3D scanning.

Extrapolation of 3D scan

For the 3D scan, data are collected on a spatially regular 3D grid having (by default) 6.4 mm steps in the lateral dimensions and 3.5 mm steps in the depth direction (away from the source). SARA2 enables full control over the selection of alternative step sizes in all directions.

The digitised shape of the head is available to the SARA2 software, which decides which points in the 3D array are sufficiently well within the shell wall to be 'visited' by the SAR probe. After the data collection, the data are extrapolated in the depth direction to assign values to points in the 3D array closer to the shell wall. A notional extrapolation value is also assigned to the first point outside the shell wall so that subsequent interpolation schemes will be applicable right up to the shell wall boundary.

Interpolation of 3D scan and volume averaging

The procedure used for defining the shape of the volumes used for SAR averaging in the SARA2 software follow the method of adapting the surface of the 'cube' to conform with the curved inner surface of the phantom (see Appendix C.2.2.1 in EN 62209-1: 2006). This is called, here, the conformal scheme.

For each row of data in the depth direction, the data are extrapolated and interpolated to less than 1mm spacing and average values are calculated from the phantom surface for the row of data over distances corresponding to the requisite depth for 10g and 1g cubes. This results in two 2D arrays of data, which are then cubic B-spline interpolated to sub mm lateral resolution. A search routine then moves an averaging square around through the 2D array and records the maximum value of the corresponding 1g and 10g volume averages. For the definition of the surface in this procedure, the digitised position of the headshell surface is used for measurement in head-shaped phantoms. For measurements in rectangular, box phantoms, the distance between the phantom wall and the closest set of gridded data points is entered into the software.

For measurements in box-shaped phantoms, this distance is under the control of the user. The effective distance must be greater than 2.5mm as this is the tip-sensor distance and to avoid interface proximity effects, it should be at least 5mm. A value of 6 or 8mm is recommended. This distance is called **dbe** in EN 62209-1: 2006.

For automated measurements inside the head, the distance cannot be less than 2.5mm, which is the radius of the probe tip and to avoid interface proximity effects, a minimum clearance distance of x mm is retained. The actual value of **dbe** will vary from point to point depending upon how the spatially-regular 3D grid points fit within the shell. The greatest separation is when a grid point is just not visited due to the probe tip dimensions. In this case the distance could be as large as the step-size plus the minimum clearance distance (i.e with $x=5$ and a step size of 3.5, **dbe** will be between 3.5 and 8.5mm).

The default step size (**dstep** in EN 62209-1: 2006) used is 3.5mm, but this is under user-control. The compromise is with time of scan, so it is not practical to make it much smaller or scan times become long and power-drop influences become larger.



Product Service

The robot positioning system specification for the repeatability of the positioning (**dss** in EN 62209-1: 2006) is $\pm 0.04\text{mm}$.

The phantom shell is made by an industrial moulding process from the CAD files of the SAM shape, with both internal and external moulds. For the upright phantoms, the external shape is subsequently digitised on a Mitutoyo CMM machine (Euro C574) to a precision of 0.001mm . Wall thickness measurements made non-destructively with an ultrasonic sensor indicate that the shell thickness (**dph**) away from the ear is $2.0 \pm 0.1\text{mm}$. The ultrasonic measurements were calibrated using additional mechanical measurements on available cut surfaces of the phantom shells.

For the upright phantom, the alignment is based upon registration of the rotation axis of the phantom on its 253mm-diameter baseplate bearing and the position of the probe axis when commanded to go to the axial position. A laser alignment tool is provided (procedure detailed elsewhere). This enables the registration of the phantom tip (**dmis**) to be assured to within approx. 0.2mm . This alignment is done with reference to the actual probe tip after installation and probe alignment. The rotational positioning of the phantom is variable – offering advantages for special studies, but locating pins ensure accurate repositioning at the principal positions (LH and RH ears).



2.1.4 Head Test Positions

This recommended practice specifies exactly two test positions for the handset against the head phantom, the “Cheek” position and the “tilted” position. These two test positions are defined in the following sub-clauses. The handset should be tested in both positions on the left and right sides of the SAM phantom. In each test position the centre of the earpiece of the device is placed directly at the entrance of the auditory canal. The angles mentioned in the test positions used are referenced to the line connecting both auditory canal openings. The plane this line is on is known as the reference plane. Testing is performed on the right and left-hand sides of the generic phantom head.




Figure 5. – Side View of Mobile next to head showing alignment.

The Cheek Position

The Cheek Position is where the mobile is in the reference plane and the line between the mobile and the line connecting both auditory canal openings is reduced until any part of the mobile touches any part of the generic twin phantom head.

The 15° Position

The 15° Position is where the mobile is in the reference Cheek position and the phone is kept in contact with the auditory canal at the earpiece; the bottom of the phone is then tilted away from the phantom mouth by 15°.




Figure 6. – Cheek Position.




Figure 7. – 15° Tilt Position.



2.2 CDMA 2000 HEAD SAR TEST RESULTS AND COURSE AREA SCANS – 2D

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	28/11/2011 13:02:58	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	01.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.00°C	LIQUID SIMULANT:	835Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	40.73
RELATIVE HUMIDITY:	32.80%	CONDUCTIVITY:	0.881
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	0°	MAX SAR Y-AXIS LOCATION:	-43.80mm
DUT POSITION:	Left-Cheek	MAX SAR Z-AXIS LOCATION:	-157.45mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	21.62
TEST FREQUENCY:	824.07MHz	SAR 1g:	0.535 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.424 W/kg
CONVERSION FACTORS:	0.217 / 0.292 / 0.232	SAR START:	0.293 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.285 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	-2.590 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	28/11/2011
INPUT POWER LEVEL:	23dBm	EXTRAPOLATION:	poly4




Figure 8: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 824.07MHz.



SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	28/11/2011 14:01:33	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	02.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.00°C	LIQUID SIMULANT:	835Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	40.73
RELATIVE HUMIDITY:	32.80%	CONDUCTIVITY:	0.881
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	0°	MAX SAR Y-AXIS LOCATION:	-28.40mm
DUT POSITION:	Left-15°	MAX SAR Z-AXIS LOCATION:	-145.95mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	19.56
TEST FREQUENCY:	824.07MHz	SAR 1g:	0.458 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.306 W/kg
CONVERSION FACTORS:	0.217 / 0.292 / 0.232	SAR START:	0.229 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.229 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	0.010 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	28/11/2011
INPUT POWER LEVEL:	23dBm	EXTRAPOLATION:	poly4




Figure 9: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 824.07MHz.



SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	28/11/2011 14:38:11	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	03.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.00°C	LIQUID SIMULANT:	835Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	40.73
RELATIVE HUMIDITY:	32.80%	CONDUCTIVITY:	0.881
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	180°	MAX SAR Y-AXIS LOCATION:	49.40mm
DUT POSITION:	Right-Cheek	MAX SAR Z-AXIS LOCATION:	-166.65mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	23.48
TEST FREQUENCY:	824.07MHz	SAR 1g:	0.575 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.433 W/kg
CONVERSION FACTORS:	0.217 / 0.292 / 0.232	SAR START:	0.349 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.344 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	-1.570 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	28/11/2011
INPUT POWER LEVEL:	23dBm	EXTRAPOLATION:	poly4




Figure 10: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 824.07MHz.



SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	28/11/2011 15:38:49	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	04.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.00°C	LIQUID SIMULANT:	835Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	40.73
RELATIVE HUMIDITY:	32.80%	CONDUCTIVITY:	0.881
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	180°	MAX SAR Y-AXIS LOCATION:	31.20mm
DUT POSITION:	Right-15°	MAX SAR Z-AXIS LOCATION:	-154.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	19.79
TEST FREQUENCY:	824.07MHz	SAR 1g:	0.417 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.310 W/kg
CONVERSION FACTORS:	0.217 / 0.292 / 0.232	SAR START:	0.225 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.228 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	1.010 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	28/11/2011
INPUT POWER LEVEL:	23dBm	EXTRAPOLATION:	poly4




Figure 11: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 824.07MHz.



2.3 CDMA 2000 835 MHz BODY SAR TEST RESULTS AND COURSE AREA SCANS – 2D

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	29/11/2011 09:58:55	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	05.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.50°C	LIQUID SIMULANT:	835Body
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	53.27
RELATIVE HUMIDITY:	41.60%	CONDUCTIVITY:	0.985
PHANTOM S/NO:	HeadBox2.csv	LIQUID TEMPERATURE:	22.40°C
PHANTOM ROTATION:	N/A	MAX SAR X-AXIS LOCATION:	-8.00mm
DUT POSITION:	15mm-Front Facing	MAX SAR Y-AXIS LOCATION:	-4.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	11.370
TEST FREQUENCY:	836.4MHz	SAR 1g:	0.163 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.111 W/kg
CONVERSION FACTORS:	0.223 / 0.294 / 0.234	SAR START:	0.045 W/kg
TYPE OF MODULATION:	GMSK (GPRS Mode)	SAR END:	0.044 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	-3.180 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	29/11/2011
INPUT POWER LEVEL:	23dBm	EXTRAPOLATION:	poly4




Figure 12: SAR Body Testing Results for the Sharp CDMA SHX12 Mobile Handset at 836.4MHz.



SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	29/11/2011 11:03:38	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	06.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.50°C	LIQUID SIMULANT:	835Body
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	53.27
RELATIVE HUMIDITY:	41.60%	CONDUCTIVITY:	0.985
PHANTOM S/NO:	HeadBox2.csv	LIQUID TEMPERATURE:	22.40°C
PHANTOM ROTATION:	N/A	MAX SAR X-AXIS LOCATION:	17.00mm
DUT POSITION:	15mm-Rear Facing	MAX SAR Y-AXIS LOCATION:	8.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	14.880
TEST FREQUENCY:	836.4MHz	SAR 1g:	0.413 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.194 W/kg
CONVERSION FACTORS:	0.223 / 0.294 / 0.234	SAR START:	0.079 W/kg
TYPE OF MODULATION:	GMSK (GPRS Mode)	SAR END:	0.074 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	-6.430 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	29/11/2011
INPUT POWER LEVEL:	23dBm	EXTRAPOLATION:	poly4




Figure 13: SAR Body Testing Results for the Sharp CDMA SHX12 Mobile Handset at 836.4MHz.



2.4 GSM 1900 MHz HEAD SAR TEST RESULTS AND COURSE AREA SCANS – 2D

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	06/12/2011 16:15:31	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	07.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.90°C	LIQUID SIMULANT:	1900Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	38.44
RELATIVE HUMIDITY:	26.80%	CONDUCTIVITY:	1.440
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	0°	MAX SAR Y-AXIS LOCATION:	-59.20mm
DUT POSITION:	Left-Cheek	MAX SAR Z-AXIS LOCATION:	-179.30mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	10.580
TEST FREQUENCY:	1880MHz	SAR 1g:	0.234 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.147 W/kg
CONVERSION FACTORS:	0.271 / 0.330 / 0.297	SAR START:	0.102 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.104 W/kg
MODN. DUTY CYCLE:	12.5%	SAR DRIFT DURING SCAN:	-0.040 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	30dBm	EXTRAPOLATION:	poly4




Figure 14: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 1880MHz.



Product Service

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	07/12/2011 08:51:37	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	08.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.20°C	LIQUID SIMULANT:	1900Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	38.44
RELATIVE HUMIDITY:	29.50%	CONDUCTIVITY:	1.440
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	0°	MAX SAR Y-AXIS LOCATION:	-8.80mm
DUT POSITION:	Left-15°	MAX SAR Z-AXIS LOCATION:	-129.85mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	7.790
TEST FREQUENCY:	1880MHz	SAR 1g:	0.132 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.076 W/kg
CONVERSION FACTORS:	0.271 / 0.330 / 0.297	SAR START:	0.047 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.046 W/kg
MODN. DUTY CYCLE:	12.5%	SAR DRIFT DURING SCAN:	-2.250 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	30dBm	EXTRAPOLATION:	poly4




Figure 15: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 1880MHz.



SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	07/12/2011 09:23:24	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	09.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.20°C	LIQUID SIMULANT:	1900Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	38.44
RELATIVE HUMIDITY:	29.50%	CONDUCTIVITY:	1.440
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	180°	MAX SAR Y-AXIS LOCATION:	56.40mm
DUT POSITION:	Right-Cheek	MAX SAR Z-AXIS LOCATION:	-182.75mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	13.350
TEST FREQUENCY:	1880MHz	SAR 1g:	0.401 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.245 W/kg
CONVERSION FACTORS:	0.271 / 0.330 / 0.297	SAR START:	0.182 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.180 W/kg
MODN. DUTY CYCLE:	12.5%	SAR DRIFT DURING SCAN:	-0.710 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	30dBm	EXTRAPOLATION:	poly4




Figure 16: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 1880MHz.



Product Service

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	07/12/2011 09:57:34	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	10.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.20°C	LIQUID SIMULANT:	1900Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	38.44
RELATIVE HUMIDITY:	29.50%	CONDUCTIVITY:	1.440
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	180°	MAX SAR Y-AXIS LOCATION:	6.00mm
DUT POSITION:	Right-15°	MAX SAR Z-AXIS LOCATION:	-134.45mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	6.940
TEST FREQUENCY:	1880MHz	SAR 1g:	0.103 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.063 W/kg
CONVERSION FACTORS:	0.271 / 0.330 / 0.297	SAR START:	0.041 W/kg
TYPE OF MODULATION:	GMSK (Voice Mode)	SAR END:	0.041 W/kg
MODN. DUTY CYCLE:	12.5%	SAR DRIFT DURING SCAN:	-2.290 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	30dBm	EXTRAPOLATION:	poly4




Figure 17: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 1880MHz.



2.5 GSM 1900 MHz BODY SAR TEST RESULTS AND COURSE AREA SCANS – 2D

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	07/12/2011 11:43:40	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	11.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.20°C	LIQUID SIMULANT:	1900Body
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	54.20
RELATIVE HUMIDITY:	29.50%	CONDUCTIVITY:	1.590
PHANTOM S/NO:	HeadBox1.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	N/A	MAX SAR X-AXIS LOCATION:	39.00mm
DUT POSITION:	15mm-Front Facing	MAX SAR Y-AXIS LOCATION:	-14.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	16.960
TEST FREQUENCY:	1880MHz	SAR 1g:	0.582 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.370 W/kg
CONVERSION FACTORS:	0.306 / 0.390 / 0.322	SAR START:	0.105 W/kg
TYPE OF MODULATION:	GMSK (GPRS Mode)	SAR END:	0.095 W/kg
MODN. DUTY CYCLE:	25%	SAR DRIFT DURING SCAN:	9.000 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	30dBm	EXTRAPOLATION:	poly4




Figure 18: SAR Body Testing Results for the Sharp CDMA SHX12 Mobile Handset at 1880MHz.



Product Service

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	07/12/2011 12:30:36	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	12.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	23.20°C	LIQUID SIMULANT:	1900Body
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	54.20
RELATIVE HUMIDITY:	29.50%	CONDUCTIVITY:	1.590
PHANTOM S/NO:	HeadBox1.csv	LIQUID TEMPERATURE:	23.00°C
PHANTOM ROTATION:	N/A	MAX SAR X-AXIS LOCATION:	40.00mm
DUT POSITION:	15mm-Rear Facing	MAX SAR Y-AXIS LOCATION:	16.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	17.440
TEST FREQUENCY:	1880MHz	SAR 1g:	0.629 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.397 W/kg
CONVERSION FACTORS:	0.306 / 0.390 / 0.322	SAR START:	0.110 W/kg
TYPE OF MODULATION:	GMSK (GPRS Mode)	SAR END:	0.104 W/kg
MODN. DUTY CYCLE:	25%	SAR DRIFT DURING SCAN:	-5.670 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	30dBm	EXTRAPOLATION:	poly4




Figure 19: SAR Body Testing Results for the Sharp CDMA SHX12 Mobile Handset at 1880MHz.



2.6 WLAN 802.11b 2450 MHz HEAD SAR TEST RESULTS AND COURSE AREA SCANS – 2D

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	05/12/2011 14:53:35	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	13.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.30°C	LIQUID SIMULANT:	2450Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	37.86
RELATIVE HUMIDITY:	24.30%	CONDUCTIVITY:	1.783
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	22.40°C
PHANTOM ROTATION:	0°	MAX SAR Y-AXIS LOCATION:	-8.80mm
DUT POSITION:	Left-Cheek	MAX SAR Z-AXIS LOCATION:	-122.95mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	6.680
TEST FREQUENCY:	2437.0MHz	SAR 1g:	0.136 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.073 W/kg
CONVERSION FACTORS:	0.282 / 0.359 / 0.319	SAR START:	0.033 W/kg
TYPE OF MODULATION:	2Mbps	SAR END:	0.033 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	1.220 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	05/12/2011
INPUT POWER LEVEL:	20dBm	EXTRAPOLATION:	poly4




Figure 20: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 2437.0MHz.



Product Service

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	05/12/2011 15:20:15	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	14.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.30°C	LIQUID SIMULANT:	2450Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	37.86
RELATIVE HUMIDITY:	24.30%	CONDUCTIVITY:	1.783
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	22.40°C
PHANTOM ROTATION:	0°	MAX SAR Y-AXIS LOCATION:	-6.00mm
DUT POSITION:	Left-15°	MAX SAR Z-AXIS LOCATION:	-121.80mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	6.080
TEST FREQUENCY:	2437.0MHz	SAR 1g:	0.117 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.062 W/kg
CONVERSION FACTORS:	0.282 / 0.359 / 0.319	SAR START:	0.027 W/kg
TYPE OF MODULATION:	2Mbs	SAR END:	0.027 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	1.610 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	05/12/2011
INPUT POWER LEVEL:	20dBm	EXTRAPOLATION:	poly4




Figure 21: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 2437.0MHz.



SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	05/12/2011 15:51:56	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	15.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.30°C	LIQUID SIMULANT:	2450Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	37.86
RELATIVE HUMIDITY:	24.30%	CONDUCTIVITY:	1.783
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	22.40°C
PHANTOM ROTATION:	180°	MAX SAR Y-AXIS LOCATION:	11.60mm
DUT POSITION:	Right-Cheek	MAX SAR Z-AXIS LOCATION:	-137.90mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	4.690
TEST FREQUENCY:	2437.0MHz	SAR 1g:	0.058 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.037 W/kg
CONVERSION FACTORS:	0.282 / 0.359 / 0.319	SAR START:	0.016 W/kg
TYPE OF MODULATION:	2Mbs	SAR END:	0.016 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	0.100 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	05/12/2011
INPUT POWER LEVEL:	20dBm	EXTRAPOLATION:	poly4




Figure 22: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 2437.0MHz.



Product Service

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	05/12/2011 16:20:36	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	16.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.30°C	LIQUID SIMULANT:	2450Head
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	37.86
RELATIVE HUMIDITY:	24.30%	CONDUCTIVITY:	1.783
PHANTOM S/NO:	Head092.csv	LIQUID TEMPERATURE:	22.40°C
PHANTOM ROTATION:	180°	MAX SAR Y-AXIS LOCATION:	1.80mm
DUT POSITION:	Right-15°	MAX SAR Z-AXIS LOCATION:	-132.15mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	4.280
TEST FREQUENCY:	2437.0MHz	SAR 1g:	0.051 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.032 W/kg
CONVERSION FACTORS:	0.282 / 0.359 / 0.319	SAR START:	0.015 W/kg
TYPE OF MODULATION:	2Mbs	SAR END:	0.015 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	0.910 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	05/12/2011
INPUT POWER LEVEL:	20dBm	EXTRAPOLATION:	poly4




Figure 23: SAR Head Testing Results for the Sharp CDMA SHX12 Mobile Handset at 2437.0MHz.



2.7 WLAN 802.11b 2450 MHz BODY SAR TEST RESULTS AND COURSE AREA SCANS – 2D

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	06/12/2011 09:25:27	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	17.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.40°C	LIQUID SIMULANT:	2450Body
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	50.12
RELATIVE HUMIDITY:	25.50%	CONDUCTIVITY:	1.926
PHANTOM S/NO:	HeadBox1.csv	LIQUID TEMPERATURE:	22.60°C
PHANTOM ROTATION:	N/A	MAX SAR X-AXIS LOCATION:	-26.00mm
DUT POSITION:	15mm-Front Facing	MAX SAR Y-AXIS LOCATION:	-2.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	2.05
TEST FREQUENCY:	2437.0MHz	SAR 1g:	0.017 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.012 W/kg
CONVERSION FACTORS:	0.355 / 0.419 / 0.382	SAR START:	0.001 W/kg
TYPE OF MODULATION:	2Mbs	SAR END:	0.001 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	0.000 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	20dBm	EXTRAPOLATION:	poly4




Figure 24: SAR Body Testing Results for the Sharp CDMA SHX12 Mobile Handset at 2437.0MHz.



Product Service

SYSTEM / SOFTWARE:	SARA2 / 2.53 VPM	INPUT POWER DRIFT:	0 dB
DATE / TIME:	06/12/2011 10:44:08	DUT BATTERY MODEL/NO:	SHX12UAA
FILENAME:	18.txt	PROBE SERIAL NUMBER:	189
AMBIENT TEMPERATURE:	22.40°C	LIQUID SIMULANT:	2450Body
DEVICE UNDER TEST:	Sharp SHX12	RELATIVE PERMITTIVITY:	50.12
RELATIVE HUMIDITY:	25.50%	CONDUCTIVITY:	1.926
PHANTOM S/NO:	HeadBox1.csv	LIQUID TEMPERATURE:	22.60°C
PHANTOM ROTATION:	N/A	MAX SAR X-AXIS LOCATION:	-41.00mm
DUT POSITION:	15mm-Rear Facing	MAX SAR Y-AXIS LOCATION:	-13.00mm
ANTENNA CONFIGURATION:	N/A	MAX E FIELD:	2.130
TEST FREQUENCY:	2437.0MHz	SAR 1g:	0.019 W/kg
AIR FACTORS:	513.08 / 463.99 / 518.85	SAR 10g:	0.013 W/kg
CONVERSION FACTORS:	0.355 / 0.419 / 0.382	SAR START:	0.001 W/kg
TYPE OF MODULATION:	2Mbs	SAR END:	0.001 W/kg
MODN. DUTY CYCLE:	100%	SAR DRIFT DURING SCAN:	0.000 %
DIODE COMPRESSION FACTORS (V*200):	20 / 20 / 20	PROBE BATTERY LAST CHANGED:	06/12/2011
INPUT POWER LEVEL:	20dBm	EXTRAPOLATION:	poly4




Figure 25: SAR Body Testing Results for the Sharp CDMA SHX12 Mobile Handset at 2437.0MHz.



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

The following test equipment was used at TÜV SÜD Product Service Ltd:

Instrument Description	Manufacturer	Model Type	TE Number	Cal Period (months)	Calibration Due Date
10MHz - 2.5GHz, 3W, Amplifier	Vectawave Technology	VTL5400	51	-	TU
Directional Coupler	Krytar	1850	58	-	TU
Signal Generator	Hewlett Packard	ESG4000A	61	12	18-May-12
SAR Robot	Mitsubishi	RV-E2	156	-	TU
Attenuator (20dB, 10W)	Weinschel	37-20-34	482	12	11-Oct-12
Fast Probe Amplifier (3 channels)	IndexSar Ltd	IFA-010	1557	-	TU
Flat Phantom	IndexSar Ltd	Headbox 02	1564	-	TU
200mm ³ Box Phantom 2	IndexSar Ltd	IXB-070	1566	-	TU
200mm Device Support (Foam)	IndexSar Ltd	IXB-032	1574	-	TU
Dipole Positioner/Support (plastic)	IndexSar Ltd	IXH-020	1580	-	TU
Dipole Positioner/Support (plastic)	IndexSar Ltd	IXH-020	1585	-	TU
Hygrometer	Rotronic	A1	2677	12	20-Jan-12
Power Sensor	Rohde & Schwarz	NRV-Z1	2879	12	25-May-12
Antenna (Omnidirectional)	Katherin Scala Division	OG-890/1990/DC	2906	12	TU
Power Meter	Rohde & Schwarz	NRVD	2979	12	24-May-12
Radio Communications Test Set	Rohde & Schwarz	CMU 200	3035	12	07-Oct-12
Radio Communications Test Set	Rohde & Schwarz	CMU 200	S/N106235	12	09-Jun-12
Power Sensor	Rohde & Schwarz	NRV-Z1	3563	12	25-May-12
Meter & T/C	R.S Components	Meter 615-8206 & Type K T/C	3612	12	18-Feb-12
Immersible SAR Probe	IndexSar Ltd	IXP-050	3892	12	23-Feb-12
835 MHz Head Fluid	TUV Product Service	Batch 18	N/A	1	25-Dec-11
835 MHz Body Fluid	TUV Product Service	Batch 10	N/A	1	25-Dec-11
1900 MHz Head Fluid	TUV Product Service	Batch 5	N/A	1	25-Dec-11
1900 MHz Body Fluid	TUV Product Service	Batch 4	N/A	1	25-Dec-11
2450 MHz Head Fluid	TUV Product Service	Batch 9	N/A	1	25-Dec-11
2450 MHz Body Fluid	TUV Product Service	Batch 7	N/A	1	25-Dec-11

TU – Traceability Unscheduled



Product Service

3.2 TEST SOFTWARE

The following software was used to control the TÜV SÜD Product Service Ltd SARA2 System.

Instrument	Version Number	Date
SARA2 system	v.2.5.3 VPM	28 November 2006
Mitsubishi robot controller firmware revision	RV-E2 Version C9a	-
IFA-10 Probe amplifier	Version 2	-



3.3 DIELECTRIC PROPERTIES OF SIMULANT LIQUIDS

The fluid properties of the simulant fluids used during routine SAR evaluation meet the dielectric properties required by OET 65(C) – 2001.

The fluids were calibrated in our Laboratory and re-checked prior to any measurements being made against reference fluids stated in IEEE 1528-2003 of 0.9% NaCl (Salt Solution) at 23°C and also for Dimethylsulphoxide (DMS) at 21°C.

IEEE 1528 Recipes

Frequency (MHz)	300	450	835	900	1450	1800	1900	1950	2000	2100	2450	3000
Recipe#	1	1	3	1	1	2	3	1	1	2	3	2
Ingredients (% by weight)												
1, 2-Propanediol					64.81							
Bactericide	0.19	0.19	0.50	0.10	0.10	0.50					0.50	
Diacetin			48.90			49.20					49.45	
DGBE						45.41	47.00	13.84	44.92	44.94	13.84	45.00
HEC	0.98	0.96		1.00	1.00							
NaCl	5.95	3.95	1.70	1.45	1.48	0.79	1.10	0.67	0.36	0.35	0.18	0.64
Sucrose	55.32	56.32		57.00	56.50							
Triton X-100								30.45				
Water	37.56	38.56	48.90	40.45	40.92	34.40	49.20	53.80	52.64	55.36	54.90	49.43
Measured dielectric parameters												
ϵ_r	46.00	43.40	44.30	41.60	41.20	41.80	42.70	40.9	39.3	41.00	40.40	39.20
σ (S/m)	0.86	0.85	0.90	0.90	0.98	0.97	0.99	1.21	1.39	1.38	1.40	1.40
Temp (°C)	22	22	20	22	22	22	20	22	21	22	20	21
Target dielectric parameters (Table 2)												
ϵ_r	45.30	43.50	41.5	41.50	40.50	40.00	39.80	39.20	38.50			
σ (S/m)	0.87	0.87	0.9	0.97	1.20	1.40	1.49	1.80	2.40			
NOTE – Multiple columns for any single frequency are optional recipe #, reference: 1 (Kanda et al. [B185]), 2 (Vigneras [B143]), 3 (Peyman and Gabriel [B119]), 4 (Fukunaga et al [B50])												



Product Service

The dielectric properties of the tissue simulant liquids used for the SAR testing at TÜV SÜD Product Service Ltd are as follows:-

Fluid Type and Frequency	Relative Permittivity ϵ_R (ϵ') Target	Relative Permittivity ϵ_R (ϵ') Measured	Conductivity σ Target	Conductivity σ Measured
835 MHz Head	41.5	40.73	0.90	0.881
835 MHz Body	55.0	53.27	0.97	0.985
1900 MHz Head	40.0	38.44	1.40	1.440
1900 MHz Body	53.3	54.20	1.52	1.590
2450 MHz Head	39.2	37.86	1.8	1.783
2450 MHz Body	52.7	50.12	1.95	1.926

3.4 TEST CONDITIONS

3.4.1 Test Laboratory Conditions

Ambient temperature: Within +15°C to +35°C.

The actual temperature during the testing ranged from 22.3°C to 23.2°C.

The actual humidity during the testing ranged from 24.3% to 41.6% RH.

3.4.2 Test Fluid Temperature Range

Frequency	Body / Head Fluid	Min Temperature	Max Temperature
835 MHz	Head	23	23
835 MHz	Body	22.4	22.4
1900 MHz	Head	23	23
1900 MHz	Body	23	23
2450 MHz	Head	22.4	22.4
2450 MHz	Body	22.6	22.6

3.4.3 SAR Drift

The SAR Drift was within acceptable limits during scans. The maximum SAR Drift, drift due to the handset electronics, was recorded as 9% (1.76 dB) for all of the testing. The measurement uncertainty budget for this assessment includes the maximum SAR Drift figures for Head and/or Body as applicable.



3.5 MEASUREMENT UNCERTAINTY

Head SAR Measurements.

Source of Uncertainty	Description	Tolerance / Uncertainty $\pm$ %	Probability distribution	Div	c_i (1g)	Standard Uncertainty $\pm$ % (1g)	V_i or V_{eff}
<i>Measurement System</i>							
Probe calibration	7.2.1	8.73	N	1	1	8.73	∞
Isotropy	7.2.1.2	3.18	R	1.73	1	1.84	∞
Probe angle >30deg	additional	12.00	R	1.73	1	6.93	∞
Boundary effect	7.2.1.5	0.49	R	1.73	1	0.28	∞
Linearity	7.2.1.3	1.00	R	1.73	1	0.58	∞
Detection limits	7.2.1.4	0.00	R	1.73	1	0.00	∞
Readout electronics	7.2.1.6	0.30	N	1	1	0.30	∞
Response time	7.2.1.7	0.00	R	1.73	1	0.00	∞
Integration time (equiv.)	7.2.1.8	1.38	R	1.73	1	0.80	∞
RF ambient conditions	7.2.3.6	3.00	R	1.73	1	1.73	∞
Probe positioner mech. restrictions	7.2.2.1	5.35	R	1.73	1	3.09	∞
Probe positioning with respect to phantom shell	7.2.2.3	5.00	R	1.73	1	2.89	∞
Post-processing	7.2.4	7.00	R	1.73	1	4.04	∞
<i>Test sample related</i>							
Test sample positioning	7.2.2.4	1.50	R	1.73	1	0.87	∞
Device holder uncertainty	7.2.2.4.2	1.73	R	1.73	1	1.00	∞
Drift of output power	7.2.3.4	-2.59	R	1.73	1	-1.50	∞
<i>Phantom and set-up</i>							
Phantom uncertainty (shape and thickness tolerances)	7.2.2.2	2.01	R	1.73	1	1.16	∞
Liquid conductivity (target)	7.2.3.3	5.00	R	1.73	0.64	1.85	∞
Liquid conductivity (meas.)	7.2.3.3	5.00	N	1	0.64	3.20	∞
Liquid permittivity (target)	7.2.3.4	5.00	R	1.73	0.6	1.73	∞
Liquid permittivity (meas.)	7.2.3.4	3.00	N	1	0.6	1.80	∞
Combined standard uncertainty			RSS			13.83	
Expanded uncertainty (95% confidence interval)			K=2			27.65	



Body SAR Measurements.

Source of Uncertainty	Description	Tolerance / Uncertainty $\pm$ %	Probability distribution	Div	c_i (1g)	Standard Uncertainty $\pm$ % (1g)	V_i or V_{eff}
<i>Measurement System</i>							
Probe calibration	7.2.1	8.73	N	1	1	8.73	∞
Isotropy	7.2.1.2	3.18	R	1.73	1	1.84	∞
Boundary effect	7.2.1.5	0.49	R	1.73	1	0.28	∞
Linearity	7.2.1.3	1.00	R	1.73	1	0.58	∞
Detection limits	7.2.1.4	0.00	R	1.73	1	0.00	∞
Readout electronics	7.2.1.6	0.30	N	1	1	0.30	∞
Response time	7.2.1.7	0.00	R	1.73	1	0.00	∞
Integration time (equiv.)	7.2.1.8	1.38	R	1.73	1	0.80	∞
RF ambient conditions	7.2.3.6	3.00	R	1.73	1	1.73	∞
Probe positioner mech. restrictions	7.2.2.1	0.60	R	1.73	1	0.35	∞
Probe positioning with respect to phantom shell	7.2.2.3	2.00	R	1.73	1	1.15	∞
Post-processing	7.2.4	7.00	R	1.73	1	4.04	∞
<i>Test sample related</i>							
Test sample positioning	7.2.2.4	1.50	R	1.73	1	0.87	∞
Device holder uncertainty	7.2.2.4.2	1.73	R	1.73	1	1.00	∞
Drift of output power	7.2.3.4	9	R	1.73	1	2.89	∞
<i>Phantom and set-up</i>							
Phantom uncertainty (shape and thickness tolerances)	7.2.2.2	2.01	R	1.73	1	1.16	∞
Liquid conductivity (target)	7.2.3.3	5.00	R	1.73	0.64	1.85	∞
Liquid conductivity (meas.)	7.2.3.3	5.00	N	1	0.64	3.20	∞
Liquid permittivity (target)	7.2.3.4	5.00	R	1.73	0.6	1.73	∞
Liquid permittivity (meas.)	7.2.3.4	3.00	N	1	0.6	1.80	∞
Combined standard uncertainty			RSS			11.52	
Expanded uncertainty (95% confidence interval)			K=2			23.05	



Product Service

SECTION 4

PHOTOGRAPHS



4.1 TEST POSITIONAL PHOTOGRAPHS



Figure 26
Left Cheek Position




Figure 27
Left Cheek 15° Position



Figure 28
Right Cheek Position



Figure 29
Right Cheek 15° Position



Figure 30
Front View




Figure 31
Rear View



4.2 PHOTOGRAPHS OF EQUIPMENT UNDER TEST (EUT)



Figure 32
Front View with Simple Headset



Figure 33
Rear View



Product Service



Figure 34
Rear View Cover Removed



Product Service

SECTION 5

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

5.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD Product Service Limited

© 2012 TÜV SÜD Product Service Limited

ANNEX A

PROBE CALIBRATION REPORT



NATIONAL PHYSICAL LABORATORY

Teddington Middlesex UK TW11 0LW Telephone +44 20 8977 3222

Certificate of Calibration

SAR PROBE

IndexSAR

Model: IXP-050

Serial number: 0189

This certificate provides traceability of measurement to recognised national standards, and to the units of measurement realised at the National Physical Laboratory or other recognised national standards laboratories. This certificate may not be reproduced other than in full, unless permission for the publication of an approved extract has been obtained in writing from the Managing Director. It does not of itself impute to the subject of calibration any attributes beyond those shown by the data contained herein.

FOR: Indexsar Ltd.
Oakfield House
Cudworth Lane
Newdigate
Surrey
RH5 5BG

DESCRIPTION: An IndexSAR isotropic electric field probe for determining specific absorption rates (SAR) in dielectric liquids. The probe has three orthogonal sensors, and the output voltage of the sensors is converted to an optical signal by a meter unit containing an analogue to digital (AD) converter. Probe readings are obtained using software via the RS232 port. The probe was calibrated with IndexSAR amplifier model IXA-010 S/N 036 belonging to NPL.

IDENTIFICATION: The probe is marked with the manufacturer's serial number 0189

MEASUREMENTS COMPLETED ON: 23rd February 2011

PREVIOUS NPL CERTIFICATE: None

The reported uncertainty is based on a coverage factor $k = 2$, providing a level of confidence of approximately 95%

Reference : 2011020183-1

Date of Issue : 3rd March 2011

Checked by : *DJ Bennett*

Signed : *B. Loader*

Name : Mr B G Loader

Page 1 of 7

(Authorised Signatory)

on half of NPLML

NPLC01-0507

NATIONAL PHYSICAL LABORATORY

Continuation Sheet

MEASUREMENT PROCEDURE

For frequencies at or above 835 MHz, the calibration method is based on establishing a calculable specific absorption rate (SAR) using a matched waveguide cell [1]. The cell has a feed-section and a liquid-filled section separated by a matching window that is designed to minimise reflections at the interface. A TE₀₁ mode is launched into the waveguide by means of a N-type-to-waveguide adapter. The power delivered to the liquid is calculated from the forward power and reflection coefficient measured at the input to the cell. At the centre of the cross-section of the waveguide cell, the volume specific absorption rate (SAR^V) in the liquid as a function of distance from the window is given by

$$SAR^V = \frac{4(P_w)}{ab\delta} e^{-2Z/\delta} \quad (1)$$

where

- a = the larger cross-sectional dimension of the waveguide.
- b = the smaller cross-sectional dimension of the waveguide.
- δ = the skin depth for the liquid in the waveguide.
- Z = the distance of the probe's sensors from the liquid to matching window boundary.
- P_w = the power delivered to the liquid.

For frequencies below 835 MHz, the SAR in the liquid is established by measuring the rate of temperature rise in the liquid at the calibration point. In this case the SAR in the liquid is related to the temperature rise by

$$SAR = c \frac{dT}{dt} \quad (2)$$

where c is the specific heat of the liquid.

Liquids having the properties specified by SAR measurement standards [2, 3, 4] were used for the calibration. The value of δ for the liquid was obtained by measuring the electric field (E) at a number of distances from the matching window. The calibration was for continuous wave (CW) signals, and the axis of the probe was parallel to the direction of propagation of the incident field i.e. end-on to the incident radiation. The probe was rotated about its axis in 15-degree steps, and the ratio of the calibration factors for the three probe sensors X, Y, & Z were optimized to give the best axial isotropy.

Reference : 2011020183-1

Page 2 of 7

Date of Issue : 3rd March 2011

Checked by : 

Continuation Sheet

ENVIRONMENT

UNCERTAINTIES

This uncertainty is valid when the probe is used in a liquid with the same dielectric properties as those used for the calibration. No estimate is made for the long-term stability of the device calibrated or of the fluids used in the calibration.

RESULTS

These calibration factors are only correct when the values for sensitivity in free-space, diode compression and sensor offset from the tip of the probe, as set in the probe software, are the same as those given in Table 1 and 2.

Reference : 2011020183-1

Page 3 of 7

Date of Issue : 3rd March 2011

Checked by : 

NATIONAL PHYSICAL LABORATORY

Continuation Sheet

REFERENCES:

- [1] Pokovic, KT, T.Schmid and N.Kuster, "Robust set-up for Precise Calibration of E-field probes in Tissue Simulating Liquids at Mobile Phone Frequencies", Proceedings ICECOM 1997, pp 120 – 124, Dubrovnik, Croatia Oct 12-17, 1997.
- [2] British Standard BS EN 503361:2001. "Basic standard for the measurement of specific absorption rate related to human exposure to electromagnetic fields from mobile phones (300 MHz – 3 GHz)".
- [3] IEEE Standard 1528-2003 "Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".
- [4] Federal Communications Commission, FCC OET Bulletin 65, Supplement C, June 2001, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", David L. Means, Kwok W. Chan.

Reference : 2011020183-1

Page 4 of 7

Date of Issue : 3rd March 2011

Checked by : *A. Bennett*

NP 553000000

NATIONAL PHYSICAL LABORATORY

Continuation Sheet

Table 2
Sensitivity in Body Simulating Liquids.
SAR probe: IXP-050
S/N 0189

Probe settings for calibration						
Sensitivity in free-space ⁽¹⁾			Diode Compression ⁽²⁾		Sensor offset from tip of probe ⁽²⁾	
Lin X = 513.08 (V/m) ² /(V*200) Lin Y = 463.99 (V/m) ² /(V*200) Lin Z = 518.85 (V/m) ² /(V*200)			DCP _X = 20 (V*200) DCP _Y = 20 (V*200) DCP _Z = 20 (V*200)		2.7 mm	
Sensitivity in Body Simulating Liquid.						
Calibration frequency	Liquid Phantom ⁽³⁾		Calibration Factors for $E^2_{\text{Liquid}} / E^2_{\text{Air}}$			Axial Isotropy
(MHz)	ϵ' ⁽³⁾	σ ⁽³⁾ (Sm ⁻¹)	ConvF _X	ConvF _Y	ConvF _Z	(dB)
450	55.0	0.92	0.200	0.267	0.201	±0.03
835	56.5	0.99	0.223	0.294	0.234	±0.01
900	56.2	1.03	0.232	0.305	0.245	±0.01
1800	53.4	1.49	0.296	0.378	0.310	±0.02
1900	53.1	1.58	0.306	0.390	0.322	±0.02
2100	52.7	1.70	0.310	0.409	0.364	±0.02
2450	54.2	2.04	0.355	0.419	0.382	±0.03
2600	51.3	2.22	0.357	0.417	0.381	±0.03

Notes.

- ⁽¹⁾ Measured at 900 MHz
⁽²⁾ The manufacturer supplied these figures.
⁽³⁾ Measured at a temperature of 22 ± 1 °C.

Reference : 2011020183-1

Page 6 of 7

Date of Issue : 3rd March 2011

Checked by : 

NATIONAL PHYSICAL LABORATORY

Continuation Sheet

Table 3
Manufacturer's boundary correction factors for
IXP-050 probes

Frequency	Head Simulating Liquid		Body Simulating Liquid	
(MHz)	$f(0)$	d	$f(0)$	d
835	1.35	1.30	1.45	1.30
900	1.20	1.30	1.45	1.30
1800	1.15	1.40	1.10	1.40
1900	1.10	1.40	1.10	1.50
2100	0.90	1.60	0.90	1.70
2450	0.85	1.60	0.85	1.80

Reference : 2011020183-1

Page 7 of 7

Date of Issue : 3rd March 2011

Checked by : 

75915934-14