



FCC EMI TEST REPORT

FCC ID : APYHRO00275
Equipment : Smart phone
Brand Name : SHARP
Applicant : SHARP CORPORATION
2-13-1, Hachihonmatsu-lida, Higashi-hiroshima-shi,
Hiroshima pref. 739-0192, Japan
Manufacturer : SHARP CORPORATION
1 Takumi-Cho, Sakai-Ku, Sakai-Shi, Osaka 590-8522, Japan
Standard : FCC 47 CFR FCC Part 15 Subpart B

The product was received on Jul. 30, 2019 and testing was started from Aug. 09, 2019 and completed on Sep. 18, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1. General Description	5
1.1. Product Feature of Equipment Under Test	5
1.2. Modification of EUT	5
1.3. Test Location	5
1.4. Applicable Standards	5
2. Test Configuration of Equipment Under Test	6
2.1. Test Mode	6
2.2. Connection Diagram of Test System	7
2.3. Support Unit used in test configuration and system	7
2.4. EUT Operation Test Setup	8
3. Test Result	9
3.1. Test of AC Conducted Emission Measurement	9
3.2. Test of Radiated Emission Measurement	11
4. List of Measuring Equipment.....	13
5. Uncertainty of Evaluation	14
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Emission Test Result	
Appendix C. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FC973034	01	Initial issue of report	Sep. 18, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.107	AC Conducted Emission	Pass	Under limit 12.46 dB at 0.204 MHz
3.2	15.109	Radiated Emission	Pass	Under limit 6.72 dB at 210.630 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Dara Chiu

Report Producer: Tina Chuang

1. General Description

1.1. Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: ILA & IFA Antenna WLAN: IFA Antenna Bluetooth: IFA Antenna GPS/Glonass/BDS/Galileo: ILA Antenna NFC: Loop Antenna

1.2. Modification of EUT

No modifications are made to the EUT during all test items.

1.3. Test Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	CO05-HY	03CH06-HY

FCC Designation No.: TW1093

1.4. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Camera (Front) + Earphone + USB Cable (Charging from Adapter)
	Mode 2: WCDMA Band V Idle + Bluetooth Link + WLAN (5GHz) Link + Camera (Rear) + Earphone + USB Cable (Charging from Adapter)
	Mode 3: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG4 + Earphone + USB Cable (Charging from Adapter)
	Mode 4: LTE Band 12 Idle + Bluetooth Idle + WLAN (5GHz) Idle + GPS Rx + Earphone + USB Cable (Charging from Adapter)
	Mode 5: LTE Band 17 Idle + Bluetooth Idle + WLAN (5GHz) Idle + NFC On + Earphone + USB Cable (Data Link with Notebook)
Radiated Emissions	Mode 1: GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Camera (Front) + Earphone + USB Cable (Charging from Adapter)
	Mode 2: WCDMA Band V Idle + Bluetooth Link + WLAN (5GHz) Link + Camera (Rear) + Earphone + USB Cable (Charging from Adapter)
	Mode 3: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG4 + Earphone + USB Cable (Charging from Adapter)
	Mode 4: LTE Band 12 Idle + Bluetooth Idle + WLAN (5GHz) Idle + GPS Rx + Earphone + USB Cable (Charging from Adapter)
	Mode 5: LTE Band 17 Idle + Bluetooth Idle + WLAN (5GHz) Idle + NFC On + Earphone + USB Cable (Data Link with Notebook)
Remark: 1. The worst case of AC is mode 1; only the test data of this mode was reported. 2. The worst case of RE is mode 5; only the test data of this mode was reported. 3. Data Linking with Notebook means data application transferred mode between EUT and Notebook.	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
3.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
5.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
6.	WLAN AP	ASUS	RT-AC1750	MSQ-RTAC66U	N/A	Unshielded, 1.8m
7.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
8.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
9.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
10.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
11.	Earphone	SHARP	N/A	FCC DoC	Unshielded, 1.2m	N/A
12.	Earphone	Sharp	RPHOE A007 AFZZ	AB-HI02JS	Unshielded, 1.2m	N/A
13.	Adapter	SHARP	N/A	N/A	N/A	N/A
14.	USB Cable	SHARP	N/A	N/A	Unshielded, 1m	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized with the BCCH, and had been continuous receiving mode by setting paging reorganization of the system simulator.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP or Notebook, and the following programs installed in the EUT were programmed during the test:

1. Data application is transferred between Laptop and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive continuous signals from GPS station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.
5. Turn on NFC function.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission

Please refer to Appendix B.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 12, 2019~ Aug. 13, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Aug. 12, 2019~ Aug. 13, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Aug. 12, 2019~ Aug. 13, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Aug. 12, 2019~ Aug. 13, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Aug. 12, 2019~ Aug. 13, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Aug. 12, 2019~ Aug. 13, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Aug. 12, 2019~ Aug. 13, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Amplifier	SONOMA	310N	186713	9kHz~1GHz	May 01, 2019	Sep. 18, 2019	Apr. 30, 2020	Radiation (03CH06-HY)
Bilog Antenna	Schaffner	CBL 6111C & N-6-06	2725 & AT-N0601	30MHz~1GHz	Jan. 10, 2019	Aug. 09, 2019	Jan. 09, 2020	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 08, 2019	Aug. 09, 2019	Jan. 07, 2020	Radiation (03CH06-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1156	1GHz~18GHz	Aug. 24, 2018	Aug. 09, 2019	Aug. 23, 2019	Radiation (03CH06-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1850117	1GHz~18GHz	May 23, 2019	Aug. 09, 2019	May 22, 2020	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF78020821 2	1m~4m	N/A	Aug. 09, 2019	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0-360 degree	N/A	Aug. 09, 2019	N/A	Radiation (03CH06-HY)
Test Software	AUDIX	e3	6.2009-8-24(k 5)	N/A	N/A	Aug. 09, 2019	N/A	Radiation (03CH06-HY)
RF Cable	HUBER+SUHNER/WOKEN/ HARBOUR INDUSTRIES	SUCOFLEX 104 /STORM/LL14 2	MY24966/4/ 00100A1O2A 178T/ CA3601-3601 -1000	30MHz-26GHz	Nov. 22, 2018	Aug. 09, 2019	Nov. 21, 2019	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 08, 2019	Sep. 18, 2019	Jan. 07, 2020	Radiation (03CH06-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1156	1GHz~18GHz	Aug. 30, 2019	Sep. 18, 2019	Aug. 29, 2020	Radiation (03CH06-HY)
Preamplifier	MITEQ	00101800-30-1 0P	1850117	1GHz~18GHz	May 23, 2019	Sep. 18, 2019	May 22, 2020	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF78020821 2	1m~4m	N/A	Sep. 18, 2019	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0-360 degree	N/A	Sep. 18, 2019	N/A	Radiation (03CH06-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Sep. 18, 2019	N/A	Radiation (03CH06-HY)
RF Cable	HUBER+SUHNER/WOKEN/ HARBOUR INDUSTRIES	SUCOFLEX 104 /STORM/LL14 2	MY24966/4/ 00100A1O2A 178T/ CA3601-3601 -1000	30MHz-26GHz	Nov. 22, 2018	Sep. 18, 2019	Nov. 21, 2019	Radiation (03CH06-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
--	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.9
--	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7
--	-----




Appendix A. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	23.0~24.7°C
		Relative Humidity :	58.9~64.7%

EUT Information

Report NO : 973034
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	31.51	55.63	24.12	L1	OFF	19.4
0.156750	42.43	---	65.63	23.20	L1	OFF	19.4
0.204000	---	37.80	53.45	15.65	L1	OFF	19.4
0.204000	50.99	---	63.45	12.46	L1	OFF	19.4
0.210750	---	33.25	53.18	19.93	L1	OFF	19.4
0.210750	48.58	---	63.18	14.60	L1	OFF	19.4
0.332250	---	30.52	49.40	18.88	L1	OFF	19.4
0.332250	42.08	---	59.40	17.32	L1	OFF	19.4
0.413250	---	31.18	47.58	16.40	L1	OFF	19.4
0.413250	40.36	---	57.58	17.22	L1	OFF	19.4
0.543750	---	29.68	46.00	16.32	L1	OFF	19.4
0.543750	38.67	---	56.00	17.33	L1	OFF	19.4
2.080500	---	26.69	46.00	19.31	L1	OFF	19.5
2.080500	33.17	---	56.00	22.83	L1	OFF	19.5
4.938000	---	29.27	46.00	16.73	L1	OFF	19.6
4.938000	35.29	---	56.00	20.71	L1	OFF	19.6
9.181500	---	30.05	50.00	19.95	L1	OFF	19.8
9.181500	36.84	---	60.00	23.16	L1	OFF	19.8
15.650250	---	28.81	50.00	21.19	L1	OFF	20.0
15.650250	36.27	---	60.00	23.73	L1	OFF	20.0

EUT Information

Report NO : 973034
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.199500	---	34.10	53.63	19.53	N	OFF	19.5
0.199500	47.07	---	63.63	16.56	N	OFF	19.5
0.330000	---	27.89	49.45	21.56	N	OFF	19.5
0.330000	37.60	---	59.45	21.85	N	OFF	19.5
0.665250	---	25.89	46.00	20.11	N	OFF	19.5
0.665250	31.54	---	56.00	24.46	N	OFF	19.5
1.306500	---	24.11	46.00	21.89	N	OFF	19.5
1.306500	27.48	---	56.00	28.52	N	OFF	19.5
5.282250	---	28.29	50.00	21.71	N	OFF	19.7
5.282250	32.88	---	60.00	27.12	N	OFF	19.7
15.317250	---	26.98	50.00	23.02	N	OFF	20.1
15.317250	31.83	---	60.00	28.17	N	OFF	20.1
23.687250	---	25.02	50.00	24.98	N	OFF	20.4
23.687250	26.09	---	60.00	33.91	N	OFF	20.4



Appendix B. Radiated Emission Test Result

Test Engineer :	You Xina Chen, Nick Yu	Temperature :	23~27°C
		Relative Humidity :	40~50%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH06-HY
Condition : FCC CLASS-B 3m 9120D_1156_180824 HORIZONTAL
Project : 973034
Power : From System
Memo : Mode 5
: SD to NB

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	159.87	33.44	-10.06	43.50	46.81	16.80	1.43	31.60	---	---	Peak
2	210.63	36.78	-6.72	43.50	50.62	16.10	1.62	31.56	100	0	Peak
3	291.63	35.49	-10.51	46.00	45.59	19.40	2.04	31.54	---	---	Peak
4	380.50	37.16	-8.84	46.00	45.10	21.40	2.30	31.64	---	---	Peak
5	502.30	30.54	-15.46	46.00	35.76	23.94	2.66	31.82	---	---	Peak
6 *	740.30	52.50			53.58	27.40	3.32	31.80	---	---	Peak
7	911.80	30.79	-15.21	46.00	29.23	29.04	3.74	31.22	---	---	Peak
8	1330.00	41.34	-32.66	74.00	70.47	26.03	4.77	59.93	---	---	Peak
9	3385.00	40.87	-33.13	74.00	64.52	28.13	7.78	59.56	---	---	Peak
10	5905.00	42.69	-31.31	74.00	55.19	32.47	11.10	56.07	---	---	Peak
11	6658.00	47.02	-26.98	74.00	56.70	34.30	12.93	56.91	---	---	Peak
12	10949.00	47.20	-26.80	74.00	50.07	40.45	15.12	58.44	---	---	Peak
13	12482.00	48.65	-25.35	74.00	51.02	38.40	16.36	57.13	100	0	Peak



Test Engineer :	You Xina Chen, Nick Yu	Temperature :	23~27°C
		Relative Humidity :	40~50%
Test Distance :	3m	Polarization :	Vertical
Remark :	#4 is system simulator signal which can be ignored.		



Site : 03CH06-HY
Condition : FCC CLASS-B 3m 9120B_1156_180824 VERTICAL
Project : 973034
Power : From System
Memo : Mode 5
: SD to NB

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	46.47	32.58	-7.42	40.00	46.86	16.50	0.84	31.62	100	0 Peak
2	154.20	35.85	-7.65	43.50	48.83	17.20	1.43	31.61	---	---
3	208.74	33.55	-9.95	43.50	47.39	16.10	1.62	31.56	---	---
4 *	740.30	52.82			53.90	27.40	3.32	31.80	---	---
5	832.00	29.91	-16.09	46.00	29.79	28.14	3.55	31.57	---	---
6	931.40	30.01	-15.99	46.00	27.74	29.52	3.79	31.04	---	---
7	955.90	30.61	-15.39	46.00	28.02	29.42	3.98	30.81	---	---
8	1645.00	40.28	-33.72	74.00	69.23	25.30	5.35	59.60	---	---
9	3125.00	42.92	-31.08	74.00	66.02	28.85	7.48	59.43	---	---
10	5140.00	41.53	-32.47	74.00	58.79	31.80	9.78	58.84	---	---
11	6637.00	47.01	-26.99	74.00	56.81	34.30	12.75	56.85	---	---
12	10928.00	46.83	-27.17	74.00	49.76	40.43	15.12	58.48	---	---
13	12601.00	47.95	-26.05	74.00	50.18	38.60	16.51	57.34	100	0 Peak