



FCC RADIO TEST REPORT

FCC ID : APYHRO00335
Equipment : Smart phone
Brand Name : SHARP
Model Name : APYHRO00335
Applicant : SHARP CORPORATION
1 Takumi-cho, Sakai-ku, Sakai City, Osaka 590-8522, Japan
Manufacturer : SHARP CORPORATION
1 Takumi-cho, Sakai-ku, Sakai City, Osaka 590-8522, Japan
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jan. 07, 2025 and testing was performed from Mar. 03, 2025 to Apr. 02, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	6
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment	22
5 Measurement Uncertainty	23
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR4D0637B	01	Initial issue of report	Apr. 23, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Ming Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs GSM/WCDMA/LTE/5G NR, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac, GNSS and NFC.		
Antenna Type Bluetooth: Loop Antenna		
Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	-2.51

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

Item	Sample 1		Sample 2		Sample 3	
	Vendor	Model Number	Vendor	Model Number	Vendor	Model Number
DDR	LONGSYS	SA0FLXC2012	Samsung	SA04UBE3010	LONGSYS	SA0FLXC2012
UFS2.2	LONGSYS	SA0N128G010	Samsung	SA02U1DC010	LONGSYS	SA064GC2010
Display	DJN	SLX3M066X00	CPT	SLX065WRX00	DJN	SLX3M066X00
Rear camera	Shinotech	S0CNN72B000	Union Image	S0C50A350A0	Union Image	S0C50A350A0
Front camera	Shinotech	S0CM8G1B060	Union Image	S0C50A350A0	Union Image	S0C50A350A0
Battery	SCUD	BPSX400001S	EVE	BPSX400002S	EVE	BPSX400002S
PCB	Tripod	SB0SX51BG0C	Compeq	SB0SX51BJ0C	Compeq	SB0SX51BJ0C
Accelerometer /Gyroscope	TDK	SA042670020	ST	SA0OETR3020	ST	SA0OETR3020
E-compass	QST	SA0C6308130	MEMSIC	SA0C56030A0	MEMSIC	SA0C56030A0
ALS/PS sensor	Sensortek	SA033562020	EMINENT	SA079911020	EMINENT	SA079911020
FPC_Side_Key	Sunflex	MESX514021A	PBH	MESX514001A	PBH	MESX514001A
FPC_USB	Sunflex	MESX114012A	PBH	MESX314004A	PBH	MESX314004A
FPC_AJ	Sunflex	MESX114013A	PBH	MESX314003A	PBH	MESX314003A
FPC_Main	Sunflex	MESX514002A	PBH	MESX514022A	PBH	MESX514022A
FPC_SPK	Sunflex	MESX514004A	AKM	MESX514024A	AKM	MESX514024A
FPC_flashlight	Sunflex	MESX514023A	PBH	MESX514003A	PBH	MESX514003A
Rear housing	LF	MESX561041A	DY	MESX561040A	LF	MESX561041A



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	TH05-HY, CO07-HY, 03CH16-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: Bluetooth Link + WLAN (2.4GHz) Link + Earphone + MPEG4 + USB Cable (Charging from Adapter) + Battery 2 for Sample 3
Remark: - For Radiated Test Cases, the tests were performed with Sample 3. - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. - The detailed Radiated test modes are shown in Appendix C.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
4.	Earphone + Mic	Samsung	Ecouteur	N/A	Unshielded 1.8m	N/A
5.	Earphone	NOKIA	WH-108	NA	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, make the EUT (SW:00.00.06A3040) get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Aug. 29, 2024	Mar. 21, 2025~ Apr. 01, 2025	Aug. 28, 2025	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Nov. 22, 2024	Mar. 21, 2025~ Apr. 01, 2025	Nov. 21, 2025	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N -06	47020 & 06	30MHz to 1GHz	Oct. 05, 2024	Mar. 21, 2025~ Apr. 01, 2025	Oct. 04, 2025	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1328	1G~18GHz	Dec. 06, 2024	Mar. 21, 2025~ Apr. 01, 2025	Dec. 05, 2025	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1GHz	Jul. 02, 2024	Mar. 21, 2025~ Apr. 01, 2025	Jul. 01, 2025	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 05, 2024	Mar. 21, 2025~ Apr. 01, 2025	Dec. 04, 2025	Radiation (03CH16-HY)
Preamplifier	EMEC	EM1G18G	060812	1GHz~18GHz	Dec. 24, 2024	Mar. 21, 2025~ Apr. 01, 2025	Dec. 23, 2025	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 27, 2024	Mar. 21, 2025~ Apr. 01, 2025	May 26, 2025	Radiation (03CH16-HY)
Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN17	1.53GHz Low Pass Filter	Jan. 14, 2025	Mar. 21, 2025~ Apr. 01, 2025	Jan. 13, 2026	Radiation (03CH16-HY)
Filter	Wainwright	WHKX12-2700 -3000-18000-6 OST	SN3	3GHz High Pass Filter	Jun. 28, 2024	Mar. 21, 2025~ Apr. 01, 2025	Jun. 27, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 22, 2024	Mar. 21, 2025~ Apr. 01, 2025	Apr. 21, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102/SUCOFLE X 104	EC-A5-300-5 757,805935/4 .802434/4	30MHz~18GHz	Aug. 07, 2024	Mar. 21, 2025~ Apr. 01, 2025	Aug. 06, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18-40GHz	Dec. 31, 2024	Mar. 21, 2025~ Apr. 01, 2025	Dec. 30, 2025	Radiation (03CH16-HY)
Software	Audix	E3 230621 V9	RK-002393	N/A	N/A	Mar. 21, 2025~ Apr. 01, 2025	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Mar. 21, 2025~ Apr. 01, 2025	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 21, 2025~ Apr. 01, 2025	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 21, 2025~ Apr. 01, 2025	N/A	Radiation (03CH16-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Apr. 02, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 02, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 23, 2024	Apr. 02, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Apr. 02, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Lisn	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 12, 2024	Apr. 02, 2025	Dec. 11, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	9kHz~30MHz	Mar. 24, 2025	Apr. 02, 2025	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Apr. 02, 2025	Sep. 22, 2025	Conduction (CO07-HY)
Hygrometer	TECEPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Mar. 03, 2025~ Mar. 31, 2025	Oct. 30, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Mar. 03, 2025~ Mar. 31, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	Mar. 03, 2025~ Mar. 31, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300484 (BOX3)	N/A	May 20, 2024	Mar. 03, 2025~ Mar. 31, 2025	May 19, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final version_25011 4	N/A	Conducted Other Test Item	N/A	Mar. 03, 2025~ Mar. 31, 2025	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sylvia Li	Temperature:	21~25	°C
Test Date:	2025/03/03~2025/03/31	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.033	0.706	0.50	Pass
BLE	1Mbps	1	19	2440	1.035	0.709	0.50	Pass
BLE	1Mbps	1	39	2480	1.033	0.704	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.30	30.00	-2.51	1.79	36.00	Pass
BLE	1Mbps	1	19	2440	4.90	30.00	-2.51	2.39	36.00	Pass
BLE	1Mbps	1	39	2480	4.70	30.00	-2.51	2.19	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	3.73	-10.71	-2.51	8.00	Pass
BLE	1Mbps	1	19	2440	4.18	-10.27	-2.51	8.00	Pass
BLE	1Mbps	1	39	2480	4.34	-10.10	-2.51	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.061	1.168	0.50	Pass
BLE	2Mbps	1	19	2440	2.065	1.170	0.50	Pass
BLE	2Mbps	1	39	2480	2.060	1.168	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	4.40	30.00	-2.51	1.89	36.00	Pass
BLE	2Mbps	1	19	2440	5.00	30.00	-2.51	2.49	36.00	Pass
BLE	2Mbps	1	39	2480	4.80	30.00	-2.51	2.29	36.00	Pass




TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	3.80	-12.54	-2.51	8.00	Pass
BLE	2Mbps	1	19	2440	4.19	-12.13	-2.51	8.00	Pass
BLE	2Mbps	1	39	2480	4.33	-12.00	-2.51	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**6dB Bandwidth**


<1Mbps>

6 dB Bandwidth Plot on Channel 0**6 dB Bandwidth Plot on Channel 19****6 dB Bandwidth Plot on Channel 39**




<2Mbps>


6 dB Bandwidth Plot on Channel 0



6 dB Bandwidth Plot on Channel 19






6 dB Bandwidth Plot on Channel 39



**99% Occupied Bandwidth**


<1Mbps>

99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**




<2Mbps>


99% Occupied Bandwidth Plot on Channel 0



99% Occupied Bandwidth Plot on Channel 19






99% Occupied Bandwidth Plot on Channel 39



**Power Spectral Density (dBm/3kHz)**


<1Mbps>

Power Density (dBm/3kHz) Plot Channel 0**Power Density (dBm/3kHz) Plot Channel 19****Power Density (dBm/3kHz) Plot Channel 39**




<2Mbps>


Power Density (dBm/3kHz) Plot Channel 0



Power Density (dBm/3kHz) Plot Channel 19







Power Density (dBm/3kHz) Plot Channel 39



**Band Edge and Conducted Spurious Emission**


<1Mbps>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~1GHz Plot****Spurious Emission 1GHz~26.5GHz Plot**




Channel 19

100kHz PSD reference Level Plot




Plot on Channel 19

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<2Mbps>






Channel 19

100kHz PSD reference Level Plot




Plot on Channel 19

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Howard Huang	Temperature :	21.2~24.5℃
		Relative Humidity :	50.4~58.2%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4D0637
Mode 1
120Vac/60Hz
Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.411000	---	29.43	47.63	18.20	L1	FLO	20.0
0.411000	39.21	---	57.63	18.42	L1	FLO	20.0
0.548250	---	27.21	46.00	18.79	L1	FLO	20.0
0.548250	37.35	---	56.00	18.65	L1	FLO	20.0
0.656250	---	17.33	46.00	28.67	L1	FLO	20.0
0.656250	35.82	---	56.00	20.18	L1	FLO	20.0
0.685500	---	18.82	46.00	27.18	L1	FLO	20.0
0.685500	37.06	---	56.00	18.94	L1	FLO	20.0
0.757500	---	17.15	46.00	28.85	L1	FLO	20.0
0.757500	32.76	---	56.00	23.24	L1	FLO	20.0
1.311000	---	18.78	46.00	27.22	L1	FLO	20.0
1.311000	35.56	---	56.00	20.44	L1	FLO	20.0
12.304500	---	19.41	50.00	30.59	L1	FLO	20.5
12.304500	23.31	---	60.00	36.69	L1	FLO	20.5

EUT Information

Report NO : 4D0637
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.408750	---	33.56	47.67	14.11	N	FLO	20.0
0.408750	40.86	---	57.67	16.81	N	FLO	20.0
0.550500	---	25.88	46.00	20.12	N	FLO	20.0
0.550500	36.30	---	56.00	19.70	N	FLO	20.0
0.654000	---	18.82	46.00	27.18	N	FLO	20.0
0.654000	38.37	---	56.00	17.63	N	FLO	20.0
0.683250	---	21.11	46.00	24.89	N	FLO	20.0
0.683250	39.63	---	56.00	16.37	N	FLO	20.0
1.308750	---	19.86	46.00	26.14	N	FLO	20.0
1.308750	36.38	---	56.00	19.62	N	FLO	20.0
4.263000	---	19.74	46.00	26.26	N	FLO	20.1
4.263000	26.28	---	56.00	29.72	N	FLO	20.1



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Jerry Lan, Gary Guo and Steven Wu	Temperature :	20~25°C
		Relative Humidity :	50~65%

Note symbol

-L	Low channel location
-R	High channel location



C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 5	2400-2483.5	4	Bluetooth-LE_GFSK	00	2402	1Mbps	-	-
Mode 6	2400-2483.5	4	Bluetooth-LE_GFSK	19	2440	1Mbps	-	-
Mode 7	2400-2483.5	4	Bluetooth-LE_GFSK	39	2480	1Mbps	-	-
Mode 8	2400-2483.5	4	Bluetooth-LE_GFSK	00	2402	2Mbps	-	-
Mode 9	2400-2483.5	4	Bluetooth-LE_GFSK	19	2440	2Mbps	-	-
Mode 10	2400-2483.5	4	Bluetooth-LE_GFSK	39	2480	2Mbps	-	-
Mode 11	2400-2483.5	4	Bluetooth-LE_GFSK	39	2480	2Mbps	-	LF



C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
5	Bluetooth-LE_GFSK	00	2388.66	47.08	54.00	-6.92	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	00	4804.00	39.07	74.00	-34.93	V	Peak	Pass	-	Harmonic
6	Bluetooth-LE_GFSK	19	2357.58	47.02	54.00	-6.98	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	19	7320.00	44.25	74.00	-29.75	V	Peak	Pass	-	Harmonic
7	Bluetooth-LE_GFSK	39	2493.74	46.99	54.00	-7.01	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	39	7440.00	44.18	74.00	-29.82	H	Peak	Pass	-	Harmonic
8	Bluetooth-LE_GFSK	00	2366.49	47.67	54.00	-6.33	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	00	4804.00	31.68	54.00	-22.32	V	Avg.	Pass	-	Harmonic
9	Bluetooth-LE_GFSK	19	2315.85	47.87	54.00	-6.13	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	19	7320.00	44.74	74.00	-29.26	H	Peak	Pass	-	Harmonic
10	Bluetooth-LE_GFSK	39	2483.62	50.75	54.00	-3.25	H	Avg.	Pass	-	Band Edge







Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
10	Bluetooth-LE_GFSK	39	7440.00	44.17	74.00	-29.83	H	Peak	Pass	-	Harmonic
11	LF	39	74.62	33.23	40.00	-6.77	V	Peak	Pass	-	LF





Mode	5																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																																																																			
ANT	4																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2315.24</td><td>56.91</td><td>74.00</td><td>-17.09</td><td>41.76</td><td>28.00</td><td>7.59</td><td>30.36</td><td>9.92</td><td>100</td><td>113</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2315.24	56.91	74.00	-17.09	41.76	28.00	7.59	30.36	9.92	100	113	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>100.32</td><td>-----</td><td>-----</td><td>85.32</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>100</td><td>113</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	100.32	-----	-----	85.32	27.68	7.73	30.33	9.92	100	113	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2315.24	56.91	74.00	-17.09	41.76	28.00	7.59	30.36	9.92	100	113	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	100.32	-----	-----	85.32	27.68	7.73	30.33	9.92	100	113	PEAK																																																																																								
Avg	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2364.46</td><td>46.89</td><td>54.00</td><td>-7.11</td><td>31.83</td><td>27.81</td><td>7.67</td><td>30.34</td><td>9.92</td><td>100</td><td>113</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2364.46	46.89	54.00	-7.11	31.83	27.81	7.67	30.34	9.92	100	113	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>99.65</td><td>-----</td><td>-----</td><td>84.65</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>100</td><td>113</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	99.65	-----	-----	84.65	27.68	7.73	30.33	9.92	100	113	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2364.46	46.89	54.00	-7.11	31.83	27.81	7.67	30.34	9.92	100	113	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	99.65	-----	-----	84.65	27.68	7.73	30.33	9.92	100	113	AVERAGE																																																																																								







Mode	5																																																																																															
	Band Edge																																																																																															
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																																																															
ANT	4																																																																																															
Pol.	Vertical						Fundamental																																																																																									
Peak																																																																																																
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2374.31</td><td>56.55</td><td>74.00</td><td>-17.45</td><td>41.62</td><td>27.66</td><td>7.69</td><td>30.34</td><td>9.92</td><td>371</td><td>74 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2374.31	56.55	74.00	-17.45	41.62	27.66	7.69	30.34	9.92	371	74 PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>94.70</td><td>-----</td><td>-----</td><td>79.70</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>371</td><td>74 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	94.70	-----	-----	79.70	27.68	7.73	30.33	9.92	371
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2374.31	56.55	74.00	-17.45	41.62	27.66	7.69	30.34	9.92	371	74 PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2402.00	94.70	-----	-----	79.70	27.68	7.73	30.33	9.92	371	74 PEAK																																																																																					
Avg																																																																																																
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.66</td><td>47.08</td><td>54.00</td><td>-6.92</td><td>32.09</td><td>27.69</td><td>7.71</td><td>30.33</td><td>9.92</td><td>371</td><td>74 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.66	47.08	54.00	-6.92	32.09	27.69	7.71	30.33	9.92	371	74 AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>93.98</td><td>-----</td><td>-----</td><td>78.98</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>371</td><td>74 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	93.98	-----	-----	78.98	27.68	7.73	30.33	9.92	371
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2388.66	47.08	54.00	-6.92	32.09	27.69	7.71	30.33	9.92	371	74 AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2402.00	93.98	-----	-----	78.98	27.68	7.73	30.33	9.92	371	74 AVERAGE																																																																																					





Mode	5																																																						
	Harmonic																																																						
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																						
ANT	4																																																						
Pol.	Horizontal						Vertical																																																
Peak Avg																																																							
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL																																																
<table><tr><th rowspan="2"></th><th rowspan="2">Freq</th><th colspan="3">Limit</th><th rowspan="2">Read</th><th rowspan="2">Ant</th><th rowspan="2">Cable</th><th rowspan="2">Preamp</th><th rowspan="2">Aux</th><th rowspan="2">APos</th><th rowspan="2">TPos</th><th rowspan="2">Remark</th></tr><tr><th>Level</th><th>Line</th><th>Margin</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>38.95</td><td>74.00</td><td>-35.05</td><td>62.53</td><td>31.30</td><td>11.04</td><td>66.40</td><td>0.48</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Freq	Limit			Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Level	Line	Margin		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4804.00	38.95	74.00	-35.05	62.53	31.30	11.04	66.40	0.48	--	--	PEAK
	Freq	Limit			Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
		Level	Line	Margin																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	4804.00	38.95	74.00	-35.05	62.53	31.30	11.04	66.40	0.48	--	--	PEAK																																											







Mode	6																																																																																																		
	Band Edge - L																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																																		
ANT	4																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2327.81</td><td>56.67</td><td>74.00</td><td>-17.33</td><td>41.58</td><td>27.92</td><td>7.61</td><td>30.36</td><td>9.92</td><td>100</td><td>111</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2327.81	56.67	74.00	-17.33	41.58	27.92	7.61	30.36	9.92	100	111	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>99.36</td><td>-----</td><td>-----</td><td>84.46</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>100</td><td>111</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	99.36	-----	-----	84.46	27.50	7.79	30.31	9.92	100	111
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2327.81	56.67	74.00	-17.33	41.58	27.92	7.61	30.36	9.92	100	111	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2440.00	99.36	-----	-----	84.46	27.50	7.79	30.31	9.92	100	111	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2311.43</td><td>46.96</td><td>54.00</td><td>-7.04</td><td>31.82</td><td>28.00</td><td>7.58</td><td>30.36</td><td>9.92</td><td>100</td><td>111</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2311.43	46.96	54.00	-7.04	31.82	28.00	7.58	30.36	9.92	100	111	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>98.79</td><td>-----</td><td>-----</td><td>83.89</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>100</td><td>111</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	98.79	-----	-----	83.89	27.50	7.79	30.31	9.92	100	111
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2311.43	46.96	54.00	-7.04	31.82	28.00	7.58	30.36	9.92	100	111	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2440.00	98.79	-----	-----	83.89	27.50	7.79	30.31	9.92	100	111	AVERAGE																																																																																							



Mode	6																																																						
	Band Edge - R																																																						
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																						
ANT	4																																																						
Pol.	Horizontal						Fundamental																																																
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2490.88</td><td>56.35</td><td>74.00</td><td>-17.65</td><td>41.35</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>100</td><td>111</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2490.88	56.35	74.00	-17.65	41.35	27.50	7.87	30.29	9.92	100	111	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2490.88	56.35	74.00	-17.65	41.35	27.50	7.87	30.29	9.92	100	111	PEAK																																											
Avg	 Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.04</td><td>46.95</td><td>54.00</td><td>-7.05</td><td>31.96</td><td>27.50</td><td>7.86</td><td>30.29</td><td>9.92</td><td>100</td><td>111</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2487.04	46.95	54.00	-7.05	31.96	27.50	7.86	30.29	9.92	100	111	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2487.04	46.95	54.00	-7.05	31.96	27.50	7.86	30.29	9.92	100	111	AVERAGE																																											



Mode	6																																																																																																	
	Band Edge - L																																																																																																	
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																																	
ANT	4																																																																																																	
Pol.	Vertical						Fundamental																																																																																											
Peak																																																																																																		
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2321.31</td><td>56.57</td><td>74.00</td><td>-17.43</td><td>41.42</td><td>27.99</td><td>7.60</td><td>30.36</td><td>9.92</td><td>383</td><td>72</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2321.31	56.57	74.00	-17.43	41.42	27.99	7.60	30.36	9.92	383	72	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>96.41</td><td>-----</td><td>-----</td><td>81.51</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>383</td><td>72</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	96.41	-----	-----	81.51	27.50	7.79	30.31	9.92	383	72
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2321.31	56.57	74.00	-17.43	41.42	27.99	7.60	30.36	9.92	383	72	PEAK																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2440.00	96.41	-----	-----	81.51	27.50	7.79	30.31	9.92	383	72	PEAK																																																																																						
Avg																																																																																																		
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2357.58</td><td>47.02</td><td>54.00</td><td>-6.98</td><td>31.88</td><td>27.90</td><td>7.66</td><td>30.34</td><td>9.92</td><td>383</td><td>72</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2357.58	47.02	54.00	-6.98	31.88	27.90	7.66	30.34	9.92	383	72	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>95.78</td><td>-----</td><td>-----</td><td>80.88</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>383</td><td>72</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	95.78	-----	-----	80.88	27.50	7.79	30.31	9.92	383	72
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2357.58	47.02	54.00	-6.98	31.88	27.90	7.66	30.34	9.92	383	72	AVERAGE																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2440.00	95.78	-----	-----	80.88	27.50	7.79	30.31	9.92	383	72	AVERAGE																																																																																						



Mode	6																																																						
	Band Edge - R																																																						
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																						
ANT	4																																																						
Pol.	Vertical						Fundamental																																																
Peak	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2493.40</td><td>56.48</td><td>74.00</td><td>-17.52</td><td>41.48</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>383</td><td>72 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2493.40	56.48	74.00	-17.52	41.48	27.50	7.87	30.29	9.92	383	72 PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2493.40	56.48	74.00	-17.52	41.48	27.50	7.87	30.29	9.92	383	72 PEAK																																												
Avg	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2492.74</td><td>46.88</td><td>54.00</td><td>-7.12</td><td>31.88</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>383</td><td>72 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2492.74	46.88	54.00	-7.12	31.88	27.50	7.87	30.29	9.92	383	72 AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2492.74	46.88	54.00	-7.12	31.88	27.50	7.87	30.29	9.92	383	72 AVERAGE																																												



Mode	6																																																																	
	Harmonic																																																																	
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																	
ANT	4																																																																	
Pol.	Horizontal																																																																	
Peak Avg																																																																		
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4880.00</td><td>40.00</td><td>74.00</td><td>-34.00</td><td>63.49</td><td>31.30</td><td>11.05</td><td>66.34</td><td>0.50</td><td>--</td><td>--</td><td></td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>44.10</td><td>74.00</td><td>-29.90</td><td>59.57</td><td>36.56</td><td>13.29</td><td>65.76</td><td>0.44</td><td>--</td><td>--</td><td></td><td>PEAK</td></tr></table>												Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4880.00	40.00	74.00	-34.00	63.49	31.30	11.05	66.34	0.50	--	--		PEAK	2	7320.00	44.10	74.00	-29.90	59.57	36.56	13.29	65.76	0.44	--	--	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																						
1	4880.00	40.00	74.00	-34.00	63.49	31.30	11.05	66.34	0.50	--	--		PEAK																																																					
2	7320.00	44.10	74.00	-29.90	59.57	36.56	13.29	65.76	0.44	--	--		PEAK																																																					
Peak Avg																																																																		
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4880.00</td><td>38.32</td><td>74.00</td><td>-35.68</td><td>61.81</td><td>31.30</td><td>11.05</td><td>66.34</td><td>0.50</td><td>--</td><td>--</td><td></td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>44.25</td><td>74.00</td><td>-29.75</td><td>59.72</td><td>36.56</td><td>13.29</td><td>65.76</td><td>0.44</td><td>--</td><td>--</td><td></td><td>PEAK</td></tr></table>												Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4880.00	38.32	74.00	-35.68	61.81	31.30	11.05	66.34	0.50	--	--		PEAK	2	7320.00	44.25	74.00	-29.75	59.72	36.56	13.29	65.76	0.44	--	--	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																						
1	4880.00	38.32	74.00	-35.68	61.81	31.30	11.05	66.34	0.50	--	--		PEAK																																																					
2	7320.00	44.25	74.00	-29.75	59.72	36.56	13.29	65.76	0.44	--	--		PEAK																																																					





Mode	7																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																			
ANT	4																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2496.78</td><td>56.87</td><td>74.00</td><td>-17.13</td><td>41.86</td><td>27.50</td><td>7.88</td><td>30.29</td><td>9.92</td><td>200</td><td>224</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2496.78	56.87	74.00	-17.13	41.86	27.50	7.88	30.29	9.92	200	224	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>89.38</td><td>-----</td><td>-----</td><td>74.41</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>200</td><td>224</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	89.38	-----	-----	74.41	27.50	7.85	30.30	9.92	200	224	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2496.78	56.87	74.00	-17.13	41.86	27.50	7.88	30.29	9.92	200	224	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	89.38	-----	-----	74.41	27.50	7.85	30.30	9.92	200	224	PEAK																																																																																								
Avg	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2493.94</td><td>46.87</td><td>54.00</td><td>-7.13</td><td>31.86</td><td>27.50</td><td>7.88</td><td>30.29</td><td>9.92</td><td>200</td><td>224</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2493.94	46.87	54.00	-7.13	31.86	27.50	7.88	30.29	9.92	200	224	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>88.78</td><td>-----</td><td>-----</td><td>73.81</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>200</td><td>224</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	88.78	-----	-----	73.81	27.50	7.85	30.30	9.92	200	224	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2493.94	46.87	54.00	-7.13	31.86	27.50	7.88	30.29	9.92	200	224	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	88.78	-----	-----	73.81	27.50	7.85	30.30	9.92	200	224	AVERAGE																																																																																								







Mode	7																																																																									
	Band Edge																																																																									
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																									
ANT	4																																																																									
Pol.	Vertical	Fundamental																																																																								
Peak	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 7 Setting : Default Plane : X with accessory <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2499.64 56.72</td><td>74.00</td><td>-17.28</td><td>41.71</td><td>27.50</td><td>7.88</td><td>30.29</td><td>9.92</td><td>400 254 PEAK</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor				MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg									1 2499.64 56.72	74.00	-17.28	41.71	27.50	7.88	30.29	9.92	400 254 PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2480.00 90.95</td><td>-----</td><td>-----</td><td>75.98</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>400 254 PEAK</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor				MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg									1 2480.00 90.95	-----	-----	75.98	27.50	7.85	30.30	9.92	400 254 PEAK
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor																																																																					
MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg																																																																										
1 2499.64 56.72	74.00	-17.28	41.71	27.50	7.88	30.29	9.92	400 254 PEAK																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor																																																																					
MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg																																																																										
1 2480.00 90.95	-----	-----	75.98	27.50	7.85	30.30	9.92	400 254 PEAK																																																																		
Avg	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto Detector : PEAK Mode : 7 Setting : Default Plane : X with accessory <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2493.74 46.99</td><td>54.00</td><td>-7.01</td><td>31.98</td><td>27.50</td><td>7.88</td><td>30.29</td><td>9.92</td><td>400 254 AVERAGE</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor				MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg									1 2493.74 46.99	54.00	-7.01	31.98	27.50	7.88	30.29	9.92	400 254 AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:2.700kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2480.00 90.22</td><td>-----</td><td>-----</td><td>75.25</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>400 254 AVERAGE</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor				MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg									1 2480.00 90.22	-----	-----	75.25	27.50	7.85	30.30	9.92	400 254 AVERAGE
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor																																																																					
MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg																																																																										
1 2493.74 46.99	54.00	-7.01	31.98	27.50	7.88	30.29	9.92	400 254 AVERAGE																																																																		
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor																																																																					
MHz dBuV/m dBuV/m dB dB dB dB dB dB dB cm deg																																																																										
1 2480.00 90.22	-----	-----	75.25	27.50	7.85	30.30	9.92	400 254 AVERAGE																																																																		







Mode	7																																																																																																																									
	Harmonic																																																																																																																									
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																																									
ANT	4																																																																																																																									
Pol.	Horizontal						Vertical																																																																																																																			
Peak Avg	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>39.50</td><td>74.00</td><td>-34.50</td><td>62.72</td><td>31.46</td><td>11.06</td><td>66.27</td><td>0.53</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>44.18</td><td>74.00</td><td>-29.82</td><td>59.50</td><td>36.56</td><td>13.38</td><td>65.77</td><td>0.51</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	39.50	74.00	-34.50	62.72	31.46	11.06	66.27	0.53	--	PEAK	2	7440.00	44.18	74.00	-29.82	59.50	36.56	13.38	65.77	0.51	--	PEAK	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>40.45</td><td>74.00</td><td>-33.55</td><td>63.67</td><td>31.46</td><td>11.06</td><td>66.27</td><td>0.53</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>43.83</td><td>74.00</td><td>-30.17</td><td>59.15</td><td>36.56</td><td>13.38</td><td>65.77</td><td>0.51</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	40.45	74.00	-33.55	63.67	31.46	11.06	66.27	0.53	--	PEAK	2	7440.00	43.83	74.00	-30.17	59.15	36.56	13.38	65.77	0.51	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	4960.00	39.50	74.00	-34.50	62.72	31.46	11.06	66.27	0.53	--	PEAK																																																																																																															
2	7440.00	44.18	74.00	-29.82	59.50	36.56	13.38	65.77	0.51	--	PEAK																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	4960.00	40.45	74.00	-33.55	63.67	31.46	11.06	66.27	0.53	--	PEAK																																																																																																															
2	7440.00	43.83	74.00	-30.17	59.15	36.56	13.38	65.77	0.51	--	PEAK																																																																																																															





Mode	8																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																																																																		
ANT	4																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2333.74</td><td>56.87</td><td>74.00</td><td>-17.13</td><td>41.78</td><td>27.90</td><td>7.62</td><td>30.35</td><td>9.92</td><td>100</td><td>116</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2333.74	56.87	74.00	-17.13	41.78	27.90	7.62	30.35	9.92	100	116	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>100.40</td><td>-----</td><td>-----</td><td>85.40</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>100</td><td>116</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	100.40	-----	-----	85.40	27.68	7.73	30.33	9.92	100	116
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2333.74	56.87	74.00	-17.13	41.78	27.90	7.62	30.35	9.92	100	116	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	100.40	-----	-----	85.40	27.68	7.73	30.33	9.92	100	116	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2366.49</td><td>47.67</td><td>54.00</td><td>-6.33</td><td>32.65</td><td>27.77</td><td>7.67</td><td>30.34</td><td>9.92</td><td>100</td><td>116</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2366.49	47.67	54.00	-6.33	32.65	27.77	7.67	30.34	9.92	100	116	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>99.01</td><td>-----</td><td>-----</td><td>84.01</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>100</td><td>116</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	99.01	-----	-----	84.01	27.68	7.73	30.33	9.92	100	116
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2366.49	47.67	54.00	-6.33	32.65	27.77	7.67	30.34	9.92	100	116	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	99.01	-----	-----	84.01	27.68	7.73	30.33	9.92	100	116	AVERAGE																																																																																							







Mode	8																																																																																															
	Band Edge																																																																																															
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																																																															
ANT	4																																																																																															
Pol.	Vertical						Fundamental																																																																																									
Peak																																																																																																
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.17</td><td>56.95</td><td>74.00</td><td>-17.05</td><td>42.06</td><td>27.62</td><td>7.69</td><td>30.34</td><td>9.92</td><td>387</td><td>76 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2378.17	56.95	74.00	-17.05	42.06	27.62	7.69	30.34	9.92	387	76 PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>95.95</td><td>-----</td><td>-----</td><td>80.95</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>387</td><td>76 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	95.95	-----	-----	80.95	27.68	7.73	30.33	9.92	387
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2378.17	56.95	74.00	-17.05	42.06	27.62	7.69	30.34	9.92	387	76 PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2402.00	95.95	-----	-----	80.95	27.68	7.73	30.33	9.92	387	76 PEAK																																																																																					
Avg																																																																																																
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2329.78</td><td>47.61</td><td>54.00</td><td>-6.39</td><td>32.53</td><td>27.90</td><td>7.61</td><td>30.35</td><td>9.92</td><td>387</td><td>76 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2329.78	47.61	54.00	-6.39	32.53	27.90	7.61	30.35	9.92	387	76 AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>94.53</td><td>-----</td><td>-----</td><td>79.53</td><td>27.68</td><td>7.73</td><td>30.33</td><td>9.92</td><td>387</td><td>76 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	94.53	-----	-----	79.53	27.68	7.73	30.33	9.92	387
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2329.78	47.61	54.00	-6.39	32.53	27.90	7.61	30.35	9.92	387	76 AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2402.00	94.53	-----	-----	79.53	27.68	7.73	30.33	9.92	387	76 AVERAGE																																																																																					





Mode	8										
	Harmonic										
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz										
ANT	4										
Pol.	Horizontal					Vertical					
Peak Avg											
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL					Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL					
	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg
1	4804.00	38.93	74.00	-35.07	62.51	31.30	11.04	66.40	0.48	--	-- PEAK
2	7206.00	44.16	74.00	-29.84	60.12	36.24	13.21	65.75	0.34	--	-- PEAK
	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg
1	4804.00	40.12	74.00	-33.88	63.70	31.30	11.04	66.40	0.48	100	73 PEAK
2	4804.00	31.68	54.00	-22.32	55.26	31.30	11.04	66.40	0.48	100	73 AVERAGE
3	7206.00	45.14	74.00	-28.86	61.10	36.24	13.21	65.75	0.34	--	-- PEAK







Mode	9																																																																																																		
	Band Edge - L																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																																		
ANT	4																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2356.00</td><td>56.85</td><td>74.00</td><td>-17.15</td><td>41.71</td><td>27.90</td><td>7.66</td><td>30.34</td><td>9.92</td><td>100</td><td>111</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2356.00	56.85	74.00	-17.15	41.71	27.90	7.66	30.34	9.92	100	111	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>99.50</td><td>-----</td><td>-----</td><td>84.60</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>100</td><td>111</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	99.50	-----	-----	84.60	27.50	7.79	30.31	9.92	100	111
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2356.00	56.85	74.00	-17.15	41.71	27.90	7.66	30.34	9.92	100	111	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2440.00	99.50	-----	-----	84.60	27.50	7.79	30.31	9.92	100	111	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2315.85</td><td>47.87</td><td>54.00</td><td>-6.13</td><td>32.72</td><td>28.00</td><td>7.59</td><td>30.36</td><td>9.92</td><td>100</td><td>111</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2315.85	47.87	54.00	-6.13	32.72	28.00	7.59	30.36	9.92	100	111	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>98.13</td><td>-----</td><td>-----</td><td>83.23</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>100</td><td>111</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	98.13	-----	-----	83.23	27.50	7.79	30.31	9.92	100	111
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2315.85	47.87	54.00	-6.13	32.72	28.00	7.59	30.36	9.92	100	111	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2440.00	98.13	-----	-----	83.23	27.50	7.79	30.31	9.92	100	111	AVERAGE																																																																																							



Mode	9																																																						
	Band Edge - R																																																						
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																						
ANT	4																																																						
Pol.	Horizontal						Fundamental																																																
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2492.26</td><td>56.48</td><td>74.00</td><td>-17.52</td><td>41.48</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>100</td><td>111</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2492.26	56.48	74.00	-17.52	41.48	27.50	7.87	30.29	9.92	100	111	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																	
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																														
1	2492.26	56.48	74.00	-17.52	41.48	27.50	7.87	30.29	9.92	100	111	PEAK																																											
Avg	 Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBW:5.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2493.88</td><td>47.85</td><td>54.00</td><td>-6.15</td><td>32.84</td><td>27.50</td><td>7.88</td><td>30.29</td><td>9.92</td><td>100</td><td>111</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2493.88	47.85	54.00	-6.15	32.84	27.50	7.88	30.29	9.92	100	111	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																	
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																														
1	2493.88	47.85	54.00	-6.15	32.84	27.50	7.88	30.29	9.92	100	111	AVERAGE																																											





Mode	9																																																																																								
	Band Edge - L																																																																																								
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																								
ANT	4																																																																																								
Pol.	Vertical						Fundamental																																																																																		
Peak																																																																																									
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamplifier</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2327.55</td><td>56.36</td><td>74.00</td><td>-17.64</td><td>41.27</td><td>27.92</td><td>7.61</td><td>30.36</td><td>9.92</td><td>300</td><td>65</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2327.55	56.36	74.00	-17.64	41.27	27.92	7.61	30.36	9.92	300	65	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamplifier</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>95.66</td><td>-----</td><td>-----</td><td>80.76</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>300</td><td>65</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2440.00	95.66	-----	-----	80.76	27.50	7.79	30.31	9.92	300	65
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2327.55	56.36	74.00	-17.64	41.27	27.92	7.61	30.36	9.92	300	65	PEAK																																																																													
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2440.00	95.66	-----	-----	80.76	27.50	7.79	30.31	9.92	300	65	PEAK																																																																													
Avg																																																																																									
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamplifier</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2342.50</td><td>47.74</td><td>54.00</td><td>-6.26</td><td>32.64</td><td>27.90</td><td>7.63</td><td>30.35</td><td>9.92</td><td>300</td><td>65</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2342.50	47.74	54.00	-6.26	32.64	27.90	7.63	30.35	9.92	300	65	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamplifier</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>94.30</td><td>-----</td><td>-----</td><td>79.40</td><td>27.50</td><td>7.79</td><td>30.31</td><td>9.92</td><td>300</td><td>65</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2440.00	94.30	-----	-----	79.40	27.50	7.79	30.31	9.92	300	65
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2342.50	47.74	54.00	-6.26	32.64	27.90	7.63	30.35	9.92	300	65	AVERAGE																																																																													
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamplifier	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2440.00	94.30	-----	-----	79.40	27.50	7.79	30.31	9.92	300	65	AVERAGE																																																																													



Mode	9																																												
	Band Edge - R																																												
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																												
ANT	4																																												
Pol.	Vertical	Fundamental																																											
Peak	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.58</td><td>56.28</td><td>74.00</td><td>-17.72</td><td>41.28</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>300</td><td>65 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2487.58	56.28	74.00	-17.72	41.28	27.50	7.87	30.29	9.92	300	65 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																			
1	2487.58	56.28	74.00	-17.72	41.28	27.50	7.87	30.29	9.92	300	65 PEAK																																		
Avg	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBW:5.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2496.46</td><td>47.58</td><td>54.00</td><td>-6.42</td><td>32.57</td><td>27.50</td><td>7.88</td><td>30.29</td><td>9.92</td><td>300</td><td>65 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2496.46	47.58	54.00	-6.42	32.57	27.50	7.88	30.29	9.92	300	65 AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																			
1	2496.46	47.58	54.00	-6.42	32.57	27.50	7.88	30.29	9.92	300	65 AVERAGE																																		







Mode	9																																																																																																																																																
	Harmonic																																																																																																																																																
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																																																																																
ANT	4																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																										
Peak Avg																																																																																																																																																	
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL																																																																																																																																										
<table><tr><th></th><th></th><th>Limit</th><th></th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>39.29</td><td>74.00</td><td>-34.71</td><td>62.78</td><td>31.30</td><td>11.05</td><td>66.34</td><td>0.50</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>44.74</td><td>74.00</td><td>-29.26</td><td>60.21</td><td>36.56</td><td>13.29</td><td>65.76</td><td>0.44</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4880.00	39.29	74.00	-34.71	62.78	31.30	11.05	66.34	0.50	--	PEAK	2	7320.00	44.74	74.00	-29.26	60.21	36.56	13.29	65.76	0.44	--	PEAK	<table><tr><th></th><th></th><th>Limit</th><th></th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>39.52</td><td>74.00</td><td>-34.48</td><td>63.01</td><td>31.30</td><td>11.05</td><td>66.34</td><td>0.50</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>44.21</td><td>74.00</td><td>-29.79</td><td>59.68</td><td>36.56</td><td>13.29</td><td>65.76</td><td>0.44</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4880.00	39.52	74.00	-34.48	63.01	31.30	11.05	66.34	0.50	--	PEAK	2	7320.00	44.21	74.00	-29.79	59.68	36.56	13.29	65.76	0.44	--	PEAK
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																							
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																						
1	4880.00	39.29	74.00	-34.71	62.78	31.30	11.05	66.34	0.50	--	PEAK																																																																																																																																						
2	7320.00	44.74	74.00	-29.26	60.21	36.56	13.29	65.76	0.44	--	PEAK																																																																																																																																						
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																							
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																						
1	4880.00	39.52	74.00	-34.48	63.01	31.30	11.05	66.34	0.50	--	PEAK																																																																																																																																						
2	7320.00	44.21	74.00	-29.79	59.68	36.56	13.29	65.76	0.44	--	PEAK																																																																																																																																						





Mode	10																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																			
ANT	4																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.66</td><td>57.97</td><td>74.00</td><td>-16.03</td><td>42.99</td><td>27.50</td><td>7.86</td><td>30.30</td><td>9.92</td><td>141</td><td>108</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.66	57.97	74.00	-16.03	42.99	27.50	7.86	30.30	9.92	141	108	PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>99.51</td><td>-----</td><td>-----</td><td>84.54</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>141</td><td>108</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	99.51	-----	-----	84.54	27.50	7.85	30.30	9.92	141	108	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.66	57.97	74.00	-16.03	42.99	27.50	7.86	30.30	9.92	141	108	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	99.51	-----	-----	84.54	27.50	7.85	30.30	9.92	141	108	PEAK																																																																																								
Avg	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>50.75</td><td>54.00</td><td>-3.25</td><td>35.77</td><td>27.50</td><td>7.86</td><td>30.30</td><td>9.92</td><td>141</td><td>108</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.62	50.75	54.00	-3.25	35.77	27.50	7.86	30.30	9.92	141	108	AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 HORIZONTAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>98.12</td><td>-----</td><td>-----</td><td>83.15</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>141</td><td>108</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	98.12	-----	-----	83.15	27.50	7.85	30.30	9.92	141	108	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.62	50.75	54.00	-3.25	35.77	27.50	7.86	30.30	9.92	141	108	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	98.12	-----	-----	83.15	27.50	7.85	30.30	9.92	141	108	AVERAGE																																																																																								





Mode	10																																																																																																
	Band Edge																																																																																																
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																
ANT	4																																																																																																
Pol.	Vertical						Fundamental																																																																																										
Peak																																																																																																	
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2492.02</td><td>56.29</td><td>74.00</td><td>-17.71</td><td>41.29</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>377</td><td>79 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2492.02	56.29	74.00	-17.71	41.29	27.50	7.87	30.29	9.92	377	79 PEAK	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>96.06</td><td>-----</td><td>-----</td><td>81.09</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>377</td><td>79 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	96.06	-----	-----	81.09	27.50	7.85	30.30	9.92	377
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2492.02	56.29	74.00	-17.71	41.29	27.50	7.87	30.29	9.92	377	79 PEAK																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2480.00	96.06	-----	-----	81.09	27.50	7.85	30.30	9.92	377	79 PEAK																																																																																						
Avg																																																																																																	
	Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2489.26</td><td>47.62</td><td>54.00</td><td>-6.38</td><td>32.62</td><td>27.50</td><td>7.87</td><td>30.29</td><td>9.92</td><td>377</td><td>79 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2489.26	47.62	54.00	-6.38	32.62	27.50	7.87	30.29	9.92	377	79 AVERAGE	Site : 03CH16-HY Condition: AVG_54 3m 91200-1328_241206 VERTICAL : RBW:1000.000kHz VBN:5.600kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>94.64</td><td>-----</td><td>-----</td><td>79.67</td><td>27.50</td><td>7.85</td><td>30.30</td><td>9.92</td><td>377</td><td>79 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	94.64	-----	-----	79.67	27.50	7.85	30.30	9.92	377
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2489.26	47.62	54.00	-6.38	32.62	27.50	7.87	30.29	9.92	377	79 AVERAGE																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2480.00	94.64	-----	-----	79.67	27.50	7.85	30.30	9.92	377	79 AVERAGE																																																																																						



Mode	10																																																																																																																													
	Harmonic																																																																																																																													
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																							
Peak Avg	 Site : 03CH16-HY Condition: PEAK_74 3m 91280-1328_241206 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>39.40</td><td>74.00</td><td>-34.60</td><td>62.62</td><td>31.46</td><td>11.06</td><td>66.27</td><td>0.53</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>44.17</td><td>74.00</td><td>-29.83</td><td>59.49</td><td>36.56</td><td>13.38</td><td>65.77</td><td>0.51</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	39.40	74.00	-34.60	62.62	31.46	11.06	66.27	0.53	--	--	PEAK	2	7440.00	44.17	74.00	-29.83	59.49	36.56	13.38	65.77	0.51	--	--	PEAK	 Site : 03CH16-HY Condition: PEAK_74 3m 91280-1328_241206 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>39.45</td><td>74.00</td><td>-34.55</td><td>62.67</td><td>31.46</td><td>11.06</td><td>66.27</td><td>0.53</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>43.74</td><td>74.00</td><td>-30.26</td><td>59.06</td><td>36.56</td><td>13.38</td><td>65.77</td><td>0.51</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	39.45	74.00	-34.55	62.67	31.46	11.06	66.27	0.53	--	--	PEAK	2	7440.00	43.74	74.00	-30.26	59.06	36.56	13.38	65.77	0.51	--	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	4960.00	39.40	74.00	-34.60	62.62	31.46	11.06	66.27	0.53	--	--	PEAK																																																																																																																		
2	7440.00	44.17	74.00	-29.83	59.49	36.56	13.38	65.77	0.51	--	--	PEAK																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	4960.00	39.45	74.00	-34.55	62.67	31.46	11.06	66.27	0.53	--	--	PEAK																																																																																																																		
2	7440.00	43.74	74.00	-30.26	59.06	36.56	13.38	65.77	0.51	--	--	PEAK																																																																																																																		



Mode	11																																																																																																																																																																																					
	LF																																																																																																																																																																																					
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																																																																																																					
ANT	4																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																				
QP/ Peak	 Site : 03CH16-HY Condition: QP 3m CBL6111D&00002N1D01N-06_47020 & 06_241005 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>69.77</td><td>30.54</td><td>40.00</td><td>-9.46</td><td>49.01</td><td>12.54</td><td>1.31</td><td>32.37</td><td>0.05 -- -- Peak</td></tr><tr><td>2</td><td>110.51</td><td>34.27</td><td>43.50</td><td>-9.23</td><td>47.75</td><td>17.17</td><td>1.62</td><td>32.33</td><td>0.06 -- -- Peak</td></tr><tr><td>3</td><td>225.94</td><td>35.99</td><td>46.00</td><td>-10.01</td><td>50.15</td><td>15.95</td><td>2.33</td><td>32.51</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>273.47</td><td>27.47</td><td>46.00</td><td>-18.53</td><td>38.29</td><td>18.05</td><td>2.56</td><td>32.30</td><td>0.07 -- -- Peak</td></tr><tr><td>5</td><td>736.16</td><td>32.97</td><td>46.00</td><td>-13.03</td><td>32.55</td><td>28.16</td><td>4.22</td><td>32.10</td><td>0.14 -- -- Peak</td></tr><tr><td>6</td><td>948.59</td><td>32.38</td><td>46.00</td><td>-13.62</td><td>28.14</td><td>30.93</td><td>4.81</td><td>31.76</td><td>0.26 -- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	69.77	30.54	40.00	-9.46	49.01	12.54	1.31	32.37	0.05 -- -- Peak	2	110.51	34.27	43.50	-9.23	47.75	17.17	1.62	32.33	0.06 -- -- Peak	3	225.94	35.99	46.00	-10.01	50.15	15.95	2.33	32.51	0.07 -- -- Peak	4	273.47	27.47	46.00	-18.53	38.29	18.05	2.56	32.30	0.07 -- -- Peak	5	736.16	32.97	46.00	-13.03	32.55	28.16	4.22	32.10	0.14 -- -- Peak	6	948.59	32.38	46.00	-13.62	28.14	30.93	4.81	31.76	0.26 -- -- Peak	 Site : 03CH16-HY Condition: QP 3m CBL6111D&00002N1D01N-06_47020 & 06_241005 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>74.62</td><td>33.23</td><td>40.00</td><td>-6.77</td><td>51.13</td><td>13.11</td><td>1.36</td><td>32.43</td><td>0.06 -- -- Peak</td></tr><tr><td>2</td><td>104.69</td><td>34.61</td><td>43.50</td><td>-8.89</td><td>48.65</td><td>16.72</td><td>1.57</td><td>32.39</td><td>0.06 -- -- Peak</td></tr><tr><td>3</td><td>225.94</td><td>31.10</td><td>46.00</td><td>-14.90</td><td>45.26</td><td>15.95</td><td>2.33</td><td>32.51</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>326.82</td><td>29.57</td><td>46.00</td><td>-16.43</td><td>39.17</td><td>19.67</td><td>2.81</td><td>32.16</td><td>0.08 -- -- Peak</td></tr><tr><td>5</td><td>736.16</td><td>31.37</td><td>46.00</td><td>-14.63</td><td>30.95</td><td>28.16</td><td>4.22</td><td>32.10</td><td>0.14 -- -- Peak</td></tr><tr><td>6</td><td>902.03</td><td>33.72</td><td>46.00</td><td>-12.28</td><td>31.87</td><td>29.26</td><td>4.68</td><td>32.25</td><td>0.16 -- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	74.62	33.23	40.00	-6.77	51.13	13.11	1.36	32.43	0.06 -- -- Peak	2	104.69	34.61	43.50	-8.89	48.65	16.72	1.57	32.39	0.06 -- -- Peak	3	225.94	31.10	46.00	-14.90	45.26	15.95	2.33	32.51	0.07 -- -- Peak	4	326.82	29.57	46.00	-16.43	39.17	19.67	2.81	32.16	0.08 -- -- Peak	5	736.16	31.37	46.00	-14.63	30.95	28.16	4.22	32.10	0.14 -- -- Peak	6	902.03	33.72	46.00	-12.28	31.87	29.26	4.68	32.25	0.16 -- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	69.77	30.54	40.00	-9.46	49.01	12.54	1.31	32.37	0.05 -- -- Peak																																																																																																																																																																													
2	110.51	34.27	43.50	-9.23	47.75	17.17	1.62	32.33	0.06 -- -- Peak																																																																																																																																																																													
3	225.94	35.99	46.00	-10.01	50.15	15.95	2.33	32.51	0.07 -- -- Peak																																																																																																																																																																													
4	273.47	27.47	46.00	-18.53	38.29	18.05	2.56	32.30	0.07 -- -- Peak																																																																																																																																																																													
5	736.16	32.97	46.00	-13.03	32.55	28.16	4.22	32.10	0.14 -- -- Peak																																																																																																																																																																													
6	948.59	32.38	46.00	-13.62	28.14	30.93	4.81	31.76	0.26 -- -- Peak																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	74.62	33.23	40.00	-6.77	51.13	13.11	1.36	32.43	0.06 -- -- Peak																																																																																																																																																																													
2	104.69	34.61	43.50	-8.89	48.65	16.72	1.57	32.39	0.06 -- -- Peak																																																																																																																																																																													
3	225.94	31.10	46.00	-14.90	45.26	15.95	2.33	32.51	0.07 -- -- Peak																																																																																																																																																																													
4	326.82	29.57	46.00	-16.43	39.17	19.67	2.81	32.16	0.08 -- -- Peak																																																																																																																																																																													
5	736.16	31.37	46.00	-14.63	30.95	28.16	4.22	32.10	0.14 -- -- Peak																																																																																																																																																																													
6	902.03	33.72	46.00	-12.28	31.87	29.26	4.68	32.25	0.16 -- -- Peak																																																																																																																																																																													



Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	60.70	380	2.63	2.7kHz
Bluetooth - LE for 2Mbps	31.41	196	5.10	5.6KHz

