

Test Report No.: RF260330B007

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	SHARP CORPORATION
Address:	2-1-25, Kyutaromachi, Chuo-ku, Osaka city, Osaka 541-8522, JAPAN



Manufacturer or Supplier:	SHARP CORPORATION
Address:	2-1-25, Kyutaromachi, Chuo-ku, Osaka city, Osaka 541-8522, JAPAN
Product:	Smart Phone
Brand Name:	SHARP
FCC ID:	APYHRO00341
Date of tests:	Mar. 19, 2026 ~ Apr.28, 2026

The tests have been carried out according to the requirements of the following standard:

☒ FCC Part 15, Subpart C, Section 15.247

☒ ANSI C63.10-2020

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Carl Xie Engineer / Mobile Department	Approved by Simon Wang Manager / Mobile Department
 Date: Apr. 28, 2026	 Date: Apr. 28, 2026

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: RF260330B007

TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1 SUMMARY OF TEST RESULTS.....	6
1.1 MEASUREMENT UNCERTAINTY	7
2 GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	12
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	12
2.3 DUTY CYCLE OF TEST SIGNAL	17
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	17
2.5 DESCRIPTION OF SUPPORT UNITS	18
3 TEST TYPES AND RESULTS.....	19
3.1 CONDUCTED EMISSION MEASUREMENT	19
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	19
3.1.2 TEST INSTRUMENTS.....	19
3.1.3 TEST PROCEDURES	20
3.1.4 DEVIATION FROM TEST STANDARD	20
3.1.5 TEST SETUP	21
3.1.6 EUT OPERATING CONDITIONS	21
3.1.7 TEST RESULTS	22
3.2 RADIATED EMISSION MEASUREMENT	26
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	26
3.2.2 TEST INSTRUMENTS.....	27
3.2.3 TEST PROCEDURES	28
3.2.4 DEVIATION FROM TEST STANDARD	28
3.2.5 TEST SETUP	29
3.2.6 EUT OPERATING CONDITIONS	30
3.2.7 TEST RESULTS	30
3.3 6 DB BANDWIDTH MEASUREMENT	107
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	107
3.3.2 TEST INSTRUMENTS.....	107
3.3.3 TEST PROCEDURE.....	108

Test Report No.: RF260330B007

3.3.4	DEVIATION FROM TEST STANDARD	108
3.3.5	TEST SETUP	108
3.3.6	EUT OPERATING CONDITIONS	108
3.3.7	TEST RESULTS	108
3.4	CONDUCTED OUTPUT POWER.....	109
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	109
3.4.2	TEST SETUP	109
3.4.3	TEST INSTRUMENTS.....	109
3.4.4	TEST PROCEDURES	109
3.4.5	DEVIATION FROM TEST STANDARD	109
3.4.6	EUT OPERATING CONDITIONS	109
3.4.7	TEST RESULTS	110
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	110
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	110
3.5	POWER SPECTRAL DENSITY MEASUREMENT	111
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	111
3.5.2	TEST SETUP	111
3.5.3	TEST INSTRUMENTS.....	111
3.5.4	TEST PROCEDURE.....	111
3.5.5	DEVIATION FROM TEST STANDARD	111
3.5.6	EUT OPERATING CONDITION	111
3.5.7	TEST RESULTS	112
3.6	OUT OF BAND EMISSION MEASUREMENT	113
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	113
3.6.2	TEST SETUP	113
3.6.3	TEST INSTRUMENTS.....	113
3.6.4	TEST PROCEDURE.....	113
3.6.5	DEVIATION FROM TEST STANDARD	114
3.6.6	EUT OPERATING CONDITION	114
3.6.7	TEST RESULTS	114
3.7	ANTENNA REQUIREMENTS.....	115
3.7.1	STANDARD APPLICABLE	115
3.7.2	ANTENNA CONNECTED CONSTRUCTION	115
3.7.3	ANTENNA GAIN	115
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	115



Test Report No.: RF260330B007

5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	115
6	APPENDIX1	116
	WLAN 2.4G	116
7	APPENDIX 2 BLE	211
	BLE ANT7	235



Test Report No.: RF260330B007

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF260330B007	Original release	Apr.28, 2026



Test Report No.: RF260330B007

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.205 15.209	Radiated Emissions	Compliance
15.247(d)	Out of band Emission Measurement	Compliance
15.247(a)(2)	6dB bandwidth	Compliance
15.247(b)	Conducted Output power	Compliance
15.247(e)	Power Spectral Density	Compliance
15.203	Antenna Requirement	Compliance

*Test Lab Information Reference

Lab A:

BOOMWAVE TEST (SHENZHEN) CO., LTD.

Lab Address:

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th Road, Chiwan Community, Zhaoshang Street, Nanshan District, Shenzhen, Guangdong, P.R. CHINA

Accredited Test Lab Cert 7607.01


The FCC Site Registration No. is 646781; The Designation No. is CN1429.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Smart Phone
BRAND NAME	SHARP
NOMINAL VOLTAGE	4.0Vdc(adapter or host equipment) 3.92Vdc (Li-ion, battery)
MODULATION	DSSS, OFDM, OFDMA, GFSK
TRANSMISSION RATE	802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n: up to 400 Mbps 802.11ax: up to 688.2 Mbps 802.11be: up to 688.2 Mbps BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20/40)/ax(HE20/40)/be(EHT20/40) 2402-2480MHz for BT-LE(GFSK)
Resource Unit (RU)	Single RU: 26-tone, 52-tone,106-tone,242-tone,484-tone, 996-tone,2*996-tone Multi-RU (Small RU):52-tone + 26-tone, 106-tone + 26-tone Multi-RU (Large RU):484-tone + 242-tone
MAX. OUTPUT POWER	WLAN: 221.82 mW (Maximum) BT-LE: 9.93 mW (Maximum) RU WLAN: 304.09 mW (Maximum)
ANTENNA TYPE	ANT3: PIFA Antenna ANT7: PIFA Antenna
ANTENNA GAIN	☒ Provided by client
	ANT3: with -1.6dBi gain ANT7: with -4.5dBi gain
Beamforming Directional Gain:	N/A



Test Report No.: RF260330B007

HW VERSION	DVT
SW VERSION	A2270
I/O PORTS	Refer to user's manual
EXTREME TEMPERATURE	5~35°C
EXTREME VOLTAGE*	3.7V~4V

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	2TX /2RX
802.11g	2TX /2RX
802.11n(HT20)/ax(HE20)	2TX /2RX
802.11n(HT40)/ax(HE40)	2TX /2RX
802.11ax (20MHz RU 26/52/106/242)	2TX /2RX
802.11ax (40MHz RU 26/52/106/242/484)	2TX /2RX
802.11be(EHT20)	2TX /2RX
802.11be(EHT40)	2TX /2RX
802.11be(20MHz RU 26/52/106/242 MRU52+26/106+26)	2TX /2RX
802.11be(40MHz RU 26/52/106/242/484 MRU52+26/106+26/484+242)	2TX /2RX
BT_LE(1MHz)	2TX /2RX
BT_LE(2MHz)	2TX /2RX
BT_LE(S2)	2TX /2RX
BT_LE(S8)	2TX /2RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.

Test Report No.: RF260330B007

5. List of Accessory:

Battery Information	Battery Type	Li-Lon
	Manufacturer	EVE ENERGY CO., LTD
	Model Number	UBATIA330AFN2
	Capacity	Typical capacity : 5100mAh Rated capacity:4900mAh
	Nominal Voltage	3.92V



Test Report No.: RF260330B007

2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), 802.11ax20 (HE20); 802.11ax20 (RU 26/52/106/242):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), 802.11ax40 (HE40); 802.11ax 40(RU 26/52/106/242/484):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



Test Report No.: RF260330B007

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
BT-LE	0 to 39	39	GFSK	1.0



Test Report No.: RF260330B007

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax 40 (RU 26/52/106/242/484)	3 to 9	3,6,9	OFDMA	MCS0
802.11be(EHT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11be(EHT40)	3 to 9	3,6,9	OFDM	MCS0
802.11be(20MHz RU 26/52/106/242 MRU52+26/106+26)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11be(40MHz RU 26/52/106/242/484 MRU52+26/106+26/484+242)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

Test Report No.: RF260330B007

POWER LINE CONDUCTED EMISSION TEST

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11ax 20	1 to 11	1, 11	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

BANDEDGE MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1,11	OFDMA	MCS0
802.11ax 40 (RU 26/52/106/242/484)	3 to 9	3,9	OFDMA	MCS0
802.11be(EHT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11be(EHT40)	3 to 9	3,6,9	OFDM	MCS0
802.11be(20MHz RU 26/52/106/242 MRU52+26/106+26)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11be(40MHz RU 26/52/106/242/484 MRU52+26/106+26/484+242)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1,11	OFDMA	MCS0
802.11ax 40 (RU26/52/106/242/484)	3 to 9	3,9	OFDMA	MCS0
802.11be(EHT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11be(EHT40)	3 to 9	3,6,9	OFDM	MCS0
802.11be(20MHz RU 26/52/106/242 MRU52+26/106+26)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11be(40MHz RU 26/52/106/242/484 MRU52+26/106+26/484+242)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0



Test Report No.: RF260330B007

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 4V By DC Supply	Carl Xie
RE≥1G	23deg. C, 70%RH	DC 4V By DC Supply	Carl Xie
PLC	25deg. C, 52%RH	DC 4V By DC Supply	Carl Xie
APCM	25deg. C, 60%RH	DC 3.7V By DC Supply	Alan Yu



Test Report No.: RF260330B007

2.3 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix1 Of this test report.

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



Test Report No.: RF260330B007

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pulse limiter	SCHWARZBECK	VTSD 9561F	01579	2025/7/22	2026/7/21
ESR.EMI TEST RECEIVER	Rohde&SCHWARZ	ESR	101405	2025/6/30	2026/6/29
LISN	SCHWARZBECK	NSLK 8127	01216	2025/8/27	2026/8/26
Cable	Tonscend	/	/	2025/7/22	2026/7/21

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



Test Report No.: RF260330B007

3.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS

BLE


AC Power line Conducted Emission

A “reference path loss” Corr.(dB) is established and the $L_{\text{cable}} + \text{ATT} + \text{VDF}$ is the attenuation of “reference path loss”, and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr. (dB)}$$

Sample calculation: $(34.42\text{dB}\mu\text{V}) = (4.82\text{dB}\mu\text{V}) + (29.6\text{dB})$, the corresponding frequency is 0.24381MHz.





Test Report No.: RF260330B007

MEASUREMENT RESULT:

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	PmeaQuasiPeak (dBμV)	PmeaAverage (dBμV)
0.24381	34.42	---	61.97	27.55	N	29.60	4.82	---
0.35042	---	22.11	48.95	26.84	N	29.60	---	-7.49
0.62760	37.86	---	56.00	18.14	N	29.60	8.26	---
0.62760	---	30.20	46.00	15.80	N	29.60	---	0.60
1.56148	31.13	---	56.00	24.87	N	29.60	1.53	---
1.57427	---	23.97	46.00	22.03	L1	29.80	---	-5.83
2.12436	---	23.32	46.00	22.68	N	29.60	---	-6.28
2.13289	30.48	---	56.00	25.52	N	29.60	0.88	---
5.25861	---	20.66	50.00	29.34	N	29.70	---	-9.04
5.27141	25.58	---	60.00	34.42	N	29.70	-4.12	---
25.50971	25.27	---	60.00	34.73	L1	30.40	-5.13	---
27.53524	---	19.24	50.00	30.76	N	30.30	---	-11.06

Test Report No.: RF260330B007


WIFI

A “reference path loss” Corr.(dB) is established and the $L_{\text{cable}} + \text{ATT} + \text{VDF}$ is the attenuation of “reference path loss”, and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr. (dB)}$$

Sample calculation: $(39.6\text{dB}\mu\text{V}) = (10\text{dB}\mu\text{V}) + (29.6\text{dB})$, the corresponding frequency is 0.15MHz.





Test Report No.: RF260330B007

MEASUREMENT RESULT:

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	PmeaQuasiPeak (dBμV)	Pmea Average (dBμV)
0.20544	32.12	---	63.39	31.27	N	29.6	2.52	---
0.34616	---	20.89	49.05	28.16	L1	29.8	---	-8.91
0.61907	34.62	---	56.00	21.38	L1	29.8	4.82	---
0.62760	---	28.72	46.00	17.28	N	29.6	---	-0.88
1.48899	31.27	---	56.00	24.73	N	29.6	1.67	---
1.57854	---	23.36	46.00	22.64	L1	29.8	---	-6.44
2.12863	30.80	---	56.00	25.20	N	29.6	1.20	---
2.12863	---	22.96	46.00	23.04	L1	29.8	---	-6.84
5.63814	24.25	---	60.00	35.75	N	29.7	-5.45	---
5.67225	---	19.36	50.00	30.64	N	29.7	---	-10.34
25.17709	23.87	---	60.00	36.13	N	30.3	-6.43	---
26.93824	---	19.23	50.00	30.77	L1	30.5	---	-11.27

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



Test Report No.: RF260330B007

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	2025/7/3	2026/7/2
BiConiLog Antenna	ETS-LINDGREN	3143B	161965	2025/7/17	2026/7/16
Horn Antenna	SCHWARZBECK	BBHA9120D	3297	2025/9/27	2026/9/26
Horn Antenna	STEATITE	QWH-SL-18-40-K-SG QMS-00361	15433	2025/7/19	2026/7/18
Preamplifier	Tonscend	TPA184045	AP24L8060388	2025/7/3	2026/7/2
MXE EMI Receiver	keysight	N9038B	MY50018017	2025/7/1	2026/6/30
MXG Vector Signal Generator	Keysight	N5183B	MY59100137	2025/6/30	2026/6/29
Preamplifier	Tonscend	TPA001330	806JSAPO40804251015	2025/6/30	2026/6/29
Preamplifier	Tonscend	TPA011845	AP24L8060392	2025/6/30	2026/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927166	2025/6/30	2026/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927165	2025/6/30	2026/6/29
Active Receive Loop Antenna	SCHWARZBECK	FMZB 1519 B	00173	2025/6/30	2026/6/29
Temp. & Humi. Recorder	Kejian	HTC-01	157246	2025/7/2	2026/7/1
HIGH pass FILTER_1-18	EWT	EWT-57-0222	EWT-57-0222	2025/6/30	2026/6/29
HIGH pass FILTER_7-18	EWT	EWT-57-0223	EWT-57-0223	2025/6/30	2026/6/29
HIGH pass FILTER_3-18	EWT	EWT-57-0221	EWT-57-0221	2025/6/30	2026/6/29
DC~1GHz Lowpass Filter	EWT	EWT-56-0649	EWT-56-0649	2025/7/3	2026/7/2
Cable 1	N/A	N/A	N/A	2025/9/28	2026/9/27
Cable 2	N/A	N/A	N/A	2025/9/28	2026/9/27
Cable 3	N/A	N/A	N/A	2025/9/28	2026/9/27

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 646781; The Designation No. is CN1429.

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD


No deviation

3.2.5 TEST SETUP


<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

3.2.7 TEST RESULTS

Note 1: Both horizontal and vertical polarizations of the antenna are set to make the measurement.


Note 2: Three-axis equipment has been evaluated in test.

Note 3: The relevant tests have been performed in order to verify in which mode would have the worst features, the result show above is the worst case (Channel, Mode, Rate, Chain...).



Test Report No.: RF260330B007

Radiated Emission Band Edge for BLE




Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE 1Mbps)

Polarity: Vertical



Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE 1Mbps)

Polarity: Horizontal


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007




Carrier frequency (MHz): 2480

Channel No.:78

Test Mode: GFSK (LE 1Mbps)

Polarity: Vertical



Carrier frequency (MHz): 2480

Channel No.:78

Test Mode: GFSK (LE 1Mbps)

Polarity: Horizontal



Test Report No.: RF260330B007

Radiated Emission for BLE

After comparison, the worst case attitude is EUT lay down.

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result = $P_{mea} + A_{Rpl}$

Sample calculation: $(22.45 \text{ dB}\mu\text{V/m}) = (41.55 \text{ BuV}) + (-19.1 \text{ dB/m})$, the corresponding frequency is 30.582 MHz.

For GFSK (LE 1Mbps)

Channel No.: 0

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.582	22.45	-19.1	41.55	Vertical	40.0	17.55
76.851	16.97	-21.5	38.47	Vertical	40.0	23.03
107.843	22.44	-17.7	40.14	Vertical	43.5	21.06
190.39	26.53	-17.6	44.13	Vertical	43.5	16.97
549.581	15.30	-7.8	23.10	Vertical	46.0	30.70
900.43	19.07	-2.2	21.27	Vertical	46.0	26.93


Channel No.: 19

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.6305	21.43	-19.1	40.53	Vertical	40.0	18.57
69.5275	18.53	-19.6	38.13	Vertical	40.0	21.47
107.843	22.53	-17.7	40.23	Vertical	43.5	20.97
190.244	26.63	-17.6	44.23	Vertical	43.5	16.87
546.622	15.56	-7.8	23.36	Vertical	46.0	30.44
947.62	19.32	-1.8	21.12	Vertical	46.0	26.68

Test Report No.: RF260330B007

Channel No.:39

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.4365	21.33	-19.2	40.53	Vertical	40.0	18.67
69.285	17.20	-19.6	36.80	Vertical	40.0	22.80
107.843	22.59	-17.7	40.29	Vertical	43.5	20.91
190.05	17.65	-17.6	35.25	Vertical	43.5	25.85
548.368	15.35	-7.8	23.15	Vertical	46.0	30.65
774.912	18.21	-4.4	22.61	Vertical	46.0	27.79



Frequency Range: 9kHz -30MHz

Detector: QP mode

Note : The relevant tests have been performed in order to verify in which mode would have the worst features, the result show above is the worst case.




Test Report No.: RF260330B007

LE 1Mbps

Channel No.:0

Full Spectrum




Frequency Range: 30MHz-1000 MHz

Detector: QP mode

Modulation type: GFSK (LE)

Full Spectrum



Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode

BOOMWAVE TEST (SHENZHEN)
CO., LTD.


Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007

Modulation type: GFSK (LE)

Full Spectrum




Frequency Range: 3GHz-18GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE)

Full Spectrum



Frequency Range: 18GHz-26GHz

Detector: Av mode and PK mode


Modulation type: GFSK (LE)



Test Report No.: RF260330B007

Channel No.:19

Full Spectrum




Frequency Range: 30MHz-1000 MHz

Detector: QP mode

Modulation type: GFSK (LE)

Full Spectrum



Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode

BOOMWAVE TEST (SHENZHEN)
CO., LTD.


Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007

Modulation type: GFSK (LE)

Full Spectrum




Frequency Range: 3GHz-18GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE)

Full Spectrum



Frequency Range: 18GHz-26GHz


Detector: Av mode and PK mode

Modulation type: GFSK (LE)

Test Report No.: RF260330B007

Channel No.:39

Full Spectrum




Frequency Range: 30MHz-1000 MHz

Detector: QP mode

Modulation type: GFSK (LE)

Full Spectrum



Frequency Range: 1GHz-3GHz


Detector: Av mode and PK mode



Test Report No.: RF260330B007

Modulation type: GFSK (LE)

Full Spectrum




Frequency Range: 3GHz-18GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE)

Full Spectrum



Frequency Range: 18GHz-26GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE)

BOOMWAVE TEST (SHENZHEN)
CO., LTD.


Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007

Radiated Emission Band Edge for WIFI




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11b

Polarization : V



Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11b

Polarization : H


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11b

Polarization : V



Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11b

Polarization : H


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11g

Polarization : V




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11g

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11g

Polarization : V




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11g

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11n(HT20)

Polarization : V



Radiated Emission Band Edge


Channel No.:1

Test Mode: 802.11n(HT20)

Polarization : H



Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11n(HT20)

Polarization : V



Radiated Emission Band Edge


Channel No.:11

Test Mode: 802.11n(HT20)

Polarization : H



Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11ax(HE20)

Polarization : V




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11ax(HE20)

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : V




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11be(EHT20)

Polarization : V



Radiated Emission Band Edge


Channel No.:1

Test Mode: 802.11be(EHT20)

Polarization : H



Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11be(EHT20)

Polarization : V



Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11be(EHT20)

Polarization : H

Partial RU (Tone26)


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11ax(HE20)

Polarization : V




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11ax(HE20)

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : V




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11be(EHT20)

Polarization : V




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11be(EHT20)

Polarization : H

Test Report No.: RF260330B007




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11be(EHT20)

Polarization : V



Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11be(EHT20)

Polarization : H



Test Report No.: RF260330B007

Radiated Emission for WIFI

After comparison, the worst case attitude is EUT lay down.

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result = $P_{mea} + A_{Rpl}$

Sample calculation: $(18.28 \text{ dB}\mu\text{V/m}) = (37.08 \text{ dB}\mu\text{V}) + (-18.8 \text{ dB/m})$, the corresponding frequency is 30.5335 MHz.

For 802.11b Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.582	22.16	-19.1	41.26	Vertical	40	17.84
69.4305	18.73	-19.6	38.33	Vertical	40	21.27
107.8425	22.34	-17.7	40.04	Vertical	43.5	21.16
187.6735	15.29	-18	33.29	Vertical	43.5	28.21
544.1485	15.3	-7.9	23.2	Vertical	46	30.7
776.318	18.09	-4.4	22.49	Vertical	46	27.91

For 802.11g Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.6305	22.14	-19.1	41.24	Vertical	40	17.86
78.6455	17.81	-21.9	39.71	Vertical	40	22.19
107.891	22.82	-17.7	40.52	Vertical	43.5	20.68
191.0685	24.36	-17.5	41.86	Vertical	43.5	19.14
531.975	15.26	-8.2	23.46	Vertical	46	30.74
948.493	21.02	-1.8	22.82	Vertical	46	24.98



Test Report No.: RF260330B007

For 802.11n(HT20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.8245	21.78	-19	40.78	Vertical	40	18.22
69.5275	18.71	-19.6	38.31	Vertical	40	21.29
107.8425	22.5	-17.7	40.2	Vertical	43.5	21
191.602	24.42	-17.5	41.92	Vertical	43.5	19.08
539.0075	14.97	-8	22.97	Vertical	46	31.03
889.905	18.65	-2.4	21.05	Vertical	46	27.35

For 802.11ax(HE20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.7275	22.09	-19.10	41.19	Vertical	40.00	17.91
69.6245	18.86	-19.60	38.46	Vertical	40.00	21.14
107.8425	22.27	-17.70	39.97	Vertical	43.50	21.23
190.5835	23.43	-17.60	41.03	Vertical	43.50	20.07
490.7985	13.70	-9.20	22.90	Vertical	46.00	32.30
779.1795	18.16	-4.40	22.56	Vertical	46.00	27.84

For 802.11be(EHT20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.679	22.15	-19.10	41.25	Vertical	40.00	17.85
69.5275	18.82	-19.60	38.42	Vertical	40.00	21.18
107.8425	22.31	-17.70	40.01	Vertical	43.50	21.19
184.6665	19.13	-18.30	37.43	Vertical	43.50	24.37
542.839	15.19	-7.90	23.09	Vertical	46.00	30.81
913.5245	18.83	-2.10	20.93	Vertical	46.00	27.17

For 802.11b Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.6305	22.22	-19.10	41.32	Vertical	40.00	17.78
85.193	16.87	-20.70	37.57	Vertical	40.00	23.13

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007

107.8425	22.20	-17.70	39.90	Vertical	43.50	21.30
188.0615	23.96	-17.90	41.86	Vertical	43.50	19.54
550.405	15.05	-7.70	22.75	Vertical	46.00	30.95
938.696	19.23	-1.80	21.03	Vertical	46.00	26.77

For 802.11g Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.6305	22.19	-19.10	41.29	Vertical	40.00	17.81
69.6245	18.94	-19.60	38.54	Vertical	40.00	21.06
107.891	22.55	-17.70	40.25	Vertical	43.50	20.95
185.394	21.67	-18.20	39.87	Vertical	43.50	21.83
550.6475	14.94	-7.70	22.64	Vertical	46.00	31.06
955.4285	18.87	-1.80	20.67	Vertical	46.00	27.13

For 802.11n(HT20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.7275	22.08	-19.10	41.18	Vertical	40.00	17.92
69.479	18.67	-19.60	38.27	Vertical	40.00	21.33
107.8425	22.26	-17.70	39.96	Vertical	43.50	21.24
185.5395	21.84	-18.20	40.04	Vertical	43.50	21.66
550.0655	14.81	-7.80	22.61	Vertical	46.00	31.19
937.241	19.22	-1.90	21.12	Vertical	46.00	26.78

For 802.11ax(HE20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.6305	22.12	-19.10	41.22	Vertical	40.00	17.88
69.7215	18.83	-19.70	38.53	Vertical	40.00	21.17
107.891	22.56	-17.70	40.26	Vertical	43.50	20.94
186.5095	20.64	-18.10	38.74	Vertical	43.50	22.86
549.0955	14.81	-7.80	22.61	Vertical	46.00	31.19
898.053	18.60	-2.30	20.90	Vertical	46.00	27.40



Test Report No.: RF260330B007

For 802.11be(EHT20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.8245	21.81	-19.00	40.81	Vertical	40.00	18.19
78.7425	18.07	-22.00	40.07	Vertical	40.00	21.93
107.8425	21.95	-17.70	39.65	Vertical	43.50	21.55
185.782	22.63	-18.20	40.83	Vertical	43.50	20.87
532.9935	14.74	-8.20	22.94	Vertical	46.00	31.26
938.0655	19.10	-1.80	20.90	Vertical	46.00	26.90

For 802.11b Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.6305	21.92	-19.10	41.02	Vertical	40.00	18.08
69.479	18.50	-19.60	38.10	Vertical	40.00	21.50
107.8425	21.39	-17.70	39.09	Vertical	43.50	22.11
185.685	23.73	-18.20	41.93	Vertical	43.50	19.77
551.2295	14.80	-7.70	22.50	Vertical	46.00	31.20
780.78	19.07	-4.30	23.37	Vertical	46.00	26.93

For 802.11g Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.97	21.21	-19.00	40.21	Vertical	40.00	18.79
79.082	17.71	-22.00	39.71	Vertical	40.00	22.29
107.8425	21.95	-17.70	39.65	Vertical	43.50	21.55
188.983	18.64	-17.80	36.44	Vertical	43.50	24.86
530.7625	14.88	-8.20	23.08	Vertical	46.00	31.12
704.344	15.94	-5.50	21.44	Vertical	46.00	30.06

For 802.11n(HT20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.1455	20.24	-19.30	39.54	Vertical	40.00	19.76
69.673	18.88	-19.70	38.58	Vertical	40.00	21.12

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007

107.8425	22.15	-17.70	39.85	Vertical	43.50	21.35
186.267	24.17	-18.10	42.27	Vertical	43.50	19.33
536.437	14.69	-8.10	22.79	Vertical	46.00	31.31
941.8	18.89	-1.80	20.69	Vertical	46.00	27.11

For 802.11ax(HE20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.873	21.64	-19.00	40.64	Vertical	40.00	18.36
78.6455	18.05	-21.90	39.95	Vertical	40.00	21.95
107.8425	22.12	-17.70	39.82	Vertical	43.50	21.38
187.5765	19.86	-18.00	37.86	Vertical	43.50	23.64
554.7215	14.98	-7.60	22.58	Vertical	46.00	31.02
781.8955	18.83	-4.30	23.13	Vertical	46.00	27.17

For 802.11be(EHT20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.3395	21.48	-19.20	40.68	Vertical	40.00	18.52
69.673	18.95	-19.70	38.65	Vertical	40.00	21.05
107.891	22.43	-17.70	40.13	Vertical	43.50	21.07
187.6735	24.38	-18.00	42.38	Vertical	43.50	19.12
527.416	14.51	-8.30	22.81	Vertical	46.00	31.49
906.977	18.46	-2.20	20.66	Vertical	46.00	27.54

Partial RU (Tone26)

For 802.11ax(HE20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.388	21.49	-19.20	40.69	Vertical	40.00	18.51
69.479	18.53	-19.60	38.13	Vertical	40.00	21.47
107.8425	21.41	-17.70	39.11	Vertical	43.50	22.09
187.6735	24.14	-18.00	42.14	Vertical	43.50	19.36
545.1185	14.76	-7.80	22.56	Vertical	46.00	31.24
958.8235	18.49	-1.70	20.19	Vertical	46.00	27.51

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007

For 802.11ax(HE20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl(dB)	Pmea(dBuV/m)	Polarity	Limit(dBuV/m)	Margin(dB)
30.485	21.37	-19.10	40.47	Vertical	40.00	18.63
78.694	17.94	-21.90	39.84	Vertical	40.00	22.06
107.8425	22.20	-17.70	39.90	Vertical	43.50	21.30
187.334	18.94	-18.00	36.94	Vertical	43.50	24.56
528.871	14.68	-8.30	22.98	Vertical	46.00	31.32
936.95	19.26	-1.90	21.16	Vertical	46.00	26.74

For 802.11ax(HE20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl(dB)	Pmea(dBuV/m)	Polarity	Limit(dBuV/m)	Margin(dB)
30.291	20.96	-19.20	40.16	Vertical	40.00	19.04
69.0425	17.47	-19.50	36.97	Vertical	40.00	22.53
107.8425	22.20	-17.70	39.90	Vertical	43.50	21.30
191.311	15.05	-17.50	32.55	Vertical	43.50	28.45
545.943	14.72	-7.80	22.52	Vertical	46.00	31.28
935.98	18.94	-1.90	20.84	Vertical	46.00	27.06

For 802.11be(EHT20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl(dB)	Pmea(dBuV/m)	Polarity	Limit(dBuV/m)	Margin(dB)
30.776	21.66	-19.00	40.66	Vertical	40.00	18.34
69.3335	18.07	-19.60	37.67	Vertical	40.00	21.93
107.891	22.31	-17.70	40.01	Vertical	43.50	21.19
185.394	20.72	-18.20	38.92	Vertical	43.50	22.78
552.539	14.85	-7.70	22.55	Vertical	46.00	31.15
781.3135	19.06	-4.30	23.36	Vertical	46.00	26.94

For 802.11be(EHT20) Channel No.:6


Frequency(MHz)	Result(dBuV/m)	ARpl(dB)	Pmea(dBuV/m)	Polarity	Limit(dBuV/m)	Margin(dB)
30.485	21.67	-19.10	40.77	Vertical	40.00	18.33

Test Report No.: RF260330B007

69.7215	18.82	-19.70	38.52	Vertical	40.00	21.18
107.8425	22.17	-17.70	39.87	Vertical	43.50	21.33
185.394	21.08	-18.20	39.28	Vertical	43.50	22.42
546.8645	14.64	-7.80	22.44	Vertical	46.00	31.36
872.0085	17.85	-2.80	20.65	Vertical	46.00	28.15

For 802.11be(EHT20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
30.7275	21.81	-19.10	40.91	Vertical	40.00	18.19
69.576	18.76	-19.60	38.36	Vertical	40.00	21.24
107.8425	21.94	-17.70	39.64	Vertical	43.50	21.56
185.588	24.26	-18.20	42.46	Vertical	43.50	19.24
541.2385	14.74	-8.00	22.74	Vertical	46.00	31.26
781.2165	19.25	-4.30	23.55	Vertical	46.00	26.75



Frequency Range: 9kHz -30MHz

Detector: QP mode

Note : The relevant tests have been performed in order to verify in which mode would have the worst features, the result show above is the worst case.




Test Report No.: RF260330B007

Carrier frequency (MHz): 2412

Channel No.:1

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

BOOMWAVE TEST (SHENZHEN)
CO., LTD.


Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com



Test Report No.: RF260330B007


Modulation type: 802.11b



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11b



Frequency Range: 18GHz -26GHz

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA


Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11g

Full Spectrum




Frequency Range: 1GHz -3GHz



Test Report No.: RF260330B007

Detector: Av mode and PK mode


Modulation type: 802.11g



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11g



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA


Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007

Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11n(HT20)






Test Report No.: RF260330B007

Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com


Test Report No.: RF260330B007

Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum






Test Report No.: RF260330B007

Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com


Test Report No.: RF260330B007

Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11be(EHT20)

Full Spectrum






Test Report No.: RF260330B007

Frequency Range: 1GHz -3GHz
Detector: Av mode and PK mode
Modulation type: 802.11be(EHT20)


Full Spectrum



Frequency Range: 3GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11be(EHT20)

Test Report No.: RF260330B007

Full Spectrum



Frequency Range: 18GHz -26GHz


Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)

Carrier frequency (MHz): 2437

Channel No.:6

Full Spectrum



Frequency Range: 30MHz -1GHz


Detector: QP mode



Test Report No.: RF260330B007

Modulation type: 802.11b

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007


Modulation type: 802.11b



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11b




Frequency Range: 30MHz -1GHz

Test Report No.: RF260330B007


Detector: QP mode
Modulation type: 802.11g

Full Spectrum



Frequency Range: 1GHz -3GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum



Frequency Range: 3GHz -18GHz




Test Report No.: RF260330B007

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 30MHz -1GHz

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com




Test Report No.: RF260330B007

Detector: QP mode

Modulation type: 802.11n(HT20)

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 3GHz -18GHz

BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com




Test Report No.: RF260330B007

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com




Test Report No.: RF260330B007

Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum






Test Report No.: RF260330B007

Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com




Test Report No.: RF260330B007

Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11be(EHT20)

Full Spectrum




Frequency Range: 1GHz -3GHz


Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)

Test Report No.: RF260330B007



Frequency Range: 3GHz -18GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)



Frequency Range: 18GHz -26GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)




Test Report No.: RF260330B007

Carrier frequency (MHz): 2462

Channel No.:11

Full Spectrum




Frequency Range 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007


Modulation type: 802.11b



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11b




Frequency Range: 18GHz -26GHz

Test Report No.: RF260330B007

Detector: Av mode and PK mode


Modulation type: 802.11b



Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11g






Test Report No.: RF260330B007

Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11g



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com




Test Report No.: RF260330B007

Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11n(HT20)

Full Spectrum






Test Report No.: RF260330B007

Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com


Test Report No.: RF260330B007

Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Test Report No.: RF260330B007

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Test Report No.: RF260330B007

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Test Report No.: RF260330B007

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11be(EHT20)

Full Spectrum




Frequency Range: 1GHz -3GHz


Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)

Test Report No.: RF260330B007



Frequency Range: 3GHz -18GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)



Frequency Range: 18GHz -26GHz
 Detector: Av mode and PK mode



Test Report No.: RF260330B007


Modulation type: 802.11be(EHT20)

Partial RU (Tone26)

Carrier frequency (MHz): 2412

Channel No.:1

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com




Test Report No.: RF260330B007

Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Test Report No.: RF260330B007

Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode


Modulation type: 802.11be(EHT20)

Full Spectrum



Test Report No.: RF260330B007


Frequency Range: 1GHz -3GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)



Frequency Range: 3GHz -18GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)

Test Report No.: RF260330B007

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)




Test Report No.: RF260330B007

Carrier frequency (MHz): 2437

Channel No.:6

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007


Modulation type: 802.11 ax(HE20)



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Test Report No.: RF260330B007


Modulation type: 802.11 ax(HE20)



Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11be(EHT20)




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Test Report No.: RF260330B007

Modulation type: 802.11be(EHT20)

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)




Test Report No.: RF260330B007

Carrier frequency (MHz): 2462

Channel No.:11

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th
Road, Chiwan Community, Zhaoshang Street, Nanshan
District, Shenzhen, Guangdong, P.R. CHINA

Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260330B007


Modulation type: 802.11 ax(HE20)



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Test Report No.: RF260330B007

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11be(EHT20)

Full Spectrum




Frequency Range: 1GHz -3GHz


Detector: Av mode and PK mode

Modulation type: 802.11be(EHT20)

Test Report No.: RF260330B007



Frequency Range: 3GHz -18GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)



Frequency Range: 18GHz -26GHz
 Detector: Av mode and PK mode
 Modulation type: 802.11be(EHT20)



Test Report No.: RF260330B007

3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Wireless communication integrated tester	Rohde&Schwarz	CMW500	166205	2025/6/30	2026/6/29
MXA Signal Analyzer	KEYSIGHT	N9020B	MY60112669	2025/8/27	2026/8/26
WiFi 7GHz Band Extender	Tonscend	TS-WF7U2	806WF7U003305251003	2025/1/17	2026/1/16
RF Control Unit	Tonscend	JS0806-2	806JS2X020201251002	2025/1/17	2026/1/16
PSG Analog Signal Generator	Agilent	E8257D	MY51111397	2025/7/01	2026/6/30
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY61250150	2025/1/15	2026/1/14
DC Power Supply	AGILENT	HMP2020	100598	2025/7/01	2026/6/30
10dB attenuator	JFW INDUSTRIES INC	50HF-010-SMA	50HF-010-SMA-1	2025/6/30	2026/6/29
10dB attenuator	JFW INDUSTRIES INC	50HF-010-SMA	50HF-010-SMA-2	2025/6/30	2026/6/29
hygrothermograph	Anymetrers	----	TH101B	2025/7/22	2026/7/21
Temperature Box	zhongkemeiqi	MA22040172	MQ-DTH50F-2	2025/7/01	2026/6/30
power divider	WOKEN	71688	204-003180-01	2025/6/30	2026/6/29

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE


In accordance with ANSI C63.10-2020 11.8.1 Option 2:

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB

3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.3.7 TEST RESULTS


Please Refer to Appendix1 Of this test report.

3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: RF260330B007

3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

Please Refer to Appendix1 Of this test report.

3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.


Please Refer to Appendix1 Of this test report.

3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: RF260330B007

3.5.7 TEST RESULTS


Please Refer to Appendix1 Of this test report.

3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



Test Report No.: RF260330B007

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Please Refer to Appendix1 Of this test report.



Test Report No.: RF260330B007

3.7 ANTENNA REQUIREMENTS

3.7.1 STANDARD APPLICABLE

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 ANTENNA CONNECTED CONSTRUCTION

An embedded-in antenna design is used.

3.7.3 ANTENNA GAIN

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit and PSD limit.

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

6 APPENDIX1

WLAN 2.4G

Duty Cycle

Modulation Type	Frequency (MHz)	Antenna	Plot	Duty Cycle	Correction Factor(dB)
802.11b	2412	Ant3	Fig.1	99.58%	0
802.11b	2412	Ant7	Fig.2	99.61%	0
802.11g	2412	Ant3	Fig.3	99.77%	0
802.11g	2412	Ant7	Fig.4	99.78%	0
802.11n HT20	2412	Ant3	Fig.5	99.90%	0
802.11n HT20	2412	Ant7	Fig.6	99.93%	0
802.11ax HE20	2412	Ant3	Fig.7	98.65%	0.43
802.11ax HE20	2412	Ant7	Fig.8	99.91%	0.10
802.11be HE20	2412	Ant3	Fig.9	99.91%	0.12
802.11be HE20	2412	Ant7	Fig.10	99.94%	0.11
802.11n HT40	2422	Ant3	Fig.11	99.91%	0
802.11n HT40	2422	Ant7	Fig.12	99.93%	0
802.11ax HE40	2422	Ant3	Fig.13	99.93%	0.10
802.11ax HE40	2422	Ant7	Fig.14	99.94%	0.10
802.11be HE40	2422	Ant3	Fig.15	99.94%	0
802.11be HE40	2422	Ant7	Fig.16	99.92%	0

Note: Correction Factor= $10 \cdot \log(1/\text{Duty Cycle})$





Test Report No.: RF260330B007




Fig.7




Fig.8




Fig.9




Fig.10




Fig.11




Fig.12