

13 MPE Calculation

Prediction of MPE limit at a given distance

For purposes of these requirements mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits. As the 20 cm separation specified under FCC rules may not be achievable under normal operation of the EUT, an RF exposure calculation is needed to show the minimum distance required to be less than the power density limit, as required under FCC rules.

Equation from IEEE C95.1

$$S = \frac{EIRP}{4\pi R^2} \text{ re - arranged } R = \sqrt{\frac{EIRP}{S 4\pi}}$$

Where:

S = power density

R = distance to the centre of radiation of the antenna

EIRP = EUT Maximum power

Result

Radio	Lowest frequency (MHz)	EIRP (mW)	Power density at 20 cm (mW/cm²)	Power density limit (mW/cm²)	Ratio	Sum of Ratios	RF Exposure Evaluation
LF	0.125	12.3	0.002	11520.000	0.000	0.001	Not Required
NFC	13.56	0.7	0.000	0.979	0.000		
BTLE	2402	1.9	0.000	1.000	0.000		