

# OSIM International Ltd

## SAR COMPLIANCE REPORT

**Report Type:**

FCC SAR assessment report

**Model:**

OS-888

**REPORT NUMBER:**

180801177SHA-002

**ISSUE DATE:**

Oct 10, 2018

**DOCUMENT CONTROL NUMBER:**

TTRFFCCSAR-01\_V1 © 2018 Intertek



**Applicant:** OSIM International Ltd  
65 Ubi Avenue 1, OSIM Headquarters, Singapore 408939

**Manufacturer:** DT-OSIM Healthcare Appliances (Suzhou) Co., Ltd.  
China-Singapore Suzhou Industrial Park,  
No. 69 Longpu Road, Xinglong Street, Suzhou, China


**FCC ID:** ARG-OS-888

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06

FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

**PREPARED BY:**

Project Engineer  
Wakeyou Wang

**REVIEWED BY:**

Reviewer  
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

| Report No.       | Version | Description             | Issued Date  |
|------------------|---------|-------------------------|--------------|
| 180801177SHA-002 | Rev. 01 | Initial issue of report | Oct 10, 2018 |
|                  |         |                         |              |
|                  |         |                         |              |

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

|                       |                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------|
| Product name:         | BT Module for Data Transfer                                                                    |
| Type/Model:           | OS-888                                                                                         |
| Description of EUT:   | The device is a BT module. It is tested together with the host (massage chair OS-888 uLove 2). |
| Rating:               | DC 3.3V powered by the massage chair indirectly (110-120V, 60Hz)                               |
| Category of EUT:      | Class B                                                                                        |
| EUT type:             | <input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing          |
| Software Version:     | /                                                                                              |
| Hardware Version:     | /                                                                                              |
| Sample received date: | Sep 20, 2018                                                                                   |
| Date of test:         | Sep 20, 2018 - Sep 30, 2018                                                                    |

### 1.2 Technical Specification

|                       |                                         |
|-----------------------|-----------------------------------------|
| Frequency Range:      | 2400MHz ~ 2483.5MHz                     |
| Support Standards:    | Bluetooth 4.2 (BR+EDR)                  |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Type of Modulation:   | GFSK, $\pi/4$ DQPSK, 8DPSK              |
| Channel Number:       | 79 (0 - 78)                             |
| Data Rate:            | 1Mbps                                   |
| Channel Separation:   | 1 MHz                                   |
| Antenna:              | Internal PCB antenna, 0dBi Peak gain    |

### 1.3 Description of Test Facility

|            |                                                                        |
|------------|------------------------------------------------------------------------|
| Name:      | Intertek Testing Services Shanghai                                     |
| Address:   | Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200                                                         |
| Telefax:   | 86 21 54262353                                                         |

|                                                                                   |                                                                          |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab<br>Registration No. CNAS L0139                    |
|                                                                                   | FCC Accredited Lab<br>Designation Number: CN1175                         |
|                                                                                   | IC Registration Lab<br>Registration code No.: 2042B-1                    |
|                                                                                   | VCCI Registration Lab<br>Registration No.: R-4243, G-845, C-4723, T-2252 |
|                                                                                   | NVLAP Accreditation Lab<br>NVLAP LAB CODE: 200849-0                      |
|                                                                                   | A2LA Accreditation Lab<br>Certificate Number: 3309.02                    |

## 2 SAR Assessment

Test result: Pass

### 2.1 SAR Test Exclusion Limit

100 MHz – 6 GHz and  $\leq 50$  mm

| MHz  | 5   | 10  | 15  | 20  | 25  | mm                                      |
|------|-----|-----|-----|-----|-----|-----------------------------------------|
| 150  | 39  | 77  | 116 | 155 | 194 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 27  | 55  | 82  | 110 | 137 |                                         |
| 450  | 22  | 45  | 67  | 89  | 112 |                                         |
| 835  | 16  | 33  | 49  | 66  | 82  |                                         |
| 900  | 16  | 32  | 47  | 63  | 79  |                                         |
| 1500 | 12  | 24  | 37  | 49  | 61  |                                         |
| 1900 | 11  | 22  | 33  | 44  | 54  |                                         |
| 2450 | 10  | 19  | 29  | 38  | 48  |                                         |
| 3600 | 8   | 16  | 24  | 32  | 40  |                                         |
| 5200 | 7   | 13  | 20  | 26  | 33  |                                         |
| 5400 | 6   | 13  | 19  | 26  | 32  |                                         |
| 5800 | 6   | 12  | 19  | 25  | 31  |                                         |
|      |     |     |     |     |     |                                         |
| MHz  | 30  | 35  | 40  | 45  | 50  | mm                                      |
| 150  | 232 | 271 | 310 | 349 | 387 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 164 | 192 | 219 | 246 | 274 |                                         |
| 450  | 134 | 157 | 179 | 201 | 224 |                                         |
| 835  | 98  | 115 | 131 | 148 | 164 |                                         |
| 900  | 95  | 111 | 126 | 142 | 158 |                                         |
| 1500 | 73  | 86  | 98  | 110 | 122 |                                         |
| 1900 | 65  | 76  | 87  | 98  | 109 |                                         |
| 2450 | 57  | 67  | 77  | 86  | 96  |                                         |
| 3600 | 47  | 55  | 63  | 71  | 79  |                                         |
| 5200 | 39  | 46  | 53  | 59  | 66  |                                         |
| 5400 | 39  | 45  | 52  | 58  | 65  |                                         |
| 5800 | 37  | 44  | 50  | 56  | 62  |                                         |

# TEST REPORT

100 MHz – 6 GHz and > 50 mm

| MHz  | 50  | 60  | 70  | 80  | 90  | 100 | 110 | 120 | 130 | 140  | 150  | 160  | 170  | 180  | 190  | mm |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|----|
| 100  | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534  | 541  | 547  | 554  | 561  | 567  | mW |
| 150  | 387 | 397 | 407 | 417 | 427 | 437 | 447 | 457 | 467 | 477  | 487  | 497  | 507  | 517  | 527  |    |
| 300  | 274 | 294 | 314 | 334 | 354 | 374 | 394 | 414 | 434 | 454  | 474  | 494  | 514  | 534  | 554  |    |
| 450  | 224 | 254 | 284 | 314 | 344 | 374 | 404 | 434 | 464 | 494  | 524  | 554  | 584  | 614  | 644  |    |
| 835  | 164 | 220 | 275 | 331 | 387 | 442 | 498 | 554 | 609 | 665  | 721  | 776  | 832  | 888  | 943  |    |
| 900  | 158 | 218 | 278 | 338 | 398 | 458 | 518 | 578 | 638 | 698  | 758  | 818  | 878  | 938  | 998  |    |
| 1500 | 122 | 222 | 322 | 422 | 522 | 622 | 722 | 822 | 922 | 1022 | 1122 | 1222 | 1322 | 1422 | 1522 |    |
| 1900 | 109 | 209 | 309 | 409 | 509 | 609 | 709 | 809 | 909 | 1009 | 1109 | 1209 | 1309 | 1409 | 1509 |    |
| 2450 | 96  | 196 | 296 | 396 | 496 | 596 | 696 | 796 | 896 | 996  | 1096 | 1196 | 1296 | 1396 | 1496 |    |
| 3600 | 79  | 179 | 279 | 379 | 479 | 579 | 679 | 779 | 879 | 979  | 1079 | 1179 | 1279 | 1379 | 1479 |    |
| 5200 | 66  | 166 | 266 | 366 | 466 | 566 | 666 | 766 | 866 | 966  | 1066 | 1166 | 1266 | 1366 | 1466 |    |
| 5400 | 65  | 165 | 265 | 365 | 465 | 565 | 665 | 765 | 865 | 965  | 1065 | 1165 | 1265 | 1365 | 1465 |    |
| 5800 | 62  | 162 | 262 | 362 | 462 | 562 | 662 | 762 | 862 | 962  | 1062 | 1162 | 1262 | 1362 | 1462 |    |

< 100 MHz and < 200 mm

| MHz  | < 50 | 50   | 60   | 70   | 80   | 90   | 100  | 110  | 120  | 130  | 140  | 150  | 160  | 170  | 180  | 190  | mm |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 100  | 237  | 474  | 481  | 487  | 494  | 501  | 507  | 514  | 521  | 527  | 534  | 541  | 547  | 554  | 561  | 567  | mW |
| 50   | 308  | 617  | 625  | 634  | 643  | 651  | 660  | 669  | 677  | 686  | 695  | 703  | 712  | 721  | 729  | 738  |    |
| 10   | 474  | 948  | 961  | 975  | 988  | 1001 | 1015 | 1028 | 1041 | 1055 | 1068 | 1081 | 1095 | 1108 | 1121 | 1135 |    |
| 1    | 711  | 1422 | 1442 | 1462 | 1482 | 1502 | 1522 | 1542 | 1562 | 1582 | 1602 | 1622 | 1642 | 1662 | 1682 | 1702 |    |
| 0.1  | 948  | 1896 | 1923 | 1949 | 1976 | 2003 | 2029 | 2056 | 2083 | 2109 | 2136 | 2163 | 2189 | 2216 | 2243 | 2269 |    |
| 0.05 | 1019 | 2039 | 2067 | 2096 | 2125 | 2153 | 2182 | 2211 | 2239 | 2268 | 2297 | 2325 | 2354 | 2383 | 2411 | 2440 |    |
| 0.01 | 1185 | 2370 | 2403 | 2437 | 2470 | 2503 | 2537 | 2570 | 2603 | 2637 | 2670 | 2703 | 2737 | 2770 | 2803 | 2837 |    |

TEST REPORT

2.2 Assessment Results

The highest EIRP adjusted with tune-up tolerance is 5.70dBm = 3.72mW < 10mW (Test Exclusion Thresholds of 2450MHz at 5mm). Therefore, the SAR requirement is deemed to be satisfied without test.

\*\*\*\*\* END \*\*\*\*\*