



RF EXPOSURE EVALUATION REPORT

APPLICANT : Top Victory Electronics (Taiwan) Co., Ltd.

PRODUCT NAME : Colour Monitor

MODEL NAME : 10BDL4151T*** (The “ * ” can be any alphanumeric including “ / ” or blank for marketing differences.)

BRAND NAME : PHILIPS

FCC ID : ARS-10BDL4151T

STANDARD(S) : 47CFR 2.1091
KDB 447498

RECEIPT DATE : 2019-01-21

TEST DATE : 2019-01-23

ISSUE DATE : 2019-04-15

Edited by: Su Jinhai
Su Jinhai (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1. Technical Information.....	4
1.1 Applicant and Manufacturer Information.....	4
1.2 Equipment under Test (EUT) Description.....	4
1.3 Identification of all used EUT.....	5
1.4 Applied Reference Documents.....	5
2. Device Category and RF Exposure Limit.....	6
3. RF Output Power.....	7
4. RF Exposure Evaluation.....	8
Annex A General Information.....	9
Annex B Photographs of the EUT.....	10



REPORT No. : SZ19010144S01

Change history		
Version	Date	Reason of changed
1.0	2019-04-15	First edition



1. Technical Information

Note: Provide by manufacturer.

1.1 Applicant and Manufacturer Information

Applicant:	Top Victory Electronics (Taiwan) Co., Ltd.
Applicant Address:	10F., No 230, Liancheng Rd., Zhonghe Dist., New Taipei City 23553, Taiwan (R.O.C)
Manufacturer:	MMD(Shanghai) Electronics Trading Co.,Ltd
Manufacturer Address:	Room 603D, No.2 Building, 80 Mo Ling Road, JingAn District,, Shanghai

1.2 Equipment under Test (EUT) Description

EUT Type:	Colour Monitor
Hardware Version:	V1.0
Software Version:	kr3368_64-userdebug 7.1.2 NHG47K eng.carl.20190107.171540 test-keys
Frequency Bands:	WLAN: 802.11b/g/n: 2412 MHz ~2462 MHz Bluetooth: 2402 MHz ~2480 MHz
Modulation Mode:	802.11b: DSSS 802.11g/n-HT20/HT40: OFDM Bluetooth: GFSK, π /4-DQPSK, 8-DPSK BLE: GFSK
Antenna Type:	FPC Antenna
Antenna Gain:	WLAN/Bluetooth: -1.8dBi

Note : For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	V1.0	kr3368_64-userdebug 7.1.2 NHG47K eng.carl.20190107.171540 test-keys

1.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1091	Radio Frequency Radiation Exposure Evaluation: mobile devices
2	KDB 447498 D01v06	General RF Exposure Guidance

2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density

3. RF Output Power

<WLAN output power>

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Limit
	802.11b 1Mbps	CH 1	2412	15.93	16.00
		CH 6	2437	16.29	16.50
		CH 11	2462	16.38	16.50
	802.11g 6Mbps	CH 1	2412	15.95	16.00
		CH 6	2437	16.70	17.00
		CH 11	2462	16.46	16.50
	802.11n-HT20 MCS0	CH 1	2412	15.83	16.00
		CH 6	2437	16.57	17.00
		CH 11	2462	16.40	16.50
	802.11n-HT40 MCS0	CH 3	2422	15.77	16.00
		CH 6	2437	16.39	16.50
		CH 9	2452	16.02	16.50

<Bluetooth output power>

Mode	Channel	Frequency (MHz)	Peak power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	7.92	9.04	9.52
	CH 39	2441	7.93	9.08	9.66
	CH 78	2480	8.37	9.58	10.09
Tune-up Limit			8.5	10	10.50

Mode	Channel	Frequency (MHz)	Peak power (dBm)
			GFSK
LE	CH 00	2402	8.81
	CH 19	2440	8.83
	CH 39	2480	8.88
Tune-up Limit			9.50

Note:

1. According to KDB 447498 Section 4.3, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

4. RF Exposure Evaluation

Standalone transmission evaluation:

Bands	Frequency (MHz)	Antenna Gain (dBi)	Maximum Tune-up Limit (dBm)	EIRP (mW)	Power density (mW/cm ²)	Limit for MPE (mW/cm ²)
2.4GHz WLAN	2437	-1.8	17.00	33.11	0.007	1.0
Bluetooth	2480	-1.8	10.50	7.41	0.001	1.0

Note:

1. According to KDB 447498, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. MPE calculation method

$$\text{Power Density} = \text{EIRP} / 4\pi R^2$$

Where: $\text{EIRP} = P + G$

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Annex B Photographs of the EUT

EUT Front View



EUT Back View

