

Report prepared by:

Technologies, Inc. **United States**
 3505 Francis Circle
 Alpharetta, GA 30004

740-0717 **Phone Number: (770)**
740-1508 **Fax Number: (770)**

TABLE OF CONTENTS

GENERAL INFORMATION

Users Manual Includes:
 Theory of Operation/ Technical Description
 Tune Up Procedure
Parts Lists
Schematics
Labeling Information
Photographs

TESTS AND MEASUREMENTS

Product Description
Test Methodology
EUT and Peripherals

Test Facility

Test Equipment

Modifications

Measurement Procedure

- RF Power Output
- Bandwidth of Fundamental Emission
- Spurious Emissions at Antenna Terminals
- Field Strength of Spurious Radiation Emissions
- Frequency Stability
- Transient Frequency Behavior

GENERAL INFORMATION

USERS MANUAL

Includes:

Theory Of Operation
Tune Up Procedure

**This has been provided in 2 separate
files from Relm Communications (Word
relmmanual.doc & relmmanual1.doc)**

PARTS LIST

**At the time of submittal, this information
was not available from Relm
Communications**

SCHEMATICS

**These have been provided in separate
files**

LABELING INFORMATION

**This information has been provided in a
separate file from Relm Communications
(Word Document fcc1b1.doc)**

PHOTOGRAPHS

PHOTOGRAPHS

Photo 1. EUT, Front View
Photo 2. EUT, Rear View
Photo 3. EUT, Internal View, Cover Removed
Photo 4. EUT, Digital Board, Top View
Photo 5. EUT, Digital Board, Bottom View
Photo 6. EUT, RX Portion, Inside Top Cover
Photo 7. RX Portion, Main Board, Top Cover Removed
Photo 8. RX Portion, Main Board, Top Cover &
Daughter Board Removed
Photo 9. RX Portion, Main Board, Bottom View
Photo 10. RX Portion, Top View Of Daughter Board
Photo 11. RX Portion, Bottom View Of Daughter Board
Photo 12. RX Portion, Inside Bottom Cover
Photo 13. EUT, TX Portion, Inside Top Cover
Photo 14. TX Portion, Main Board, Top Cover Removed
Photo 15. TX Portion, Main Board, Top Cover &
Daughter Board Removed
Photo 16. TX Portion, Main Board, Bottom View
Photo 17. TX Portion, Top View Of Daughter Board
Photo 18. TX Portion, Bottom View Of Daughter Board
Photo 19. TX Portion, Inside Bottom Cover
Photo 20. Top Of Power Amplifier Board

These have been provided in separate files

TESTS AND MEASUREMENTS

TESTS AND MEASUREMENTS

Product Description

The Equipment Under Test (EUT) is the RELM Communications, Inc. S Series (Models SRU50A, SRU50B, & SRU50C). The S Series (Models SRU50A, SRU50B, & SRU50C) of radio systems uses state-of-the-art design and construction methods to deliver a range of high-performance, ultra-reliable radio devices. These radio systems are ideally suited for use in VHF or UHF two-way voice radio systems; however, the S Series (Models SRU50A, SRU50B, & SRU50C) can perform any number of applications where the added advantage of linear frequency and phase response from DC to 5KHz can be used. The S Series (Models SRU50A, SRU50B, & SRU50C), unlike conventional PLL radio systems, uses a two-point modulation method synthesizer for extended low-end VF transmit frequency response.

The flexibility of the S Series (Models SRU50A, SRU50B, & SRU50C) allows it to be configured for a wide range of applications:

- Standard or wideband voice, full duplex radio
- Cellular or trunking systems
- POCSAG paging transmitter
- Direct FSK modulation
- Two- or four-level FSK transmissions
- Other paging formats
- Cross band link or repeater

Three separate units were tested to cover the 400-435 MHz (N2), 450-485 MHz (P2), and 485-520 MHz (Q) bands.

These units are identical in design nature except for a few minor component value changes to cover each individual band. Each model equates to the following frequency bands:

SRU50A	400-435 MHz
SRU50B	450-485 MHz
SRU50C	485-520 MHz

Test Methodology

Prepared in accordance with the requirements of FCC Rules and Regulations Part 2 Subpart F, Paragraphs 2.983 through 2.999 and applicable portions of Parts 24, 74, 80 and 90. All measurements are peak unless stated otherwise. The video filter associated with the spectrum analyzer was off throughout the evaluation process. Interconnecting cables were manipulated as necessary to maximize emissions. A block diagram of the tested system is shown in Figure 1.

Test Facility

Testing was performed at US Tech's measurement facility as described to the FCC and acknowledged in their letter marked 31040/SIT/US TECH. Additionally this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number IC2982.

Test Equipment

Table 1 describes test equipment used to evaluate this product.

Modifications

US Tech did not make any modifications to bring the EUT into compliance.

Test Date: July 15, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

Figure 1
System Block Diagram



Test Date: July 15, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 1**EUT AND PERIPHERALS**

PERIPHERAL MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID:	CABLES P/D
Base Station RELM Communications (EUT)	SRU50A-N2 SRU50B-P2 SRU50C-QQ	None	ARUSRU50ABC (Pending)	50 Ω Term. Attenuation
DC Power Supply Astron	VS-35M	311364	None	6'U 6'U Power Cord

Test Date: July 15, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, &
SRU50C)

RADIATED EMISSION TEST SET-UP PHOTO

These have been provided in additional files
(2 photos)

TABLE 2
TEST INSTRUMENTS

TYPE	MANUFACTURER	MODEL	SN .
SPECTRUM ANALYZER	HEWLETT - PACKARD	8593E	3205A00124
SPECTRUM ANALYZER	HEWLETT - PACKAR D	8558B	2332A09900
S A DISPLAY	HEWLETT - PACKAR D	853A	2404A02387
COMB GENERATOR	HEWLETT - PACKAR D	8406A	1632A01519
RF PREAMP	HEWLETT - PACKAR D	8447D	1937A03355
RF PREAMP	HEWLETT - PACKARD	8449B	3008A00480
BICONICAL ANTENNA	EMCO	3110	9307-1431
LOG PERIODIC ANTENNA	EMCO	3146	9110-3600
HORN ANTENNA	EMCO	3115	167
THERMOMETER	FLUKE	52	5215250
MULTIMETER	FLUKE	85	53710469
DUAL OUTPUT POWER SUPPLY	HEWLETT - PACKARD	E3620A	KR41200373
PLOTTER	HEWLETT - PACKARD	7475A	2325A65394

MEASUREMENT PROCEDURE

Subpart 2.985(a), 90.205(d)**RF Power Output**

The EUT was directly connected to a spectrum analyzer with the input resistance set to 50Ω . An external 30 dB attenuation was used during the test. The maximum RF output power was measured and compared to the manufacturer's rating. The connector and cable that was used to connect the EUT to the spectrum analyzer has an unknown loss. Only the highest power measured is reported for each unit.

FCC Minimum Standard

Typically (+/-) 20 % of the manufacturer's rated output power and less than the maximum power.

Mfg. Rated Power: +46.99 dBm/50,000.0 mW across 50Ω at output terminals

Power Measured (corrected)

	<u>Power (dBm)</u>	<u>Power (mW)</u>
Figure 2A SRU50A		46.8
47,973		
Figure 2B SRU50B		46.3
43,152		
Figure 2C SRU50C	47.8	
59,979		

Example Calculation

Power in mW = $\text{antilog}(46.8 / 10) = 47,973$

Results

T. R. J.

Reviewed By: _____

_____ **Name:** Tim R. Johnson

**Figure 2A RF Power Output
Model SRU50A**

Refer to file fig2a.jpg

**Figure 2B RF Power Output
Model SRU50B**

Refer to file fig2b.jpg

**Figure 2C RF Power Output
Model SRU50C**

Refer to file fig2c.jpg

MEASUREMENT PROCEDURE**Subpart 2.989(h), 90.210(b)****BANDWIDTH OF FUNDAMENTAL EMISSION UNDER MODULATION**

The EUT was modulated by a 2.5kHz tone. Table 3 and Figure 3 show the data for 25 kHz channel bandwidth.

FCC Minimum Standard**25 kHz Channel Bandwidth****10 kHz up to and including 20 kHz 25 dB****20 kHz up to and including 50 kHz 35 dB****> 50 kHz $43 + 10 \log (P)$ dB**

Test Date: July 23, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 3A
25 kHz CHANNEL BANDWIDTH
Model SRU50A

FREQUENCY (kHz) FROM CARRIER	ATTENUATI ON BELOW CARRIER LEVEL	MINIMUM STANDARD
-16.6	73.7	25.0
-14.4	69.0	25.0
-12.5	60.1	25.0
-10.0	42.9	25.0
10.0	43.7	25.0
12.5	59.3	25.0
14.9	73.9	25.0
16.1	75.2	25.0

Tester

Signature: _____

_____ **Name:** Erik Collins

—

Test Date: July 23, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 3B
25 kHz CHANNEL BANDWIDTH
Model SRU50B

FREQUENCY (kHz) FROM CARRIER	ATTENUATI ON BELOW CARRIER LEVEL	MINIMUM STANDARD
- 15 . 6	73 . 1	25 . 0
- 13 . 5	68 . 4	25 . 0
- 12 . 5	58 . 9	25 . 0
- 10 . 0	43 . 2	25 . 0
10 . 0	43 . 6	25 . 0
12 . 6	59 . 4	25 . 0
14 . 7	71 . 3	25 . 0
15 . 5	73 . 5	25 . 0

Tester

Signature: _____

_____ **Name:** Erik Collins

—

Test Date: July 23, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 3C
25 kHz CHANNEL BANDWIDTH
Model SRU50C

FREQUENCY (kHz) FROM CARRIER	ATTENUATI ON BELOW CARRIER LEVEL	MINIMUM STANDARD
-17.5	68.8	25.0
-15.0	56.1	25.0
-12.5	41.7	25.0
-10.0	28.1	25.0
10.0	28.4	25.0
12.5	41.7	25.0
15.1	56.4	25.0
17.5	67.0	25.0

Tester

Signature: _____

_____ **Name:** Erik Collins

—

FIGURE 3A
25 kHz CHANNEL BANDWIDTH
Model SRU50A

Refer to file fig3a.jpg

FIGURE 3B
25 kHz CHANNEL BANDWIDTH
Model SRU50B

Refer to file fig3b.jpg

FIGURE 3C
25 kHz CHANNEL BANDWIDTH
Model SRU50C

Refer to file fig3c.jpg

MEASUREMENT PROCEDURE

Subpart 2.991, 90.210(b), 22.359(a), and
74.462(c)

Transmitter Spurious Emissions At Antenna
Terminals

FCC Minimum Standard

25 kHz Channel Bandwidth

$43 + 10 \log (P) = \text{dB}$

P = Measured Power

Transmitter Spurious Emissions At Antenna Terminals (Subpart 2.911 and 90.210(c))

Test Date: June 27, 1998

UST Project: 98-280


Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

Table 4A
Model SRU50A

FREQUENCY (MHz)	ATTENUATED LEVEL (dB) BELOW CARRIER POWER	MINIMUM STANDARD
800.0	62.3	59.8
1200.0	63.5	59.8
1600.0	70.4	59.8
2000.0	73.8	59.8

Results
Reviewed

By: 

Name: Tim R. Johnson

Transmitter Spurious Emissions At Antenna Terminals (Subpart 2.911 and 90.210(c))

Test Date: June 27, 1998

UST Project: 98-280


Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

Table 4B
Model SRU50B

FREQUENCY (MHz)	ATTENUATED LEVEL (dB) BELOW CARRIER POWER	MINIMUM STANDARD
970.0	62.3	59.4
1455.0	64.3	59.4
1940.0	76.9	59.4
2424.8	78.5	59.4

Results
Reviewed

By: 

Name: Tim R. Johnson

Transmitter Spurious Emissions At Antenna Terminals (Subpart 2.911 and 90.210(c))

Test Date: June 27, 1998

UST Project: 98-280


Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

Table 4C
Model SRU50C

FREQUENCY (MHz)	ATTENUATED LEVEL (dB) BELOW CARRIER POWER	MINIMUM STANDARD
1000.0	62.3	60.8
1500.0	63.1	60.8
3000.0	73.9	60.8
2500.0	74.3	60.8

Results
Reviewed

By: 

Name: Tim R. Johnson

MEASUREMENT PROCEDURE

Subpart 2.993(a), 90.210(b), 22.359(a), and 74.462(c)

Field Strength of Spurious Radiation

Spurious emissions were evaluated from 30 MHz to 2.0 GHz at an EUT to antenna distance of 3 meters. Measurements for 30 to 1000 MHz were made with the analyzer's bandwidth set to 120 kHz. Measurements above 1000 MHz were made with the analyzer's bandwidth set to 1 MHz. Since the EUT is part of a portable handheld configuration, the EUT was rotated through three orthogonal axis to produce the highest emission relative to the limit.

This level is interpolated to 30 meters using:

$$\text{dBm @ 3 meters} + 20 \log(3/30) = \text{dBm @ 30 meters}$$

This level is compared to the level a transmitter would produce at 30 meters if connected to a 1/2 wave dipole using:

$$E = \frac{[(30 \text{ Pt Gt})]^{1/2}}{d} \text{ volts per meter}$$

E = Field intensity (volts per meter)

Pt = Power output of transmitter (watts)

Gt = Gain of antenna (1.64 for 1/2 wave dipole)

d = distance (meters)

Example: A 25 watt transmitter would produce

$$\frac{[(30)(25)(1.64)]^{1/2}}{30.0} \text{ volts per meter}$$

= 1,150,635 microvolts per meter @ 30 meters

FCC Minimum Standard

25 kHz Channel Bandwidth

$$43 + 10 \log_{10} (P) = \text{attenuation below carrier (dB)}$$
FIELD STRENGTH OF SPURIOUS RADIATION**Test Date: June 27, 1998****UST Project: 98-280****Customer: RELM Communications****Model: S Series (Models SRU50A, SRU50B, & SRU50C)****25 kHz Channel Bandwidth**

$$\text{FCC Minimum Standard: } 50 + 10 \log (48.0) = 59.8 \text{ dB}$$

$$\text{Fundamental} = \text{Corrected Reading in Far Field (30m)} = 17.1 \text{ dBm}$$
**TABLE 5A
SRU50A**

FREQ (MHz)	MEASUREME NT @ 3 m (dBm) *	CORRECTI ON AF + CL + AMP GAIN	CORRECTED MEASUREME NT @ 30 m (dBm)	ATTENUA TED LEVEL BELOW CARRIER POWER (dB)
800.06	-71.7	29.2	-62.5	79.6
1200.05	-21.5	-6.4	-47.9	65.0
1600.13	-49.4	-5.0	-74.4	91.5
2000.25	-49.3	-2.6	-71.9	89.0
2400.10	-44.7	-.3	-65.0	82.1
2800.13	-47.9	.7	-67.2	84.3
3200.20	-54.6	1.5	-73.1	90.2
3600.20	-55.4	3.0	-72.4	89.5
4000.10	-59.0	4.7	-74.3	91.4

SAMPLE CALCULATION:

Results dBm @ 30 m:

$$-71.7 + 29.2 - 20 = -62.5$$

CONVERSION FROM 3 METERS TO 30 METERS = 20 dB

* = Measurements were made with a 50W
 termination connected to the antenna
 port. 

Results

Reviewed By: _____

_____ **Name:** Tim R. Johnson

FIELD STRENGTH OF SPURIOUS RADIATION**Test Date: June 27, 1998****UST Project: 98-280****Customer: RELM Communications****Model: S Series (Models SRU50A, SRU50B, & SRU50C)****25 kHz Channel Bandwidth****FCC Minimum Standard: $50 + 10 \log (46.3) = 59.4 \text{ dB}$** **Fundamental = Corrected Reading in Far Field (30m) = 17.0 dBm****TABLE 5B
SRU50B**

FREQ (MHz)	MEASUREME NT @ 3 m (dBm) *	CORRECTI ON AF + CL + AMP GAIN	CORRECTED MEASUREME NT @ 30 m (dBm)	ATTENUA TED LEVEL BELOW CARRIER POWER (dB)
970.04	-71.7	32.4	-59.3	76.3
1454.83	-23.8	-5.7	-49.5	66.5
1939.90	-58.8	-3.0	-81.8	98.8
2424.78	-44.0	-.2	-64.2	81.2
2909.68	-49.4	.9	-68.5	85.5
3394.83	-57.5	2.2	-75.3	92.3
3879.80	-62.2	4.2	-78.0	95.0
4364.55	-54.6	4.5	-69.5	86.5
4849.85	-58.2	4.7	-73.5	90.5

SAMPLE CALCULATION:**Results dBm @ 30 m:**

$$-71.7 + 32.4 - 20 = -59.3$$

CONVERSION FROM 3 METERS TO 30 METERS = 20

dB

* = Measurements were made with a 50W
termination connected to the antenna
port. 

Results

Reviewed By: _____
Name: Tim R. Johnson

FIELD STRENGTH OF SPURIOUS RADIATION**Test Date: June 27, 1998****UST Project: 98-280****Customer: RELM Communications****Model: S Series (Models SRU50A, SRU50B, & SRU50C)****25 kHz Channel Bandwidth****FCC Minimum Standard: $50 + 10 \log (60.0) = 69.8 \text{ dB}$** **Fundamental = Corrected Reading in Far Field (30m) = 18.2 dBm****TABLE 5C
SRU50C**

FREQ (MHz)	MEASUREME NT @ 3 m (dBm) *	CORRECTI ON AF + CL + AMP GAIN	CORRECTED MEASUREME NT @ 30 m (dBm)	ATTENUA TED LEVEL BELOW CARRIER POWER (dB)
1499.95	-74.3	-6.9	-101.2	119.4
1999.90	-28.0	-5.7	-53.7	71.9
2499.90	-46.7	-2.6	-69.3	87.5
2999.95	-47.9	0.3	-67.6	85.8
3500.05	-42.1	1.0	-61.1	79.3
3999.95	-53.1	2.4	-70.7	88.9
4500.05	-57.6	4.7	-72.9	91.1
4999.95	-54.4	4.3	-70.1	88.3
4849.85	-56.6	4.8	-71.8	90.0

SAMPLE CALCULATION:**Results dBm @ 30 m:**

$$-74.3 + -6.9 - 20 = -101.2$$

CONVERSION FROM 3 METERS TO 30 METERS = 20

dB

* = Measurements were made with a 50W
termination connected to the antenna
port. 

Results

Reviewed By: _____
Name: Tim R. Johnson

MEASUREMENT PROCEDURE

Frequency Stability

Subpart 2.995, 90.213, and 22.355

The frequency tolerance of the carrier signal was measured while ambient temperature was varied from -30 to 50 degrees centigrade. The frequency tolerance was verified at 10 degree increments. The EUT was tested with fully charged batteries. The supply voltage was varied from 11.7 Volts to 15.9 Volts. The data is shown in the following tables and figures.

FCC Minimum Standard

< 2.5 ppm

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 6A
SRU50A**

At Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	420.00100	< 2.5ppm
-20.0	420.00100	< 2.5ppm
-10.0	420.00092	< 2.5ppm
-0.0	420.00100	< 2.5ppm
10.0	420.00076	< 2.5ppm
20.0	420.00052	< 2.5ppm
30.0	420.00062	< 2.5ppm
40.0	420.00078	< 2.5ppm
50.0	420.00078	< 2.5ppm

Tester

Signature: _____

Name: Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 6B
SRU50A**

2 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	420.00100	< 2.5ppm
-20.0	420.00100	< 2.5ppm
-10.0	420.00094	< 2.5ppm
-0.0	420.00098	< 2.5ppm
10.0	420.00076	< 2.5ppm
20.0	420.00044	< 2.5ppm
30.0	420.00043	< 2.5ppm
40.0	420.00052	< 2.5ppm
50.0	420.00078	< 2.5ppm

Tester

Signature: _____
 _____ Name: Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998
 UST Project: 98-280
 Customer: RELM Communications
 Model: S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 6C
SRU50A

5 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	420.00100	< 2.5ppm
-20.0	420.00104	< 2.5ppm
-10.0	420.00102	< 2.5ppm
-0.0	420.00090	< 2.5ppm
10.0	420.00084	< 2.5ppm
20.0	420.00044	< 2.5ppm
30.0	420.00058	< 2.5ppm
40.0	420.00058	< 2.5ppm
50.0	420.00059	< 2.5ppm

Tester

Signature: _____

Name: Erik D. Collins**FREQUENCY STABILITY (Subpart 2.995 and 90.213)**

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 6D
SRU50A****10 Minutes After Startup**

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	420.00100	< 2.5ppm
-20.0	420.00100	< 2.5ppm
-10.0	420.00096	< 2.5ppm
-0.0	420.00100	< 2.5ppm
10.0	420.00086	< 2.5ppm
20.0	420.00054	< 2.5ppm

30.0	420.00054	< 2.5ppm
40.0	420.00061	< 2.5ppm
50.0	420.00070	< 2.5ppm

Results

Reviewed By: _____
 _____ **Name:** Tim R. Johnson

**FREQUENCY STABILITY (Subpart 2.995 and
90.213)**

Test Date: July 8-13, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, &
 SRU50C)

**TABLE 7A
SRU50B**

At Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	460.00110	< 2.5ppm
-20.0	460.00110	< 2.5ppm

-10.0	460.00110	< 2.5ppm
-0.0	460.00110	< 2.5ppm
10.0	460.00094	< 2.5ppm
20.0	460.00078	< 2.5ppm
30.0	460.00078	< 2.5ppm
40.0	460.00110	< 2.5ppm
50.0	460.00110	< 2.5ppm

Tester

Signature: _____

_____ Name: Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, &
SRU50C)

TABLE 7B
SRU50B

2 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC
-----------	-------------	-----

		DEVIATION
-30.0	460.00110	< 2.5ppm
-20.0	460.00110	< 2.5ppm
-10.0	460.00110	< 2.5ppm
-0.0	460.00110	< 2.5ppm
10.0	460.00098	< 2.5ppm
20.0	460.00078	< 2.5ppm
30.0	460.00078	< 2.5ppm
40.0	460.00110	< 2.5ppm
50.0	460.00110	< 2.5ppm

Tester

Signature: _____

_____ Name: Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 7C
SRU50B**

5 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	460.00110	< 2.5ppm
-20.0	460.00110	< 2.5ppm
-10.0	460.00110	< 2.5ppm
-0.0	460.00108	< 2.5ppm
10.0	460.00090	< 2.5ppm
20.0	460.00086	< 2.5ppm
30.0	460.00074	< 2.5ppm
40.0	460.00100	< 2.5ppm
50.0	460.00110	< 2.5ppm

Tester**Signature:** __________
Name: Erik D. Collins**FREQUENCY STABILITY (Subpart 2.995 and 90.213)****Test Date:** July 8-13, 1998**UST Project:** 98-280**Customer:** RELM Communications**Model:** S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 7D
SRU50B

10 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	460.00110	< 2.5ppm
-20.0	460.00110	< 2.5ppm
-10.0	460.00110	< 2.5ppm
-0.0	460.00110	< 2.5ppm
10.0	460.00090	< 2.5ppm
20.0	460.00076	< 2.5ppm
30.0	460.00078	< 2.5ppm
40.0	460.00110	< 2.5ppm
50.0	460.00110	< 2.5ppm

Tester

Signature: _____

Name: Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

TABLE 8A
SRU50C

At Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	500.00120	< 2.5ppm
-20.0	500.00100	< 2.5ppm
-10.0	500.00058	< 2.5ppm
-0.0	500.00100	< 2.5ppm
10.0	500.00063	< 2.5ppm
20.0	500.00120	< 2.5ppm
30.0	500.00058	< 2.5ppm
40.0	500.00120	< 2.5ppm
50.0	500.00114	< 2.5ppm

Tester

Signature: _____

_____ **Name:** Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications


Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 8B
SRU50C**

2 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	500.00120	< 2.5ppm
-20.0	500.00098	< 2.5ppm
-10.0	500.00058	< 2.5ppm
-0.0	500.00066	< 2.5ppm
10.0	500.00063	< 2.5ppm
20.0	500.00124	< 2.5ppm
30.0	500.00120	< 2.5ppm
40.0	500.00120	< 2.5ppm
50.0	500.00110	< 2.5ppm

Results

Reviewed By: Name: Tim R. Johnson**FREQUENCY STABILITY (Subpart 2.995 and 90.213)**

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 8C
SRU50C****5 Minutes After Startup**

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	500.00120	< 2.5ppm
-20.0	500.00120	< 2.5ppm
-10.0	500.00068	< 2.5ppm
-0.0	500.00062	< 2.5ppm
10.0	500.00063	< 2.5ppm
20.0	500.00120	< 2.5ppm
30.0	500.00120	< 2.5ppm

40.0	500.00120	< 2.5ppm
50.0	500.00114	< 2.5ppm

Tester

Signature: _____
 _____ Name: Erik D. Collins

FREQUENCY STABILITY (Subpart 2.995 and 90.213)

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 8D
SRU50C**

10 Minutes After Startup

TEMP (°C)	FREQ. (MHz)	FCC DEVIATION
-30.0	500.00120	< 2.5ppm
-20.0	500.00120	< 2.5ppm
-10.0	500.00068	< 2.5ppm

- 0 . 0	500.00070	< 2.5ppm
10 . 0	500.00063	< 2.5ppm
20 . 0	500.00120	< 2.5ppm
30 . 0	500.00120	< 2.5ppm
40 . 0	500.00120	< 2.5ppm
50 . 0	500.00108	< 2.5ppm

Tester

Signature: _____

_____ Name: Erik D. Collins

FREQUENCY STABILITY WITH VARIATION OF PRIMARY SUPPLY VOLTAGE

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

Model: S Series (Models SRU50A, SRU50B, &
SRU50C)

TABLE 9A
SRU50A

VOLTAGE	FREQUENCY (MHz)	FCC DEVIATION
11.7	420.00058	< 2.5ppm
12.8	420.00052	< 2.5ppm

13.8	420.00052	< 2.5ppm
14.8	420.00052	< 2.5ppm
15.9	420.00058	< 2.5ppm

Tester

Signature: _____

_____ **Name:** Erik D. Collins

FREQUENCY STABILITY WITH VARIATION OF PRIMARY SUPPLY VOLTAGE

Test Date: July 8-13, 1998

UST Project: 98-280

Customer: RELM Communications

**Model: S Series (Models SRU50A, SRU50B, &
SRU50C)**

**TABLE 9B
SRU50B**

VOLTAGE	FREQUENCY (MHz)	FCC DEVIATION
11.7	460.00078	< 2.5ppm
12.8	460.00076	< 2.5ppm
13.8	460.00078	< 2.5ppm
14.8	460.00078	< 2.5ppm
15.9	460.00078	< 2.5ppm

Tester

Signature: _____

Name: Erik D. Collins

FREQUENCY STABILITY WITH VARIATION OF PRIMARY SUPPLY VOLTAGE

Test Date: July 8-13, 1998
UST Project: 98-280
Customer: RELM Communications
Model: S Series (Models SRU50A, SRU50B, & SRU50C)

**TABLE 9C
SRU50C**

VOLTAGE	FREQUENCY (MHz)	FCC DEVIATION
11.7	500.00120	< 2.5ppm
12.8	500.00120	< 2.5ppm
13.8	500.00120	< 2.5ppm
14.8	500.00104	< 2.5ppm
15.9	500.00114	< 2.5ppm

Tester

Signature: _____

Name: Erik D. Collins

MEASUREMENT PROCEDURE

Subpart 90.214

TRANSIENT FREQUENCY BEHAVIOR

Information regarding this requirement has been supplied by RELM Communications. The data is shown in Figure 4.

TRANSIENT FREQUENCY BEHAVIOR

Figure 4A
SRU50A

Refer to file fig4a.jpg

TRANSIENT FREQUENCY BEHAVIOR

Figure 4B
SRU50B

Refer to file fig4b.jpg

TRANSIENT FREQUENCY BEHAVIOR

Figure 4C
SRU50C

Refer to file fig4c.jpg