Prüfbericht-Nr.: *Test Report No.:*	**10053819 001**	**Auftrags-Nr.:** *Order No.:*	114041127	Seite 1 von 44 *Page 1 of 44*
Kunden-Referenz-Nr.: *Client Reference No.:*	N/A	**Auftragsdatum:** *Order date:*	13-Aug-2015	
Auftraggeber: *Client:*	Global Power international Group Ltd., 2F, NO363, FU-SHING S. RD, SEC.2, TAIPEI TW			
Prüfgegenstand: *Test item:*	Bluetooth Speaker			
Bezeichnung / Typ-Nr.: *Identification / Type No.:*	DP1301ADB			
Auftrags-Inhalt: *Order content:*	FCC Part 15C / IC RSS-247 Test report			
Prüfgrundlage: *Test specification:*	FCC 47CFR Part 15: Subpart C Section 15.247 RSS-247 (05-2015)			

Wareneingangsdatum: *Date of receipt:*	9-Oct-2015
Prüfmuster-Nr.: *Test sample No.:*	A000261439-001 A000261439-001
Prüfzeitraum: *Testing period:*	19-Oct-2015 - 23-Oct-2015
Ort der Prüfung: *Place of testing:*	EMC Laboratory Taipei
Prüflaboratorium: *Testing laboratory:*	TUV Rheinland Taiwan Ltd.
Prüfergebnis*: *Test result*:*	Pass



geprüft von / *tested by:*			**kontrolliert von** / *reviewed by:*		
2016-02-22	Ryan W. T. Chen / Project Manager		2016-02-22	Rene Charton/Senior Project Manager	
Datum *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*	**Datum** *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*

Sonstiges / *Other:*

Zustand des Prüfgegenstandes bei Anlieferung:
Condition of the test item at delivery:

Prüfmuster vollständig und unbeschädigt
Test item complete and undamaged

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend:	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT
RESULT: Passed

5.1.2 PEAK OUTPUT POWER
RESULT: Passed

5.1.3 20DB BANDWIDTH
RESULT: Passed

5.1.4 99% BANDWIDTH
RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100KHZ BANDWIDTH
RESULT: Passed

5.1.6 SPURIOUS EMISSION
RESULT: Passed

5.1.7 FREQUENCY SEPARATION
RESULT: Passed

5.1.8 NUMBER OF HOPPING FREQUENCY
RESULT: Passed

5.1.9 TIME OF OCCUPANCY
RESULT: Passed

5.2.1 MAINS CONDUCTED EMISSIONS
RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS
RESULT: Passed

Contents

1. GENERAL REMARKS 5
1.1 COMPLEMENTARY MATERIALS 5
2. TEST SITES 6
2.1 TEST LABORATORY 6
2.2 TEST FACILITY 6
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS 7
2.4 TRACEABILITY 8
2.5 CALIBRATION 8
2.6 MEASUREMENT UNCERTAINTY 8
3. GENERAL PRODUCT INFORMATION 9
3.1 PRODUCT FUNCTION AND INTENDED USE 9
3.2 SYSTEM DETAILS AND RATINGS 9
3.3 INDEPENDENT OPERATION MODES 10
3.4 NOISE GENERATING AND NOISE SUPPRESSING PARTS 11
3.5 SUBMITTED DOCUMENTS 11
4. TEST SET-UP AND OPERATION MODES 12
4.1 PRINCIPLE OF CONFIGURATION SELECTION 12
4.2 TEST OPERATION AND TEST SOFTWARE 12
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 12
4.4 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 13
4.5 TEST SETUP DIAGRAM 13
5. TEST RESULTS 15
5.1 TRANSMITTER REQUIREMENT & TEST SUITES 15
5.1.1 Antenna Requirement 15
5.1.2 Peak Output Power 16
5.1.3 20dB Bandwidth 17
5.1.4 99% Bandwidth 21
5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth 22
5.1.6 Spurious Emission 30
5.1.7 Frequency Separation 31
5.1.8 Number of hopping frequency 33
5.1.9 Time of Occupancy 35
5.2 MAINS EMISSIONS 38
5.2.1 Mains Conducted Emissions 38

6. SAFETY HUMAN EXPOSURE 39

6.1 RADIO FREQUENCY EXPOSURE COMPLIANCE 39

6.1.1 Electromagnetic Fields 39

7. PHOTOGRAPHS OF THE TEST SET-UP 40

8. LIST OF TABLES 44

9. LIST OF PHOTOGRAPHS 44

1. General Remarks

1.1 Complementary Materials

The following attachments are integral parts of this test report:

Appendix P: Photo Documentation
(File Name: 10053819APPENDIX P)
Appendix D: Test Result of Radiated Emissions
(File Name: 10053819APPENDIX D)

Test Specifications

The following standards were applied

Table 1: Applied Standard and Test Levels

Radio
FCC CFR47 Part 15: Subpart C Section 15.247 RSS-247 Issue 1 May 2015 RSS-Gen, Issue 4, November 2014 ANSI C63.10:2013 Public Notice DA 00-705 NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2011)(100年6月28日)

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,
Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facility

TUV Rheinland Taiwan Ltd.
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC RegistrationNo.: 799772
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2013-Jul-1st to 2016-Jun-30th

Testing Laboratory
0759

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Last Calibration	Next Calibration
EMI Test Receiver	R&S	ESR7	101062	10-Sep-15	19-Sep-16
Bilog Antenna	TESEQ	CBL6111D	29802	4-Jul-14	3-Jul-16
Spectrum Analyzer	R&S	FSV 40	100921	17-Dec-14	16-Dec-15
Spectrum Analyzer	Agilent	N9010A	MY53470241	1-Apr-15	30-Mar-16
Horn Antenna	ETS-Lindgren	3117	138160	12-Jan-15	11-Jan-17
Horn Antenna (18GHz~40GHz)	COM-POWER	AH840	101031	30-Oct-13	29-Oct-15
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	24-Dec-14	24-Dec-15
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	26-Aug-14	26-Aug-16
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM30180	60558	4-Nov-14	3-Nov-15
EMI Test Receiver	R&S	ESCI7	100797	28-Dec-14	27-Dec-15
Spectrum Analyzer	R&S	FSL3	101943	7-Sep-15	7-Sep-16
LISN (1 phase)	R&S	ENV216	101243	1-Jun-15	31-May-16
LISN	R&S	ENV216	101262	16-Jun-15	15-Jun-16

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basics using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements:.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
RF power, conducted	± 1.5 dB
Adjacent channel power	± 3 dB
Radiated emission of transmitter, valid up to 26 GHz	± 6 dB
Radiated emission of receiver, valid up to 26 GHz	± 6 dB
Temperature	± 2 ºC
Humidity	± 10 %

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Bluetooth Speaker. It contains a Bluetooth 3.0 EDR compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment	Bluetooth Speaker
Type Designation	DP1301ADB
FCC ID	ARZAA15001

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Spacing	1 MHz
Channel number	79
Operation Voltage	5Vdc
Modulation	GFSK, π/4 DQPSK, 8 DPSK
Antenna gain	3.51 dBi

Table 6: Frequency hopping information

Technical Specification	Description
Hopping Range	Hereby we declare that the maximum frequency of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V2.1+EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04).
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73, 07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56, 69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43, 15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings. Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

3.3 Independent Operation Modes

The basic operation modes are:

A. Transmitting
   1. Low channel
   2. Middle channel
   3. High channel
B. Receiving

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 4. All testing were performed according to the procedures in ANSI C63.10: 2013 and DA 00-705 of March 30, 2000.

The samples were used as follows:
Conducted: **A000261439-001**
Radiation: **A000261439-001**

Full test was applied on all test modes, but only worst case was shown.

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested containing the noise suppression parts as in the Photo Appendix and the Test Setup Photos. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement



Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: **Passed**

Test standard	:	LP0002(2011): 2.2, 3.10.1, (3) FCC Part 15.247(b)(4), Part 15.203 and RSS-Gen 8.3
Requirement	:	use of approved antennas only with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.51 dBi dBi. The antenna is Monopole Antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT: **Passed**

Test standard	:	FCC Part 15.247(b)(1), RSS-247 5.4(2) LP0002(2011): 3.10.1, (2)
Basic standard	:	DA 00-705 of March 30, 2000 LP0002(2011) Appendix II
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A

Ambient temperature	:	22-26 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa

Table 7: Test result of Peak Output Power, GFSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	-6.55	0.00022	0.125
Middle Channel	2441	-7.88	0.00016	0.125
High Channel	2480	-6.82	0.00021	0.125

Table 8: Test result of Peak Output Power, 8DPSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	-7.50	0.00018	0.125
Middle Channel	2441	-8.43	0.00014	0.125
High Channel	2480	-7.30	0.00019	0.125

Pmax: 0.2213 mW

5.1.3 20dB Bandwidth

RESULT: **Passed**

Test standard	:	FCC Part 15.247(a)(1), RSS-247 5.1(1) LP0002(2011): 3.10.1, (6.1.1)
Basic standard	:	DA 00-705 of March 30, 2000 LP0002(2011) Appendix II

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103kPa

Table 9: Test result of 20dB Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	945.6	1.5	Pass
Mid Channel	2441	944.3	1.5	Pass
High Channel	2480	942.7	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.

Table 10: Test result of 20dB Bandwidth, 8DPSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	1259	1.5	Pass
Mid Channel	2441	1258	1.5	Pass
High Channel	2480	1258	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.
If the carrier separation frequency of a Bluetooth Device is set at 1 MHz due to the firmware setting and the Bluetooth Standard, then the limit for the 20 dB Bandwidth, becomes 1 MHZ / 0.66666 = 1.5 MHz.

Test Plot of 20dB Bandwidth, GFSK modulation

Low Channel



Middle Channel



High Channel



Test Plot of 20dB Bandwidth, 8DPSK modulation

Low Channel



Middle Channel



High Channel



5.1.4 99% Bandwidth

RESULT: **Passed**

Test standard	:	RSS-Gen (Issue 4)
Basic standard	:	RSS-Gen (Issue 4)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103kPa

Table 11: Test result of 99% Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)
Mid Channel	2441	874.17

Table 12: Test result of 99% Bandwidth, PSK modulation

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Mid Channel	2441	1.1584

5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

RESULT: **Passed**

Test standard	:	FCC part 15.247(d), RSS-247 5.5 LP0002(2011): 3.10.1, (5)
Basic standard	:	DA 00-705 of March 30, 2000 LP0002(2011) Appendix II
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achived as well.
Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Test Plot of 100kHz Conducted Emissions, GFSK modulation

Low Channel



Middle Channel

High Channel

Test Plot of 100kHz Conducted Emissions, 8DPSK modulation

Low Channel

Middle Channel

High Channel



Test Plot of 100kHz Bandwidth of Frequency Band Edge, GFSK modulation

Low Channel



High Channel



Hopping ON

Keysight Spectrum Analyzer - Swept SA
Display Line -27.59 dBm
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 10 dB
Avg Type: Log-Pwr
08:42:55 PM Oct 22, 2015
Ref Offset 1.8 dB
10 dB/div
Ref 1.80 dBm
Log
Mkr1 2.405 80 GHz
-7.59 dBm
-27.59 dBm
Start 2.38000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 11.53 ms (1001 pts)
1 N 1 f 2.405 80 GHz -7.59 dBm
2 N 1 f 2.400 00 GHz -58.290 dBm
3 N 1 f 2.483 50 GHz -73.605 dBm
Display
Annotation
Title
Graticule
Display Line
System Display Settings

Test Plot of 100kHz Bandwidth of Frequency Band Edge, 8DPSK modulation

Low Channel



High Channel



Hopping ON


Keysight Spectrum Analyzer - Swept SA
Display Line -28.36 dBm
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 10 dB
Avg Type: Log-Pwr
08:42:21 PM Oct 22, 2015
Ref Offset 1.8 dB
10 dB/div
Ref 1.80 dBm
Log
Mkr1 2.406 88 GHz
-8.355 dBm
-28.36 dBm
Start 2.38000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 11.53 ms (1001 pts)
1 N 1 f 2.406 88 GHz -8.355 dBm
2 N 1 f 2.400 00 GHz -61.673 dBm
3 N 1 f 2.483 50 GHz -74.390 dBm
Display
Annotation
Title
Graticule
Display Line
System Display Settings

5.1.6 Spurious Emission

RESULT: **Passed**

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-210 2.2, RSS-247 5.5 and RSS-Gen 8.9 LP0002(2011): 3.10.1, (5)
Basic standard	:	ANSI C63.10
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4, 8.9 (Table 4 and 5). Radiated emissions which fall in the restricted bands, as defined in LP0002(2011): 2.7 , must comply with the radiated emission limits specified in LP0002(2011): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2011): 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

5.1.7 Frequency Separation

RESULT: **Passed**

Test standard	:	FCC part 15.247(a)(1) RSS-247 5.1 LP0002(2011): 3.10.1, (6.1.1)
Basic standard	:	DA 00-705 of March 30, 2000 LP0002(2011) Appendix II
Limit	:	≥ 25kHz or 2/3 of 20dB bandwidth, whichever is greater

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	24℃
Relative humidity	:	53%

Table 13: Test result of Frequency Separation

Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
Record Channel	2441	1	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Record Channel adj 1	2440			
Record Channel adj 2	2442			

Test Plot of Frequency Separation

GFSK



5.1.8 Number of hopping frequency

RESULT: **Passed**

Test standard	:	FCC part 15.247(a)(1)(iii) RSS-247 5.1(5) LP0002(2011): 3.10.1, (6.1.2)
Basic standard	:	DA 00-705 of March 30, 2000 LP0002(2011) Appendix II

Test setup

Test Channel	:	Hopping On

Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 14: Test result of Number of hopping frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2400 to 2483.5 MHz	79	≥15	Pass

Test Plot of Number of hopping frequencies





5.1.9 Time of Occupancy

RESULT: **Passed**

Test standard	:	FCC part 15.247(a)(1)(iii) RSS-247 5.1(5) LP0002(2011): 3.10.1, (6.1.2)
Basic standard	:	DA 00-705 of March 30, 2000 LP0002(2011) Appendix II
Limits	:	0.4s
Kind of test site	:	Shield room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 15: Test result of Time of Occupancy

Data Mode	Captured Burst (s)	Dwell time (s)	On+Off time (s)	Limit (s)	Result
DH5	0.00294	0.3128	0.00376	0.4	Pass
3DH5	0.00294	0.3128	0.00376	0.4	Pass

Note:
Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds.

Hopping rate = 1 / (On+Off time) = 266 Hz

Test Plot of Time of Occupancy, GFSK modulation





Test Plot of Time of Occupancy, 8DPSK modulation



5.2 Mains Emissions

5.2.1 Mains Conducted Emissions

RESULT: **Passed**

Test standard	:	FCC Part 15.207 FCC Part 15.107 RSS-Gen 8.8 LP0002: 2.3
Limits	:	Mains Conducted emissions as defined in above test standards must comply with the mains conducted emission limits specified
Kind of test site	:	Shielded Room

Test setup

Test Channel	:	Middle
Operation mode	:	A

Remark: For details refer to Appendix D.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: **Passed**

Test standard : FCC KDB Publication 447498

Since maximum peak output power of the transmitter is 0.2213mW <1mW, hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498 D01: Mobile Portable RF Exposure..

7. Photographs of the Test Set-Up

Photograph 1: Set-up for Spurious Emissions (Front View)



Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)



Photograph 4: Set-up for Conducted testing

Photograph 5: Set-up for for Mains Conducted testing Back



Photograph 6: Set-up for for Mains Conducted testing Front

8. List of Tables

Table 1: Applied Standard and Test Levels 5
Table 2: List of Test and Measurement Equipment 7
Table 3: Emission Measurement Uncertainty.....8
Table 4: Basic Information of EUT 9
Table 5: Technical Specification of EUT 9
Table 6: Frequency hopping information.....10
Table 7: Test result of Peak Output Power, GFSK modulation.....16
Table 8: Test result of Peak Output Power, 8DPSK modulation.....16
Table 9: Test result of 20dB Bandwidth, GFSK modulation.....17
Table 10: Test result of 20dB Bandwidth, 8DPSK modulation.....17
Table 11: Test result of 99% Bandwidth, GFSK modulation.....21
Table 12: Test result of 99% Bandwidth, PSK modulation.....21
Table 13: Test result of Frequency Separation 31
Table 14: Test result of Number of hopping frequency.....33
Table 15: Test result of Time of Occupancy.....35

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....40
Photograph 2: Set-up for Spurious Emissions (Back View 1).....41
Photograph 3: Set-up for Spurious Emissions (Back View 2).....42
Photograph 4: Set-up for Conducted testing.....42
Photograph 5: Set-up for for Mains Conducted testing Back.....43
Photograph 6: Set-up for for Mains Conducted testing Front.....43