

Lucent Technologies
Bell Labs Innovations



**Federal Communications Commission
Office of Engineering and Technology
Equipment Authorization Division,
Application Processing Branch**

Lucent Technologies Inc.
67 Whippany Road
Whippany, NJ 07981

July 12, 1999

Federal Communications Commission
Office of Engineering and Technology
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, Maryland 21046

Dear Examiner:

In accordance with Parts 2 and 24 of the Commission's Rules and Regulations, we are submitting herewith, statements and supporting data to show compliance with the requirements of the Commission for Product Certification of the Lucent Technologies Corp. Ultra Linear Amplifier Module/ Multi Carrier Amplifier, henceforth **ULAM**, **FCC ID: AS5CMP-34**. This **ULAM** is used in Lucent Technologies Corp **FLEXENT**® Land Station Cellular system using Code Division Multiple Access (CDMA) technology, for use in Domestic Personal Communication Services.

This application for the **ULAM**, under **FCC ID: AS5CMP-34**, is for operation in PCS Blocks A and B. The **ULAM** is capable of operation in all PCS Blocks but production filters are only available at time of filing for the tested Blocks.

The **ULAM** is a nominally 32 Watt Class A CW amplifier designed to provide 16 watts of long term average power per carrier at the antenna connection port. The **ULAM** is configurable in a single, dual or three amplifier "Multi Carrier Amplifier" (**MCA**) with external passive signal combiners and splitters. The **ULAM/ MCA** provides 16 watts per carrier in each of the **MCA** configurations (single, dual or three amplifier) with total RF Power of 16, 32 or 48 watts for each of the respective configurations. Under the dynamics conditions of CDMA service a maximum of 16 watts per carrier/ 48 Watts total will be available at the antenna port and this value is used for this filing.

The data summarized below is in the form presently used by the Commission's Radio Equipment List.

Manufacturer	Lucent Technologies, Inc.
Equipment Identification	AS5CMP-34
Rules Part Number	24 (E)
Frequency Range	1930-1945 MHz and 1950-1965 MHz: PCS Blocks A and B
Output Power	0.16 to 16.0 Watts/carrier - 48 Watts Total: Varied By Software
Frequency Tolerance	+/- 0.5 ppm
Emission Designator	1M25G9W

The unit is called the PCS Ultra Linear Amplifier Module/ Multi Carrier Amplifier. It is designed to the limitations specified in Part 24 subpart E. Whenever possible, the test procedures defined in CFR 47 Parts 2 and 24(E) were followed. Because of the "state of the art" nature of this equipment, some of the characteristics cannot be tested using the requirements in CFR 47. For those characteristics ANSI J-STD-008 were used to define the tests and evaluation criteria used in this application. The **ULAM** rating at the amplifier output has a listed power output of 0.32 to 32.0 watts. Losses internal to the cabinet and Multi Carrier Amplifier configuration will limit the long term average output power to 16.0 watts/ carrier when measured at the (J4) antenna connector. The total power is limited by the latter value is the level for this application. The actual power levels delivered by the **ULAM** are under the software control of the Mobile Switching Center of the local PCS system. The software control only allows for adjustment in power up to the 16.0 Watt maximum. This filing to operate the **ULAM/ AS5CMP-34** is based upon signals supplied to the **ULAM** by a Lucent Technologies Inc. CDMA Baseband Radio 1900 (**CBR-1900** henceforth **CBR**), **FCC ID: AS5CMP-26**, granted 23 March 1999 for all PCS Blocks.

This application for **AS5CMP-34**, is for PCS Blocks "A" and "B". The amplifier is capable of operation in all PCS Blocks but production transmit filters for other PCS Blocks are not yet available. Since this application encompasses the single, dual and three carrier configurations it presents the required test data for each of those **ULAM/ MCA** operational configurations.

The **ULAM/ AS5CMP-34** is produced by Lucent Technologies Inc. solely for incorporation into Lucent Technologies Inc. products. The **CBR/ AS5CMP-26** is a Lucent Technologies Inc. designed and manufactured products.

Enclosed in this electronically transmitted online package is a copy of FCC Form 731 (Application for Equipment Authorization - Radio Frequency Devices) and the required exhibits. These exhibits contain the technical data, and the required statements and documents for Product Certification. The technical contact at Lucent Technologies, Bell Laboratories, will comply with any request for additional information should the need arise.

Sincerely,

R.J.Pillmeier
Member Technical Staff
Cell Test and Field Support
Phone: 973-386-3837
email: rpillmeier@lucent.com

Att
FCC Form 731 w/ Attachments

Technical Contact
W. Steve Majkowski
Phone 973-386-3812
email: majkowski@lucent.com

TABLE OF CONTENTS

Exhibit 1	Section 2.911 (d)	Qualifications and Certifications
Exhibit 2	Section 2.1033(a) (b) (c)	Manufactures, Identification, Production
Exhibit 3	Section 2.1033(c) (1-5)	Emission, Freq. Range, Power Level
Exhibit 4	Section 2.1033(c) (8)	Active Circuit Devices Drive Levels
Exhibit 5	Section 2.1033(c) (10)	Complete Circuit Diagrams
Exhibit 6	Section 2.1033(c) (3)	Instruction Book
Exhibit 7	Section 2.1033(c) (9)	Tune-Up procedure
Exhibit 8	Section 2.1033(c) (10)	Circuitry for determining frequency
Exhibit 9	Section 2.1033(c) (11)	Circuitry for Suppression of Spurious
Exhibit 10	Section 2.1033(c) (13)	Description of Modulation System
Exhibit 11	Section 2.1033(e)	Listing of Required Measurements
Exhibit 12	Section 2.1046	Measurement of Radio Frequency Power Output
Exhibit 13	Section 2.1047	Measurement of Modulation Characteristics
Exhibit 14	Section 2.1049	Measurement of Occupied Bandwidth
Exhibit 15	Section 2.1051	Measurement of Spurious Emissions at Antenna
Exhibit 16	Section 2.1053	Field Strength of Spurious Radiation
Exhibit 17	Section 2.1055	Measurement of Frequency Stability
Exhibit 18	Section 2.1033(f)	Drawing of the Identification Label
Exhibit 19	Section 2.1033(g)	Photographs of the Equipment
Exhibit 20		Human Exposure Compliance Sheet
Exhibit 21		Test Equipment List

EXHIBITS TO BE KEPT CONFIDENTIAL

Exhibit 4	Section 2.1033(c) (6)	Function of Active Circuit Devices
Exhibit 5	Section 2.1033(c) (7)	Complete Circuit Diagrams
Exhibit 6	Section 2.1033(c) (8)	Instruction Book
Exhibit 7	Section 2.1033(c) (9)	Tune-Up procedure
Exhibit 8	Section 2.1033(c) (10)	Circuitry for determining frequency
Exhibit 9	Section 2.1033(c) (11)	Circuitry for Suppression of Spurious