


10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
 - Centre Frequency: The centre frequency of the middle hopping channel.
 - Resolution BW: 10 MHz.
 - Video BW: 10 MHz.
 - Span: Zero span.
 - Detector: Peak.
 - Trace Mode: Clear Write.
 - Sweep: Video Trigger
- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle


10.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.8℃,29.1%RH	Test Date:	2026.01.08
Test Power Supply:	DC 12V	Sample Number:	S25111816-003


Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2412	12.42	12.60	98.57
		2437	12.44	12.56	99.04
		2462	12.44	12.52	99.36
11G	Ant1	2412	2.07	2.23	92.83
		2437	2.07	2.17	95.39
		2462	2.07	2.19	94.52
11N20SISO	Ant1	2412	1.93	2.08	92.79
		2437	1.92	2.07	92.75
		2462	1.93	2.01	96.02
11N40SISO	Ant1	2422	0.94	1.10	85.45
		2437	0.95	1.10	86.36
		2452	0.95	1.07	88.79

10.5. Test graphs









11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


12. Radiated Emission

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak)	
		54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m

18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m
-----------------	-----------------------------	-----

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

(12) The worst simultaneous case and was recorded.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-07

Tested By:

Li Xiongbin

Test Mode:

TX 11B 2412MHz

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Below 1G\13

Memo:

Sample Number:S25111816-003



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	82.922	43.21	8.90	4.21	24.02	40.00	15.98	QP	Horizontal
2	196.574	46.47	10.41	4.86	29.34	43.50	14.16	QP	Horizontal
3	233.417	51.7	11.72	5.01	36.03	46.00	9.97	QP	Horizontal
4	239.888	49.64	12.48	5.04	34.76	46.00	11.24	QP	Horizontal
5	308.336	46.78	13.63	5.32	33.32	46.00	12.68	QP	Horizontal
6	331.660	47.43	14.37	5.42	34.79	46.00	11.21	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-07

Tested By:

Li Xiongbín

Test Mode:

TX 11B 2412MHz

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Below 1G\14

Memo:

Sample Number:S25111816-003



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	54.217	41.03	13.25	4.01	25.99	40.00	14.01	QP	Vertical
2	82.922	48.6	8.90	4.21	29.41	40.00	10.59	QP	Vertical
3	95.942	43.31	11.14	4.28	26.43	43.50	17.07	QP	Vertical
4	193.158	45.24	9.78	4.84	27.47	43.50	16.03	QP	Vertical
5	239.888	42.1	12.48	5.04	27.22	46.00	18.78	QP	Vertical
6	557.621	41.22	17.78	6.25	32.51	46.00	13.49	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11N20 2412MHz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\1

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3871.300	46.31	30.56	4.55	-39.65	41.77	74.00	32.23	PK	Horizontal
2	4867.500	45.44	32.97	5.16	-39.79	43.78	74.00	30.22	PK	Horizontal
3	7434.500	43.73	36.63	5.77	-39.86	46.27	74.00	27.73	PK	Horizontal
4	9044.400	41.90	38.86	6.79	-38.65	48.90	74.00	25.10	PK	Horizontal
5	10922.900	41.73	39.62	7.35	-39.61	49.09	74.00	24.91	PK	Horizontal
6	11392.100	41.34	39.71	7.57	-39.60	49.02	74.00	24.98	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbn

Test Mode:

11N20 2412MHz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\2

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4221.500	46.33	31.09	4.72	-39.72	42.42	74.00	31.58	PK	Vertical
2	4845.400	45.02	32.83	5.14	-39.78	43.21	74.00	30.79	PK	Vertical
3	7393.700	43.74	36.74	5.76	-39.86	46.38	74.00	27.62	PK	Vertical
4	9146.400	42.06	38.93	6.78	-38.76	49.01	74.00	24.99	PK	Vertical
5	11409.100	41.21	39.71	7.57	-39.60	48.89	74.00	25.11	PK	Vertical
6	12162.200	42.25	39.31	7.81	-39.47	49.90	74.00	24.10	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11N20 2437Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\3

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3862.800	46.87	30.45	4.55	-39.65	42.22	74.00	31.78	PK	Horizontal
2	5013.700	44.94	33.03	5.26	-39.80	43.43	74.00	30.57	PK	Horizontal
3	7397.100	44.27	36.72	5.76	-39.86	46.89	74.00	27.11	PK	Horizontal
4	9080.100	42.48	38.36	6.79	-38.69	48.94	74.00	25.06	PK	Horizontal
5	11147.300	42.13	38.85	7.47	-39.60	48.85	74.00	25.15	PK	Horizontal
6	11997.300	42.28	38.99	7.81	-39.60	49.48	74.00	24.52	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N20 2437Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\4

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4053.200	46.47	31.19	4.61	-39.71	42.56	74.00	31.44	PK	Vertical
2	4865.800	44.60	32.96	5.16	-39.79	42.93	74.00	31.07	PK	Vertical
3	7443.000	43.69	36.61	5.78	-39.86	46.22	74.00	27.78	PK	Vertical
4	9059.700	42.21	38.73	6.79	-38.67	49.06	74.00	24.94	PK	Vertical
5	11392.100	41.05	39.71	7.57	-39.60	48.73	74.00	25.27	PK	Vertical
6	12209.800	41.87	39.22	7.81	-39.43	49.47	74.00	24.53	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N20 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\5

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3830.500	46.82	30.53	4.55	-39.63	42.27	74.00	31.73	PK	Horizontal
2	4984.800	45.25	33.03	5.24	-39.80	43.72	74.00	30.28	PK	Horizontal
3	7376.700	43.83	36.84	5.75	-39.86	46.56	74.00	27.44	PK	Horizontal
4	9058.000	41.79	38.76	6.79	-38.66	48.68	74.00	25.32	PK	Horizontal
5	10805.600	42.18	39.03	7.27	-39.62	48.86	74.00	25.14	PK	Horizontal
6	11779.700	42.54	38.58	7.72	-39.60	49.24	74.00	24.76	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11N20 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\6

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3941.000	46.52	30.41	4.56	-39.68	41.81	74.00	32.19	PK	Vertical
2	4872.600	44.87	32.99	5.16	-39.79	43.23	74.00	30.77	PK	Vertical
3	7507.600	44.03	36.79	5.80	-39.85	46.77	74.00	27.23	PK	Vertical
4	9114.100	42.32	38.28	6.79	-38.73	48.66	74.00	25.34	PK	Vertical
5	10914.400	42.36	39.61	7.35	-39.61	49.71	74.00	24.29	PK	Vertical
6	12082.300	41.86	39.41	7.81	-39.53	49.55	74.00	24.45	PK	Vertical

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11B 2412Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\7

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2385.698	21.35	27.49	3.77	0.00	52.61	74.00	21.39	PK	Horizontal
2	2390.000	17.45	27.46	3.78	0.00	48.69	74.00	25.31	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2385.698	15.40	27.49	3.77	46.66	54.00	7.34	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11B 2412Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\8

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2354.954	19.90	27.67	3.74	0.00	51.31	74.00	22.69	PK	Vertical
2	2390.000	16.74	27.46	3.78	0.00	47.98	74.00	26.02	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2354.954	15.51	27.67	3.74	46.92	54.00	7.08	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11B 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\9

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.66	27.54	3.88	0.00	50.08	74.00	23.92	PK	Horizontal
2	2483.755	23.57	27.54	3.88	0.00	54.99	74.00	19.01	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.755	16.35	27.54	3.88	47.77	54.00	6.23	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11B 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\10

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.91	27.54	3.88	0.00	50.33	74.00	23.67	PK	Vertical
2	2487.820	21.53	27.58	3.88	0.00	52.99	74.00	21.01	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2487.820	15.62	27.58	3.88	47.08	54.00	6.92	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11G 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\11

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	27.21	27.54	3.88	0.00	58.63	74.00	15.37	PK	Horizontal
2	2483.920	31.49	27.54	3.88	0.00	62.91	74.00	11.09	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	16.77	27.54	3.88	48.19	54.00	5.81	AV	Horizontal	
2	2483.691	16.68	27.54	3.88	48.10	54.00	5.90	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11G 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\12

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	23.21	27.54	3.88	0.00	54.63	74.00	19.37	PK	Vertical
2	2483.950	28.77	27.54	3.88	0.00	60.19	74.00	13.81	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	16.17	27.54	3.88	47.59	54.00	6.41	AV	Vertical	
2	2483.955	15.68	27.54	3.88	47.10	54.00	6.90	AV	Vertical	

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11G 2412Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\13

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.394	24.38	27.46	3.77	0.00	55.61	74.00	18.39	PK	Horizontal
2	2390.000	20.37	27.46	3.78	0.00	51.61	74.00	22.39	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2389.394	16.14	27.46	3.77	47.37	54.00	6.63	AV	Horizontal	
2	2390.000	15.80	27.46	3.78	47.04	54.00	6.96	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11G 2412Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\14

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.324	20.43	27.46	3.77	0.00	51.66	74.00	22.34	PK	Vertical
2	2390.000	18.14	27.46	3.78	0.00	49.38	74.00	24.62	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2389.324	15.74	27.46	3.77	46.97	54.00	7.03	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N20 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\15

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	23.25	27.54	3.88	0.00	54.67	74.00	19.33	PK	Horizontal
2	2484.033	24.74	27.54	3.88	0.00	56.16	74.00	17.84	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.362	15.92	27.54	3.88	47.34	54.00	6.66	AV	Horizontal	
2	2483.995	16.03	27.54	3.88	47.45	54.00	6.55	AV	Horizontal	

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11N20 2462Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\16

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	22.16	27.54	3.88	0.00	53.58	74.00	20.42	PK	Vertical
2	2485.090	24.33	27.55	3.88	0.00	55.76	74.00	18.24	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	15.88	27.54	3.88	47.30	54.00	6.70	AV	Vertical	
2	2485.090	16.07	27.55	3.88	47.50	54.00	6.50	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N20 2412Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\17

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2389.268	23.24	27.46	3.77	0.00	54.47	74.00	19.53	PK	Horizontal
2	2390.000	18.70	27.46	3.78	0.00	49.94	74.00	24.06	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity	
1	2389.268	16.57	27.46	3.77	47.80	54.00	6.20	AV	Horizontal	

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N20 2412Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\18

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2389.590	23.82	27.46	3.77	0.00	55.05	74.00	18.95	PK	Vertical
2	2390.000	19.28	27.46	3.78	0.00	50.52	74.00	23.48	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity	
1	2389.590	16.41	27.46	3.77	47.64	54.00	6.36	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11N40 2452Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\19

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	28.22	27.54	3.88	0.00	59.64	74.00	14.36	PK	Horizontal
2	2486.643	29.47	27.57	3.88	0.00	60.92	74.00	13.08	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	17.63	27.54	3.88	49.05	54.00	4.95	AV	Horizontal	
2	2486.393	17.29	27.57	3.88	48.74	54.00	5.26	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbin

Test Mode:

11N40 2452Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\20

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	22.81	27.54	3.88	0.00	54.23	74.00	19.77	PK	Vertical
2	2484.130	27.33	27.54	3.88	0.00	58.75	74.00	15.25	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	16.70	27.54	3.88	48.12	54.00	5.88	AV	Vertical	
2	2484.350	17.41	27.54	3.88	48.83	54.00	5.17	AV	Vertical	

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N40 2422Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\21

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.994	26.74	27.47	3.77	0.00	57.98	74.00	16.02	PK	Horizontal
2	2390.000	25.60	27.46	3.78	0.00	56.84	74.00	17.16	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2388.032	16.50	27.47	3.77	47.74	54.00	6.26	AV	Horizontal	
2	2389.901	16.55	27.46	3.78	47.79	54.00	6.21	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-06

Tested By:

Li Xiongbín

Test Mode:

11N40 2422Hz TX Mode

Power Supply:

DC 12V

Condition:

Temp:23.6°C;Humi:48.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111816-1E\FCC Above 1G 2.4G\22

Memo:

Sample Number:S25111816-003



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.604	24.00	27.46	3.77	0.00	55.23	74.00	18.77	PK	Vertical
2	2390.000	21.04	27.46	3.78	0.00	52.28	74.00	21.72	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2389.604	16.41	27.46	3.77	47.64	54.00	6.36	AV	Vertical	
2	2390.000	16.23	27.46	3.78	47.47	54.00	6.53	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

15. Photos of the EUT

Please refer to DDT-Q25111816-2E appendix I

-----End Report-----