

## RADIO TEST REPORT


The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

Applicant : Action Electronics Co.,Ltd.  
Address : 2480,TINGKAT PERUSAHAAN ENAM,PRAI FREE TRADE ZONE,  
13600, PERAI,, PENANG, Malaysia  
Manufacturer /Factory : ACTION ASIA (SHENZHEN) CO., LTD  
Address : 4 Floor, Block 1, No.25 Jinxing Industrial Park, Jian'an Road, Fuyong  
Town, Bao'an District, Shenzhen, China  
E.U.T. : 10.1" IN-CAR SEATBACK MONITOR  
Brand Name : VOXX, moviestoGO, Audiovox  
Model No. : SB10M1, SBA71012, SBB71013, SB10UHD  
(For model difference, refer to section 1.)  
FCC ID : AT19R3SBA71012  
Measurement Standard : FCC PART 15.247: 2017  
Date of Receiver : October 12, 2018  
Date of Test : October 12, 2018 to October 26, 2018  
Date of Report : October 26, 2018

This Test Report is Issued Under the Authority of :

Prepared by

Approved & Authorized Signer

  
Rose Hu / Engineer

  
Jori Fan / Authorized Signatory

This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.

## Table of Contents

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                        | <b>5</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST .....     | 5         |
| 1.2 RELATED SUBMITTAL(S) / GRANT (S) .....                 | 5         |
| 1.3 TEST METHODOLOGY .....                                 | 7         |
| 1.4 EQUIPMENT MODIFICATIONS .....                          | 7         |
| 1.5 SUPPORT DEVICE .....                                   | 7         |
| 1.6 TEST FACILITY AND LOCATION .....                       | 8         |
| 1.7 SUMMARY OF TEST RESULTS.....                           | 9         |
| <b>2. SYSTEM TEST CONFIGURATION.....</b>                   | <b>10</b> |
| 2.1 EUT CONFIGURATION .....                                | 10        |
| 2.2 SPECIAL ACCESSORIES .....                              | 10        |
| 2.3 DESCRIPTION OF TEST MODES .....                        | 10        |
| 2.4 EUT EXERCISE .....                                     | 10        |
| <b>3. CONDUCTED EMISSIONS TEST .....</b>                   | <b>11</b> |
| 3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....     | 11        |
| 3.2 TEST CONDITION.....                                    | 11        |
| 3.3 MEASUREMENT RESULTS .....                              | 11        |
| <b>4. MAX. CONDUCTED OUTPUT POWER.....</b>                 | <b>12</b> |
| 4.1 MEASUREMENT PROCEDURE .....                            | 12        |
| 4.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....     | 12        |
| 4.3 MEASUREMENT RESULTS .....                              | 12        |
| <b>5. 6DB&amp;20DB BANDWIDTH.....</b>                      | <b>14</b> |
| 5.1 MEASUREMENT PROCEDURE .....                            | 14        |
| 5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....     | 14        |
| 5.3 MEASUREMENT RESULTS .....                              | 14        |
| <b>6. POWER SPECTRAL DENSITY .....</b>                     | <b>21</b> |
| 6.1 MEASUREMENT PROCEDURE .....                            | 21        |
| 6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....     | 21        |
| 6.3 MEASUREMENT RESULTS .....                              | 21        |
| <b>7. BAND EDGE AND CONDUCTED SPURIOUS EMISSIONS .....</b> | <b>28</b> |
| 7.1 REQUIREMENT AND MEASUREMENT PROCEDURE.....             | 28        |
| 7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....     | 28        |
| 7.3 MEASUREMENT RESULTS .....                              | 28        |



**8. RADIATED SPURIOUS EMISSIONS AND RESTRICTED BANDS..... 35**

8.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) ..... 35

8.2 MEASUREMENT PROCEDURE ..... 36

8.3 LIMIT ..... 37

8.4 MEASUREMENT RESULTS ..... 37

**9. ANTENNA APPLICATION ..... 42**

9.1 ANTENNA REQUIREMENT..... 42

9.2 MEASUREMENT RESULTS ..... 42

**10. TEST EQUIPMENT LIST..... 43**

## Revision History of This Test Report

| Report Number  | Description   | Issued Date |
|----------------|---------------|-------------|
| NTC1810270FV00 | Initial Issue | 2018-10-26  |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test

|                       |                                                                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Product Name          | : 10.1" IN-CAR SEATBACK MONITOR                                                                                                      |
| Main Model Name       | : SB10M1                                                                                                                             |
| Additional Model Name | : SBA71012, SBB71013, SB10UHD                                                                                                        |
| Model difference      | : These models have the same circuitry, electrical mechanical, PCB layout and physical construction. The difference in model number. |
| Power Supply          | : DC 12V come from vehicle power supply                                                                                              |
| Adapter               | : N/A                                                                                                                                |
| Test voltage          | : DC 12V battery                                                                                                                     |
| Hardware version      | : V1.0                                                                                                                               |
| Software version      | : V1.0                                                                                                                               |
| Serial number         | : N/A                                                                                                                                |
| Note                  | : All tests were carried on model SB10M1.                                                                                            |

#### Technical parameters For WIFI Function

|                   |                                                             |
|-------------------|-------------------------------------------------------------|
| Frequency Range   | : 2412-2462MHz for 802.11b/g/n(HT20)                        |
| Modulation        | : CCK, DQPSK, DBPSK for 802.11b<br>OFDM for 802.11g/n(HT20) |
| Number of Channel | : 11 for 802.11b/g/n(HT20)                                  |
| Channel space     | : 5MHz                                                      |
| Date Rate         | : 802.11b:1~11Mbps<br>802.11g:6~54Mbps<br>n20: 6.5~72.2Mbps |
| Antenna Type      | : PCB Antenna                                               |
| Antenna Gain      | : 0 dBi                                                     |

### WIFI Channel List

| 802.11 b/g/n(HT20) |               |         |               |
|--------------------|---------------|---------|---------------|
| Channel            | Frequency MHz | Channel | Frequency MHz |
| 1                  | 2412          | 7       | 2442          |
| 2                  | 2417          | 8       | 2447          |
| 3                  | 2422          | 9       | 2452          |
| 4                  | 2427          | 10      | 2457          |
| 5                  | 2432          | 11      | 2462          |
| 6                  | 2437          |         |               |

**Note:** According to section 15.31(m), regards to the operating frequency range over 10MHz, the Lowest, middle, and the Highest frequency of channel were selected to perform the test. The selected frequency see below:

| 802.11b/g/n(HT20) |               |
|-------------------|---------------|
| Channel           | Frequency MHz |
| 1                 | 2412          |
| 6                 | 2437          |
| 11                | 2462          |

|                 |             |
|-----------------|-------------|
| Test SW version | RFTTestTool |
|-----------------|-------------|

## **1.2 Related Submittal(s) / Grant (s)**

This submittal(s) (test report) is intended for FCC ID: **ATI9R3SBA71012** filing to comply with Section 15.247 of the FCC Part 15(2016), Subpart C Rule.

## **1.3 Test Methodology**

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters. All other measurements were made in accordance with the procedures in 47 CFR part 2.

## **1.4 Equipment Modifications**

Not available for this EUT intended for grant.

## **1.5 Support Device**

N/A

## 1.6 Test Facility and Location

### Site Description

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EMC Lab       | : Listed by CNAS, August 13, 2018<br>The certificate is valid until August 13, 2024<br>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01<br>The Certificate Registration Number is L5795.<br><br>Listed by A2LA, November 01, 2017<br>The certificate is valid until December 31, 2019<br>The Laboratory has been assessed and proved to be in compliance with ISO17025<br>The Certificate Registration Number is 4429.01<br><br>Listed by FCC, November 06, 2017<br>The Designation Number is CN1214<br>Test Firm Registration Number: 907417<br><br>Listed by Industry Canada, June 08, 2017<br>The Certificate Registration Number. Is 46405-9743 |
| Name of Firm  | : Dongguan Nore Testing Center Co., Ltd.<br>(Dongguan NTC Co., Ltd.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Site Location | : Building D, Gaosheng Science & Technology Park,<br>Zhouxi Longxi Road, Nancheng District, Dongguan<br>City, Guangdong Province, China                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## 1.7 Summary of Test Results

| FCC Rules                    | Description Of Test                              | Uncertainty               | Result    |
|------------------------------|--------------------------------------------------|---------------------------|-----------|
| §15.207 (a)                  | AC Power Conducted Emission                      | ±1.06dB                   | N/A       |
| §15.247(b)(3)                | Max. Conducted Output Power                      | ±1.06dB                   | Compliant |
| §15.247(a)(2)                | 6dB Bandwidth                                    | ±1.42 x10 <sup>-4</sup> % | Compliant |
| §15.247(e)                   | Power Spectral Density                           | ±1.06dB                   | Compliant |
| §15.247(d)                   | Band Edge and Conducted Spurious Emissions       | ±1.70dB & ±2.51dB         | Compliant |
| §15.247(d), §15.209, §15.205 | Radiated Spurious Emissions and Restricted Bands | ±3.70dB                   | Compliant |
| §15.203                      | Antenna Requirement                              | ---                       | Compliant |

Note: The EUT powered by DC 12V come from vehicle power source, therefore the AC Power Conducted Emission is not applicable.

---

## **2. System Test Configuration**

### **2.1 EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

### **2.2 Special Accessories**

Not available for this EUT intended for grant.

### **2.3 Description of test modes**


The EUT has been tested under continuous operating condition. Test program used to control the EUT staying in continuous transmitting mode. The Lowest, middle and highest channel were chosen for testing, and modulation type CCK, DQPSK, DBPSK, OFDM and all data rate were tested. But only the worst case data is shown in this report.

### **2.4 EUT Exercise**

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

### 3. Conducted Emissions Test

#### 3.1 Test SET-UP (Block Diagram of Configuration)



#### 3.2 Test Condition

**Test Requirement: FCC Part 15.207**

**Frequency Range: 150KHz ~ 30MHz**

**Detector: RBW 9KHz, VBW 30KHz**

**Operation Mode: WIFI Link**

#### 3.3 Measurement Results

**Not applicable.**

## 4. Max. Conducted Output Power

### 4.1 Measurement Procedure

Maximum Conducted Output power at Antenna Terminals, FCC Rules 15.247(b)(3):

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

### 4.2 Test SET-UP (Block Diagram of Configuration)



### 4.3 Measurement Results

**Pass**

Please refer to following table and plots.

|                                                   |                   |                          |                  |
|---------------------------------------------------|-------------------|--------------------------|------------------|
| Temperature :                                     | 24 °C             | Humidity :               | 50%              |
| Test By:                                          | Sance             | Test Date :              | October 22, 2018 |
| Test Result:                                      | PASS              |                          |                  |
| Frequency<br>MHz                                  | Data Rate<br>Mbps | Peak Output Power<br>dBm | Limit<br>dBm     |
| IEEE 802.11b Mode (CCK, Antenna Gain=0dBi)        |                   |                          |                  |
| Low Channel: 2412                                 | 1                 | 15.02                    | 30               |
| Middle Channel: 2437                              | 1                 | 14.69                    | 30               |
| High Channel: 2462                                | 1                 | 14.66                    | 30               |
| IEEE 802.11g Mode (OFDM, Antenna Gain=0dBi)       |                   |                          |                  |
| Low Channel: 2412                                 | 6                 | 14.47                    | 30               |
| Middle Channel: 2437                              | 6                 | 14.34                    | 30               |
| High Channel: 2462                                | 6                 | 14.70                    | 30               |
| IEEE 802.11n(HT20) Mode (OFDM, Antenna Gain=0dBi) |                   |                          |                  |
| Low Channel: 2412                                 | 6.5               | 14.59                    | 30               |
| Middle Channel: 2437                              | 6.5               | 14.52                    | 30               |
| High Channel: 2462                                | 6.5               | 14.90                    | 30               |

Note: CCK was the worst ase of the 802.11b.

## 5. 6dB Bandwidth


### 5.1 Measurement Procedure

DTS 6dB Channel Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074(v05):

1. Set resolution bandwidth (RBW) = 100kHz
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 5.2 Test SET-UP (Block Diagram of Configuration)



### 5.3 Measurement Results

**Pass**

Please refer to following table and plots.


|                                |                   |                              |         |
|--------------------------------|-------------------|------------------------------|---------|
| Temperature :                  | 24 °C             | Humidity : 50 %              |         |
| Test By:                       | Sance             | Test Date : October 22, 2018 |         |
| Test Result:                   | PASS              |                              |         |
| Frequency<br>MHz               | Data Rate<br>Mbps | 6dB Bandwidth<br>MHz         | Limit   |
| IEEE 802.11b Mode (CCK)        |                   |                              |         |
| Low Channel: 2412              | 1                 | 7.550                        | >500KHz |
| Middle Channel: 2437           | 1                 | 7.572                        | >500KHz |
| High Channel: 2462             | 1                 | 7.559                        | >500KHz |
| IEEE 802.11g Mode (OFDM)       |                   |                              |         |
| Low Channel: 2412              | 6                 | 16.30                        | >500KHz |
| Middle Channel: 2437           | 6                 | 16.34                        | >500KHz |
| High Channel: 2462             | 6                 | 16.28                        | >500KHz |
| IEEE 802.11n(HT20) Mode (OFDM) |                   |                              |         |
| Low Channel: 2412              | 6.5               | 17.16                        | >500KHz |
| Middle Channel: 2437           | 6.5               | 17.55                        | >500KHz |
| High Channel: 2462             | 6.5               | 17.28                        | >500KHz |

Note: CCK was the worst ase of the 802.11b.


## 802.11b Low Channel




## 802.11b Middle Channel




## 802.11b High Channel




## 802.11g Low Channel




## 802.11g Middle Channel




## 802.11g High Channel




### 802.11n(HT20) Low Channel



### 802.11n(HT20) Middle Channel



802.11n(HT20) High Channel



## 6. Power Spectral Density


### 6.1 Measurement Procedure

Power Spectral Density, FCC Rule 15.247(e):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074 (v05):

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ KHz}$
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 6.2 Test SET-UP (Block Diagram of Configuration)



### 6.3 Measurement Results


**Pass**

Please refer to following table and plots.


|                                |                   |                 |                   |
|--------------------------------|-------------------|-----------------|-------------------|
| Temperature :                  | 24 °C             | Humidity :      | 50 %              |
| Test By:                       | Sance             | Test Date :     | October 22, 2018  |
| Test Result:                   | PASS              |                 |                   |
| Frequency<br>MHz               | Data Rate<br>Mbps | PSD<br>dBm/3kHz | Limit<br>dBm/3kHz |
| IEEE 802.11b Mode (CCK)        |                   |                 |                   |
| Low Channel: 2412              | 1                 | -6.750          | 8                 |
| Middle Channel: 2437           | 1                 | -6.484          | 8                 |
| High Channel: 2462             | 1                 | -6.835          | 8                 |
| IEEE 802.11g Mode (OFDM)       |                   |                 |                   |
| Low Channel: 2412              | 6                 | -10.454         | 8                 |
| Middle Channel: 2437           | 6                 | -10.079         | 8                 |
| High Channel: 2462             | 6                 | -8.985          | 8                 |
| IEEE 802.11n(HT20) Mode (OFDM) |                   |                 |                   |
| Low Channel: 2412              | 6.5               | -9.846          | 8                 |
| Middle Channel: 2437           | 6.5               | -10.292         | 8                 |
| High Channel: 2462             | 6.5               | -9.981          | 8                 |

Note: CCK was the worst ase of the 802.11b.


## 802.11b Low Channel




## 802.11b Middle Channel




## 802.11b High Channel




## 802.11g Low Channel




## 802.11g Middle Channel




## 802.11g High Channel




### 802.11n(HT20) Low Channel



### 802.11n(HT20) Middle Channel



## 802.11n(HT20) High Channel



## 7. Band Edge and Conducted Spurious Emissions

### 7.1 Requirement and Measurement Procedure

In any 100KHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below.

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 7.2 Test SET-UP (Block Diagram of Configuration)




### 7.3 Measurement Results

The test plots and table showed all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband. Please refer to below plots.



## 802.11g Low Channel



## 802.11g High Channel



802.11n(HT20) Low Channel




802.11n(HT20) High Channel






## Middle Channel



## High Channel




Note: Sweep points=30001pts


## 8. Radiated Spurious Emissions and Restricted Bands

### 8.1 Test SET-UP (Block Diagram of Configuration)

#### 8.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz



### 8.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



### 8.2 Measurement Procedure

- Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- For the radiated emission test above 1GHz:  
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

| Frequency Band (MHz) | Level   | Resolution Bandwidth | Video Bandwidth |
|----------------------|---------|----------------------|-----------------|
| 30 to 1000           | QP      | 120 kHz              | 300 kHz         |
| Above 1000           | Peak    | 1 MHz                | 3 MHz           |
|                      | Average | 1 MHz                | 10 Hz           |

### 8.3 Limit

| Frequency range MHz | Distance Meters | Field Strengths Limit (15.209) |
|---------------------|-----------------|--------------------------------|
|                     |                 | $\mu\text{V/m}$                |
| 0.009 ~ 0.490       | 300             | $2400/F(\text{kHz})$           |
| 0.490 ~ 1.705       | 30              | $24000/F(\text{kHz})$          |
| 1.705 ~ 30          | 30              | 30                             |
| 30 ~ 88             | 3               | 100                            |
| 88 ~ 216            | 3               | 150                            |
| 216 ~ 960           | 3               | 200                            |
| Above 960           | 3               | 500                            |

- Remark:
- (1) Emission level  $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
  - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
  - (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

### 8.4 Measurement Results

Please refer to following plots of the worst case 802.11g Middle channel.



Dongguan NTC Co., Ltd.  
Tel: +86-769-22022444 Fax: +86-769-22022799  
Web: <http://www.ntc-c.com>

### Radiated Emission Measurement


File :SBA71012

Data :#8

Date: 2018-10-18

Time: 18:16:23

80.0 dBuV/m



Site: 3m Chamber

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15C\_Class B\_3M

Power: DC12V

Humidity: 47 %

EUT: 10.1" IN-CAR SEATBACK MONITOR

Distance:

M/N: SB10M1

Mode: TX

Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB/m | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1   |     | 78.5000      | 43.97                    | -17.59                    | 26.38                      | 40.00           | -13.62     | peak                    |                           |         |
| 2   |     | 114.3900     | 43.52                    | -12.87                    | 30.65                      | 43.50           | -12.85     | peak                    |                           |         |
| 3   |     | 189.0800     | 47.01                    | -13.63                    | 33.38                      | 43.50           | -10.12     | peak                    |                           |         |
| 4   |     | 445.1600     | 40.55                    | -8.08                     | 32.47                      | 46.00           | -13.53     | peak                    |                           |         |
| 5   |     | 524.7000     | 43.41                    | -6.71                     | 36.70                      | 46.00           | -9.30      | peak                    |                           |         |
| 6   | *   | 549.9200     | 44.38                    | -6.56                     | 37.82                      | 46.00           | -8.18      | peak                    |                           |         |

**Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.**



Dongguan NTC Co., Ltd.  
Tel: +86-769-22022444 Fax: +86-769-22022799  
Web: [Http://www.ntc-c.com](http://www.ntc-c.com)


### Radiated Emission Measurement

File : SBA71012

Data : #7

Date: 2018-10-18

Time: 18:10:54



Site: 3m Chamber

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15C\_Class B\_3M

Power: DC12V

Humidity: 47 %

EUT: 10.1" IN-CAR SEATBACK MONITOR

Distance:

M/N: SB10M1

Mode: TX

Note:

| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   | Antenna Height | Table Degree |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | cm             | degree       | Comment |
| 1   |     | 114.3900 | 39.58         | -15.99         | 23.59       | 43.50  | -19.91 | peak           |              |         |
| 2   |     | 137.6700 | 41.28         | -18.48         | 22.80       | 43.50  | -20.70 | peak           |              |         |
| 3   |     | 188.1100 | 45.59         | -16.68         | 28.91       | 43.50  | -14.59 | peak           |              |         |
| 4   |     | 396.6600 | 36.74         | -11.13         | 25.61       | 46.00  | -20.39 | peak           |              |         |
| 5   |     | 453.8900 | 37.81         | -10.17         | 27.64       | 46.00  | -18.36 | peak           |              |         |
| 6   | *   | 531.4900 | 42.62         | -8.68          | 33.94       | 46.00  | -12.06 | peak           |              |         |

**Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.**

Test Mode: The worst case: Test Date : October 23, 2018  
802.11g  
Frequency Range: Above 1GHz Temperature : 24°C  
Test Result: PASS Humidity : 50 %  
Measured Distance: 3m Test By: Sance

| Freq.<br>(MHz)                 | Ant.Pol.<br>(H/V) | Reading<br>Level(dBuV) |       | Factor<br>(dB/m) | Emission Level<br>(dBuV) |       | Limit 3m<br>(dBuV/m) |       | Margin<br>(dB) |        |
|--------------------------------|-------------------|------------------------|-------|------------------|--------------------------|-------|----------------------|-------|----------------|--------|
|                                |                   | PK                     | AV    |                  | PK                       | AV    | PK                   | AV    | PK             | AV     |
| Operation Mode: TX Mode (Low)  |                   |                        |       |                  |                          |       |                      |       |                |        |
| 4824                           | V                 | 47.38                  | 32.89 | 6.38             | 53.76                    | 39.27 | 74.00                | 54.00 | -20.24         | -14.73 |
| 7236                           | V                 | 46.36                  | 32.39 | 10.48            | 56.84                    | 42.87 | 74.00                | 54.00 | -17.16         | -11.13 |
| ---                            |                   |                        |       |                  |                          |       |                      |       |                |        |
| 4824                           | H                 | 47.44                  | 33.2  | 6.38             | 53.82                    | 39.58 | 74.00                | 54.00 | -20.18         | -14.42 |
| 7236                           | H                 | 46.85                  | 32.07 | 10.48            | 57.33                    | 42.55 | 74.00                | 54.00 | -16.67         | -11.45 |
| ---                            |                   |                        |       |                  |                          |       |                      |       |                |        |
| Operation Mode: TX Mode (Mid)  |                   |                        |       |                  |                          |       |                      |       |                |        |
| 4874                           | V                 | 47.32                  | 33.56 | 6.56             | 53.88                    | 40.12 | 74.00                | 54.00 | -20.12         | -13.88 |
| 7311                           | V                 | 46.89                  | 33.03 | 10.53            | 57.42                    | 43.56 | 74.00                | 54.00 | -16.58         | -10.44 |
| ---                            |                   |                        |       |                  |                          |       |                      |       |                |        |
| 4874                           | H                 | 46.93                  | 32.96 | 6.56             | 53.49                    | 39.52 | 74.00                | 54.00 | -20.51         | -14.48 |
| 7311                           | H                 | 45.99                  | 33.3  | 10.53            | 56.52                    | 43.83 | 74.00                | 54.00 | -17.48         | -10.17 |
| ---                            |                   |                        |       |                  |                          |       |                      |       |                |        |
| Operation Mode: TX Mode (High) |                   |                        |       |                  |                          |       |                      |       |                |        |
| 4924                           | V                 | 46.85                  | 32.11 | 6.76             | 53.61                    | 38.87 | 74.00                | 54.00 | -20.39         | -15.13 |
| 7386                           | V                 | 46.35                  | 31.96 | 10.57            | 56.92                    | 42.53 | 74.00                | 54.00 | -17.08         | -11.47 |
| ---                            |                   |                        |       |                  |                          |       |                      |       |                |        |
| 4924                           | H                 | 47.36                  | 33    | 6.76             | 54.12                    | 39.76 | 74.00                | 54.00 | -19.88         | -14.24 |
| 7386                           | H                 | 47.12                  | 31.95 | 10.57            | 57.69                    | 42.52 | 74.00                | 54.00 | -16.31         | -11.48 |
| ---                            |                   |                        |       |                  |                          |       |                      |       |                |        |

- Note:**
- (1) All Readings are Peak Value and AV.
  - (2) Emission Level= Reading Level + Factor
  - (3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
  - (4) Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
  - (5) Measurement uncertainty :  $\pm 3.7$ dB.
  - (6) Horn antenna used for the emission over 1000MHz.

Spurious Emission in restricted band:

|                    |            |               |                  |
|--------------------|------------|---------------|------------------|
| Operation Mode:    | TX         | Test Date :   | October 23, 2018 |
| Frequency Range:   | Above 1GHz | Temperature : | 24 °C            |
| Test Result:       | PASS       | Humidity :    | 50 %             |
| Measured Distance: | 3m         | Test By:      | Sance            |

| Freq.<br>(MHz)                        | Ant.Pol.<br>(H/V) | Reading<br>Level(dBuV) |       | Factor<br>(dB/m) | Emission Level<br>(dBuV) |       | Limit 3m<br>(dBuV/m) |       | Margin<br>(dB) |        |
|---------------------------------------|-------------------|------------------------|-------|------------------|--------------------------|-------|----------------------|-------|----------------|--------|
|                                       |                   | PK                     | AV    |                  | PK                       | AV    | PK                   | AV    | PK             | AV     |
| The worst case:<br>Test Mode: 802.11g |                   |                        |       |                  |                          |       |                      |       |                |        |
| 2399.000                              | H                 | 50.98                  | 37.15 | 0.09             | 51.07                    | 37.24 | 74.00                | 54.00 | -22.93         | -16.76 |
| 2399.000                              | V                 | 50.58                  | 37.14 | 0.09             | 50.67                    | 37.23 | 74.00                | 54.00 | -23.33         | -16.77 |
| 2483.500                              | H                 | 50.88                  | 37.02 | 0.34             | 51.22                    | 37.36 | 74.00                | 54.00 | -22.78         | -16.64 |
| 2483.500                              | V                 | 51.3                   | 37.78 | 0.34             | 51.64                    | 38.12 | 74.00                | 54.00 | -22.36         | -15.88 |

**Note:** (1) All Readings are Peak Value and AV.  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss  
 (3) Measurement uncertainty :  $\pm 3.7$ dB

---

## 9. Antenna Application

### 9.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 9.2 Measurement Results

The antenna is PCB antenna and no consideration of replacement, and the best case gain of the antenna is 0dBi. So, the antenna is consider meet the requirement.

## 10. Test Equipment List

| Description                 | Manufacturer    | Model Number | Serial Number | Characteristics | Calibration Date | Calibration Due Date |
|-----------------------------|-----------------|--------------|---------------|-----------------|------------------|----------------------|
| Test Receiver               | Rohde & Schwarz | ESCI7        | 100837        | 9KHz~7GHz       | Mar. 14, 2018    | Mar. 13, 2019        |
| Antenna                     | Schwarzbeck     | VULB9162     | 9162-010      | 30MHz~7GHz      | Mar. 15, 2018    | Mar. 14, 2019        |
| Cable                       | Huber+Suhner    | CBL2-NN-1M   | 22390001      | 9KHz~7GHz       | Mar. 14, 2018    | Mar. 13, 2019        |
| Cable                       | Huber+Suhner    | CIL02        | N/A           | 9KHz~7GHz       | Mar. 14, 2018    | Mar. 13, 2019        |
| RF Cable                    | Huber+Suhner    | SF-104       | MY16559/4     | 9KHz~25GHz      | Apr. 25, 2018    | Apr. 25, 2019        |
| Power Amplifier             | HP              | HP 8447D     | 1145A00203    | 100KHz~1.3GHz   | Mar. 14, 2018    | Mar. 13, 2019        |
| Horn Antenna                | Schwarzbeck     | BBHA9170     | 9170-242      | 15GHz~40GHz     | Mar. 14, 2018    | Mar. 13, 2019        |
| Horn Antenna                | Com-Power       | AH-118       | 071078        | 1GHz~18GHz      | Mar. 15, 2018    | Mar. 14, 2019        |
| RF Cable                    | Huber+Suhner    | SF-104       | N/A           | 9KHz~40GHz      | Apr. 25, 2018    | Apr. 24, 2019        |
| Loop antenna                | Daze            | ZA30900A     | 0708          | 9KHz~30MHz      | Apr. 25, 2018    | Apr. 24, 2019        |
| Spectrum Analyzer           | Rohde & Schwarz | FSU26        | 200409/026    | 20Hz~26.5GHz    | Apr. 25, 2018    | Apr. 24, 2019        |
| Spectrum Analyzer           | Rohde & Schwarz | FSV40        | 101003        | 10Hz~40GHz      | Apr. 06, 2018    | April. 05, 2019      |
| Pre-Amplifier               | EMCI            | EMC 184045   | 980102        | 18GHz~40GHz     | Nov. 03, 2017    | Nov. 02, 2018        |
| Pre-Amplifier               | Agilent         | 8449B        | 3008A02964    | 1GHz~26.5GHz    | Apr. 25, 2018    | Apr. 24, 2019        |
| L.I.S.N.                    | Rohde & Schwarz | ENV 216      | 101317        | 9KHz~30MHz      | Mar. 14, 2018    | Mar. 13, 2019        |
| Temporary antenna connector | TESCOM          | SS402        | N/A           | 9KHz-25GHz      | N/A              | N/A                  |
| Power Meter                 | Anritsu         | ML2495A      | 1139001       | 100k-65GHz      | Nov. 03, 2017    | Nov. 02, 2018        |
| Power Sensor                | Anritsu         | MA2411B      | 100345        | 300M-40GHz      | Nov. 03, 2017    | Nov. 02, 2018        |

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

---End---