

Onkyo Corporation
KOKUGIKAN FRONT BUILDING 1-10-5 Yokoami,
Sumida-ku, Tokyo 130-0015 Japan

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: Wireless neck speaker
Model No: SE-C9NS

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the
Product : Wireless neck speaker
will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.


The appropriate information can be drawn from the test report no: W6M21906-19174-C-1 and the accompanying calculations.

Company: Onkyo Corporation
Address: KOKUGIKAN FRONT BUILDING 1-10-5 Yokoami, Sumida-ku, Tokyo 130-0015
Japan

Date: July 08, 2019

Signature





Registration number: W6M21906-19174-C-1

FCC ID: ATMSEC9NS

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

Bluetooth 2.0+EDR

Test exclusion = max. conducted output power

Test exclusion = 3.76 dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Bluetooth 4.0 1M

Test exclusion = max. conducted output power

Test exclusion = 3.80 dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Bluetooth 5.0 2M

Test exclusion = max. conducted output power

Test exclusion = 3.53 dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

RESULT:

Test standard : FCC KDB Publication
447498 D01 General RF Exposure Guidance v06

According to 447498 D01 General RF Exposure Guidance v06:

SAR evaluation, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

The enclosure of the device provides ≥ 0.5 cm separation from the antenna elements to significant metal parts of the enclosure to minimize potential perturbations.

Frequency Band: 2400-2483.5 MHz

Maximum Power fed to Antenna (BT2.0): 2.3768 mW


Maximum Power fed to Antenna (BT4.0): 2.3988 mW

Maximum Power fed to Antenna (BT5.0): 2.2542 mW

Separation distances:

Radiator to user: > 5 mm

Distance prescribed in user manual: > 5 mm



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21906-19174-C-1
FCC ID: ATMSEC9NS

MHz	5	10	15	20	25	mm
2450	10	19	29	38	48	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
2450	57	67	77	86	96	SAR Test Exclusion Threshold (mW)

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	mW