

**Musical Electronics Ltd.**

Application  
For  
Certification  
**(FCC ID: AUIDM9032-4)**  
Transmitter

WO# 9908384  
DY/kl  
August 14, 1999

- The test results reported in this report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited

FCC ID: AUIDM9032-4

# INTERTEK TESTING SERVICES

---

## LIST OF EXHIBITS

### *INTRODUCTION*

|                   |                           |
|-------------------|---------------------------|
| <i>EXHIBIT 1:</i> | General Description       |
| <i>EXHIBIT 2:</i> | System Test Configuration |
| <i>EXHIBIT 3:</i> | Emission Results          |
| <i>EXHIBIT 4:</i> | Equipment Photographs     |
| <i>EXHIBIT 5:</i> | Product Labelling         |
| <i>EXHIBIT 6:</i> | Technical Specifications  |
| <i>EXHIBIT 7:</i> | Instruction Manual        |
| <i>EXHIBIT 8:</i> | Miscellaneous Information |

---

## INTERTEK TESTING SERVICES

---

### MEASUREMENT/TECHNICAL REPORT

**Musical Electronics Ltd. - MODEL: MUSICAL DM9032-4**  
**FCC ID: AUIDM9032-4**

**August 14, 1999**

This report concerns (check one):    Original Grant   X      Class II Change \_\_\_\_\_

Equipment Type: Low Power Transmitter (example: computer, printer, modem, etc.)  
\_\_\_\_\_

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?    Yes \_\_\_\_\_    No   X  

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.  
\_\_\_\_\_

Transition Rules Request per 15.37?    Yes \_\_\_\_\_    No   X  

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-1-98 Edition] provision.  
\_\_\_\_\_

Report prepared by:

Daniel Yau  
Intertek Testing Services  
Hong Kong Ltd.  
2/F., Garment Centre,  
576, Castle Peak Road,  
Kowloon, Hong Kong  
Phone: 852-2173-8542  
Fax: 852-2371-0914

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

|                                                |    |
|------------------------------------------------|----|
| <b>1.0 General Description</b>                 | 2  |
| 1.1 Product Description                        | 2  |
| 1.2 Related Submittal(s) Grants                | 2  |
| 1.3 Test Methodology                           | 3  |
| 1.4 Test Facility                              | 3  |
| <b>2.0 System Test Configuration</b>           | 5  |
| 2.1 Justification                              | 5  |
| 2.2 EUT Exercising Software                    | 5  |
| 2.3 Special Accessories                        | 5  |
| 2.4 Equipment Modification                     | 6  |
| 2.5 Support Equipment List and Description     | 6  |
| <b>3.0 Emission Results</b>                    | 8  |
| 3.1 Field Strength Calculation                 | 9  |
| 3.1 Field Strength Calculation (cont)          | 10 |
| 3.2 Radiated Emission Configuration Photograph | 11 |
| 3.3 Radiated Emission Data                     | 12 |
| 3.4 Line Conducted Configuration Photograph    | 15 |
| 3.5 Line Conducted Emission Data               | 17 |
| <b>4.0 Equipment Photographs</b>               | 19 |
| <b>5.0 Product Labelling</b>                   | 21 |
| <b>6.0 Technical Specifications</b>            | 23 |
| <b>7.0 Instruction Manual</b>                  | 25 |
| <b>8.0 Miscellaneous Information</b>           | 27 |
| 8.1 Measured Bandwidth                         | 28 |
| 8.2 Discussion of Pulse Desensitization        | 29 |
| 8.3 Calculation of Average Factor              | 30 |
| 8.4 Emissions Test Procedures                  | 31 |
| 8.4 Emissions Test Procedures (cont'd)         | 32 |

---

## INTERTEK TESTING SERVICES

---

### List of attached file

| Exhibit type          | File Description               | filename                                                                        |
|-----------------------|--------------------------------|---------------------------------------------------------------------------------|
| Cover Letter          | Letter of Agency               | letter.pdf                                                                      |
| Test Report           | Test Report                    | report.doc                                                                      |
| Operation Description | Technical Description          | descri.pdf                                                                      |
| Test Setup Photo      | Radiated Emission              | radiated1.jpg, radiated2.jpg                                                    |
| Test Setup Photo      | Conducted Emission             | conduct1.jpg, conduct2.jpg, conduct3.jpg                                        |
| Test Report           | Conducted Emission Test Result | conduct.pdf                                                                     |
| Test Report           | Bandwidth Plot                 | bw.pdf                                                                          |
| External Photo        | External Photo                 | ophoto1.jpg, ophoto2.jpg                                                        |
| Internal Photo        | Internal Photo                 | iphoto1.jpg, iphoto2.jpg, iphoto3.jpg, iphoto4.jpg, iphoto5.jpg and iphoto6.jpg |
| Block Diagram         | Block Diagram                  | block.pdf                                                                       |
| Schematics            | Circuit Diagram                | circuit.pdf                                                                     |
| ID Label/Location     | Label Artwork and Location     | label1.jpg and label2.jpg                                                       |
| User Manual           | User Manual                    | manual.pdf                                                                      |

**EXHIBIT 1**

**GENERAL DESCRIPTION**

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a CD player with AM/FM PLL radio and low power transmitter operating at 88.2 - 91.5MHz. The EUT is powered by 3V DC (2 “AA” batteries) or AC/DC adapter. The CD audio signal can be transmitted by switching on the switch on the bottom side of the EUT. By turning the fine-tuning switch, the transmitting frequency can be tuned from 88.2 to 91.5MHz. The user can use any FCC Part 15 verified FM radio to receive the transmitted FM signal.

The brief circuit description of the EUT is listed in the following:

- IC 101 and associated circuit act as Driver / DC-DC converter.
- IC 201 and associated circuit act as RF AMP.
- IC 301 and associated circuit act as DSP.
- IC 401 and associated circuit act as U-Com.
- IC 501 and associated circuit act as Headphone AMP.
- IC 601 and associated circuit act as Transmitter.

The brief circuit description of the transmitter portion is saved with filename: descri.pdf

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transmitter. **The receiver for this transmitter is FM radio receivers which are subject to verification procedure.**

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (1992). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

**EXHIBIT 2**

**SYSTEM TEST CONFIGURATION**

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (1992.)

The EUT was powered from a 6V AC/DC adaptor.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

For simplicity of testing, the unit was wired to transmit continuously.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the switch is turned ON, the unit transmits the typical signal. For simplicity of testing, the unit was wired to transmit continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

## INTERTEK TESTING SERVICES

---

### 2.4 Equipment Modification

Any modifications installed previous to testing by Musical Electronics Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services.

### 2.5 Support Equipment List and Description

This product was tested in a standalone configuration.

All the items listed under section 2.0 of this report are

- 1.2m headphone
- 1m antenna wire
- 6V AC/DC adaptor

*Confirmed by:*

*Daniel Yau  
Technical Manager- Home Entertainment Electronics  
Intertek Testing Services  
Agent for Musical Electronics Ltd.*



\_\_\_\_\_  
Signature

\_\_\_\_\_  
August 14, 1999 Date

**EXHIBIT 3**

**EMISSION RESULTS**

### 3.0 **Emission Results**

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

### 3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

### 3.1 Field Strength Calculation (cont'd)

#### Example

Assume a receiver reading of 62.0 dBμV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dBμV/m. This value in dBμV/m was converted to its corresponding level in μV/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission

at 90.702 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated1.jpg and radiated2.jpg.

## INTERTEK TESTING SERVICES


---

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed with 1.5 dB margin

#### **TEST PERSONNEL:**



---

*Signature*

Prudence S. M. Poon, Compliance Engineer

*Typed/Printed Name*

*Date : August 14, 1999*

---

## INTERTEK TESTING SERVICES

---

Company: Musical Electronics Ltd.

Date of Test: August 13, 1999

Model: MUSICAL DM9032-4

Worst-Case Operating Mode: Transmitting (Lower Frequency Band)

Table 1

### Radiated Emissions

| Polarity | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Antenna<br>Factor<br>(dB) | Pre-Amp<br>Gain<br>(dB) | Net<br>at 3m<br>(dB $\mu$ V/m) | Limit<br>at 3m<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|----------|--------------------|-------------------------|---------------------------|-------------------------|--------------------------------|----------------------------------|----------------|
| H        | 88.355             | 50.7                    | 9                         | 16                      | 43.7                           | 48.0                             | -4.3           |
| H        | 176.712            | 28.4                    | 19                        | 16                      | 31.4                           | 43.5                             | -12.1          |
| H        | *265.065           | 30.2                    | 21                        | 16                      | 35.2                           | 46.0                             | -10.8          |
| H        | 353.420            | 29.8                    | 24                        | 16                      | 37.8                           | 46.0                             | -8.2           |
| H        | 441.775            | 25.9                    | 26                        | 16                      | 35.9                           | 46.0                             | -10.1          |

Notes: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

\*Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Prudence S. M. Poon

---

## INTERTEK TESTING SERVICES

---

Company: Musical Electronics Ltd.

Date of Test: August 13, 1999

Model: MUSICAL DM9032-4

Worst-Case Operating Mode: Transmitting (Upper Frequency Band)

Table 2

### Radiated Emissions

| Polarity | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Antenna<br>Factor<br>(dB) | Pre-Amp<br>Gain<br>(dB) | Net<br>at 3m<br>(dB $\mu$ V/m) | Limit<br>at 3m<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|----------|--------------------|-------------------------|---------------------------|-------------------------|--------------------------------|----------------------------------|----------------|
| H        | 90.702             | 52.5                    | 10                        | 16                      | 46.5                           | 48.0                             | -1.5           |
| H        | 181.404            | 24.9                    | 20                        | 16                      | 28.9                           | 43.5                             | -14.6          |
| H        | *272.106           | 26.7                    | 22                        | 16                      | 32.7                           | 46.0                             | -13.3          |
| H        | 362.808            | 26.7                    | 24                        | 16                      | 34.7                           | 46.0                             | -11.3          |
| H        | 453.510            | 24.8                    | 26                        | 16                      | 34.8                           | 46.0                             | -11.2          |

Notes: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

\*Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Prudence S. M. Poon

### 3.4 Line Conducted Configuration Photograph

#### Worst Case Line-Conducted Configuration

For electronic filing, the worst case line-conducted configuration photograph are saved with filename: conduct1.jpg, conduct2.jpg and conduct3.jpg.

## **INTERTEK TESTING SERVICES**

---

Company: Musical Electronics Ltd.  
Model: MUSICAL DM9032-4

Date of Test: August 13, 1999

### **Conducted Emissions Section 15.107 Requirements**

For electronic filing, the conducted emission test result is saved with filename: conduct.pdf

## INTERTEK TESTING SERVICES

---


### 3.5 Line Conducted Emission Configuration Data

The data on the following page lists the significant emission frequencies, the limit, and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed with more than 20 dB margin

\* All readings are peak unless stated otherwise.

#### **TEST PERSONNEL:**



---

*Signature*

Prudence S. M. Poon, Compliance Engineer  
*Typed/Printed Name*

Date: August 14, 1999

**EXHIBIT 4**

**EQUIPMENT PHOTOGRAPHS**

### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: ophoto1.jpg to ophoto2.jpg and iphoto1.jpg to iphoto6.jpg.

**EXHIBIT 5**

**PRODUCT LABELLING**

### 5.0 **Product Labelling**

For electronic filing, the FCC ID label location and the artwork location are saved with filename: label1.jpg and label2.jpg.

**EXHIBIT 6**

**TECHNICAL SPECIFICATIONS**

### 6.0 Technical Specifications

For electronic filing, the block diagram and schematics are saved with filename: block.pdf and circuit.pdf respectively.

**EXHIBIT 7**

**INSTRUCTION MANUAL**

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

**EXHIBIT 8**

**MISCELLANEOUS INFORMATION**

### 8.0 **Miscellaneous Information**

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

### 8.1 **Measured Bandwidth**

The plot saved in bw.pdf shows the fundamental emission when modulated by a 1KHz, 0dB level by a CD input. From the plot, the bandwidth is observed to be confined within a band 200 kHz. The 200 kHz band is wholly within the frequency range of 88-108 MHz.

Figure 8.1      Bandwidth

### 8.2 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device. Since the transmitted frequency is a continue signal.

### 8.3 Calculation of Average Factor

The average factor is not applicable for this device as the transmitted signal is a continue signal.

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 1992.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 450 kHz to 30 MHz.

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 1992.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.