

RF Exposure / SAR Statement (Reference)
No. : 10705692S-K/L

Applicant	:	Clarion Co., Ltd.
Type of Equipment	:	Navigation Unit
Model No.	:	QY-5120, PH-3782
FCC ID	:	AX2QY5120

Clarion Co., Ltd. declares that Model : QY-5120, PH-3782
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.
* The results for QY-5092 is used, since QY-5092, QY-5120 and PH-3782 has the identical RF output power.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “QY-5120, PH-3782” as calculated from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = ((P1 + P2) * G) / (4 * \pi * r^2)$$

Where

P1 =	22.08	mW (Maximum average output power) *1)
P2 =	1.44	mW (Maximum average output power) *2)
G =	2.00	Numerical Antenna gain; equal to 3.00 dBi
r =	20.0	cm

For: QY-5120, PH-3782

$$S = 0.00934 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

*1) Wireless LAN value

*2) Bluetooth value

This calculation was made to show that the EUT complies with the limit in simultaneous transmitting of Wireless LAN and Bluetooth.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401