

EXHIBIT 2

Attestation and Product Family Declaration

(Pursuant to FCC Part 2.907, 2.908 and RSP 100 Sec 4)

2.1 Statement of Certification

Transceiver type described herein (AZ489FT3859/109U-89FT3859) is in compliance with all applicable parts of the FCC rules and ISSED RSS standards.

Each unit manufactured, imported, or marketed will conform to the samples tested herein, within the statistical variations that can be expected due to high volume production and test measurement error.

NAME: CHEW LOOI WONG

SIGNATURE:



DATE: 9-Jul-2026

TITLE: Engineering Manager

2.2 Spectrum Efficiency Declaration

The device supports TDMA (F2) transmission with 12.5 kHz spacing. Each transmit slot is 30 ms long and it is followed by 30 ms standby / receive. Transmission in digital TDMA mode (according to 6.25e efficiency standard) allows improved spectrum utilization whereby, the existing 12.5 kHz channel now allows two voice conversations to take place instead of one. Furthermore, the portable radio has integrated voice & data feature that extends the capability of the system to send & receive data through conventional infrastructure.

This device is also capable of supporting a minimum data rate of 4800 bits per second per 6.25kHz channel bandwidth.

NAME: CHEW LOOI WONG

SIGNATURE:



DATE: 9-Jul-2026

TITLE: Engineering Manager

2.3 Product Family Declaration

FCC Model Number	Hardware Version Identification Number (HVIN)	Product Marketing Name (PMN)	Software Version (FVIN)	Description
AAH88LDK8AA3AN	AAH88LDK8AA3AN	BPR 45	T0.00.08	Handheld Portable - TANAPA BPR 45 136-174 MHZ 5W NKP

NAME: CHEW LOOI WONG

SIGNATURE: 

DATE: 9-Jul-2026

TITLE: Engineering Manager