

	 MS ISO/IEC 17025 TESTING SAMM No. 0825																														
MOTOROLA PENANG ADV. COMM. LABORATORY Motorola Solutions Malaysia Sdn. Bhd. Innoplex Plot 2A Medan Bayan Lepas, Mukim 12, S.W.D. 11900 Bayan Lepas, Penang, Malaysia.	FCC / ISED TEST REPORT Report Revision : Rev.A																														
<table><tr><td>Date/s Tested</td><td>: 12-September-2019 - 18-September-2019</td></tr><tr><td>Report Issue Date</td><td>: 26-September-2019</td></tr><tr><td>Manufacturer/Location</td><td>: Motorola Solutions Malaysia Sdn Bhd</td></tr><tr><td>Manufacturer/Address</td><td>: Innoplex Plot 2A, Medan Bayan lepas, Mukim 12, S.W.D. 11900 Bayan Lepas, Penang, Malaysia</td></tr><tr><td>Requestor</td><td>: AYUB, `ABDUL HAKIM</td></tr><tr><td>Product Type</td><td>: Hand-held</td></tr><tr><td>Product Version (PMN)</td><td>: WM500</td></tr><tr><td>Model Number (HVIN)</td><td>: PMMN4127A</td></tr><tr><td>Frequency Band</td><td>: 2.402 - 2.480 GHz</td></tr><tr><td>Rated / Max RF Output Power</td><td>: 2.5 mWatts / 10 mWatts</td></tr><tr><td>Applicant Name</td><td>: Motorola Solutions Inc</td></tr><tr><td>FCC Registrations</td><td>: 461337</td></tr><tr><td>IC Registrations</td><td>: 109AK</td></tr><tr><td>Firmware Version (FVIN)</td><td>: D01.01.07</td></tr></table>  The equipment was tested accordance to the requirement listed below: <table><tr><td>(2.4GHz BT) FCC 47CFR Part 15C ISED RSS 247 Issue 2, February 2017</td><td>PASS</td></tr></table>		Date/s Tested	: 12-September-2019 - 18-September-2019	Report Issue Date	: 26-September-2019	Manufacturer/Location	: Motorola Solutions Malaysia Sdn Bhd	Manufacturer/Address	: Innoplex Plot 2A, Medan Bayan lepas, Mukim 12, S.W.D. 11900 Bayan Lepas, Penang, Malaysia	Requestor	: AYUB, `ABDUL HAKIM	Product Type	: Hand-held	Product Version (PMN)	: WM500	Model Number (HVIN)	: PMMN4127A	Frequency Band	: 2.402 - 2.480 GHz	Rated / Max RF Output Power	: 2.5 mWatts / 10 mWatts	Applicant Name	: Motorola Solutions Inc	FCC Registrations	: 461337	IC Registrations	: 109AK	Firmware Version (FVIN)	: D01.01.07	(2.4GHz BT) FCC 47CFR Part 15C ISED RSS 247 Issue 2, February 2017	PASS
Date/s Tested	: 12-September-2019 - 18-September-2019																														
Report Issue Date	: 26-September-2019																														
Manufacturer/Location	: Motorola Solutions Malaysia Sdn Bhd																														
Manufacturer/Address	: Innoplex Plot 2A, Medan Bayan lepas, Mukim 12, S.W.D. 11900 Bayan Lepas, Penang, Malaysia																														
Requestor	: AYUB, `ABDUL HAKIM																														
Product Type	: Hand-held																														
Product Version (PMN)	: WM500																														
Model Number (HVIN)	: PMMN4127A																														
Frequency Band	: 2.402 - 2.480 GHz																														
Rated / Max RF Output Power	: 2.5 mWatts / 10 mWatts																														
Applicant Name	: Motorola Solutions Inc																														
FCC Registrations	: 461337																														
IC Registrations	: 109AK																														
Firmware Version (FVIN)	: D01.01.07																														
(2.4GHz BT) FCC 47CFR Part 15C ISED RSS 247 Issue 2, February 2017	PASS																														
This report shall not be reproduced without written approval from an officially designated representative of the Motorola Penang Adv. Comm. Laboratory. The results and statements contained in this report pertain only to the device(s) evaluated.																															
Prepared By:  Gan Boon Teong Test Personnel	Approved By:  Vincent Foong Chuen Kit Deputy Technical Manager																														

Table of Contents

1.0. General Information.....	4
2.0. Summary of Test Results	5
3.0. Measurement Uncertainty	6
4.0. Equipment List.....	7
5.0. Test Mode Applicability and Test Channel Detail	8
6.0. Transmitter Test Parameters	9
6.1. Conducted RF Output Power (Peak).....	9
6.1.1. Test Setup	9
6.1.2. Test Limits:	9
6.1.3. Test Data:	9
6.2. 20dB Channel Bandwidth.....	13
6.2.1. Test Setup	13
6.2.2. Test Limits:	13
6.2.3. Test Data:	13
6.3. Band-edge Conducted Spurious Emission.....	17
6.3.1. Test Setup	17
6.3.2. Test Limits.....	17
6.3.3. Test Result.....	17
6.4. Dwell time on each channel.....	21
6.4.1. Test Setup	21
6.4.2. Test Limits:	21
6.4.3. Test Result.....	22
6.5. Number of hopping Frequency	27
6.5.1. Test Setup	27
6.5.2. Test Limits:	27
6.5.3. Test Result.....	27
6.6. Channel Separation	29
6.6.1. Test Setup	29
6.6.2. Test Limits:	29
6.6.3. Test Result.....	29
6.7. Conducted Spurious Emission	33
6.7.1. Test Setup	33
6.7.2. Test Limits:	33
6.7.3. Test Data:	33
6.8. Radiated Emission within restricted Bands	40
6.8.1. Test Setup	40
6.8.2. Test Limits:	41
6.8.3. Test Data:	42
6.9. AC Powerline Conducted Emission.....	99
6.9.1. Test Setup	99
6.9.2. Test Limits:	99
6.9.3. Test Result.....	100

REVISION HISTORY

Revision History	Description	Date	Originator
Rev. A	Initial Report	26-September-2019	GAN BOON TEONG

1.0. General Information

EUT Description:

Technologies	2.4GHz BT
TX Frequency range	2402MHz – 2480MHz
Modulation Type	GFSK, Pi/4 DQPSK,8DPSK
Connector type	PROGRAMMING, TEST & ALIGNMENT CABLE
Antenna type	INTERNAL

The EUT contains following accessory devices and data cable:

Item	Brand	Model or P/N
POWER SUPPLY ADAPTOR,PS WALL 240VAC UNIVERSAL US/JPN ADAPTER 5VDC/1.5A L6 USB-A DETACHABLE	MOTOROLA	8397-PS000150A31-1
CABLE,1000 MM,USB-A TO USB-C,LEX L11	MOTOROLA	CB000756A01

Channel number and frequency information:

79 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, the EUT is to comply with the requirements of the following standards:

FCC 47 CFR Part 15 Subpart C
KDB 558074 D01 15.247 Meas Guidance v05
ANSI C63.10-2013

A pigtail was soldered out of the Bluetooth subsection to allow for conducted tests in this report.

Deviation from standard

Not applicable as no deviation from standard test method

2.0. Summary of Test Results

FCC Clause	ISED Clause	Test Item	Result	Remark	Serial number tested
15.247 (b)(1)	RSS-247 5.4(b)	Conducted RF Output Power (Peak)	Pass	Highest output power: 9.114 dBm	CAB19NCA014G
15.247 (a)(1)	RSS-247 5.1(a) RSS-247 5.1(b)	(1) 20dB Channel Bandwidth (2) Channel Separation	Pass	Highest 99% OCB: 0.873 MHz (873KG1D)	CAB19NCA014G
15.247(a)(1)(iii)	RSS-247 5.1(d)	Number of hopping Frequency used	Pass	Meet the limit requirement.	CAB19NCA014G
15.247(a)(1)(iii)	RSS-247 5.1(d)	Dwell time on each channel	Pass	Meet the limit requirement.	CAB19NCA014G
15.247 (d)	RSS-247 5.5	Band Edge Conducted Spurious Emission	Pass	Worst case emission: -46.89 dB	CAB19NCA014G
15.247 (d)	RSS-247 5.5	Conducted Spurious Emission	Pass	Worst case emission: -48.852 dBm	CAB19NCA014G
15.205, 15.209, 15.247 (d)	RSS-247 5.5	Radiated Emission within Restricted Bands	Pass	Meet the limit requirement.	CAB19NCA00YZ
15.207	RSS-Gen 8.8	AC Powerline Conducted Emission	Pass	Meet the limit requirement.	CAB19NCA00YZ
15.203	-	Antenna Requirement	NA	Internal antenna is not accessible to the end-user	NA

3.0. Measurement Uncertainty

Measurement	Frequency	Expanded Uncertainty (k=1.96) (±dB)
AC Power Line Conducted Spurious Emission	150KHz ~ 30MHz	3.43
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	5.01
	200MHz ~ 1000MHz	5.01
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.01
	18GHz ~ 25GHz	5.01

4.0. Equipment List

Bluetooth ATE # 1 (SW Version: Ate Main_3.1.10_R2)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
SPECTRUM ANALYZER	FSEK30	838495/014	19-Jul-19	19-Jul-20
SPECTRUM ANALYZER	E4443A	MY46181974	9-Aug-18	9-Aug-20
POWER SUPPLY	6033A	3004A05137	24-Jul-18	24-Jul-20

Radiated Emission Station (SW Version: EMC FCC RE v1.6.0)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
DRG HORN FREQ.	SAS-571	720	21-Mar-19	21-Mar-21
DRG HORN FREQ.	SAS-571	1143	14-Feb-19	14-Feb-21
POWER SUPPLY	6032A	MY41001736	25-May-19	25-May-20
SIGNAL GENERATOR	SMB 100A	181117	8-Nov-18	8-Nov-21
EMI TEST RECEIVER	ESW44	101750	24-Jul-19	24-Jul-20
EMI TEST RECEIVER	ESIB26	100017	19-Jul-19	19-Jul-20
5m Semi-anechoic Chamber	S800-HX	J2308	Not Required	Not Required
BILOG ANTENNA	CBL6112D	25224	1-Aug-18	1-Nov-19
BILOG ANTENNA	CBL6112B	2964	16-Feb-18	16-Feb-20
DATA LOGGER	SDL500	A.016800	19-Mar-19	18-Mar-20
SYSTEM CONTROLLER	SC104V	050806-1	Not Required	Not Required
TURNTABLE FLUSH MOUNT 2M	FM2011	NA	Not Required	Not Required
ANTENNA POSITIONING TOWER	TLT2	NA	Not Required	Not Required
BROAD-BAND HORN ANTENNA	BBHA9170	BBHA9170255	21-Dec-18	21-Dec-19
18 - 40GHz PREAMPLIFIER	Miteq Hi Gain Sucoflex	001	Not Required	Not Required
PREAMPLIFIER	PAM-0118	269	24-May-19	24-May-20
LOOP ANTENNA	6502	00203479	10-Dec-18	10-Dec-19

AC Power Line Conducted Emission Station (SW Version: EMC 32 v10.50.10)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
DRG HORN FREQ.	SAS-571	720	21-Mar-19	21-Mar-21
DRG HORN FREQ.	SAS-571	1143	14-Feb-19	14-Feb-21
POWER SUPPLY	6032A	MY41001736	25-May-19	25-May-20
SIGNAL GENERATOR	SMB 100A	181117	8-Nov-18	8-Nov-21
EMI TEST RECEIVER	ESW44	101750	24-Jul-19	24-Jul-20
EMI TEST RECEIVER	ESIB26	100017	19-Jul-19	19-Jul-20

5.0. Test Mode Applicability and Test Channel Detail

Radiated Emission Test (Above 1GHz)

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK	23.3°C, 70.3%RH

Radiated Emission Test (Below 1GHz)

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK	23.3°C, 70.3%RH

Power Line Conducted Emission Test

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Application Mode	0 to 78	AUTO	FHSS	AUTO	21.1°C, 69.9%RH

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).


☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK	24.6°C, 54%RH

6.0. Transmitter Test Parameters

6.1. Conducted RF Output Power (Peak)

6.1.1. Test Setup



- Check and ensure the spectrum analyzer well calibrate.
- Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- Setting of Spectrum analyzer :
 - RBW = > 20 dB bandwidth
 - VBW = RBW
 - Detector mode = Peak
 - AMPLITUDE → Scale/Div = 10 dB
 - Trace = Max hold
 - Sweep = auto
- Measure the captured power within the band and recording the plot.
- Repeat above procedure with other different mode of operation.


6.1.2. Test Limits:

Normal Condition (25 ° C)
≤ 125mW (or 20.9dBm)


6.1.3. Test Data:

Test Conditions		Test Frequency (GHz)	Results	
Modulation	Voltage(V)		dBm	Status
GFSK	7.50	2.4020	9.038	Pass
		2.4410	8.814	Pass
		2.4800	8.676	Pass
Pi/4DQPSK	7.50	2.4020	9.114	Pass
		2.4410	8.861	Pass
		2.4800	8.533	Pass
8DPSK	7.50	2.4020	9.097	Pass
		2.4410	8.913	Pass
		2.4800	8.753	Pass


The Conducted RF Output Power test with result at low frequency, GFSK.




The Conducted RF Output Power test with result at mid frequency, GFSK.




The Conducted RF Output Power test with result at high frequency, GFSK.




The Conducted RF Output Power test with result at low frequency, Pi/4 DQPSK.




The Conducted RF Output Power test with result at mid frequency, Pi/4 DQPSK.




The Conducted RF Output Power test with result at high frequency, Pi/4 DQPSK.




The Conducted RF Output Power test with result at low frequency, 8DPSK.



The Conducted RF Output Power test with result at mid frequency, 8DPSK.




The Conducted RF Output Power test with result at high frequency, 8DPSK.



6.2. 20dB Channel Bandwidth

6.2.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 30 kHz
 - b. VBW = 100 kHz
 - c. SPAN = 3 MHz, center on test frequency
 - d. AMPLITUDE → Scale/Div = 10 dB
 - e. Detector mode = Peak
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the freq different of two frequencies that were attenuated 20dB from peak of the emission & record the frequency difference as the emission bandwidth.
- f) Save the plot result from spectrum analyzer screen.
- g) Repeat above procedure with other different mode of operation.


6.2.2. Test Limits:

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


6.2.3. Test Data:

Test Conditions		Test Frequency TX (GHz)	Results (MHz)		
Modulation Type	Voltage(V)		20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Status
GFSK	7.50	2.4020	0.963	0.873	Pass
		2.4410	0.961	0.865	Pass
		2.4800	0.960	0.864	Pass
Pi/4 DQPSK	7.50	2.4020	0.686	0.829	Pass
		2.4410	0.676	0.805	Pass
		2.4800	0.687	0.796	Pass
8DPSK	7.50	2.4020	0.682	0.776	Pass
		2.4410	0.687	0.773	Pass
		2.4800	0.687	0.759	Pass


i. The 20 dB BW & occupied bandwidth test with result at low frequency, GFSK.




ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, GFSK.




iii. The 20 dB BW & occupied bandwidth test with result at high frequency, GFSK.




- i. The 20 dB BW & occupied bandwidth test with result at low frequency, Pi/4 DQPSK.



- ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, Pi/4 DQPSK.



- iii. The 20 dB BW & occupied bandwidth test with result at high frequency, Pi/4 DQPSK.



- i. The 20 dB BW & occupied bandwidth test with result at low frequency, 8DPSK.



- ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, 8DPSK.




- iii. The 20 dB BW & occupied bandwidth test with result at high frequency, 8DPSK.



6.3. Band-edge Conducted Spurious Emission

6.3.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = 4 MHz (Low channel) or 6MHz(High Channel)
 - d. Detector mode = Peak
 - e. AMPLITUDE → Scale/Div = 10 dB
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the captured band edge emission result and recording the plot.
- f) Repeat above on EUT with hopping disable.
- g) Repeat above procedure with other different test frequency.


6.3.2. Test Limits

Normal Condition (25 ° C)
Shall be at least 20 dB below the peak power.


6.3.3. Test Result

Test Conditions		Hopping Method	Test Frequency(GHz)	Results	
Modulation	Voltage(V)			dB	Status
GFSK	7.50	Enabled (continuously)	2.4020	-49.71	Pass
			2.4800	-57.20	Pass
		Disabled (constantly)	2.4020	-48.17	Pass
			2.4800	-54.92	Pass
Pi/4 DQPSK	7.50	Enabled (continuously)	2.4020	-48.15	Pass
			2.4800	-53.33	Pass
		Disabled (constantly)	2.4020	-48.59	Pass
			2.4800	-54.34	Pass
8DPSK	7.50	Enabled (continuously)	2.4020	-46.89	Pass
			2.4800	-53.79	Pass
		Disabled (constantly)	2.4020	-47.36	Pass
			2.4800	-55.62	Pass


i. The highest band edge emission at low carrier frequency with hopping function enabled, GFSK




ii. The highest band edge emission at high carrier frequency with hopping function enabled, GFSK




iii. The highest band edge emission at low carrier frequency with hopping function disabled, GFSK




iv. The highest band edge emission at high carrier frequency with hopping function disabled, GFSK




i. The highest band edge emission at low carrier frequency with hopping function enabled, Pi/4 DQPSK




ii. The highest band edge emission at high carrier frequency with hopping function enabled, Pi/4 DQPSK




iii. The highest band edge emission at low carrier frequency with hopping function disabled, Pi/4 DQPSK




iv. The highest band edge emission at high carrier frequency with hopping function disabled, Pi/4 DQPSK




i. The highest band edge emission at low carrier frequency with hopping function enabled, 8DPSK




ii. The highest band edge emission at high carrier frequency with hopping function enabled, 8DPSK



iii. The highest band edge emission at low carrier frequency with hopping function disabled, 8DPSK




iv. The highest band edge emission at high carrier frequency with hopping function disabled, 8DPSK



6.4. Dwell time on each channel

6.4.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = Zero SPAN, center on hopping frequency
 - d. Detector mode = Peak
 - e. Trace = Max hold
 - f. Sweep time = 5second
 - g. Sweep = Single
- e) Measure total numbers of transmissions occur in 5 second and save the plot.
- f) Change the setting of spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. Sweep time = sufficient to capture dwell time for 1 transmission
 - d. Sweep = Single
- g) Measure dwell time for 1 transmission and save the plot.
- h) Calculate accumulate dwell time in a given period equal to number of hopping frequencies x 0.4
- i) Repeat above procedure with other different mode of operation.

6.4.2. Test Limits:


Normal Condition (25 ° C)
$\leq 400\text{ms}$

6.4.3. Test Result


Test Conditions			Data Package	Results			
Modulation	Voltage (V)	Test Frequency (GHz)		No. of transmission in 5s (a)	Dwell time in one transmission (b) (msec)	Total accumulate dwell time in 31.6s. (c) (msec)	Status
GFSK	7.50	2.4410	DH1	52	0.399	131.127360	Pass
			DH3	26	1.655	271.949600	Pass
			DH5	18	2.904	330.359040	Pass
Pi/4 DQPSK	7.50		DH1	51	0.307	98.952240	Pass
			DH3	26	1.608	264.226560	Pass
			DH5	17	2.808	301.691520	Pass
8 DPSK	7.50		DH1	51	0.209	67.364880	Pass
			DH3	27	1.609	274.559760	Pass
			DH5	18	2.810	319.665600	Pass

****Note:** Total dwell time 31.6s (79Hopping*0.4), (c) = (a) x 6.32 x (b)


i. Dwell Time at DH1, GFSK





ii. Dwell Time at DH3, GFSK





iii. Dwell Time at DH5, GFSK




iv. Dwell Time at DH1, PI/4DQPSK




v. Dwell Time at DH3, PI/4DQPSK





vi. Dwell Time at DH5, PI/4DQPSK





vii. Dwell Time at DH1, 8DQPSK



viii. Dwell Time at DH3, 8DQPSK




ix. Dwell Time at DH5, 8DQPSK



6.5. Number of hopping Frequency

6.5.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 300 kHz
 - b. VBW = 300 kHz
 - c. Detector mode = Peak
 - d. Trace = Max hold
- e) Allow the trace to stabilized & save the plot result from spectrum analyzer screen.
- f) Count number of channel frequency in the operating.
- g) Repeat above procedure for other test frequency.


6.5.2. Test Limits:

Normal Condition (25 ° C)
≥ 15


6.5.3. Test Result

Test Conditions		Sweep Range (GHz)	Results	
Modulation	Voltage(V)		No. of Hopping Frequencies	Status
GFSK	7.50	2.4000-2.4835	79	Pass
PI/4DQPSK	7.50	2.4000-2.4835	79	Pass
8DPSK	7.50	2.4000-2.4835	79	Pass


i. Number of Hopping Frequencies, GFSK



ii. Number of Hopping Frequencies, Pi/4 DQPSK




iii. Number of Hopping Frequencies, 8DPSK



6.6. Channel Separation

6.6.1. Test Setup



- Check and ensure the spectrum analyzer well calibrate.
- Turn on the EUT and keep the EUT in hopping mode.
- Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- Setting of Spectrum analyzer :
 - RBW = 300 kHz
 - VBW = 300 kHz
 - SPAN = 3 MHz, center on test frequency
 - AMPLITUDE → Scale/Div = 5 dB
 - Detector mode = Peak
 - Trace = Max hold
 - Sweep = auto
- Measure the frequency different of these two adjacent channels with marker delta function & record the measurement results.
- Repeat above procedure with other different mode of operation.


6.6.2. Test Limits:

Normal Condition (25 ° C)
≥ 2/3 of 20dB Bandwidth


6.6.3. Test Result

Test Conditions		Test Frequency (GHz)	Results			
Modulation	Voltage(V)		Test Data Adjacent Channel Separation (MHz)	20dB Bandwidth (MHz)	Min Limit = 2/3 of 20dB Bandwidth (kHz)	Status
GFSK	7.50	2.4020	1.003	0.963	641.681	Pass
		2.4410	1.001	0.961	640.905	Pass
		2.4800	0.992	0.960	640.068	Pass
Pi/4DQPSK	7.50	2.4020	1.007	0.686	457.113	Pass
		2.4410	1.006	0.676	450.893	Pass
		2.4800	1.003	0.687	458.185	Pass
8DPSK	7.50	2.4020	0.994	0.692	461.566	Pass
		2.4410	1.006	0.691	460.420	Pass
		2.4800	1.007	0.680	453.656	Pass


The Conducted RF Output Power test with result at low frequency, GFSK.




The Conducted RF Output Power test with result at mid frequency, GFSK.




The Conducted RF Output Power test with result at high frequency, GFSK.




The Conducted RF Output Power test with result at low frequency, Pi/4 DQPSK.




The Conducted RF Output Power test with result at mid frequency, Pi/4 DQPSK.




The Conducted RF Output Power test with result at high frequency, Pi/4 DQPSK.




The Conducted RF Output Power test with result at low frequency, Pi/4 8DPSK.



The Conducted RF Output Power test with result at mid frequency, 8DPSK.




The Conducted RF Output Power test with result at high frequency, Pi/4 8DPSK.



6.7. Conducted Spurious Emission

6.7.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = Cover until 10th harmonic
 - d. Detector mode = Peak
 - e. AMPLITUDE → Scale/Div = 10 dB
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the captured spurious emission result and recording the plot.
- f) Repeat above procedure with other different mode of operation.

6.7.2. Test Limits:


Normal Condition (25 ° C)
Shall be at least 20 dB below for peak power.

6.7.3. Test Data:


Test Conditions			Results		
Modulation	Voltage(V)	Test Frequency (GHz)	Spurs (MHz)	Level (dBm)	Status
GFSK	7.50	2.4020	14191.343	-49.611	Pass
		2.4410	14191.343	-49.404	Pass
		2.4800	14191.343	-49.418	Pass
Pi/4 DQPSK	7.50	2.4020	14191.343	-49.115	Pass
		2.4410	6685.331	-50.058	Pass
		2.4800	6985.571	-48.852	Pass
8DPSK	7.50	2.4020	14191.343	-49.467	Pass
		2.4410	7335.852	-50.048	Pass
		2.4800	6685.331	-48.936	Pass

GFSK Modulation:


- The high emission level within the assigned band at low carrier frequency.




- Spurious emission measurement in 30MHz – 25GHz at low carrier frequency.




- The high emission level within the assigned band at mid carrier frequency.




- Spurious emission measurement in 30MHz – 25GHz at mid carrier frequency.



• The high emission level within the assigned band at high carrier frequency.




• Spurious emission measurement in 30MHz – 25GHz at high carrier frequency.




Pi/4 DQPSK Modulation:


i. The high emission level within the assigned band at low carrier frequency.




ii. Spurious emission measurement in 30MHz – 25GHz at low carrier frequency.




iii. The high emission level within the assigned band at mid carrier frequency.




iv. Spurious emission measurement in 30MHz – 25GHz at mid carrier frequency.



v. The high emission level within the assigned band at high carrier frequency.




vi. Spurious emission measurement in 30MHz – 25GHz at high carrier frequency.




8DPSK Modulation:


i. The high emission level within the assigned band at low carrier frequency.




ii. Spurious emission measurement in 30MHz – 25GHz at low carrier frequency.




iii. The high emission level within the assigned band at mid carrier frequency.




iv. Spurious emission measurement in 30MHz – 25GHz at mid carrier frequency.



v. The high emission level within the assigned band at high carrier frequency.




vi. Spurious emission measurement in 30MHz – 25GHz at high carrier frequency.



6.8. Radiated Emission within restricted Bands

6.8.1. Test Setup



- The EUT is placed on the top of a rotating table 0.8m (frequency < 1GHz) or 1.5m (frequency > 1GHz) above the ground at a 3m semi-anechoic chamber. The table is rotated 360 degrees to determine the position of the highest radiation.
- The EUT is set 3m away from the interference-receiving antenna, which is mounted on the top of a variable-height antenna tower.
- The antenna is Bilog/Horn antenna depend on which frequency range uses, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT is arranged to its worst case and then the antenna is tuned to heights from 1m to 4m and the rotatable table is turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system is set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode is fall within the range of 10dB from the limit specified, the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. Otherwise, the testing could be stopped and the peak values of the EUT would be reported.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

6.8.2. Test Limits:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

NOTE:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Model#: PMMN4127A S/N: CAB19NCA00YZ EMC SR ID#: 18020-EMC-00005
Battery: NA Accessory: CB000756A01, 8397-PS000150A31-1
Test Channel: Low Test Frequency: 2402.0000 MHz Test Standard: ANSI C63.10-2013
Worst Case Plane: Y-Plane (GFSK)

Restricted Band Edge (Low Channel) tabular data


[illegible]

Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------


Temperature (degC):23.1
Test Performed by: Qawiman&Nazrin
System MU: 5.01dB

Humidity (%): 70.1
Test Date: Sat, Sep 14, 2019


Restricted Band Edge (Low Channel, Vertical, Peak) graphical screen shot




Restricted Band Edge (Low Channel, Horizontal, Peak) graphical screen shot



Restricted Band Edge (Low Channel, Vertical, Average) graphical screen shot



Restricted Band Edge (Low Channel, Horizontal, Average) graphical screen shot



Test: Bluetooth SAC Restricted Band Edge

Model#: PMMN4127A **S/N:** CAB19NCA00YZ **EMC SR ID#:** 18020-EMC-00005
Battery: NA **Accessory:** CB000756A01, 8397-PS000150A31-1
Test Channel: High **Test Frequency:** 2480.0000 MHz **Test Standard:** ANSI C63.10-2013
Worst Case Plane: Y-Plane (GFSK)

Restricted Band Edge (High Channel) tabular data


Vertical Radiated Emission Result										
Spur Freq (MHz)	Spur level QPK (dBμV/m)	Spur level PK (dBμV/m)	Spur level AV (dBμV/m)	Limit QPK (dBμV/m)	Limit PK (dBμV/m)	Limit AV (dBμV/m)	Margin QPK (dBμV/m)	Margin PK (dBμV/m)	Margin AV (dBμV/m)	Carrier PK Power (dBμV/m)
2483.5000	-	54.7306	42.5043	-	74.0000	54.0000	-	-19.2694	-11.4957	-
2484.0790	-	-	42.3660	-	-	54.0000	-	-	-11.6340	-
2486.7650	-	56.0911	-	-	74.0000	-	-	-17.9089	-	-
2490.5570	-	-	42.1048	-	-	54.0000	-	-	-11.8952	-
2492.4530	-	-	42.1680	-	-	54.0000	-	-	-11.8320	-
2494.3490	-	-	42.1092	-	-	54.0000	-	-	-11.8908	-
2495.6130	-	-	42.0530	-	-	54.0000	-	-	-11.9470	-
2498.4570	-	-	42.0721	-	-	54.0000	-	-	-11.9279	-
2502.5650	-	-	42.0662	-	-	54.0000	-	-	-11.9338	-
2503.8290	-	-	42.0930	-	-	54.0000	-	-	-11.9070	-
2516.9430	-	-	42.0760	-	-	54.0000	-	-	-11.9240	-
2542.0650	-	-	42.0352	-	-	54.0000	-	-	-11.9648	-
Horizontal Radiated Emission Result										
2483.5000	-	53.9664	42.6883	-	74.0000	54.0000	-	-20.0336	-11.3117	-
2488.0290	-	-	42.4632	-	-	54.0000	-	-	-11.5368	-
2494.5070	-	-	42.1400	-	-	54.0000	-	-	-11.8600	-
2496.0870	-	-	42.0634	-	-	54.0000	-	-	-11.9366	-
2496.7190	-	-	42.1032	-	-	54.0000	-	-	-11.8968	-
2497.5090	-	-	42.0612	-	-	54.0000	-	-	-11.9388	-
2500.3530	-	-	42.0796	-	-	54.0000	-	-	-11.9204	-
2502.0910	-	-	42.0765	-	-	54.0000	-	-	-11.9235	-
2505.4090	-	-	42.0903	-	-	54.0000	-	-	-11.9097	-
2514.0990	-	-	42.0575	-	-	54.0000	-	-	-11.9425	-
2541.4330	-	-	42.0049	-	-	54.0000	-	-	-11.9951	-
2550.9130	-	54.8579	-	-	74.0000	-	-	-19.1421	-	-

Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------

Temperature (degC):23.1
Test Performed by: Qawiman&Nazrin
System MU: 5.01dB


Humidity (%): 70.1
Test Date: Sun, Sep 15, 2019

Restricted Band Edge (High Channel, Vertical, Peak) graphical screen shot




19:15:26 14.09.2019

Restricted Band Edge (High Channel, Horizontal, Peak) graphical screen shot




19:18:56 14.09.2019


Restricted Band Edge (High Channel, Vertical, Average) graphical screen shot




Restricted Band Edge (High Channel, Horizontal, Average) graphical screen shot




Restricted Band Edge (Low Channel, Vertical, Peak) graphical screen shot



Restricted Band Edge (Low Channel, Horizontal, Peak) graphical screen shot




Restricted Band Edge (Low Channel, Vertical, Average) graphical screen shot



20:10:51 14.09.2019

Restricted Band Edge (Low Channel, Horizontal, Average) graphical screen shot



20:15:11 14.09.2019

Test: Bluetooth SAC Restricted Band Edge

Model#: PMMN4127A **S/N:** CAB19NCA00YZ **EMC SR ID#:** 18020-EMC-00005
Battery: NA **Accessory:** CB000756A01, 8397-PS000150A31-1
Test Channel: High **Test Frequency:** 2480.0000 MHz **Test Standard:** ANSI C63.10-2013
Worst Case Plane: Y-Plane (DQPSK)

Restricted Band Edge (High Channel) tabular data


Vertical Radiated Emission Result										
Spur Freq (MHz)	Spur level QPK (dBμV/m)	Spur level PK (dBμV/m)	Spur level AV (dBμV/m)	Limit QPK (dBμV/m)	Limit PK (dBμV/m)	Limit AV (dBμV/m)	Margin QPK (dBμV/m)	Margin PK (dBμV/m)	Margin AV (dBμV/m)	Carrier PK Power (dBμV/m)
2483.5000	-	55.0389	42.5347	-	74.0000	54.0000	-	-18.9611	-11.4653	-
2484.3950	-	-	42.3140	-	-	54.0000	-	-	-11.6860	-
2486.6070	-	55.8263	-	-	74.0000	-	-	-18.1737	-	-
2492.9270	-	-	42.0737	-	-	54.0000	-	-	-11.9263	-
2493.7170	-	-	42.0852	-	-	54.0000	-	-	-11.9148	-
2494.5070	-	-	42.1132	-	-	54.0000	-	-	-11.8868	-
2503.5130	-	-	42.0773	-	-	54.0000	-	-	-11.9227	-
2505.5670	-	-	42.0778	-	-	54.0000	-	-	-11.9222	-
2509.3590	-	-	42.0737	-	-	54.0000	-	-	-11.9263	-
2512.5190	-	-	42.1224	-	-	54.0000	-	-	-11.8776	-
2527.6870	-	-	42.1253	-	-	54.0000	-	-	-11.8747	-
2536.8510	-	-	42.0005	-	-	54.0000	-	-	-11.9995	-
Horizontal Radiated Emission Result										
2483.5000	-	54.9571	42.3129	-	74.0000	54.0000	-	-19.0429	-11.6871	-
2484.5530	-	-	42.2404	-	-	54.0000	-	-	-11.7596	-
2488.1870	-	-	42.1869	-	-	54.0000	-	-	-11.8131	-
2490.3990	-	-	42.0844	-	-	54.0000	-	-	-11.9156	-
2491.3470	-	-	42.0970	-	-	54.0000	-	-	-11.9030	-
2493.4010	-	-	42.0896	-	-	54.0000	-	-	-11.9104	-
2496.7190	-	-	42.0956	-	-	54.0000	-	-	-11.9044	-
2497.5090	-	-	42.0987	-	-	54.0000	-	-	-11.9013	-
2498.7730	-	-	42.0827	-	-	54.0000	-	-	-11.9173	-
2501.4590	-	-	42.0842	-	-	54.0000	-	-	-11.9158	-
2504.6190	-	55.0975	-	-	74.0000	-	-	-18.9025	-	-
2537.7990	-	-	42.0325	-	-	54.0000	-	-	-11.9675	-

Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------

Temperature (degC):23.1
Test Performed by: Qawiman&Nazrin
System MU: 5.01dB


Humidity (%): 70.1
Test Date: Sun, Sep 15, 2019

Restricted Band Edge (High Channel, Vertical, Peak) graphical screen shot




19:47:59 14.09.2019

Restricted Band Edge (High Channel, Horizontal, Peak) graphical screen shot




19:51:04 14.09.2019

Restricted Band Edge (High Channel, Vertical, Average) graphical screen shot




19:39:31 14.09.2019

Restricted Band Edge (High Channel, Horizontal, Average) graphical screen shot




19:44:04 14.09.2019


Restricted Band Edge (Low Channel, Vertical, Peak) graphical screen shot



Restricted Band Edge (Low Channel, Horizontal, Peak) graphical screen shot




Restricted Band Edge (Low Channel, Vertical, Average) graphical screen shot



20:32:49 14.09.2019

Restricted Band Edge (Low Channel, Horizontal, Average) graphical screen shot



20:37:16 14.09.2019

Test: Bluetooth SAC Restricted Band Edge

Model#: PMMN4127A **S/N:** CAB19NCA00YZ **EMC SR ID#:** 18020-EMC-00005
Battery: NA **Accessory:** CB000756A01, 8397-PS000150A31-1
Test Channel: High **Test Frequency:** 2480.0000 MHz **Test Standard:** ANSI C63.10-2013
Worst Case Plane: Y-Plane (8 DPSK)

Restricted Band Edge (High Channel) tabular data


Vertical Radiated Emission Result										
Spur Freq (MHz)	Spur level QPK (dBμV/m)	Spur level PK (dBμV/m)	Spur level AV (dBμV/m)	Limit QPK (dBμV/m)	Limit PK (dBμV/m)	Limit AV (dBμV/m)	Margin QPK (dBμV/m)	Margin PK (dBμV/m)	Margin AV (dBμV/m)	Carrier PK Power (dBμV/m)
2483.5000	-	54.4246	42.0782	-	74.0000	54.0000	-	-19.5754	-11.9218	-
2484.3950	-	-	42.0804	-	-	54.0000	-	-	-11.9196	-
2484.8690	-	55.2933	-	-	74.0000	-	-	-18.7067	-	-
2485.0270	-	-	42.1007	-	-	54.0000	-	-	-11.8993	-
2485.9750	-	-	42.1107	-	-	54.0000	-	-	-11.8893	-
2487.5550	-	-	42.1138	-	-	54.0000	-	-	-11.8862	-
2489.1350	-	-	42.1268	-	-	54.0000	-	-	-11.8732	-
2490.7150	-	-	42.1131	-	-	54.0000	-	-	-11.8869	-
2493.5590	-	-	42.0844	-	-	54.0000	-	-	-11.9156	-
2498.6150	-	-	42.0564	-	-	54.0000	-	-	-11.9436	-
2521.3670	-	-	42.0771	-	-	54.0000	-	-	-11.9229	-
2549.0170	-	-	42.0184	-	-	54.0000	-	-	-11.9816	-
Horizontal Radiated Emission Result										
2483.5000	-	53.1138	41.9386	-	74.0000	54.0000	-	-20.8862	-12.0614	-
2487.0810	-	-	42.0163	-	-	54.0000	-	-	-11.9837	-
2487.7130	-	-	42.0093	-	-	54.0000	-	-	-11.9907	-
2488.3450	-	55.8210	-	-	74.0000	-	-	-18.1790	-	-
2488.6610	-	-	42.0475	-	-	54.0000	-	-	-11.9525	-
2489.2930	-	-	42.0095	-	-	54.0000	-	-	-11.9905	-
2491.3470	-	-	42.0416	-	-	54.0000	-	-	-11.9584	-
2491.8210	-	-	42.1870	-	-	54.0000	-	-	-11.8130	-
2500.0370	-	-	42.0318	-	-	54.0000	-	-	-11.9682	-
2503.5130	-	-	42.0244	-	-	54.0000	-	-	-11.9756	-
2505.4090	-	-	42.0222	-	-	54.0000	-	-	-11.9778	-
2510.6230	-	-	42.0091	-	-	54.0000	-	-	-11.9909	-

Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------


Temperature (degC):23.1
Test Performed by: Qawiman&Nazrin
System MU: 5.01dB

Humidity (%): 70.1
Test Date: Sun, Sep 15, 2019


Restricted Band Edge (High Channel, Vertical, Peak) graphical screen shot




Restricted Band Edge (High Channel, Horizontal, Peak) graphical screen shot



Restricted Band Edge (High Channel, Vertical, Average) graphical screen shot



Restricted Band Edge (High Channel, Horizontal, Average) graphical screen shot



Model#: PMMN4127A S/N: CAB19NCA00YZ EMC SR ID#: 18020-EMC-00005
 Battery: NA Accessory: CB000756A01, 8397-PS000150A31-1
 Test Channel: Low Test Frequency: 2402.0000 MHz Test Standard: ANSI C63.10-2013
 Worst Case Plane: Y-Plane (GFSK)


Vertical Radiated Emission Result

[illegible]


Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------

Humidity (%): 70.1
Test Date: Mon, Sep 16, 2019


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK




VERTICAL, AV




HORIZONTAL, AV




VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK




VERTICAL, AV




HORIZONTAL, AV




VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK



HORIZONTAL, PK



VERTICAL, AV



HORIZONTAL, AV



NOTE:

Transmitter Duty Cycle Calculation, FCC Rule 15.35 (b,c)

Based on the Bluetooth Specification Version 2.1+EDR, and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = $1 / 133.33$ hops/second = 7.5 ms


Time to cycle through all channels = 7.5×20 channels = 150 ms

Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$


Worst case dwell time = 7.5 ms

Duty cycle connection factor = $20\log_{10} (7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK



VERTICAL, AV



HORIZONTAL, AV




Radiated Emission (Mid Channel) tabular data


Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------

Humidity (%): 70.1
Test Date: Mon, Sep 16, 2019


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK




VERTICAL, AV




HORIZONTAL, AV




VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK



HORIZONTAL, PK



VERTICAL, AV



HORIZONTAL, AV



NOTE:

Transmitter Duty Cycle Calculation, FCC Rule 15.35 (b,c)

Based on the Bluetooth Specification Version 2.1+EDR, and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = $1 / 133.33$ hops/second = 7.5 ms


Time to cycle through all channels = 7.5×20 channels = 150 ms

Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$


Worst case dwell time = 7.5 ms

Duty cycle connection factor = $20\log_{10} (7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK



HORIZONTAL, PK




VERTICAL, AV




HORIZONTAL, AV




VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK



HORIZONTAL, PK




VERTICAL, AV




HORIZONTAL, AV




VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK



HORIZONTAL, PK



VERTICAL, AV



HORIZONTAL, AV



NOTE:

Transmitter Duty Cycle Calculation, FCC Rule 15.35 (b,c)

Based on the Bluetooth Specification Version 2.1+EDR, and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = $1 / 133.33$ hops/second = 7.5 ms

Time to cycle through all channels = 7.5×20 channels = 150 ms


Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$

Worst case dwell time = 7.5 ms

Duty cycle connection factor = $20\log_{10} (7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$

6.9. AC Powerline Conducted Emission

6.9.1. Test Setup



- 1) Tests were conducted for both Receive and Transmit Mode of the EUT.
- 2) The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50uH of coupling impedance for the measuring instrument.
- 3) Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- 4) The frequency range from 150 kHz to 30MHz was measured.

6.9.2. Test Limits:

For AC Power Line Conducted Test Limit can be Class A or B depends on product classification.

Limits for conducted disturbance at the mains ports
of class A ITE

Frequency range MHz	Limits dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	79	66
0,50 to 30	73	60
NOTE The lower limit shall apply at the transition frequency.		

Table 1: Limits for Conducted Disturbance at the Mains Ports of Class A ITE.


Limits for conducted disturbance at the mains ports of class B ITE		
Frequency range MHz	Limits dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

NOTE 1 The lower limit shall apply at the transition frequencies.
 NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

Table 2: Limits for Conducted Disturbance at the Mains Ports of Class B ITE


6.9.3. Test Result

1) Ambient Noise



120 VAC/60 Hz

1) RSM Bluetooth mode DQPSK (2402)



END OF TEST REPORT