

# FCC SAR Test Report

Report No. : SA141118C01

Applicant : Motorola Solutions Inc.

Address : 1301 East Algonquin Road, Schaumburg, Illinois 60196

Product : Smart phone

FCC ID : AZ489FT7062

Brand : Motorola Solutions Inc.

Model No. : LEX L10

Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2003  
IEEE 1528a-2005 / KDB 865664 D01 v01r03 / KDB 865664 D02 v01r01  
KDB 248227 D01 v01r02 / KDB 447498 D01 v05r02 / KDB 648474 D04 v01r02  
KDB 941225 D01 v02 / KDB 941225 D05 v02r03 / KDB 941225 D06 v01r01

Sample Received Date : Dec. 16, 2014

Date of Testing : Dec. 20, 2014 ~ Jan. 20, 2015

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :



Vera Huang / Specialist

Approved By :



Gordon Lin / Assistant Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## **Table of Contents**

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                                    | <b>3</b>  |
| <b>1. Summary of Maximum SAR Value .....</b>                           | <b>4</b>  |
| <b>2. Description of Equipment Under Test .....</b>                    | <b>5</b>  |
| <b>3. SAR Measurement System .....</b>                                 | <b>6</b>  |
| 3.1 Definition of Specific Absorption Rate (SAR) .....                 | 6         |
| 3.2 SPEAG DASY System .....                                            | 6         |
| 3.2.1 Robot.....                                                       | 7         |
| 3.2.2 Probes.....                                                      | 8         |
| 3.2.3 Data Acquisition Electronics (DAE) .....                         | 8         |
| 3.2.4 Phantoms .....                                                   | 9         |
| 3.2.5 Device Holder.....                                               | 10        |
| 3.2.6 System Validation Dipoles.....                                   | 10        |
| 3.2.7 Tissue Simulating Liquids.....                                   | 11        |
| 3.3 SAR System Verification .....                                      | 14        |
| 3.4 SAR Measurement Procedure .....                                    | 15        |
| 3.4.1 Area & Zoom Scan Procedure .....                                 | 15        |
| 3.4.2 Volume Scan Procedure.....                                       | 15        |
| 3.4.3 Power Drift Monitoring.....                                      | 16        |
| 3.4.4 Spatial Peak SAR Evaluation .....                                | 16        |
| 3.4.5 SAR Averaged Methods .....                                       | 16        |
| <b>4. SAR Measurement Evaluation .....</b>                             | <b>17</b> |
| 4.1 EUT Configuration and Setting.....                                 | 17        |
| 4.2 EUT Testing Position .....                                         | 20        |
| 4.2.1 Head Exposure Conditions.....                                    | 20        |
| 4.2.2 Body-Worn Accessory Exposure Conditions .....                    | 22        |
| 4.2.3 Hotspot Mode Exposure conditions.....                            | 23        |
| 4.3 Tissue Verification .....                                          | 24        |
| 4.4 System Validation.....                                             | 25        |
| 4.5 System Verification.....                                           | 26        |
| 4.6 Maximum Output Power.....                                          | 27        |
| 4.6.1 Maximum Conducted Power .....                                    | 27        |
| 4.6.2 Measured Conducted Power Result.....                             | 27        |
| 4.7 SAR Testing Results .....                                          | 34        |
| 4.7.1 SAR Results for Head .....                                       | 34        |
| 4.7.2 SAR Results for Body-Worn .....                                  | 37        |
| 4.7.3 SAR Results for Hotspot (Separation Distance is 1.0 cm Gap)..... | 42        |
| 4.7.4 SAR Measurement Variability .....                                | 45        |
| 4.7.5 Simultaneous Multi-band Transmission Evaluation .....            | 45        |
| <b>5. Calibration of Test Equipment.....</b>                           | <b>59</b> |
| <b>6. Measurement Uncertainty .....</b>                                | <b>60</b> |
| <b>7. +Information on the Testing Laboratories.....</b>                | <b>62</b> |

**Appendix A. SAR Plots of System Verification**

**Appendix B. SAR Plots of SAR Measurement**

**Appendix C. Calibration Certificate for Probe and Dipole**

**Appendix D. Photographs of EUT and Setup**



## Release Control Record

| Report No.  | Reason for Change | Date Issued   |
|-------------|-------------------|---------------|
| SA141118C01 | Initial release   | Feb. 06, 2015 |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |

## 1. Summary of Maximum SAR Value

| Equipment Class                       | Mode      | Highest Reported Head SAR <sub>1g</sub> (W/kg) | Highest Reported Body-Worn SAR <sub>1g</sub> (W/kg) | Highest Reported Hotspot SAR <sub>1g</sub> (1.0 cm Gap) (W/kg) |
|---------------------------------------|-----------|------------------------------------------------|-----------------------------------------------------|----------------------------------------------------------------|
| PCE                                   | CDMA BC0  | 0.73                                           | 1.01                                                | 1.01                                                           |
|                                       | CDMA BC1  | 0.60                                           | 0.76                                                | 0.76                                                           |
|                                       | LTE 4     | 0.51                                           | 0.70                                                | 0.70                                                           |
|                                       | LTE 13    | 0.49                                           | 0.69                                                | 0.69                                                           |
|                                       | LTE 14    | 0.39                                           | 0.62                                                | 0.62                                                           |
| DTS                                   | 2.4G WLAN | 0.49                                           | 0.09                                                | 0.20                                                           |
| NII                                   | 5.2G WLAN | 0.44                                           | 0.16                                                | 0.34                                                           |
|                                       | 5.3G WLAN | 0.39                                           | 0.17                                                | N/A                                                            |
|                                       | 5.6G WLAN | 0.55                                           | 0.30                                                | N/A                                                            |
|                                       | 5.8G WLAN | 0.59                                           | 0.29                                                | 0.66                                                           |
| DSS                                   | Bluetooth | N/A                                            | 0.04                                                | N/A                                                            |
| Highest Simultaneous Transmission SAR |           | Head (W/kg)                                    | Body-Worn (W/kg)                                    | Hotspot (W/kg)                                                 |
| PCE+DTS                               |           | 1.06                                           | 1.08                                                | 1.08                                                           |
| PCE+NII                               |           | 1.15                                           | 1.31                                                | 1.30                                                           |
| PCE+DSS                               |           | N/A                                            | 1.04                                                | N/A                                                            |
| PCE+ PCE                              |           | 1.07                                           | 1.49                                                | 1.49                                                           |
| PCE+ PCE+DTS                          |           | 1.26                                           | 1.28                                                | 1.28                                                           |
| PCE+ PCE+ NII                         |           | 1.36                                           | 1.51                                                | 1.50                                                           |
| PCE+ PCE+DSS                          |           | 0.86                                           | 1.24                                                | 1.21                                                           |

### Note:

- The SAR limit (**Head & Body: SAR<sub>1g</sub> 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

## 2. Description of Equipment Under Test

|                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Type</b>                                        | Smart phone                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>FCC ID</b>                                          | AZ489FT7062                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Brand Name</b>                                      | Motorola Solutions Inc.                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Model Name</b>                                      | LEX L10                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>HW Version</b>                                      | MSM-8974-1-990BPNSP-TR-01-0-AB                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>SW Version</b>                                      | M8974AAAAANLYD4050.1                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Tx Frequency Bands<br/>(Unit: MHz)</b>              | CDMA BC0 : 824.7 ~ 848.31<br>CDMA BC1 : 1851.25 ~ 1908.75<br>LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M),<br>1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M)<br>LTE Band 13 : 779.5 ~ 784.5 (5M), 782 (10M)<br>LTE Band 14 : 790.5 ~ 795.5 (5M), 793 (10M)<br>WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825<br>Bluetooth : 2402 ~ 2480                            |
| <b>Uplink Modulations</b>                              | CDMA : QPSK<br>LTE : QPSK, 16QAM<br>802.11b : DSSS<br>802.11a/g/n : OFDM<br>Bluetooth : GFSK                                                                                                                                                                                                                                                                                                                                               |
| <b>Maximum Tune-up Conducted Power<br/>(Unit: dBm)</b> | CDMA BC0 : 25.5 (Max Power :25.16)<br>CDMA BC1 : 25.0 (Max Power :24.99)<br>LTE Band 4 : 24.0 (Max Power :23.67)<br>LTE Band 13 : 24.0 (Max Power :23.71)<br>LTE Band 14 : 24.0 (Max Power :23.69)<br>WLAN 2.4G : 16.5 (Max Power :16.15)<br>WLAN 5.2G : 15.5 (Max Power :15.5)<br>WLAN 5.3G : 15.5 (Max Power :15.33)<br>WLAN 5.6G : 15.5 (Max Power :15.15)<br>WLAN 5.8G : 14.5 (Max Power :14.45)<br>Bluetooth : 11.0 (Max Power :10.6) |
| <b>Antenna Type</b>                                    | Fixed Internal Antenna<br>CDMA BC0 :-2.77 dBi (Inverted-L with two arms)<br>CDMA BC1 :0.6 dBi (Inverted-L with two arms)<br>LTE 4 :-0.23 dBi (Inverted L with parasitic element)<br>LTE 13 :-0.93 dBi (Inverted L with parasitic element)<br>LTE 14 :-1.13 dBi (Inverted L with parasitic element)<br>WLAN :2.4G 1.7 dBi, 5G 3.56 dBi (Inverted-L)<br>Bluetooth : 1.7 dBi (Inverted-L)                                                     |
| <b>EUT Stage</b>                                       | Identical Prototype                                                                                                                                                                                                                                                                                                                                                                                                                        |

**Note:**

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

**List of Accessory:**

|                  |                     |                         |
|------------------|---------------------|-------------------------|
| <b>Battery 1</b> | <b>Brand Name</b>   | MOTOROLA                |
|                  | <b>Model Name</b>   | PMNN4472A               |
|                  | <b>Power Rating</b> | 3.7Vdc, 2340mAh, 8.7Wh  |
|                  | <b>Type</b>         | Li-ion                  |
| <b>Battery 2</b> | <b>Brand Name</b>   | MOTOROLA                |
|                  | <b>Model Name</b>   | PMNN4475A               |
|                  | <b>Power Rating</b> | 3.7Vdc, 4560mAh, 16.9Wh |
|                  | <b>Type</b>         | Li-ion                  |
| <b>Holster</b>   | <b>P/N</b>          | HKLN4618A               |

### 3. SAR Measurement System

#### 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

#### 3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4/5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

## FCC SAR Test Report




**Fig-3.1 DASY System Setup**

### 3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB; DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



**Fig-3.2 DASY4**



**Fig-3.3 DASY5**

## FCC SAR Test Report

### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

|                      |                                                                                                                                                          |                                                                                     |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>         | EX3DV4                                                                                                                                                   |  |
| <b>Construction</b>  | Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |                                                                                     |
| <b>Frequency</b>     | 10 MHz to 6 GHz<br>Linearity: $\pm 0.2$ dB                                                                                                               |                                                                                     |
| <b>Directivity</b>   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                      |                                                                                     |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)                                                                   |                                                                                     |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                     |                                                                                     |

|                      |                                                                                                                                                                               |                                                                                      |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>         | ES3DV3                                                                                                                                                                        |  |
| <b>Construction</b>  | Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |                                                                                      |
| <b>Frequency</b>     | 10 MHz to 4 GHz<br>Linearity: $\pm 0.2$ dB                                                                                                                                    |                                                                                      |
| <b>Directivity</b>   | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.3$ dB in tissue material (rotation normal to probe axis)                                                           |                                                                                      |
| <b>Dynamic Range</b> | 5 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB                                                                                                                            |                                                                                      |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm                                                |                                                                                      |

### 3.2.3 Data Acquisition Electronics (DAE)

|                             |                                                                                                                                                                                                                                                     |                                                                                       |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>                | DAE3, DAE4                                                                                                                                                                                                                                          |  |
| <b>Construction</b>         | Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop. |                                                                                       |
| <b>Measurement Range</b>    | -100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)                                                                                                                                                                              |                                                                                       |
| <b>Input Offset Voltage</b> | $< 5$ $\mu$ V (with auto zero)                                                                                                                                                                                                                      |                                                                                       |
| <b>Input Bias Current</b>   | $< 50$ fA                                                                                                                                                                                                                                           |                                                                                       |
| <b>Dimensions</b>           | 60 x 60 x 68 mm                                                                                                                                                                                                                                     |                                                                                       |

## FCC SAR Test Report

### 3.2.4 Phantoms

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>           | Twin SAM                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |  |
| <b>Construction</b>    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. |                                                                                     |
| <b>Material</b>        | Vinylester, glass fiber reinforced (VE-GF)                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                     |
| <b>Shell Thickness</b> | $2 \pm 0.2$ mm ( $6 \pm 0.2$ mm at ear point)                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                     |
| <b>Dimensions</b>      | Length: 1000 mm<br>Width: 500 mm<br>Height: adjustable feet                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                     |
| <b>Filling Volume</b>  | approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                     |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                      |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>           | ELI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |
| <b>Construction</b>    | Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. |                                                                                      |
| <b>Material</b>        | Vinylester, glass fiber reinforced (VE-GF)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                      |
| <b>Shell Thickness</b> | $2.0 \pm 0.2$ mm (bottom plate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                      |
| <b>Dimensions</b>      | Major axis: 600 mm<br>Minor axis: 400 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                      |
| <b>Filling Volume</b>  | approx. 30 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                      |

## 3.2.5 Device Holder

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>        | Mounting Device                                                                                                                                                                                                                                                                                                                                                                                                               |  |
| <b>Construction</b> | In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). |                                                                                     |
| <b>Material</b>     | POM                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                     |

|                     |                                                                                                                                                                                                                                                                                         |                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>        | Laptop Extensions Kit                                                                                                                                                                                                                                                                   |  |
| <b>Construction</b> | Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. |                                                                                     |
| <b>Material</b>     | POM, Acrylic glass, Foam                                                                                                                                                                                                                                                                |                                                                                     |


## 3.2.6 System Validation Dipoles

|                         |                                                                                                                                                                      |                                                                                       |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>            | D-Serial                                                                                                                                                             |  |
| <b>Construction</b>     | Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions. |                                                                                       |
| <b>Frequency</b>        | 750 MHz to 5800 MHz                                                                                                                                                  |                                                                                       |
| <b>Return Loss</b>      | > 20 dB                                                                                                                                                              |                                                                                       |
| <b>Power Capability</b> | > 100 W (f < 1GHz), > 40 W (f > 1GHz)                                                                                                                                |                                                                                       |

## FCC SAR Test Report

### 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

**Table-3.1 Targets of Tissue Simulating Liquid**

| Frequency (MHz) | Target Permittivity | Range of $\pm 5\%$ | Target Conductivity | Range of $\pm 5\%$ |
|-----------------|---------------------|--------------------|---------------------|--------------------|
| <b>For Head</b> |                     |                    |                     |                    |
| 750             | 41.9                | 39.8 ~ 44.0        | 0.89                | 0.85 ~ 0.93        |
| 835             | 41.5                | 39.4 ~ 43.6        | 0.90                | 0.86 ~ 0.95        |
| 900             | 41.5                | 39.4 ~ 43.6        | 0.97                | 0.92 ~ 1.02        |
| 1450            | 40.5                | 38.5 ~ 42.5        | 1.20                | 1.14 ~ 1.26        |
| 1640            | 40.3                | 38.3 ~ 42.3        | 1.29                | 1.23 ~ 1.35        |
| 1750            | 40.1                | 38.1 ~ 42.1        | 1.37                | 1.30 ~ 1.44        |
| 1800            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 1900            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 2000            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 2300            | 39.5                | 37.5 ~ 41.5        | 1.67                | 1.59 ~ 1.75        |
| 2450            | 39.2                | 37.2 ~ 41.2        | 1.80                | 1.71 ~ 1.89        |
| 2600            | 39.0                | 37.1 ~ 41.0        | 1.96                | 1.86 ~ 2.06        |
| 3500            | 37.9                | 36.0 ~ 39.8        | 2.91                | 2.76 ~ 3.06        |
| 5200            | 36.0                | 34.2 ~ 37.8        | 4.66                | 4.43 ~ 4.89        |
| 5300            | 35.9                | 34.1 ~ 37.7        | 4.76                | 4.52 ~ 5.00        |
| 5500            | 35.6                | 33.8 ~ 37.4        | 4.96                | 4.71 ~ 5.21        |
| 5600            | 35.5                | 33.7 ~ 37.3        | 5.07                | 4.82 ~ 5.32        |
| 5800            | 35.3                | 33.5 ~ 37.1        | 5.27                | 5.01 ~ 5.53        |
| <b>For Body</b> |                     |                    |                     |                    |
| 750             | 55.5                | 52.7 ~ 58.3        | 0.96                | 0.91 ~ 1.01        |
| 835             | 55.2                | 52.4 ~ 58.0        | 0.97                | 0.92 ~ 1.02        |
| 900             | 55.0                | 52.3 ~ 57.8        | 1.05                | 1.00 ~ 1.10        |
| 1450            | 54.0                | 51.3 ~ 56.7        | 1.30                | 1.24 ~ 1.37        |
| 1640            | 53.8                | 51.1 ~ 56.5        | 1.40                | 1.33 ~ 1.47        |
| 1750            | 53.4                | 50.7 ~ 56.1        | 1.49                | 1.42 ~ 1.56        |
| 1800            | 53.3                | 50.6 ~ 56.0        | 1.52                | 1.44 ~ 1.60        |
| 1900            | 53.3                | 50.6 ~ 56.0        | 1.52                | 1.44 ~ 1.60        |
| 2000            | 53.3                | 50.6 ~ 56.0        | 1.52                | 1.44 ~ 1.60        |
| 2300            | 52.9                | 50.3 ~ 55.5        | 1.81                | 1.72 ~ 1.90        |
| 2450            | 52.7                | 50.1 ~ 55.3        | 1.95                | 1.85 ~ 2.05        |
| 2600            | 52.5                | 49.9 ~ 55.1        | 2.16                | 2.05 ~ 2.27        |
| 3500            | 51.3                | 48.7 ~ 53.9        | 3.31                | 3.14 ~ 3.48        |
| 5200            | 49.0                | 46.6 ~ 51.5        | 5.30                | 5.04 ~ 5.57        |
| 5300            | 48.9                | 46.5 ~ 51.3        | 5.42                | 5.15 ~ 5.69        |
| 5500            | 48.6                | 46.2 ~ 51.0        | 5.65                | 5.37 ~ 5.93        |
| 5600            | 48.5                | 46.1 ~ 50.9        | 5.77                | 5.48 ~ 6.06        |
| 5800            | 48.2                | 45.8 ~ 50.6        | 6.00                | 5.70 ~ 6.30        |

The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid**

| Tissue Type | Bactericide | DGBE | HEC | NaCl | Sucrose | Triton X-100 | Water | Diethylene Glycol Mono-hexylether |
|-------------|-------------|------|-----|------|---------|--------------|-------|-----------------------------------|
| H750        | 0.2         | -    | 0.2 | 1.5  | 56.0    | -            | 42.1  | -                                 |
| H835        | 0.2         | -    | 0.2 | 1.5  | 57.0    | -            | 41.1  | -                                 |
| H900        | 0.2         | -    | 0.2 | 1.4  | 58.0    | -            | 40.2  | -                                 |
| H1450       | -           | 43.3 | -   | 0.6  | -       | -            | 56.1  | -                                 |
| H1640       | -           | 45.8 | -   | 0.5  | -       | -            | 53.7  | -                                 |
| H1750       | -           | 47.0 | -   | 0.4  | -       | -            | 52.6  | -                                 |
| H1800       | -           | 44.5 | -   | 0.3  | -       | -            | 55.2  | -                                 |
| H1900       | -           | 44.5 | -   | 0.2  | -       | -            | 55.3  | -                                 |
| H2000       | -           | 44.5 | -   | 0.1  | -       | -            | 55.4  | -                                 |
| H2300       | -           | 44.9 | -   | 0.1  | -       | -            | 55.0  | -                                 |
| H2450       | -           | 45.0 | -   | 0.1  | -       | -            | 54.9  | -                                 |
| H2600       | -           | 45.1 | -   | 0.1  | -       | -            | 54.8  | -                                 |
| H3500       | -           | 8.0  | -   | 0.2  | -       | 20.0         | 71.8  | -                                 |
| H5G         | -           | -    | -   | -    | -       | 17.2         | 65.5  | 17.3                              |
| B750        | 0.2         | -    | 0.2 | 0.8  | 48.8    | -            | 50.0  | -                                 |
| B835        | 0.2         | -    | 0.2 | 0.9  | 48.5    | -            | 50.2  | -                                 |
| B900        | 0.2         | -    | 0.2 | 0.9  | 48.2    | -            | 50.5  | -                                 |
| B1450       | -           | 34.0 | -   | 0.3  | -       | -            | 65.7  | -                                 |
| B1640       | -           | 32.5 | -   | 0.3  | -       | -            | 67.2  | -                                 |
| B1750       | -           | 31.0 | -   | 0.2  | -       | -            | 68.8  | -                                 |
| B1800       | -           | 29.5 | -   | 0.4  | -       | -            | 70.1  | -                                 |
| B1900       | -           | 29.5 | -   | 0.3  | -       | -            | 70.2  | -                                 |
| B2000       | -           | 30.0 | -   | 0.2  | -       | -            | 69.8  | -                                 |
| B2300       | -           | 31.0 | -   | 0.1  | -       | -            | 68.9  | -                                 |
| B2450       | -           | 31.4 | -   | 0.1  | -       | -            | 68.5  | -                                 |
| B2600       | -           | 31.8 | -   | 0.1  | -       | -            | 68.1  | -                                 |
| B3500       | -           | 28.8 | -   | 0.1  | -       | -            | 71.1  | -                                 |
| B5G         | -           | -    | -   | -    | -       | 10.7         | 78.6  | 10.7                              |

## 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.




**Fig-3.4 System Verification Setup**

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

## FCC SAR Test Report

### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

| Items                                 | <= 2 GHz | 2-3 GHz  | 3-4 GHz  | 4-5 GHz  | 5-6 GHz  |
|---------------------------------------|----------|----------|----------|----------|----------|
| Area Scan<br>( $\Delta x, \Delta y$ ) | <= 15 mm | <= 12 mm | <= 12 mm | <= 10 mm | <= 10 mm |
| Zoom Scan<br>( $\Delta x, \Delta y$ ) | <= 8 mm  | <= 5 mm  | <= 5 mm  | <= 4 mm  | <= 4 mm  |
| Zoom Scan<br>( $\Delta z$ )           | <= 5 mm  | <= 5 mm  | <= 4 mm  | <= 3 mm  | <= 2 mm  |
| Zoom Scan<br>Volume                   | >= 30 mm | >= 30 mm | >= 28 mm | >= 25 mm | >= 22 mm |

#### Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## FCC SAR Test Report

### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 4. SAR Measurement Evaluation

### 4.1 EUT Configuration and Setting

The EUT is a voice/data transmitter device that contains two WWAN transmitters (one is for CDMA2000, and the other is for LTE). The CDMA2000 and LTE can transmit simultaneously. Confirming the LTE transmitter follows 3GPP standards, is category 3, FDD-LTE band 4 (BW 1.4/3/5/10/15/20 MHz), FDD-LTE band 13 and 14 (BW 5/10 MHz), supports QPSK / 16QAM modulations, and supports data transmission only. Tested per 3GPP 36.521 maximum transmit procedures for both QPSK / 16QAM.

**LTE Maximum Power Reduction in accordance with 3GPP 36.101:** Power Reduction in accordance to 3GPP is active all times during LTE operation.

| Modulation   | Channel Bandwidth / RB Configurations |          |          |           |           |           | LTE MPR Setting (dB) |
|--------------|---------------------------------------|----------|----------|-----------|-----------|-----------|----------------------|
|              | BW 1.4 MHz                            | BW 3 MHz | BW 5 MHz | BW 10 MHz | BW 15 MHz | BW 20 MHz |                      |
| <b>QPSK</b>  | > 5                                   | > 4      | > 8      | > 12      | > 16      | > 18      | 1                    |
| <b>16QAM</b> | <= 5                                  | <= 4     | <= 8     | <= 12     | <= 16     | <= 18     | 1                    |
| <b>16QAM</b> | > 5                                   | > 4      | > 8      | > 12      | > 16      | > 18      | 2                    |

**Note:** MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with A-MPR requirements defined in 36.101 section 6.2.4 that may be required to meet 3GPP Adjacent Channel Leakage Ratio ("ACLR") requirements. A-MPR was disabled for all FCC compliance testing.

The simultaneous transmission possibilities are listed as below.

| Simultaneous TX Combination | Configuration                             | Head (Voice / VoIP) | Body Worn (Voice / VoIP) | Hotspot (Data) |
|-----------------------------|-------------------------------------------|---------------------|--------------------------|----------------|
| 1                           | CDMA BC0 (Voice / Data) + LTE 4 (Data)    | Yes                 | Yes                      | Yes            |
| 2                           | CDMA BC1 (Voice / Data) + LTE 4 (Data)    | Yes                 | Yes                      | Yes            |
| 3                           | CDMA BC0 (Voice / Data) + LTE 13 (Data)   | Yes                 | Yes                      | Yes            |
| 4                           | CDMA BC1 (Voice / Data) + LTE 13 (Data)   | Yes                 | Yes                      | Yes            |
| 5                           | CDMA2000 BC0 (Voice / Data) + WLAN (Data) | Yes                 | Yes                      | Yes            |
| 6                           | CDMA2000 BC1 (Voice / Data) + WLAN (Data) | Yes                 | Yes                      | Yes            |
| 7                           | LTE 4 (Data) + WLAN (Data)                | Yes                 | Yes                      | Yes            |
| 8                           | LTE 13 (Data) + WLAN (Data)               | Yes                 | Yes                      | Yes            |
| 9                           | LTE 14 (Data) + WLAN (Data)               | Yes                 | Yes                      | Yes            |
| 10                          | CDMA2000 BC0 (Voice / Data) + BT (Data)   | No                  | Yes                      | No             |
| 11                          | CDMA2000 BC1 (Voice / Data) + BT (Data)   | No                  | Yes                      | No             |
| 12                          | LTE 4 (Data) + BT (Data)                  | No                  | Yes                      | No             |
| 13                          | LTE 13 (Data) + BT (Data)                 | No                  | Yes                      | No             |
| 14                          | LTE 14 (Data) + BT (Data)                 | No                  | Yes                      | No             |

| Simultaneous TX Combination | Configuration                                         | Head (Voice / VoIP) | Body Worn (Voice / VoIP) | Hotspot (Data) |
|-----------------------------|-------------------------------------------------------|---------------------|--------------------------|----------------|
| 15                          | CDMA BC0 (Voice / Data) + LTE 4 (Data) + WLAN (Data)  | Yes                 | Yes                      | Yes            |
| 16                          | CDMA BC1 (Voice / Data) + LTE 4 (Data) + WLAN (Data)  | Yes                 | Yes                      | Yes            |
| 17                          | CDMA BC0 (Voice / Data) + LTE 13 (Data) + WLAN (Data) | Yes                 | Yes                      | Yes            |
| 18                          | CDMA BC1 (Voice / Data) + LTE 13 (Data) + WLAN (Data) | Yes                 | Yes                      | Yes            |
| 19                          | CDMA BC0 (Voice / Data) + LTE 4 (Data) + BT (Data)    | No                  | Yes                      | No             |
| 20                          | CDMA BC1 (Voice / Data) + LTE 4 (Data) + BT (Data)    | No                  | Yes                      | No             |
| 21                          | CDMA BC0 (Voice / Data) + LTE 13 (Data) + BT (Data)   | No                  | Yes                      | No             |
| 22                          | CDMA BC1 (Voice / Data) + LTE 13 (Data) + BT (Data)   | No                  | Yes                      | No             |

## Note:

1. The WLAN and BT cannot transmit simultaneously, so there is no co-location test requirement for WLAN and BT. For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

The EUT is communicated with base station simulator (Agilent E5515C is used for CDMA2000, and Anritsu MT8820C is used for LTE) by air link. During SAR testing, the base station simulator is set to make the EUT to radiate maximum output power.

For CDMA, SAR is tested under 1xRTT mode using RC3 with the EUT configured to transmit at full rate using Loopback Service Option SO55 on head position, and RC3 with the EUT configured using TDSO/SO32, to transmit at full rate on FCH with all other code channels disabled on body position. SAR for RC1 is not required when the maximum power is less than 1/4 dB higher than RC3. SAR for multiple code channels (FCH+SCH<sub>n</sub>) is not required when the maximum power is less than 1/4 dB higher than that measured with FCH only. SAR for EVDO Rev.0 is not required when the maximum power is less than 1/4 dB higher than RC3 (1xRTT). SAR for EVDO Rev.A is not required when the maximum power is less than Rev.0 or less than 1/4 dB higher than RC3. The steps for system simulator (Agilent E5515C) setup are as below.

1. Set the System ID and Network ID
2. Set the Cell Band and connecting Channel
3. Set the power control to All Up Bits
4. Press "Originate Call" button

## FCC SAR Test Report

---

For LTE, set the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB in base station simulator. When the EUT has registered and communicated to base station simulator, set the simulator to make EUT transmitting the maximum radiated power. The steps for system simulator (Anritsu MT8820C) setup are as below.

1. Press the “Std” button to select “LTE 22.20S” function
2. Choose the “Screen Select” item to “Fundamental Measurement”
3. Enter the “Common” item
4. Set the Operating Band
5. Set the Channel Bandwidth
6. Set the UL Channel & Frequency
7. Set the Modulation
8. Set the RB number and RB shift
9. Press “Start Call” button when EUT register to the system simulator
10. Set the TX-1 Max. Power to make the EUT transmit maximum output power

For WLAN SAR testing, the EUT has installed WLAN engineering testing software which can provide continuous transmitting RF signal. According to KDB 248227 D01, WLAN SAR should tested at the lowest data rate, and testing at higher data rate is not required when the maximum average output power is less than 1/4 dB higher than those measured at the lowest data rate. Since the WLAN power at lowest data rate has highest output power, WLAN SAR for this device was performed at the lowest data rate.

## 4.2 EUT Testing Position

According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

### 4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2003 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
  - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
  - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
  - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




**Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines**

## FCC SAR Test Report

### 2. Cheek Position

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




**Fig-4.2 Illustration for Cheek Position**

### 3. Tilted Position

- To position the device in the "cheek" position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).




**Fig-4.3 Illustration for Tilted Position**

## FCC SAR Test Report

### 4.2.2 Body-Worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance  $\leq 5 \text{ mm}$  to support compliance.





**Fig-4.4 Illustration for Body Worn Position**

## 4.2.3 Hotspot Mode Exposure conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

| Antenna   | Front Face | Rear Face | Left Side | Right Side | Top Side | Bottom Side |
|-----------|------------|-----------|-----------|------------|----------|-------------|
| CDMA      | V          | V         | -         | V          | -        | V           |
| LTE       | V          | V         | V         | -          | -        | V           |
| WLAN / BT | V          | V         | -         | V          | -        | -           |

## 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

| Test Date     | Tissue Type | Frequency (MHz) | Liquid Temp. (°C) | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Target Conductivity ( $\sigma$ ) | Target Permittivity ( $\epsilon_r$ ) | Conductivity Deviation (%) | Permittivity Deviation (%) |
|---------------|-------------|-----------------|-------------------|------------------------------------|----------------------------------------|----------------------------------|--------------------------------------|----------------------------|----------------------------|
| Dec. 24, 2014 | Head        | 750             | 21.8              | 0.912                              | 40.638                                 | 0.89                             | 41.9                                 | 2.47                       | -3.01                      |
| Dec. 25, 2014 | Head        | 750             | 21.1              | 0.890                              | 41.109                                 | 0.89                             | 41.9                                 | 0.00                       | -1.89                      |
| Dec. 20, 2014 | Head        | 835             | 21.7              | 0.908                              | 42.576                                 | 0.90                             | 41.5                                 | 0.89                       | 2.59                       |
| Dec. 22, 2014 | Head        | 1750            | 21.4              | 1.327                              | 40.761                                 | 1.37                             | 40.1                                 | -3.14                      | 1.65                       |
| Dec. 23, 2014 | Head        | 1900            | 21.3              | 1.430                              | 39.118                                 | 1.40                             | 40.0                                 | 2.14                       | -2.20                      |
| Jan. 09, 2015 | Head        | 2450            | 21.8              | 1.817                              | 40.019                                 | 1.80                             | 39.2                                 | 0.94                       | 2.09                       |
| Jan. 12, 2015 | Head        | 5200            | 21.9              | 4.777                              | 37.320                                 | 4.66                             | 36.0                                 | 2.51                       | 3.67                       |
| Jan. 12, 2015 | Head        | 5300            | 21.8              | 4.914                              | 37.221                                 | 4.91                             | 35.9                                 | 0.00                       | 3.68                       |
| Jan. 11, 2015 | Head        | 5600            | 21.3              | 5.278                              | 36.522                                 | 5.07                             | 35.5                                 | 4.10                       | 2.88                       |
| Jan. 11, 2015 | Head        | 5800            | 21.3              | 5.434                              | 36.253                                 | 5.27                             | 35.3                                 | 3.11                       | 2.70                       |
| Dec. 20, 2014 | Body        | 750             | 21.2              | 0.966                              | 55.259                                 | 0.96                             | 55.5                                 | 0.63                       | -0.43                      |
| Dec. 21, 2014 | Body        | 835             | 21.1              | 0.992                              | 56.824                                 | 0.97                             | 55.2                                 | 2.27                       | 2.94                       |
| Dec. 22, 2014 | Body        | 1750            | 21.3              | 1.501                              | 52.937                                 | 1.49                             | 53.4                                 | 0.74                       | -0.87                      |
| Dec. 22, 2014 | Body        | 1900            | 21.1              | 1.548                              | 52.591                                 | 1.52                             | 53.3                                 | 1.84                       | -1.33                      |
| Jan. 09, 2015 | Body        | 2450            | 21.8              | 1.998                              | 50.750                                 | 1.95                             | 52.7                                 | 2.46                       | -3.70                      |
| Jan. 14, 2015 | Body        | 2450            | 21.9              | 1.966                              | 54.662                                 | 1.95                             | 52.7                                 | 0.82                       | 3.72                       |
| Jan. 20, 2015 | Body        | 2450            | 20.9              | 1.971                              | 51.349                                 | 1.95                             | 52.7                                 | 1.08                       | -2.56                      |
| Jan. 12, 2015 | Body        | 5200            | 21.9              | 5.347                              | 47.666                                 | 5.30                             | 49.0                                 | 0.89                       | -2.72                      |
| Jan. 14, 2015 | Body        | 5200            | 21.7              | 5.327                              | 47.281                                 | 5.30                             | 49.0                                 | 0.51                       | -3.51                      |
| Jan. 12, 2015 | Body        | 5300            | 21.9              | 5.488                              | 47.439                                 | 5.42                             | 48.9                                 | 1.25                       | -2.99                      |
| Jan. 14, 2015 | Body        | 5300            | 21.7              | 5.462                              | 47.107                                 | 5.42                             | 48.9                                 | 0.77                       | -3.67                      |
| Jan. 11, 2015 | Body        | 5600            | 21.7              | 5.898                              | 46.563                                 | 5.77                             | 48.5                                 | 2.22                       | -3.99                      |
| Jan. 14, 2015 | Body        | 5600            | 22.0              | 5.894                              | 46.817                                 | 5.77                             | 48.5                                 | 2.15                       | -3.47                      |
| Jan. 06, 2015 | Body        | 5800            | 21.2              | 6.185                              | 46.167                                 | 6.00                             | 48.2                                 | 3.08                       | -4.22                      |
| Jan. 11, 2015 | Body        | 5800            | 21.7              | 6.185                              | 46.167                                 | 6.00                             | 48.2                                 | 3.08                       | -4.22                      |
| Jan. 14, 2015 | Body        | 5800            | 22.0              | 6.185                              | 46.167                                 | 6.00                             | 48.2                                 | 3.08                       | -4.22                      |

### Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2^\circ\text{C}$ .

## 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

| Test Date     | Probe S/N | Calibration Point |      | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Validation for CW |                 |                | Validation for Modulation |             |      |
|---------------|-----------|-------------------|------|------------------------------------|----------------------------------------|-------------------|-----------------|----------------|---------------------------|-------------|------|
|               |           |                   |      |                                    |                                        | Sensitivity Range | Probe Linearity | Probe Isotropy | Modulation Type           | Duty Factor | PAR  |
| Dec. 24, 2014 | 3650      | Head              | 750  | 0.912                              | 40.638                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 25, 2014 | 3590      | Head              | 750  | 0.890                              | 41.109                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 20, 2014 | 3650      | Head              | 835  | 0.908                              | 42.576                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 22, 2014 | 3650      | Head              | 1750 | 1.327                              | 40.761                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 23, 2014 | 3650      | Head              | 1900 | 1.430                              | 39.118                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Jan. 09, 2015 | 3971      | Head              | 2450 | 1.817                              | 40.019                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 12, 2015 | 3971      | Head              | 5200 | 4.777                              | 37.320                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 12, 2015 | 3971      | Head              | 5300 | 4.914                              | 37.221                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 11, 2015 | 3971      | Head              | 5600 | 5.278                              | 36.522                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 11, 2015 | 3971      | Head              | 5800 | 5.434                              | 36.253                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Dec. 20, 2014 | 3650      | Body              | 750  | 0.966                              | 55.259                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 21, 2014 | 3650      | Body              | 835  | 0.992                              | 56.824                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 22, 2014 | 3650      | Body              | 1750 | 1.501                              | 52.937                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Dec. 22, 2014 | 3650      | Body              | 1900 | 1.548                              | 52.591                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A  |
| Jan. 09, 2015 | 3971      | Body              | 2450 | 1.998                              | 50.750                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 14, 2015 | 3864      | Body              | 2450 | 1.966                              | 54.662                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 20, 2015 | 3864      | Body              | 2450 | 1.971                              | 51.349                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 12, 2015 | 3971      | Body              | 5200 | 5.347                              | 47.666                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 14, 2015 | 3864      | Body              | 5200 | 5.327                              | 47.281                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 12, 2015 | 3971      | Body              | 5300 | 5.488                              | 47.439                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 14, 2015 | 3864      | Body              | 5300 | 5.462                              | 47.107                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 11, 2015 | 3971      | Body              | 5600 | 5.898                              | 46.563                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 14, 2015 | 3864      | Body              | 5600 | 5.894                              | 46.817                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 06, 2015 | 3864      | Body              | 5800 | 6.185                              | 46.167                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 11, 2015 | 3971      | Body              | 5800 | 6.185                              | 46.167                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |
| Jan. 14, 2015 | 3864      | Body              | 5800 | 6.185                              | 46.167                                 | Pass              | Pass            | Pass           | OFDM                      | N/A         | Pass |

## 4.5 System Verification

The measuring result for system verification is tabulated as below.

| Test Date     | Mode | Frequency (MHz) | 1W Target SAR-1g (W/kg) | Measured SAR-1g (W/kg) | Normalized to 1W SAR-1g (W/kg) | Deviation (%) | Dipole S/N | Probe S/N | DAE S/N |
|---------------|------|-----------------|-------------------------|------------------------|--------------------------------|---------------|------------|-----------|---------|
| Dec. 24, 2014 | Head | 750             | 8.35                    | 2.22                   | 8.88                           | 6.35          | 1013       | 3650      | 1277    |
| Dec. 25, 2014 | Head | 750             | 8.35                    | 2.01                   | 8.04                           | -3.71         | 1013       | 3590      | 861     |
| Dec. 20, 2014 | Head | 835             | 9.43                    | 2.35                   | 9.40                           | -0.32         | 4d121      | 3650      | 1277    |
| Dec. 22, 2014 | Head | 1750            | 37.30                   | 9.31                   | 37.24                          | -0.16         | 1055       | 3650      | 1277    |
| Dec. 23, 2014 | Head | 1900            | 40.60                   | 9.62                   | 38.48                          | -5.22         | 5d036      | 3650      | 1277    |
| Jan. 09, 2015 | Head | 2450            | 51.00                   | 12.80                  | 51.20                          | 0.39          | 737        | 3971      | 1431    |
| Jan. 12, 2015 | Head | 5200            | 79.70                   | 8.05                   | 80.50                          | 1.00          | 1019       | 3971      | 1431    |
| Jan. 12, 2015 | Head | 5300            | 83.40                   | 8.21                   | 82.10                          | -1.56         | 1019       | 3971      | 1431    |
| Jan. 11, 2015 | Head | 5600            | 83.80                   | 8.35                   | 83.50                          | -0.36         | 1019       | 3971      | 1431    |
| Jan. 11, 2015 | Head | 5800            | 80.20                   | 7.61                   | 76.10                          | -5.11         | 1019       | 3971      | 1431    |
| Dec. 20, 2014 | Body | 750             | 8.71                    | 2.03                   | 8.12                           | -6.77         | 1013       | 3650      | 1277    |
| Dec. 21, 2014 | Body | 835             | 9.55                    | 2.44                   | 9.76                           | 2.20          | 4d121      | 3650      | 1277    |
| Dec. 22, 2014 | Body | 1750            | 37.70                   | 9.25                   | 37.00                          | -1.86         | 1055       | 3650      | 1277    |
| Dec. 22, 2014 | Body | 1900            | 41.00                   | 10.60                  | 42.40                          | 3.41          | 5d036      | 3650      | 1277    |
| Jan. 09, 2015 | Body | 2450            | 49.50                   | 12.30                  | 49.20                          | -0.61         | 737        | 3971      | 1431    |
| Jan. 14, 2015 | Body | 2450            | 49.50                   | 12.30                  | 49.20                          | -0.61         | 737        | 3864      | 510     |
| Jan. 20, 2015 | Body | 2450            | 49.50                   | 13.10                  | 52.40                          | 5.86          | 737        | 3590      | 861     |
| Jan. 12, 2015 | Body | 5200            | 74.70                   | 7.58                   | 75.80                          | 1.47          | 1019       | 3971      | 1431    |
| Jan. 14, 2015 | Body | 5200            | 74.70                   | 7.23                   | 72.30                          | -3.21         | 1019       | 3864      | 510     |
| Jan. 12, 2015 | Body | 5300            | 77.10                   | 7.91                   | 79.10                          | 2.59          | 1019       | 3971      | 1431    |
| Jan. 14, 2015 | Body | 5300            | 77.10                   | 7.78                   | 77.80                          | 0.91          | 1019       | 3864      | 510     |
| Jan. 11, 2015 | Body | 5600            | 80.80                   | 7.85                   | 78.50                          | -2.85         | 1019       | 3971      | 1431    |
| Jan. 14, 2015 | Body | 5600            | 80.80                   | 8.41                   | 84.10                          | 4.08          | 1019       | 3864      | 510     |
| Jan. 06, 2015 | Body | 5800            | 73.90                   | 7.84                   | 78.40                          | 6.09          | 1019       | 3864      | 510     |
| Jan. 11, 2015 | Body | 5800            | 73.90                   | 7.23                   | 72.30                          | -2.17         | 1019       | 3971      | 1431    |
| Jan. 14, 2015 | Body | 5800            | 73.90                   | 7.65                   | 76.50                          | 3.52          | 1019       | 3864      | 510     |

### Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

## 4.6 Maximum Output Power

### 4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

| Mode         | CDMA BC0 | CDMA BC1 |
|--------------|----------|----------|
| 1xRTT        | 25.5     | 25.0     |
| 1xEVDO Rev.0 | 25.5     | 25.0     |
| 1xEVDO Rev.A | 25.5     | 25.0     |

| Mode         | LTE 4<br>(without Power Reduction) | LTE 4<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|------------------------------------|---------------------------------|--------------------------|
| QPSK / 16QAM | 24.0                               | 21.0                            | 3.0                      |

| Mode         | LTE 13<br>(without Power Reduction) | LTE 13<br>(with Power Reduction) | Power Reduction<br>(dBm) |
|--------------|-------------------------------------|----------------------------------|--------------------------|
| QPSK / 16QAM | 24.0                                | 18.0                             | 6.0                      |

| Mode         | LTE 14 |
|--------------|--------|
| QPSK / 16QAM | 24.0   |

| Mode         | 2.4G WLAN | 5.2G WLAN | 5.3G WLAN | 5.6G WLAN | 5.8G WLAN |
|--------------|-----------|-----------|-----------|-----------|-----------|
| 802.11b      | 16.5      | N/A       | N/A       | N/A       | N/A       |
| 802.11g      | 16.0      | N/A       | N/A       | N/A       | N/A       |
| 802.11a      | N/A       | 15.5      | 15.5      | 15.5      | 14.5      |
| 802.11n HT20 | 14.5      | 15.5      | 15.5      | 15.5      | 14.5      |
| 802.11n HT40 | N/A       | 15.5      | 15.5      | 15.5      | 14.5      |

| Mode | Bluetooth |
|------|-----------|
| All  | 11.0      |

### 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

| Band                       | CDMA BC0 |        |        | CDMA BC1 |         |         |
|----------------------------|----------|--------|--------|----------|---------|---------|
| Channel                    | 1013     | 384    | 777    | 25       | 600     | 1175    |
| Frequency (MHz)            | 824.70   | 836.52 | 848.31 | 1851.25  | 1880.00 | 1908.75 |
| 1xRTT RC1+SO55             | 25.00    | 25.13  | 25.10  | 24.93    | 24.90   | 24.86   |
| 1xRTT RC3+SO55             | 25.03    | 25.16  | 25.13  | 24.99    | 24.96   | 24.92   |
| 1xRTT RC3+SO32 (FCH)       | 25.02    | 25.15  | 25.12  | 24.85    | 24.82   | 24.78   |
| 1xRTT RC3+SO32 (SCH)       | 25.00    | 25.13  | 25.10  | 24.93    | 24.90   | 24.86   |
| 1xEVDO Rev.0<br>RTAP 153.6 | 24.31    | 24.44  | 24.41  | 24.57    | 24.54   | 24.50   |
| 1xEVDO Rev.A<br>RETAP 4096 | 24.28    | 24.41  | 24.38  | 24.58    | 24.55   | 24.51   |

# FCC SAR Test Report

A D T

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>19957 | Mid CH<br>20175 | High CH<br>20393 |                     | Low CH<br>19957 | Mid CH<br>20175 | High CH<br>20393 |                     |
|                             |            |              | 1710.7<br>MHz   | 1732.5<br>MHz   | 1754.3<br>MHz    |                     | 1710.7<br>MHz   | 1732.5<br>MHz   | 1754.3<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 1.4M                    | 1          | 0            | 22.89           | 23.05           | 23.07            | 0                   | 21.88           | 22.04           | 22.06            | 1                   |
|                             | 1          | 2            | 22.80           | 22.96           | 22.98            | 0                   | 21.79           | 21.95           | 21.97            | 1                   |
|                             | 1          | 5            | 22.66           | 22.82           | 22.84            | 0                   | 21.65           | 21.81           | 21.83            | 1                   |
|                             | 3          | 0            | 21.95           | 22.11           | 22.13            | 0                   | 20.94           | 21.10           | 21.12            | 1                   |
|                             | 3          | 1            | 21.92           | 22.08           | 22.10            | 0                   | 20.91           | 21.07           | 21.09            | 1                   |
|                             | 3          | 3            | 21.83           | 21.99           | 22.01            | 0                   | 20.82           | 20.98           | 21.00            | 1                   |
|                             | 6          | 0            | 21.81           | 21.97           | 21.99            | 1                   | 20.80           | 20.96           | 20.98            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 1.4M                    | 1          | 0            | 20.07           | 20.10           | 20.14            | 0                   | 19.06           | 19.09           | 19.13            | 1                   |
|                             | 1          | 2            | 19.99           | 20.02           | 20.06            | 0                   | 18.98           | 19.01           | 19.05            | 1                   |
|                             | 1          | 5            | 19.90           | 19.93           | 19.97            | 0                   | 18.89           | 18.92           | 18.96            | 1                   |
|                             | 3          | 0            | 18.99           | 19.02           | 19.06            | 0                   | 17.98           | 18.01           | 18.05            | 1                   |
|                             | 3          | 1            | 18.95           | 18.98           | 19.02            | 0                   | 17.94           | 17.97           | 18.01            | 1                   |
|                             | 3          | 3            | 18.94           | 18.97           | 19.01            | 0                   | 17.93           | 17.96           | 18.00            | 1                   |
|                             | 6          | 0            | 18.98           | 19.01           | 19.05            | 1                   | 17.97           | 18.00           | 18.04            | 2                   |

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>19965 | Mid CH<br>20175 | High CH<br>20385 |                     | Low CH<br>19965 | Mid CH<br>20175 | High CH<br>20385 |                     |
|                             |            |              | 1711.5<br>MHz   | 1732.5<br>MHz   | 1753.5<br>MHz    |                     | 1711.5<br>MHz   | 1732.5<br>MHz   | 1753.5<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 3M                      | 1          | 0            | 23.01           | 23.17           | 23.19            | 0                   | 22.00           | 22.16           | 22.18            | 1                   |
|                             | 1          | 7            | 22.92           | 23.08           | 23.10            | 0                   | 21.91           | 22.07           | 22.09            | 1                   |
|                             | 1          | 14           | 22.78           | 22.94           | 22.96            | 0                   | 21.77           | 21.93           | 21.95            | 1                   |
|                             | 8          | 0            | 22.07           | 22.23           | 22.25            | 1                   | 21.06           | 21.22           | 21.24            | 2                   |
|                             | 8          | 3            | 22.04           | 22.20           | 22.22            | 1                   | 21.03           | 21.19           | 21.21            | 2                   |
|                             | 8          | 7            | 21.95           | 22.11           | 22.13            | 1                   | 20.94           | 21.10           | 21.12            | 2                   |
|                             | 15         | 0            | 21.93           | 22.09           | 22.11            | 1                   | 20.92           | 21.08           | 21.10            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 3M                      | 1          | 0            | 20.18           | 20.21           | 20.25            | 0                   | 19.17           | 19.20           | 19.24            | 1                   |
|                             | 1          | 7            | 20.10           | 20.13           | 20.17            | 0                   | 19.09           | 19.12           | 19.16            | 1                   |
|                             | 1          | 14           | 20.01           | 20.04           | 20.08            | 0                   | 19.00           | 19.03           | 19.07            | 1                   |
|                             | 8          | 0            | 19.10           | 19.13           | 19.17            | 1                   | 18.09           | 18.12           | 18.16            | 2                   |
|                             | 8          | 3            | 19.06           | 19.09           | 19.13            | 1                   | 18.05           | 18.08           | 18.12            | 2                   |
|                             | 8          | 7            | 19.05           | 19.08           | 19.12            | 1                   | 18.04           | 18.07           | 18.11            | 2                   |
|                             | 15         | 0            | 19.09           | 19.12           | 19.16            | 1                   | 18.08           | 18.11           | 18.15            | 2                   |

# FCC SAR Test Report

A D T

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>19975 | Mid CH<br>20175 | High CH<br>20375 |                     | Low CH<br>19975 | Mid CH<br>20175 | High CH<br>20375 |                     |
|                             |            |              | 1712.5<br>MHz   | 1732.5<br>MHz   | 1752.5<br>MHz    |                     | 1712.5<br>MHz   | 1732.5<br>MHz   | 1752.5<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 5M                      | 1          | 0            | 23.13           | 23.29           | 23.31            | 0                   | 22.12           | 22.28           | 22.30            | 1                   |
|                             | 1          | 12           | 23.04           | 23.20           | 23.22            | 0                   | 22.03           | 22.19           | 22.21            | 1                   |
|                             | 1          | 24           | 22.90           | 23.06           | 23.08            | 0                   | 21.89           | 22.05           | 22.07            | 1                   |
|                             | 12         | 0            | 22.19           | 22.35           | 22.37            | 1                   | 21.18           | 21.34           | 21.36            | 2                   |
|                             | 12         | 6            | 22.16           | 22.32           | 22.34            | 1                   | 21.15           | 21.31           | 21.33            | 2                   |
|                             | 12         | 13           | 22.07           | 22.23           | 22.25            | 1                   | 21.06           | 21.22           | 21.24            | 2                   |
|                             | 25         | 0            | 22.05           | 22.21           | 22.23            | 1                   | 21.04           | 21.20           | 21.22            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 5M                      | 1          | 0            | 20.29           | 20.32           | 20.36            | 0                   | 19.28           | 19.31           | 19.35            | 1                   |
|                             | 1          | 12           | 20.21           | 20.24           | 20.28            | 0                   | 19.20           | 19.23           | 19.27            | 1                   |
|                             | 1          | 24           | 20.12           | 20.15           | 20.19            | 0                   | 19.11           | 19.14           | 19.18            | 1                   |
|                             | 12         | 0            | 19.21           | 19.24           | 19.28            | 1                   | 18.20           | 18.23           | 18.27            | 2                   |
|                             | 12         | 6            | 19.17           | 19.20           | 19.24            | 1                   | 18.16           | 18.19           | 18.23            | 2                   |
|                             | 12         | 13           | 19.16           | 19.19           | 19.23            | 1                   | 18.15           | 18.18           | 18.22            | 2                   |
|                             | 25         | 0            | 19.20           | 19.23           | 19.27            | 1                   | 18.19           | 18.22           | 18.26            | 2                   |

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>20000 | Mid CH<br>20175 | High CH<br>20350 |                     | Low CH<br>20000 | Mid CH<br>20175 | High CH<br>20350 |                     |
|                             |            |              | 1715.0<br>MHz   | 1732.5<br>MHz   | 1750.0<br>MHz    |                     | 1715.0<br>MHz   | 1732.5<br>MHz   | 1750.0<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 10M                     | 1          | 0            | 23.25           | 23.41           | 23.43            | 0                   | 22.24           | 22.40           | 22.42            | 1                   |
|                             | 1          | 24           | 23.16           | 23.32           | 23.34            | 0                   | 22.15           | 22.31           | 22.33            | 1                   |
|                             | 1          | 49           | 23.02           | 23.18           | 23.20            | 0                   | 22.01           | 22.17           | 22.19            | 1                   |
|                             | 25         | 0            | 22.31           | 22.47           | 22.49            | 1                   | 21.30           | 21.46           | 21.48            | 2                   |
|                             | 25         | 12           | 22.28           | 22.44           | 22.46            | 1                   | 21.27           | 21.43           | 21.45            | 2                   |
|                             | 25         | 25           | 22.19           | 22.35           | 22.37            | 1                   | 21.18           | 21.34           | 21.36            | 2                   |
|                             | 50         | 0            | 22.17           | 22.33           | 22.35            | 1                   | 21.16           | 21.32           | 21.34            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 10M                     | 1          | 0            | 20.40           | 20.43           | 20.47            | 0                   | 19.39           | 19.42           | 19.46            | 1                   |
|                             | 1          | 24           | 20.32           | 20.35           | 20.39            | 0                   | 19.31           | 19.34           | 19.38            | 1                   |
|                             | 1          | 49           | 20.23           | 20.26           | 20.30            | 0                   | 19.22           | 19.25           | 19.29            | 1                   |
|                             | 25         | 0            | 19.32           | 19.35           | 19.39            | 1                   | 18.31           | 18.34           | 18.38            | 2                   |
|                             | 25         | 12           | 19.28           | 19.31           | 19.35            | 1                   | 18.27           | 18.30           | 18.34            | 2                   |
|                             | 25         | 25           | 19.27           | 19.30           | 19.34            | 1                   | 18.26           | 18.29           | 18.33            | 2                   |
|                             | 50         | 0            | 19.31           | 19.34           | 19.38            | 1                   | 18.30           | 18.33           | 18.37            | 2                   |

# FCC SAR Test Report

A D T

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>20025 | Mid CH<br>20175 | High CH<br>20325 |                     | Low CH<br>20025 | Mid CH<br>20175 | High CH<br>20325 |                     |
|                             |            |              | 1717.5<br>MHz   | 1732.5<br>MHz   | 1747.5<br>MHz    |                     | 1717.5<br>MHz   | 1732.5<br>MHz   | 1747.5<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 15M                     | 1          | 0            | 23.37           | 23.53           | 23.55            | 0                   | 22.36           | 22.52           | 22.54            | 1                   |
|                             | 1          | 37           | 23.28           | 23.44           | 23.46            | 0                   | 22.27           | 22.43           | 22.45            | 1                   |
|                             | 1          | 74           | 23.14           | 23.30           | 23.32            | 0                   | 22.13           | 22.29           | 22.31            | 1                   |
|                             | 36         | 0            | 22.43           | 22.59           | 22.61            | 1                   | 21.42           | 21.58           | 21.60            | 2                   |
|                             | 36         | 19           | 22.40           | 22.56           | 22.58            | 1                   | 21.39           | 21.55           | 21.57            | 2                   |
|                             | 36         | 39           | 22.31           | 22.47           | 22.49            | 1                   | 21.30           | 21.46           | 21.48            | 2                   |
|                             | 75         | 0            | 22.29           | 22.45           | 22.47            | 1                   | 21.28           | 21.44           | 21.46            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 15M                     | 1          | 0            | 20.51           | 20.54           | 20.58            | 0                   | 19.50           | 19.53           | 19.57            | 1                   |
|                             | 1          | 37           | 20.43           | 20.46           | 20.50            | 0                   | 19.42           | 19.45           | 19.49            | 1                   |
|                             | 1          | 74           | 20.34           | 20.37           | 20.41            | 0                   | 19.33           | 19.36           | 19.40            | 1                   |
|                             | 36         | 0            | 19.43           | 19.46           | 19.50            | 1                   | 18.42           | 18.45           | 18.49            | 2                   |
|                             | 36         | 19           | 19.39           | 19.42           | 19.46            | 1                   | 18.38           | 18.41           | 18.45            | 2                   |
|                             | 36         | 39           | 19.38           | 19.41           | 19.45            | 1                   | 18.37           | 18.40           | 18.44            | 2                   |
|                             | 75         | 0            | 19.42           | 19.45           | 19.49            | 1                   | 18.41           | 18.44           | 18.48            | 2                   |

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>20050 | Mid CH<br>20175 | High CH<br>20300 |                     | Low CH<br>20050 | Mid CH<br>20175 | High CH<br>20300 |                     |
|                             |            |              | 1720.0<br>MHz   | 1732.5<br>MHz   | 1745.0<br>MHz    |                     | 1720.0<br>MHz   | 1732.5<br>MHz   | 1745.0<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 20M                     | 1          | 0            | 23.49           | 23.65           | 23.67            | 0                   | 22.48           | 22.64           | 22.66            | 1                   |
|                             | 1          | 50           | 23.40           | 23.56           | 23.58            | 0                   | 22.39           | 22.55           | 22.57            | 1                   |
|                             | 1          | 99           | 23.26           | 23.42           | 23.44            | 0                   | 22.25           | 22.41           | 22.43            | 1                   |
|                             | 50         | 0            | 22.55           | 22.71           | 22.73            | 1                   | 21.54           | 21.70           | 21.72            | 2                   |
|                             | 50         | 25           | 22.52           | 22.68           | 22.70            | 1                   | 21.51           | 21.67           | 21.69            | 2                   |
|                             | 50         | 50           | 22.43           | 22.59           | 22.61            | 1                   | 21.42           | 21.58           | 21.60            | 2                   |
|                             | 100        | 0            | 22.41           | 22.57           | 22.59            | 1                   | 21.40           | 21.56           | 21.58            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 4 / 20M                     | 1          | 0            | 20.62           | 20.65           | 20.69            | 0                   | 19.61           | 19.64           | 19.68            | 1                   |
|                             | 1          | 50           | 20.54           | 20.57           | 20.61            | 0                   | 19.53           | 19.56           | 19.60            | 1                   |
|                             | 1          | 99           | 20.45           | 20.48           | 20.52            | 0                   | 19.44           | 19.47           | 19.51            | 1                   |
|                             | 50         | 0            | 19.54           | 19.57           | 19.61            | 1                   | 18.53           | 18.56           | 18.60            | 2                   |
|                             | 50         | 25           | 19.50           | 19.53           | 19.57            | 1                   | 18.49           | 18.52           | 18.56            | 2                   |
|                             | 50         | 50           | 19.49           | 19.52           | 19.56            | 1                   | 18.48           | 18.51           | 18.55            | 2                   |
|                             | 100        | 0            | 19.53           | 19.56           | 19.60            | 1                   | 18.52           | 18.55           | 18.59            | 2                   |

# FCC SAR Test Report

A D T

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                             |            |              | Low CH<br>23205 | Mid CH<br>23230 | High CH<br>23255 |                     | Low CH<br>23205 | Mid CH<br>23230 | High CH<br>23255 |                     |
|                             |            |              | 779.5<br>MHz    | 782.0<br>MHz    | 784.5<br>MHz     |                     | 779.5<br>MHz    | 782.0<br>MHz    | 784.5<br>MHz     |                     |
| EUT without Power Reduction |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 13 / 5M                     | 1          | 0            | 23.75           | 23.65           | 23.66            | 0                   | 22.73           | 22.63           | 22.64            | 1                   |
|                             | 1          | 12           | 23.73           | 23.63           | 23.64            | 0                   | 22.71           | 22.61           | 22.62            | 1                   |
|                             | 1          | 24           | 23.72           | 23.62           | 23.63            | 0                   | 22.70           | 22.60           | 22.61            | 1                   |
|                             | 12         | 0            | 22.71           | 22.61           | 22.62            | 1                   | 21.69           | 21.59           | 21.60            | 2                   |
|                             | 12         | 6            | 22.66           | 22.56           | 22.57            | 1                   | 21.64           | 21.54           | 21.55            | 2                   |
|                             | 12         | 13           | 22.67           | 22.57           | 22.58            | 1                   | 21.65           | 21.55           | 21.56            | 2                   |
|                             | 25         | 0            | 22.68           | 22.58           | 22.59            | 1                   | 21.66           | 21.56           | 21.57            | 2                   |
| EUT with Power Reduction    |            |              |                 |                 |                  |                     |                 |                 |                  |                     |
| 13 / 5M                     | 1          | 0            | 17.89           | 17.90           | 17.88            | 0                   | 16.88           | 16.89           | 16.87            | 1                   |
|                             | 1          | 12           | 17.83           | 17.84           | 17.82            | 0                   | 16.82           | 16.83           | 16.81            | 1                   |
|                             | 1          | 24           | 17.82           | 17.83           | 17.81            | 0                   | 16.81           | 16.82           | 16.80            | 1                   |
|                             | 12         | 0            | 16.85           | 16.86           | 16.84            | 1                   | 15.84           | 15.85           | 15.83            | 2                   |
|                             | 12         | 6            | 16.73           | 16.74           | 16.72            | 1                   | 15.72           | 15.73           | 15.71            | 2                   |
|                             | 12         | 13           | 16.72           | 16.73           | 16.71            | 1                   | 15.71           | 15.72           | 15.70            | 2                   |
|                             | 25         | 0            | 16.79           | 16.80           | 16.78            | 1                   | 15.78           | 15.79           | 15.77            | 2                   |

| LTE<br>Band / BW            | RB<br>Size | RB<br>Offset | QPSK            | 3GPP<br>MPR<br>(dB) | 16QAM           | 3GPP<br>MPR<br>(dB) |
|-----------------------------|------------|--------------|-----------------|---------------------|-----------------|---------------------|
|                             |            |              | Mid CH<br>23230 |                     | Mid CH<br>23230 |                     |
|                             |            |              | 782.0<br>MHz    |                     | 782.0<br>MHz    |                     |
| EUT without Power Reduction |            |              |                 |                     |                 |                     |
| 13 / 10M                    | 1          | 0            | 23.71           | 0                   | 22.68           | 1                   |
|                             | 1          | 24           | 23.66           | 0                   | 22.63           | 1                   |
|                             | 1          | 49           | 23.64           | 0                   | 22.61           | 1                   |
|                             | 25         | 0            | 22.60           | 1                   | 21.57           | 2                   |
|                             | 25         | 12           | 22.55           | 1                   | 21.52           | 2                   |
|                             | 25         | 25           | 22.56           | 1                   | 21.53           | 2                   |
|                             | 50         | 0            | 22.61           | 1                   | 21.58           | 2                   |
| EUT with Power Reduction    |            |              |                 |                     |                 |                     |
| 13 / 10M                    | 1          | 0            | 17.98           | 0                   | 16.88           | 1                   |
|                             | 1          | 24           | 17.87           | 0                   | 16.86           | 1                   |
|                             | 1          | 49           | 17.88           | 0                   | 16.87           | 1                   |
|                             | 25         | 0            | 16.81           | 1                   | 15.80           | 2                   |
|                             | 25         | 12           | 16.80           | 1                   | 15.79           | 2                   |
|                             | 25         | 25           | 16.79           | 1                   | 15.78           | 2                   |
|                             | 50         | 0            | 16.79           | 1                   | 15.78           | 2                   |

# FCC SAR Test Report

A D T

| LTE<br>Band / BW | RB<br>Size | RB<br>Offset | QPSK            |                 |                  | 3GPP<br>MPR<br>(dB) | 16QAM           |                 |                  | 3GPP<br>MPR<br>(dB) |
|------------------|------------|--------------|-----------------|-----------------|------------------|---------------------|-----------------|-----------------|------------------|---------------------|
|                  |            |              | Low CH<br>23305 | Mid CH<br>23330 | High CH<br>23355 |                     | Low CH<br>23305 | Mid CH<br>23330 | High CH<br>23355 |                     |
|                  |            |              | 790.5<br>MHz    | 793.0<br>MHz    | 795.5<br>MHz     |                     | 790.5<br>MHz    | 793.0<br>MHz    | 795.5<br>MHz     |                     |
| 14 / 5M          | 1          | 0            | 23.64           | <b>23.75</b>    | 23.63            | 0                   | 22.62           | 22.73           | 22.61            | 1                   |
|                  | 1          | 12           | 23.51           | 23.62           | 23.50            | 0                   | 22.49           | 22.60           | 22.48            | 1                   |
|                  | 1          | 24           | 23.56           | 23.67           | 23.55            | 0                   | 22.54           | 22.65           | 22.53            | 1                   |
|                  | 12         | 0            | 22.50           | 22.61           | 22.49            | 1                   | 21.48           | 21.59           | 21.47            | 2                   |
|                  | 12         | 6            | 22.44           | 22.55           | 22.43            | 1                   | 21.42           | 21.53           | 21.41            | 2                   |
|                  | 12         | 13           | 22.47           | 22.58           | 22.46            | 1                   | 21.45           | 21.56           | 21.44            | 2                   |
|                  | 25         | 0            | 22.48           | 22.59           | 22.47            | 1                   | 21.46           | 21.57           | 21.45            | 2                   |

| LTE<br>Band / BW | RB<br>Size | RB<br>Offset | QPSK            | 3GPP<br>MPR<br>(dB) | 16QAM           | 3GPP<br>MPR<br>(dB) |
|------------------|------------|--------------|-----------------|---------------------|-----------------|---------------------|
|                  |            |              | Mid CH<br>23330 |                     | Mid CH<br>23330 |                     |
|                  |            |              | 793.0<br>MHz    |                     | 793.0<br>MHz    |                     |
| 14 / 10M         | 1          | 0            | 23.69           | 0                   | 22.67           | 1                   |
|                  | 1          | 24           | 23.61           | 0                   | 22.59           | 1                   |
|                  | 1          | 49           | 23.63           | 0                   | 22.61           | 1                   |
|                  | 25         | 0            | 22.61           | 1                   | 21.60           | 2                   |
|                  | 25         | 12           | 22.59           | 1                   | 21.57           | 2                   |
|                  | 25         | 25           | 22.58           | 1                   | 21.56           | 2                   |
|                  | 50         | 0            | 22.60           | 1                   | 21.58           | 2                   |

## <WLAN 2.4G>

| Mode                      | 802.11b        |              |              |
|---------------------------|----------------|--------------|--------------|
| Channel / Frequency (MHz) | 1 (2412)       | 6 (2437)     | 11 (2462)    |
| Average Power             | 15.04          | 16.14        | <b>16.15</b> |
| Mode                      | 802.11g        |              |              |
| Channel / Frequency (MHz) | 1 (2412)       | 6 (2437)     | 11 (2462)    |
| Average Power             | 14.15          | 15.54        | <b>15.56</b> |
| Mode                      | 802.11n (HT20) |              |              |
| Channel / Frequency (MHz) | 1 (2412)       | 6 (2437)     | 11 (2462)    |
| Average Power             | 12.73          | <b>14.39</b> | 13.83        |

## <WLAN 5.2G>

| Mode                      | 802.11a        |              |           |           |
|---------------------------|----------------|--------------|-----------|-----------|
| Channel / Frequency (MHz) | 36 (5180)      | 40 (5200)    | 44 (5220) | 48 (5240) |
| Average Power             | 15.27          | <b>15.50</b> | 15.19     | 15.14     |
| Mode                      | 802.11n (HT20) |              |           |           |
| Channel / Frequency (MHz) | 36 (5180)      | 40 (5200)    | 44 (5220) | 48 (5240) |
| Average Power             | 15.10          | <b>15.22</b> | 15.07     | 15.18     |
| Mode                      | 802.11n (HT40) |              |           |           |
| Channel / Frequency (MHz) | 38 (5190)      |              | 46 (5230) |           |
| Average Power             | <b>15.29</b>   |              | 15.11     |           |

# FCC SAR Test Report

A D T

## <WLAN 5.3G>

| Mode                      | 802.11a        |           |           |           |
|---------------------------|----------------|-----------|-----------|-----------|
| Channel / Frequency (MHz) | 52 (5260)      | 56 (5280) | 60 (5300) | 64 (5320) |
| Average Power             | 15.02          | 15.05     | 14.94     | 14.80     |
| Mode                      | 802.11n (HT20) |           |           |           |
| Channel / Frequency (MHz) | 52 (5260)      | 56 (5280) | 60 (5300) | 64 (5320) |
| Average Power             | 15.23          | 15.21     | 15.15     | 15.33     |
| Mode                      | 802.11n (HT40) |           |           |           |
| Channel / Frequency (MHz) | 54 (5270)      |           | 62 (5310) |           |
| Average Power             | 15.33          |           | 14.94     |           |

## <WLAN 5.6G>

| Mode                      | 802.11a        |            |            |            |            |            |            |            |
|---------------------------|----------------|------------|------------|------------|------------|------------|------------|------------|
| Channel / Frequency (MHz) | 100 (5500)     | 104 (5520) | 108 (5540) | 112 (5560) | 116 (5580) | 132 (5660) | 136 (5680) | 140 (5700) |
| Average Power             | 15.11          | 14.82      | 14.91      | 14.88      | 14.78      | 14.89      | 14.83      | 13.76      |
| Mode                      | 802.11n (HT20) |            |            |            |            |            |            |            |
| Channel / Frequency (MHz) | 100 (5500)     | 104 (5520) | 108 (5540) | 112 (5560) | 116 (5580) | 132 (5660) | 136 (5680) | 140 (5700) |
| Average Power             | 15.15          | 15.13      | 15.08      | 15.06      | 15.03      | 13.90      | 13.88      | 13.77      |
| Mode                      | 802.11n (HT40) |            |            |            |            |            |            |            |
| Channel / Frequency (MHz) | 102 (5510)     |            |            |            | 134 (5670) |            |            |            |
| Average Power             | 13.63          |            |            |            | 13.91      |            |            |            |

## <WLAN 5.8G>

| Mode                      | 802.11a        |            |            |            |            |
|---------------------------|----------------|------------|------------|------------|------------|
| Channel / Frequency (MHz) | 149 (5745)     | 153 (5765) | 157 (5785) | 161 (5805) | 165 (5825) |
| Average Power             | 14.44          | 14.23      | 14.35      | 14.29      | 14.03      |
| Mode                      | 802.11n (HT20) |            |            |            |            |
| Channel / Frequency (MHz) | 149 (5745)     | 153 (5765) | 157 (5785) | 161 (5805) | 165 (5825) |
| Average Power             | 14.45          | 14.38      | 14.32      | 14.25      | 14.11      |
| Mode                      | 802.11n (HT40) |            |            |            |            |
| Channel / Frequency (MHz) | 151 (5755)     |            | 159 (5795) |            |            |
| Average Power             | 14.25          |            | 14.01      |            |            |

## 4.7 SAR Testing Results

### 4.7.1 SAR Results for Head

| Plot No. | Band     | Mode     | Test Position | Ch. | Battery | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|----------|---------------|-----|---------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 01       | CDMA BC0 | RC3+SO55 | Right Cheek   | 384 | 1       | 25.5                     | 25.16                          | 1.08           | -0.13            | 0.672                  | 0.73                 |
|          | CDMA BC0 | RC3+SO55 | Right Tilted  | 384 | 1       | 25.5                     | 25.16                          | 1.08           | -0.16            | 0.382                  | 0.41                 |
|          | CDMA BC0 | RC3+SO55 | Left Cheek    | 384 | 1       | 25.5                     | 25.16                          | 1.08           | 0.1              | 0.52                   | 0.56                 |
|          | CDMA BC0 | RC3+SO55 | Left Tilted   | 384 | 1       | 25.5                     | 25.16                          | 1.08           | -0.13            | 0.348                  | 0.38                 |
|          | CDMA BC0 | RC3+SO55 | Right Cheek   | 384 | 2       | 25.5                     | 25.16                          | 1.08           | -0.13            | 0.643                  | 0.70                 |
| 02       | CDMA BC1 | RC3+SO55 | Right Cheek   | 25  | 1       | 25.0                     | 24.99                          | 1.00           | 0.19             | 0.602                  | 0.60                 |
|          | CDMA BC1 | RC3+SO55 | Right Tilted  | 25  | 1       | 25.0                     | 24.99                          | 1.00           | 0.12             | 0.223                  | 0.22                 |
|          | CDMA BC1 | RC3+SO55 | Left Cheek    | 25  | 1       | 25.0                     | 24.99                          | 1.00           | -0.13            | 0.122                  | 0.12                 |
|          | CDMA BC1 | RC3+SO55 | Left Tilted   | 25  | 1       | 25.0                     | 24.99                          | 1.00           | 0.15             | 0.223                  | 0.22                 |
|          | CDMA BC1 | RC3+SO55 | Right Cheek   | 25  | 2       | 25.0                     | 24.99                          | 1.00           | 0.12             | 0.514                  | 0.52                 |

#### Note:

- SAR is performed on the highest power channel. When the reported SAR value of highest power channel is  $\leq 0.8$  W/kg, SAR testing for optional channel is not required.

| Plot No. | Band  | Mode    | Test Position | Ch.   | Power Reduction | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-------|---------|---------------|-------|-----------------|---------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 4 | QPSK20M | Right Cheek   | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.06            | 0.277                  | 0.30                 |
|          | LTE 4 | QPSK20M | Right Cheek   | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | -0.06            | 0.198                  | 0.21                 |
|          | LTE 4 | QPSK20M | Right Tilted  | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | 0.1              | 0.214                  | 0.23                 |
|          | LTE 4 | QPSK20M | Right Tilted  | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | 0.06             | 0.17                   | 0.18                 |
|          | LTE 4 | QPSK20M | Left Cheek    | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.01            | 0.424                  | 0.46                 |
|          | LTE 4 | QPSK20M | Left Cheek    | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | 0.01             | 0.338                  | 0.36                 |
|          | LTE 4 | QPSK20M | Left Tilted   | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.03            | 0.186                  | 0.20                 |
|          | LTE 4 | QPSK20M | Left Tilted   | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | -0.06            | 0.147                  | 0.16                 |
| 03       | LTE 4 | QPSK20M | Left Cheek    | 20300 | w/o             | 2       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.08            | 0.477                  | 0.51                 |
|          | LTE 4 | QPSK20M | Right Cheek   | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | -0.02            | 0.122                  | 0.13                 |
|          | LTE 4 | QPSK20M | Right Cheek   | 20300 | w               | 1       | 50  | 0         | 21.0                     | 20.69                          | 1.09           | -0.05            | 0.087                  | 0.10                 |
|          | LTE 4 | QPSK20M | Right Tilted  | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.01             | 0.095                  | 0.10                 |
|          | LTE 4 | QPSK20M | Right Tilted  | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | 0.12             | 0.072                  | 0.08                 |
|          | LTE 4 | QPSK20M | Left Cheek    | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.08             | 0.191                  | 0.21                 |
|          | LTE 4 | QPSK20M | Left Cheek    | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | 0.05             | 0.149                  | 0.16                 |
|          | LTE 4 | QPSK20M | Left Tilted   | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | -0.06            | 0.081                  | 0.09                 |
|          | LTE 4 | QPSK20M | Left Tilted   | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | -0.01            | 0.062                  | 0.07                 |
|          | LTE 4 | QPSK20M | Left Cheek    | 20300 | w               | 2       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.06             | 0.084                  | 0.09                 |

#### Note:

- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
- According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.



# FCC SAR Test Report

A D T

| Plot No. | Band   | Mode    | Test Position | Ch.   | Power Reduction | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|---------------|-------|-----------------|---------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 13 | QPSK10M | Right Cheek   | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.07            | 0.399                  | 0.43                 |
|          | LTE 13 | QPSK10M | Right Cheek   | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.16            | 0.301                  | 0.33                 |
|          | LTE 13 | QPSK10M | Right Tilted  | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0                | 0.226                  | 0.24                 |
|          | LTE 13 | QPSK10M | Right Tilted  | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.07            | 0.172                  | 0.19                 |
| 04       | LTE 13 | QPSK10M | Left Cheek    | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0.12             | 0.46                   | 0.49                 |
|          | LTE 13 | QPSK10M | Left Cheek    | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.11            | 0.353                  | 0.39                 |
|          | LTE 13 | QPSK10M | Left Tilted   | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.04            | 0.26                   | 0.28                 |
|          | LTE 13 | QPSK10M | Left Tilted   | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | 0.01             | 0.199                  | 0.22                 |
|          | LTE 13 | QPSK10M | Left Cheek    | 23230 | w/o             | 2       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0.03             | 0.452                  | 0.48                 |
|          | LTE 13 | QPSK10M | Right Cheek   | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.07             | 0.087                  | 0.09                 |
|          | LTE 13 | QPSK10M | Right Cheek   | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | -0.12            | 0.069                  | 0.07                 |
|          | LTE 13 | QPSK10M | Right Tilted  | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.14             | 0.042                  | 0.04                 |
|          | LTE 13 | QPSK10M | Right Tilted  | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | -0.02            | 0.032                  | 0.03                 |
|          | LTE 13 | QPSK10M | Left Cheek    | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.03             | 0.104                  | 0.10                 |
|          | LTE 13 | QPSK10M | Left Cheek    | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | -0.03            | 0.081                  | 0.08                 |
|          | LTE 13 | QPSK10M | Left Tilted   | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.07             | 0.051                  | 0.05                 |
|          | LTE 13 | QPSK10M | Left Tilted   | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.16             | 0.039                  | 0.04                 |
|          | LTE 13 | QPSK10M | Left Cheek    | 23230 | w               | 2       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.03             | 0.103                  | 0.10                 |
|          | LTE 14 | QPSK10M | Right Cheek   | 23330 | w/o             | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.14            | 0.324                  | 0.35                 |
|          | LTE 14 | QPSK10M | Right Cheek   | 23330 | w/o             | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.01            | 0.259                  | 0.28                 |
|          | LTE 14 | QPSK10M | Right Tilted  | 23330 | w/o             | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.12            | 0.169                  | 0.18                 |
|          | LTE 14 | QPSK10M | Right Tilted  | 23330 | w/o             | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.02            | 0.136                  | 0.15                 |
|          | LTE 14 | QPSK10M | Left Cheek    | 23330 | w/o             | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.01             | 0.345                  | 0.37                 |
|          | LTE 14 | QPSK10M | Left Cheek    | 23330 | w/o             | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | 0.16             | 0.28                   | 0.31                 |
|          | LTE 14 | QPSK10M | Left Tilted   | 23330 | w/o             | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.03             | 0.212                  | 0.23                 |
|          | LTE 14 | QPSK10M | Left Tilted   | 23330 | w/o             | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | 0.02             | 0.163                  | 0.18                 |
| 05       | LTE 14 | QPSK10M | Left Cheek    | 23330 | w/o             | 2       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.07             | 0.361                  | 0.39                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

# FCC SAR Test Report

A D T

| Plot No. | Band    | Test Position | Ch. | Battery | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|---------|---------------|-----|---------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | 802.11b | Right Cheek   | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.11             | 0.300                  | 0.33                 |
|          | 802.11b | Right Tilted  | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.11             | 0.063                  | 0.07                 |
|          | 802.11b | Left Cheek    | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.09             | 0.417                  | 0.45                 |
|          | 802.11b | Left Tilted   | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.06             | 0.103                  | 0.11                 |
| 06       | 802.11b | Left Cheek    | 11  | 2       | 16.5                     | 16.15                          | 1.08           | 0.15             | 0.448                  | 0.49                 |
|          | 802.11a | Right Cheek   | 40  | 1       | 15.5                     | 15.50                          | 1.00           | -0.10            | 0.253                  | 0.25                 |
|          | 802.11a | Right Tilted  | 40  | 1       | 15.5                     | 15.50                          | 1.00           | -0.02            | 0.078                  | 0.08                 |
| 07       | 802.11a | Left Cheek    | 40  | 1       | 15.5                     | 15.50                          | 1.00           | -0.07            | 0.436                  | 0.44                 |
|          | 802.11a | Left Tilted   | 40  | 1       | 15.5                     | 15.50                          | 1.00           | 0.01             | 0.08                   | 0.08                 |
|          | 802.11a | Left Cheek    | 40  | 2       | 15.5                     | 15.50                          | 1.00           | 0                | 0.393                  | 0.39                 |
|          | 802.11a | Right Cheek   | 56  | 1       | 15.5                     | 15.05                          | 1.11           | -0.06            | 0.174                  | 0.19                 |
|          | 802.11a | Right Tilted  | 56  | 1       | 15.5                     | 15.05                          | 1.11           | 0.01             | 0.054                  | 0.06                 |
|          | 802.11a | Left Cheek    | 56  | 1       | 15.5                     | 15.05                          | 1.11           | -0.02            | 0.338                  | 0.37                 |
|          | 802.11a | Left Tilted   | 56  | 1       | 15.5                     | 15.05                          | 1.11           | 0.09             | 0.061                  | 0.07                 |
| 08       | 802.11a | Left Cheek    | 56  | 2       | 15.5                     | 15.05                          | 1.11           | 0                | 0.354                  | 0.39                 |
|          | 802.11a | Right Cheek   | 100 | 1       | 15.5                     | 15.11                          | 1.09           | 0.11             | 0.231                  | 0.25                 |
|          | 802.11a | Right Tilted  | 100 | 1       | 15.5                     | 15.11                          | 1.09           | 0.12             | 0.065                  | 0.07                 |
|          | 802.11a | Left Cheek    | 100 | 1       | 15.5                     | 15.11                          | 1.09           | -0.13            | 0.337                  | 0.37                 |
|          | 802.11a | Left Tilted   | 100 | 1       | 15.5                     | 15.11                          | 1.09           | 0.13             | 0.063                  | 0.07                 |
| 09       | 802.11a | Left Cheek    | 100 | 2       | 15.5                     | 15.11                          | 1.09           | -0.04            | 0.507                  | 0.55                 |
|          | 802.11a | Right Cheek   | 149 | 1       | 14.5                     | 14.44                          | 1.01           | -0.11            | 0.252                  | 0.26                 |
|          | 802.11a | Right Tilted  | 149 | 1       | 14.5                     | 14.44                          | 1.01           | 0.17             | 0.058                  | 0.06                 |
|          | 802.11a | Left Cheek    | 149 | 1       | 14.5                     | 14.44                          | 1.01           | 0.00             | 0.262                  | 0.27                 |
|          | 802.11a | Left Tilted   | 149 | 1       | 14.5                     | 14.44                          | 1.01           | -0.13            | 0.060                  | 0.06                 |
| 10       | 802.11a | Left Cheek    | 149 | 2       | 14.5                     | 14.44                          | 1.01           | -0.15            | 0.582                  | 0.59                 |

## Note:

1. According to KDB 248227, when the extrapolated maximum peak SAR for the maximum output power channel is  $\leq 1.6$  W/kg and the 1g averaged SAR is  $\leq 0.8$  W/kg, WLAN SAR testing for other channels is not required.
2. SAR testing for 802.11g/n is not required when its maximum power is less than 1/4 dB higher than 802.11b.
3. SAR testing for 802.11n is not required when its maximum power is less than 1/4 dB higher than 802.11a.

## 4.7.2 SAR Results for Body-Worn

| Plot No. | Band     | Mode       | Test Position            | Ch.  | Gap (cm) | Holster | Battery | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|------------|--------------------------|------|----------|---------|---------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 11       | CDMA BC0 | RTAP 153.6 | Front Face               | 384  | 1        | w/o     | 1       | 25.5                     | 24.44                          | 1.28           | -0.02            | 0.564                  | 0.72                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face                | 384  | 1        | w/o     | 1       | 25.5                     | 24.44                          | 1.28           | 0.02             | 0.793                  | 1.01                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face                | 1013 | 1        | w/o     | 1       | 25.5                     | 24.31                          | 1.32           | 0.03             | 0.753                  | 0.99                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face                | 777  | 1        | w/o     | 1       | 25.5                     | 24.41                          | 1.29           | 0.02             | 0.706                  | 0.91                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face                | 384  | 1        | w/o     | 2       | 25.5                     | 24.44                          | 1.28           | 0.01             | 0.645                  | 0.82                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face                | 1013 | 1        | w/o     | 2       | 25.5                     | 24.31                          | 1.32           | 0.02             | 0.593                  | 0.78                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face                | 777  | 1        | w/o     | 2       | 25.5                     | 24.41                          | 1.29           | 0.01             | 0.552                  | 0.71                 |
|          | CDMA BC0 | RTAP 153.6 | Front Face + Top Side    | 384  | 0        | w/      | 1       | 25.5                     | 24.44                          | 1.28           | 0.1              | 0.453                  | 0.58                 |
|          | CDMA BC0 | RTAP 153.6 | Front Face + Bottom Side | 384  | 0        | w/      | 1       | 25.5                     | 24.44                          | 1.28           | -0.02            | 0.487                  | 0.62                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face + Top Side     | 384  | 0        | w/      | 1       | 25.5                     | 24.44                          | 1.28           | 0                | 0.55                   | 0.70                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face + Bottom Side  | 384  | 0        | w/      | 1       | 25.5                     | 24.44                          | 1.28           | -0.03            | 0.506                  | 0.65                 |
| 12       | CDMA BC0 | RTAP 153.6 | Rear Face + Top Side     | 384  | 0        | w/      | 2       | 25.5                     | 24.44                          | 1.28           | 0.03             | 0.482                  | 0.62                 |
|          | CDMA BC1 | RTAP 153.6 | Front Face               | 25   | 1        | w/o     | 1       | 25.0                     | 24.57                          | 1.10           | -0.15            | 0.584                  | 0.64                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face                | 25   | 1        | w/o     | 1       | 25.0                     | 24.57                          | 1.10           | -0.19            | 0.686                  | 0.76                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face                | 25   | 1        | w/o     | 2       | 25.0                     | 24.57                          | 1.10           | 0.04             | 0.25                   | 0.28                 |
|          | CDMA BC1 | RTAP 153.6 | Front Face + Top Side    | 25   | 0        | w/      | 1       | 25.0                     | 24.57                          | 1.10           | 0.045            | 0.252                  | 0.28                 |
|          | CDMA BC1 | RTAP 153.6 | Front Face + Bottom Side | 25   | 0        | w/      | 1       | 25.0                     | 24.57                          | 1.10           | -0.13            | 0.141                  | 0.16                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face + Top Side     | 25   | 0        | w/      | 1       | 25.0                     | 24.57                          | 1.10           | 0.15             | 0.254                  | 0.28                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face + Bottom Side  | 25   | 0        | w/      | 1       | 25.0                     | 24.57                          | 1.10           | -0.16            | 0.199                  | 0.22                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face + Top Side     | 25   | 0        | w/      | 2       | 25.0                     | 24.57                          | 1.10           | 0.1              | 0.202                  | 0.22                 |

### Note:

- SAR is performed on the highest power channel. When the reported SAR value of highest power channel is  $\leq 0.8$  W/kg, SAR testing for optional channel is not required.

# FCC SAR Test Report

A D T

| Plot No. | Band  | Mode    | Test Position            | Ch.   | Power Reduction | Gap (cm) | Holster | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-------|---------|--------------------------|-------|-----------------|----------|---------|---------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 4 | QPSK20M | Front Face               | 20300 | w/o             | 1        | w/o     | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | 0.15             | 0.539                  | 0.58                 |
|          | LTE 4 | QPSK20M | Front Face               | 20300 | w/o             | 1        | w/o     | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | -0.04            | 0.424                  | 0.45                 |
|          | LTE 4 | QPSK20M | Rear Face                | 20300 | w/o             | 1        | w/o     | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.02            | 0.449                  | 0.48                 |
|          | LTE 4 | QPSK20M | Rear Face                | 20300 | w/o             | 1        | w/o     | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | 0.07             | 0.354                  | 0.38                 |
| 13       | LTE 4 | QPSK20M | Front Face               | 20300 | w/o             | 1        | w/o     | 2       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | 0.17             | 0.646                  | 0.70                 |
|          | LTE 4 | QPSK20M | Front Face + Top Side    | 20300 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | 0.05             | 0.147                  | 0.16                 |
|          | LTE 4 | QPSK20M | Front Face + Top Side    | 20300 | w/o             | 0        | w/      | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | -0.03            | 0.114                  | 0.12                 |
|          | LTE 4 | QPSK20M | Front Face + Bottom Side | 20300 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.06            | 0.155                  | 0.17                 |
|          | LTE 4 | QPSK20M | Front Face + Bottom Side | 20300 | w/o             | 0        | w/      | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | -0.04            | 0.126                  | 0.13                 |
|          | LTE 4 | QPSK20M | Rear Face + Top Side     | 20300 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | 0.09             | 0.384                  | 0.41                 |
|          | LTE 4 | QPSK20M | Rear Face + Top Side     | 20300 | w/o             | 0        | w/      | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | -0.02            | 0.29                   | 0.31                 |
|          | LTE 4 | QPSK20M | Rear Face + Bottom Side  | 20300 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | 0.01             | 0.255                  | 0.28                 |
|          | LTE 4 | QPSK20M | Rear Face + Bottom Side  | 20300 | w/o             | 0        | w/      | 1       | 50  | 0         | 23.0                     | 22.73                          | 1.06           | 0.07             | 0.199                  | 0.21                 |
|          | LTE 4 | QPSK20M | Rear Face + Top Side     | 20300 | w/o             | 0        | w/      | 2       | 1   | 0         | 24.0                     | 23.67                          | 1.08           | -0.09            | 0.231                  | 0.25                 |
|          | LTE 4 | QPSK20M | Front Face               | 20300 | w               | 1        | w/o     | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.08             | 0.236                  | 0.25                 |
|          | LTE 4 | QPSK20M | Front Face               | 20300 | w               | 1        | w/o     | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | 0.01             | 0.185                  | 0.20                 |
|          | LTE 4 | QPSK20M | Rear Face                | 20300 | w               | 1        | w/o     | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.13             | 0.19                   | 0.20                 |
|          | LTE 4 | QPSK20M | Rear Face                | 20300 | w               | 1        | w/o     | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | -0.06            | 0.154                  | 0.17                 |
|          | LTE 4 | QPSK20M | Front Face               | 20300 | w               | 1        | w/o     | 2       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.14             | 0.285                  | 0.31                 |
|          | LTE 4 | QPSK20M | Front Face + Top Side    | 20300 | w               | 0        | w/      | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.06             | 0.061                  | 0.07                 |
|          | LTE 4 | QPSK20M | Front Face + Top Side    | 20300 | w               | 0        | w/      | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | 0.12             | 0.047                  | 0.05                 |
|          | LTE 4 | QPSK20M | Front Face + Bottom Side | 20300 | w               | 0        | w/      | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | -0.08            | 0.065                  | 0.07                 |
|          | LTE 4 | QPSK20M | Front Face + Bottom Side | 20300 | w               | 0        | w/      | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | 0.11             | 0.051                  | 0.06                 |
|          | LTE 4 | QPSK20M | Rear Face + Top Side     | 20300 | w               | 0        | w/      | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | -0.04            | 0.17                   | 0.18                 |
|          | LTE 4 | QPSK20M | Rear Face + Top Side     | 20300 | w               | 0        | w/      | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | -0.03            | 0.124                  | 0.14                 |
|          | LTE 4 | QPSK20M | Rear Face + Bottom Side  | 20300 | w               | 0        | w/      | 1       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | 0.02             | 0.108                  | 0.12                 |
|          | LTE 4 | QPSK20M | Rear Face + Bottom Side  | 20300 | w               | 0        | w/      | 1       | 50  | 0         | 20.0                     | 19.61                          | 1.09           | 0.09             | 0.084                  | 0.09                 |
|          | LTE 4 | QPSK20M | Rear Face + Top Side     | 20300 | w               | 0        | w/      | 2       | 1   | 0         | 21.0                     | 20.69                          | 1.07           | -0.1             | 0.098                  | 0.11                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

# FCC SAR Test Report

A D T

| Plot No. | Band   | Mode    | Test Position            | Ch.   | Power Reduction | Gap (cm) | Holster | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|--------------------------|-------|-----------------|----------|---------|---------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 14       | LTE 13 | QPSK10M | Front Face               | 23230 | w/o             | 1        | w/o     | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0                | 0.623                  | 0.67                 |
|          | LTE 13 | QPSK10M | Front Face               | 23230 | w/o             | 1        | w/o     | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.02            | 0.472                  | 0.52                 |
|          | LTE 13 | QPSK10M | Rear Face                | 23230 | w/o             | 1        | w/o     | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.03            | 0.649                  | 0.69                 |
|          | LTE 13 | QPSK10M | Rear Face                | 23230 | w/o             | 1        | w/o     | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.03            | 0.488                  | 0.54                 |
|          | LTE 13 | QPSK10M | Rear Face                | 23230 | w/o             | 1        | w/o     | 2       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.05            | 0.529                  | 0.57                 |
|          | LTE 13 | QPSK10M | Front Face + Top Side    | 23230 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.02            | 0.405                  | 0.43                 |
|          | LTE 13 | QPSK10M | Front Face + Top Side    | 23230 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | 0.01             | 0.304                  | 0.33                 |
|          | LTE 13 | QPSK10M | Front Face + Bottom Side | 23230 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0.01             | 0.34                   | 0.36                 |
|          | LTE 13 | QPSK10M | Front Face + Bottom Side | 23230 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.01            | 0.25                   | 0.27                 |
|          | LTE 13 | QPSK10M | Rear Face + Top Side     | 23230 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0                | 0.409                  | 0.44                 |
|          | LTE 13 | QPSK10M | Rear Face + Top Side     | 23230 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.02            | 0.304                  | 0.33                 |
|          | LTE 13 | QPSK10M | Rear Face + Bottom Side  | 23230 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0.02             | 0.365                  | 0.39                 |
|          | LTE 13 | QPSK10M | Rear Face + Bottom Side  | 23230 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | 0.02             | 0.272                  | 0.30                 |
|          | LTE 13 | QPSK10M | Rear Face + Top Side     | 23230 | w/o             | 0        | w/      | 2       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0.02             | 0.351                  | 0.38                 |
|          | LTE 13 | QPSK10M | Front Face               | 23230 | w               | 1        | w/o     | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.02             | 0.151                  | 0.15                 |
|          | LTE 13 | QPSK10M | Front Face               | 23230 | w               | 1        | w/o     | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.08             | 0.118                  | 0.12                 |
|          | LTE 13 | QPSK10M | Rear Face                | 23230 | w               | 1        | w/o     | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.06             | 0.17                   | 0.17                 |
|          | LTE 13 | QPSK10M | Rear Face                | 23230 | w               | 1        | w/o     | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.02             | 0.132                  | 0.14                 |
|          | LTE 13 | QPSK10M | Rear Face                | 23230 | w               | 1        | w/o     | 2       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.03             | 0.139                  | 0.14                 |
|          | LTE 13 | QPSK10M | Front Face + Top Side    | 23230 | w               | 0        | w/      | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.08             | 0.098                  | 0.10                 |
|          | LTE 13 | QPSK10M | Front Face + Top Side    | 23230 | w               | 0        | w/      | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.06             | 0.077                  | 0.08                 |
|          | LTE 13 | QPSK10M | Front Face + Bottom Side | 23230 | w               | 0        | w/      | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.04             | 0.082                  | 0.08                 |
|          | LTE 13 | QPSK10M | Front Face + Bottom Side | 23230 | w               | 0        | w/      | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.04             | 0.064                  | 0.07                 |
|          | LTE 13 | QPSK10M | Rear Face + Top Side     | 23230 | w               | 0        | w/      | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.05             | 0.103                  | 0.10                 |
|          | LTE 13 | QPSK10M | Rear Face + Top Side     | 23230 | w               | 0        | w/      | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | -0.07            | 0.08                   | 0.08                 |
|          | LTE 13 | QPSK10M | Rear Face + Bottom Side  | 23230 | w               | 0        | w/      | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.01             | 0.086                  | 0.09                 |
|          | LTE 13 | QPSK10M | Rear Face + Bottom Side  | 23230 | w               | 0        | w/      | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0                | 0.066                  | 0.07                 |
|          | LTE 13 | QPSK10M | Rear Face + Top Side     | 23230 | w               | 0        | w/      | 2       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.09             | 0.089                  | 0.09                 |

## Note:

- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
- According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

# FCC SAR Test Report

A D T

| Plot No. | Band   | Mode    | Test Position            | Ch.   | Power Reduction | Gap (cm) | Holster | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|--------------------------|-------|-----------------|----------|---------|---------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 14 | QPSK10M | Front Face               | 23330 | w/o             | 1        | w/o     | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.06             | 0.497                  | 0.53                 |
|          | LTE 14 | QPSK10M | Front Face               | 23330 | w/o             | 1        | w/o     | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.03            | 0.383                  | 0.42                 |
| 15       | LTE 14 | QPSK10M | Rear Face                | 23330 | w/o             | 1        | w/o     | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.01            | 0.574                  | 0.62                 |
|          | LTE 14 | QPSK10M | Rear Face                | 23330 | w/o             | 1        | w/o     | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | 0.01             | 0.439                  | 0.48                 |
|          | LTE 14 | QPSK10M | Rear Face                | 23330 | w/o             | 1        | w/o     | 2       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.03            | 0.467                  | 0.50                 |
|          | LTE 14 | QPSK10M | Front Face + Top Side    | 23330 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.03            | 0.347                  | 0.37                 |
|          | LTE 14 | QPSK10M | Front Face + Top Side    | 23330 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | 0                | 0.273                  | 0.30                 |
|          | LTE 14 | QPSK10M | Front Face + Bottom Side | 23330 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0                | 0.252                  | 0.27                 |
|          | LTE 14 | QPSK10M | Front Face + Bottom Side | 23330 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.01            | 0.201                  | 0.22                 |
|          | LTE 14 | QPSK10M | Rear Face + Top Side     | 23330 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.05            | 0.348                  | 0.37                 |
|          | LTE 14 | QPSK10M | Rear Face + Top Side     | 23330 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.03            | 0.275                  | 0.30                 |
|          | LTE 14 | QPSK10M | Rear Face + Bottom Side  | 23330 | w/o             | 0        | w/      | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.02             | 0.298                  | 0.32                 |
|          | LTE 14 | QPSK10M | Rear Face + Bottom Side  | 23330 | w/o             | 0        | w/      | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | 0.02             | 0.234                  | 0.26                 |
|          | LTE 14 | QPSK10M | Rear Face + Top Side     | 23330 | w/o             | 0        | w/      | 2       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.03            | 0.313                  | 0.34                 |

## Note:

1. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
2. According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
3. According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
4. According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
5. According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

# FCC SAR Test Report

A D T

| Plot No. | Band      | Test Position            | Ch. | Gap (cm) | Holster | Battery | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-----------|--------------------------|-----|----------|---------|---------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 16       | 802.11b   | Front Face               | 11  | 1        | w/o     | 1       | 16.5                     | 16.15                          | 1.08           | 0.04             | 0.079                  | 0.09                 |
|          | 802.11b   | Rear Face                | 11  | 1        | w/o     | 1       | 16.5                     | 16.15                          | 1.08           | 0.13             | 0.061                  | 0.07                 |
|          | 802.11b   | Front Face               | 11  | 1        | w/o     | 2       | 16.5                     | 16.15                          | 1.08           | -0.05            | 0.056                  | 0.06                 |
|          | 802.11b   | Front Face + Top Side    | 11  | 0        | w/      | 1       | 16.5                     | 16.15                          | 1.08           | -0.11            | 0.029                  | 0.03                 |
|          | 802.11b   | Front Face + Bottom Side | 11  | 0        | w/      | 1       | 16.5                     | 16.15                          | 1.08           | 0.04             | 0.033                  | 0.04                 |
|          | 802.11b   | Rear Face + Top Side     | 11  | 0        | w/      | 1       | 16.5                     | 16.15                          | 1.08           | 0.01             | 0.034                  | 0.04                 |
|          | 802.11b   | Rear Face + Bottom Side  | 11  | 0        | w/      | 1       | 16.5                     | 16.15                          | 1.08           | 0.08             | 0.039                  | 0.04                 |
|          | 802.11b   | Rear Face + Bottom Side  | 11  | 0        | w/      | 2       | 16.5                     | 16.15                          | 1.08           | 0.03             | 0.012                  | 0.01                 |
|          | 802.11a   | Front Face               | 40  | 1        | w/o     | 1       | 15.5                     | 15.50                          | 1.00           | 0.12             | 0.071                  | 0.07                 |
| 17       | 802.11a   | Rear Face                | 40  | 1        | w/o     | 1       | 15.5                     | 15.50                          | 1.00           | 0.05             | 0.162                  | 0.16                 |
|          | 802.11a   | Rear Face                | 40  | 1        | w/o     | 2       | 15.5                     | 15.50                          | 1.00           | 0.09             | 0.108                  | 0.11                 |
|          | 802.11a   | Front Face + Top Side    | 40  | 0        | w/      | 1       | 15.5                     | 15.50                          | 1.00           | 0.02             | 0.018                  | 0.02                 |
|          | 802.11a   | Front Face + Bottom Side | 40  | 0        | w/      | 1       | 15.5                     | 15.50                          | 1.00           | 0.01             | 0.027                  | 0.03                 |
|          | 802.11a   | Rear Face + Top Side     | 40  | 0        | w/      | 1       | 15.5                     | 15.50                          | 1.00           | -0.06            | 0.047                  | 0.05                 |
|          | 802.11a   | Rear Face + Bottom Side  | 40  | 0        | w/      | 1       | 15.5                     | 15.50                          | 1.00           | 0.04             | 0.093                  | 0.09                 |
|          | 802.11a   | Rear Face + Bottom Side  | 40  | 0        | w/      | 2       | 15.5                     | 15.50                          | 1.00           | 0.07             | 0.053                  | 0.05                 |
|          | 802.11a   | Front Face               | 56  | 1        | w/o     | 1       | 15.5                     | 15.05                          | 1.11           | 0.01             | 0.07                   | 0.08                 |
| 18       | 802.11a   | Rear Face                | 56  | 1        | w/o     | 1       | 15.5                     | 15.05                          | 1.11           | 0.01             | 0.157                  | 0.17                 |
|          | 802.11a   | Rear Face                | 56  | 1        | w/o     | 2       | 15.5                     | 15.05                          | 1.11           | -0.01            | 0.098                  | 0.11                 |
|          | 802.11a   | Front Face + Top Side    | 56  | 0        | w/      | 1       | 15.5                     | 15.05                          | 1.11           | 0.02             | 0.027                  | 0.03                 |
|          | 802.11a   | Front Face + Bottom Side | 56  | 0        | w/      | 1       | 15.5                     | 15.05                          | 1.11           | 0                | 0.04                   | 0.04                 |
|          | 802.11a   | Rear Face + Top Side     | 56  | 0        | w/      | 1       | 15.5                     | 15.05                          | 1.11           | -0.13            | 0.086                  | 0.10                 |
|          | 802.11a   | Rear Face + Bottom Side  | 56  | 0        | w/      | 1       | 15.5                     | 15.05                          | 1.11           | -0.05            | 0.094                  | 0.10                 |
|          | 802.11a   | Rear Face + Bottom Side  | 56  | 0        | w/      | 2       | 15.5                     | 15.05                          | 1.11           | 0.07             | 0.065                  | 0.07                 |
|          | 802.11a   | Front Face               | 100 | 1        | w/o     | 1       | 15.5                     | 15.11                          | 1.09           | 0.12             | 0.104                  | 0.11                 |
| 19       | 802.11a   | Rear Face                | 100 | 1        | w/o     | 1       | 15.5                     | 15.11                          | 1.09           | 0.12             | 0.271                  | 0.30                 |
|          | 802.11a   | Rear Face                | 100 | 1        | w/o     | 2       | 15.5                     | 15.11                          | 1.09           | 0.12             | 0.120                  | 0.13                 |
|          | 802.11a   | Front Face + Top Side    | 100 | 0        | w/      | 1       | 15.5                     | 15.11                          | 1.09           | 0.12             | 0.034                  | 0.04                 |
|          | 802.11a   | Front Face + Bottom Side | 100 | 0        | w/      | 1       | 15.5                     | 15.11                          | 1.09           | 0.08             | 0.044                  | 0.05                 |
|          | 802.11a   | Rear Face + Top Side     | 100 | 0        | w/      | 1       | 15.5                     | 15.11                          | 1.09           | -0.08            | 0.125                  | 0.14                 |
|          | 802.11a   | Rear Face + Bottom Side  | 100 | 0        | w/      | 1       | 15.5                     | 15.11                          | 1.09           | -0.16            | 0.132                  | 0.14                 |
|          | 802.11a   | Rear Face + Bottom Side  | 100 | 0        | w/      | 2       | 15.5                     | 15.11                          | 1.09           | -0.08            | 0.092                  | 0.10                 |
|          | 802.11a   | Front Face               | 149 | 1        | w/o     | 1       | 14.5                     | 14.44                          | 1.01           | 0.15             | 0.105                  | 0.11                 |
| 20       | 802.11a   | Rear Face                | 149 | 1        | w/o     | 1       | 14.5                     | 14.44                          | 1.01           | 0                | 0.285                  | 0.29                 |
|          | 802.11a   | Rear Face                | 149 | 1        | w/o     | 2       | 14.5                     | 14.44                          | 1.01           | 0.16             | 0.180                  | 0.18                 |
|          | 802.11a   | Front Face + Top Side    | 149 | 0        | w/      | 1       | 14.5                     | 14.44                          | 1.01           | 0.08             | 0.068                  | 0.07                 |
|          | 802.11a   | Front Face + Bottom Side | 149 | 0        | w/      | 1       | 14.5                     | 14.44                          | 1.01           | 0.08             | 0.07                   | 0.07                 |
|          | 802.11a   | Rear Face + Top Side     | 149 | 0        | w/      | 1       | 14.5                     | 14.44                          | 1.01           | 0.06             | 0.113                  | 0.11                 |
|          | 802.11a   | Rear Face + Bottom Side  | 149 | 0        | w/      | 1       | 14.5                     | 14.44                          | 1.01           | -0.04            | 0.126                  | 0.13                 |
|          | 802.11a   | Rear Face + Bottom Side  | 149 | 0        | w/      | 2       | 14.5                     | 14.44                          | 1.01           | 0.14             | 0.078                  | 0.08                 |
|          | Bluetooth | Front Face               | 0   | 1        | w/o     | 1       | 11.0                     | 10.60                          | 1.10           | -0.03            | 0.035                  | 0.04                 |
|          | Bluetooth | Rear Face                | 0   | 1        | w/o     | 1       | 11.0                     | 10.60                          | 1.10           | 0.01             | 0.027                  | 0.03                 |
| 21       | Bluetooth | Front Face               | 0   | 1        | w/o     | 2       | 11.0                     | 10.60                          | 1.10           | -0.03            | 0.036                  | 0.04                 |
|          | Bluetooth | Front Face + Top Side    | 0   | 0        | w/      | 1       | 11.0                     | 10.60                          | 1.10           | 0.05             | 0.014                  | 0.02                 |
|          | Bluetooth | Front Face + Bottom Side | 0   | 0        | w/      | 1       | 11.0                     | 10.60                          | 1.10           | -0.05            | 0.012                  | 0.01                 |
|          | Bluetooth | Rear Face + Top Side     | 0   | 0        | w/      | 1       | 11.0                     | 10.60                          | 1.10           | 0.01             | 0.016                  | 0.02                 |
|          | Bluetooth | Rear Face + Bottom Side  | 0   | 0        | w/      | 1       | 11.0                     | 10.60                          | 1.10           | 0.09             | 0.014                  | 0.02                 |
|          | Bluetooth | Rear Face + Top Side     | 0   | 0        | w/      | 2       | 11.0                     | 10.60                          | 1.10           | -0.13            | 0.012                  | 0.01                 |

## Note:

- According to KDB 248227, when the extrapolated maximum peak SAR for the maximum output power channel is  $\leq 1.6$  W/kg and the 1g averaged SAR is  $\leq 0.8$  W/kg, WLAN SAR testing for other channels is not required.
- SAR testing for 802.11g/n is not required when its maximum power is less than 1/4 dB higher than 802.11b.
- SAR testing for 802.11n is not required when its maximum power is less than 1/4 dB higher than 802.11a.

## 4.7.3 SAR Results for Hotspot (Separation Distance is 1.0 cm Gap)

| Plot No. | Band     | Mode       | Test Position | Ch.  | Battery | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|------------|---------------|------|---------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
| 11       | CDMA BC0 | RTAP 153.6 | Front Face    | 384  | 1       | 25.5                     | 24.44                          | 1.28           | -0.02            | 0.564                  | 0.72                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face     | 384  | 1       | 25.5                     | 24.44                          | 1.28           | 0.02             | 0.793                  | 1.01                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face     | 1013 | 1       | 25.5                     | 24.31                          | 1.32           | 0.03             | 0.753                  | 0.99                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face     | 777  | 1       | 25.5                     | 24.41                          | 1.29           | 0.02             | 0.706                  | 0.91                 |
|          | CDMA BC0 | RTAP 153.6 | Right Side    | 384  | 1       | 25.5                     | 24.44                          | 1.28           | -0.05            | 0.465                  | 0.59                 |
|          | CDMA BC0 | RTAP 153.6 | Bottom Side   | 384  | 1       | 25.5                     | 24.44                          | 1.28           | -0.07            | 0.175                  | 0.22                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face     | 384  | 2       | 25.5                     | 24.44                          | 1.28           | 0.01             | 0.645                  | 0.82                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face     | 1013 | 2       | 25.5                     | 24.31                          | 1.32           | 0.02             | 0.593                  | 0.78                 |
|          | CDMA BC0 | RTAP 153.6 | Rear Face     | 777  | 2       | 25.5                     | 24.41                          | 1.29           | 0.01             | 0.552                  | 0.71                 |
| 12       | CDMA BC1 | RTAP 153.6 | Front Face    | 25   | 1       | 25.0                     | 24.57                          | 1.10           | -0.15            | 0.584                  | 0.64                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face     | 25   | 1       | 25.0                     | 24.57                          | 1.10           | -0.19            | 0.686                  | 0.76                 |
|          | CDMA BC1 | RTAP 153.6 | Right Side    | 25   | 1       | 25.0                     | 24.57                          | 1.10           | 0.12             | 0.437                  | 0.48                 |
|          | CDMA BC1 | RTAP 153.6 | Bottom Side   | 25   | 1       | 25.0                     | 24.57                          | 1.10           | -0.07            | 0.543                  | 0.60                 |
|          | CDMA BC1 | RTAP 153.6 | Rear Face     | 25   | 2       | 25.0                     | 24.57                          | 1.10           | 0.04             | 0.25                   | 0.28                 |

### Note:

- SAR is performed on the highest power channel. When the reported SAR value of highest power channel is  $\leq 0.8$  W/kg, SAR testing for optional channel is not required.

| Plot No. | Band  | Mode    | Test Position | Ch.   | Power Reduction | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducte d Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|-------|---------|---------------|-------|-----------------|---------|-----|-----------|--------------------------|---------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 4 | QPSK20M | Front Face    | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                           | 1.08           | 0.15             | 0.539                  | 0.58                 |
|          | LTE 4 | QPSK20M | Front Face    | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                           | 1.06           | -0.04            | 0.424                  | 0.45                 |
|          | LTE 4 | QPSK20M | Rear Face     | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                           | 1.08           | -0.02            | 0.449                  | 0.48                 |
|          | LTE 4 | QPSK20M | Rear Face     | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                           | 1.06           | 0.07             | 0.354                  | 0.38                 |
|          | LTE 4 | QPSK20M | Left Side     | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                           | 1.08           | -0.02            | 0.389                  | 0.42                 |
|          | LTE 4 | QPSK20M | Left Side     | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                           | 1.06           | -0.09            | 0.311                  | 0.33                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 20300 | w/o             | 1       | 1   | 0         | 24.0                     | 23.67                           | 1.08           | 0.15             | 0.247                  | 0.27                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 20300 | w/o             | 1       | 50  | 0         | 23.0                     | 22.73                           | 1.06           | 0.12             | 0.204                  | 0.22                 |
| 13       | LTE 4 | QPSK20M | Front Face    | 20300 | w/o             | 2       | 1   | 0         | 24.0                     | 23.67                           | 1.08           | 0.17             | 0.646                  | 0.70                 |
|          | LTE 4 | QPSK20M | Front Face    | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                           | 1.07           | 0.08             | 0.236                  | 0.25                 |
|          | LTE 4 | QPSK20M | Front Face    | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                           | 1.09           | 0.01             | 0.185                  | 0.20                 |
|          | LTE 4 | QPSK20M | Rear Face     | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                           | 1.07           | 0.13             | 0.19                   | 0.20                 |
|          | LTE 4 | QPSK20M | Rear Face     | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                           | 1.09           | -0.06            | 0.154                  | 0.17                 |
|          | LTE 4 | QPSK20M | Left Side     | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                           | 1.07           | 0.03             | 0.168                  | 0.18                 |
|          | LTE 4 | QPSK20M | Left Side     | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                           | 1.09           | -0.11            | 0.136                  | 0.15                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 20300 | w               | 1       | 1   | 0         | 21.0                     | 20.69                           | 1.07           | 0.04             | 0.105                  | 0.11                 |
|          | LTE 4 | QPSK20M | Bottom Side   | 20300 | w               | 1       | 50  | 0         | 20.0                     | 19.61                           | 1.09           | 0.01             | 0.087                  | 0.10                 |
|          | LTE 4 | QPSK20M | Front Face    | 20300 | w               | 2       | 1   | 0         | 21.0                     | 20.69                           | 1.07           | 0.14             | 0.285                  | 0.31                 |

### Note:

- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.

# FCC SAR Test Report

A D T

- According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
- According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

| Plot No. | Band   | Mode    | Test Position | Ch.   | Power Reduction | Battery | RB# | RB Offset | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|---------------|-------|-----------------|---------|-----|-----------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 13 | QPSK10M | Front Face    | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | 0                | 0.623                  | 0.67                 |
|          | LTE 13 | QPSK10M | Front Face    | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.02            | 0.472                  | 0.52                 |
| 14       | LTE 13 | QPSK10M | Rear Face     | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.03            | 0.649                  | 0.69                 |
|          | LTE 13 | QPSK10M | Rear Face     | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.03            | 0.488                  | 0.54                 |
|          | LTE 13 | QPSK10M | Left Side     | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.03            | 0.434                  | 0.46                 |
|          | LTE 13 | QPSK10M | Left Side     | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.01            | 0.326                  | 0.36                 |
|          | LTE 13 | QPSK10M | Bottom Side   | 23230 | w/o             | 1       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.07            | 0.364                  | 0.39                 |
|          | LTE 13 | QPSK10M | Bottom Side   | 23230 | w/o             | 1       | 25  | 0         | 23.0                     | 22.60                          | 1.10           | -0.08            | 0.273                  | 0.30                 |
|          | LTE 13 | QPSK10M | Rear Face     | 23230 | w/o             | 2       | 1   | 0         | 24.0                     | 23.71                          | 1.07           | -0.05            | 0.529                  | 0.57                 |
|          | LTE 13 | QPSK10M | Front Face    | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.02             | 0.151                  | 0.15                 |
|          | LTE 13 | QPSK10M | Front Face    | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.08             | 0.118                  | 0.12                 |
|          | LTE 13 | QPSK10M | Rear Face     | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.06             | 0.17                   | 0.17                 |
|          | LTE 13 | QPSK10M | Rear Face     | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.02             | 0.132                  | 0.14                 |
|          | LTE 13 | QPSK10M | Left Side     | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.04             | 0.111                  | 0.11                 |
|          | LTE 13 | QPSK10M | Left Side     | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | 0.06             | 0.087                  | 0.09                 |
|          | LTE 13 | QPSK10M | Bottom Side   | 23230 | w               | 1       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0                | 0.088                  | 0.09                 |
|          | LTE 13 | QPSK10M | Bottom Side   | 23230 | w               | 1       | 25  | 0         | 17.0                     | 16.81                          | 1.04           | -0.01            | 0.07                   | 0.07                 |
|          | LTE 13 | QPSK10M | Rear Face     | 23230 | w               | 2       | 1   | 0         | 18.0                     | 17.98                          | 1.00           | 0.03             | 0.139                  | 0.14                 |
|          | LTE 14 | QPSK10M | Front Face    | 23330 | w               | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.06             | 0.497                  | 0.53                 |
|          | LTE 14 | QPSK10M | Front Face    | 23330 | w               | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.03            | 0.383                  | 0.42                 |
| 15       | LTE 14 | QPSK10M | Rear Face     | 23330 | w               | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.01            | 0.574                  | 0.62                 |
|          | LTE 14 | QPSK10M | Rear Face     | 23330 | w               | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | 0.01             | 0.439                  | 0.48                 |
|          | LTE 14 | QPSK10M | Left Side     | 23330 | w               | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | 0.05             | 0.348                  | 0.37                 |
|          | LTE 14 | QPSK10M | Left Side     | 23330 | w               | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.02            | 0.27                   | 0.30                 |
|          | LTE 14 | QPSK10M | Bottom Side   | 23330 | w               | 1       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.05            | 0.304                  | 0.33                 |
|          | LTE 14 | QPSK10M | Bottom Side   | 23330 | w               | 1       | 25  | 0         | 23.0                     | 22.61                          | 1.09           | -0.11            | 0.235                  | 0.26                 |
|          | LTE 14 | QPSK10M | Rear Face     | 23330 | w               | 2       | 1   | 0         | 24.0                     | 23.69                          | 1.07           | -0.03            | 0.467                  | 0.50                 |

## Note:

- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 1RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for remaining RB offset configurations and required test channels is not required when the reported SAR of highest power 50% RB configuration is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 100% RB is not required when the maximum power of 100% RB is less than the maximum power of 1RB and 50% RB, and the highest reported SAR for 1RB and 50% RB is less than 0.8 W/kg.
- According to KDB 941225, LTE SAR testing for 16QAM is not required when the maximum power of 16QAM is less 1/2 dB higher than QPSK, and the highest reported SAR of QPSK is less than 1.45 W/kg.
- According to KDB 941225, LTE SAR testing for smaller channel bandwidth is not required when the maximum power of smaller channel bandwidth is less 1/2 dB higher than largest channel bandwidth, and the highest reported SAR of largest channel bandwidth is less than 1.45 W/kg.

# FCC SAR Test Report

A D T

| Plot No. | Band    | Test Position | Ch. | Battery | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|---------|---------------|-----|---------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | 802.11b | Front Face    | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.04             | 0.079                  | 0.09                 |
|          | 802.11b | Rear Face     | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.13             | 0.061                  | 0.07                 |
|          | 802.11b | Right Side    | 11  | 1       | 16.5                     | 16.15                          | 1.08           | 0.07             | 0.141                  | 0.15                 |
| 22       | 802.11b | Right Side    | 11  | 2       | 16.5                     | 16.15                          | 1.08           | 0.02             | 0.184                  | 0.20                 |
|          | 802.11a | Front Face    | 40  | 1       | 15.5                     | 15.50                          | 1.00           | 0.02             | 0.071                  | 0.07                 |
|          | 802.11a | Rear Face     | 40  | 1       | 15.5                     | 15.50                          | 1.00           | 0.05             | 0.162                  | 0.16                 |
| 23       | 802.11a | Right Side    | 40  | 1       | 15.5                     | 15.50                          | 1.00           | 0.07             | 0.342                  | 0.34                 |
|          | 802.11a | Right Side    | 40  | 2       | 15.5                     | 15.50                          | 1.00           | 0.05             | 0.335                  | 0.34                 |
|          | 802.11a | Front Face    | 149 | 1       | 14.5                     | 14.44                          | 1.01           | 0.15             | 0.105                  | 0.11                 |
|          | 802.11a | Rear Face     | 149 | 1       | 14.5                     | 14.44                          | 1.01           | 0                | 0.285                  | 0.29                 |
|          | 802.11a | Right Side    | 149 | 1       | 14.5                     | 14.44                          | 1.01           | 0.11             | 0.466                  | 0.47                 |
| 24       | 802.11a | Right Side    | 149 | 2       | 14.5                     | 14.44                          | 1.01           | 0.13             | 0.65                   | 0.66                 |

## Note:

1. According to KDB 248227, when the extrapolated maximum peak SAR for the maximum output power channel is  $\leq 1.6$  W/kg and the 1g averaged SAR is  $\leq 0.8$  W/kg, WLAN SAR testing for other channels is not required.
2. SAR testing for 802.11g/n is not required when its maximum power is less than 1/4 dB higher than 802.11b.
3. Only WLAN 5G band 1 and 4 (5.15~5.25 and 5.725~5.85 GHz) support wireless hotspot mode.

## FCC SAR Test Report

### 4.7.4 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Since all the measured SAR are less than 0.8 W/kg, the repeated measurement is not required.

### 4.7.5 Simultaneous Multi-band Transmission Evaluation

#### <SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of  $SAR_{1g}$  of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit ( $SAR_{1g}$  1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of  $SAR_{1g}$  is greater than the SAR limit ( $SAR_{1g}$  1.6 W/kg), SAR test exclusion is determined by the SPLSR.

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2) | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                   |
|-----|-----------------------------|-----------------------|------------------|--------------|--------------|------------------|-------------------------------------|
| 1   | CDMA BC0<br>+<br>WLAN (DTS) | Head                  | Right Cheek      | 0.73         | 0.33         | 1.06             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Tilted     | 0.41         | 0.07         | 0.48             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Cheek       | 0.56         | 0.49         | 1.05             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Tilted      | 0.38         | 0.11         | 0.49             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Body-Worn             | Front Face       | 0.72         | 0.09         | 0.81             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.01         | 0.07         | 1.08             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Hotspot               | Front Face       | 0.72         | 0.09         | 0.81             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.01         | 0.07         | 1.08             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.59         | 0.20         | 0.79             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.22         | 0.00         | 0.22             | $\Sigma$ SAR < 1.6,<br>Not required |
| 2   | CDMA BC0<br>+<br>WLAN (NII) | Head                  | Right Cheek      | 0.73         | 0.26         | 0.99             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Tilted     | 0.41         | 0.08         | 0.49             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Cheek       | 0.56         | 0.59         | 1.15             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Tilted      | 0.38         | 0.08         | 0.46             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Body-Worn             | Front Face       | 0.72         | 0.11         | 0.83             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.01         | 0.30         | 1.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Hotspot               | Front Face       | 0.72         | 0.11         | 0.83             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.01         | 0.29         | 1.30             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.59         | 0.66         | 1.25             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.22         | 0.00         | 0.22             | $\Sigma$ SAR < 1.6,<br>Not required |
| 3   | CDMA BC0<br>+<br>BT (DSS)   | Body-Worn             | Front Face       | 0.72         | 0.04         | 0.76             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 1.01         | 0.03         | 1.04             | $\Sigma$ SAR < 1.6,<br>Not required |



# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2) | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                   |
|-----|-----------------------------|-----------------------|------------------|--------------|--------------|------------------|-------------------------------------|
| 4   | CDMA BC1<br>+<br>WLAN (DTS) | Head                  | Right Cheek      | 0.60         | 0.33         | 0.93             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Tilted     | 0.22         | 0.07         | 0.29             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Cheek       | 0.12         | 0.49         | 0.61             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Tilted      | 0.22         | 0.11         | 0.33             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Body-Worn             | Front Face       | 0.64         | 0.09         | 0.73             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.76         | 0.07         | 0.83             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Hotspot               | Front Face       | 0.64         | 0.09         | 0.73             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.76         | 0.07         | 0.83             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.48         | 0.20         | 0.68             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.60         | 0.00         | 0.60             | $\Sigma$ SAR < 1.6,<br>Not required |
| 5   | CDMA BC1<br>+<br>WLAN (NII) | Head                  | Right Cheek      | 0.60         | 0.26         | 0.86             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Tilted     | 0.22         | 0.08         | 0.30             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Cheek       | 0.12         | 0.59         | 0.71             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Tilted      | 0.22         | 0.08         | 0.30             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Body-Worn             | Front Face       | 0.64         | 0.11         | 0.75             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.76         | 0.30         | 1.06             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Hotspot               | Front Face       | 0.64         | 0.11         | 0.75             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.76         | 0.29         | 1.05             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.48         | 0.66         | 1.14             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.60         | 0.00         | 0.60             | $\Sigma$ SAR < 1.6,<br>Not required |
| 6   | CDMA BC1<br>+<br>BT (DSS)   | Body-Worn             | Front Face       | 0.64         | 0.04         | 0.68             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.76         | 0.03         | 0.79             | $\Sigma$ SAR < 1.6,<br>Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2)                              | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                   |
|-----|----------------------------------------------------------|-----------------------|------------------|--------------|--------------|------------------|-------------------------------------|
| 7   | LTE 4<br>(without Power<br>Reduction)<br>+<br>WLAN (DTS) | Head                  | Right Cheek      | 0.30         | 0.33         | 0.63             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Right Tilted     | 0.23         | 0.07         | 0.30             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Left Cheek       | 0.51         | 0.49         | 1.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Left Tilted      | 0.20         | 0.11         | 0.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          | Body-Worn             | Front Face       | 0.70         | 0.09         | 0.79             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Rear Face        | 0.48         | 0.07         | 0.55             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          | Hotspot               | Front Face       | 0.70         | 0.09         | 0.79             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Rear Face        | 0.48         | 0.07         | 0.55             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Left Side        | 0.42         | 0.00         | 0.42             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Right Side       | 0.00         | 0.20         | 0.20             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Bottom Side      | 0.27         | 0.00         | 0.27             | $\Sigma$ SAR < 1.6,<br>Not required |
| 8   | LTE 4<br>(without Power<br>Reduction)<br>+<br>WLAN (NII) | Head                  | Right Cheek      | 0.30         | 0.26         | 0.56             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Right Tilted     | 0.23         | 0.08         | 0.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Left Cheek       | 0.51         | 0.59         | 1.10             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Left Tilted      | 0.20         | 0.08         | 0.28             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          | Body-Worn             | Front Face       | 0.70         | 0.11         | 0.81             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Rear Face        | 0.48         | 0.30         | 0.78             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          | Hotspot               | Front Face       | 0.70         | 0.11         | 0.81             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Rear Face        | 0.48         | 0.29         | 0.77             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Left Side        | 0.42         | 0.00         | 0.42             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Right Side       | 0.00         | 0.66         | 0.66             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Bottom Side      | 0.27         | 0.00         | 0.27             | $\Sigma$ SAR < 1.6,<br>Not required |
| 9   | LTE 4<br>(without Power<br>Reduction)<br>+<br>BT (DSS)   | Body-Worn             | Front Face       | 0.70         | 0.04         | 0.74             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                          |                       | Rear Face        | 0.48         | 0.03         | 0.51             | $\Sigma$ SAR < 1.6,<br>Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2)                               | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                            |
|-----|-----------------------------------------------------------|-----------------------|------------------|--------------|--------------|------------------|----------------------------------------------|
| 10  | LTE 13<br>(without Power<br>Reduction)<br>+<br>WLAN (DTS) | Head                  | Right Cheek      | 0.43         | 0.33         | 0.76             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Right Tilted     | 0.24         | 0.07         | 0.31             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Left Cheek       | 0.49         | 0.49         | 0.98             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Left Tilted      | 0.28         | 0.11         | 0.39             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           | Body-Worn             | Front Face       | 0.67         | 0.09         | 0.76             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Rear Face        | 0.69         | 0.07         | 0.76             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           | Hotspot               | Front Face       | 0.67         | 0.09         | 0.76             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Rear Face        | 0.69         | 0.07         | 0.76             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Left Side        | 0.46         | 0.00         | 0.46             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Right Side       | 0.00         | 0.20         | 0.20             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Bottom Side      | 0.39         | 0.00         | 0.39             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
| 11  | LTE 13<br>(without Power<br>Reduction)<br>+<br>WLAN (NII) | Head                  | Right Cheek      | 0.43         | 0.26         | 0.69             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Right Tilted     | 0.24         | 0.08         | 0.32             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Left Cheek       | 0.49         | 0.59         | 1.08             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Left Tilted      | 0.28         | 0.08         | 0.36             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           | Body-Worn             | Front Face       | 0.67         | 0.11         | 0.78             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Rear Face        | 0.69         | 0.30         | 0.99             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           | Hotspot               | Front Face       | 0.67         | 0.11         | 0.78             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Rear Face        | 0.69         | 0.29         | 0.98             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Left Side        | 0.46         | 0.00         | 0.46             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Right Side       | 0.00         | 0.66         | 0.66             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Bottom Side      | 0.39         | 0.00         | 0.39             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
| 12  | LTE 13<br>(without Power<br>Reduction)<br>+<br>BT (DSS)   | Body-Worn             | Front Face       | 0.67         | 0.04         | 0.71             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |
|     |                                                           |                       | Rear Face        | 0.69         | 0.03         | 0.72             | $\Sigma \text{ SAR} < 1.6$ ,<br>Not required |



# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2) | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                   |
|-----|-----------------------------|-----------------------|------------------|--------------|--------------|------------------|-------------------------------------|
| 13  | LTE 14<br>+<br>WLAN (DTS)   | Head                  | Right Cheek      | 0.35         | 0.33         | 0.68             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Tilted     | 0.18         | 0.07         | 0.25             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Cheek       | 0.39         | 0.49         | 0.88             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Tilted      | 0.23         | 0.11         | 0.34             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Body-Worn             | Front Face       | 0.53         | 0.09         | 0.62             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.62         | 0.07         | 0.69             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Hotspot               | Front Face       | 0.53         | 0.09         | 0.62             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.62         | 0.07         | 0.69             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.37         | 0.00         | 0.37             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.00         | 0.20         | 0.20             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.33         | 0.00         | 0.33             | $\Sigma$ SAR < 1.6,<br>Not required |
| 14  | LTE 14<br>+<br>WLAN (NII)   | Head                  | Right Cheek      | 0.35         | 0.26         | 0.61             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Tilted     | 0.18         | 0.08         | 0.26             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Cheek       | 0.39         | 0.59         | 0.98             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Tilted      | 0.23         | 0.08         | 0.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Body-Worn             | Front Face       | 0.53         | 0.11         | 0.64             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.62         | 0.30         | 0.92             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             | Hotspot               | Front Face       | 0.53         | 0.11         | 0.64             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.62         | 0.29         | 0.91             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Left Side        | 0.37         | 0.00         | 0.37             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Right Side       | 0.00         | 0.66         | 0.66             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Bottom Side      | 0.33         | 0.00         | 0.33             | $\Sigma$ SAR < 1.6,<br>Not required |
| 15  | LTE 14<br>+<br>BT (DSS)     | Body-Worn             | Front Face       | 0.53         | 0.04         | 0.57             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                             |                       | Rear Face        | 0.62         | 0.03         | 0.65             | $\Sigma$ SAR < 1.6,<br>Not required |



# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2)                            | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                   |
|-----|--------------------------------------------------------|-----------------------|------------------|--------------|--------------|------------------|-------------------------------------|
| 16  | CDMA BC0<br>+<br>LTE 4<br>(without Power<br>Reduction) | Head                  | Right Cheek      | 0.73         | 0.30         | 1.03             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Right Tilted     | 0.41         | 0.23         | 0.64             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Left Cheek       | 0.56         | 0.51         | 1.07             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Left Tilted      | 0.38         | 0.20         | 0.58             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        | Body-Worn             | Front Face       | 0.72         | 0.70         | 1.42             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Rear Face        | 1.01         | 0.48         | 1.49             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        | Hotspot               | Front Face       | 0.72         | 0.70         | 1.42             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Rear Face        | 1.01         | 0.48         | 1.49             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Left Side        | 0.00         | 0.42         | 0.42             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Right Side       | 0.59         | 0.00         | 0.59             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Bottom Side      | 0.22         | 0.27         | 0.49             | $\Sigma$ SAR < 1.6,<br>Not required |
| 17  | CDMA BC1<br>+<br>LTE 4<br>(with Power<br>Reduction)    | Head                  | Right Cheek      | 0.60         | 0.13         | 0.73             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Right Tilted     | 0.22         | 0.10         | 0.32             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Left Cheek       | 0.12         | 0.21         | 0.33             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Left Tilted      | 0.22         | 0.09         | 0.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        | Body-Worn             | Front Face       | 0.64         | 0.31         | 0.95             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Rear Face        | 0.76         | 0.20         | 0.96             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        | Hotspot               | Front Face       | 0.64         | 0.31         | 0.95             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Rear Face        | 0.76         | 0.20         | 0.96             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Left Side        | 0.00         | 0.18         | 0.18             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Right Side       | 0.48         | 0.00         | 0.48             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                        |                       | Bottom Side      | 0.60         | 0.11         | 0.71             | $\Sigma$ SAR < 1.6,<br>Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2)                             | Exposure<br>Condition | Test<br>Position | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | SPLSR<br>Analysis                   |
|-----|---------------------------------------------------------|-----------------------|------------------|--------------|--------------|------------------|-------------------------------------|
| 18  | CDMA BC0<br>+<br>LTE 13<br>(with Power<br>Reduction)    | Head                  | Right Cheek      | 0.73         | 0.09         | 0.82             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Right Tilted     | 0.41         | 0.04         | 0.45             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Left Cheek       | 0.56         | 0.10         | 0.66             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Left Tilted      | 0.38         | 0.05         | 0.43             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         | Body-Worn             | Front Face       | 0.72         | 0.15         | 0.87             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Rear Face        | 1.01         | 0.17         | 1.18             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         | Hotspot               | Front Face       | 0.72         | 0.15         | 0.87             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Rear Face        | 1.01         | 0.17         | 1.18             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Left Side        | 0.00         | 0.11         | 0.11             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Right Side       | 0.59         | 0.00         | 0.59             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Bottom Side      | 0.22         | 0.09         | 0.31             | $\Sigma$ SAR < 1.6,<br>Not required |
| 19  | CDMA BC1<br>+<br>LTE 13<br>(without Power<br>Reduction) | Head                  | Right Cheek      | 0.60         | 0.43         | 1.03             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Right Tilted     | 0.22         | 0.24         | 0.46             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Left Cheek       | 0.12         | 0.49         | 0.61             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Left Tilted      | 0.22         | 0.28         | 0.50             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         | Body-Worn             | Front Face       | 0.64         | 0.67         | 1.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Rear Face        | 0.76         | 0.69         | 1.45             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         | Hotspot               | Front Face       | 0.64         | 0.67         | 1.31             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Rear Face        | 0.76         | 0.69         | 1.45             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Left Side        | 0.00         | 0.46         | 0.46             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Right Side       | 0.48         | 0.00         | 0.48             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Top Side         | 0.00         | 0.00         | 0.00             | $\Sigma$ SAR < 1.6,<br>Not required |
|     |                                                         |                       | Bottom Side      | 0.60         | 0.39         | 0.99             | $\Sigma$ SAR < 1.6,<br>Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2 + SAR3)                                  | Exposure Condition | Test Position | Max. SAR1 | Max. SAR2 | Max. SAR3 | SAR Summation | SPLSR Analysis                   |
|-----|---------------------------------------------------------------------|--------------------|---------------|-----------|-----------|-----------|---------------|----------------------------------|
| 20  | CDMA BC0<br>+<br>LTE 4<br>(with Power Reduction)<br>+<br>WLAN (DTS) | Head               | Right Cheek   | 0.73      | 0.13      | 0.33      | 1.19          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Tilted  | 0.41      | 0.10      | 0.07      | 0.58          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Cheek    | 0.56      | 0.21      | 0.49      | 1.26          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Tilted   | 0.38      | 0.09      | 0.11      | 0.58          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Body-Worn          | Front Face    | 0.72      | 0.31      | 0.09      | 1.12          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 1.01      | 0.20      | 0.07      | 1.28          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Hotspot            | Front Face    | 0.72      | 0.31      | 0.09      | 1.12          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 1.01      | 0.20      | 0.07      | 1.28          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Side     | 0.00      | 0.18      | 0.00      | 0.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Side    | 0.59      | 0.00      | 0.20      | 0.79          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Bottom Side   | 0.22      | 0.11      | 0.00      | 0.33          | $\Sigma$ SAR < 1.6, Not required |
| 21  | CDMA BC0<br>+<br>LTE 4<br>(with Power Reduction)<br>+<br>WLAN (NII) | Head               | Right Cheek   | 0.73      | 0.13      | 0.26      | 1.12          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Tilted  | 0.41      | 0.10      | 0.08      | 0.59          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Cheek    | 0.56      | 0.21      | 0.59      | 1.36          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Tilted   | 0.38      | 0.09      | 0.08      | 0.55          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Body-Worn          | Front Face    | 0.72      | 0.31      | 0.11      | 1.14          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 1.01      | 0.20      | 0.30      | 1.51          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Hotspot            | Front Face    | 0.72      | 0.31      | 0.11      | 1.14          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 1.01      | 0.20      | 0.29      | 1.50          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Side     | 0.00      | 0.18      | 0.00      | 0.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Side    | 0.59      | 0.00      | 0.66      | 1.25          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Bottom Side   | 0.22      | 0.11      | 0.00      | 0.33          | $\Sigma$ SAR < 1.6, Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2 + SAR3)                                  | Exposure Condition | Test Position | Max. SAR1 | Max. SAR2 | Max. SAR3 | SAR Summation | SPLSR Analysis                   |
|-----|---------------------------------------------------------------------|--------------------|---------------|-----------|-----------|-----------|---------------|----------------------------------|
| 22  | CDMA BC1<br>+<br>LTE 4<br>(with Power Reduction)<br>+<br>WLAN (DTS) | Head               | Right Cheek   | 0.60      | 0.13      | 0.33      | 1.06          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Tilted  | 0.22      | 0.10      | 0.07      | 0.39          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Cheek    | 0.12      | 0.21      | 0.49      | 0.82          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Tilted   | 0.22      | 0.09      | 0.11      | 0.42          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Body-Worn          | Front Face    | 0.64      | 0.31      | 0.09      | 1.04          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 0.76      | 0.20      | 0.07      | 1.03          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Hotspot            | Front Face    | 0.64      | 0.31      | 0.09      | 1.04          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 0.76      | 0.20      | 0.07      | 1.03          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Side     | 0.00      | 0.18      | 0.00      | 0.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Side    | 0.48      | 0.00      | 0.20      | 0.68          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Bottom Side   | 0.60      | 0.11      | 0.00      | 0.71          | $\Sigma$ SAR < 1.6, Not required |
| 23  | CDMA BC1<br>+<br>LTE 4<br>(with Power Reduction)<br>+<br>WLAN (NII) | Head               | Right Cheek   | 0.60      | 0.13      | 0.26      | 0.99          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Tilted  | 0.22      | 0.10      | 0.08      | 0.40          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Cheek    | 0.12      | 0.21      | 0.59      | 0.92          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Tilted   | 0.22      | 0.09      | 0.08      | 0.39          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Body-Worn          | Front Face    | 0.64      | 0.31      | 0.11      | 1.06          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 0.76      | 0.20      | 0.30      | 1.26          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     | Hotspot            | Front Face    | 0.64      | 0.31      | 0.11      | 1.06          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Rear Face     | 0.76      | 0.20      | 0.29      | 1.25          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Left Side     | 0.00      | 0.18      | 0.00      | 0.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Right Side    | 0.48      | 0.00      | 0.66      | 1.14          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                     |                    | Bottom Side   | 0.60      | 0.11      | 0.00      | 0.71          | $\Sigma$ SAR < 1.6, Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2 + SAR3)                                   | Exposure Condition | Test Position | Max. SAR1 | Max. SAR2 | Max. SAR3 | SAR Summation | SPLSR Analysis                   |
|-----|----------------------------------------------------------------------|--------------------|---------------|-----------|-----------|-----------|---------------|----------------------------------|
| 24  | CDMA BC0<br>+<br>LTE 13<br>(with Power Reduction)<br>+<br>WLAN (DTS) | Head               | Right Cheek   | 0.73      | 0.09      | 0.33      | 1.15          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Tilted  | 0.41      | 0.04      | 0.07      | 0.52          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Cheek    | 0.56      | 0.10      | 0.49      | 1.15          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Tilted   | 0.38      | 0.05      | 0.11      | 0.54          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Body-Worn          | Front Face    | 0.72      | 0.15      | 0.09      | 0.96          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 1.01      | 0.17      | 0.07      | 1.25          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Hotspot            | Front Face    | 0.72      | 0.15      | 0.09      | 0.96          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 1.01      | 0.17      | 0.07      | 1.25          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Side     | 0.00      | 0.11      | 0.00      | 0.11          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Side    | 0.59      | 0.00      | 0.20      | 0.79          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Bottom Side   | 0.22      | 0.09      | 0.00      | 0.31          | $\Sigma$ SAR < 1.6, Not required |
| 25  | CDMA BC0<br>+<br>LTE 13<br>(with Power Reduction)<br>+<br>WLAN (NII) | Head               | Right Cheek   | 0.73      | 0.09      | 0.26      | 1.08          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Tilted  | 0.41      | 0.04      | 0.08      | 0.53          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Cheek    | 0.56      | 0.10      | 0.59      | 1.25          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Tilted   | 0.38      | 0.05      | 0.08      | 0.51          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Body-Worn          | Front Face    | 0.72      | 0.15      | 0.11      | 0.98          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 1.01      | 0.17      | 0.30      | 1.48          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Hotspot            | Front Face    | 0.72      | 0.15      | 0.11      | 0.98          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 1.01      | 0.17      | 0.29      | 1.47          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Side     | 0.00      | 0.11      | 0.00      | 0.11          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Side    | 0.59      | 0.00      | 0.66      | 1.25          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Bottom Side   | 0.22      | 0.09      | 0.00      | 0.31          | $\Sigma$ SAR < 1.6, Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2 + SAR3)                                   | Exposure Condition | Test Position | Max. SAR1 | Max. SAR2 | Max. SAR3 | SAR Summation | SPLSR Analysis                   |
|-----|----------------------------------------------------------------------|--------------------|---------------|-----------|-----------|-----------|---------------|----------------------------------|
| 26  | CDMA BC1<br>+<br>LTE 13<br>(with Power Reduction)<br>+<br>WLAN (DTS) | Head               | Right Cheek   | 0.60      | 0.09      | 0.33      | 1.02          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Tilted  | 0.22      | 0.04      | 0.07      | 0.33          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Cheek    | 0.12      | 0.10      | 0.49      | 0.71          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Tilted   | 0.22      | 0.05      | 0.11      | 0.38          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Body-Worn          | Front Face    | 0.64      | 0.15      | 0.09      | 0.88          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 0.76      | 0.17      | 0.07      | 1.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Hotspot            | Front Face    | 0.64      | 0.15      | 0.09      | 0.88          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 0.76      | 0.17      | 0.07      | 1.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Side     | 0.00      | 0.11      | 0.00      | 0.11          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Side    | 0.48      | 0.00      | 0.20      | 0.68          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Bottom Side   | 0.60      | 0.09      | 0.00      | 0.69          | $\Sigma$ SAR < 1.6, Not required |
| 27  | CDMA BC1<br>+<br>LTE 13<br>(with Power Reduction)<br>+<br>WLAN (NII) | Head               | Right Cheek   | 0.60      | 0.09      | 0.26      | 0.95          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Tilted  | 0.22      | 0.04      | 0.08      | 0.34          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Cheek    | 0.12      | 0.10      | 0.59      | 0.81          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Tilted   | 0.22      | 0.05      | 0.08      | 0.35          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Body-Worn          | Front Face    | 0.64      | 0.15      | 0.11      | 0.90          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 0.76      | 0.17      | 0.30      | 1.23          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      | Hotspot            | Front Face    | 0.64      | 0.15      | 0.11      | 0.90          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Rear Face     | 0.76      | 0.17      | 0.29      | 1.22          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Left Side     | 0.00      | 0.11      | 0.00      | 0.11          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Right Side    | 0.48      | 0.00      | 0.66      | 1.14          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                      |                    | Bottom Side   | 0.60      | 0.09      | 0.00      | 0.69          | $\Sigma$ SAR < 1.6, Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2 + SAR3)                                | Exposure Condition | Test Position | Max. SAR1 | Max. SAR2 | Max. SAR3 | SAR Summation | SPLSR Analysis                   |
|-----|-------------------------------------------------------------------|--------------------|---------------|-----------|-----------|-----------|---------------|----------------------------------|
| 28  | CDMA BC0<br>+<br>LTE 4<br>(with Power Reduction)<br>+<br>BT (DSS) | Head               | Right Cheek   | 0.73      | 0.13      | 0.00      | 0.86          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Right Tilted  | 0.41      | 0.10      | 0.00      | 0.51          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Left Cheek    | 0.56      | 0.21      | 0.00      | 0.77          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Left Tilted   | 0.38      | 0.09      | 0.00      | 0.47          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   | Body-Worn          | Front Face    | 0.72      | 0.31      | 0.04      | 1.07          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Rear Face     | 1.01      | 0.20      | 0.03      | 1.24          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   | Hotspot            | Front Face    | 0.72      | 0.31      | 0.00      | 1.03          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Rear Face     | 1.01      | 0.20      | 0.00      | 1.21          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Left Side     | 0.00      | 0.18      | 0.00      | 0.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Right Side    | 0.59      | 0.00      | 0.00      | 0.59          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Bottom Side   | 0.22      | 0.11      | 0.00      | 0.33          | $\Sigma$ SAR < 1.6, Not required |
| 29  | CDMA BC1<br>+<br>LTE 4<br>(with Power Reduction)<br>+<br>BT (DSS) | Head               | Right Cheek   | 0.60      | 0.13      | 0.00      | 0.73          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Right Tilted  | 0.22      | 0.10      | 0.00      | 0.32          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Left Cheek    | 0.12      | 0.21      | 0.00      | 0.33          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Left Tilted   | 0.22      | 0.09      | 0.00      | 0.31          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   | Body-Worn          | Front Face    | 0.64      | 0.31      | 0.04      | 0.99          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Rear Face     | 0.76      | 0.20      | 0.03      | 0.99          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   | Hotspot            | Front Face    | 0.64      | 0.31      | 0.00      | 0.95          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Rear Face     | 0.76      | 0.20      | 0.00      | 0.96          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Left Side     | 0.00      | 0.18      | 0.00      | 0.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Right Side    | 0.48      | 0.00      | 0.00      | 0.48          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                   |                    | Bottom Side   | 0.60      | 0.11      | 0.00      | 0.71          | $\Sigma$ SAR < 1.6, Not required |

# FCC SAR Test Report

A D T

| No. | Conditions<br>(SAR1 + SAR2 + SAR3)                                 | Exposure Condition | Test Position | Max. SAR1 | Max. SAR2 | Max. SAR3 | SAR Summation | SPLSR Analysis                   |
|-----|--------------------------------------------------------------------|--------------------|---------------|-----------|-----------|-----------|---------------|----------------------------------|
| 30  | CDMA BC0<br>+<br>LTE 13<br>(with Power Reduction)<br>+<br>BT (DSS) | Head               | Right Cheek   | 0.73      | 0.09      | 0.00      | 0.82          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Right Tilted  | 0.41      | 0.04      | 0.00      | 0.45          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Left Cheek    | 0.56      | 0.10      | 0.00      | 0.66          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Left Tilted   | 0.38      | 0.05      | 0.00      | 0.43          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    | Body-Worn          | Front Face    | 0.72      | 0.15      | 0.04      | 0.91          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Rear Face     | 1.01      | 0.17      | 0.03      | 1.21          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    | Hotspot            | Front Face    | 0.72      | 0.15      | 0.00      | 0.87          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Rear Face     | 1.01      | 0.17      | 0.00      | 1.18          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Left Side     | 0.00      | 0.11      | 0.00      | 0.11          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Right Side    | 0.59      | 0.00      | 0.00      | 0.59          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Bottom Side   | 0.22      | 0.09      | 0.00      | 0.31          | $\Sigma$ SAR < 1.6, Not required |
| 31  | CDMA BC1<br>+<br>LTE 13<br>(with Power Reduction)<br>+<br>BT (DSS) | Head               | Right Cheek   | 0.60      | 0.09      | 0.00      | 0.69          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Right Tilted  | 0.22      | 0.04      | 0.00      | 0.26          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Left Cheek    | 0.12      | 0.10      | 0.00      | 0.22          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Left Tilted   | 0.22      | 0.05      | 0.00      | 0.27          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    | Body-Worn          | Front Face    | 0.64      | 0.15      | 0.04      | 0.83          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Rear Face     | 0.76      | 0.17      | 0.03      | 0.96          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    | Hotspot            | Front Face    | 0.64      | 0.15      | 0.00      | 0.79          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Rear Face     | 0.76      | 0.17      | 0.00      | 0.93          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Left Side     | 0.00      | 0.11      | 0.00      | 0.11          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Right Side    | 0.48      | 0.00      | 0.00      | 0.48          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Top Side      | 0.00      | 0.00      | 0.00      | 0.00          | $\Sigma$ SAR < 1.6, Not required |
|     |                                                                    |                    | Bottom Side   | 0.60      | 0.09      | 0.00      | 0.69          | $\Sigma$ SAR < 1.6, Not required |

Test Engineer : Eric Wu, and Smith Chen

## 5. Calibration of Test Equipment

| Equipment                       | Manufacturer | Model   | SN         | Cal. Date     | Cal. Interval |
|---------------------------------|--------------|---------|------------|---------------|---------------|
| System Validation Dipole        | SPEAG        | D750V3  | 1013       | Aug. 28, 2014 | 2 ears        |
| System Validation Dipole        | SPEAG        | D835V2  | 4d121      | Aug. 28, 2014 | 2 ears        |
| System Validation Dipole        | SPEAG        | D1750V2 | 1055       | Aug. 28, 2014 | 2 ears        |
| System Validation Dipole        | SPEAG        | D1900V2 | 5d036      | Jan. 21, 2013 | 2 ears        |
| System Validation Dipole        | SPEAG        | D2450V2 | 737        | Aug. 21, 2014 | 2Year         |
| System Validation Dipole        | SPEAG        | D5GHzV2 | 1019       | Aug. 25, 2014 | 2Year         |
| Dosimetric E-Field Probe        | SPEAG        | EX3DV4  | 3590       | Mar. 04, 2014 | 1 Year        |
| Dosimetric E-Field Probe        | SPEAG        | EX3DV4  | 3650       | Jul. 28, 2014 | 1 Year        |
| Dosimetric E-Field Probe        | SPEAG        | EX3DV4  | 3864       | Jul. 25, 2014 | 1 Year        |
| Dosimetric E-Field Probe        | SPEAG        | EX3DV4  | 3971       | Mar. 31, 2014 | 1 Year        |
| Data Acquisition Electronics    | SPEAG        | DAE3    | 510        | Aug. 26, 2014 | 1 Year        |
| Data Acquisition Electronics    | SPEAG        | DAE4    | 861        | Apr. 23, 2014 | 1 Year        |
| Data Acquisition Electronics    | SPEAG        | DAE4    | 1277       | Jul. 22, 2014 | 1 Year        |
| Data Acquisition Electronics    | SPEAG        | DAE4    | 1431       | Mar. 24, 2014 | 1 Year        |
| Wireless Communication Test Set | Agilent      | E5515C  | MY50266628 | Dec. 05, 2013 | 2 Years       |
| Radio Communication Analyzer    | Anritsu      | MT8820C | 6201300638 | Jul. 22, 2014 | 1 Year        |
| ENA Series Network Analyzer     | Agilent      | E5071C  | MY46214281 | Jun. 13, 2014 | 1 Year        |
| EXA Spectrum Analyzer           | Agilent      | N9010A  | MY53470455 | Feb. 22, 2014 | 1 Year        |
| MXG Analog Signal Generator     | Agilent      | N5181A  | MY50143868 | Jun. 26, 2014 | 1 Year        |
| Power Meter                     | Anritsu      | ML2495A | 1218009    | Jun. 26, 2014 | 1 Year        |
| Power Sensor                    | Anritsu      | MA2411B | 1207252    | Jun. 26, 2014 | 1 Year        |
| Thermometer                     | YFE          | YF-160A | 130504579  | Aug. 21, 2014 | 1 Year        |

## 6. Measurement Uncertainty

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Standard Uncertainty (1g) | Vi |
|--------------------------------------|------------------------|--------------------------|---------|---------|---------------------------|----|
| <b>Measurement System</b>            |                        |                          |         |         |                           |    |
| Probe Calibration                    | 6.0                    | Normal                   | 1       | 1       | ± 6.0 %                   | ∞  |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | ± 1.9 %                   | ∞  |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | ± 3.9 %                   | ∞  |
| Boundary Effects                     | 1.0                    | Rectangular              | √3      | 1       | ± 0.6 %                   | ∞  |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | ± 2.7 %                   | ∞  |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | ± 0.6 %                   | ∞  |
| Readout Electronics                  | 0.6                    | Normal                   | 1       | 1       | ± 0.6 %                   | ∞  |
| Response Time                        | 0.0                    | Rectangular              | √3      | 1       | ± 0.0 %                   | ∞  |
| Integration Time                     | 1.7                    | Rectangular              | √3      | 1       | ± 1.0 %                   | ∞  |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| Probe Positioner                     | 0.5                    | Rectangular              | √3      | 1       | ± 0.3 %                   | ∞  |
| Probe Positioning                    | 2.9                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| Max. SAR Eval.                       | 2.3                    | Rectangular              | √3      | 1       | ± 1.3 %                   | ∞  |
| <b>Test Sample Related</b>           |                        |                          |         |         |                           |    |
| Device Positioning                   | 3.9                    | Normal                   | 1       | 1       | ± 3.9 %                   | 31 |
| Device Holder                        | 2.7                    | Normal                   | 1       | 1       | ± 2.7 %                   | 19 |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | ± 2.9 %                   | ∞  |
| <b>Phantom and Setup</b>             |                        |                          |         |         |                           |    |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | ± 2.3 %                   | ∞  |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | ± 1.8 %                   | ∞  |
| Liquid Conductivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.64    | ± 3.2 %                   | 29 |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | ± 1.7 %                   | ∞  |
| Liquid Permittivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.6     | ± 3.0 %                   | 29 |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         | ± 11.7 %                  |    |
| <b>Expanded Uncertainty (K=2)</b>    |                        |                          |         |         | ± 23.4 %                  |    |

Uncertainty budget for frequency range 300 MHz to 3 GHz

# FCC SAR Test Report

A D T

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Standard Uncertainty (1g) | Vi |
|--------------------------------------|------------------------|--------------------------|---------|---------|---------------------------|----|
| <b>Measurement System</b>            |                        |                          |         |         |                           |    |
| Probe Calibration                    | 6.55                   | Normal                   | 1       | 1       | ± 6.55 %                  | ∞  |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | ± 1.9 %                   | ∞  |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | ± 3.9 %                   | ∞  |
| Boundary Effects                     | 2.0                    | Rectangular              | √3      | 1       | ± 1.2 %                   | ∞  |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | ± 2.7 %                   | ∞  |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | ± 0.6 %                   | ∞  |
| Readout Electronics                  | 0.3                    | Normal                   | 1       | 1       | ± 0.3 %                   | ∞  |
| Response Time                        | 0.8                    | Rectangular              | √3      | 1       | ± 0.5 %                   | ∞  |
| Integration Time                     | 2.6                    | Rectangular              | √3      | 1       | ± 1.5 %                   | ∞  |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | ± 1.7 %                   | ∞  |
| Probe Positioner                     | 0.8                    | Rectangular              | √3      | 1       | ± 0.5 %                   | ∞  |
| Probe Positioning                    | 9.9                    | Rectangular              | √3      | 1       | ± 5.7 %                   | ∞  |
| Max. SAR Eval.                       | 4.0                    | Rectangular              | √3      | 1       | ± 2.3 %                   | ∞  |
| <b>Test Sample Related</b>           |                        |                          |         |         |                           |    |
| Device Positioning                   | 3.9                    | Normal                   | 1       | 1       | ± 3.9 %                   | 31 |
| Device Holder                        | 2.7                    | Normal                   | 1       | 1       | ± 2.7 %                   | 19 |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | ± 2.9 %                   | ∞  |
| <b>Phantom and Setup</b>             |                        |                          |         |         |                           |    |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | ± 2.3 %                   | ∞  |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | ± 1.8 %                   | ∞  |
| Liquid Conductivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.64    | ± 3.2 %                   | 30 |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | ± 1.7 %                   | ∞  |
| Liquid Permittivity (Meas.)          | 5.0                    | Normal                   | 1       | 0.6     | ± 3.0 %                   | 30 |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         | ± 13.4 %                  |    |
| <b>Expanded Uncertainty (K=2)</b>    |                        |                          |         |         | ± 26.8 %                  |    |

Uncertainty budget for frequency range 3 GHz to 6 GHz

## FCC SAR Test Report

### 7. +Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Taiwan HwaYa EMC/RF/Safety/Telecom Lab:**

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232

Fax: 886-3-327-0892

**Taiwan LinKo EMC/RF Lab:**

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180

Fax: 886-2-2605-1924

**Taiwan HsinChu EMC/RF Lab:**

Add: No. 81-1, Lu Liao Keng, 9<sup>th</sup> Ling, Wu Lung Vil., Chiung Lin Township, Hsinchu County 307, Taiwan, R.O.C.

Tel: 886-3-593-5343

Fax: 886-3-593-5342

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The road map of all our labs can be found in our web site also.

---END---

## **Appendix A. SAR Plots of System Verification**

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

## System Check\_H750\_141224

**DUT: Dipole 750 MHz; Type: D750V3; SN: 1013**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: H07T08N1\_1224 Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.912 \text{ S/m}$ ;  $\epsilon_r = 40.638$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature :  $22.3 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.8 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.93, 9.93, 9.93); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1485; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $2.77 \text{ W/kg}$


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $53.52 \text{ V/m}$ ; Power Drift =  $-0.01 \text{ dB}$

Peak SAR (extrapolated) =  $3.23 \text{ W/kg}$

**SAR(1 g) =  $2.22 \text{ W/kg}$ ; SAR(10 g) =  $1.49 \text{ W/kg}$**

Maximum value of SAR (measured) =  $2.78 \text{ W/kg}$



## System Check\_H835\_141220

**DUT: Dipole 835 MHz; Type: D835V2; SN: 4d121**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: H08T09N3\_1220 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.908 \text{ S/m}$ ;  $\epsilon_r = 42.576$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature :  $22.1 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.7 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.52, 9.52, 9.52); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $2.98 \text{ W/kg}$


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $55.27 \text{ V/m}$ ; Power Drift =  $-0.01 \text{ dB}$

Peak SAR (extrapolated) =  $3.52 \text{ W/kg}$

**SAR(1 g) =  $2.35 \text{ W/kg}$ ; SAR(10 g) =  $1.54 \text{ W/kg}$**

Maximum value of SAR (measured) =  $2.99 \text{ W/kg}$



## System Check\_H1750\_141222

**DUT: Dipole 1750 MHz; Type: D1750V2; SN: 1055**

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: H17T18N1\_1222 Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.327$  S/m;  $\epsilon_r = 40.761$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.8 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(8.1, 8.1, 8.1); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.6 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 100.3 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 16.4 W/kg

**SAR(1 g) = 9.31 W/kg; SAR(10 g) = 5.07 W/kg**

Maximum value of SAR (measured) = 12.9 W/kg



## System Check\_H1900\_141223

**DUT: Dipole 1900 MHz; Type: D1900V2; SN: 5d036**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: H18T19N1\_1223 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.43$  S/m;  $\epsilon_r = 39.118$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.92, 7.92, 7.92); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.3 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.65 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 17.7 W/kg

**SAR(1 g) = 9.62 W/kg; SAR(10 g) = 5.03 W/kg**

Maximum value of SAR (measured) = 13.7 W/kg



## System Check\_H2450\_150109

**DUT: Dipole 2450 MHz; Type: D2450V2; SN: 737**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: H24T25N2\_0109 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.817$  S/m;  $\epsilon_r = 40.019$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(7.43, 7.43, 7.43); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 19.9 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.7 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 27.4 W/kg

**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.85 W/kg**

Maximum value of SAR (measured) = 20.0 W/kg



## System Check\_H5200\_150112

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: H50T60N1\_0112 Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.777$  S/m;  $\epsilon_r = 37.32$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(5.22, 5.22, 5.22); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 17.1 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.26 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 34.6 W/kg

**SAR(1 g) = 8.05 W/kg; SAR(10 g) = 2.29 W/kg**

Maximum value of SAR (measured) = 16.7 W/kg



## System Check\_H5300\_150112

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: H50T60N1\_0112 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 4.914$  S/m;  $\epsilon_r = 37.221$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.8°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.81, 4.81, 4.81); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.8 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 61.31 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 34.4 W/kg

**SAR(1 g) = 8.21 W/kg; SAR(10 g) = 2.32 W/kg**

Maximum value of SAR (measured) = 17.0 W/kg



## System Check\_H5600\_150111

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: H50T60N1\_0111 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.278$  S/m;  $\epsilon_r = 36.522$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.9 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.55, 4.55, 4.55); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 17.6 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 62.33 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 36.6 W/kg

**SAR(1 g) = 8.35 W/kg; SAR(10 g) = 2.36 W/kg**

Maximum value of SAR (measured) = 18.1 W/kg



## System Check\_H5800\_150111

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: H50T60N1\_0111 Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.434$  S/m;  $\epsilon_r = 36.253$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.9 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.53, 4.53, 4.53); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.0 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 59.14 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 32.7 W/kg

**SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.16 W/kg**

Maximum value of SAR (measured) = 16.4 W/kg



## System Check\_B750\_141220

**DUT: Dipole 750 MHz; Type: D750V3; SN: 1013**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: B07T08N3\_1220 Medium parameters used:  $f = 750 \text{ MHz}$ ;  $\sigma = 0.966 \text{ S/m}$ ;  $\epsilon_r = 55.259$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature :  $22.2 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.62, 9.62, 9.62); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x81x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $2.53 \text{ W/kg}$


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $52.34 \text{ V/m}$ ; Power Drift =  $0.01 \text{ dB}$

Peak SAR (extrapolated) =  $2.90 \text{ W/kg}$

**SAR(1 g) =  $2.03 \text{ W/kg}$ ; SAR(10 g) =  $1.37 \text{ W/kg}$**

Maximum value of SAR (measured) =  $2.52 \text{ W/kg}$



## System Check\_B835\_141221

**DUT: Dipole 835 MHz; Type: D835V2; SN: 4d121**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: B08T09N3\_1221 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.992 \text{ S/m}$ ;  $\epsilon_r = 56.824$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature :  $22.1 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.1 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.7, 9.7, 9.7); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $3.15 \text{ W/kg}$


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $53.84 \text{ V/m}$ ; Power Drift =  $-0.02 \text{ dB}$

Peak SAR (extrapolated) =  $3.69 \text{ W/kg}$

**SAR(1 g) =  $2.44 \text{ W/kg}$ ; SAR(10 g) =  $1.6 \text{ W/kg}$**

Maximum value of SAR (measured) =  $3.09 \text{ W/kg}$



## System Check\_B1750\_141222

**DUT: Dipole 1750 MHz; Type: D1750V2; SN: 1055**

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: B17T18N3\_1222 Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.501$  S/m;  $\epsilon_r = 52.937$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

### DASY5 Configuration

- Probe: EX3DV4 - SN3650; ConvF(7.78, 7.78, 7.78); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.6 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 95.00 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 16.2 W/kg

**SAR(1 g) = 9.25 W/kg; SAR(10 g) = 4.94 W/kg**

Maximum value of SAR (measured) = 12.8 W/kg



## System Check\_B1900\_141222

**DUT: Dipole 1900 MHz; Type: D1900V2; SN: 5d036**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: B18T19N3\_1222 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.548$  S/m;  $\epsilon_r = 52.591$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.41, 7.41, 7.41); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.5 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 100.6 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 19.3 W/kg

**SAR(1 g) = 10.6 W/kg; SAR(10 g) = 5.49 W/kg**

Maximum value of SAR (measured) = 15.2 W/kg



**System Check\_B2450\_150120****DUT: Dipole 2450 MHz; Type: D2450V2; SN: 737**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: B24T25N1\_0120 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.971$  S/m;  $\epsilon_r = 51.349$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(7.72, 7.72, 7.72); Calibrated: 2014/03/04;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2014/04/23
- Phantom: ELI Phantom\_1043; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 20.4 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 102.3 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 28.3 W/kg

**SAR(1 g) = 13.1 W/kg; SAR(10 g) = 5.99 W/kg**

Maximum value of SAR (measured) = 20.6 W/kg



**System Check\_B5200\_150114****DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: B50T60N1\_0114 Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.327$  S/m;  $\epsilon_r = 47.281$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(4.49, 4.49, 4.49); Calibrated: 2014/07/25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510; Calibrated: 2014/08/26
- Phantom: Twin SAM Phantom\_1653; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 14.9 W/kg



**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 55.62 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 29.2 W/kg

**SAR(1 g) = 7.23 W/kg; SAR(10 g) = 2.05 W/kg**

Maximum value of SAR (measured) = 15.0 W/kg



## System Check\_B5300\_150112

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: B50T60N1\_0112 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.488$  S/m;  $\epsilon_r = 47.439$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.19, 4.19, 4.19); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.7 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.32 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 31.1 W/kg

**SAR(1 g) = 7.91 W/kg; SAR(10 g) = 2.25 W/kg**

Maximum value of SAR (measured) = 16.4 W/kg



**System Check\_B5600\_150114****DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: B50T60N1\_0114 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.894$  S/m;  $\epsilon_r = 46.817$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.9 °C ; Liquid Temperature : 22.0 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(3.77, 3.77, 3.77); Calibrated: 2014/07/25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510; Calibrated: 2014/08/26
- Phantom: Twin SAM Phantom\_1653; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.4 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.06 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 34.5 W/kg

**SAR(1 g) = 8.41 W/kg; SAR(10 g) = 2.39 W/kg**

Maximum value of SAR (measured) = 17.6 W/kg



**System Check\_B5800\_150106****DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: B50T60N2\_0106 Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.185$  S/m;  $\epsilon_r = 46.167$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.7 °C ; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(4.01, 4.01, 4.01); Calibrated: 2014/07/25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510; Calibrated: 2014/08/26
- Phantom: Twin SAM Phantom\_1652; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 17.7 W/kg



**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 55.94 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 33.9 W/kg

**SAR(1 g) = 7.84 W/kg; SAR(10 g) = 2.22 W/kg**

Maximum value of SAR (measured) = 16.9 W/kg





### Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.


**P01 CDMA2000 BC0\_RC3+SO55\_Right Cheek\_Ch384\_Battery1****DUT: 141118C01**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: H08T09N3\_1220 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.91 \text{ S/m}$ ;  $\epsilon_r = 42.555$ ;  $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature :  $22.1 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.7 \text{ }^\circ\text{C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.52, 9.52, 9.52); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.760 \text{ W/kg}$ **- Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $9.964 \text{ V/m}$ ; Power Drift =  $-0.13 \text{ dB}$ Peak SAR (extrapolated) =  $0.855 \text{ W/kg}$ **SAR(1 g) =  $0.672 \text{ W/kg}$ ; SAR(10 g) =  $0.513 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.770 \text{ W/kg}$ 

**P02 CDMA2000 BC1\_RC3+SO55\_Right Cheek\_Ch25\_Battery1****DUT: 141118C01**

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: H18T19N1\_1223 Medium parameters used:  $f = 1851.25$  MHz;  $\sigma = 1.378$  S/m;  $\epsilon_r = 39.339$ ; $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.92, 7.92, 7.92); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.853 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.799 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.980 W/kg

**SAR(1 g) = 0.602 W/kg; SAR(10 g) = 0.365 W/kg**

Maximum value of SAR (measured) = 0.759 W/kg



## P03 LTE 4\_QPSK20M\_Left Cheek\_Ch20300\_Battery2\_1RB\_OS0

**DUT: 141118C01**

Communication System: LTE; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: H17T18N1\_1222 Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.324$  S/m;  $\epsilon_r = 40.773$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.8 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(8.1, 8.1, 8.1); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- **Area Scan (71x121x1)**: Interpolated grid:  $dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.621 W/kg


- **Zoom Scan (5x5x7)/Cube 0**: Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 8.700 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.740 W/kg

**SAR(1 g) = 0.477 W/kg; SAR(10 g) = 0.297 W/kg**

Maximum value of SAR (measured) = 0.612 W/kg




**P04 LTE 13\_QPSK10M\_Left Cheek\_Ch23230\_Battery1\_1RB\_OS0****DUT: 141118C01**

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H07T08N1\_1224 Medium parameters used:  $f = 782 \text{ MHz}$ ;  $\sigma = 0.931 \text{ S/m}$ ;  $\epsilon_r = 40.503$ ;  $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature :  $22.3 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.8 \text{ }^\circ\text{C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.93, 9.93, 9.93); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1485; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.531 \text{ W/kg}$ **- Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $9.109 \text{ V/m}$ ; Power Drift =  $0.12 \text{ dB}$ Peak SAR (extrapolated) =  $0.581 \text{ W/kg}$ **SAR(1 g) =  $0.460 \text{ W/kg}$ ; SAR(10 g) =  $0.354 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.524 \text{ W/kg}$ 


**P05 LTE 14\_QPSK10M\_Left Cheek\_Ch23330\_Battery2\_1RB\_OS0****DUT: 141118C01**

Communication System: LTE; Frequency: 793 MHz; Duty Cycle: 1:1

Medium: H07T08N3\_1225 Medium parameters used:  $f = 793 \text{ MHz}$ ;  $\sigma = 0.906 \text{ S/m}$ ;  $\epsilon_r = 40.977$ ;  $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature :  $21.7^\circ\text{C}$ ; Liquid Temperature :  $21.1^\circ\text{C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.89, 10.89, 10.89); Calibrated: 2014/03/04;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2014/04/23
- Phantom: Twin SAM Phantom\_1654; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x111x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.421 \text{ W/kg}$ **- Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $6.033 \text{ V/m}$ ; Power Drift =  $0.07 \text{ dB}$ Peak SAR (extrapolated) =  $0.511 \text{ W/kg}$ **SAR(1 g) =  $0.361 \text{ W/kg}$ ; SAR(10 g) =  $0.249 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.397 \text{ W/kg}$ 

**P06 802.11b\_Left Cheek\_Ch11\_Battery2****DUT: 141118C01**

Communication System: WLAN\_2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: H24T25N2\_0109 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.831$  S/m;  $\epsilon_r = 39.975$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(7.43, 7.43, 7.43); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (91x141x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.527 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.291 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.06 W/kg

**SAR(1 g) = 0.448 W/kg; SAR(10 g) = 0.213 W/kg**

Maximum value of SAR (measured) = 0.725 W/kg



**P07 802.11a\_Left Cheek\_Ch40\_Battery1****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5200 MHz; Duty Cycle: 1:1.15

Medium: H50T60N1\_0112 Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.777$  S/m;  $\epsilon_r = 37.32$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(5.22, 5.22, 5.22); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.498 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.848 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.68 W/kg

**SAR(1 g) = 0.436 W/kg; SAR(10 g) = 0.124 W/kg**

Maximum value of SAR (measured) = 0.930 W/kg



**P08 802.11a\_Left Cheek\_Ch56\_Battery2****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5280 MHz; Duty Cycle: 1:1.16

Medium: H50T60N1\_0112 Medium parameters used:  $f = 5280$  MHz;  $\sigma = 4.925$  S/m;  $\epsilon_r = 37.221$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.81, 4.81, 4.81); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.321 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.25 W/kg

**SAR(1 g) = 0.354 W/kg; SAR(10 g) = 0.104 W/kg**

Maximum value of SAR (measured) = 0.721 W/kg



**P09 802.11a\_Left Cheek\_Ch100\_Battery2****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5500 MHz; Duty Cycle: 1:1.15

Medium: H50T60N1\_0111 Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.178$  S/m;  $\epsilon_r = 36.797$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.9 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.93, 4.93, 4.93); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.627 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.243 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.81 W/kg

**SAR(1 g) = 0.507 W/kg; SAR(10 g) = 0.153 W/kg**

Maximum value of SAR (measured) = 0.967 W/kg



**P10 802.11a\_Left Cheek\_Ch149\_Battery2****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5745 MHz; Duty Cycle: 1:1.15

Medium: H50T60N1\_0111 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 5.426$  S/m;  $\epsilon_r = 36.507$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.9 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.53, 4.53, 4.53); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.887 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.028 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 1.91 W/kg

**SAR(1 g) = 0.582 W/kg; SAR(10 g) = 0.187 W/kg**

Maximum value of SAR (measured) = 1.13 W/kg



**P11 CDMA2000 BC0\_RTAP153.6\_Rear Face\_1cm\_Ch384\_Battery1****DUT: 141118C01**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: B08T09N3\_1221 Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.994$  S/m;  $\epsilon_r = 56.805$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.7, 9.7, 9.7); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.932 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.51 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.02 W/kg

**SAR(1 g) = 0.793 W/kg; SAR(10 g) = 0.596 W/kg**

Maximum value of SAR (measured) = 0.917 W/kg



**P12 CDMA2000 BC1\_RTAP153.6\_Rear Face\_1cm\_Ch25\_Battery1****DUT: 141118C01**

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: B18T19N3\_1222 Medium parameters used:  $f = 1851.4$  MHz;  $\sigma = 1.493$  S/m;  $\epsilon_r = 52.741$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.41, 7.41, 7.41); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.881 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.31 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.10 W/kg

**SAR(1 g) = 0.686 W/kg; SAR(10 g) = 0.397 W/kg**

Maximum value of SAR (measured) = 0.891 W/kg



**P13 LTE 4\_QPSK20M\_Front Face\_1cm\_Ch20300\_Battery2\_1RB\_OS0****DUT: 141118C01**

Communication System: LTE; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: B17T18N3\_1222 Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.497$  S/m;  $\epsilon_r = 52.945$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.78, 7.78, 7.78); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: Twin SAM Phantom\_1822; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.878 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.599 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.988 W/kg

**SAR(1 g) = 0.646 W/kg; SAR(10 g) = 0.395 W/kg**

Maximum value of SAR (measured) = 0.814 W/kg




**P14 LTE 13\_QPSK10M\_Rear Face\_1cm\_Ch23230\_Battery1\_1RB\_OS0****DUT: 141118C01**

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B07T08N3\_1220 Medium parameters used:  $f = 782 \text{ MHz}$ ;  $\sigma = 0.992 \text{ S/m}$ ;  $\epsilon_r = 54.935$ ;  $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature :  $22.2 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.2 \text{ }^\circ\text{C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.62, 9.62, 9.62); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.751 \text{ W/kg}$ **- Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $23.11 \text{ V/m}$ ; Power Drift =  $-0.03 \text{ dB}$ Peak SAR (extrapolated) =  $0.875 \text{ W/kg}$ **SAR(1 g) =  $0.649 \text{ W/kg}$ ; SAR(10 g) =  $0.472 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.760 \text{ W/kg}$ 


**P15 LTE 14\_QPSK10M\_Rear Face\_1cm\_Ch23330\_Battery1\_1RB\_OS0****DUT: 141118C01**

Communication System: LTE; Frequency: 793 MHz; Duty Cycle: 1:1

Medium: B07T08N3\_1220 Medium parameters used:  $f = 793 \text{ MHz}$ ;  $\sigma = 1.001 \text{ S/m}$ ;  $\epsilon_r = 54.822$ ;  $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature :  $22.2 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $21.2 \text{ }^\circ\text{C}$ 

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.62, 9.62, 9.62); Calibrated: 2014/07/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2014/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.681 \text{ W/kg}$ **- Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $21.36 \text{ V/m}$ ; Power Drift =  $-0.01 \text{ dB}$ Peak SAR (extrapolated) =  $0.787 \text{ W/kg}$ **SAR(1 g) =  $0.574 \text{ W/kg}$ ; SAR(10 g) =  $0.412 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.683 \text{ W/kg}$ 

**P16 802.11b\_Front Face\_1cm\_Ch11\_Battery1****DUT: 141118C01**

Communication System: WLAN\_2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: B24T25N2\_0109 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.011$  S/m;  $\epsilon_r = 50.713$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(7.29, 7.29, 7.29); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (91x141x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.105 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.871 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.163 W/kg

**SAR(1 g) = 0.079 W/kg; SAR(10 g) = 0.040 W/kg**

Maximum value of SAR (measured) = 0.115 W/kg



**P17 802.11a\_Rear Face\_1cm\_Ch40\_Battery1****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5200 MHz; Duty Cycle: 1:1.15

Medium: B50T60N1\_0112 Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.347$  S/m;  $\epsilon_r = 47.666$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.59, 4.59, 4.59); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.330 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.838 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.538 W/kg

**SAR(1 g) = 0.162 W/kg; SAR(10 g) = 0.062 W/kg**

Maximum value of SAR (measured) = 0.294 W/kg



**P18 802.11a\_Rear Face\_1cm\_Ch56\_Battery1****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5280 MHz; Duty Cycle: 1:1.16

Medium: B50T60N1\_0112 Medium parameters used:  $f = 5280$  MHz;  $\sigma = 5.454$  S/m;  $\epsilon_r = 47.457$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.19, 4.19, 4.19); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.313 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.309 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.520 W/kg

**SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.059 W/kg**

Maximum value of SAR (measured) = 0.278 W/kg



**P19 802.11a\_Rear Face\_1cm\_Ch100\_Battery1****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5500 MHz; Duty Cycle: 1:1.16

Medium: B50T60N1\_0111 Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.749$  S/m;  $\epsilon_r = 46.751$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.14, 4.14, 4.14); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.471 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 1.909 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.943 W/kg

**SAR(1 g) = 0.271 W/kg; SAR(10 g) = 0.106 W/kg**

Maximum value of SAR (measured) = 0.471 W/kg



**P20 802.11a\_Rear Face\_1cm\_Ch149\_Battery1****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: B50T60N2\_0106 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 6.086$  S/m;  $\epsilon_r = 46.241$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.7 °C ; Liquid Temperature : 21.2 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3864; ConvF(4.01, 4.01, 4.01); Calibrated: 2014/07/25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510; Calibrated: 2014/08/26
- Phantom: Twin SAM Phantom\_1652; Type: QD000P40;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- **Area Scan (121x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.558 W/kg


- **Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 3.129 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.75 W/kg

**SAR(1 g) = 0.285 W/kg; SAR(10 g) = 0.109 W/kg**

Maximum value of SAR (measured) = 0.549 W/kg



**P21 Bluetooth\_DH5\_Front Face\_1cm\_Ch0\_Battery2****DUT: 141118C01**

Communication System: BT; Frequency: 2402 MHz; Duty Cycle: 1:1.32

Medium: B24T25N1\_0120 Medium parameters used:  $f = 2402$  MHz;  $\sigma = 1.911$  S/m;  $\epsilon_r = 51.53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 21.6 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(7.72, 7.72, 7.72); Calibrated: 2014/03/04;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2014/04/23
- Phantom: ELI Phantom\_1043; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x141x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0465 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.326 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.0680 W/kg

**SAR(1 g) = 0.036 W/kg; SAR(10 g) = 0.020 W/kg**

Maximum value of SAR (measured) = 0.0480 W/kg



**P22 802.11b\_Right Side\_1cm\_Ch11\_Battery2****DUT: 141118C01**

Communication System: WLAN\_2.4G; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: B24T25N2\_0109 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.011$  S/m;  $\epsilon_r = 50.713$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(7.29, 7.29, 7.29); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (51x141x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.270 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.902 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.405 W/kg

**SAR(1 g) = 0.184 W/kg; SAR(10 g) = 0.083 W/kg**

Maximum value of SAR (measured) = 0.277 W/kg



**P23 802.11a\_Right Side\_1cm\_Ch40\_Battery1****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5200 MHz; Duty Cycle: 1:1.15

Medium: B50T60N1\_0112 Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.347$  S/m;  $\epsilon_r = 47.666$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.59, 4.59, 4.59); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (61x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.798 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 7.245 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.20 W/kg

**SAR(1 g) = 0.342 W/kg; SAR(10 g) = 0.124 W/kg**

Maximum value of SAR (measured) = 0.616 W/kg



**P24 802.11a\_Right Side\_1cm\_Ch149\_Battery2****DUT: 141118C01**

Communication System: WLAN\_5G; Frequency: 5745 MHz; Duty Cycle: 1:1.15

Medium: B50T60N1\_0111 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 6.086$  S/m;  $\epsilon_r = 46.241$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3971; ConvF(4.12, 4.12, 4.12); Calibrated: 2014/03/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2014/03/24
- Phantom: Twin SAM Phantom\_1823; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (61x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.20 W/kg

**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 5.125 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 2.54 W/kg

**SAR(1 g) = 0.650 W/kg; SAR(10 g) = 0.206 W/kg**

Maximum value of SAR (measured) = 1.17 W/kg

