

FCC DoC Test Report

Report No.: FD141118C01

FCC ID: AZ489FT7062

Test Model: LEX L10

Received Date: Dec. 16, 2014

Test Date: Dec. 23 ~ Dec. 25, 2014

Issued Date: Dec. 30, 2014

Applicant: Motorola Solutions Inc

Address: 1301 East Algonquin Road, Schaumburg, Illinois 60196

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty	5
2.2 Modification Record	5
3 General Information	6
3.1 Features of EUT	6
3.2 General Description of EUT	6
3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode	8
3.4 Test Program Used and Operation Descriptions.....	9
3.5 Primary Clock Frequencies of Internal Source	9
3.6 Miscellaneous.....	9
4 Configuration and Connections with EUT	11
4.1 Connection Diagram of EUT and Peripheral Devices	11
4.2 Configuration of Peripheral Devices and Cable Connections	12
5 Conducted Emissions at Mains Ports.....	13
5.1 Limits	13
5.2 Test Instruments	13
5.3 Test Arrangement	14
5.4 Test Results.....	15
6 Radiated Emissions up to 1 GHz	17
6.1 Limits	17
6.2 Test Instruments	18
6.3 Test Arrangement	19
6.4 Test Results.....	20
7 Radiated Emissions above 1 GHz.....	22
7.1 Limits	22
7.2 Test Instruments	23
7.3 Test Arrangement	24
7.4 Test Results.....	25
8 Pictures of Test Arrangements	29
8.1 Conducted Emissions at Mains Ports	29
8.2 Radiated Emissions up to 1 GHz	30
8.3 Radiated Emissions above 1 GHz	31
Appendix – Information on the Testing Laboratories	32



Release Control Record

Issue No.	Description	Date Issued
FD141118C01	Original release.	Dec. 30, 2014

1 Certificate of Conformity

Product: Smart phone

Brand: Motorola Solutions Inc

Test Model: LEX L10

Sample Status: PROTOTYPE

Applicant: Motorola Solutions Inc

Test Date: Dec. 23 ~ Dec. 25, 2014

Standards: 47 CFR FCC Part 15, Subpart B, Class B
ICES-003:2012 Issue 5, Class B
ANSI C63.4:2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Ivy Lin / Specialist

Date:

Dec. 30, 2014

Approved by :


Ken Liu / Senior Manager

Date:

Dec. 30, 2014

2 Summary of Test Results

47 CFR FCC Part 15, Subpart B / ICES-003:2012 Issue 5, Class B

ANSI C63.4:2009

FCC Clause	ICES-003 Clause	Test Item	Result/Remarks	Verdict
15.107	6.1	AC Power Line Conducted Emissions	Minimum passing Class B margin is -12.02 dB at 1.06103 MHz	Pass
15.109	6.2.1	Radiated Emissions up to 1 GHz	Minimum passing Class B margin is -6.01 dB at 185.60 MHz	Pass
	6.2.2	Radiated Emissions above 1 GHz	Minimum passing Class B margin is -19.22 dB at 20583.41 MHz	Pass

Note: There is no deviation to the applied test methods and requirements covered by the scope of this report.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.70 dB
Radiated Emissions above 1 GHz	Above 1GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 Features of EUT

The tests reported herein were performed according to the method specified by Motorola Solutions Inc, for detailed feature description, please refer to the manufacturer's specifications or user's manual.

3.2 General Description of EUT

Product	Smart phone		
Brand	Motorola Solutions Inc		
Test Model	LEX L10		
Sample Status	PROTOTYPE		
Operating Software	Andriod 4.4.4		
Power Supply Rating	3.7Vdc (Battery) 5Vdc (Adapter)		
Mode of Operation	Wireless LAN		
	Bluetooth EDR		
	Bluetooth LE		
	CDMA BC0, BC1		
	LTE Band 4, 13, 14		
Operating Frequency	WLAN	2.4GHz: 2412 ~ 2472MHz 5.0GHz: 5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5700MHz & 5745 ~ 5825MHz	
	Bluetooth EDR	2402MHz~2480MHz	
	Bluetooth LE	2402MHz~2480MHz	
	CDMA	824.7MHz ~ 848.31MHz 1851.25MHz ~ 1908.75MHz	
	LTE Band 4	Channel Bandwidth 1.4MHz	1710.7MHz ~ 1754.3MHz
		Channel Bandwidth 3MHz	1711.5MHz ~ 1753.5MHz
		Channel Bandwidth 5MHz	1712.5MHz ~ 1752.5MHz
		Channel Bandwidth 10MHz	1715MHz ~ 1750MHz
		Channel Bandwidth 15MHz	1715.5MHz ~ 1747.5MHz
		Channel Bandwidth 20MHz	1720MHz ~ 1745MHz
	LTE Band 13	Channel Bandwidth 5MHz	779.5MHz ~ 784.5MHz
		Channel Bandwidth 10MHz	782MHz
	LTE Band 14	Channel Bandwidth 5MHz	790.5MHz, 795.50MHz
		Channel Bandwidth 10MHz	793MHz

Output Power	WLAN	2.4GHz: 161.065mW 5.0GHz: 5180 ~ 5240MHz: 35.481mW 5260 ~ 5320MHz: 34.119mW 5500 ~ 5700MHz: 32.734mW 5745 ~ 5825MHz: 27.861mW	
	Bluetooth EDR	12.677mW	
	Bluetooth LE	1.762mW	
Max. ERP Power	CDMA BC0	824.7MHz ~ 848.31MHz: 238.781mW (23.78dBm)	
Max. EIRP Power	CDMA BC1	1851.25MHz ~ 1908.75MHz: 223.872mW (23.50dBm)	
Max. EIRP Power	LTE Band 4	Channel Bandwidth 1.4MHz	387.258mW (25.88dBm)
		Channel Bandwidth 3MHz	293.765mW (24.68dBm)
		Channel Bandwidth 5MHz	298.538mW (24.75dBm)
		Channel Bandwidth 10MHz	281.190mW (24.49dBm)
		Channel Bandwidth 15MHz	271.019mW (24.33dBm)
		Channel Bandwidth 20MHz	301.995mW (24.80dBm)
Max. ERP Power	LTE Band 13	Channel Bandwidth 5MHz	199.526mW (23.00dBm)
		Channel Bandwidth 10MHz	110.154mW (20.42dBm)
Max. ERP Power	LTE Band 14	Channel Bandwidth 5MHz	790.5MHz: 253.513mW (24.04dBm)
Max. ERP Power	LTE Band 14	Channel Bandwidth 5MHz	795.50MHz: 229.087mW (23.60dBm)
		Channel Bandwidth 10MHz	793MHz: 125.893mW (21.00dBm)
Accessory Device	Refer to Note for more details		
Data Cable Supplied	Refer to Note for more details		
SW Version	M8974AAAAANLYD4050.1		
HW Version	MSM-8974-1-990BPNSP-TR-01-0-AB		
S/N	071PQX0110		

Note:

- The EUT contains following accessory devices and data cable.

Item	Brand	Model or P/N	Specification
Rechargeable Lithium ion battery	MOTOROLA	PMNN4472A	3.7Vdc, 2340mAh, 8.7Wh
Rechargeable Lithium ion battery	MOTOROLA	PMNN4475A	3.7Vdc, 4560mAh, 16.9Wh
ITE power supply	MOTOROLA	IU08-2050120-WP (P/N: HKTN4008A)	I/P: 100-240Vac, 50-60Hz, 0.2A O/P: 5Vdc, 1.2A
USB cable (CABLE: ES400 USB SYNC AND CHARGE)	N/A	P/N: CKN6969A	1.4m shielded cable without core
Holster	N/A	P/N: HKLN4618A	-

3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode

The EUT is designed with AC power adapter of rating 100-240Vac, 50/60Hz.

For radiated emission evaluation, 230Vac/50Hz (for AS/NZS CISPR 11) and 120Vac/60Hz (for FCC Part 15), had been covered during the pre-test. The worst data was found at **230Vac/50Hz** and recorded in the applied test report.

For radiated emission test, the EUT has been pre-tested under following test modes, and test mode 7 was the worst case for final test.

Mode	Test Condition
1	WLAN 2.4GHz Link + CDMA bc 1 Link + LTE Band 4 Link + MP4 play from SD card + earphone + Battery model: PMNN4475A + adapter + 230Vac/ 50Hz
2	WLAN 5GHz Link + CDMA bc 1 Link + LTE Band 4 Link + MP4 play from SD card + Battery model: PMNN4475A + adapter + 230Vac/ 50Hz
3	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + GPS + earphone + Battery model: PMNN4475A + adapter + 230Vac/ 50Hz
4	WLAN 5GHz Link + CDMA bc 1 Link + LTE Band 14 Link + Rear camera + earphone + Battery model: PMNN4475A + adapter + 230Vac/ 50Hz
5	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 4 Link + Front camera + earphone + Battery model: PMNN4475A + adapter + 230Vac/ 50Hz
6	EUT Charging + Battery model: PMNN4475A + USB 3.0 R/W + NB Link + 230Vac/ 50Hz
7	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + Front camera + earphone + Battery model: PMNN4472A + adapter + 230Vac/ 50Hz
8	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + Front camera + earphone + Battery model: PMNN4472A + adapter + 120Vac/ 60Hz

For conducted emission test, the worst mode was selected from radiated emission test to pre-test under following test modes, and test mode 1 was the worst case for final test.

Mode	Test Condition
1	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + Front camera + earphone + Battery model: PMNN4472A + adapter
2	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + Front camera + earphone + Battery model: PMNN4472A + Notebook Link

Test modes are presented in the report as below.

Mode	Test Condition
Conducted emission test	
-	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + Front camera + earphone + Battery model: PMNN4472A + adapter
Radiated emission test	
-	WLAN 2.4GHz Link + CDMA bc 0 Link + LTE Band 13 Link + Front camera + earphone + Battery model: PMNN4472A + adapter

3.4 Test Program Used and Operation Descriptions

- a. The EUT linked with Bluetooth earphone, Wireless N Dual band Router, CMU 200 and Radio Communication Analyzer, which acted as a communication partner.
- b. The EUT sent audio signal to the earphone and Bluetooth earphone.
- c. The EUT run front camera function.

3.5 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 5 GHz, provided by Motorola Solutions Inc, for detailed internal source, please refer to the manufacturer's specifications.

3.6 Miscellaneous

Labelling Requirements for Part 15 Devices:

➤ Verification

The specific labelling requirements for a device subject to the Verification procedure are contained in Section 15.19(a). These labelling requirements are:

If the device is subject only to Verification, include a label bearing a unique identifier (Section 2.954) and one of three compliance statements specified in Section 15.19(a). If the labeling area for the device is so small, and/or it is not practical to place the compliance statement on the device, then the statement can be placed in the user manual or product packaging (Section 15.19(a)(5)). However, the device must still be labelled with the unique identifier (Verification). Generally, devices smaller than the palm of the hand are considered too small for the compliance statement.

➤ Certification

If the device is subject to Certification: (1) Section 2.925 contains information on identification of the equipment; (2) include a label bearing an FCC Identifier (FCC ID) (Section 2.926) and (3) include the appropriate compliance statement in Section 15.19(a). If the device is considered too small and therefore it is impractical (smaller than the palm of the hand) to display the compliance statement, then the statement may be placed in the user manual or product packaging. However, the device must still be labelled with the FCC ID. If the device is unquestionably too small for the FCC ID to be readable (smaller than 4-6 points), the FCC ID may be placed in the user manual. However, it must be determined that the device itself is too small – the label area allocated to the FCC ID may not be reduced because of over crowded identification of other product and regulatory information.

An electronic display of the FCC ID (see 9. Electronic Labelling below) may be used for Certification of Section 15.212 modular transmitters and software defined radios (Section 2.944).

➤ Declaration of Conformity (DoC):

The labelling requirements for a device subject to the DoC procedure are specified in Section 15.19(b). The label should include the FCC logo along with the Trade Name and Model Number, which satisfies the unique identifier requirement of Section 2.1074 if it represents the identical equipment tested for DoC compliance. For personal computers assembled from authorized components, the following additional text must also be included: "Assembled from tested components," "Complete system not tested." When the device is so small and/or when it is not practical to place the required additional text on the device, the text may be placed in the user manual or pamphlet supplied to the user. However, the FCC logo, Trade Name, and Model Number must still be displayed on the device (Section 15.19(b)(3)).



Part 15 Declaration of Conformity (DoC) Label Examples

Equipment certified as software defined radio may use a means that readily displays the FCC ID on an electronic display screen, instead of labelling the device (Section 2.925 (e)).

Further information may refer to FCC KDB:784748 D01 Labelling Part 15 &18 Guidelines

Labelling Requirements for ICES-003 Devices:


➤ Industry Canada ICES-003 Compliance Label:

CAN ICES-3 ()/NMB-3(*)*

* Insert either "A" or "B" but not both to identify the applicable Class of ITE.

4 Configuration and Connections with EUT

4.1 Connection Diagram of EUT and Peripheral Devices



4.2 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Earphone	Apple	N/A	N/A	N/A	-
B.	BLUETOOTH EARPHONE	ELECOM	LBT-MPHS400	N/A	N/A	-
C.	Wireless N Dual band Router	D-LINK	DIR-815	PVK21B5000399	KA21R815A1	-
D.	CMU 200	R&S	CMU 200	101095	N/A	-
E.	Radio Communication Analyzer	Anritsu	MT8820C	6201010284	N/A	-
F.	SIM card	N/A	N/A	N/A	N/A	Provided by the manufacturer
G.	Micro SD Card	Transcend	8GB	N/A	N/A	-

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items B~E acted as communication partners to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Earphone cable	1	1.2	Y	0	-
2.	USB cable	1	1.4	Y	0	Accessory

5 Conducted Emissions at Mains Ports

5.1 Limits

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Notes: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Test Instruments


Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100612	Sep. 30, 2014	Sep. 29, 2015
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 13, 2014	Feb. 12, 2015
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 21, 2014	Jul. 20, 2015
Software ADT	BV ADT_Conc_ V7.3.7.3	NA	NA	NA

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

5.3 Test Arrangement

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


5.4 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	James Chang	Test Date	2014/12/23

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15782	0.11	40.73	27.83	40.84	27.94	65.58	55.58	-24.74	-27.64
2	0.29858	0.10	38.05	27.29	38.15	27.39	60.28	50.28	-22.13	-22.89
3	0.33928	0.10	39.25	33.26	39.35	33.36	59.22	49.22	-19.87	-15.86
4	0.95546	0.20	35.80	25.84	36.00	26.04	56.00	46.00	-20.00	-19.96
5	1.26044	0.22	43.07	32.40	43.29	32.62	56.00	46.00	-12.71	-13.38
6	1.37383	0.22	36.38	28.81	36.60	29.03	56.00	46.00	-19.40	-16.97

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	James Chang	Test Date	2014/12/23

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.05	41.85	28.39	41.90	28.44	66.00	56.00	-24.10	-27.56
2	0.34198	0.15	40.73	35.42	40.88	35.57	59.16	49.16	-18.28	-13.59
3	0.83816	0.21	36.29	27.79	36.50	28.00	56.00	46.00	-19.50	-18.00
4	1.06103	0.22	43.76	32.39	43.98	32.61	56.00	46.00	-12.02	-13.39
5	1.24089	0.22	39.61	29.27	39.83	29.49	56.00	46.00	-16.17	-16.51
6	1.36992	0.22	38.11	30.28	38.33	30.50	56.00	46.00	-17.67	-15.50

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



6 Radiated Emissions up to 1 GHz

6.1 Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960				
960-1000	49.5	43.5	47	37

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960			57.5	47.5
960-1000	60	54		

- Notes:
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
 3. QP detector shall be applied if not specified.

6.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ (V)	ESR-7	101240	Sep. 29, 2014	Sep. 28, 2015
Test Receiver ROHDE & SCHWARZ (H)	ESR-7	101264	Dec. 04, 2014	Dec. 03, 2015
BILOG Antenna SCHWARZBECK (V)	VULB9168	9168-148	Feb. 25, 2014	Feb. 24, 2015
BILOG Antenna SCHWARZBECK (H)	VULB9168	9168-149	Feb. 25, 2014	Feb. 24, 2015
Preamplifier Agilent (V)	8447D	2944A10636	Oct. 18, 2014	Oct. 17, 2015
Preamplifier Agilent (H)	8447D	2944A10637	Oct. 18, 2014	Oct. 17, 2015
Preamplifier Agilent	8449B	3008A01959	Oct. 18, 2014	Oct. 17, 2015
RF signal cable Woken (V)	8D-FB	Cable-CH(V)-01	Oct. 25, 2014	Oct. 24, 2015
RF signal cable Woken (H)	8D-FB	Cable-CH(H)-01	Oct. 25, 2014	Oct. 24, 2015
Software BV ADT	BV ADT_Radiated_ V 8.7.07	NA	NA	NA
Antenna Tower (V)	MFA-440	9707	NA	NA
Antenna Tower (H)	MFA-440	970705	NA	NA
Turn Table	DS430	50303	NA	NA
Controller (V)	MF7802	074	NA	NA
Controller (H)	MF7802	08093	NA	NA


Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 1.
3. The FCC Site Registration No. is 477732.
4. The IC Site Registration No. is IC 7450F-1.
5. The VCCI Site Registration No. is R-1893.

6.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.




6.4 Test Results

Frequency Range	30MHz ~ 1GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120kHz
Environmental Conditions	20°C, 71%RH	Test Date	2014/12/24
Tested by	Fox Chang		

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	45.04	13.53 QP	30.00	-16.47	4.00 H	140	27.91	-14.38
2	150.38	20.27 QP	30.00	-9.73	4.00 H	346	34.10	-13.83
3	185.60	22.66 QP	30.00	-7.34	3.50 H	329	38.18	-15.52
4	204.32	16.23 QP	30.00	-13.77	4.00 H	336	32.61	-16.38
5	377.62	24.61 QP	37.00	-12.39	3.00 H	57	34.14	-9.53
6	441.59	25.20 QP	37.00	-11.80	2.50 H	62	33.18	-7.98

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	30MHz ~ 1GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120kHz
Environmental Conditions	20°C, 71%RH	Test Date	2014/12/24
Tested by	Fox Chang		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	42.47	19.03 QP	30.00	-10.97	1.00 V	162	33.44	-14.41
2	150.38	22.68 QP	30.00	-7.32	1.50 V	135	36.13	-13.45
3	185.60	23.99 QP	30.00	-6.01	1.00 V	177	39.03	-15.04
4	310.39	20.84 QP	37.00	-16.16	2.50 V	191	31.45	-10.61
5	379.17	22.07 QP	37.00	-14.93	3.00 V	50	31.13	-9.06
6	441.59	26.96 QP	37.00	-10.04	1.00 V	284	34.63	-7.67

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



7 Radiated Emissions above 1 GHz

7.1 Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
Above 3000	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
1000-3000	Avg: 60	Avg: 54	Avg: 56 Peak: 76	Avg: 50 Peak: 70
Above 3000	Peak: 80	Peak: 74	Avg: 60 Peak: 80	Avg: 54 Peak: 74

- Notes:
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBμV/m) = 20 log Emission level (uV/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Radiated Emissions Limits at 1.5 meter (dBμV/m)		
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B
18000-40000	Avg: 66 Peak: 86	Avg: 60 Peak: 80

Note: Limit@1.5m = Limit@3m + 20log(3/1.5)

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40GHz, whichever is lower


7.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 06, 2014	Oct. 05, 2015
Spectrum Analyzer Agilent	E4446A	MY44360124	Feb. 12, 2014	Feb. 11, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 26, 2014	Feb. 25, 2015
RF signal cable Woken	8D-FB	NA	Mar. 21, 2014	Mar. 20, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-404	Jan. 05, 2014	Jan. 04, 2015
Preamplifier Agilent (Above 1GHz)	8449B	3008A01959	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MWX322+MWX2211308 S0295	Nov. 06, 2014	Nov. 05, 2015
Software BV ADT	BV ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Controller BV ADT	SC100	SC93021702	NA	NA
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Jan. 09, 2014	Jan. 08, 2015
RF signal cable HUBER+SUHNER	SUCOFLEX 102	38218/2+37433/2	Oct. 25, 2014	Oct. 24, 2015
Fix tool for Boresight antenna tower	BAF-01	2	NA	NA
26GHz ~ 40GHz Amplifier	EMC26400	815221	Oct. 18, 2014	Oct. 17, 2015

- Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 2.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 686814.
5. The IC Site Registration No. is IC 7450F-2.
6. The VCCI Site Registration No. is G-18.

7.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- For frequency range 1GHz ~ 18GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- For frequency range 18GHz ~ 40GHz, the EUT was set 1.5 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The spectrum analyzer system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.




7.4 Test Results

Frequency Range	1GHz ~ 18GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Mick Chou	Test Date	2014/12/25

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1084.43	37.15 PK	74.00	-36.85	1.00 H	16	47.16	-10.01
2	1084.43	26.81 AV	54.00	-27.19	1.00 H	16	36.82	-10.01
3	1345.10	37.91 PK	74.00	-36.09	1.00 H	255	46.58	-8.67
4	1345.10	26.03 AV	54.00	-27.97	1.00 H	255	34.70	-8.67
5	1492.01	36.00 PK	74.00	-38.00	1.04 H	258	44.24	-8.24
6	1492.01	24.86 AV	54.00	-29.14	1.04 H	258	33.10	-8.24

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	1GHz ~ 18GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Mick Chou	Test Date	2014/12/25

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1235.50	36.91 PK	74.00	-37.09	1.00 V	355	46.06	-9.15
2	1235.50	26.58 AV	54.00	-27.42	1.00 V	355	35.73	-9.15
3	1475.17	37.15 PK	74.00	-36.85	1.03 V	190	45.44	-8.29
4	1475.17	26.49 AV	54.00	-27.51	1.03 V	190	34.78	-8.29
5	1750.11	37.44 PK	74.00	-36.56	1.00 V	340	44.90	-7.46
6	1750.11	27.19 AV	54.00	-26.81	1.00 V	340	34.65	-7.46

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




Frequency Range	18GHz ~ 40GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Mick Chou	Test Date	2014/12/25

Antenna Polarity & Test Distance : Horizontal at 1.5 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	20966.15	50.13 PK	80.00	-29.87	1.00 H	131	55.77	-5.64
2	20966.15	40.19 AV	60.00	-19.81	1.00 H	131	45.83	-5.64

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



Frequency Range	18GHz ~ 40GHz	Detector Function & Resolution Bandwidth	Peak (PK) / Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	20°C, 60%RH
Tested by	Mick Chou	Test Date	2014/12/25

Antenna Polarity & Test Distance : Vertical at 1.5 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	20583.41	51.26 PK	80.00	-28.74	1.00 V	245	57.77	-6.51
2	20583.41	40.78 AV	60.00	-19.22	1.00 V	245	47.29	-6.51

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value

