MOTOROLA SOLUTIONS

CERTIFICATE 2518.08

MS ISO/IEC 17025 TESTING SAMM NO. 0825

MOTOROLA PENANG ADV. COMM. LABORATORY
Motorola Solutions Malaysia Sdn. Bhd.
Plot 2A Medan Bayan Lepas,
Mukim 12, S.W.D. 11900 Bayan Lepas,
Penang, Malaysia.

FCC / ISED TEST REPORT
Report Revision : Rev.B

Date/s Tested	:	08-Nov-2021 - 03-Dec-2021
Report Issue Date	:	06-Dec-2021
Manufacturer/Location	:	Motorola Solutions Malaysia Sdn Bhd Plot 2A, Medan Bayan Lepas, Mukim 12 SWD, 11900 Bayan Lepas, Penang, Malaysia
Requestor	:	LIM POH CHIN
Product Type	:	Hand-held
Product Version (PMN)	:	APX 6000 / APX 6000Li
Model Number (HVIN)	:	H98QDH9PW7BN (IC Model: H98QDH9PW7BN)
Frequency Band	:	2.402 - 2.480 GHz
Max RF Output Power	:	10 mWatts
Applicant Name	:	Motorola Solutions Inc
Applicant Address	:	8000 West Sunrise Boulevard, Fort Lauderdale, Florida 33322
FCC Registrations	:	461337
IC Registrations	:	MY0001
Firmware Version (FVIN)	:	L10212256

The equipment was tested accordance to the requirement listed below:

(2.4GHz BT) **FCC 47CFR Part 15C** **ISED RSS 247 Issue 2**	**PASS**

This report shall not be reproduced without written approval from an officially designated representative of the Motorola Penang Adv. Comm. Laboratory. The results and statements contained in this report pertain only to the device(s) evaluated.

Prepared By:

GAN BOON TEONG
Test Personnel

Approved Signatory:

VINCENT FOONG CHUEN KIT
Responsible Engineer

Table of Contents

1.0. General Information 3
2.0. Summary of Test Results 5
3.0. Measurement Uncertainty 6
4.0. Equipment List 6
5.0. Test Mode Applicability and Test Channel Detail 7
6.0. Transmitter Test Parameters 8
6.1. Conducted RF Output Power (Peak) 8
6.1.1. Test Setup 8
6.1.2. Test Limits: 8
6.1.3. Test Data: 8
6.2. 20dB Channel Bandwidth 12
6.2.1. Test Setup 12
6.2.2. Test Limits: 12
6.2.3. Test Data: 12
6.3. Band-edge Conducted Spurious Emission 13
6.3.1. Test Setup 13
6.3.2. Test Limits 13
6.3.3. Test Result 13
6.4. Dwell time on each channel 14
6.4.1. Test Setup 14
6.4.2. Test Limits: 14
6.4.3. Test Result 14
6.5. Number of hopping Frequency 15
6.5.1. Test Setup 15
6.5.2. Test Limits: 15
6.5.3. Test Result 15
6.6. Channel Separation 16
6.6.1. Test Setup 16
6.6.2. Test Limits: 16
6.6.3. Test Result 16
6.7. Conducted Spurious Emission 17
6.7.1. Test Setup 17
6.7.2. Test Limits: 17
6.7.3. Test Data: 17
6.8. Radiated Emission within restricted Bands 18
6.8.1. Test Setup 18
6.8.2. Test Limits: 19
6.8.3. Test Data: 20
6.9. AC Powerline Conducted Emission 27
6.9.1. Test Setup 27
6.9.2. Test Limits: 28
6.9.3. Test Result 28

REVISION HISTORY

Revision History	Description	Date	Originator
Rev. A	Initial Report	**05-Dec-2021**	**Gan Boon Teong**
Rev. B	Added noise floor desc	**21-Dec-2021**	**Vincent Foong**

1.0. General Information

EUT Description:

Technologies	2.4GHz BT
TX Frequency range	2402MHz – 2480MHz
Modulation Type	GFSK, Pi/4 DQPSK,8DPSK
Connector type	PROGRAMMING, TEST & ALIGNMENT CABLE
Antenna type	INTERNAL BT/WLAN ANTENNA

The EUT contains following accessory devices and data cable:

Item	Brand	Model or P/N
BATT IMP STD DELTA T RUGGED LIION 5000T	MOTOROLA	PMNN4494A
Programming, Test & Alignment Cable	MOTOROLA	PMKN4013C
UHF R1 380-470,GPS 9.3CM 1/4 WAVE	MOTOROLA	FAF5259A

Channel number and frequency information:

79 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, the EUT is to comply with the requirements of the following standards:

FCC 47 CFR Part 15 Subpart C
KDB 558074 D01 15.247 Meas Guidance v05
ANSI C63.10-2013

Deviation from standard

Not applicable as no deviation from standard test method

Modifications to EUT

For RF conducted measurements a pigtail was soldered out of the board while for radiated measurements there were no modifications to the device

Test configuration of EUT

All relevant configurations involving radio models and accessories (including chargers, batteries, antennas) were assessed. Only worst case configurations will be included in this report.

Summary of Test Results

FCC Clause	ISED Clause	Test Item	Result	Remark	Serial number tested	Tested by
15.247 (b)(1)	RSS-247 5.4(b)	Conducted RF Output Power (Peak)	Pass	Highest output power: 9.153 dBm (8.23 mW)	755TXV0019	Gan
15.247 (a)(1)	RSS-247 5.1(a) RSS-247 5.1(b)	(1) 20dB Channel Bandwidth (2) Channel Separation	NA	References data from FCC ID AZ489FT7087 / ISED 109U-89FT7087	NA	NA
15.247(a)(1)(iii)	RSS-247 5.1(d)	Number of hopping Frequency used	NA	References data from FCC ID AZ489FT7087 / ISED 109U-89FT7087	NA	NA
15.247(a)(1)(iii)	RSS-247 5.1(d)	Dwell time on each channel	NA	References data from FCC ID AZ489FT7087 / ISED 109U-89FT7087	NA	NA
15.247 (d)	RSS-247 5.5	Band Edge Conducted Spurious Emission	NA	References data from FCC ID AZ489FT7087 / ISED 109U-89FT7087	NA	NA
15.247 (d)	RSS-247 5.5	Conducted Spurious Emission	NA	References data from FCC ID AZ489FT7087 / ISED 109U-89FT7087	NA	NA
15.205, 15.209, 15.247 (d)	RSS-247 5.5	Radiated Emission within Restricted Bands	Pass	Worst case emission: RBE: 45.8451dBuV/m, margin: 8.1549dB, noise floor RSE: 61.0948dBuV/m, margin 12.9052dB, noise floor	755TXV0017	Nazrin&Qawiman
15.207	RSS-Gen 8.8	AC Powerline Conducted Emission	NA	Testing is not required, radio shall turn off during charging mode	NA	NA
15.203	-	Antenna Requirement	NA	Internal antenna is not accessible to the end-user	NA	NA

NA： Not Available

***NOTE: The BT chipset is identical to FCC ID AZ489FT7087 / ISED 109U-89FT7087. The rest of conducted measurements are by similarity. Only worst case configuration of radiated emission based on FCC ID AZ489FT7087 / ISED 109U-89FT7087 is tested. As per KDB 484596 D01v01, the applicant takes full responsibility that data referenced represents compliance to the relevant rules for this current FCC ID.**

3.0. Measurement Uncertainty

Measurement	Frequency	Expended Uncertainty (k=1.96) (±)
AC Power Line Conducted Spurious Emission	150kHz ~ 30MHz	3.48 dB
Radiated Emissions up to 1 GHz (Field Strength)	30MHz ~ 1000MHz	5.88 dB
Radiated Emissions above 1 GHz (Field Strength)	1GHz ~ 18GHz	5.84 dB
	18GHz ~ 40GHz	6.02 dB
Radiated Emissions (ERP)	30MHz ~ 18GHz	4.03 dB
Conducted Spurious Emissions	9kHz ~ 12.75GHz	2.82 dB

4.0. Equipment List

Bluetooth ATE # 1 (SW Version: Ate Main_3.1.11)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
POWER SUPPLY	6652A	3640A02941	22-Jan-21	22-Jan-22
SPECTRUM ANALYZER	E4440A	US45303111	14-Jul-21	14-Jul-22
CHAMBER	SH-641	92003820	14-Jul-21	14-Jul-22
N to N RF Cable # 1	SF126/11N/11N	NA	NA	NA

Radiated Emission Station (SW Version: EMC FCC RE v1.6.2)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
DRG HORN FREQ.	SAS-571	720	06-Apr-21	06-Apr-23
DRG HORN FREQ.	SAS-571	719	13-Sep-21	13-Sep-22
POWER SUPPLY	N7976A	MY53410110	24-May-21	24-May-22
SIGNAL GENERATOR	SMB 100A	182511	4-Jun-21	4-Jun-24
EMI TEST RECEIVER	ESW44	101750	15-Jan-21	15-Jan-22
EMI TEST RECEIVER	ESIB26	827769/009	11-Mar-21	11-Mar-22
5m SEMI-ANECHOIC CHAMBER	S800-HX	J2308	Not Required	Not Required
BILOG ANTENNA	CBL6112D	55546	06-Jun-21	06-Jun-22
BILOG ANTENNA	CBL6112B	2964	4-May-21	4-May-22
HYGRO-THERMOMETER	SDL500	A.016800	18-May-21	18-May-22
SYSTEM CONTROLLER	SC104V	050806-1	Not Required	Not Required
TURNTABLE FLUSH MOUNT 2M	FM2011	NA	Not Required	Not Required
ANTENNA POSITIONING TOWER	TLT2	NA	Not Required	Not Required
BROAD-BAND HORN ANTENNA	BBHA9170	BBHA9170255	4-Feb-21	4-Feb-22
AMPLIFIER	JS44-18004000-33-8P	2034566	12-June-19	12-June-22
PREAMPLIFIER	PAM-0118P	361	11-Sep-20	11-Sep-23
LOOP ANTENNA	6502	00203479	5-Feb-21	5-Feb-22

5.0. Test Mode Applicability and Test Channel Detail

Radiated Emission Test (Above 1GHz)

☒Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK	23.3°C, 69.5%RH

Radiated Emission Test (Below 1GHz)

☒Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK	23.3°C, 69.5%RH

Power Line Conducted Emission Test

☐Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☐Following channel(s) was (were) selected for the final test as listed below.

NAEUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Application Mode	0 to 78	AUTO	FHSS	AUTO	NA

Antenna Port Conducted Measurement:

☒This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Environmental Conditions
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK	26.9°C, 53.5%RH

6.0. Transmitter Test Parameters

6.1. Conducted RF Output Power (Peak)

6.1.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
   a. RBW = > 20 dB bandwidth
   b. VBW = RBW
   c. Detector mode = Peak
   d. AMPLITUDE → Scale/Div = 10 dB
   e. Trace = Max hold
   f. Sweep = auto
e) Measure the captured power within the band and recording the plot.
f) Repeat above procedure with other different mode of operation.

6.1.2. Test Limits:

Normal Condition (25 ° C)
≤ 125mW (or 20.9dBm)

6.1.3. Test Data:

Test Conditions			Results	
Modulation	Voltage(V)	Test Frequency(GHz)	dBm	Status
GFSK	7.50	2.4020	9.153	Pass
		2.4410	8.954	Pass
		2.4800	8.691	Pass
Pi/4 DQPSK	7.50	2.4020	6.906	Pass
		2.4410	6.772	Pass
		2.4800	6.512	Pass
8DPSK	7.50	2.4020	7.214	Pass
		2.4410	7.083	Pass
		2.4800	6.833	Pass

The Conducted RF Output Power test with result at low frequency, GFSK.



The Conducted RF Output Power test with result at mid frequency, GFSK.



The Conducted RF Output Power test with result at high frequency, GFSK.



The Conducted RF Output Power test with result at low frequency, Pi/4 DQPSK.



The Conducted RF Output Power test with result at mid frequency, Pi/4 DQPSK.



The Conducted RF Output Power test with result at high frequency, Pi/4 DQPSK.



The Conducted RF Output Power test with result at low frequency, 8DPSK.



The Conducted RF Output Power test with result at mid frequency, 8DPSK.



The Conducted RF Output Power test with result at high frequency, 8DPSK.



6.2. 20dB Channel Bandwidth

6.2.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
    a. RBW = 30 kHz
    b. VBW = 100 kHz
    c. SPAN = 3 MHz, center on test frequency
    d. AMPLITUDE → Scale/Div = 10 dB
    e. Detector mode = Peak
    f. Trace = Max hold
    g. Sweep = auto
e) Measure the freq different of two frequencies that were attenuated 20dB from peak of the emission & record the frequency difference as the emission bandwidth.
f) Save the plot result from spectrum analyzer screen.
g) Repeat above procedure with other different mode of operation.

6.2.2. Test Limits:

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

6.2.3. Test Data:

NA

6.3. Band-edge Conducted Spurious Emission

6.3.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and keep the EUT in hopping mode.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
    a. RBW = 100 kHz
    b. VBW = 300 kHz
    c. SPAN = 4 MHz (Low channel) or 6MHz(High Channel)
    d. Detector mode = Peak
    e. AMPLITUDE → Scale/Div = 10 dB
    f. Trace = Max hold
    g. Sweep = auto
e) Measure the captured band edge emission result and recording the plot.
f) Repeat above on EUT with hopping disable.
g) Repeat above procedure with other different test frequency.

6.3.2. Test Limits

Normal Condition (25 º C)
Shall be at least 20 dB below the peak power.

6.3.3. Test Result

NA

6.4. Dwell time on each channel

6.4.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and keep the EUT in hopping mode.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
    a. RBW = 100 kHz
    b. VBW = 300 kHz
    c. SPAN = Zero SPAN, center on hopping frequency
    d. Detector mode = Peak
    e. Trace = Max hold
    f. Sweep time = 5second
    g. Sweep = Single
e) Measure total numbers of transmissions occur in 5 second and save the plot.
f) Change the setting of spectrum analyzer :
    a. RBW = 100 kHz
    b. VBW = 300 kHz
    c. Sweep time = sufficient to capture dwell time for 1 transmission
    d. Sweep = Single
g) Measure dwell time for 1 transmission and save the plot.
h) Calculate accumulate dwell time in a given period equal to number of hopping frequencies x 0.4
i) Repeat above procedure with other different mode of operation.

6.4.2. Test Limits:

Normal Condition (25 º C)
≤ 400ms

6.4.3. Test Result

NA

6.5. Number of hopping Frequency

6.5.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and keep the EUT in hopping mode.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
    a. RBW = 300 kHz
    b. VBW = 300 kHz
    c. Detector mode = Peak
    d. Trace = Max hold
e) Allow the trace to stabilized & save the plot result from spectrum analyzer screen.
f) Count number of channel frequency in the operating.
g) Repeat above procedure for other test frequency.

6.5.2. Test Limits:

Normal Condition (25 º C)
≥ 15

6.5.3. Test Result

NA

6.6. Channel Separation

6.6.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and keep the EUT in hopping mode.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
    a. RBW = 300 kHz
    b. VBW = 300 kHz
    c. SPAN = 3 MHz, center on test frequency
    d. AMPLITUDE → Scale/Div = 5 dB
    e. Detector mode = Peak
    f. Trace = Max hold
    g. Sweep = auto
e) Measure the frequency different of these two adjacent channels with marker delta function & record the measurement results.
f) Repeat above procedure with other different mode of operation.

6.6.2. Test Limits:

Normal Condition (25 º C)
≥ 2/3 of 20dB Bandwidth

6.6.3. Test Result

NA

6.7. Conducted Spurious Emission

6.7.1. Test Setup



a) Check and ensure the spectrum analyzer well calibrate.
b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
d) Setting of Spectrum analyzer :
    a. RBW = 100 kHz
    b. VBW = 300 kHz
    c. SPAN = Cover until 10th harmonic
    d. Detector mode = Peak
    e. AMPLITUDE → Scale/Div = 10 dB
    f. Trace = Max hold
    g. Sweep = auto
e) Measure the captured spurious emission result and recording the plot.
f) Repeat above procedure with other different mode of operation.

6.7.2. Test Limits:

Normal Condition (25 º C)
Shall be at least 20 dB below for peak power.

6.7.3. Test Data:

NA

6.8. Radiated Emission within restricted Bands

6.8.1. Test Setup



a. The EUT is placed on the top of a rotating table 0.8m (<1GHz) or 1.5m (>1GHz) above the ground at a 3m semi-anechoic chamber. The table is rotated 360 degrees to determine the position of the highest radiation.
b. The EUT is set 3m away from the interference-receiving antenna, which is mounted on the top of a variable-height antenna tower.
c. The antenna is Bilog/Horn antenna depend on which frequency range uses, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT is arranged to its worst case and then the antenna is tuned to heights from 1m to 4m and the rotatable table is turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system is set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode is fall within the range of 10dB from the limit specified, the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. Otherwise, the testing could be stopped and the peak values of the EUT would be reported.

NOTE:

a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1GHz.
b. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
c. All modes of operation were investigated and the worst-case emissions are reported.

6.8.2. Test Limits:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

NOTE:

a. The lower limit shall apply at the transition frequencies.
b. Emission level (dBuV/m) = 20 log Emission level (uV/m).
c. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

6.8.3. Test Data:

Test: Bluetooth SAC Restricted Band Edge
Model Number: H98QDH9PW7BN S/N: 755TXV0017 EMC SR ID#: 03195-EMC-00126
Battery: PMNN4494A Accessory: FAF5259A
Test Channel: High Test Frequency: 2480.0000 MHz Test Standard: ANSI C63.10-2013 Worst Case Plane: X-Plane (GFSK)

Restricted Band Edge (High Channel) tabular data

Vertical Radiated Emission Result										
Spur Freq (MHz)	Spur level QPK (dBµV/m)	Spur level PK (dBµV/m)	Spur level AV (dBµV/m)	Limit QPK (dBµV/m)	Limit PK (dBµV/m)	Limit AV (dBµV/m)	Margin QPK (dBµV/m)	Margin PK (dBµV/m)	Margin AV (dBµV/m)	Carrier PK Power (dBµV/m)
2483.5000	-	55.1292	45.1498	-	74.0000	54.0000	-	-18.8708	-8.8502	-
Horizontal Radiated Emission Result										
2483.5000	-	56.4237	45.8451	-	74.0000	54.0000	-	-17.5763	-8.1549	-

Remarks: Pass Result	Marginal Result	Fail Result

Temperature (degC): 23.7 **Humidity (%): 70.1**
Test Performed by: Nazrin&Qawiman **Test Date: Tue, 9 Nov, 2021**
System MU: 5.84 dB

Restricted Band Edge (High Channel, Vertical, Peak) graphical screen shot



04:41:34 09.11.2021

Restricted Band Edge (High Channel, Horizontal, Peak) graphical screen shot



04:45:28 09.11.2021

Restricted Band Edge (High Channel, Vertical, Average) graphical screen shot



04:51:33 09.11.2021

Restricted Band Edge (High Channel, Horizontal, Average) graphical screen shot



04:55:21 09.11.2021

Test: Bluetooth SAC Transmitter Radiated Emission
Model#: H98QDH9PW7BN S/N: 755TXV0018 EMC SR ID#: 03195-EMC-00126
Battery: PMNN4494A Accessory: FAF5259A
Test Channel: Low Test Frequency: 2402.0000 MHz Test Standard: ANSI C63.10-2013
Worst Case Plane: X-Plane (GFSK)

Radiated Emission (Low Channel) tabular data

Vertical Radiated Emission Result										
Spur Freq (MHz)	Spur level QPK (dBµV/m)	Spur level PK (dBµV/m)	Spur level AV (dBµV/m)	Limit QPK (dBµV/m)	Limit PK (dBµV/m)	Limit AV (dBµV/m)	Margin QPK (dBµV/m)	Margin PK (dBµV/m)	Margin AV (dBµV/m)	Carrier PK Power (dBµV/m)
4804	-	48.7703**	-	-	74.0	-	-	25.2297	-	-
7206	-	53.4420**	-	-	77.0604	-	-	23.6184	-	107.0604
9608	-	55.4380**	-	-	77.0604	-	-	21.6224	-	107.0604
12010	-	61.0948**	38.5948**	-	74.0	54.0	-	12.9052	15.4052	-
14412	-	61.4617**	-	-	77.0604	-	-	15.5987	-	107.0604
16814	-	63.5036**	-	-	77.0604	-	-	13.5568	-	107.0604
19216	-	34.6700**	-	-	74.0	-	-	39.3300	-	-
21618	-	35.5268**	-	-	77.0604	-	-	41.5336	-	107.0604
24020	-	35.9154**	-	-	77.0604	-	-	41.1450	-	107.0604
Horizontal Radiated Emission Result										
4804	-	49.2173**	-	-	74.0	-	-	24.7827	-	-
7206	-	54.8589**	-	-	77.0604	-	-	22.2015	-	107.0604
9608	-	57.3163**	-	-	77.0604	-	-	19.6991	-	107.0604
12010	-	60.4512**	37.9512**	-	74.0	54.0	-	13.5488	16.0488	-
14412	-	61.9895**	-	-	77.0604	-	-	15.0709	-	107.0604
16814	-	62.5850**	-	-	77.0604	-	-	14.4754	-	107.0604
19216	-	34.0046**	-	-	74.0	-	-	39.9954	-	-
21618	-	37.5275**	-	-	77.0604	-	-	39.5329	-	107.0604
24020	-	35.9744**	-	-	77.0604	-	-	41.0860	-	107.0604

Remarks: Pass Result	Marginal Result	Fail Result

Temperature (degC): 23.7 Humidity (%): 70.1
Test Performed by: Nazrin&Qawiman Test Date: Tue, 9 Nov, 2021
System MU: 5.88 dB (30-1000MHz), 5.84 dB (1000-18000MHz), 6.02 dB (18000MHz-40000MHz)

Remarks: ** Indicates the spurious emission could not be detected due to noise limitations or ambient.
***Pursuant to CFR 47 Part 2.1057 (c), emissions attenuated more than 20 dB below the permissible limit are not reported.**

VERTICAL, QPK



HORIZONTAL, QPK



VERTICAL, PK



HORIZONTAL, PK







NOTE:
Transmitter Duty Cycle Calculation, FCC Rule 15.35 (b,c)

Based on the Bluetooth Specification Version 2.1+EDR, and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)
Adjusted channel hop rate for DH5 mode = 133.33 hops/second
Time per channel hop = 1 / 133.33 hops/second = 7.5 ms
Time to cycle through all channels = 7.5 x 20 channels = 150 ms
Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)
Worst case dwell time = 7.5 ms
Duty cycle connection factor = $20\log_{10}$ (7.5ms / 100ms) = **-22.5 dB**

6.9. AC Powerline Conducted Emission

6.9.1. Test Setup



1) Tests were conducted for both Receive and Transmit Mode of the EUT.
2) The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50uH of coupling impedance for the measuring instrument.
3) Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
4) The frequency range from 150 kHz to 30MHz was measured.

6.9.2. Test Limits:

For AC Power Line Conducted Test Limit can be Class A or B depends on product classification.

Limits for conducted disturbance at the mains ports of class A ITE

Frequency range MHz	Limits dB(µV)	
	Quasi-peak	Average
0,15 to 0,50	79	66
0,50 to 30	73	60
NOTE The lower limit shall apply at the transition frequency.		

Table 1: Limits for Conducted Disturbance at the Mains Ports of Class A ITE.

Limits for conducted disturbance at the mains ports of class B ITE

Frequency range MHz	Limits dB(µV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50
NOTE 1 The lower limit shall apply at the transition frequencies. NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

Table 2: Limits for Conducted Disturbance at the Mains Ports of Class B ITE

6.9.3. Test Result

Not Applicable. Testing is not required, radio shall turn off during charging mode

END OF TEST REPORT