

## Partial FCC Test Report

**Report No.:** RF190104C22

**FCC ID:** AZ489FT7119

**Test Model:** H55TGT9PW8AN

**Received Date:** Jan. 04, 2019

**Test Date:** Jan. 08 ~ Jan. 19, 2019

**Issued Date:** Jan. 29, 2019

**Applicant:** Motorola Solutions, Inc.

**Address:** 8000 West Sunrise Boulevard, Fort Lauderdale, Florida 33322

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /** 788550 / TW0003  
**Designation Number:**



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                              | <b>3</b>  |
| <b>1 Certificate of Conformity.....</b>                          | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                           | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                                | 5         |
| 2.2 Modification Record .....                                    | 5         |
| <b>3 General Information.....</b>                                | <b>6</b>  |
| 3.1 General Description of EUT .....                             | 6         |
| 3.2 Description of Test Modes .....                              | 7         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....     | 8         |
| 3.3 Description of Support Units .....                           | 9         |
| 3.3.1 Configuration of System under Test .....                   | 9         |
| 3.4 General Description of Applied Standards .....               | 10        |
| <b>4 Test Types and Results .....</b>                            | <b>11</b> |
| 4.1 Radiated Emission and Bandedge Measurement.....              | 11        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement ..... | 11        |
| 4.1.2 Test Instruments .....                                     | 12        |
| 4.1.3 Test Procedures.....                                       | 13        |
| 4.1.4 Deviation from Test Standard .....                         | 13        |
| 4.1.5 Test Setup.....                                            | 14        |
| 4.1.6 EUT Operating Conditions.....                              | 15        |
| 4.1.7 Test Results .....                                         | 16        |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>34</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b>  | <b>35</b> |

### Release Control Record

| Issue No.   | Description      | Date Issued   |
|-------------|------------------|---------------|
| RF190104C22 | Original release | Jan. 29, 2019 |

## 1 Certificate of Conformity

**Product:** Portable Radio

**Brand:** Motorola Solutions

**Test Model:** H55TGT9PW8AN


**Sample Status:** Engineering sample

**Applicant:** Motorola Solutions, Inc.

**Test Date:** Jan. 08 ~ Jan. 19, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** , **Date:** Jan. 29, 2019  
Polly Chien / Specialist

**Approved by :** , **Date:** Jan. 29, 2019  
Bruce Chen / Project Engineer

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) |                                              |        |                                                                                   |
|------------------------------------------------|----------------------------------------------|--------|-----------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                    | Result | Remarks                                                                           |
| 15.205 /<br>15.209 /<br>15.247(d)              | Radiated Emissions and Band Edge Measurement | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -1.6dB at 2483.50MHz. |

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency        | Expanded Uncertainty (k=2) ( $\pm$ ) |
|--------------------------------|------------------|--------------------------------------|
| Radiated Emissions up to 1 GHz | 30MHz ~ 200MHz   | 3.59 dB                              |
|                                | 200MHz ~ 1000MHz | 3.60 dB                              |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz     | 2.29 dB                              |
|                                | 18GHz ~ 40GHz    | 2.29 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------|
| Product               | Portable Radio                                                                                           |
| Brand                 | Motorola Solutions                                                                                       |
| Test Model            | H55TGT9PW8AN                                                                                             |
| Sample Status         | Engineering sample                                                                                       |
| Power Supply Rating   | 14.5Vdc (Single Unit Charger)<br>12Vdc (Multi-unit Charger)<br>5Vdc (host equipment)<br>7.4Vdc (Battery) |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM                                          |
| Modulation Technology | DSSS, OFDM                                                                                               |
| Transfer Rate         | 802.11b: 11/5.5/2/1Mbps<br>802.11g: 54/48/36/24/18/12/9/6Mbps<br>802.11n: up to 150Mbps                  |
| Operating Frequency   | 2412 ~ 2462MHz                                                                                           |
| Number of Channel     | 802.11b, 802.11g, 802.11n (HT20): 11<br>802.11n (HT40): 7                                                |
| Antenna Type          | Refer to Note                                                                                            |
| Antenna Connector     | NA                                                                                                       |
| Accessory Device      | Refer to Note                                                                                            |
| Cable Supplied        | Refer to Note                                                                                            |

Note:

- The EUT provides 1 completed transmitter and 1 receiver.

| Modulation Mode | TX Function |
|-----------------|-------------|
| 802.11b         | 1TX         |
| 802.11g         | 1TX         |
| 802.11n (HT20)  | 1TX         |
| 802.11n (HT40)  | 1TX         |

- The EUT with follow antennas gain is listed as table below.

| Type          | Connector | Gain(dBi) |         |         |         |         |         |
|---------------|-----------|-----------|---------|---------|---------|---------|---------|
|               |           | 2400MHz   | 2440MHz | 2480MHz | 5150MHz | 5550MHz | 5850MHz |
| Stamped metal | NA        | 3.1       | 3.2     | 2.9     | 2.8     | 4.0     | 1.9     |

3. The EUT uses following devices.

| Item                 | Brand    | Model                                                | Specification                                                                               | Remark    |
|----------------------|----------|------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------|
| Single Unit Charger  | MOTOROLA | NNTN8845A (Charger Base) +PS000040A01 (Power Supply) | Input: 110-120Vac, ~60Hz, 1A<br>Output: 14.5Vdc, 2.5A<br>1.5m DC cable with 1 core attached | Accessory |
| Standard Cap Battery | MOTOROLA | NNTN9087A                                            | BATTERY PACK, IMPRES GEN2, LIION, IP68, 3800T<br>Rating: 7.4Vdc                             | Accessory |
| Hi-Cap Battery       | MOTOROLA | NNTN9089A                                            | BATTERY PACK, IMPRES GEN2, LIION, IP68, 5650T<br>Rating: 7.4Vdc                             | Accessory |
| Multi-unit Charger   | MOTOROLA | NNTN9115A (Charger Base) + 3087791G01 (Linecord)     | Input: 100-240Vac, 50/60Hz, 3A<br>Output: 12Vdc, 3A<br>2.2m DC cable without core attached  | Accessory |

4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |       | Description                  |
|--------------------|---------------|-------|------------------------------|
|                    | RE $\geq$ 1G  | RE<1G |                              |
| A                  | √             | √     | EUT with Notebook            |
| B                  | -             | √     | EUT with single unit charger |
| C                  | -             | √     | EUT with multi-unit charger  |

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement RE<1G: Radiated Emission below 1GHz

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.
2. "-" means no effect.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode           | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| A                  | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              |
| A                  | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              |
| A                  | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              |
| A                  | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode    | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|--------------------|---------|-------------------|----------------|-----------------------|-----------------|------------------|
| A, B, C            | 802.11g | 1 to 11           | 6              | OFDM                  | BPSK            | 6.0              |

#### Test Condition:

| Applicable to | Environmental Conditions | Input Power  | Tested by |
|---------------|--------------------------|--------------|-----------|
| RE $\geq$ 1G  | 20 deg. C, 69% RH        | 120Vac, 60Hz | Tim Chen  |
| RE<1G         | 22 deg. C, 68% RH        | 120Vac, 60Hz | Greg Lin  |

### 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product                 | Brand    | Model No. | Serial No. | FCC ID           | Remarks            |
|----|-------------------------|----------|-----------|------------|------------------|--------------------|
| A. | Notebook                | DELL     | E5420     | BPQ7MQ1    | FCC DoC Approved | -                  |
| B. | Battery                 | MOTOROLA | NNTN9087A | NA         | NA               | Accessory          |
| C. | Battery                 | MOTOROLA | NNTN9089A | NA         | NA               | Accessory          |
| D. | USB Resistive Load x2   | NA       | NA        | NA         | NA               | Provided by client |
| E. | USB Resistive Load x6   | NA       | NA        | NA         | NA               | Provided by client |
| F. | Fleet Management Module | NA       | NA        | NA         | NA               | Provided by client |


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as communication partner to transfer data.


| ID | Descriptions   | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks            |
|----|----------------|------|------------|--------------------|--------------|--------------------|
| 1. | USB Cable      | 1    | 1.5        | Y                  | 0            | -                  |
| 2. | USB Cable      | 2    | 1          | Y                  | 0            | -                  |
| 3. | Mini USB cable | 1    | 1          | Y                  | 0            | Provided by client |
| 4. | Cable          | 1    | 0.3        | N                  | 0            | Provided by client |

#### 3.3.1 Configuration of System under Test


Mode A



Mode B



Mode C



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**KDB 558074 D01 15.247 Meas Guidance v05r01**

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

| Frequencies<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490        | 2400/F(kHz)                          | 300                              |
| 0.490 ~ 1.705        | 24000/F(kHz)                         | 30                               |
| 1.705 ~ 30.0         | 30                                   | 30                               |
| 30 ~ 88              | 100                                  | 3                                |
| 88 ~ 216             | 150                                  | 3                                |
| 216 ~ 960            | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

| Description & Manufacturer               | Model No.                              | Serial No.                                          | Cal. Date     | Cal. Due      |
|------------------------------------------|----------------------------------------|-----------------------------------------------------|---------------|---------------|
| Test Receiver<br>KEYSIGHT                | N9038A                                 | MY55420137                                          | Apr. 11, 2018 | Apr. 10, 2019 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ     | FSP40                                  | 100269                                              | May 29, 2018  | May 28, 2019  |
| BILOG Antenna<br>SCHWARZBECK             | VULB9168                               | 9168-160                                            | Nov. 21, 2018 | Nov. 20, 2019 |
| HORN Antenna<br>SCHWARZBECK              | BBHA 9120 D                            | 9120D-1169                                          | Nov. 25, 2018 | Nov. 24, 2019 |
| HORN Antenna<br>SCHWARZBECK              | BBHA 9170                              | BBHA9170241                                         | Nov. 25, 2018 | Nov. 24, 2019 |
| Loop Antenna<br>TESEQ                    | HLA 6121                               | 45745                                               | Jun. 14, 2018 | Jun. 13, 2019 |
| Preamplifier<br>Agilent<br>(Below 1GHz)  | 8447D                                  | 2944A10638                                          | Aug. 08, 2018 | Aug. 07, 2019 |
| Preamplifier<br>Agilent<br>(Above 1GHz)  | 8449B                                  | 3008A02367                                          | Feb. 22, 2018 | Feb. 21, 2019 |
| RF signal cable<br>HUBER+SUHNER&EMCI     | SUCOFLEX 104 &<br>EMC104-SM-<br>SM8000 | CABLE-CH9-02<br>(248780+171006)                     | Jan. 15, 2018 | Jan. 14, 2019 |
|                                          |                                        |                                                     | Jan. 19, 2019 | Jan. 18, 2020 |
| RF signal cable<br>HUBER+SUHNER          | SUCOFLEX 104                           | CABLE-CH9-(250795/4)                                | Aug. 08, 2018 | Aug. 07, 2019 |
| RF signal cable<br>Woken                 | 8D-FB                                  | Cable-CH9-01                                        | Jul. 31, 2018 | Jul. 30, 2019 |
| Software<br>BV ADT                       | ADT_Radiated_<br>V7.6.15.9.5           | NA                                                  | NA            | NA            |
| Antenna Tower<br>EMCO                    | 2070/2080                              | 512.835.4684                                        | NA            | NA            |
| Turn Table<br>EMCO                       | 2087-2.03                              | NA                                                  | NA            | NA            |
| Antenna Tower & Turn<br>BV ADT           | AT100                                  | AT93021705                                          | NA            | NA            |
| Turn Table<br>BV ADT                     | TT100                                  | TT93021705                                          | NA            | NA            |
| Turn Table Controller<br>BV ADT          | SC100                                  | SC93021705                                          | NA            | NA            |
| Boresight Antenna Fixture                | FBA-01                                 | FBA-SIP01                                           | NA            | NA            |
| USB Wideband Power<br>Sensor<br>KEYSIGHT | U2021XA                                | MY55050005/MY5519000<br>4/MY55190007/MY55210<br>005 | Jul. 17, 2018 | Jul. 16, 2019 |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 9.  
3. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.  
4. The IC Site Registration No. is IC 7450F-9.

#### 4.1.3 Test Procedures

##### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10 Hz (Duty cycle  $\geq 98\%$ ) for Peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

##### Mode A

- Connected the EUT with the notebook.
- Set the EUT under transmission condition continuously at specific channel frequency.

##### Mode B

- Placed the EUT on the charger under charging.
- Set the EUT under transmission condition continuously at specific channel frequency.

##### Mode C

- Placed the EUT and batteries on the charger under charging.
- Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

Above 1GHz Data:

802.11b

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 55.1 PK                       | 74.0              | -18.9          | 1.51 H                   | 220                        | 23.1                   | 32.0                           |
| 2                                                   | 2390.00        | 42.2 AV                       | 54.0              | -11.8          | 1.51 H                   | 220                        | 10.2                   | 32.0                           |
| 3                                                   | *2412.00       | 109.1 PK                      |                   |                | 1.54 H                   | 222                        | 77.0                   | 32.1                           |
| 4                                                   | *2412.00       | 107.0 AV                      |                   |                | 1.54 H                   | 222                        | 74.9                   | 32.1                           |
| 5                                                   | 4824.00        | 43.4 PK                       | 74.0              | -30.6          | 1.56 H                   | 252                        | 42.3                   | 1.1                            |
| 6                                                   | 4824.00        | 32.3 AV                       | 54.0              | -21.7          | 1.56 H                   | 252                        | 31.2                   | 1.1                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.3 PK                       | 74.0              | -17.7          | 1.49 V                   | 120                        | 24.3                   | 32.0                           |
| 2                                                   | 2390.00        | 42.7 AV                       | 54.0              | -11.3          | 1.49 V                   | 120                        | 10.7                   | 32.0                           |
| 3                                                   | *2412.00       | 112.1 PK                      |                   |                | 1.45 V                   | 117                        | 80.0                   | 32.1                           |
| 4                                                   | *2412.00       | 110.0 AV                      |                   |                | 1.45 V                   | 117                        | 77.9                   | 32.1                           |
| 5                                                   | 4824.00        | 45.3 PK                       | 74.0              | -28.7          | 1.42 V                   | 127                        | 44.2                   | 1.1                            |
| 6                                                   | 4824.00        | 37.6 AV                       | 54.0              | -16.4          | 1.42 V                   | 127                        | 36.5                   | 1.1                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 107.7 PK                      |                   |                | 1.58 H                   | 224                        | 75.7                   | 32.0                           |
| 2                                                   | *2437.00       | 105.2 AV                      |                   |                | 1.58 H                   | 224                        | 73.2                   | 32.0                           |
| 3                                                   | 4874.00        | 44.7 PK                       | 74.0              | -29.3          | 1.61 H                   | 225                        | 43.4                   | 1.3                            |
| 4                                                   | 4874.00        | 38.9 AV                       | 54.0              | -15.1          | 1.61 H                   | 225                        | 37.6                   | 1.3                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 107.8 PK                      |                   |                | 1.59 V                   | 123                        | 75.8                   | 32.0                           |
| 2                                                   | *2437.00       | 105.0 AV                      |                   |                | 1.59 V                   | 123                        | 73.0                   | 32.0                           |
| 3                                                   | 4874.00        | 45.2 PK                       | 74.0              | -28.8          | 1.60 V                   | 119                        | 43.9                   | 1.3                            |
| 4                                                   | 4874.00        | 38.5 AV                       | 54.0              | -15.5          | 1.60 V                   | 119                        | 37.2                   | 1.3                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 108.3 PK                      |                   |                | 1.53 H                   | 218                        | 76.3                   | 32.0                           |
| 2                                                   | *2462.00       | 106.1 AV                      |                   |                | 1.53 H                   | 218                        | 74.1                   | 32.0                           |
| 3                                                   | 2483.50        | 55.9 PK                       | 74.0              | -18.1          | 1.57 H                   | 221                        | 23.9                   | 32.0                           |
| 4                                                   | 2483.50        | 42.7 AV                       | 54.0              | -11.3          | 1.57 H                   | 221                        | 10.7                   | 32.0                           |
| 5                                                   | 4924.00        | 43.6 PK                       | 74.0              | -30.4          | 1.60 H                   | 248                        | 42.1                   | 1.5                            |
| 6                                                   | 4924.00        | 36.7 AV                       | 54.0              | -17.3          | 1.60 H                   | 248                        | 35.2                   | 1.5                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 110.4 PK                      |                   |                | 1.52 V                   | 115                        | 78.4                   | 32.0                           |
| 2                                                   | *2462.00       | 108.1 AV                      |                   |                | 1.52 V                   | 115                        | 76.1                   | 32.0                           |
| 3                                                   | 2483.50        | 55.6 PK                       | 74.0              | -18.4          | 1.58 V                   | 121                        | 23.6                   | 32.0                           |
| 4                                                   | 2483.50        | 42.9 AV                       | 54.0              | -11.1          | 1.58 V                   | 121                        | 10.9                   | 32.0                           |
| 5                                                   | 4924.00        | 44.3 PK                       | 74.0              | -29.7          | 1.55 V                   | 119                        | 42.8                   | 1.5                            |
| 6                                                   | 4924.00        | 37.2 AV                       | 54.0              | -16.8          | 1.55 V                   | 119                        | 35.7                   | 1.5                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 54.8 PK                       | 74.0              | -19.2          | 1.56 H                   | 224                        | 22.8                   | 32.0                           |
| 2                                                   | 2390.00        | 42.2 AV                       | 54.0              | -11.8          | 1.56 H                   | 224                        | 10.2                   | 32.0                           |
| 3                                                   | *2412.00       | 104.7 PK                      |                   |                | 1.54 H                   | 222                        | 72.6                   | 32.1                           |
| 4                                                   | *2412.00       | 94.3 AV                       |                   |                | 1.54 H                   | 222                        | 62.2                   | 32.1                           |
| 5                                                   | 4824.00        | 42.7 PK                       | 74.0              | -31.3          | 1.58 H                   | 217                        | 41.6                   | 1.1                            |
| 6                                                   | 4824.00        | 32.5 AV                       | 54.0              | -21.5          | 1.58 H                   | 217                        | 31.4                   | 1.1                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 55.7 PK                       | 74.0              | -18.3          | 1.00 V                   | 77                         | 23.7                   | 32.0                           |
| 2                                                   | 2390.00        | 41.8 AV                       | 54.0              | -12.2          | 1.00 V                   | 77                         | 9.8                    | 32.0                           |
| 3                                                   | *2412.00       | 105.5 PK                      |                   |                | 1.00 V                   | 75                         | 73.4                   | 32.1                           |
| 4                                                   | *2412.00       | 94.8 AV                       |                   |                | 1.00 V                   | 75                         | 62.7                   | 32.1                           |
| 5                                                   | 4824.00        | 44.7 PK                       | 74.0              | -29.3          | 1.00 V                   | 71                         | 43.6                   | 1.1                            |
| 6                                                   | 4824.00        | 36.2 AV                       | 54.0              | -17.8          | 1.00 V                   | 71                         | 35.1                   | 1.1                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 110.1 PK                      |                   |                | 1.37 H                   | 221                        | 78.1                   | 32.0                           |
| 2                                                   | *2437.00       | 99.9 AV                       |                   |                | 1.37 H                   | 221                        | 67.9                   | 32.0                           |
| 3                                                   | 4874.00        | 43.8 PK                       | 74.0              | -30.2          | 1.40 H                   | 220                        | 42.5                   | 1.3                            |
| 4                                                   | 4874.00        | 38.4 AV                       | 54.0              | -15.6          | 1.40 H                   | 220                        | 37.1                   | 1.3                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 113.0 PK                      |                   |                | 1.00 V                   | 80                         | 81.0                   | 32.0                           |
| 2                                                   | *2437.00       | 102.6 AV                      |                   |                | 1.00 V                   | 80                         | 70.6                   | 32.0                           |
| 3                                                   | 4874.00        | 43.9 PK                       | 74.0              | -30.1          | 1.00 V                   | 72                         | 42.6                   | 1.3                            |
| 4                                                   | 4874.00        | 37.4 AV                       | 54.0              | -16.6          | 1.00 V                   | 72                         | 36.1                   | 1.3                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz)    | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2462.00       | 110.4 PK                |                |             | 1.58 H             | 215                  | 78.4             | 32.0                     |
| 2                                                   | *2462.00       | 100.1 AV                |                |             | 1.58 H             | 215                  | 68.1             | 32.0                     |
| 3                                                   | 2483.50        | 65.2 PK                 | 74.0           | -8.8        | 1.47 H             | 217                  | 33.2             | 32.0                     |
| 4                                                   | 2483.50        | 51.2 AV                 | 54.0           | -2.8        | 1.47 H             | 217                  | 19.2             | 32.0                     |
| 5                                                   | 4924.00        | 42.3 PK                 | 74.0           | -31.7       | 1.45 H             | 211                  | 40.8             | 1.5                      |
| 6                                                   | 4924.00        | 28.8 AV                 | 54.0           | -25.2       | 1.45 H             | 211                  | 27.3             | 1.5                      |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz)    | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2462.00       | 111.6 PK                |                |             | 1.00 V             | 76                   | 79.6             | 32.0                     |
| 2                                                   | *2462.00       | 101.1 AV                |                |             | 1.00 V             | 76                   | 69.1             | 32.0                     |
| 3                                                   | 2483.50        | 67.6 PK                 | 74.0           | -6.4        | 1.00 V             | 78                   | 35.6             | 32.0                     |
| 4                                                   | <b>2483.50</b> | <b>52.4 AV</b>          | <b>54.0</b>    | <b>-1.6</b> | <b>1.00 V</b>      | <b>78</b>            | <b>20.4</b>      | <b>32.0</b>              |
| 5                                                   | 4924.00        | 42.9 PK                 | 74.0           | -31.1       | 1.00 V             | 81                   | 41.4             | 1.5                      |
| 6                                                   | 4924.00        | 29.8 AV                 | 54.0           | -24.2       | 1.00 V             | 81                   | 28.3             | 1.5                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.6 PK                       | 74.0              | -17.4          | 1.51 H                   | 224                        | 24.6                   | 32.0                           |
| 2                                                   | 2390.00        | 44.6 AV                       | 54.0              | -9.4           | 1.51 H                   | 224                        | 12.6                   | 32.0                           |
| 3                                                   | *2412.00       | 105.1 PK                      |                   |                | 1.54 H                   | 220                        | 73.0                   | 32.1                           |
| 4                                                   | *2412.00       | 93.6 AV                       |                   |                | 1.54 H                   | 220                        | 61.5                   | 32.1                           |
| 5                                                   | 4824.00        | 42.7 PK                       | 74.0              | -31.3          | 1.55 H                   | 224                        | 41.6                   | 1.1                            |
| 6                                                   | 4824.00        | 29.2 AV                       | 54.0              | -24.8          | 1.55 H                   | 224                        | 28.1                   | 1.1                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.8 PK                       | 74.0              | -17.2          | 1.00 V                   | 78                         | 24.8                   | 32.0                           |
| 2                                                   | 2390.00        | 44.8 AV                       | 54.0              | -9.2           | 1.00 V                   | 78                         | 12.8                   | 32.0                           |
| 3                                                   | *2412.00       | 105.4 PK                      |                   |                | 1.00 V                   | 76                         | 73.3                   | 32.1                           |
| 4                                                   | *2412.00       | 94.0 AV                       |                   |                | 1.00 V                   | 76                         | 61.9                   | 32.1                           |
| 5                                                   | 4824.00        | 42.0 PK                       | 74.0              | -32.0          | 1.00 V                   | 81                         | 40.9                   | 1.1                            |
| 6                                                   | 4824.00        | 29.0 AV                       | 54.0              | -25.0          | 1.00 V                   | 81                         | 27.9                   | 1.1                            |

## Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 110.8 PK                      |                   |                | 1.43 H                   | 222                        | 78.8                   | 32.0                           |
| 2                                                   | *2437.00       | 99.5 AV                       |                   |                | 1.43 H                   | 222                        | 67.5                   | 32.0                           |
| 3                                                   | 4874.00        | 42.4 PK                       | 74.0              | -31.6          | 1.46 H                   | 226                        | 41.1                   | 1.3                            |
| 4                                                   | 4874.00        | 28.9 AV                       | 54.0              | -25.1          | 1.46 H                   | 226                        | 27.6                   | 1.3                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 113.5 PK                      |                   |                | 1.00 V                   | 207                        | 81.5                   | 32.0                           |
| 2                                                   | *2437.00       | 101.8 AV                      |                   |                | 1.00 V                   | 207                        | 69.8                   | 32.0                           |
| 3                                                   | 4874.00        | 41.8 PK                       | 74.0              | -32.2          | 1.00 V                   | 210                        | 40.5                   | 1.3                            |
| 4                                                   | 4874.00        | 28.7 AV                       | 54.0              | -25.3          | 1.00 V                   | 210                        | 27.4                   | 1.3                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2462.00    | 110.5 PK                |                |             | 1.51 H             | 221                  | 78.5             | 32.0                     |
| 2                                                   | *2462.00    | 99.0 AV                 |                |             | 1.51 H             | 221                  | 67.0             | 32.0                     |
| 3                                                   | 2483.50     | 65.2 PK                 | 74.0           | -8.8        | 1.47 H             | 215                  | 33.2             | 32.0                     |
| 4                                                   | 2483.50     | 51.0 AV                 | 54.0           | -3.0        | 1.47 H             | 215                  | 19.0             | 32.0                     |
| 5                                                   | 4924.00     | 43.2 PK                 | 74.0           | -30.8       | 1.52 H             | 219                  | 41.7             | 1.5                      |
| 6                                                   | 4924.00     | 29.6 AV                 | 54.0           | -24.4       | 1.52 H             | 219                  | 28.1             | 1.5                      |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2462.00    | 112.3 PK                |                |             | 1.00 V             | 197                  | 80.3             | 32.0                     |
| 2                                                   | *2462.00    | 100.9 AV                |                |             | 1.00 V             | 197                  | 68.9             | 32.0                     |
| 3                                                   | 2483.50     | 66.6 PK                 | 74.0           | -7.4        | 1.00 V             | 194                  | 34.6             | 32.0                     |
| 4                                                   | 2483.50     | 52.3 AV                 | 54.0           | -1.7        | 1.00 V             | 194                  | 20.3             | 32.0                     |
| 5                                                   | 4924.00     | 42.8 PK                 | 74.0           | -31.2       | 1.00 V             | 194                  | 41.3             | 1.5                      |
| 6                                                   | 4924.00     | 29.2 AV                 | 54.0           | -24.8       | 1.00 V             | 194                  | 27.7             | 1.5                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 59.1 PK                       | 74.0              | -14.9          | 1.45 H                   | 221                        | 27.1                   | 32.0                           |
| 2                                                   | 2390.00        | 47.4 AV                       | 54.0              | -6.6           | 1.45 H                   | 221                        | 15.4                   | 32.0                           |
| 3                                                   | *2422.00       | 105.4 PK                      |                   |                | 1.47 H                   | 227                        | 73.4                   | 32.0                           |
| 4                                                   | *2422.00       | 93.7 AV                       |                   |                | 1.47 H                   | 227                        | 61.7                   | 32.0                           |
| 5                                                   | 4844.00        | 44.0 PK                       | 74.0              | -30.0          | 1.50 H                   | 229                        | 42.7                   | 1.3                            |
| 6                                                   | 4844.00        | 28.9 AV                       | 54.0              | -25.1          | 1.50 H                   | 229                        | 27.6                   | 1.3                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 65.4 PK                       | 74.0              | -8.6           | 1.00 V                   | 180                        | 33.4                   | 32.0                           |
| 2                                                   | 2390.00        | 52.1 AV                       | 54.0              | -1.9           | 1.00 V                   | 180                        | 20.1                   | 32.0                           |
| 3                                                   | *2422.00       | 111.4 PK                      |                   |                | 1.10 V                   | 179                        | 79.4                   | 32.0                           |
| 4                                                   | *2422.00       | 99.6 AV                       |                   |                | 1.10 V                   | 179                        | 67.6                   | 32.0                           |
| 5                                                   | 4844.00        | 43.6 PK                       | 74.0              | -30.4          | 1.13 V                   | 177                        | 42.3                   | 1.3                            |
| 6                                                   | 4844.00        | 28.4 AV                       | 54.0              | -25.6          | 1.13 V                   | 177                        | 27.1                   | 1.3                            |

## Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 106.6 PK                      |                   |                | 1.36 H                   | 236                        | 74.6                   | 32.0                           |
| 2                                                   | *2437.00       | 94.9 AV                       |                   |                | 1.36 H                   | 236                        | 62.9                   | 32.0                           |
| 3                                                   | 2483.50        | 60.5 PK                       | 74.0              | -13.5          | 1.82 H                   | 228                        | 28.5                   | 32.0                           |
| 4                                                   | 2483.50        | 47.7 AV                       | 54.0              | -6.3           | 1.82 H                   | 228                        | 15.7                   | 32.0                           |
| 5                                                   | 4874.00        | 40.7 PK                       | 74.0              | -33.3          | 1.82 H                   | 228                        | 39.4                   | 1.3                            |
| 6                                                   | 4874.00        | 27.7 AV                       | 54.0              | -26.3          | 1.82 H                   | 228                        | 26.4                   | 1.3                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 111.3 PK                      |                   |                | 1.00 V                   | 178                        | 79.3                   | 32.0                           |
| 2                                                   | *2437.00       | 99.6 AV                       |                   |                | 1.00 V                   | 178                        | 67.6                   | 32.0                           |
| 3                                                   | 2483.50        | 65.5 PK                       | 74.0              | -8.5           | 1.00 V                   | 176                        | 33.5                   | 32.0                           |
| 4                                                   | 2483.50        | 51.4 AV                       | 54.0              | -2.6           | 1.00 V                   | 176                        | 19.4                   | 32.0                           |
| 5                                                   | 4874.00        | 41.9 PK                       | 74.0              | -32.1          | 1.00 V                   | 180                        | 40.6                   | 1.3                            |
| 6                                                   | 4874.00        | 28.4 AV                       | 54.0              | -25.6          | 1.00 V                   | 180                        | 27.1                   | 1.3                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 103.2 PK                      |                   |                | 1.63 H                   | 215                        | 71.2                   | 32.0                           |
| 2                                                   | *2452.00       | 91.7 AV                       |                   |                | 1.63 H                   | 215                        | 59.7                   | 32.0                           |
| 3                                                   | 2483.50        | 61.7 PK                       | 74.0              | -12.3          | 1.60 H                   | 217                        | 29.7                   | 32.0                           |
| 4                                                   | 2483.50        | 48.5 AV                       | 54.0              | -5.5           | 1.60 H                   | 217                        | 16.5                   | 32.0                           |
| 5                                                   | 4904.00        | 42.8 PK                       | 74.0              | -31.2          | 1.66 H                   | 220                        | 41.5                   | 1.3                            |
| 6                                                   | 4904.00        | 28.4 AV                       | 54.0              | -25.6          | 1.66 H                   | 220                        | 27.1                   | 1.3                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 109.2 PK                      |                   |                | 1.00 V                   | 178                        | 77.2                   | 32.0                           |
| 2                                                   | *2452.00       | 97.5 AV                       |                   |                | 1.00 V                   | 178                        | 65.5                   | 32.0                           |
| 3                                                   | 2483.50        | 65.5 PK                       | 74.0              | -8.5           | 1.00 V                   | 176                        | 33.5                   | 32.0                           |
| 4                                                   | 2483.50        | 52.2 AV                       | 54.0              | -1.8           | 1.00 V                   | 176                        | 20.2                   | 32.0                           |
| 5                                                   | 4904.00        | 43.4 PK                       | 74.0              | -30.6          | 1.00 V                   | 182                        | 42.1                   | 1.3                            |
| 6                                                   | 4904.00        | 28.5 AV                       | 54.0              | -25.5          | 1.00 V                   | 182                        | 27.2                   | 1.3                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

Below 1GHz worst-case data:


802.11g

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | A               |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 30.00       | 33.9 QP                 | 40.0           | -6.1        | 1.50 H             | 342                  | 45.1             | -11.2                    |
| 2                                                   | 106.63      | 25.4 QP                 | 43.5           | -18.1       | 1.25 H             | 88                   | 38.2             | -12.8                    |
| 3                                                   | 246.31      | 41.1 QP                 | 46.0           | -4.9        | 1.00 H             | 59                   | 50.9             | -9.8                     |
| 4                                                   | 331.67      | 30.3 QP                 | 46.0           | -15.7       | 1.50 H             | 50                   | 37.5             | -7.2                     |
| 5                                                   | 776.90      | 31.8 QP                 | 46.0           | -14.2       | 1.00 H             | 230                  | 30.3             | 1.5                      |
| 6                                                   | 942.77      | 33.8 QP                 | 46.0           | -12.2       | 1.50 H             | 232                  | 29.7             | 4.1                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | A               |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 32.91       | 37.7 QP                 | 40.0           | -2.3        | 1.50 V             | 164                  | 48.8             | -11.1                    |
| 2                                                 | 144.46      | 31.9 QP                 | 43.5           | -11.6       | 1.00 V             | 292                  | 41.5             | -9.6                     |
| 3                                                 | 255.04      | 33.2 QP                 | 46.0           | -12.8       | 1.00 V             | 50                   | 42.7             | -9.5                     |
| 4                                                 | 489.78      | 33.8 QP                 | 46.0           | -12.2       | 1.25 V             | 188                  | 38.5             | -4.7                     |
| 5                                                 | 759.44      | 30.8 QP                 | 46.0           | -15.2       | 1.00 V             | 43                   | 29.8             | 1.0                      |
| 6                                                 | 933.07      | 34.2 QP                 | 46.0           | -11.8       | 1.50 V             | 138                  | 30.3             | 3.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | B               |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 30.00       | 36.9 QP                 | 40.0           | -3.1        | 1.25 H             | 348                  | 48.1             | -11.2                    |
| 2                                                   | 63.95       | 19.1 QP                 | 40.0           | -20.9       | 1.00 H             | 280                  | 29.9             | -10.8                    |
| 3                                                   | 194.90      | 32.5 QP                 | 43.5           | -11.0       | 1.00 H             | 58                   | 44.1             | -11.6                    |
| 4                                                   | 443.22      | 25.0 QP                 | 46.0           | -21.0       | 1.25 H             | 143                  | 30.4             | -5.4                     |
| 5                                                   | 718.70      | 36.4 QP                 | 46.0           | -9.6        | 1.25 H             | 4                    | 36.6             | -0.2                     |
| 6                                                   | 932.10      | 39.6 QP                 | 46.0           | -6.4        | 1.50 H             | 338                  | 35.7             | 3.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | B               |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 30.00       | 33.3 QP                 | 40.0           | -6.7        | 1.00 V             | 184                  | 44.5             | -11.2                    |
| 2                                                 | 58.13       | 28.0 QP                 | 40.0           | -12.0       | 1.50 V             | 218                  | 38.3             | -10.3                    |
| 3                                                 | 154.16      | 19.6 QP                 | 43.5           | -23.9       | 1.25 V             | 145                  | 28.8             | -9.2                     |
| 4                                                 | 381.14      | 22.8 QP                 | 46.0           | -23.2       | 1.00 V             | 74                   | 29.4             | -6.6                     |
| 5                                                 | 638.19      | 28.0 QP                 | 46.0           | -18.0       | 1.00 V             | 121                  | 29.3             | -1.3                     |
| 6                                                 | 917.55      | 33.6 QP                 | 46.0           | -12.4       | 1.00 V             | 152                  | 29.9             | 3.7                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | C               |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 30.00       | 35.3 QP                 | 40.0           | -4.7        | 1.00 H             | 341                  | 46.5             | -11.2                    |
| 2                                                   | 107.60      | 29.4 QP                 | 43.5           | -14.1       | 1.50 H             | 29                   | 42.0             | -12.6                    |
| 3                                                   | 186.17      | 27.9 QP                 | 43.5           | -15.6       | 1.25 H             | 248                  | 39.1             | -11.2                    |
| 4                                                   | 245.34      | 23.9 QP                 | 46.0           | -22.1       | 1.25 H             | 37                   | 33.7             | -9.8                     |
| 5                                                   | 610.06      | 28.0 QP                 | 46.0           | -18.0       | 1.00 H             | 52                   | 30.1             | -2.1                     |
| 6                                                   | 951.50      | 33.6 QP                 | 46.0           | -12.4       | 1.25 H             | 6                    | 29.4             | 4.2                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | C               |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 30.00       | 37.9 QP                 | 40.0           | -2.1        | 1.25 V             | 178                  | 49.1             | -11.2                    |
| 2                                                 | 72.68       | 33.4 QP                 | 40.0           | -6.6        | 1.25 V             | 142                  | 45.8             | -12.4                    |
| 3                                                 | 122.15      | 28.5 QP                 | 43.5           | -15.0       | 1.00 V             | 333                  | 40.0             | -11.5                    |
| 4                                                 | 467.47      | 25.7 QP                 | 46.0           | -20.3       | 1.00 V             | 314                  | 30.7             | -5.0                     |
| 5                                                 | 744.89      | 30.1 QP                 | 46.0           | -15.9       | 1.50 V             | 18                   | 29.5             | 0.6                      |
| 6                                                 | 933.07      | 34.0 QP                 | 46.0           | -12.0       | 1.00 V             | 297                  | 30.1             | 3.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### **Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

### **Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

### **Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---