



CFR 47 FCC PART 15 SUBPART C
CERTIFICATION TEST REPORT

For

Mobile

PRODUCT MARKETING NAME: APX6500

MODEL NUMBER: M25URS9PW1BN

REPORT NUMBER: 4789278436.1-3

ISSUE DATE: January 07, 2020

Prepared for

Motorola Solutions (Malaysia) Sdn Bhd
Unit 1807-12 Two Harbourfront 22 Tak Fung St, Hung Hom Kowloon Hong Kong

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake
Hi-Tech Development Zone Dongguan, People's Republic of China
Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	01/07/2020	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Pass
Note: 1. only above test item were performed according to manufacturer's requirement. 2. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.			



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. TEST CHANNEL CONFIGURATION	8
5.3. TEST ENVIRONMENT	8
5.4. DESCRIPTION OF TEST SETUP	9
6. MEASURING INSTRUMENT AND SOFTWARE USED	10
7. RADIATED TEST RESULTS.....	11
7.1. RESTRICTED BANDEDGE	17
7.1.1. 802.11b MODE	17
7.1.2. 802.11g MODE	25
7.1.3. 802.11n HT20 MODE	33
7.2. SPURIOUS EMISSIONS (3~18GHz)	41
7.2.1. 802.11b MODE	41
7.2.2. 802.11g MODE	47
7.2.3. 802.11n HT20 MODE	53
7.3. SPURIOUS EMISSIONS (1~3GHz)	59
7.3.1. 802.11b MODE	59
7.3.2. 802.11g MODE	65
7.3.3. 802.11n HT20 MODE	71
7.4. SPURIOUS EMISSIONS 18G ~ 26GHz	77
7.4.1. 802.11b MODE	77
7.5. SPURIOUS EMISSIONS 30M ~ 1 GHz	79
7.5.1. 802.11b MODE	79
7.6. SPURIOUS EMISSIONS BELOW 30M	81
7.6.1. 802.11b MODE	81



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Motorola Solutions (Malaysia) Sdn Bhd
Address: Unit 1807-12 Two Harbourfront 22 Tak Fung St, Hunghom
Kowloon Hong Kong

Manufacturer Information

Company Name: Motorola Solutions (Malaysia) Sdn Bhd
Address: Unit 1807-12 Two Harbourfront 22 Tak Fung St, Hunghom
Kowloon Hong Kong

EUT Information

Product Type: Mobile
Product Marketing Name: APX6500
Model Number: M25URS9PW1BN
Sample Status: Normal
Sample ID: 2738299
Sample Received Date: December 06, 2019
Date of Tested: December 09 ~ December 27, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247 (d)	PASS

Prepared By:

Mick Zhang
Engineer Project Associate

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	5.78dB (1GHz-18Gz)
	5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Equipment	Mobile
Model Name	APX6500
Radio Technology	IEEE802.11b/g/n HT20
Operation frequency	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz
Modulation	IEEE 802.11b: DSSS(CCK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Rated Input	DC 13.6V

5.2. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel Number	Test Channel
WiFi TX(802.11b)	CH 1, CH 6, CH 11	Low, Middle, High
WiFi TX(802.11g)	CH 1, CH 6, CH 11	Low, Middle, High
WiFi TX(802.11n HT20)	CH 1, CH 6, CH 11	Low, Middle, High

5.3. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	45 ~ 70%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	22 ~ 28°C
Voltage :	VL	N/A
	VN	DC 13.6V
	VH	N/A

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage

VH= Upper Extreme Test Voltage

TN= Normal Temperature



5.4. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	PC	HP	HP ZBook 15G4c	/
2	USB TO UART	/	/	/

I/O CABLES

Cable No	Port	Part Number	Serial No / Tag	Country Of Origin	Remarks
1	Radio Power Cable	HKN4191B	HKN4191B-3	Malaysia	/
2	Cable	HKN6163C	HKN6163C-2	Malaysia	/
3	131ft remote cable	HKN6164B	HKN6164B-CF1	Malaysia	/
4	Control Head Power Cable	HKN6188B	HKN6188B	Malaysia	/


ACCESSORY

Item	Accessory	Part Number	Serial No / Tag	Country Of Origin
1	Control head	PMHN4194C	PMHN4194C-CF2	Malaysia
2	CHIB	PMUN1057B	PMUN1057B-CF1	Malaysia
3	TIB	PMUN1083A	PMUN1083A-C3	Malaysia
4	Antenna	AN000197A10	AN000197A10-CF1	Malaysia
5	Antenna	AN000163A02	AN000163A02-C2	Mexico
6	RSM	HMN4079G	HMN4079G-4	Malaysia
7	Audio Accy	HSN4040A	HSN4040A-C4	Taiwan
8	Mate plate	/	2pcs	Malaysia
9	Antenna holder	/	1pcs	Malaysia

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TEST





6. MEASURING INSTRUMENT AND SOFTWARE USED

Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec.06,2019	Dec.06,2020
☒	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021
☒	Preamplifier	HP	8447D	2944A09099	Dec.05,2019	Dec.05,2020
☒	EMI Measurement Receiver	R&S	ESR26	101377	Dec.05,2019	Dec.05,2020
☒	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021
☒	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021
☒	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.05,2019	Dec.05,2020
☒	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.05,2019	Dec.05,2020
☒	Loop antenna	Schwarzbeck	1519B	00008	Jan.07, 2019	Jan.07, 2022
☒	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.05,2019	Dec.05,2020
☒	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.05,2019	Dec.05,2020
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Radiated disturbance		Farad	EZ-EMC		Ver. UL-3A1
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.06,2019	Dec.06,2020
☒	Power Meter	Keysight	N1911A	MY55416024	Dec.06,2019	Dec.06,2020
☒	Power Sensor	Keysight	U2021XA	MY5100022	Dec.06,2019	Dec.06,2020



7. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Please refer to ISED RSS-GEN Clause 8.9 (Transmitter)

Radiation Disturbance Test Limit for FCC (Class B)(9kHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



Radiation Disturbance Test Limit for FCC (Above 1GHz)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

IC Restricted bands please refer to ISSED RSS-GEN Clause 8.10

FCC Restricted bands of operation:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9kHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of 1 meter height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120kHz
VBW	300kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

ABOVE 1G




The setting of the spectrum analyser

RBW	1MHz
VBW	PEAK: 3MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

TEST ENVIRONMENT

Temperature	24.2°C	Relative Humidity	61%
Atmosphere Pressure	101kPa	Test Voltage	DC 13.6V




7.1. RESTRICTED BANDEDGE

7.1.1. 802.11b MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2366.810	27.01	32.87	59.88	74.00	-14.12	peak
2	2390.000	26.09	32.94	59.03	74.00	-14.97	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2366.810	11.61	32.87	44.48	54.00	-9.52	AVG
2	2390.000	12.09	32.94	45.03	54.00	-8.97	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2377.505	26.86	32.90	59.76	74.00	-14.24	peak
2	2390.000	24.78	32.94	57.72	74.00	-16.28	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2377.505	11.89	32.90	44.79	54.00	-9.21	AVG
2	2390.000	12.21	32.94	45.15	54.00	-8.85	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	25.19	33.58	58.77	74.00	-15.23	peak
2	2490.450	27.25	33.63	60.88	74.00	-13.12	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.00	33.58	46.58	54.00	-7.42	AVG
2	2490.450	13.43	33.63	47.06	54.00	-6.94	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	27.30	33.58	60.88	74.00	-13.12	peak
2	2484.250	28.48	33.58	62.06	74.00	-11.94	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.56	33.58	47.14	54.00	-6.86	AVG
2	2484.250	13.65	33.58	47.23	54.00	-6.77	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



7.1.2. 802.11g MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	36.95	32.94	69.89	74.00	-4.11	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	12.36	32.94	45.30	54.00	-8.70	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.




RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.580	35.96	32.94	68.90	74.00	-5.10	peak
2	2390.000	35.64	32.94	68.58	74.00	-5.42	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.580	12.64	32.94	45.58	54.00	-8.42	AVG
2	2390.000	12.74	32.94	45.68	54.00	-8.32	AVG


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	37.98	33.58	71.56	74.00	-2.44	peak
2	2483.600	39.49	33.58	73.07	74.00	-0.93	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.72	33.58	47.30	54.00	-6.70	AVG
2	2483.600	13.70	33.58	47.28	54.00	-6.72	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	31.09	33.58	64.67	74.00	-9.33	peak
2	2485.550	39.93	33.59	73.52	74.00	-0.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	12.00	33.58	45.58	54.00	-8.42	AVG
2	2485.550	11.87	33.59	45.46	54.00	-8.54	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



7.1.3. 802.11n HT20 MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	35.82	32.94	68.76	74.00	-5.24	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	12.36	32.94	45.30	54.00	-8.70	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.430	34.25	32.94	67.19	74.00	-6.81	peak
2	2390.000	34.18	32.94	67.12	74.00	-6.88	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.430	12.75	32.94	45.69	54.00	-8.31	AVG
2	2390.000	13.05	32.94	45.99	54.00	-8.01	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	31.72	33.58	65.30	74.00	-8.70	peak
2	2484.050	37.65	33.58	71.23	74.00	-2.77	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.66	33.58	47.24	54.00	-6.76	AVG
2	2484.050	13.46	33.58	47.04	54.00	-6.96	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	33.53	33.58	67.11	74.00	-6.89	peak
2	2484.100	37.85	33.58	71.43	74.00	-2.57	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.51	33.58	47.09	54.00	-6.91	AVG
2	2484.110	13.42	33.58	47.00	54.00	-7.00	AVG

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.



7.2. SPURIOUS EMISSIONS (3~18GHz)

7.2.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4823.310	54.89	-0.06	54.83	74.00	-19.17	peak
2	4823.310	42.00	-0.06	41.94	54.00	-12.06	AVG
3	7815.000	40.11	9.31	49.42	74.00	-24.58	peak
4	11505.000	36.09	14.50	50.59	74.00	-23.41	peak
5	13845.000	35.09	17.22	52.31	74.00	-21.69	peak
6	16455.000	32.74	19.16	51.90	74.00	-22.10	peak
7	17925.000	30.04	23.34	53.38	74.00	-20.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4823.210	54.09	-0.06	54.03	74.00	-19.97	peak
2	4823.210	40.68	-0.06	40.62	54.00	-13.38	AVG
3	7815.000	40.21	9.31	49.52	74.00	-24.48	peak
4	10560.000	38.86	12.67	51.53	74.00	-22.47	peak
5	13830.000	33.61	17.36	50.97	74.00	-23.03	peak
6	17265.000	30.34	21.77	52.11	74.00	-21.89	peak
7	17715.000	29.62	22.65	52.27	74.00	-21.73	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4877.500	55.61	0.10	55.71	74.00	-18.29	peak
2	4877.500	42.56	0.10	42.66	54.00	-11.34	AVG
3	7770.000	40.65	8.97	49.62	74.00	-24.38	peak
4	11505.000	37.04	14.50	51.54	74.00	-22.46	peak
5	13605.000	35.97	16.40	52.37	74.00	-21.63	peak
6	14430.000	35.29	16.66	51.95	74.00	-22.05	peak
7	16950.000	31.63	20.61	52.24	74.00	-21.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4877.600	55.27	0.10	55.37	74.00	-18.63	peak
2	4877.600	41.39	0.10	41.49	54.00	-12.51	AVG
3	7305.000	42.81	7.35	50.16	74.00	-23.84	peak
4	10590.000	37.56	12.83	50.39	74.00	-23.61	peak
5	11730.000	36.79	14.13	50.92	74.00	-23.08	peak
6	15255.000	35.99	16.12	52.11	74.00	-21.89	peak
7	17700.000	30.14	22.53	52.67	74.00	-21.33	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4923.300	54.87	0.28	55.15	74.00	-18.85	peak
2	4923.300	41.33	0.28	41.61	54.00	-12.39	AVG
3	7740.000	40.05	8.53	48.58	74.00	-25.42	peak
4	10140.000	37.38	11.26	48.64	74.00	-25.36	peak
5	11505.000	37.36	14.50	51.86	74.00	-22.14	peak
6	13995.000	35.09	16.64	51.73	74.00	-22.27	peak
7	16920.000	32.40	20.46	52.86	74.00	-21.14	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4923.300	54.67	0.28	54.95	74.00	-19.05	peak
2	4923.300	40.88	0.28	41.16	54.00	-12.84	AVG
3	7845.000	39.70	9.12	48.82	74.00	-25.18	peak
4	11715.000	37.18	14.09	51.27	74.00	-22.73	peak
5	13800.000	35.58	17.60	53.18	74.00	-20.82	peak
6	14925.000	35.56	15.97	51.53	74.00	-22.47	peak
7	17265.000	31.03	21.77	52.80	74.00	-21.20	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.2.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	48.93	-0.10	48.83	74.00	-25.17	peak
2	7830.000	39.00	9.21	48.21	74.00	-25.79	peak
3	9375.000	38.83	10.49	49.32	74.00	-24.68	peak
4	10590.000	38.23	12.83	51.06	74.00	-22.94	peak
5	13575.000	35.86	16.33	52.19	74.00	-21.81	peak
6	16455.000	33.01	19.16	52.17	74.00	-21.83	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	49.26	-0.10	49.16	74.00	-24.84	peak
2	7860.000	40.13	9.01	49.14	74.00	-24.86	peak
3	10590.000	38.52	12.83	51.35	74.00	-22.65	peak
4	13965.000	35.62	16.68	52.30	74.00	-21.70	peak
5	17280.000	30.52	21.89	52.41	74.00	-21.59	peak
6	17715.000	29.81	22.65	52.46	74.00	-21.54	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	50.57	0.10	50.67	74.00	-23.33	peak
2	7410.000	39.46	7.77	47.23	74.00	-26.77	peak
3	9390.000	38.57	10.57	49.14	74.00	-24.86	peak
4	11775.000	36.73	14.24	50.97	74.00	-23.03	peak
5	13965.000	35.17	16.68	51.85	74.00	-22.15	peak
6	17835.000	29.66	23.34	53.00	74.00	-21.00	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	50.32	0.10	50.42	74.00	-23.58	peak
2	7815.000	39.27	9.31	48.58	74.00	-25.42	peak
3	11565.000	37.52	14.35	51.87	74.00	-22.13	peak
4	13905.000	35.25	16.76	52.01	74.00	-21.99	peak
5	14475.000	34.97	16.64	51.61	74.00	-22.39	peak
6	17580.000	30.30	21.87	52.17	74.00	-21.83	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	47.33	0.26	47.59	74.00	-26.41	peak
2	7035.000	39.88	6.97	46.85	74.00	-27.15	peak
3	9465.000	38.69	10.55	49.24	74.00	-24.76	peak
4	11520.000	37.02	14.46	51.48	74.00	-22.52	peak
5	14430.000	35.74	16.66	52.40	74.00	-21.60	peak
6	16950.000	31.78	20.61	52.39	74.00	-21.61	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	50.04	0.26	50.30	74.00	-23.70	peak
2	8190.000	39.18	9.84	49.02	74.00	-24.98	peak
3	11715.000	37.07	14.09	51.16	74.00	-22.84	peak
4	13830.000	34.48	17.36	51.84	74.00	-22.16	peak
5	14400.000	35.38	16.68	52.06	74.00	-21.94	peak
6	17805.000	28.98	23.34	52.32	74.00	-21.68	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.2.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	47.98	-0.10	47.88	74.00	-26.12	peak
2	5880.000	41.22	5.10	46.32	74.00	-27.68	peak
3	7800.000	39.42	9.41	48.83	74.00	-25.17	peak
4	11520.000	36.96	14.46	51.42	74.00	-22.58	peak
5	14865.000	35.67	15.99	51.66	74.00	-22.34	peak
6	16980.000	31.57	20.75	52.32	74.00	-21.68	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	48.44	-0.10	48.34	74.00	-25.66	peak
2	5895.000	39.99	5.40	45.39	74.00	-28.61	peak
3	7740.000	39.85	8.53	48.38	74.00	-25.62	peak
4	10980.000	37.73	13.47	51.20	74.00	-22.80	peak
5	13500.000	35.91	16.10	52.01	74.00	-21.99	peak
6	17325.000	30.43	21.96	52.39	74.00	-21.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	48.28	0.10	48.38	74.00	-25.62	peak
2	7815.000	39.75	9.31	49.06	74.00	-24.94	peak
3	9810.000	38.21	10.67	48.88	74.00	-25.12	peak
4	11940.000	37.29	14.43	51.72	74.00	-22.28	peak
5	13800.000	34.60	17.60	52.20	74.00	-21.80	peak
6	16650.000	31.89	19.97	51.86	74.00	-22.14	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	48.74	0.10	48.84	74.00	-25.16	peak
2	7815.000	39.29	9.31	48.60	74.00	-25.40	peak
3	10320.000	37.46	11.95	49.41	74.00	-24.59	peak
4	12675.000	36.63	14.61	51.24	74.00	-22.76	peak
5	14085.000	35.25	16.55	51.80	74.00	-22.20	peak
6	17850.000	29.93	23.34	53.27	74.00	-20.73	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	47.59	0.19	47.78	74.00	-26.22	peak
2	5895.000	40.10	5.40	45.50	74.00	-28.50	peak
3	8160.000	39.16	9.68	48.84	74.00	-25.16	peak
4	10980.000	37.05	13.47	50.52	74.00	-23.48	peak
5	13605.000	35.93	16.40	52.33	74.00	-21.67	peak
6	17715.000	29.82	22.65	52.47	74.00	-21.53	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	47.74	0.26	48.00	74.00	-26.00	peak
2	8190.000	39.55	9.84	49.39	74.00	-24.61	peak
3	11700.000	37.63	14.05	51.68	74.00	-22.32	peak
4	13440.000	36.20	16.27	52.47	74.00	-21.53	peak
5	16965.000	31.90	20.68	52.58	74.00	-21.42	peak
6	17715.000	30.22	22.65	52.87	74.00	-21.13	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.3. SPURIOUS EMISSIONS (1~3GHz)


7.3.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1238.000	46.59	-12.79	33.80	74.00	-40.20	peak
2	1754.000	50.59	-10.57	40.02	74.00	-33.98	peak
3	2100.000	44.71	-9.32	35.39	74.00	-38.61	peak
4	2364.000	50.42	-8.08	42.34	74.00	-31.66	peak
5	2414.000	58.72	-7.86	50.86	74.00	-23.14	peak
6	2520.000	52.53	-7.35	45.18	74.00	-28.82	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1212.000	47.75	-12.88	34.87	74.00	-39.13	peak
2	1778.000	45.80	-10.33	35.47	74.00	-38.53	peak
3	2362.000	52.66	-8.10	44.56	74.00	-29.44	peak
4	2414.000	58.53	-7.86	50.67	74.00	-23.33	peak
5	2520.000	55.47	-7.35	48.12	74.00	-25.88	peak
6	2718.000	48.09	-6.98	41.11	74.00	-32.89	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1102.000	47.63	-13.76	33.87	74.00	-40.13	peak
2	1754.000	50.79	-10.57	40.22	74.00	-33.78	peak
3	2338.000	54.63	-8.17	46.46	74.00	-27.54	peak
4	2432.000	60.41	-7.72	52.69	74.00	-21.31	peak
5	2580.000	57.95	-7.66	50.29	74.00	-23.71	peak
6	2774.000	48.44	-6.35	42.09	74.00	-31.91	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1110.000	49.93	-13.68	36.25	74.00	-37.75	peak
2	1590.000	46.66	-11.70	34.96	74.00	-39.04	peak
3	1808.000	46.05	-10.11	35.94	74.00	-38.06	peak
4	2336.000	52.13	-8.18	43.95	74.00	-30.05	peak
5	2434.000	59.62	-7.71	51.91	74.00	-22.09	peak
6	2596.000	57.26	-7.73	49.53	74.00	-24.47	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1398.000	48.06	-12.61	35.45	74.00	-38.55	peak
2	1594.000	46.36	-11.66	34.70	74.00	-39.30	peak
3	2178.000	45.02	-8.92	36.10	74.00	-37.90	peak
4	2362.000	47.94	-8.10	39.84	74.00	-34.16	peak
5	2466.000	60.05	-7.49	52.56	74.00	-21.44	peak
6	2570.000	54.20	-7.60	46.60	74.00	-27.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	54.20	-13.81	40.39	74.00	-33.61	peak
2	1196.000	50.85	-12.96	37.89	74.00	-36.11	peak
3	1746.000	48.55	-10.65	37.90	74.00	-36.10	peak
4	2354.000	52.32	-8.12	44.20	74.00	-29.80	peak
5	2466.000	60.43	-7.49	52.94	74.00	-21.06	peak
6	2564.000	58.70	-7.58	51.12	74.00	-22.88	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.3.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1214.000	47.22	-12.87	34.35	74.00	-39.65	peak
2	1636.000	46.34	-11.42	34.92	74.00	-39.08	peak
3	2062.000	45.98	-9.57	36.41	74.00	-37.59	peak
4	2366.000	58.68	-8.07	50.61	74.00	-23.39	peak
5	2420.000	56.35	-7.81	48.54	74.00	-25.46	peak
6	2538.000	54.20	-7.44	46.76	74.00	-27.24	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1410.000	48.22	-12.59	35.63	74.00	-38.37	peak
2	1616.000	47.12	-11.53	35.59	74.00	-38.41	peak
3	2368.000	58.07	-8.07	50.00	74.00	-24.00	peak
4	2420.000	57.95	-7.81	50.14	74.00	-23.86	peak
5	2546.000	54.74	-7.48	47.26	74.00	-26.74	peak
6	2676.000	50.96	-7.32	43.64	74.00	-30.36	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1320.000	46.26	-12.58	33.68	74.00	-40.32	peak
2	1888.000	45.92	-10.14	35.78	74.00	-38.22	peak
3	2066.000	45.32	-9.55	35.77	74.00	-38.23	peak
4	2352.000	49.16	-8.13	41.03	74.00	-32.97	peak
5	2444.000	59.11	-7.65	51.46	74.00	-22.54	peak
6	2540.000	55.71	-7.46	48.25	74.00	-25.75	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1074.000	51.71	-13.80	37.91	74.00	-36.09	peak
2	1196.000	50.48	-12.96	37.52	74.00	-36.48	peak
3	1400.000	52.26	-12.61	39.65	74.00	-34.35	peak
4	2366.000	54.83	-8.07	46.76	74.00	-27.24	peak
5	2444.000	58.90	-7.65	51.25	74.00	-22.75	peak
6	2546.000	59.23	-7.48	51.75	74.00	-22.25	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1218.000	47.72	-12.86	34.86	74.00	-39.14	peak
2	1744.000	51.01	-10.66	40.35	74.00	-33.65	peak
3	2136.000	45.84	-9.14	36.70	74.00	-37.30	peak
4	2362.000	48.91	-8.10	40.81	74.00	-33.19	peak
5	2444.000	59.98	-7.65	52.33	74.00	-21.67	peak
6	2554.000	54.53	-7.53	47.00	74.00	-27.00	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1076.000	49.12	-13.79	35.33	74.00	-38.67	peak
2	1354.000	47.18	-12.60	34.58	74.00	-39.42	peak
3	1770.000	46.00	-10.41	35.59	74.00	-38.41	peak
4	2348.000	48.53	-8.14	40.39	74.00	-33.61	peak
5	2470.000	59.56	-7.46	52.10	74.00	-21.90	peak
6	2518.000	57.10	-7.34	49.76	74.00	-24.24	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.3.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1208.000	47.92	-12.90	35.02	74.00	-38.98	peak
2	1518.000	46.72	-12.28	34.44	74.00	-39.56	peak
3	1990.000	45.15	-10.02	35.13	74.00	-38.87	peak
4	2368.000	54.12	-8.07	46.05	74.00	-27.95	peak
5	2414.000	55.55	-7.86	47.69	74.00	-26.31	peak
6	2544.000	52.50	-7.47	45.03	74.00	-28.97	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1198.000	51.09	-12.93	38.16	74.00	-35.84	peak
2	1402.000	53.27	-12.61	40.66	74.00	-33.34	peak
3	2368.000	58.89	-8.07	50.82	74.00	-23.18	peak
4	2420.000	58.27	-7.81	50.46	74.00	-23.54	peak
5	2542.000	54.28	-7.46	46.82	74.00	-27.18	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1218.000	46.86	-12.86	34.00	74.00	-40.00	peak
2	1406.000	45.74	-12.60	33.14	74.00	-40.86	peak
3	1704.000	46.26	-11.06	35.20	74.00	-38.80	peak
4	2310.000	49.69	-8.27	41.42	74.00	-32.58	peak
5	2446.000	59.55	-7.63	51.92	74.00	-22.08	peak
6	2546.000	54.97	-7.48	47.49	74.00	-26.51	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1218.000	47.66	-12.86	34.80	74.00	-39.20	peak
2	1620.000	46.00	-11.50	34.50	74.00	-39.50	peak
3	2358.000	53.09	-8.11	44.98	74.00	-29.02	peak
4	2446.000	59.17	-7.63	51.54	74.00	-22.46	peak
5	2524.000	57.57	-7.37	50.20	74.00	-23.80	peak
6	2870.000	47.57	-5.69	41.88	74.00	-32.12	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1220.000	47.26	-12.85	34.41	74.00	-39.59	peak
2	1590.000	46.05	-11.70	34.35	74.00	-39.65	peak
3	2064.000	44.68	-9.55	35.13	74.00	-38.87	peak
4	2334.000	47.05	-8.20	38.85	74.00	-35.15	peak
5	2470.000	57.73	-7.46	50.27	74.00	-23.73	peak
6	2510.000	54.94	-7.29	47.65	74.00	-26.35	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1078.000	49.67	-13.79	35.88	74.00	-38.12	peak
2	1402.000	47.22	-12.61	34.61	74.00	-39.39	peak
3	1882.000	45.67	-10.14	35.53	74.00	-38.47	peak
4	2340.000	48.81	-8.17	40.64	74.00	-33.36	peak
5	2466.000	60.01	-7.49	52.52	74.00	-21.48	peak
6	2516.000	58.20	-7.32	50.88	74.00	-23.12	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.4. SPURIOUS EMISSIONS 18G ~ 26GHz

7.4.1. 802.11b MODE

SPURIOUS EMISSIONS (WORST-CASE CONFIGURATION, LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18456.000	49.93	-4.38	45.55	74.00	-28.45	peak
2	19536.000	49.40	-4.73	44.67	74.00	-29.33	peak
3	21032.000	50.52	-5.32	45.20	74.00	-28.80	peak
4	22544.000	51.48	-5.79	45.69	74.00	-28.31	peak
5	23992.000	50.16	-4.03	46.13	74.00	-27.87	peak
6	24896.000	48.27	-1.44	46.83	74.00	-27.17	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



SPURIOUS EMISSIONS (WORST-CASE CONFIGURATION, LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18808.000	51.05	-4.85	46.20	74.00	-27.80	peak
2	20280.000	49.04	-4.89	44.15	74.00	-29.85	peak
3	22128.000	50.74	-6.15	44.59	74.00	-29.41	peak
4	23256.000	50.38	-5.24	45.14	74.00	-28.86	peak
5	23992.000	50.72	-4.03	46.69	74.00	-27.31	peak
6	24976.000	47.22	-1.16	46.06	74.00	-27.94	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.


Note: All the test modes have been tested, only the worst data record in the report.



7.5. SPURIOUS EMISSIONS 30M ~ 1 GHz

7.5.1. 802.11b MODE

SPURIOUS EMISSIONS (WORST-CASE CONFIGURATION, LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	95.9600	53.14	-21.43	31.71	43.50	-11.79	QP
2	167.7400	48.06	-17.04	31.02	43.50	-12.48	QP
3	288.9900	46.19	-14.49	31.70	46.00	-14.30	QP
4	480.0800	42.26	-10.84	31.42	46.00	-14.58	QP
5	802.1200	34.77	-5.24	29.53	46.00	-16.47	QP
6	991.2700	35.09	-3.35	31.74	54.00	-22.26	QP

Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



SPURIOUS EMISSIONS (WORST-CASE CONFIGURATION, LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	48.00	-17.19	30.81	40.00	-9.19	QP
2	95.9600	50.25	-21.43	28.82	43.50	-14.68	QP
3	167.7400	52.17	-17.04	35.13	43.50	-8.37	QP
4	191.9900	48.30	-15.99	32.31	43.50	-11.19	QP
5	411.2100	40.72	-12.13	28.59	46.00	-17.41	QP
6	757.5000	37.26	-5.81	31.45	46.00	-14.55	QP

- Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Note: All the test modes has been tested, only the worst data record in the report




7.6. SPURIOUS EMISSIONS BELOW 30M

7.6.1. 802.11b MODE

SPURIOUS EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT, LOW CHANNEL, WORST-CASE CONFIGURATION)

9kHz~ 150kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0117	68.98	-101.39	-32.41	46.24	-78.65	peak
2	0.0200	66.36	-101.34	-34.98	41.58	-76.56	peak
3	0.0330	61.48	-101.40	-39.92	37.23	-77.15	peak
4	0.0514	58.68	-101.48	-42.80	33.38	-76.18	peak
5	0.0835	54.78	-101.66	-46.88	29.17	-76.05	peak
6	0.1073	53.80	-101.77	-47.97	26.99	-74.96	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.



150kHz ~ 490kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1605	65.68	-101.65	-35.97	23.49	-59.46	peak
2	0.1819	62.49	-101.68	-39.19	22.41	-61.60	peak
3	0.2190	61.77	-101.75	-39.98	20.79	-60.77	peak
4	0.2530	61.59	-101.80	-40.21	19.54	-59.75	peak
5	0.3027	59.89	-101.86	-41.97	17.98	-59.95	peak
6	0.4032	56.97	-101.96	-44.99	15.49	-60.48	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.



490kHz ~ 30MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6481	52.57	-62.10	-9.53	31.37	-40.90	peak
2	1.3205	51.09	-62.12	-11.03	25.19	-36.22	peak
3	2.5935	50.61	-61.68	-11.07	29.54	-40.61	peak
4	5.5655	48.87	-61.41	-12.54	29.54	-42.08	peak
5	10.0510	46.25	-60.80	-14.55	29.54	-44.09	peak
6	19.7895	48.92	-60.84	-11.92	29.54	-41.46	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the test modes have been tested, only the worst data record in the report.

END OF REPORT