

 MOTOROLA SOLUTIONS	    CERTIFICATE 2518.08 SAMM 825																																
MOTOROLA PENANG ADV. COMM. LABORATORY Motorola Solutions Malaysia Sdn Bhd, Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia.	FCC / ISED TEST REPORT Report Revision : Rev.B																																
<table><tr><td>Date/s Tested</td><td>: 04-September-2025 - 12-September-2025</td></tr><tr><td>Report Issue Date</td><td>: 18-September-2025</td></tr><tr><td>Manufacturer/Location</td><td>: Motorola Solutions Malaysia Sdn Bhd</td></tr><tr><td>Manufacturer Address</td><td>: Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia</td></tr><tr><td>Requestor</td><td>: HAN ZHONG TING</td></tr><tr><td>Product Type</td><td>: Fixed Installation</td></tr><tr><td>Product Marketing Name (PMN)</td><td>: CB900D</td></tr><tr><td>Hardware Version Identification Number (HVIN)</td><td>: CBS101NBKLBA</td></tr><tr><td>Frequency Band</td><td>: 902 - 928 MHz</td></tr><tr><td>Max RF Output Power</td><td>: 1 Watt</td></tr><tr><td>Applicant Name</td><td>: Motorola Solutions Inc</td></tr><tr><td>Applicant Address</td><td>: Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia</td></tr><tr><td>Firmware Version Identification Number (FVIN)</td><td>: A0.00.06</td></tr><tr><td>FCC Registrations</td><td>: 461337</td></tr><tr><td>ISED Registrations</td><td>: MY0001</td></tr></table> The equipment was tested accordance to the requirement listed below: <table><tr><td>FCC 47 CFR Part 15C ISED RSS-GEN Issue 5 /247 Issue 4</td><td>PASS</td></tr></table>		Date/s Tested	: 04-September-2025 - 12-September-2025	Report Issue Date	: 18-September-2025	Manufacturer/Location	: Motorola Solutions Malaysia Sdn Bhd	Manufacturer Address	: Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia	Requestor	: HAN ZHONG TING	Product Type	: Fixed Installation	Product Marketing Name (PMN)	: CB900D	Hardware Version Identification Number (HVIN)	: CBS101NBKLBA	Frequency Band	: 902 - 928 MHz	Max RF Output Power	: 1 Watt	Applicant Name	: Motorola Solutions Inc	Applicant Address	: Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia	Firmware Version Identification Number (FVIN)	: A0.00.06	FCC Registrations	: 461337	ISED Registrations	: MY0001	FCC 47 CFR Part 15C ISED RSS-GEN Issue 5 /247 Issue 4	PASS
Date/s Tested	: 04-September-2025 - 12-September-2025																																
Report Issue Date	: 18-September-2025																																
Manufacturer/Location	: Motorola Solutions Malaysia Sdn Bhd																																
Manufacturer Address	: Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia																																
Requestor	: HAN ZHONG TING																																
Product Type	: Fixed Installation																																
Product Marketing Name (PMN)	: CB900D																																
Hardware Version Identification Number (HVIN)	: CBS101NBKLBA																																
Frequency Band	: 902 - 928 MHz																																
Max RF Output Power	: 1 Watt																																
Applicant Name	: Motorola Solutions Inc																																
Applicant Address	: Plot 2A, Medan Bayan Lepas, Mukim 12 S.W.D, 11900 Bayan Lepas, Penang, Malaysia																																
Firmware Version Identification Number (FVIN)	: A0.00.06																																
FCC Registrations	: 461337																																
ISED Registrations	: MY0001																																
FCC 47 CFR Part 15C ISED RSS-GEN Issue 5 /247 Issue 4	PASS																																
This report shall not be reproduced without written approval from an officially designated representative of the Motorola Penang Adv. Comm. Laboratory. The results and statements contained in this report pertain only to the device(s) evaluated.																																	
Prepared By:  Nur Alieya Binti Mat Yusoff Test Personnel	Approved Signatory:  Vincent Foong Chuen Kit Responsible Engineer																																

Table of Contents

1.0.	General Information.....	4
2.0.	Summary of Test Results.....	5
3.0.	Measurement Uncertainty.....	6
4.0.	Equipment List.....	7
5.0.	Test Mode Applicability and Test Channel Detail.....	8
6.0.	Transmitter Test Parameters.....	9
6.1.	Conducted RF Output Power (Peak) and E.I.R.P Measurement.....	9
6.1.1.	Test Setup.....	9
6.1.2.	Test Limits:.....	9
6.1.3.	Test Data:.....	10
6.2.	20dB Channel Bandwidth.....	11
6.2.1.	Test Setup.....	11
6.2.2.	Test Limits:.....	11
6.2.3.	Test Data:.....	12
6.3.	Band-edge Conducted Spurious Emission.....	13
6.3.1.	Test Setup.....	13
6.3.2.	Test Limits.....	13
6.3.3.	Test Result.....	14
6.4.	Dwell time.....	15
6.4.1.	Test Setup.....	15
6.4.2.	Test Limits.....	15
6.4.3.	Test Result.....	16
6.5.	Number of hopping Frequency.....	17
6.5.1.	Test Setup.....	17
6.5.2.	Test Limits.....	17
6.5.3.	Test Result.....	18
6.6.	Channel Separation.....	19
6.6.1.	Test Setup.....	19
6.6.2.	Test Limits.....	19
6.6.3.	Test Result.....	20
6.7.	Conducted Spurious Emission.....	21
6.7.1.	Test Setup.....	21
6.7.2.	Test Limits.....	21
6.7.3.	Test Data.....	22
6.8.	Radiated Spurious Emission.....	24
6.8.1.	Test Setup.....	24
6.8.2.	Test Limits.....	25
6.8.3.	Test Data:.....	26
6.9.	AC Powerline Conducted Emission.....	27
6.9.1.	Test Setup.....	27
6.9.2.	Test Limits.....	28
6.9.3.	Test Result.....	29

REVISION HISTORY

Revision History	Description	Date	Originator
Rev. A	Initial Report	17-September-2025	Nur Alieya
Rev. B	Updated ANSI C63.10 to latest accepted version	4-December-2025	Vincent

1.0.General Information

EUT Description:

Technologies	900MHz ISM
TX Frequency range	902MHz – 928MHz
Modulation Type	8FSK
No of Hopset	10
No of Channel Per Hopset	50
Input/Output	RF port
Connector type	PROGRAMMING
Antenna type	PIFA
Antenna Gain	2.94dBi

The EUT contains following accessory devices and data cable:

Item	Brand	Model or P/N
NA	NA	NA

General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, the EUT is to comply with the requirements of the following standards:

ANSI C63.10-2020

No modifications were done to the UUT to facilitate the tests in this report.

Deviation from standard

Not applicable as no deviation from standard test method

2.0. Summary of Test Results

FCC Clause	IC Clause	Test Item	Result	Remarks	Serial number	Tested by
15.247 (b)(2)	RSS-247 5.4(1)	Conducted RF Output Power (Peak) & EIRP Measurement	Pass	Highest output power: 29.56dBm (0.9W)	08722BL0245	Alieya
15.247 (a)(1)	RSS-247 5.1(3) RSS-247 5.1(2)	(1) 20dB Channel Bandwidth (2) Channel Separation	Pass	Highest 99% OCB: 26.085kHz (26K1F1D)	08722BL0245	Alieya
15.247(a)(1)(i)	RSS-247 5.1(3)	Number of hopping Frequency used	Pass	NA	08722BL0245	Alieya
15.247(a)(1)(i)	RSS-247 5.1(3)	Dwell time on each channel	Pass	NA	08722BL0245	Alieya
15.247 (d)	RSS-247 5.5	Band Edge Conducted Spurious Emission	Pass	Worst case emission: -41.44dBm	08722BL0245	Alieya
15.247 (d)	RSS-247 5.5	Conducted Spurious Emission	Pass	Worst case emission: -35.343dBm	08722BL0245	Alieya
15.205, 15.209, 15.247 (d)	RSS-247 5.5	Radiated Emission within Restricted Bands	NA	NA	NA	NA
15.207	RSS-Gen 8.8	AC Powerline Conducted Emission	NA	NA	NA	NA

3.0. Measurement Uncertainty

Measurement	Frequency	Expanded Uncertainty (k=1.96) (±)
AC Power Line Conducted Spurious Emission	150KHz ~ 30MHz	NA
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	NA
	200MHz ~ 1000MHz	NA
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	NA
	18GHz ~ 25GHz	NA
Conducted Spurious Emission	9kHz ~ 12.75GHz	2.82

4.0. Equipment List

Bluetooth ATE # 1 (SW Version: Ate Main 3.2.1)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
SPECTRUM ANALYZER	E4440A	MY46186938	29-Oct-24	29-Oct-25
POWER SUPPLY	6623A	2906A01118	18-Jul-25	18-Jul-26
CHAMBER	SH-641	92003820	09-Jul-25	09-Jul-26

5.0. Test Mode Applicability and Test Channel Detail

Radiated Emission Test (Above 1GHz)

☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☐ Following channel(s) was (were) selected for the final test as listed below.

Radiated Emission Test (Below 1GHz)

☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☐ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Total Channel	Tested Channel	Modulation Technology	Modulation Type	Tested by	Environmental Conditions
Test Mode	1 to 500	Hopset 1: 1, 26 Hopset 10: 50	FHSS	8FSK	NA	NA

Power Line Conducted Emission Test

☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☐ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Tested by	Environmental Conditions
Application Mode	1 to 500	AUTO	FHSS	AUTO	NA	NA

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).


☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Total Channel	Tested Channel	Modulation Technology	Modulation Type	Tested by	Environmental Conditions
Test Mode	1 to 500	Hopset 1: 1, 26 Hopset 10: 50	FHSS	8FSK	Alieya	25°C

6.0. Transmitter Test Parameters

6.1. Conducted RF Output Power (Peak) and E.I.R.P Measurement

6.1.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit in hopping disable mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = > 20 dB bandwidth
 - b. VBW = RBW
 - c. Detector mode = Peak
 - d. AMPLITUDE → Scale/Div = 10 dB
 - e. Trace = Max hold
 - f. Sweep = auto
- e) Measure the captured power within the band and recording the plot.
- f) Repeat above procedure with different channel frequency of operation.

6.1.2. Test Limits

Normal Condition (25 ° C)
Peak Output Power : < 1W (or 30dBm); E.I.R.P: < 4W



6.1.3. Test Data

Antenna Gain: 2.94dBi


Test Conditions		Test Frequency (MHz)	Peak Output Power			E.I.R.P.		
Modulation	Voltage(V)		dBm	Watt	Status	dBm	Watt	Status
8FSK	3.70	902.525	29.42	0.87	Pass	32.36	1.72	Pass
		915.025	29.40	0.87	Pass	32.34	1.71	Pass
		927.475	29.56	0.90	Pass	32.50	1.78	Pass

**Note: EIRP = PT +GT – LC, PT = Transmit Output Power, dBm
 GT = Antenna Gain, dBi
 LC = signal attenuation, dB1

- i. The Conducted RF Output Power test with result at low frequency, 902.525MHz ii. The Conducted RF Output Power test with result at mid frequency, 915.025MHz.




- iii. The Conducted RF Output Power test with result at high frequency, 927.475MHz.



6.2.20dB Channel Bandwidth

6.2.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit in hopping disable mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 1 kHz
 - b. VBW = 3 kHz
 - c. SPAN = 130kHz, center on test frequency
 - d. AMPLITUDE → Scale/Div = 10 dB
 - e. Detector mode = Peak
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure 20dB & 99% Bandwidth and record as the emission bandwidth.
- f) Save the plot result from spectrum analyzer screen.
- g) Repeat above procedure with different channel frequency of operation.


6.2.2. Test Limits

Normal Condition (25 ° C)
For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies


6.2.3. Test Data

Test Conditions		Test Frequency TX (MHz)	Results		
Modulation Type	Voltage(V)		20dB Bandwidth (kHz)	99% Occupied Bandwidth (kHz)	Status
8FSK	3.70	902.525	28.267	26.085	Pass
		915.025	28.490	25.891	Pass
		927.475	28.948	26.021	Pass


i. The 20 dB BW & occupied bandwidth test with result at low frequency, 902.525MHz.



ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, 915.025MHz.




iii. The 20 dB BW & occupied bandwidth test with result at high frequency, 927.475MHz.



6.3. Band-edge Conducted Spurious Emission

6.3.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = 4 MHz (Low channel) or 6MHz(High Channel)
 - d. Detector mode = Peak
 - e. Trace = Max hold
 - f. Sweep = auto
- e) Measure the captured band edge emission result and recording the plot.
- f) Repeat above on EUT with hopping disable.
- g) Repeat above procedure with other different test frequency.



6.3.2. Test Limits

Normal Condition (25 ° C)
Shall be at least 20 dB below the peak power.



6.3.3. Test Result

Test Conditions		Hopping Method	Test Frequency(MHz)	Results	
Modulation	Voltage(V)			dBm	Status
8FSK	3.70	Enabled (continuously)	902.525	-42.61	Pass
			927.475	-41.44	Pass
		Disabled (constantly)	902.525	-42.83	Pass
			927.475	-41.85	Pass

- i. The lowest band edge emission at low carrier frequency with hopping function enabled, 902.525MHz ii. The highest band edge emission at high carrier frequency with hopping function enabled, 927.475MHz




- iii. The lowest band edge emission at low carrier frequency with hopping function disabled, 902.525MHz iv. The highest band edge emission at high carrier frequency with hopping function disabled, 927.475MHz



6.4. Dwell time on each channel

6.4.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 10 kHz
 - b. VBW = 30 kHz
 - c. SPAN = Zero SPAN, center on hopping frequency
 - d. Detector mode = Peak
 - e. Trace = Max hold
 - f. Sweep time = 10 second
 - g. Sweep = Single
- e) Measure total numbers of transmissions occur in 10 second and save the plot.
- f) Change the setting of spectrum analyzer :
 - a. RBW = 10 kHz
 - b. VBW = 30 kHz
 - c. Sweep time = sufficient to capture dwell time for 1 transmission
 - d. Sweep = Single
- g) Measure dwell time for 1 transmission and save the plot.
- h) Calculate accumulate dwell time in a given period equal to number of hopping frequencies.
- i) Repeat above procedure with different channel frequency of operation

6.4.2. Test Limits



Normal Condition (25 ° C)
≤ 0.4sec

6.4.3. Test Result

Test Conditions			Results			
Modulation	Voltage (V)	Test Frequency (MHz)	No. of transmission in 10s (a)	Dwell time in one transmission (msec) (b)	Total accumulate dwell time in 20s. (msec) (c)	Status
8FSK	3.70	915.025	2	85.427	341.708000	Pass


**Note: Total dwell time in 20s, (c) = (a) x (b) x 2

Dwell Time



6.5. Number of hopping Frequency

6.5.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 10 kHz
 - b. VBW = 10 kHz
 - c. Detector mode = Peak
 - d. Trace = Max hold
- e) Allow the trace to stabilized & save the plot result from spectrum analyzer screen.
- f) Count number of channel frequency in the operating.
- g) Repeat above procedure for other test frequency.

6.5.2. Test Limits


Normal Condition (25 ° C)
≥ 50

6.5.3. Test Result

Voltage = 3.70V


HOPSET	Sweep Range (MHz)	Results			
		Start Frequency (MHz)	Last Frequency (MHz)	No. of Hopping Frequencies	Status
1	902 - 928	902.525	927.475	50	Pass

i. Number of Hopping Frequencies per HOPSET



6.6.Channel Separation

6.6.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 10 kHz
 - b. VBW = 30 kHz
 - c. SPAN = 1 MHz, center on test frequency
 - d. Detector mode = Peak
 - e. Trace = Max hold
 - f. Sweep = auto
- e) Measure the frequency different of these two adjacent channels with marker delta function & record the measurement results.
- f) Repeat above procedure with different channel frequency of operation


6.6.2. Test Limits

Normal Condition (25 ° C)
At least 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


6.6.3. Test Result

Modulation	Voltage(V)	Test Frequency (MHz)	Test Data Adjacent Channel Separation (MHz)	Status
8FSK	3.70	902.525	0.513	Pass
		915.025	0.476	Pass
		927.475	0.485	Pass


i. The Channel Separation test with result at low frequency, 902.525MHz.



ii. The Channel Separation test with result at mid frequency, 915.025MHz.




iii. The Channel Separation test with result at high frequency, 927.475MHz.



6.7. Conducted Spurious Emission

6.7.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = Cover until 10th harmonic
 - d. Detector mode = Peak
 - e. AMPLITUDE → Scale/Div = 10 dB
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the captured spurious emission result and recording the plot.
- f) Repeat above procedure with different channel frequency of operation.


6.7.2. Test Limits

Normal Condition (25 ° C)
Shall be at least 20 dB below for peak power.


6.7.3. Test Data

Test Conditions		Test Frequency (MHz)	Results	
Modulation	Voltage(V)		Spurious Level	Status
8FSK	3.70	902.525	-35.744	Pass
		915.025	-35.343	Pass
		927.475	-35.917	Pass


8FSK Modulation:




The highest emission level within the assigned band at low carrier frequency.




The highest emission level within the assigned band at middle carrier frequency.




Spurious emission measurement in 30MHz – 10GHz at low carrier frequency.



Spurious emission measurement in 30MHz – 10GHz at middle carrier frequency.




The highest emission level within the assigned band at high carrier frequency.



Spurious emission measurement in 30MHz – 10GHz at high carrier frequency.

6.8. Radiated Spurious Emission

6.8.1. Test Setup



- The EUT is placed on the top of a rotating table 0.8m (<1Ghz) and 1.5m (>1Ghz) above the ground at a 3m semi-anechoic chamber. The table is rotated 360 degrees to determine the position of the highest radiation.
- The EUT is set 3m away from the interference-receiving antenna, which is mounted on the top of a variable-height antenna tower.
- The antenna is Bilog/Horn antenna depend on which frequency range uses, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT is arranged to its worst case and then the antenna is tuned to heights from 1m to 4m and the rotatable table is turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system is set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode is fall within the range of 10dB from the limit specified, the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. Otherwise, the testing could be stopped and the peak values of the EUT would be reported.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

6.8.2. Test Limits

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

NOTE:


- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

6.8.3. Test Data

Not Applicable.

6.9. AC Powerline Conducted Emission

6.9.1. Test Setup



- 1) Tests were conducted for both Receive and Transmit Mode of the EUT.
- 2) The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50uH of coupling impedance for the measuring instrument.
- 3) Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- 4) The frequency range from 150 kHz to 30MHz was measured.

6.9.2. Test Limits

For AC Power Line Conducted Test Limit can be Class A or B depends on product classification.

**Limits for conducted disturbance at the mains ports
of class A ITE**

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	79	66
0,50 to 30	73	60
NOTE The lower limit shall apply at the transition frequency.		

Table 1: Limits for Conducted Disturbance at the Mains Ports of Class A ITE.

**Limits for conducted disturbance at the mains ports
of class B ITE**

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50
NOTE 1 The lower limit shall apply at the transition frequencies. NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

Table 2: Limits for Conducted Disturbance at the Mains Ports of Class B ITE

6.9.3. Test Result

Not Applicable. Testing is not required, radio shall turn off during charging mode

~ End of Test Report ~