

RF Exposure / SAR Statement

No. : 10679344S-A

Applicant	:	Canon Inc.
Type of Equipment	:	Wireless Module
Model No.	:	WM319
FCC ID	:	AZD319

Canon Inc. declares that Model : WM319
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “WM319” as calculated from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P =	13.18	mW (Maximum average output power)	
G =	0.55	Numerical Antenna gain; equal to	-2.60 dBi
r =	20.0	cm	

For: WM319

$$S = 0.00144 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401