FCC RF Test Report

APPLICANT	:	VeriFone, Inc.
EQUIPMENT	:	Point of Sale Terminal
BRAND NAME	:	Verifone or VERIFONE or verifone
MODEL NAME	:	VS100-P, VS102-P
FCC ID	:	B32VS100P
STANDARD	:	47 CFR Part 90(R)
CLASSIFICATION	:	PCS Licensed Transmitter (PCB)
TEST DATE(S)	:	Apr. 14, 2026 ~ May 06, 2026

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Maximum ERP Power, and Emission Designator 6
1.5 Testing Site 6
1.6 Test Software 6
1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10

3 CONDUCTED TEST ITEMS **11**

3.1 Measuring Instruments 11
3.2 Conducted Output Power and ERP 12
3.3 Peak-to-Average Ratio 13
3.4 Occupied Bandwidth 14
3.5 Conducted Band Edge Measurement 15
3.6 Emission Mask 16
3.7 Conducted Spurious Emission Measurement 17
3.8 Frequency Stability Measurement 18

4 RADIATED TEST ITEMS **19**

4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Radiated Spurious Emission Measurement 21

5 LIST OF MEASURING EQUIPMENT **22**

6 MEASUREMENT UNCERTAINTY **23**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG632616-02D	Rev. 01	Initial issue of report	Jun. 05, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.2	§2.1046	Conducted Output Power	—	Reporting only	-
	§90.542 (a)(7)	Effective Radiated Power	ERP < 3Watt	PASS	-
3.3	-	Peak-to-Average Ratio	—	Reporting only	-
3.4	§2.1049	Occupied Bandwidth	—	Reporting only	-
3.5	§2.1053 §90.543 (e)(2)(3)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.6	§2.1051 §90.210(n)	Emission Mask	Mask B	PASS	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	< $43+10\log_{10}(P[Watts])$	PASS	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	< ±1.25 ppm	PASS	-
4.4	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	< $43+10\log_{10}(P[Watts])$	PASS	Under limit 6.68 dB at 1584.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

VeriFone, Inc.
6020 West Oaks Blvd., Suite 260, Rocklin CA 95765, USA

1.2 Manufacturer

VeriFone, Inc.
6020 West Oaks Blvd., Suite 260, Rocklin CA 95765, USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Point of Sale Terminal
Brand Name	Verifone or VERIFONE or verifone
Model Name	VS100-P, VS102-P
FCC ID	B32VS100P
Tx Frequency	LTE Band 14: 788 MHz ~ 798 MHz
Rx Frequency	LTE Band 14: 758 MHz ~ 768 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	23.19 dBm
Antenna Gain	-0.5 dBi
Type of Modulation	QPSK / 16QAM / 64QAM
SN	Conducted: 713-027-886 Radiation: 713-027-928
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two samples, Sample 1 (VS100-P) and Sample 2 (VS102-P), Model VS102-P reflect the transition of the embedded SIM (eSIM) remote provisioning specification from GSMA SGP.02 to GSMA SGP.32, This change is limited to the eUICC firmware and remote provisioning protocol layer. According to the difference, we choose sample 1 to full test.

1.4 Maximum ERP Power, and Emission Designator

LTE Band 14		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	**790.5~795.5**	0.1130	4M48G7D	0.0853	4M50W7D
10	**793**	0.1132	9M03G7D	0.0853	8M97W7D

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	SPORTON	FCC LTE_Ver2.0 Auto_china_210503	2.0
2.	03CH04-KS	AUDIX	E3	210616

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 90(R)
- ANSI C63.26
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (X/Z Plane)

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	v		-	-	v	v	v	v			v	v	v
	14	-	-		v	-	-	v	v	v	v		v		v	
Peak-to-Average Ratio	14	-	-		v	-	-	v	v	v			v		v	
26dB and 99% Bandwidth	14	-	-	v	v	-	-	v	v				v		v	
Conducted Band Edge	14	-	-	v	v	-	-	v	v	v	v		v	v		v
Emission Mask	14	-	-	v		-	-	v	v	v	v		v	v	v	v
	14	-	-		v	-	-	v	v	v	v		v		v	
Conducted Spurious Emission	14	-	-	v		-	-	v			v			v	v	v
	14	-	-		v	-	-	v			v				v	
Frequency Stability	14	-	-		v	-	-	v					v		v	
E.R.P	14	-	-	v		-	-	v	v	v	v			v	v	v
	14	-	-		v	-	-	v	v	v	v		v		v	
Radiated Spurious Emission	14	-	-	v		-	-	v			v			v	v	v
	14	-	-		v	-	-	v			v				v	
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.6 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.6 + 10 = 14.6 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 14 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power

3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T – L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.6 Emission Mask

3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.

(2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.

(3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 + 10 log (P) dB.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10^{th} harmonic.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and power divider. The path loss was compensated to the results for each measurement.
   Path Loss Factor = Cable + Power Divider, Where the cable and power divider are the total path loss for the system calibration.
4. The low/middle/high channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±1.25 ppm of the center frequency.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Apr. 14, 2026~ Apr. 16, 2026	Jul. 06, 2026	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Apr. 14, 2026~ Apr. 16, 2026	NCR	Conducted (TH01-KS)
Temperature & humidity	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 02, 2025	Apr. 14, 2026~ Apr. 16, 2026	Jul. 01, 2026	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 10, 2025	May 06, 2026	Oct. 09, 2026	Radiation (03CH04-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	May 06, 2026	Aug. 09, 2026	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Nov. 22, 2025	May 06, 2026	Nov. 21, 2026	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00227860	1GHz~18GHz	Aug. 22, 2025	May 06, 2026	Aug. 21, 2026	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 10, 2026	May 06, 2026	Jan. 09, 2027	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 02, 2025	May 06, 2026	Jul. 01, 2026	Radiation (03CH04-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Dec. 24, 2025	May 06, 2026	Dec. 23, 2026	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18GA	060890	1Ghz-18Ghz	Feb. 09, 2026	May 06, 2026	Feb. 08, 2027	Radiation (03CH04-KS)
Amplifier	EM	EM01G18GA	060892	1Ghz-18Ghz	Oct. 11, 2025	May 06, 2026	Oct. 10, 2026	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 06, 2026	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 06, 2026	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 06, 2026	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	**±2.00 dB**
Occupied Channel Bandwidth	**±0.384%**
Conducted Power	**±0.90 dB**
Peak to Average Ratio	**±0.90 dB**
Frequency Stability	**±0.38 ppm**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.83 dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.83 dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.82 dB**

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Smile Wang	Temperature :	22~23℃
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP

LTE Band 14:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel					23330				
Frequency (MHz)					793			M	
10	QPSK	1	0		23.19			0.1132	
10	QPSK	1	49		23.09			0.1107	
10	QPSK	50	0		22.12			0.0885	
10	16QAM	1	0		21.96			0.0853	
10	64QAM	1	0		20.67			0.0634	
Channel				23305	23330	23355	ERP(W)		
Frequency (MHz)				790.5	793	795.5	L	M	H
5	QPSK	1	0	23.15	23.17	23.18	0.1122	0.1127	0.1130
5	16QAM	1	0	21.92	21.96	21.92	0.0845	0.0853	0.0845

LTE Band 14

Peak-to-Average Ratio

Mode	LTE Band 14 / 10MHz				
Mod.	QPSK	16QAM	64QAM		Limit: 13dB
RB Size	Full RB	Full RB	Full RB		Result
Middle CH	5.25	6.26	6.52		PASS

LTE Band 14 / 5MHz

Middle Channel / Full RB/ QPSK



Middle Channel / Full RB/ 16QAM



Middle Channel / Full RB/ 64QAM



26dB Bandwidth

Mode	LTE Band 14 : 26dB BW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	9.67	10.03
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	4.92	4.89

LTE Band 14

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 14

Middle Channel /5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 14 : 99%OBW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	4.48	4.50
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	9.03	8.97

LTE Band 14

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 14

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.13736 MHz	-53.30 dBm	-40.30 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.57455 MHz	-66.00 dBm	-31.00 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-18.25 dBm	-5.25 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.34615 MHz	21.67 dBm	-8.33 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.78281 MHz	-61.29 dBm	-26.29 dB

Date: 14.APR.2026 01:41:49

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.76374 MHz	-53.40 dBm	-40.40 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.12545 MHz	-66.20 dBm	-31.20 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.33117 MHz	-49.62 dBm	-36.62 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.66484 MHz	21.37 dBm	-8.63 dB
799.000 MHz	806.000 MHz	6.250 kHz	800.49219 MHz	-53.04 dBm	-18.04 dB

Date: 14.APR.2026 01:55:33

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.69780 MHz	-53.67 dBm	-40.67 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.14955 MHz	-65.99 dBm	-30.99 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-26.56 dBm	-13.56 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.70879 MHz	7.34 dBm	-22.66 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.11719 MHz	-57.34 dBm	-22.34 dB

Date: 14.APR.2026 01:47:20

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.22527 MHz	-53.16 dBm	-40.16 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.26295 MHz	-65.74 dBm	-30.74 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-43.13 dBm	-30.13 dB
788.000 MHz	799.000 MHz	100.000 kHz	795.30220 MHz	7.45 dBm	-22.55 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.06406 MHz	-47.93 dBm	-12.93 dB

Date: 14.APR.2026 01:50:03

LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge /1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.11538 MHz	-53.39 dBm	-40.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.33705 MHz	-66.14 dBm	-31.14 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-18.84 dBm	-5.84 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.33516 MHz	20.17 dBm	-9.83 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.75469 MHz	-62.07 dBm	-27.07 dB

Date: 14.APR.2026 01:42:44

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.39011 MHz	-53.58 dBm	-40.58 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.93527 MHz	-66.25 dBm	-31.25 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.31818 MHz	-51.24 dBm	-38.24 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.64286 MHz	19.88 dBm	-10.12 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.64844 MHz	-52.97 dBm	-17.97 dB

Date: 14.APR.2026 01:56:27

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.40110 MHz	-53.43 dBm	-40.43 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.54598 MHz	-66.01 dBm	-31.01 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-29.24 dBm	-16.24 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.35714 MHz	6.77 dBm	-23.23 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.04219 MHz	-57.62 dBm	-22.62 dB

Date: 14.APR.2026 01:48:15

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.08242 MHz	-53.60 dBm	-40.60 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.19955 MHz	-66.01 dBm	-31.01 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.72078 MHz	-45.06 dBm	-32.06 dB
788.000 MHz	799.000 MHz	100.000 kHz	794.93956 MHz	6.43 dBm	-23.57 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.37344 MHz	-47.43 dBm	-12.43 dB

Date: 14.APR.2026 01:50:57

LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.62088 MHz	-53.26 dBm	-40.26 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.65313 MHz	-66.08 dBm	-31.08 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-18.79 dBm	-5.79 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.36813 MHz	19.59 dBm	-10.41 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.71406 MHz	-62.38 dBm	-27.38 dB

Date: 14.APR.2026 01:43:38

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.11538 MHz	-53.19 dBm	-40.19 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.80491 MHz	-66.14 dBm	-31.14 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.33117 MHz	-51.69 dBm	-38.69 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.65385 MHz	19.84 dBm	-10.16 dB
799.000 MHz	806.000 MHz	6.250 kHz	800.50156 MHz	-54.23 dBm	-19.23 dB

Date: 14.APR.2026 01:57:21

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.17033 MHz	-53.24 dBm	-40.24 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.17902 MHz	-66.14 dBm	-31.14 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-26.18 dBm	-13.18 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.80769 MHz	5.35 dBm	-24.65 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.13281 MHz	-58.85 dBm	-23.85 dB

Date: 14.APR.2026 01:49:09

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.59890 MHz	-53.20 dBm	-40.20 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.76027 MHz	-66.02 dBm	-31.02 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.86364 MHz	-45.71 dBm	-32.71 dB
788.000 MHz	799.000 MHz	100.000 kHz	795.26923 MHz	5.64 dBm	-24.36 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.01719 MHz	-47.44 dBm	-12.44 dB

Date: 14.APR.2026 01:51:51

LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.84066 MHz	-53.19 dBm	-40.19 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.59777 MHz	-66.12 dBm	-31.12 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-31.08 dBm	-18.08 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.60989 MHz	21.38 dBm	-8.62 dB
799.000 MHz	806.000 MHz	6.250 kHz	801.80781 MHz	-58.81 dBm	-23.81 dB

Date: 14.APR.2026 01:58:15

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.42308 MHz	-53.78 dBm	-40.78 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.15223 MHz	-65.97 dBm	-30.97 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.17532 MHz	-46.79 dBm	-33.79 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.42308 MHz	22.08 dBm	-7.92 dB
799.000 MHz	806.000 MHz	6.250 kHz	800.24219 MHz	-51.94 dBm	-16.94 dB

Date: 14.APR.2026 02:03:39

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.33516 MHz	-52.99 dBm	-39.99 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.52723 MHz	-66.10 dBm	-31.10 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-35.33 dBm	-22.33 dB
788.000 MHz	799.000 MHz	100.000 kHz	795.43407 MHz	4.44 dBm	-25.56 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.00781 MHz	-48.95 dBm	-13.95 dB

Date: 14.APR.2026 02:06:20

LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.30220 MHz	-53.66 dBm	-40.66 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.42277 MHz	-65.77 dBm	-30.77 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-37.08 dBm	-24.08 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.57692 MHz	20.26 dBm	-9.74 dB
799.000 MHz	806.000 MHz	6.250 kHz	801.80469 MHz	-61.72 dBm	-26.72 dB

Date: 14.APR.2026 01:59:09

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.00549 MHz	-53.32 dBm	-40.32 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.75580 MHz	-65.97 dBm	-30.97 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.18831 MHz	-48.79 dBm	-35.79 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.40110 MHz	19.94 dBm	-10.06 dB
799.000 MHz	806.000 MHz	6.250 kHz	800.27031 MHz	-53.85 dBm	-18.85 dB

Date: 14.APR.2026 02:04:33

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.66484 MHz	-53.48 dBm	-40.48 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.67991 MHz	-66.00 dBm	-31.00 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-36.22 dBm	-23.22 dB
788.000 MHz	799.000 MHz	100.000 kHz	794.89560 MHz	3.72 dBm	-26.28 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.03906 MHz	-48.27 dBm	-13.27 dB

Date: 14.APR.2026 02:07:14

LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.62088 MHz	-53.27 dBm	-40.27 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.39598 MHz	-65.98 dBm	-30.98 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-35.13 dBm	-22.13 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.57692 MHz	19.24 dBm	-10.76 dB
799.000 MHz	806.000 MHz	6.250 kHz	801.80781 MHz	-62.29 dBm	-27.29 dB

Date: 14.APR.2026 02:00:02

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	758.70879 MHz	-53.24 dBm	-40.24 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.20670 MHz	-66.07 dBm	-31.07 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.16234 MHz	-49.51 dBm	-36.51 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.40110 MHz	19.39 dBm	-10.61 dB
799.000 MHz	806.000 MHz	6.250 kHz	800.27031 MHz	-54.30 dBm	-19.30 dB

Date: 14.APR.2026 02:05:26

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.36813 MHz	-53.41 dBm	-40.41 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.46027 MHz	-66.16 dBm	-31.16 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-32.93 dBm	-19.93 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.09341 MHz	2.73 dBm	-27.27 dB
799.000 MHz	806.000 MHz	6.250 kHz	799.36719 MHz	-48.52 dBm	-13.52 dB

Date: 14.APR.2026 02:08:08

Conducted Spurious Emission

LTE Band 14 / 5MHz

Lowest Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	750.000 MHz	1 MHz	3 MHz	35.22233 MHz	-47.434 dBm	-48.656 dB	-13.000 dBm	4.970 dB	---	---
2	750.000 MHz	810.000 MHz	1 MHz	3 MHz	788.33650 MHz	-24.658 dBm	-5.242 dB	30.000 dBm	4.985 dB	---	---
3	810.000 MHz	1.000 GHz	1 MHz	3 MHz	994.73379 MHz	-42.430 dBm	-49.430 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	1.57050 GHz	-47.196 dBm	-34.196 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	7.44750 GHz	-42.926 dBm	-29.263 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation
Ver 1.1(20241209)
2026-04-16 05:47:20

Middle Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	750.000 MHz	1 MHz	3 MHz	705.05587 MHz	-59.885 dBm	-48.085 dB	-13.000 dBm	4.970 dB	---	---
2	750.000 MHz	810.000 MHz	1 MHz	3 MHz	795.99000 MHz	-24.615 dBm	-5.385 dB	30.000 dBm	4.985 dB	---	---
3	810.000 MHz	1.000 GHz	1 MHz	3 MHz	972.73675 MHz	-42.079 dBm	-49.079 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	2.09550 GHz	-49.494 dBm	-35.484 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	7.45130 GHz	-42.047 dBm	-28.547 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation
Ver 1.1(20241209)
2026-04-16 05:47:26

Highest Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	750.000 MHz	1 MHz	3 MHz	65.96320 MHz	-61.830 dBm	-48.830 dB	-13.000 dBm	4.970 dB	---	---
2	750.000 MHz	810.000 MHz	1 MHz	3 MHz	793.32050 MHz	24.482 dBm	-5.518 dB	30.000 dBm	4.985 dB	---	---
3	810.000 MHz	1.000 GHz	1 MHz	3 MHz	992.54125 MHz	-62.338 dBm	-49.338 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	1.58650 GHz	-47.749 dBm	-34.749 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	7.47950 GHz	-42.623 dBm	-29.623 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation
Ver 1.1(20241209)
2026-04-16 05:47:35

LTE Band 14 / 10MHz

Middle Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	750.000 MHz	1 MHz	3 MHz	742.61493 MHz	-64.804 dBm	-51.804 dB	-13.000 dBm	4.970 dB	---	---
2	750.000 MHz	810.000 MHz	1 MHz	3 MHz	788.64400 MHz	24.342 dBm	-5.658 dB	30.000 dBm	4.985 dB	---	---
3	810.000 MHz	1.000 GHz	1 MHz	3 MHz	956.71000 MHz	-66.539 dBm	-53.539 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	2.36600 GHz	-20.962 dBm	-7.962 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	6.43800 GHz	-49.583 dBm	-36.583 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation

Ver 1.1(20241209)

2026-04-16 05:47:52

Mask

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / 64QAM

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / QPSK

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / 64QAM

Middle Channel / 1RB





Middle Channel / Full RB