



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: May 31, 2002

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division
Applicant: Titan Corporation
(formerly Datron World Communications Inc.)
Equipment: G25RMV110
FCC ID: B3TG25RMV110
FCC Rules: 22, 74, 80, 90, 90.210 and Confidentiality

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'M. Flom P. Eng.', with a horizontal line drawn underneath.

Morton Flom, P. Eng.

enclosure(s)
cc: Applicant
MF/jmm

LIST OF EXHIBITS
(FCC **CERTIFICATION** ~~(TRANSMITTERS)~~ - REVISED 9/28/98)

APPLICANT: Titan Corporation

FCC ID: B3TG25RMV110

BY APPLICANT:

- | | |
|--|---|
| 1. LETTER OF AUTHORIZATION | X |
| 2. IDENTIFICATION DRAWINGS, 2.1033(c)(11) | |
| ☒ LABEL | |
| ☒ LOCATION OF LABEL | |
| ☒ COMPLIANCE STATEMENT | |
| ☒ LOCATION OF COMPLIANCE STATEMENT | |
| 3. PHOTOGRAPHS, 2.1033(c)(12) | X |
| 4. DOCUMENTATION: 2.1033(c) | |
| (3) USER MANUAL | X |
| (9) TUNE UP INFO | X |
| (10) SCHEMATIC DIAGRAM | X |
| (10) CIRCUIT DESCRIPTION | X |
| BLOCK DIAGRAM | X |
| PARTS LIST | X |
| ACTIVE DEVICES | X |
| 5. PART 90.203(e) & (g) ATTESTATION | X |
| 6. PART 80 ATTESTATION | X |
| 7. MPE REPORT | X |

BY M.F.A. INC.

- A. TESTIMONIAL & STATEMENT OF CERTIFICATION
- B. STATEMENT OF QUALIFICATIONS



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

T R A N S M I T T E R C E R T I F I C A T I O N

of

FCC ID: B3TG25RMV110

MODEL: G25RMV110

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 22, 74, 80, 90, 90.210 and Confidentiality

DATE OF REPORT: May 31, 2002

ON THE BEHALF OF THE APPLICANT:

Titan Corporation

AT THE REQUEST OF:

P.O. 70432

Datron World Communications Division
3030 Enterprise Court
Vista, CA 92083

Attention of:

Mark S. Allen, VP Engineering
(760) 597-3735
mallen@dtwc.com

SUPERVISED BY:

A handwritten signature in black ink that reads 'M. Flom P. Eng.' The signature is stylized with a large 'M' and a long horizontal stroke.

Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	6
	Standard Test Conditions and Engineering Practices	7
2.1046(a)	Carrier Output Power (Conducted)	8
2.1046(a)	ERP Carrier Power (Radiated)	10
2.1051	Unwanted Emissions (Transmitter Conducted)	12
2.1053(a)	Field Strength of Spurious Radiation	16
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	20
90.214	Transient Frequency Behavior	34
2.1047(a)	Audio Low Pass Filter (Voice Input)	42
2.1047(a)	Audio Frequency Response	45
2.1047(b)	Modulation Limiting	47
2.1055(a)(1)	Frequency Stability (Temperature Variation)	50
2.1055(b)(1)	Frequency Stability (Voltage Variation)	53
2.202(g)	Necessary Bandwidth and Emission Bandwidth	54

PAGE NO.

1 of 54.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

TEST REPORT

- b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225
- c) Report Number: d0250060
- d) Client: Titan Corporation
(formerly Datron World Communications Inc.)
3030 Enterprise Court
Vista, CA 92083
- e) Identification: G25RMV110
FCC ID: B3TG25RMV110
EUT Description: VHF Mobile Radio
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: May 31, 2002
EUT Received: May 14, 2002
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by:
- 
Morton Flom, P. Eng.
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 54.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO22, 74, 80, 90, 90.210 and Confidentiality
Sub-part 2.1033(c)(1): NAME AND ADDRESS OF APPLICANT:Titan Corporation
formerly Datron World Communications Inc.
3030 Enterprise Court
Vista, CA 92083MANUFACTURER:

Datron World Communications Division

(c)(2): FCC ID: B3TG25RMV110MODEL NO: G25RMV110(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E, 11K0F3E, 22K0F1E,
14K6F1E(c)(5): FREQUENCY RANGE, MHz: 136 to 174(c)(6): POWER RATING, Watts: 25 to 110
x Switchable Variable N/A

FCC GRANT NOTE:

BF - The output power is
continuously variable from
the value listed in this
entry to 20%-25% of the
value listed.(c)(7): MAXIMUM POWER RATING, Watts: 500DUT RESULTS: Passes x Fails

PAGE NO.

3 of 54.

INFORMATION FOR PUSH-TO-TALK DEVICES

Type and number of antenna to be used for this device:

One (1), $\frac{1}{4}$ Wave

Maximum antenna gain for antenna indicated above:

0 dbd

Can this device sustain continuous operation with respect to its hardware capabilities and allowable operating functions?

No

Other hardware or operating restrictions that could limit a person's RF Exposure:

See Mandatory Instructions To Installers and Users

Source-based time-averaging (see 2.1093 of rules) applicable to reduce the average output power:

No

If device has headset and belt-clip accessories that would allow body-worn operations, what is the minimum separation distance between the antenna and the user's body in this operating configuration?

N/A

Can device access wire-line services to make phone calls, either directly or through an operator?

No

Can specific operating instructions be given to users to eliminate any potential RF Exposure concerns for both front-of-the-face and body-worn operating configurations?

N/A


Other applicable information the applicant may provide that can serve as effective means for ensuring RF Exposure compliance:

See Mandatory Instructions To Installers and Users

PAGE NO.

4 of 54.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

PAGE NO. 5 of 54.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 13.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for
determining and stabilizing frequency, for suppression of
spurious radiation, for limiting modulation and limiting
power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 X N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

6 of 54.

Sub-part

2.1033(c)(14):

TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ☐ 21 - Domestic Public Fixed Radio Services
- ☒ 22 - Public Mobile Services
- ☐ 22 Subpart H - Cellular Radiotelephone Service
- ☐ 22.901(d) - Alternative technologies and auxiliary services
- ☐ 23 - International Fixed Public Radiocommunication services
- ☐ 24 - Personal Communications Services
- ☒ 74 Subpart H - Low Power Auxiliary Stations
- ☒ 80 - Stations in the Maritime Services
- ☐ 80 Subpart E - General Technical Standards
- ☐ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ☐ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ☐ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ☐ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ☐ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ☐ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ☐ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ☐ 80 Subpart X - Voluntary Radio Installations
- ☐ 87 - Aviation Services
- ☒ 90 - Private Land Mobile Radio Services
- ☐ 94 - Private Operational-Fixed Microwave Service
- ☐ 95 Subpart A - General Mobile Radio Service (GMRS)
- ☐ 95 Subpart C - Radio Control (R/C) Radio Service
- ☐ 95 Subpart D - Citizens Band (CB) Radio Service
- ☐ 95 Subpart E - Family Radio Service
- ☐ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ☐ 97 - Amateur Radio Service
- ☐ 101 - Fixed Microwave Services

PAGE NO.

7 of 54.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 8 of 54.
NAME OF TEST: Carrier Output Power (Conducted)
SPECIFICATION: 47 CFR 2.1046(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(worst case)

FREQUENCY OF CARRIER, MHz = 155.2, 136.1, 173.9


POWER SETTING	R. F. POWER, WATTS
Low	25
High	110

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
TEST 2: FREQUENCY STABILITY



Asset	Description (as applicable)	s/n
(1)	<u>COAXIAL ATTENUATOR</u>	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2)	<u>POWER METERS</u>	
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(3)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 10 of 54.


NAME OF TEST: ERP Carrier Power (Radiated)

SPECIFICATION: TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.


e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \Sigma 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

	136.1 MHz		155.2 MHz		173.9 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	50.4	+ 0.8	43.9	+ 1.9	47.9	- 0.6
45°	50.3	+ 0.8	43.2	+ 1.9	43.3	- 0.6
90°	48.3	+ 0.8	40.1	+ 1.9	35.3	- 0.6
135°	47.5	+ 0.8	43.1	+ 1.9	35.9	- 0.6
180°	48.3	+ 0.8	34.8	+ 1.9	35.9	- 0.6
225°	48.0	+ 0.8	39.3	+ 1.9	35.5	- 0.6
270°	48.6	+ 0.8	38.9	+ 1.9	38.3	- 0.6
315°	49.2	+ 0.8	35.2	+ 1.9	31.5	- 0.6

	136.1 MHz	155.2 MHz	173.9 MHz
Av. Radiated Power:	49.625 dbm	41.71 dbm	37.35 dbm

TRANSMITTER RADIATED MEASUREMENTS



Asset	Description (as applicable)	s/n
(1)	TRANSDUCER	
i00091	Emco 3115	001469
i00089	Apel Log Periodic	001500
(2)	HIGH PASS FILTER	
i00	Narda μPAD (In-Band Only)	
i00	Trilithic (Out-Of-Band Only)	
(3)	PREAMP	
i00028	HP 8449 (+30 dB)	2749A00121
(4)	SPECTRUM ANALYZER	
i00048	HP 8566B	2511A01467
i00057	HP 8557A	1531A00191
i00029	HP 8563E	3213A00104

PAGE NO. 12 of 54.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE


FREQUENCY OF CARRIER, MHz	= 155.2, 136.1, 173.9
SPECTRUM SEARCHED, GHz	= 0 to 10 x F _c
MAXIMUM RESPONSE, Hz	= 2510
ALL OTHER EMISSIONS	= ≥ 20 dB BELOW LIMIT

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO. 14 of 54.
NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc

-(50+10xLOG P) = -64 (25 Watts)

-(50+10xLOG P) = -70.4 (110 Watts)

STATE: 1:Low Power g0250131: 2002-May-14 Tue 10:13:00

FREQUENCY TUNED, MHz	EMISSION, MHz	FREQUENCY LEVEL, dBm	LEVEL, dBc	MARGIN, dB
155.200000	310.404500	-33.1	-77	-13.1
173.900000	347.785500	-33.4	-77.3	-13.4
136.100000	408.302500	-30.6	-74.5	-10.6
155.200000	465.593500	-32.4	-76.3	-12.4
173.900000	521.669500	-34	-77.9	-14
136.100000	544.403500	-33.5	-77.4	-13.5
155.200000	620.792000	-33.3	-77.2	-13.3
136.100000	680.426400	-33.8	-77.7	-13.8
173.900000	695.652100	-33.8	-77.7	-13.8
155.200000	775.984000	-33.3	-77.2	-13.3
136.100000	816.702700	-34.1	-78	-14.1
173.900000	869.671800	-33.6	-77.5	-13.6
155.200000	931.204500	-34.4	-78.3	-14.4
136.100000	952.650400	-34.2	-78.1	-14.2
173.900000	1043.302300	-34.3	-78.2	-14.3
155.200000	1086.494700	-32.7	-76.6	-12.7
136.100000	1088.641700	-33.6	-77.5	-13.6
173.900000	1217.460800	-33.8	-77.7	-13.8
136.100000	1224.775300	-34.1	-78	-14.1
155.200000	1241.827900	-33.8	-77.7	-13.8
136.100000	1361.023000	-33.7	-77.6	-13.7
173.900000	1391.385300	-34.3	-78.2	-14.3
155.200000	1396.830000	-33.5	-77.4	-13.5
136.100000	1497.342900	-33	-76.9	-13
155.200000	1551.979500	-33.9	-77.8	-13.9
173.900000	1565.005800	-33.2	-77.1	-13.2
136.100000	1632.954100	-33.5	-77.4	-13.5
155.200000	1707.432400	-33.1	-77	-13.1
173.900000	1739.046100	-34.6	-78.5	-14.6
136.100000	1769.269000	-33.7	-77.6	-13.7
155.200000	1862.229700	-33.5	-77.4	-13.5
136.100000	1905.312400	-31.3	-75.2	-11.3
173.900000	1913.126900	-32.5	-76.4	-12.5
155.200000	2017.418700	-33	-76.9	-13
136.100000	2041.495500	-33.1	-77	-13.1
173.900000	2086.598200	-31.7	-75.6	-11.7
155.200000	2172.780000	-32.6	-76.5	-12.6
173.900000	2260.760100	-31.3	-75.2	-11.3
155.200000	2327.891800	-31.6	-75.5	-11.6
173.900000	2434.511900	-31.9	-75.8	-11.9
173.900000	2608.251600	-34.4	-78.3	-14.4



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 15 of 54.
NAME OF TEST: Unwanted Emissions (Transmitter Conducted)


LIMIT(S), dBc

-(50+10xLOG P) = -64 (25 Watts)

-(50+10xLOG P) = -70.4 (110 Watts)

STATE: 2:High Power g0250130: 2002-May-14 Tue 10:10:00

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
136.100000	272.198500	-19.7	-70.2	0.3
155.200000	310.400000	-24.1	-74.6	-4.1
173.900000	347.801500	-22.9	-73.4	-2.9
136.100000	408.295000	-25.1	-75.6	-5.1
155.200000	465.600500	-30	-80.5	-10
173.900000	521.702000	-26	-76.5	-6
136.100000	544.391500	-27.2	-77.7	-7.2
155.200000	620.808000	-30.5	-81	-10.5
136.100000	680.485000	-34	-84.5	-14
173.900000	695.791300	-34.5	-85	-14.5
155.200000	776.014000	-32.8	-83.3	-12.8
136.100000	816.512900	-33.9	-84.4	-13.9
173.900000	869.458400	-33.9	-84.4	-13.9
155.200000	931.085300	-33.3	-83.8	-13.3
136.100000	952.687000	-33.2	-83.7	-13.2
173.900000	1043.393500	-33.5	-84	-13.5
155.200000	1086.171600	-32.9	-83.4	-12.9
136.100000	1088.816000	-32.6	-83.1	-12.6
173.900000	1217.272500	-33.1	-83.6	-13.1
136.100000	1224.904000	-32.6	-83.1	-12.6
155.200000	1241.612500	-31.9	-82.4	-11.9
136.100000	1360.995000	-32.7	-83.2	-12.7
173.900000	1391.399300	-32.9	-83.4	-12.9
155.200000	1397.026900	-33.7	-84.2	-13.7
136.100000	1497.066400	-33.6	-84.1	-13.6
155.200000	1551.873300	-32.8	-83.3	-12.8
173.900000	1564.949300	-33.4	-83.9	-13.4
136.100000	1633.178500	-33.1	-83.6	-13.1
155.200000	1707.029700	-33.6	-84.1	-13.6
173.900000	1738.857800	-33	-83.5	-13
136.100000	1769.323500	-32.4	-82.9	-12.4
155.200000	1862.224200	-33.8	-84.3	-13.8
136.100000	1905.285800	-32.8	-83.3	-12.8
173.900000	1912.880500	-32.9	-83.4	-12.9
155.200000	2017.827900	-31.4	-81.9	-11.4
136.100000	2041.493500	-32.7	-83.2	-12.7
173.900000	2086.567100	-30.9	-81.4	-10.9
155.200000	2172.794500	-31	-81.5	-11
173.900000	2260.484200	-32.1	-82.6	-12.1
155.200000	2328.222900	-33.1	-83.6	-13.1
173.900000	2434.772800	-30.9	-81.4	-10.9
173.900000	2608.720900	-34.9	-85.4	-14.9



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 16 of 54.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)


GUIDE: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement


- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth ≥ 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO. 17 of 54.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to $\pm$ the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO. 18 of 54.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =
 $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step l)}$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:


Asset Description (as applicable)	s/n	Cycle	Last Cal
Per ANSI C63.4-1992/2000 Draft, 10.1.4			
TRANSDUCER			
i00088 EMC0 3109-B 25MHz-300MHz	2336	12 mo.	Sep-01
i00065 EMC0 3301-B Active Monopole	2635	12 mo.	Sep-01
i00089 Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-01
i00103 EMC0 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-01
AMPLIFIER			
i00028 HP 8449A	2749A00121	12 mo.	Mar-02
SPECTRUM ANALYZER			
i00029 HP 8563E	3213A00104	12 mo.	Jan-02
i00033 HP 85462A	3625A00357	12 mo.	Jan-02
i00048 HP 8566B	2511AD1467	6 mo.	Jan-02
MICROPHONE, ANTENNA PORT, AND CABELING			
Microphone Yes/No	Y	Cable Length <u>1.0</u> Meters	
Antenna Port Terminated Yes/No	Y	Antenna Gain <u>0 dbd</u>	
All Ports Terminated by Load	Y		

PAGE NO. 19 of 54.

NAME OF TEST: Field Strength of Spurious Radiation
 g0250142: 2002-May-14 Tue 15:15:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	ERP, dBm	ERP, dbc
155.200000	310.398800	-30.9	≤ -70.4
155.200000	465.602500	-20.4	≤ -70.4
155.200000	620.801300	-33.4	≤ -70.4
155.200000	776.002500	-32.8	≤ -70.4
155.200000	931.200600	-33.8	≤ -70.4
155.200000	1086.412300	-40.5	≤ -70.4
155.200000	1241.606100	-37.1	≤ -70.4
155.200000	1396.787200	-43.4	≤ -70.4
155.200000	1552.047800	-42.7	≤ -70.4

SUPERVISED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 20 of 54.
NAME OF TEST: Emission Masks (Occupied Bandwidth)
SPECIFICATION: 47 CFR 2.1049(c)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED


PAGE NO.

21 of 54.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250120: 2002-May-14 Tue 09:44:00
 STATE: 1:Low Power




PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

22 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250121: 2002-May-14 Tue 09:47:00
 STATE: 1:Low Power



POWER:
 MODULATION:


LOW
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/LPF

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 23 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250125: 2002-May-14 Tue 09:57:00
 STATE: 1:Low Power



POWER:
MODULATION:


LOW
VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 24 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250127: 2002-May-14 Tue 10:03:00
 STATE: 1:Low Power



POWER:
 MODULATION:


LOW
 DIGITIZED VOICE PROJECT 25
 MASK: C, VHF/UHF 25kHz, no
 LPF

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 25 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250129: 2002-May-14 Tue 10:07:00
 STATE: 1:Low Power



POWER:
MODULATION:


LOW
DIGITIZED VOICE PROJECT 25
MASK: D, VHF/UHF 12.5kHz BW

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.


PAGE NO. 26 of 54.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250119: 2002-May-14 Tue 09:42:00
 STATE: 2:High Power



POWER: HIGH
 MODULATION: NONE


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

27 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250122: 2002-May-14 Tue 09:48:00
 STATE: 2:High Power



POWER:
MODULATION:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz,
w/LPF


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

28 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250123: 2002-May-14 Tue 09:52:00
 STATE: 2:High Power



POWER:
MODULATION:


HIGH
VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 29 of 54.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250126: 2002-May-14 Tue 10:01:00
 STATE: 2:High Power



POWER:
 MODULATION:


HIGH
 DIGITIZED VOICE PROJECT 25
 MASK: C, VHF/UHF 25kHz, no
 LPF

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 30 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250128: 2002-May-14 Tue 10:06:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 DIGITIZED VOICE PROJECT 25
 MASK: D, VHF/UHF 12.5kHz BW


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

31 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0250001: 2002-May-15 Wed 15:34:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 99 % POWER BANDWIDTH


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

32 of 54.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
g0250002: 2002-May-15 Wed 15:35:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
DIGITIZED VOICE PROJECT 25
99 % POWER BANDWIDTH

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO.

33 of 54.

PAGE INTENTIONALLY LEFT

PAGE NO. 34 of 54.

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: 47 CFR 90.214

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:


<u>step f</u> , dBm	=	-8.1
<u>step h</u> , dBm	=	-38.5
<u>step l</u> , dBm	=	10.7



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.


TRANSIENT FREQUENCY BEHAVIOR



Asset	Description (as applicable)	s/n
(1)	ATTENUATOR (Removed after 1st step)	
i00112	Philco 30 dB	989
(2)	ATTENUATOR	
i00112	Philco 30 dB	989
i00172	Bird 30 dB	989
i00122	Narda 10 dB	7802
i00123	Narda 10 dB	7802A
i00110	Kay Variable	145-387
(3)	COMBINER	
i00154	4 x 25 Ω COMBINER	154
(4)	CRYSTAL DETECTOR	
i00159	HP 8470B	1822A10054
(5)	RF SIGNAL GENERATOR	
i00018	HP 8656A	2228A03472
i00031	HP 8656A	2402A06180
i00067	HP 8920A	3345U01242
(6)	MODULATION ANALYZER	
i00020	HP 8901A	2105A01087
(7)	SCOPE	
i00030	HP 54502A	2927A00209


PAGE NO. 36 of 54.

NAME OF TEST: Transient Frequency Behavior
g0250134: 2002-May-14 Tue 11:38:00
STATE: 2:High Power




POWER:	HIGH
MODULATION:	Ref Gen=25 kHz Deviation
DESCRIPTION:	CARRIER ON TIME

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 37 of 54.

NAME OF TEST: Transient Frequency Behavior
g0250135: 2002-May-14 Tue 11:40:00
STATE: 2:High Power




POWER: HIGH
MODULATION: Ref Gen=25 kHz Deviation
DESCRIPTION: CARRIER OFF TIME

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 38 of 54.

NAME OF TEST: Transient Frequency Behavior
g0250138: 2002-May-14 Tue 11:44:00
STATE: 2:High Power




POWER:	HIGH
MODULATION:	Ref Gen=25 kHz Deviation
DESCRIPTION:	CARRIER ON TIME

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 39 of 54.

NAME OF TEST: Transient Frequency Behavior
g0250139: 2002-May-14 Tue 11:45:00
STATE: 2:High Power




POWER:	HIGH
MODULATION:	Ref Gen=25 kHz Deviation
DESCRIPTION:	CARRIER OFF TIME

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 40 of 54.

NAME OF TEST: Transient Frequency Behavior
g0250140: 2002-May-14 Tue 11:47:00
STATE: 2:High Power




POWER:	HIGH
MODULATION:	Ref Gen=12.5 kHz Deviation
DESCRIPTION:	CARRIER ON TIME

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 41 of 54.

NAME OF TEST: Transient Frequency Behavior
g0250141: 2002-May-14 Tue 11:49:00
STATE: 2:High Power



POWER: HIGH
MODULATION: Ref Gen=12.5 kHz Deviation
DESCRIPTION: CARRIER OFF TIME

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 42 of 54.
NAME OF TEST: Audio Low Pass Filter (Voice Input)
SPECIFICATION: 47 CFR 2.1047(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. MODULATION CAPABILITY/DISTORTION
- TEST B. AUDIO FREQUENCY RESPONSE
- TEST C. HUM AND NOISE LEVEL
- TEST D. RESPONSE OF LOW PASS FILTER
- TEST E. MODULATION LIMITING




Asset Description (as applicable)	s/n
(1) <u>Audio Oscillator</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00118 HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 NARDA 766-10	7802
i00123 NARDA 766-10	7802A
i00113 SIERRA 661A-3D	1059
i00069 BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>	
i00020 HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>	
i00017 HP 8903A	2216A01753


PAGE NO.

44 of 54.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g0250109: 2002-May-14 Tue 09:06:00
STATE: 0:General



PERFORMED BY:


Doug Noble, B.A.S. E.E.T.


PAGE NO. 45 of 54.
NAME OF TEST: Audio Frequency Response
SPECIFICATION: 47 CFR 2.1047(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 46 of 54.

NAME OF TEST: Audio Frequency Response
g0250108: 2002-May-14 Tue 09:01:00
STATE: 0:General




Frequency of Maximum Audio Response, Hz = 2510

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-18.59
20000	-29.21
30000	-29.24
50000	-29.55

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 47 of 54.
NAME OF TEST: Modulation Limiting
SPECIFICATION: 47 CFR 2.1047(b)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


48 of 54.

NAME OF TEST: Modulation Limiting
 g0250111: 2002-May-14 Tue 09:12:00
 STATE: 0:General


Positive
 Peaks:



Negative
 Peaks:



PERFORMED BY:



 Doug Noble, B.A.S. E.E.T.

PAGE NO.


49 of 54.

NAME OF TEST: Modulation Limiting
 g0250112: 2002-May-14 Tue 09:17:00
 STATE: 0:General


Positive
 Peaks:



Negative
 Peaks:



PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.


PAGE NO. 50 of 54.
NAME OF TEST: Frequency Stability (Temperature Variation)
SPECIFICATION: 47 CFR 2.1055(a)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2
TEST CONDITIONS: As Indicated
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. OPERATIONAL STABILITY
- TEST B. CARRIER FREQUENCY STABILITY
- TEST C. OPERATIONAL PERFORMANCE STABILITY
- TEST D. HUMIDITY
- TEST E. VIBRATION
- TEST F. ENVIRONMENTAL TEMPERATURE
- TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
- TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Asset	Description (as applicable)	s/n
(1)	<u>TEMPERATURE, HUMIDITY, VIBRATION</u>	
i00027	Tenney Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2)	<u>COAXIAL ATTENUATOR</u>	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	<u>R.F. POWER</u>	
i00014	HP 435A POWER METER	1733A05839
i00039	HP 436A POWER METER	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(4)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

PAGE NO.


52 of 54.

NAME OF TEST: Frequency Stability (Temperature Variation)
 g0250146: 2002-May-15 Wed 16:12:11
 STATE: 0:General



°C	Frequency, MHz	Change in Freq, Hz	Change in Freq, PPM
-30	155.199882	-242.0	-1.6
-20	155.199925	-199.0	-1.3
-10	155.200009	-115.0	-0.7
0	155.200082	-42.0	-0.3
10	155.200123	-1.0	0.0
20	155.200129	5.0	0.0
25	155.200124	0.0	0.0
30	155.200115	-9.0	-0.1
40	155.200067	-57.0	-0.4
50	155.200003	-121.0	-0.8

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 53 of 54.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(d)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

g0250118: 2002-May-14 Tue 09:34:10

STATE: 0:General


LIMIT, ppm = 2.5

LIMIT, Hz = 388

BATTERY END POINT (Voltage) = 9.8

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	11.56	155.200060	60	0.39
100	13.6	155.200000	0	0.00
115	15.64	155.199970	-30	-0.19
72	9.8	155.199960	-40	-0.26

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 54 of 54.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 2.5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 11.0

MODULATION = 22K0F1E

NECESSARY BANDWIDTH CALCULATION:


MAXIMUM MODULATION (M), kHz	= 9.6
MAXIMUM DEVIATION (D), kHz	= 3
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 22.0

MODULATION = 14K6F1E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 4.8
MAXIMUM DEVIATION (D), kHz	= 2.5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 14.6

PERFORMED BY:
END OF TEST REPORT


Doug Noble, B.A.S. E.E.T.

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:


Morton Flom, P. Eng.