VS300
bottom_back_left side

nautel
Exciter
Power Amplifier
Output Network
Power Supply
VS300

VS300
front

VS300
top_front_right side

FCC LABEL LOCATION
RF SAMPLE OUT (J1)
RF MONITOR (J2 39dB (TYP.)
RF OUT (J3)
RF DRIVE IN (J4)
CAUTION MAX INPUT LEVEL +23dBm
DWA10-047,10-096,10-132, 10-151,10-172,10-117,10-236
XMTR LINK (A1J1)
REMOTE I/O-A (A1J2A)
REMOTE I/O-B (A1J2B)
AES/EBU IN (A1J3)
PILOT SAMPLE OUT (A1J4A)
10MHz IN (A1J4B)
RDS/RBDS (A1J5A)
ANALOG AUDIO/ SCA3/1PPS (A1J5B)
SCA1 (A1J6A)
SCA2/RDS (A1J6B)
INPUTS
MPX BAL/UNBAL (A1J7)
Livewire LAN (A1J8A)
USB-A (A1J8B)
USB-B (A1J8C)
WARNING: DISCONNECT AND LOCK OUT UPSTREAM SUPPLY BEFORE SERVICING
AC INPUT (U1) 200-240 VAC (NOM.) 50/60Hz 1-PHASE (8A MAX)
POWER (CB1)
I
O
E1
OPER# 19
VS300-H0199

VS300 back