TEST REPORT

Applicant Name :	FCC: Porta Phone Company Inc ISEDC: PORTA PHONE CO., INC.
Address :	FCC: 145 Dean Knauss Drive Narragansett, Rhode Island 02882 United States ISEDC: 145 Dean Knauss Drive Narragansett, RI 02882, United States of America
ReportNumber:	RA221230-64583E-RFA
FCC ID:	B4H-DBXCBS
IC	3064A-DBXCBS

Test Standard (s)

FCC PART 15.247;RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247, ISSUE 2, FEBRUARY 2017

Sample Description

Product Type:	900 MHz / 2.4 GHz Base Station Conference Module
Model No.:	DBX-CMod
Multiple Model(s) No.:	N/A
Trade Mark:	DBX Conference Module
Date Received:	2022/12/30
Report Date:	2023/02/17

Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards above.

Prepared andChecked By: **Approved By:**

Andy Yu
EMC Engineer

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★ ".
Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect testresults are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.
1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY **4**

GENERAL INFORMATION **5**

PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 5
OBJECTIVE 5
TEST METHODOLOGY 5
MEASUREMENT UNCERTAINTY 6
TEST FACILITY 6

SYSTEM TEST CONFIGURATION **7**

DESCRIPTION OF TEST CONFIGURATION 7
EUT EXERCISE SOFTWARE 7
SPECIAL ACCESSORIES 7
EQUIPMENT MODIFICATIONS 7
SUPPORT EQUIPMENT LIST AND DETAILS 8
EXTERNAL I/O CABLE 8
BLOCK DIAGRAM OF TEST SETUP 8

SUMMARY OF TEST RESULTS **10**

TEST EQUIPMENT LIST **11**

FCC§15.247 (I), §1.1307 (B)(1)&§2.1093 – RF EXPOSURE **13**

APPLICABLE STANDARD 13

RSS-102– RF EXPOSURE **14**

APPLICABLE STANDARD 14

FCC §15.203 & RSS-GEN §6.8– ANTENNA REQUIREMENT **15**

APPLICABLE STANDARD 15
ANTENNA CONNECTOR CONSTRUCTION 15

FCC §15.207 (A) & RSS-GEN §8.8 – AC LINE CONDUCTED EMISSIONS **16**

APPLICABLE STANDARD 16
EUT SETUP 17
EMI TEST RECEIVER SETUP 17
TEST PROCEDURE 17
CORRECTED FACTOR & MARGIN CALCULATION 18
TEST DATA 18

FCC §15.205, §15.209&§15.247(D) & RSS-247§ 5.5– RADIATED EMISSIONS **21**

APPLICABLE STANDARD 21
EUT SETUP 21
EMI TEST RECEIVER&SPECTRUM ANALYZER SETUP 22
TEST PROCEDURE 22
CORRECTED FACTOR& MARGIN CALCULATION 22
TEST DATA 22

FCC §15.247(A) (1)&RSS-247 § 5.1 (B)-CHANNEL SEPARATION TEST **33**

APPLICABLE STANDARD 33
TEST PROCEDURE 33
TEST DATA 33

FCC §15.247(A) (1)& RSS-GEN § 6.7&RSS-247 § 5.1 (A)–99% OCCUPIED BANDWIDTH & 20DBEMISSION BANDWIDTH 36
APPLICABLE STANDARD 36
TEST PROCEDURE 36
TEST DATA 37
FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D)-QUANTITY OF HOPPING CHANNEL TEST....41
APPLICABLE STANDARD 41
TEST PROCEDURE 41
TEST DATA 41
FCC §15.247(A) (1) (III) &RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME) 43
APPLICABLE STANDARD 43
TEST PROCEDURE 43
TEST DATA 43
FCC §15.247(B) (1)& RSS-247§ 5.1(B) &§ 5.4(B) - PEAK OUTPUT POWER MEASUREMENT....47
APPLICABLE STANDARD 47
TEST PROCEDURE 47
TEST DATA 47
FCC §15.247(D) &RSS-247 § 5.5 - BAND EDGES TESTING....52
APPLICABLE STANDARD 52
TEST PROCEDURE 52
TEST DATA 52

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA221230-64583E-RFA	Original Report	2023-02-17

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	DBX-CMod
Frequency Range	2407-2475MHz
Maximum conducted Peak output power	16.95dBm
Modulation Technique	GFSK
Antenna Specification*	0 dBi(It is provided by the applicant)
Voltage Range	DC3.7V from battery or DC5V from adapter
Sample number	1X2T-3for Conductedand Radiated emission test 1X2S-2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247, Issue 2, February 2017, RSS-GEN Issue 5, Feb. 2021Amendment 2 of theInnovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and RSS-247, Issue 2, February 2017, RSS-GEN Issue 5, Feb. 2021Amendment 2 of theInnovation, Science and Economic Development Canada rules.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		$0.082*10^{-7}$
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz -26.5GHz	5.06dB
	26.5GHz -40GHz	4.72dB
Temperature		1℃
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISEDC), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	**2407**	15	2425	30	2443	45	2461
1	2408	16	2426	31	2444	46	2462
2	2409	17	2427	32	2445	47	2466
3	2410	18	2428	33	2446	48	2467
4	2411	19	2429	**34**	**2450**	49	2468
5	2412	20	2430	35	2451	50	2469
6	2413	21	2434	36	2452	51	2470
7	2414	22	2435	37	2453	52	2471
8	2418	23	2436	38	2454	53	2472
9	2419	24	2437	39	2455	54	2473
10	2420	25	2438	40	2456	55	2474
11	2421	26	2439	41	2457	**56**	**2475**
12	2422	27	2440	42	2458	/	/
13	2423	28	2441	43	2459	/	/
14	2424	29	2442	44	2460	/	/

Note: The equipment has designed 57 channels totally, but only 20 channelsselected from the 57 channels active at same time, which were separated by more than 2MHz.

EUT was test in channel 0, 34, 56.

Note : The EUT has two RF modules, according to the manufacturer, the two modules can’t transmit simultaneously.

EUT Exercise Software

EUT was configured to testing mode by applicant and power level is default*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Dell	Notebook	Latitude E5430	11429208685
Porta Phone	Headphone	EVX-CMod	Unknown
Porta Phone	Adapter	YNQX09G050100UL	Unknown
Bull	Receptacle	902#	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielded Un-detachable HDMI Cable	1.5	EUT	Notebook
Un-shielded Un-detachable Cable	1.5	Receptacle	LISN/AC Mains
Un-shielded Un-detachable Cable	1.0	EUT	Headphone
Un-shielded Un-detachable DC Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission



For Radiated Emission for below 1 GHz



For Radiated Emission for above 1 GHz



SUMMARY OF TEST RESULTS

FCC Rules	ISEDC Rules	Description of Test	Result
§15.247 (i), §2.1093	RSS-102	RF EXPOSURE	Compliant
§15.203	RSS-Gen§6.8	Antenna Requirement	Compliant
§15.207(a)	RSS-Gen§8.8	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	RSS-247 § 5.5	Radiated Emissions	Compliant
§15.247(a)(1)	RSS- Gen§6.7, RSS-247 § 5.1 (a)	99% Occupied Bandwidth & 20dBEmission Bandwidth	Compliant
§15.247(a)(1)	RSS-247 § 5.1 (b)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	RSS-247 § 5.1 (d)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	RSS-247 § 5.1 (d)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	RSS-247 § 5.1(b) &§ 5.4(b)	Peak Output Power Measurement	Compliant
§15.247(d)	RSS-247 § 5.5	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Conducted Emission Test Software: e3 19821b (V9)					
Radiated emission test					
Rohde& Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2022/11/30	2025/11/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSU26	200982	2022/07/04	2023/07/03
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101948	2022/11/25	2023/11/24
WEINSCHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b)(1)&§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b)(1), systems operating under the provisions of this sectionshall be operated in a manner that ensure that the public is not exposed to radio frequency energylevel in excess of the Commission's guideline.

Measurement Result

Please refer to SAR test report: RA221230-64588E-SAA.

RSS-102– RF EXPOSURE

Applicable Standard

According to RSS-102, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Result: Compliance.

Please refer to SAR ReportNumber: RA221230-64588E-SAB.

FCC §15.203 & RSS-GEN §6.8– ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.
Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has two internal antenna arrangements which were permanently attached and the gain are 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain	Impedance
Monopole	0dBi	50 Ω

Result: Compliance.

FCC §15.207 (a) & RSS-GEN §8.8 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a) & RSS-Gen §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 µH / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 - AC Power Lines Conducted Emission Limits

Frequency range (MHz)	Conducted limit (dBµV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56[1]	56 to 46[1]
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specifiedin FCC Part 15.207 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by addingLISN VDF (Voltage Division Factor), Cable Loss. The basic equation is as follows:

Factor = LISN VDF + Cable Loss

The "**Over limit**" column of the following data tables indicates the degree of compliance with the applicablelimit. For example, a over limit of -7dB means the emission is 7 dB below the limit. The equation for margincalculation is as follows:

Over limit = Level – Limit
Level= read level + factor

Test Data

Environmental Conditions

Temperature:	23℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Lipa Wu on 2023-02-01.

EUT operation mode:Transmitting (worst case is ANT A,low channel)

AC 120V/60 Hz, Line



Site : Shielding Room
Condition: Line
Job No. : RA221230-64583E-RF
Mode : Charging& Transmitting
Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	9.90	19.75	29.65	55.65	-26.00	Average
2	0.156	9.90	29.01	38.91	65.65	-26.74	QP
3	0.275	9.87	17.93	27.80	50.96	-23.16	Average
4	0.275	9.87	23.95	33.82	60.96	-27.14	QP
5	0.436	9.81	25.98	35.79	47.13	-11.34	Average
6	0.436	9.81	32.71	42.52	57.13	-14.61	QP
7	0.525	9.82	20.55	30.37	46.00	-15.63	Average
8	0.525	9.82	26.52	36.34	56.00	-19.66	QP
9	2.559	9.93	14.46	24.39	46.00	-21.61	Average
10	2.559	9.93	23.32	33.25	56.00	-22.75	QP
11	10.206	10.00	14.84	24.84	50.00	-25.16	Average
12	10.206	10.00	30.18	40.18	60.00	-19.82	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room
Condition: Neutral
Job No. : RA221230-64583E-RF
Mode : Charging& Transmitting
Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.177	9.80	18.33	28.13	54.64	-26.51	Average
2	0.177	9.80	27.10	36.90	64.64	-27.74	QP
3	0.287	9.84	21.25	31.09	50.60	-19.51	Average
4	0.287	9.84	30.72	40.56	60.60	-20.04	QP
5	0.424	9.88	26.46	36.34	47.37	-11.03	Average
6	0.424	9.88	37.08	46.96	57.37	-10.41	QP
7	0.437	9.89	28.74	38.63	47.12	-8.49	Average
8	0.437	9.89	39.00	48.89	57.12	-8.23	QP
9	0.451	9.89	25.44	35.33	46.86	-11.53	Average
10	0.451	9.89	36.47	46.36	56.86	-10.50	QP
11	0.531	9.89	22.08	31.97	46.00	-14.03	Average
12	0.531	9.89	31.97	41.86	56.00	-14.14	QP
13	10.308	10.00	18.08	28.08	50.00	-21.92	Average
14	10.308	10.00	31.25	41.25	60.00	-18.75	QP

FCC §15.205, §15.209&§15.247(d) & RSS-247§ 5.5– RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d) and RSS-247 §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limitsand RSS-247/RSS-Gen limits.

EMI Test Receiver&Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK

For average measurement:

Use the duty cycle factor correction factor method per 15.35(c).
Duty cycle=On time/100milliseconds, On time=N1*L1+N2*L2+…Nn-1*Ln-1+Nn*Ln,
where N1 is number of type 1 pulses, L1 is length of type 1 pulse, etc.
Average Emission Level=Peak Emission Level+20*log(Duty cycle)

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with allinstallation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Factor& Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The "**Over Limit or Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin/Over Limit = Corrected Amplitude/Level-Limit
Corrected Amplitude/Level = Reading + Corrected Factor

Test Data

Environmental Conditions

Temperature:	20~25.9℃
Relative Humidity:	55~58 %
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng on 2023-01-31 for below 1GHzandJason Liu on 2023-01-10 and 2023-02-15for above 1GHz.

EUT operation mode: Transmitting(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientationwas recorded)

30MHz-1GHz: *(worst case is ANT A,low channel)*

Note: when the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.

Horizontal:



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA221230-64583E-RF
Test Mode: Charging+Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	56.050	-10.18	31.54	21.36	40.00	-18.64	Peak
2	136.340	-15.12	36.46	21.34	43.50	-22.16	Peak
3	191.829	-11.28	38.55	27.27	43.50	-16.23	Peak
4	299.316	-9.23	42.83	33.60	46.00	-12.40	Peak
5	514.535	-4.28	29.76	25.48	46.00	-20.52	Peak
6	799.330	-0.34	31.56	31.22	46.00	-14.78	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA221230-64583E-RF
Test Mode: Charging+Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.032	-11.19	33.52	22.33	40.00	-17.67	Peak
2	54.166	-10.34	36.07	25.73	40.00	-14.27	Peak
3	139.545	-15.43	37.44	22.01	43.50	-21.49	Peak
4	298.530	-9.25	34.09	24.84	46.00	-21.16	Peak
5	604.863	-2.31	33.96	31.65	46.00	-14.35	Peak
6	796.881	-0.28	31.94	31.66	46.00	-14.34	Peak

Above 1GHz:

ANT A:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(2407MHz)									
2310	61.92	PK	190	1.4	H	-7.24	54.68	74	-19.32
2310	62.36	PK	6	1.1	V	-7.24	55.12	74	-18.88
2390	71.09	PK	69	2.5	H	-7.22	63.87	74	-10.13
2390	66.84	PK	336	1.1	V	-7.22	59.62	74	-14.38
4814	58.38	PK	326	1.4	H	-3.52	54.86	74	-19.14
4814	58.25	PK	299	1.4	V	-3.52	54.73	74	-19.27
Middle Channel(2450MHz)									
4900	58.95	PK	212	1.5	H	-3.28	55.67	74	-18.33
4900	59.61	PK	124	1.5	V	-3.28	56.33	74	-17.67
High Channel(2475MHz)									
2483.5	76.07	PK	286	1.1	H	-7.20	68.87	74	-5.13
2483.5	71.86	PK	39	1.2	V	-7.20	64.66	74	-9.34
2500	72.64	PK	80	2.5	H	-7.18	65.46	74	-8.54
2500	70.75	PK	6	2.2	V	-7.18	63.57	74	-10.43
4950	58.22	PK	8	1.6	H	-3.04	55.18	74	-18.82
4950	59.05	PK	306	1.6	V	-3.04	56.01	74	-17.99

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/RSS-247		
					Limit (dBμV/m)	Margin (dB)	Comment
Low Channel(2407MHz)							
2310	54.68	H	-20.22	34.46	54	-19.54	Band Edge
2310	55.12	V	-20.22	34.90	54	-19.10	Band Edge
2390	63.87	H	-20.22	43.65	54	-10.35	Band Edge
2390	59.62	V	-20.22	39.40	54	-14.60	Band Edge
4814	54.86	H	-20.22	34.64	54	-19.36	Harmonic
4814	54.73	V	-20.22	34.51	54	-19.49	Harmonic
Middle Channel(2450MHz)							
4900	55.67	H	-20.22	35.45	54	-18.55	Harmonic
4900	56.33	V	-20.22	36.11	54	-17.89	Harmonic
High Channel(2475MHz)							
2483.5	68.87	H	-20.22	48.65	54	-5.35	Band Edge
2483.5	64.66	V	-20.22	44.44	54	-9.56	Band Edge
2500	65.46	H	-20.22	45.24	54	-8.76	Band Edge
2500	63.57	V	-20.22	43.35	54	-10.65	Band Edge
4950	55.18	H	-20.22	34.96	54	-19.04	Harmonic
4950	56.01	V	-20.22	35.79	54	-18.21	Harmonic

Note:

Corrected. Amplitude = Factor + Reading
Margin = Corrected. Amplitude - Limit
Average level= Peak level+ Duty Cycle Corrected Factor

Through observe the test plots below, the maximum hops in 100ms period is 6times(the second high signals from other channel), the worst case duty cycle as below:
Duty cycle = Ton/100ms = 1.625*6/100=0.0975
Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0975 =-20.22

Duty cycle





ANT B:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(2407MHz)									
2310	60.84	PK	312	2.1	H	-7.24	53.60	74	-20.40
2310	61.11	PK	246	1.1	V	-7.24	53.87	74	-20.13
2390	73.10	PK	63	1.6	H	-7.22	65.88	74	-8.12
2390	66.44	PK	41	2	V	-7.22	59.22	74	-14.78
4814	58.38	PK	326	1.4	H	-3.52	54.86	74	-19.14
4814	58.25	PK	299	1.4	V	-3.52	54.73	74	-19.27
Middle Channel(2450MHz)									
4900	57.91	PK	344	1.3	H	-3.28	54.63	74	-19.37
4900	58.01	PK	191	1.3	V	-3.28	54.73	74	-19.27
High Channel(2475MHz)									
2483.5	75.53	PK	32	1.4	H	-7.20	68.33	74	-5.67
2483.5	76.72	PK	151	1.2	V	-7.20	69.52	74	-4.48
2500	71.78	PK	86	1.7	H	-7.18	64.60	74	-9.40
2500	69.74	PK	70	2.4	V	-7.18	62.56	74	-11.44
4950	57.52	PK	80	1.9	H	-3.04	54.48	74	-19.52
4950	57.80	PK	288	1.9	V	-3.04	54.76	74	-19.24

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/RSS-247		
					Limit (dBμV/m)	Margin (dB)	Comment
Low Channel(2407MHz)							
2310	53.60	H	-20.22	33.38	54	-20.62	Band Edge
2310	53.87	V	-20.22	33.65	54	-20.35	Band Edge
2390	65.88	H	-20.22	45.66	54	-8.34	Band Edge
2390	59.22	V	-20.22	39.00	54	-15.00	Band Edge
4814	54.86	H	-20.22	34.64	54	-19.36	Harmonic
4814	54.73	V	-20.22	34.51	54	-19.49	Harmonic
Middle Channel(2450MHz)							
4900	54.63	H	-20.22	34.41	54	-19.59	Harmonic
4900	54.73	V	-20.22	34.51	54	-19.49	Harmonic
High Channel(2475MHz)							
2483.5	68.33	H	-20.22	48.11	54	-5.89	Band Edge
2483.5	69.52	V	-20.22	49.30	54	-4.70	Band Edge
2500	64.60	H	-20.22	44.38	54	-9.62	Band Edge
2500	62.56	V	-20.22	42.34	54	-11.66	Band Edge
4950	54.48	H	-20.22	34.26	54	-19.74	Harmonic
4950	54.76	V	-20.22	34.54	54	-19.46	Harmonic

Note:

Corrected. Amplitude = Factor + Reading
Margin = Corrected. Amplitude - Limit
Average level= Peak level+ Duty Cycle Corrected Factor

Through observe the test plots below, the maximum hops in 100ms period is 6times(the second high signals from other channel), the worst case duty cycle as below:
Duty cycle = Ton/100ms = 1.625*6/100=0.0975
Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0975 =-20.22

Duty cycle



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	5.075 ms	-16.02 dBm		
D1	M1	1	1.625 ms	-0.26 dB		
D2	M1	1	10.55 ms	-0.40 dB		

Date: 10.JAN.2023 18:47:06



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	399.9304 ms	-11.31 dBm		
D1	M1	1	10.5224 ms	0.54 dB		
D2	M1	1	399.9739 ms	0.17 dB		

Date: 15.FEB.2023 16:39:58

1-18GHz

Pre-scan for ANT A

Middle Channel

Horizontal:



Vertical:



18-25GHz

Pre-scan forANT A

Middle Channel

Horizontal:



Vertical:



1-18GHz

Pre-scan for ANT B

Low Channel

Horizontal:



Vertical:



18-25GHz

Pre-scan for ANT B

Low Channel

Horizontal:



Vertical:



FCC §15.247(a) (1)&RSS-247 § 5.1 (b)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems (FHSs) shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel and in Operating mode, RBW was set at 500 kHz, VBW≥ 3RBW max-hold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.



Test Data

Environmental Conditions

Temperature:	27℃
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-02-10.

EUT operation mode: Transmitting

Test Result: Compliant.

Note: According to frequency table in page 7 and inverstigating the hopping channel test in page 42, the minimum channel separation is the worst case which were recorded as below:

ANT A

Test Mode	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result
GFSK					
Hopping	2.046	2.322	1.548	> two-thirds of the 20 dB bandwidth	Pass

ANT B

Test Mode	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result
GFSK					
Hopping	2.052	2.311	1.541	> two-thirds of the 20 dB bandwidth	Pass

Please refer to the below plots:

ANT A

Hop



ANT B

Hop



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.466155 GHz	16.40 dBm		
D1	M1	1	2.052 MHz	0.02 dB		

Date: 10.FEB.2023 14:14:54

FCC §15.247(a) (1)& RSS-GEN § 6.7&RSS-247 § 5.1 (a)–99% OCCUPIED BANDWIDTH & 20dBEMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

The occupied bandwidth or the "99% emission bandwidth" is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the "20 dB bandwidth" is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:
• The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

• The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

• The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.

• The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.
For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data

Environmental Conditions

Temperature:	25℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-01-29.

EUT operation mode: Transmitting

Test Result: Compliant.

ANT A

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)	OBW (MHz)
GFSK	Low	2407	2.295	2.300
	Middle	2450	2.322	2.322
	High	2475	2.389	2.389

ANT B

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)	OBW (MHz)
GFSK	Low	2407	2.300	2.288
	Middle	2450	2.311	2.322
	High	2475	2.300	2.311

Please refer to the below plots:

ANT A

Low Channel



Date: 29.JAN.2023 16:00:25

Middle Channel



Date: 29.JAN.2023 16:01:54

High Channel



Date: 29.JAN.2023 16:03:53

ANT B

Low Channel



Date: 29.JAN.2023 16:07:55

Middle Channel



Date: 29.JAN.2023 16:09:17

High Channel



Date: 29.JAN.2023 16:10:37

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems (FHSs) in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

2. Set the EUT in hopping mode from first channel to last.

3. By using the max-hold function record the quantity of the channel.



Test Data

Environmental Conditions

Temperature:	27℃
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-02-10.

EUT operation mode: Transmitting

Test Result: Compliant.

ANT A

Mode	FrequencyRange (MHz)	Number of Hopping Channel (CH)	Limit (CH)
GFSK	2400-2483.5	20	≥15

ANT B

Mode	FrequencyRange (MHz)	Number of Hopping Channel (CH)	Limit (CH)
GFSK	2400-2483.5	20	≥15

ANT A

Hop



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40695 GHz	16.09 dBm		
D1	M1	1	68.07 MHz	0.13 dB		
M2		1	2.46592 GHz	16.48 dBm		
M3		1	2.46797 GHz	16.24 dBm		

Date: 10.FEB.2023 14:10:55

ANT B

Hop



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40695 GHz	15.99 dBm		
D1	M1	1	68.07 MHz	0.35 dB		
M2		1	2.46604 GHz	16.50 dBm		
M3		1	2.46797 GHz	16.11 dBm		

Date: 10.FEB.2023 14:13:28

FCC §15.247(a) (1) (iii) &RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems (FHSs) in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses



Test Data

Environmental Conditions

Temperature:	25~27℃
Relative Humidity:	54~60%
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-02-14 and 2023-02-15.

EUT operation mode: Transmitting

Test Result: Compliant.

ANT A

Test Mode	Channel	Pulse Time [ms]	Total Hops [Num]	Result[s]	Limit[s]	Verdict
GFSK	Hop	1.692	120	0.203	<=0.4	PASS

ANT B

Test Mode	Channel	Pulse Time [ms]	Total Hops [Num]	Result[s]	Limit[s]	Verdict
GFSK	Hop	1.675	120	0.201	<=0.4	PASS

Note: A period time=0.4*20=8(s), Result=Pulse Time *Total hops; Totalhops = 20*6 =120

ANT A

Pulse time



Date: 14.FEB.2023 18:53:58

Maximum Pulse number in one hop: 6



Date: 15.FEB.2023 11:31:39

TotalHops in 8s



Date: 14.FEB.2023 18:55:40

ANT B

Pulse time



Date: 14.FEB.2023 16:52:37

Maximum Pulse number in one hop: 6



Date: 15.FEB.2023 11:32:51

TotalHops in 8s



Date: 14.FEB.2023 16:53:42

FCC §15.247(b) (1)& RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

For frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-01-10.

EUT operation mode: Transmitting

Test Result: Compliant.

ANT A

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
GFSK	Low	2407	16.72	20.97
	Middle	2450	16.94	20.97
	High	2475	16.88	20.97

ANT B

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
GFSK	Low	2407	16.00	20.97
	Middle	2450	16.81	20.97
	High	2475	16.95	20.97

Note: the antenna gain is 0dBi, the maximum EIRP=16.95dBm+0dBi=16.95dBm<36dBm, so it's compliance with the EIRP limit of ISEDC.

ANT A

Low Channel



Middle Channel



Date: 10.JAN.2023 17:10:08

High Channel



Date: 10.JAN.2023 17:10:24

ANT B

Low Channel



Date: 10.JAN.2023 18:30:54

Middle Channel



Date: 10.JAN.2023 18:33:53

High Channel



Date: 10.JAN.2023 18:34:15

FCC §15.247(d) &RSS-247 § 5.5 - BAND EDGES TESTING

Applicable Standard

According to FCC §15.247(d)&RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))&RSS-Gen.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency spanincluding 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25~27℃
Relative Humidity:	54~60 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-02-14 and 2023-02-15 and 2023-02-17.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

ANT A

GFSK_Low Channel



Date: 14.FEB.2023 18:51:41

GFSK_Hop_Low Channel



Date: 14.FEB.2023 18:48:34

GFSK_High Channel



Date: 14.FEB.2023 18:52:38

GFSK_Hop_High Channel



Date: 14.FEB.2023 18:50:18

ANT B

GFSK_Low Channel



Date: 17.FEB.2023 13:39:43

GFSK_Hop_Low Channel



Date: 15.FEB.2023 13:17:28

GFSK_High Channel



GFSK_Hop_High Channel



******* END OF REPORT *******