

TEST REPORT

Applicant Name: FCC: Porta Phone Company Inc
IC: PORTA PHONE CO., INC.
Address: FCC: 145 Dean Knauss Drive Narragansett, Rhode Island 02882
United States
IC: 145 Dean Knauss Drive Narragansett, RI 02882, United States of America
Report Number: 2401V84617E-RF
FCC ID: B4HEVX2R
IC: 3064A-EVX2R

Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247 ISSUE 3, AUGUST 2023

Sample Description

Product Type: Full Duplex 2.4 GHz Transceiver-Remote
Model No.: EVX2-RS
Multiple Model(s) No.: EVX2-RSW, EVX2-RD, EVX2-RDW
Trade Mark: EVADE Wireless
Date Received: 2024/07/10
Issue Date: 2024/08/08

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Andy Yu

Andy Yu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES.....	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.247 (I) & §1.1307 (B) (1) & §2.1093 - RF EXPOSURE	11
APPLICABLE STANDARD	11
MEASUREMENT RESULT	11
RSS-102 – RF EXPOSURE.....	12
APPLICABLE STANDARD	12
RESULT	12
FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.205, §15.209 & §15.247(D) & RSS-247§ 5.5 - RADIATED EMISSIONS.....	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
FACTOR & OVER LIMIT/MARGIN CALCULATION	16
TEST DATA	16
FCC §15.247(A) (1) & RSS-247 § 5.1 (B) - CHANNEL SEPARATION TEST	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	37
FCC §15.247(A) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (A) - 99% OCCUPIED BANDWIDTH & 20 DB EMISSION BANDWIDTH.....	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	40

FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - QUANTITY OF HOPPING CHANNEL TEST.....	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	44
FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME)	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	46
FCC §15.247(B) (1) & RSS-247§ 5.1(B) & § 5.4(B) - PEAK OUTPUT POWER MEASUREMENT	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	48
FCC §15.247(D) & RSS-247 § 5.5 - BAND EDGES TESTING	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51
EUT PHOTOGRAPHS	54
TEST SETUP PHOTOGRAPHS	55

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401V84617E-RF	Original Report	2024/08/08

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	EVX2-RS, EVX2-RSW, EVX2-RD, EVX2-RDW
FVIN	N/A
Product	Full Duplex 2.4 GHz Transceiver-Remote
Tested Model	EVX2-RS
Multiple Model(s)	EVX2-RSW, EVX2-RD, EVX2-RDW
Frequency Range	2407~2475 MHz
Maximum conducted Peak output power	17.70dBm
Modulation Technique	FLRC
Antenna Specification [#]	0dBi(It is provided by the applicant)
Voltage Range	DC3.7V from battery
Sample number	EVX2-RS: 202M-1 for RF Conducted Test, 203J-1 for Radiated Emissions EVX2-RSW: 203J-2 for Radiated Emissions EVX2-RD: 203J-3 for Radiated Emissions EVX2-RDW: 203J-4 for Radiated Emissions (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A
Note: The Multiple models are electrically identical with the test model except for model No., appearance and the types of audio chips. Please refer to the declaration letter [#] for more detail, which was provided by manufacturer.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Frequency		213.55 Hz(k=2, 95% level of confidence)
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
Unwanted Emission, conducted		1.75 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9 kHz~150 KHz	3.94dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2407	15	2425	30	2443	45	2461
1	2408	16	2426	31	2444	46	2462
2	2409	17	2427	32	2445	47	2466
3	2410	18	2428	33	2446	48	2467
4	2411	19	2429	34	2450	49	2468
5	2412	20	2430	35	2451	50	2469
6	2413	21	2434	36	2452	51	2470
7	2414	22	2435	37	2453	52	2471
8	2418	23	2436	38	2454	53	2472
9	2419	24	2437	39	2455	54	2473
10	2420	25	2429	40	2456	55	2474
11	2421	26	2439	41	2457	56	2475
12	2422	27	2440	42	2458	/	/
13	2423	28	2441	43	2459	/	/
14	2424	29	2442	44	2460	/	/
Note: 1. The equipment has designed 57 channels totally, but only 20 channels selected from the 57 channels active at same time, which were separated by more than 2MHz. 2. EUT was test in channel 0, 34, 56.							

EUT Exercise Software

EUT was configured to testing mode by applicant and power level is default[#].

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emission



SUMMARY OF TEST RESULTS

FCC Rules	ISED Rules	Description of Test	Result
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1093	RSS-102	RF Exposure	Compliant
§15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
§15.207(a)	RSS-Gen §8.8	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209 & §15.247(d)	RSS-247 § 5.5	Radiated Emissions	Compliant
§15.247(a)(1)	RSS- Gen§6.7, RSS-247 § 5.1 (a)	99% Occupied Bandwidth & 20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	RSS-247 § 5.1 (b)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	RSS-247 § 5.1 (d)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	RSS-247 § 5.1 (d)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	RSS-247 § 5.1(b) & § 5.4(b)	Peak Output Power Measurement	Compliant
§15.247(d)	RSS-247 § 5.5	Band edges	Compliant

Not Applicable: EUT only powered by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated emission test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber A Cable 1	N/A	2024/06/18	2025/06/17
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/05/21	2025/05/20
Unknown	Cable	PNG214	1354	2024/05/21	2025/05/20
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2024/06/18	2025/06/17
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	735	2024/06/18	2025/06/17
Unknown	RF Cable	UFA147	219661	2024/06/18	2025/06/17
JD	Multiplex Switch Test Control Set	DT7220FSU	DQ77926	2024/06/18	2025/06/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
RF Conducted Test					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200982	2023/12/18	2024/12/17
R&S	SPECTRUM ANALYZER	FSV40-N	102259	2024/01/16	2025/01/15
Unknown	10dB Attenuator	Unknown	F-03-EM065	2024/06/27	2025/06/26
Unknown	RF Cable	65475	01670515	2024/06/27	2025/06/26

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (B) (1) & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Measurement Result

Please refer to SAR test report: 2401V84617E-SAA.

RSS-102 – RF EXPOSURE

Applicable Standard

According to RSS-102, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Result

Compliance. Please refer to SAR test report: 2401V84617E-SAB.

FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangements which were permanently attached for FHSS and the gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain [#]	Impedance
Monopole	0dBi	50Ω

Result: Compliant

FCC §15.205, §15.209 & §15.247(d) & RSS-247§ 5.5 - RADIATED EMISSIONS


Applicable Standard

FCC §15.205; §15.209; §15.247(d) and RSS-247 §5.5


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits and RSS-247/RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK
Above 1 GHz	Harmonics & Band Edge			
	1MHz	3 MHz	/	PK
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)			
	Other Emissions			
	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Average

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle= On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	22~26 °C
Relative Humidity:	45~54 %
ATM Pressure:	101 kPa

The testing was performed by Anson Su on 2024-07-15 for below 1GHz and Dylan Yang from 2024-07-19 to 2024-07-23 for above 1GHz and Rainbow Zhu from 2024-08-02 to 2024-08-05 for Duty Cycle.

EUT operation mode: Transmitting

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation was recorded.


9 kHz-30MHz: (*Maximum output power mode, Middle channel*)

The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.

30MHz-1GHz: (Maximum output power mode, Middle channel)

For model: EVX2-RS


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	40.08	-11.57	24.34	12.77	40.00	-27.23	QP
2	98.01	-15.96	24.72	8.76	43.50	-34.74	QP
3	131.35	-12.14	25.37	13.23	43.50	-30.27	QP
4	270.37	-13.82	31.70	17.88	46.00	-28.12	QP
5	479.27	-8.82	33.05	24.23	46.00	-21.77	QP
6	838.81	-4.93	28.67	23.74	46.00	-22.26	QP

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	40.56	-13.33	24.21	10.88	40.00	-29.12	QP
2	99.35	-17.06	25.14	8.08	43.50	-35.42	QP
3	122.19	-12.73	25.81	13.08	43.50	-30.42	QP
4	379.25	-11.41	26.45	15.04	46.00	-30.96	QP
5	686.55	-6.72	26.01	19.29	46.00	-26.71	QP
6	838.81	-5.19	28.67	23.48	46.00	-22.52	QP

For model: EVX2-RSW


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	Freq	Factor	Level	Level	Line	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	41.64	-12.56	23.90	11.34	40.00	-28.66 QP
2	99.62	-15.53	24.75	9.22	43.50	-34.28 QP
3	130.72	-12.10	25.33	13.23	43.50	-30.27 QP
4	274.43	-13.67	32.40	18.73	46.00	-27.27 QP
5	479.27	-8.82	33.04	24.22	46.00	-21.78 QP
6	838.81	-4.93	29.31	24.38	46.00	-21.62 QP

Vertical




Site : Chamber A
 Condition : 3m Vertical
 Project Number: 2401V84617E-RF
 Test Mode :
 Tester : Anson Su

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.33	-13.20	24.24	11.04	40.00	-28.96	QP
2	98.31	-17.26	24.92	7.66	43.50	-35.84	QP
3	126.16	-12.64	25.70	13.06	43.50	-30.44	QP
4	370.70	-11.67	26.50	14.83	46.00	-31.17	QP
5	479.27	-9.15	30.69	21.54	46.00	-24.46	QP
6	873.71	-4.98	25.87	20.89	46.00	-25.11	QP

For model: EVX2-RD


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	MHz	dB/m	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	41.77	-12.64	24.23	11.59	40.00	-28.41 QP
2	99.70	-15.51	25.13	9.62	43.50	-33.88 QP
3	131.12	-12.13	25.89	13.76	43.50	-29.74 QP
4	266.26	-13.95	29.69	15.74	46.00	-30.26 QP
5	479.27	-8.82	33.31	24.49	46.00	-21.51 QP
6	838.81	-4.93	27.16	22.23	46.00	-23.77 QP

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.36	-13.22	24.30	11.08	40.00	-28.92	QP
2	99.14	-17.10	24.44	7.34	43.50	-36.16	QP
3	128.79	-12.58	26.85	14.27	43.50	-29.23	QP
4	387.31	-11.18	26.05	14.87	46.00	-31.13	QP
5	479.27	-9.15	29.76	20.61	46.00	-25.39	QP
6	838.81	-5.19	28.06	22.87	46.00	-23.13	QP

For model: EVX2-RDW


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	MHz	dB/m	Level	Line	Limit	
			dBuV	dBuV/m	dBuV/m	dB
1	40.65	-11.93	24.65	12.72	40.00	-27.28 QP
2	97.24	-16.16	24.78	8.62	43.50	-34.88 QP
3	127.61	-12.13	25.22	13.09	43.50	-30.41 QP
4	282.61	-13.39	35.48	22.09	46.00	-23.91 QP
5	479.27	-8.82	32.39	23.57	46.00	-22.43 QP
6	838.81	-4.93	30.17	25.24	46.00	-20.76 QP

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number: 2401V84617E-RF
Test Mode :
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	MHz	dB/m	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	40.79	-13.46	24.58	11.12	40.00	-28.88 QP
2	98.36	-17.26	26.52	9.26	43.50	-34.24 QP
3	158.74	-14.13	27.57	13.44	43.50	-30.06 QP
4	399.38	-10.81	26.58	15.77	46.00	-30.23 QP
5	479.27	-9.15	31.68	22.53	46.00	-23.47 QP
6	722.99	-6.32	30.70	24.38	46.00	-21.62 QP

For model: EVX2-RS

Above 1GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
Low Channel(2407MHz)							
2389.48	62.01	PK	H	-2.93	59.08	74.00	-14.92
2389.36	61.62	PK	V	-2.93	58.69	74.00	-15.31
4814.00	51.06	PK	H	1.69	52.75	74.00	-21.25
4814.00	53.11	PK	V	1.69	54.80	74.00	-19.20
Middle Channel(2450MHz)							
4900.00	52.35	PK	H	1.79	54.14	74.00	-19.86
4900.00	52.67	PK	V	1.79	54.46	74.00	-19.54
High Channel(2475MHz)							
2483.56	67.57	PK	H	-3.17	64.40	74.00	-9.60
2483.82	67.86	PK	V	-3.17	64.69	74.00	-9.31
4950.00	50.04	PK	H	2.77	52.81	74.00	-21.19
4950.00	53.54	PK	V	2.77	56.31	74.00	-17.69

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

Other emissions which were more than 20dB below limit or on noise floor level was not recorded.


Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Corrected Factor (dB)	Average Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel 2407MHz							
2389.48	59.08	H	-22.33	36.75	54.00	-17.25	Bandedge
2389.36	58.69	V	-22.33	36.36	54.00	-17.64	Bandedge
4814.00	52.75	H	-22.33	30.42	54.00	-23.58	Harmonic
4814.00	54.80	V	-22.33	32.47	54.00	-21.53	Harmonic
Middle Channel 2450MHz							
4900.00	54.14	H	-22.33	31.81	54.00	-22.19	Harmonic
4900.00	54.46	V	-22.33	32.13	54.00	-21.87	Harmonic
High Channel 2475MHz							
2483.56	64.40	H	-22.33	42.07	54.00	-11.93	Bandedge
2483.82	64.69	V	-22.33	42.36	54.00	-11.64	Bandedge
4950.00	52.81	H	-22.33	30.48	54.00	-23.52	Harmonic
4950.00	56.31	V	-22.33	33.98	54.00	-20.02	Harmonic

Note: Average level= Peak level+ Duty Cycle Corrected Factor


Worst case duty cycle:

Duty cycle = Ton/100ms = 0.425*18/100=0.0765

Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0765 = -22.33



Test plots for Band Edge Measurements (Radiated):




Test Channel:

2475MHz

Ant. Polar. :

Vertical



Condition : Vertical


Project No.: 2401V84617E-RF


Tester : Dylan


Note : FHSS_2475


		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.823	-3.17	67.86	64.69	74.00	-9.31	Peak


Test plots for Harmonic and Emissions Measurements:















FCC §15.247(a) (1) & RSS-247 § 5.1 (b) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

According to ANSI C63.10-2013 section 7.8.2

1. Set the EUT in transmitting mode, maxhold the channel and in Operating mode, RBW was set at 100 kHz, VBW $\geq$ 3RBW max-hold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

**Test Data****Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	47 %
ATM Pressure:	101 kPa

The testing was performed by Allen Bai on 2024-07-20.

EUT operation mode: Transmitting


Test Result: Compliant

Note: According to frequency table in page 7 and investigating the hopping channel test in page 45, the minimum channel separation is the worst case which were recorded as below:

Test Mode	Test Frequency (MHz)	Channel Separation (MHz)	Limits (MHz)
FLRC	Hop_2450	2.000	1.003

Note: Limit= Two-thirds of the 20 dB bandwidth

Please refer to the below plots:



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 21:14:34

FCC §15.247(a) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (a) - 99% OCCUPIED BANDWIDTH & 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “20 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

Test Procedure

According to ANSI C63.10-2013 section 7.8.7


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	47 %
ATM Pressure:	101 kPa

The testing was performed by Allen Bai on 2024-07-20.

EUT operation mode: Transmitting


Test Result: Compliant

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)	OBW (MHz)
FLRC	Low	2407	1.510	1.404
	Middle	2450	1.504	1.410
	High	2475	1.510	1.404

Please refer to the below plots:


20 dB Emission Bandwidth

Low Channel




ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:25:30

Middle Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:24:46


High Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:24:01


99% Occupied Bandwidth

Low Channel




ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:19:16

Middle Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:19:47

High Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:22:55

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - QUANTITY OF HOPPING CHANNEL TEST


Applicable Standard

Frequency hopping systems (FHSs) in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

According to ANSI C63.10-2013 section 7.8.3

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101 kPa


The testing was performed by Rainbow Zhu on 2024-08-02.

EUT operation mode: Transmitting

Test Result: Compliant

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
FLRC	2400-2483.5	20	≥15

Hop



ProjectNo.:2401V84617E-RF Tester:Rainbow Zhu
Date: 2.AUG.2024 11:09:06

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)


Applicable Standard

Frequency hopping systems (FHSs) in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

According to ANSI C63.10-2013 section 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses



Test Data

Environmental Conditions

Temperature:	25.9~26 °C
Relative Humidity:	45~47 %
ATM Pressure:	101 kPa


The testing was performed by Rainbow Zhu and Allen Bai from 2024-07-20 to 2024-08-05.

EUT operation mode: Transmitting

Test Result: Compliant


Test Frequency (MHz)	Pulse Width (ms)	Observation time (s)	Hopping Numbers in Observation time	Dwell Time (s)	Limit (s)
Hop_2450	7.65	8	20	0.153	0.400
Note: Observation time= Hopping Channel Number $\times$ 0.4= 20 $\times$ 0.4= 8 (s) Pulse Width = Pulse Time* Pulse Number =0.425ms*18= 7.65ms Dwell Time = Pulse Width $\times$ Hopping Numbers in Observation time					

Pulse Time: 0.425ms & Maximum Pulse number in one hop: 18



ProjectNo.:2401V84617E-RF Tester:Rainbow Zhu
 Date: 5.AUG.2024 11:19:29

Hopping Numbers in 8s



ProjectNo.:2401V84617E-RF Tester:Allen Bai
 Date: 20.JUL.2024 21:02:09

FCC §15.247(b) (1) & RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.


For frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

Test Procedure

According to ANSI C63.10-2013 section 7.8.5

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	47 %
ATM Pressure:	101 kPa


The testing was performed by Allen Bai on 2024-07-20.

EUT operation mode: Transmitting

Test Result: Compliant


Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
FLRC	Low	2407	17.42	21
	Middle	2450	17.70	21
	High	2475	17.59	21
Note: EIRP Limit for RSS-247:36dBm The antenna gain=0dBi, the maximum EIRP=17.70dBm<36dBm				

Low Channel




ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:16:25

Middle Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:16:43

High Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:17:04

FCC §15.247(d) & RSS-247 § 5.5 - BAND EDGES TESTING

Applicable Standard


According to FCC §15.247(d) & RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)) & RSS-Gen.

Test Procedure

According to ANSI C63.10-2013 section 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	47 %
ATM Pressure:	101 kPa


The testing was performed by Allen Bai on 2024-07-20.

EUT operation mode: Transmitting

Test Result: Compliant

Conducted Band Edge Result:


FLRC_Low Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai

Date: 20.JUL.2024 20:54:18


FLRC_Hop_Low Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai


Date: 20.JUL.2024 21:07:45

FLRC_High Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 20:52:55

FLRC_Hop_High Channel



ProjectNo.:2401V84617E-RF Tester:Allen Bai
Date: 20.JUL.2024 21:05:51

EUT PHOTOGRAPHS

Please refer to the attachment 2401V84617E-RF External photo and 2401V84617E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401V84617E-RF Test Setup photo.

******* END OF REPORT *******