

TEST REPORT

Applicant Name: FCC: Porta Phone Company Inc
IC: PORTA PHONE CO., INC.
Address: FCC: 145 Dean Knauss Drive Narragansett, Rhode Island
02882 United States
IC: 145 Dean Knauss Drive Narragansett, RI 02882, United
States of America
Report Number: 2601U67572E-RFB
FCC ID: B4HPCDCP
IC: 3064A-PCDCP

Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2;
RSS-247 ISSUE 4, JULY 2025

Sample Description

Product Type: 900 MHz Receiver With Speaker
Model No.: PC-DCP
Multiple Model(s) No.: N/A
Trade Mark: PlayCaller Digital
Date Received: 2026/07/01
Issue Date: 2026/09/04

Test Result:

Pass[▲]

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Wing K Ji

Wing K Ji
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
REQUIREMENTS AND TEST PROCEDURES	10
AC LINE CONDUCTED EMISSIONS	10
RADIATED EMISSIONS	12
20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH	15
CHANNEL SEPARATION TEST	17
QUANTITY OF HOPPING CHANNEL TEST	19
TIME OF OCCUPANCY (DWELL TIME)	21
PEAK OUTPUT POWER MEASUREMENT	23
BAND EDGES	25
CONDUCTED SPURIOUS EMISSION	27
RF EXPOSURE EVALUATION	29
ANTENNA REQUIREMENT	32
TEST DATA AND RESULTS	34
RADIATED EMISSIONS	34
RF CONDUCTED DATA	65
20 dB Emission Bandwidth	66
99% Occupied Bandwidth	69
Channel Separation	72
Number of Hopping Frequency	73
Maximum Conducted Output Power	74
100 kHz Bandwidth of Frequency Band Edge	77
Time of Occupancy (dwell time)	79
Conducted Spurious Emission	83
EUT PHOTOGRAPHS	85
TEST SETUP PHOTOGRAPHS	86

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2601U67572E-RFB	Original Report	2026/09/04

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	PC-DCP
FVIN	PC-DCP
Frequency Range	2402~2480MHz
Transmit Peak Power	0.44dBm
Modulation Technique	BDR (DH1/DH3/DH5): GFSK, EDR (2DH1/2DH3/2DH5): $\pi/4$ -DQPSK EDR (3DH1/3DH3/3DH5): 8DPSK
Antenna Specification[#]	1.0dBi (provided by the applicant)
Voltage Range	DC 3.7V from battery or 5V from charger or 5V from USB port
Sample serial number	3P5M-4 for Radiated Emissions Test 3P5M-3 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model: YNQX30G050500UL Input: 100-240V~50/60Hz 1A Output: 5.0V=5.0A 25.0W

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247 ISSUE 4, July 2025, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024 ▼, RSS-Gen and RSS-247.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		52.29kHz(k=1.96, 95% level of confidence)
RF output power, conducted		1.57dB(k=1.96, 95% level of confidence)
Dwell Time		±1%(k=2, 95% level of confidence)
Conducted Spurious Emission		2.48dB(k=1.96, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.46dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.72dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.66dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Horizontal)	5.10dB(k=2, 95% level of confidence)
	30MHz~1000MHz (Vertical)	6.28dB(k=2, 95% level of confidence)
	1GHz - 6GHz	6.18dB(k=2, 95% level of confidence)
	6GHz - 18GHz	6.62dB(k=2, 95% level of confidence)
	18GHz - 40GHz	6.66dB(k=2, 95% level of confidence)
Temperature		±0.4°C
Humidity		±2%
Supply voltages		DC±0.4%;AC±1%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, test firm registration No.: 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
2	2404	42	2444
...	...	...	...
...	...	...	...
36	2438	75	2477
37	2439	76	2478
38	2440	77	2479
39	2441	78	2480
EUT was tested with Channel 0, 39 and 78.			

EUT Exercise Software

Exercise Software [#]	CyBluetool.exe
Power Level [#]	0x2

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emission Below 1GHz:



For Radiated Emission Above 1GHz:



SUMMARY OF TEST RESULTS

Rules		Description of Test	Result
FCC §1.1307&§2.1093&§15.247 (i)	/	RF Exposure	Compliant
/	RSS-102 § 6.3	SAR Exemption Limits	Compliant
FCC §15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
FCC §15.207(a)	RSS-Gen §8.8	AC Line Conducted Emissions	Not applicable
FCC §15.205, §15.209, §15.247(d)	RSS-247 §6.6, RSS-GEN §8.10	Radiated Emissions	Compliant
FCC §15.247(a)(1)	RSS-247 §6.2.1(a), RSS-GEN §6.7	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliant
FCC §15.247(a)(1)	RSS-247 §6.2.1(b), §6.2.3.1(a)	Channel Separation Test	Compliant
FCC §15.247(a)(1)(iii)	RSS-247 §6.2.3.1(b)	Quantity of Hopping Channel Test	Compliant
FCC §15.247(a)(1)(iii)	RSS-247 §6.2.3.1(b)	Time of Occupancy (Dwell Time)	Compliant
FCC §15.247(b)(1)	RSS-247 §6.2.3.2	Peak Output Power Measurement	Compliant
FCC §15.247(d)	RSS-247 §6.6	Band edges	Compliant
FCC §15.247(d)	RSS-247 §6.6	Conducted Spurious Emission	Compliant

Not Applicable: the device was powered by battery when operating.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2025/09/01	2026/08/31
Sonoma instrument	Pre-amplifier	310 N	186238	2025/09/08	2026/09/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2026/06/26	2029/06/25
Unknown	Chamber A Cable	Cable A1	Cable A1	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A2	Cable A2	2025/09/08	2026/09/07
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Chamber A Cable	Cable A3	Cable A3	2025/09/08	2026/09/07
Unknown	Chamber A Cable	Cable A4	Cable A4	2025/09/08	2026/09/07
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
TDK	Chamber	Chamber A	2#	2026/07/03	2029/07/02
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2025/09/01	2026/08/31
A.H.System	Preamplifier	PAM-0118P	489	2025/09/08	2026/09/07
Schwarzbeck	Horn Antenna	BBHA9120D (1201)	1143	2026/07/15	2027/07/14
Unknown	Chamber B Cable	Cable B1	Cable B1	2025/09/08	2026/09/07
Unknown	Chamber B Cable	Cable B3	Cable B3	2025/09/08	2026/09/07
JD	Filter Switch Unit	DT7220FSU	DS79906	2026/06/23	2027/06/22
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2026/06/23	2027/06/22
Unknown	Chamber B Cable	Cable B6	Cable B6	2026/07/06	2027/07/05
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/09/08	2026/09/07
Electro-Mechanics Co	Horn Antenna	3116	2026	2025/09/18	2028/09/17
Unknown	Chamber B Cable	Cable B4	Cable B4	2025/09/17	2026/09/16
Unknown	Chamber B Cable	Cable B5	Cable B5	2025/09/17	2026/09/16
Audix	EMI Test software	E3	191218 V9(c)	NCR	NCR
TDK	Chamber	Chamber B	1#	2026/07/06	2029/07/05
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2026/08/04	2027/08/03
Unknown	10dB Attenuator	Unknown	F-03-EM224	2026/06/24	2027/06/23
JD	JD Auto Test software	NA	1.0.0.3769	NCR	NCR

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


REQUIREMENTS AND TEST PROCEDURES

AC Line Conducted Emissions

Applicable Standard

FCC §15.207(a), RSS-GEN § 8.8

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207 & RSS-Gen.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


Radiated Emissions

Applicable Standard


FCC §15.205; §15.209; §15.247(d); RSS-247§ 6.6; RSS-GEN § 8.10


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.247, RSS-247, RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	120 kHz	500 kHz	/	PK	Peak
Above 1 GHz	Harmonics				
	1MHz	3 MHz	/	PK	Peak
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)				
	Band Edge & Other Emissions				
	1MHz	3 MHz	/	PK	Peak
	1MHz	≥10 Hz	/	Average	Peak

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

20 dB Emission Bandwidth & 99% Occupied Bandwidth

According to FCC §15.247(a) (1):

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to RSS-247 § 6.2.1 (a), RSS-Gen § 6.7:

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system's RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

The 20 dB bandwidth is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.


The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “–xx dB down” requirement; that is, if the requirement calls for measuring the –20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max-hold.

- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Channel Separation Test

According to FCC §15.247(a) (1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to RSS-247 § 6.2.1 (b):

The hopping channel carrier frequencies shall be separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

According to RSS-247 § 6.2.3.1 (a):

FHS operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

Test Procedure


Test Method: ANSI C63.10a-2024 Clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq 1/10^{\text{th}}$ the RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A spectral plot of the data shall be included in the test report.

Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the carrier separation need only be measured for one of those modulation schemes or data rates.



Note 1: The limit is $2/3 \times 20$ dB bandwidth

Note 2: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Quantity of Hopping Channel Test

Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

According to RSS-247 § 6.2.3.1 (b):

FHS operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 s within a period of 0.4 s, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

Test Procedure

Test Method: ANSI C63.10a-2024 Clause 7.8.3


The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq 1/10^{\text{th}}$ the RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A spectral plot of the data shall be included in the test report.

Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the number of channels need only be measured for one of those modulation schemes or data rates.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Time of Occupancy (Dwell Time)

Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

According to RSS-247 § 6.2.3.1 (b):

FHS operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 s within a period of 0.4 s, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.4


Use the following spectrum analyzer settings to determine the dwell time per hop:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected transmission time per hop.
- c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this.
- d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel.
- e) Detector function: Peak.
- f) Trace: Clear-write, single sweep.
- g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers.

To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time.

The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is $3 / 0.5 \times 10$, or 60 hops.

The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Peak Output Power Measurement

Applicable Standard

According to FCC §15.247(b) (1):

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

According to RSS-247§6.2.3.2:

The following transmitter output power and e.i.r.p. requirements shall apply:


- a. if the hopset uses 75 or more hopping channels, the maximum peak conducted output power shall not exceed 1.0 W.
- b. if the hopset uses less than 75 hopping channels the maximum peak conducted output power shall not exceed 0.125 W.
- c. the e.i.r.p. shall not exceed 4 W, except as provided in sections 6.5 a) and b).

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Frequency hopping shall be disabled for this test. Use the following spectrum analyzer settings:

- a) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- b) RBW > 20 dB bandwidth of the emission being measured.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow trace to stabilize.
- h) Use the marker-to-peak function to set the marker to the peak of the emission.
- i) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- j) A spectral plot of the test results and setup description shall be included in the test report.



Note 1: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

Note 2: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Band Edges

Applicable Standard

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


According to RSS-247 § 6.6,

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device, or hybrid system is operating,, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power– based on either an RF conducted or a radiated measurement– provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.7.2 & Clause 6.10

- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products that fall outside of the authorized band of operation.
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: No faster than coupled (auto) time.
- 5) Resolution bandwidth: 100 kHz.
- 6) Video bandwidth: 300 kHz.
- 7) Detector: Peak.
- 8) Trace: Max-hold.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Conducted Spurious Emission

Applicable Standard

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 § 6.6,

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device, or hybrid system is operating,, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power– based on either an RF conducted or a radiated measurement– provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.7.1

To demonstrate compliance with the relative out-of-band emissions requirements conducted spurious emissions shall be measured for the transmit frequencies, per 5.5 and 5.6, and at the maximum transmit powers. Frequency hopping shall be disabled for this test with the exception of measurements at the allocated band-edges which shall be repeated with hopping enabled.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The frequency range of testing shall span 30 MHz to 10 times the operating frequency and this may be done in a single sweep or, to aid resolution, across a number of sweeps. The resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector.

The limit is based on the highest in-band level across all channels measured using the same instrument settings (resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector). To help clearly demonstrate compliance a display line may be set at the required offset (typically 20 dB) below the highest in-band level. Where the highest in-band level is not clearly identified in the out-of-band measurements a separate spectral plot showing the in-band level shall be provided.



Note 1: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the worst case cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

Note 2: Offset (12.5dB) = Attenuator (10dB) + Cable loss (2.5dB)

RF EXPOSURE EVALUATION

RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max tune-up conducted power [#] (dBm)	Max tune-up conducted power [#] (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BT	2402-2480	1.0	1.26	5	0.4	3.0	Yes

Result: Compliant

SAR EXEMPTION LIMITS

Applicable Standard

According to RSS-102 Issue 6 § (6.3), Devices operating at or below the applicable output power levels (adjusted for tune-up tolerance) specified in table 11, based on the separation distance, are exempt from SAR evaluation. The separation distance, defined as the distance between the user and/or bystander and the antenna and/or radiating element of the device or the outer surface of the device, shall be less than or equal to 20 cm for these exemption limits to apply.

Table 11: Power limits for exemption from routine SAR evaluation based on the separation distance

Frequency (MHz)	≤ 5 mm (mW)	10 mm (mW)	15 mm (mW)	20 mm (mW)	25 mm (mW)	30 mm (mW)	35 mm (mW)	40 mm (mW)	45 mm (mW)	> 50 mm (mW)
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296
835	21	32	41	54	72	96	129	172	228	298
1900	6	10	18	33	57	92	138	194	257	323
2450	3	7	16	32	56	89	128	170	209	245
3500	2	6	15	29	50	72	94	114	134	158
5800	1	5	13	23	32	41	54	74	102	128

The exemption limits in table 11 are based on measurements and simulations of half-wave dipole antennas at separation distances of 5 mm to 50 mm from a flat phantom, which provides a SAR value of approximately 0.4 W/kg for 1 g of tissue.

For limb-worn devices where the 10 gram of tissue applies, the exemption limits for routine evaluation in table 11 are multiplied by a factor of 2.5.

For controlled-use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in table 11 are multiplied by a factor of 5.

When the operating frequency of the device is between two frequencies located in table 11, linear interpolation shall be applied for the applicable separation distance. If the separation distance of the device is between two distances located in table 11, linear interpolation may be applied for the applicable frequency. Alternatively, the limit corresponding to the smaller distance may be employed. For example, in case of a 7 mm separation distance, either use the exception value for a 5 mm separation distance or interpolate between the limits corresponding to 5 mm and 10 mm separation distances.

For implanted medical devices, the exemption limit for routine SAR evaluation is set at an output power of 1 mW, regardless of frequency.

The SAR levels from exempted transmitters shall be included in the compliance assessment and the determination of the TER. Detailed guidance is included in sections 7.1.8 and 8.2.2.1.

Test Result:

Mode	Frequency (MHz)	Gain [#] (dBi)	Max tune-up conducted power [#] (dBm)	Max tune-up EIRP [#]		Distance (mm)	Exemption Limit (mW)	SAR Evaluation Exemption
				(dBm)	(mW)			
BT	2402-2480	1.0	1.0	2.0	1.58	5	2.97	Yes

Note 1: $(2480-2450)/(3500-2450) = (3-P)/(3-2)$, the exemption limit of 2480MHz is $P = 2.97\text{mW}$

Note 2: The max tune-up conducted power[#] and antenna gain[#] were declared by the applicant

Result: Compliant

ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

According to RSS-Gen §6.8,

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISSED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has an internal antenna arrangements which was permanently attached and the antenna gain[#] is 1.0dBi, fulfill the requirement of this section. Please refer to the EUT photos

Type	Antenna Gain [#]	Impedance	Frequency Range
PCB	1.0dBi	50Ω	2400~2500MHz

Result: Compliant.

TEST DATA AND RESULTS


Radiated Emissions

Environmental Conditions

Temperature (°C)	23.1-23.8	Relative Humidity (%)	56-60
ATM Pressure (kPa):	101.5	Test engineer:	Hugh Li & Anson Su
Test date:	2026/8/15		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, BDR(GFSK) 2441MHz) Above 1GHz: Transmitting		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded. 3. After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded. 4. The spurious emission from 9 kHz-30MHz of IC RSS-GEN standard, the unit of final result on the test plots are dBμV/m, so the limit should be added by 51,5 dB from dBμA/m to dBμV/m.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number : 2601U67572E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.011	32.07	24.42	56.49	126.63	-70.14	Peak
2	0.019	30.52	22.24	52.76	121.87	-69.11	Peak
3	0.027	29.09	21.35	50.44	119.01	-68.57	Peak
4	0.045	26.96	21.52	48.48	114.60	-66.12	Peak
5	0.066	24.80	20.08	44.88	111.21	-66.33	Peak
6	0.115	21.11	19.08	40.19	106.38	-66.19	Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number : 2601U67572E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.494	6.51	33.14	39.65	73.73	-34.08	Peak
2	0.618	4.95	34.78	39.73	71.75	-32.02	Peak
3	0.809	2.63	33.94	36.57	69.35	-32.78	Peak
4	0.943	1.63	33.09	34.72	67.99	-33.27	Peak
5	1.137	0.82	33.24	34.06	66.33	-32.27	Peak
6	1.527	-0.28	31.87	31.59	63.72	-32.13	Peak


30MHz-1GHz_Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2601U67572E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 120/500kHz
Tester : Anson Su

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	34.32	-7.85	27.32	19.47	40.00	-20.53	Peak
2	128.45	-11.02	28.00	16.98	43.50	-26.52	Peak
3	165.27	-12.48	28.75	16.27	43.50	-27.23	Peak
4	273.35	-11.37	28.68	17.31	46.00	-28.69	Peak
5	500.30	-5.56	28.40	22.84	46.00	-23.16	Peak
6	641.17	-2.93	30.10	27.17	46.00	-18.83	Peak

30MHz-1GHz_Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2601U67572E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 120/500kHz
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	Level	Level	Line	Limit	
			dBuV	dBuV/m	dBuV/m	dB	
1	33.05	-7.38	27.48	20.10	40.00	-19.90	Peak
2	126.33	-10.79	27.61	16.82	43.50	-26.68	Peak
3	174.88	-13.35	29.31	15.96	43.50	-27.54	Peak
4	277.46	-11.11	28.16	17.05	46.00	-28.95	Peak
5	445.05	-6.87	28.29	21.42	46.00	-24.58	Peak
6	665.80	-3.07	29.30	26.23	46.00	-19.77	Peak

Above 1GHz:

Frequency (MHz)	Reading (dBμV)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Maximum output power mode, BDR(GFSK)							
Low Channel							
4804	51.77	PK	H	-8.58	43.19	74	-30.81
4804	52.27	PK	V	-8.58	43.69	74	-30.31
Middle Channel							
4882	52.56	PK	H	-8.6	43.96	74	-30.04
4882	52.53	PK	V	-8.6	43.93	74	-30.07
High Channel							
4960	52.61	PK	H	-8.63	43.98	74	-30.02
4960	52.15	PK	V	-8.63	43.52	74	-30.48

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit


The other spurious emission which is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

Test plots:

1-25GHz (Listed with the worst case test plot)


1-4G_Horizontal_BT_DH5_2480MHz



Condition : Horizontal
 Project No. : 2601U67572E-RF
 Tester : Hugh Li
 Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
 Note : BT_1DH5_2480

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3866.875	-8.72	49.05	40.33	74.00	-33.67	Peak


1-4G_Vertical_BT_DH5_2480MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 3739.375	-8.79	48.87	40.08	74.00	-33.92	Peak


4-18G_Horizontal_Peak_BT_DH5_2480MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 4960.000	-8.63	52.61	43.98	74.00	-30.02 Peak
2 17996.500	10.74	49.46	60.20	74.00	-13.80 Peak


4-18G_Horizontal_Average_BT_DH5_2480MHz



Condition : Horizontal
 Project No. : 2601U67572E-RF
 Tester : Hugh Li
 Spectrum setting: Average reading:RBW:1MHz VBW:500Hz Detector:Peak
 Note : BT_1DH5_2480

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17991.250	10.64	37.16	47.80	54.00	-6.20 Average


4-18G_Vertical_Peak_BT_DH5_2480MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4960.000	-8.63	52.15	43.52	74.00	-30.48	Peak
2 17893.250	9.29	50.51	59.80	74.00	-14.20	Peak


4-18G_Vertical_Average_BT_DH5_2480MHz



Condition : Vertical
 Project No. : 2601U67572E-RF
 Tester : Hugh Li
 Spectrum setting: Average reading:RBW:1MHz VBW:500Hz Detector:Peak
 Note : BT_1DH5_2480

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBUV/m	dBUV/m	dB	
1 17996.500	10.74	37.09	47.83	54.00	-6.17	Average


18-25G_Horizontal_Peak_BT_DH5_2480MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 19928.500	17.81	39.34	57.15	74.00	-16.85 Peak


18-25G_Horizontal_Average_BT_DH5_2480MHz



Condition : Horizontal
 Project No. : 2601U67572E-RF
 Tester : Hugh Li
 Spectrum setting: Average reading:RBW:1MHz VBW:500Hz Detector:Peak
 Note : BT_1DH5_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	19824.380	17.75	27.15	44.90	54.00	-9.10	Average


18-25G_Vertical_Peak_BT_DH5_2480MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 19816.500	17.75	38.90	56.65	74.00	-17.35 Peak

18-25G_Vertical_Average_BT_DH5_2480MHz




Condition : Vertical
 Project No. : 2601U67572E-RF
 Tester : Hugh Li
 Spectrum setting: Average reading:RBW:1MHz VBW:500Hz Detector:Peak
 Note : BT_1DH5_2480

Freq Factor		Read	Limit	Over	Remark
		Level	Level	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 19832.250	17.76	26.82	44.58	54.00	-9.42 Average

Band Edge


Left band edge_Horizontal_Peak_BT_DH5_2402MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2402

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2382.215	-11.86	66.95	55.09	74.00	-18.91	Peak
2	2390.000	-11.94	59.78	47.84	74.00	-26.16	Peak


Left band edge_Horizontal_Average_BT_DH5_2402MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : BT_1DH5_2402

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2381.874	-11.85	63.74	51.89	54.00	-2.11	Average
2	2390.000	-11.94	47.94	36.00	54.00	-18.00	Average


Left band edge_Vertical_BT_DH5_2402MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2402

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2381.792	-11.85	63.77	51.92	74.00	-22.08 Peak
2	2390.000	-11.94	58.87	46.93	74.00	-27.07 Peak


Right band edge_Horizontal_BT_DH5_2480MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-12.27	60.59	48.32	74.00	-25.68	Peak
2 2499.617	-12.38	64.68	52.30	74.00	-21.70	Peak


Right band edge_Vertical_BT_DH5_2480MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_1DH5_2480

Freq Factor		Read		Limit	Over	Remark
MHz	dB/m	Level	Level	Line	Limit	
		dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-12.27	60.44	48.17	74.00	-25.83 Peak
2	2485.120	-12.28	62.37	50.09	74.00	-23.91 Peak


Left band edge_Horizontal_Peak_BT_2DH5_2402MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_2DH5_2402

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2382.329	-11.86	65.94	54.08	74.00	-19.92 Peak
2	2390.000	-11.94	59.33	47.39	74.00	-26.61 Peak

Left band edge_Horizontal_Average_BT_2DH5_2402MHz



Condition : Horizontal

Project No. : 2601U67572E-RF


Tester : Hugh Li

Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak

Note : BT_2DH5_2402

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2381.939	-11.86	59.21	47.35	54.00	-6.65	Average
2	2390.000	-11.94	47.90	35.96	54.00	-18.04	Average


Left band edge_Vertical_BT_2DH5_2402MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_2DH5_2402

Freq Factor		Read	Limit	Over	Remark
MHz	dB/m	Level	Level	Line	
		dBuV	dBuV/m	dBuV/m	dB
1	2381.451 -11.85	63.04	51.19	74.00	-22.81 Peak
2	2390.000 -11.94	59.31	47.37	74.00	-26.63 Peak


Right band edge_Horizontal_BT_2DH5_2480MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_2DH5_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-12.27	61.26	48.99	74.00	-25.01	Peak
2	2499.782	-12.38	63.69	51.31	74.00	-22.69	Peak


Right band edge_Vertical_BT_2DH5_2480MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_2DH5_2480

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-12.27	59.62	47.35	74.00	-26.65	Peak
2 2499.880	-12.38	62.76	50.38	74.00	-23.62	Peak


Left band edge_Horizontal_Peak_BT_3DH5_2402MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2382.410	-11.86	65.90	54.04	74.00	-19.96 Peak
2	2390.000	-11.94	59.28	47.34	74.00	-26.66 Peak


Left band edge_Horizontal_Average_BT_3DH5_2402MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Average reading: RBW:1MHz VBW:500Hz Detector:Peak
Note : BT_3DH5_2402

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2381.939	-11.86	59.18	47.32	54.00	-6.68	Average
2	2390.000	-11.94	47.78	35.84	54.00	-18.16	Average


Left band edge_Vertical_BT_3DH5_2402MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2402

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2381.825	-11.85	63.28	51.43	74.00	-22.57	Peak
2 2390.000	-11.94	58.96	47.02	74.00	-26.98	Peak


Right band edge_Horizontal_BT_3DH5_2480MHz



Condition : Horizontal
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2480

Freq Factor		Read Level		Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-12.27	60.03	47.76	74.00	-26.24 Peak
2	2499.722	-12.38	64.00	51.62	74.00	-22.38 Peak

Right band edge_Vertical_BT_3DH5_2480MHz



Condition : Vertical
Project No. : 2601U67572E-RF
Tester : Hugh Li
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT_3DH5_2480

Freq Factor		Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-12.27	59.80	47.53	74.00	-26.47	Peak
2 2499.790	-12.38	62.75	50.37	74.00	-23.63	Peak

RF Conducted data**Test Information:**

Sample No.:	3P5M-3	Test Date:	2026/08/27~2026/09/03
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jackson Zhu & Barry Feng	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.5-26.1	Relative Humidity: (%)	52-53	ATM Pressure: (kPa)	100.1-100.5
----------------------	-----------	------------------------------	-------	------------------------	-------------


20 dB Emission Bandwidth

Mode	Channel	Result (MHz)
DH1	Low Channel	0.950
	Middle Channel	0.935
	High Channel	0.965
2DH1	Low Channel	1.342
	Middle Channel	1.357
	High Channel	1.357
3DH1	Low Channel	1.297
	Middle Channel	1.297
	High Channel	1.281


DH1_Low




DH1_Middle




DH1_High




2DH1_Low




2DH1_Middle



2DH1_High




3DH1_Low




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:38:28

3DH1_Middle



ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:39:03

3DH1_High




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:40:11

99% Occupied Bandwidth


Mode	Channel	99% OBW (MHz)
DH1	Low Channel	0.894
	Middle Channel	0.891
	High Channel	0.891
2DH1	Low Channel	1.188
	Middle Channel	1.191
	High Channel	1.191
3DH1	Low Channel	1.188
	Middle Channel	1.185
	High Channel	1.185

DH1_Low




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27,AUG,2026 13:33:37

DH1_Middle




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27,AUG,2026 13:35:13

DH1_High




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27,AUG,2026 13:35:57

2DH1_Low




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27,AUG,2026 13:37:03

2DH1_Middle




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27,AUG,2026 13:37:39

2DH1_High




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27,AUG,2026 13:38:01

3DH1_Low




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:38:31

3DH1_Middle



ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:39:07

3DH1_High




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:40:15

Channel Separation

Mode	Channel	Result (MHz)	Limit (MHz)	Verdict
DH1	Middle Channel	1.003	0.905	Pass

Note: Only the BDR (GFSK) mode result is reported since EDR ($\pi/4$ -DQPSK) and EDR (8DPSK) modes have the exact same channel plan, and the limit is the maximum 20dB bandwidth *2/3.

DH1_Middle




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27_AUG_2026 14:07:27

Number of Hopping Frequency


Mode	Channel	Result	Limit	Verdict
DH1	Hopping Channel	79	15	Pass
2DH1	Hopping Channel	79	15	Pass
3DH1	Hopping Channel	79	15	Pass

DH1_Hopping




ProjectNo.:2601U67572E-RF Tester:Harry Feng
Date: 27.AUG.2026 14:41:45

2DH1_Hopping



ProjectNo.:2601U67572E-RF Tester:Harry Feng
Date: 27.AUG.2026 14:57:34

3DH1_Hopping




ProjectNo.:2601U67572E-RF Tester:Harry Feng
Date: 27.AUG.2026 15:15:09


Maximum Conducted Output Power

Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	EIRP (dBm)	EIRP Limit (IC) (dBm)	Verdict
DH1	2402	-0.32	21.00	0.68	36.00	Pass
	2441	0.44	21.00	1.44	36.00	Pass
	2480	0.44	21.00	1.44	36.00	Pass
2DH1	2402	-1.50	21.00	-0.50	36.00	Pass
	2441	-0.88	21.00	0.12	36.00	Pass
	2480	-1.00	21.00	0.00	36.00	Pass
3DH1	2402	-1.00	21.00	0.00	36.00	Pass
	2441	-0.37	21.00	0.63	36.00	Pass
	2480	-0.51	21.00	0.49	36.00	Pass


DH1_Low




DH1_Middle




DH1_High




2DH1_Low




2DH1_Middle




2DH1_High




3DH1_Low



3DH1_Middle




3DH1_High




100 kHz Bandwidth of Frequency Band Edge

DH1_Low




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:33:54

DH1_High




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:36:09

DH1_Hopping_Lower




ProjectNo.:2601U67572E-RF Tester:Jackson Zhu
Date: 3.SEP.2026 11:07:04

DH1_Hopping_Upper




ProjectNo.:2601U67572E-RF Tester:Jackson Zhu
Date: 3.SEP.2026 11:07:56

2DH1_Low




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:37:19

2DH1_High




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 13:38:13


2DH1_Hopping_Lower




2DH1_Hopping_Upper




3DH1_Low




3DH1_High



3DH1_Hopping_Lower



3DH1_Hopping_Upper



Time of Occupancy (dwell time)


Test Mode	Channel	BurstWidth (ms)	TotalHops (Num)	Result (s)	Limit (s)	Verdict
DH1	Hopping Channel	0.399	320	0.128	≤ 0.4	Pass
DH3	Hopping Channel	1.664	160	0.266	≤ 0.4	Pass
DH5	Hopping Channel	2.913	100	0.291	≤ 0.4	Pass
2DH1	Hopping Channel	0.406	320	0.130	≤ 0.4	Pass
2DH3	Hopping Channel	1.664	160	0.266	≤ 0.4	Pass
2DH5	Hopping Channel	2.918	100	0.292	≤ 0.4	Pass
3DH1	Hopping Channel	0.406	320	0.130	≤ 0.4	Pass
3DH3	Hopping Channel	1.664	180	0.300	≤ 0.4	Pass
3DH5	Hopping Channel	2.918	110	0.321	≤ 0.4	Pass

Note 1: A period time = $0.4 \times 79 = 31.6(S)$, Result = BurstWidth * Totalhops

Note 2: Totalhops = Hopping Number in $3.16s \times 10$


Note 3: Hopping Number in $3.16s$ = Total of highest signals in $3.16s$ (Second high signals were other channel)

DH1_Hopping




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 14:15:07

DH1_Hopping




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 14:15:31

DH3_Hopping




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 14:19:04

DH3_Hopping




ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 14:19:23

DH5_Hopping



ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 14:19:35

DH5_Hopping



ProjectNo.:2601U67572E-RF Tester:Barry Feng
Date: 27.AUG.2026 14:19:58