



GE Interlogix

**GE Interlogix, Inc.
Telephone Interface Module
B4Z-786A-DTIM
Certification**

10/16/02 10:34 AM	FCC ID: B4Z-786A-DTIM	Page 1 of 24
H:\DTIM\parts\In doc form\FCC_REPTA.DOC		



GE Interlogix

**Telephone Interface Module
B4Z-786A-DTIM**

10/16/2002

**GE Interlogix, Inc.
2266 North Second Street
North Saint Paul, MN 55109
(651) 777-2690**

FCC_REPTA.DOC 10/16/02 10:34 AM	FCC ID: B4Z-786A-DTIM	Page 2 of 24
------------------------------------	------------------------------	--------------

1. INTRODUCTION	4
2. STATEMENT OF COMPLIANCE	4
3. LAB MEASUREMENTS DISCUSSION / TEST NOTES	7
3.1 Test Notes	7
3.1.1 Transmissions shall cease within 5 seconds of activation [§15.231(a)(2)]	7
3.1.2 Supervisory Calculation [§15.231(a)(3)]	9
3.1.3 Duty Cycle Correction Factor [§15.231(b)(2) and §15.35(c)]	9
3.1.4 Bandwidth Measurement [§15.231(c)]	12
3.1.5 Emissions Measurements	16
3.1.5.1 Radiated Emissions Summary	16
3.1.5.2 FCC Emissions Calculation	16
3.1.5.2.1 Terms	16
3.1.5.2.2 Example Calculation	17
3.1.5.3 Radiated Emissions	18
3.1.5.4 Forbidden Bands	18

1. Introduction

This device is a wireless Telephone Interface Module transmitter for use in a wireless security system. The unit is self-contained and powered by one 3.6 Volt Lithium battery. The transmitter's frequency is crystal controlled and is not adjustable by the user. The device measures approximately 4" in width, 14.5" in length (including the antennas), and 1.125" in height. The unit weighs approximately 7.3 ounces with the battery.

We are requesting Certification under FCC Rules, Part 15, Subpart C, Paragraph 15.231.

Please send comments/suggestions on the report format to:
Rick.Conner@GE-Interlogix.com

2. Statement of Compliance

§2.907 Certification

This is an application for certification

§2.911 Application

- a) This is an application and has been filed electronically with form 731.
- b) All information required has been supplied.
- c) The applicant has signed the application (electronically).
- d) The technical data has been signed.
(See Radiated Emissions)
- e) Applicant signature block on electronic form 731 completed by officer of the company or authorized company personnel.
- f) The appropriate fee has been paid electronically with VISA on 10/3/2002.

§2.915 Grant

This application demonstrates that all applicable technical standards have been met and a grant of this application will serve the public interest.

§2.925 Label

Each piece of equipment for which authorization will be granted will be uniquely identified with "FCC ID: B4Z-786A-DTIM" The required statement will appear with the FCC ID on the product and, although not required, in the installation instructions. See Exhibit A, PDF file *id_label.pdf*



§2.947

Measurement Procedure

- a) The measurement procedure follows ANSI C63.4 procedure.
Procedural notes are contained in the laboratory report.
- d) A list of test equipment used is contained in the laboratory report.

§2.948

Description of Measurement Facilities

Measurements were performed at TUV Testing Services Open Test Site. The FCC keeps a full description of the measurement facilities on file. TUV's acceptance and approval is dated as December 5, 1993 in a letter received from the FCC.

The address of the test facility is:

TUV Product Service
19035 Wild Mountain Road
Taylors Falls, MN 55084-1758

Phone: 651-638-0297
Contact: Joel Schneider
Test Engineer in Charge

See Exhibit F, PDF file *test_pho.pdf* for sketch of measurement setup

§2.1033

Application for Certification

- a) Form 731 has been electronically filed on 10/04/02. Items that did not apply were left blank.
- b) This technical report contains the following information where applicable.
 - 1) Full name and mailing address of manufacturer and applicant for certification:
GE Interlogix, Inc.
2266 North Second Street
North Saint Paul, MN 55109
 - 2) FCC Identifier:
B4Z-786A-DTIM
 - 3) Copy of installation instructions:
See Exhibit G, PDF file: *user_man.pdf*
 - 4) Brief Description of circuit functions and device operation:
See Exhibit I, PDF file *op_desc.pdf*
See Exhibit D, PDF file *schemat.pdf* for schematics (page 1) and parts placement (page 2) diagrams.

FCC_REPTA.DOC 10/16/02 10:34 AM	FCC ID: B4Z-786A-DTIM	Page 5 of 24
------------------------------------	------------------------------	--------------



- 5) Block Diagram
See Exhibit C, PDF file *block.pdf*.
- 6) Report of the measurements of radiation and conducted emissions:
This document.
- 7) Photographs
External:
See Exhibit B, PDF file *extern.pdf*
Internal:
See Exhibit H, PDF file *intern.pdf*
- 8) Peripheral or Accessory devices:
This is not applicable since this device is stand-alone product.
- 9) Transition Rules
This application is not pursuant to the transition rules of §15.37
- 10) Emergency Broadcast decoding:
This is not applicable to device in this application.
- 11) Application for direct sequence spread spectrum devices...
This is not applicable to device in this application.
- 12) Application for scanning receivers...
This is not applicable to device in this application.
- c) Composite Systems
This is not applicable to device in this application.

3. Lab Measurements Discussion / Test Notes

3.1 Test Notes

3.1.1 Transmissions shall cease within 5 seconds of activation [§15.231(a)(2)]


In the event of an alarm condition, 8 packets are sent in the transmission. The packet duration is, at most, 30 mS, see **Duty Cycle Correction Factor** [§15.231(b)(2) and §15.35(c)]. The time between packets random between 100 mS and 450 mS so the length of the longest transmission is:

$$8*30\text{mS} + 7*450\text{mS} = 3.39 \text{ seconds.}$$

The following plot shows an 8-packet transmission that concludes in less than 5 seconds.



GE Interlogix



3.1.2 Supervisory Calculation [§15.231(a)(3)]

As permitted, this device will transmit three packets for supervision purposes. The inter-packet delay is a random time between 100 mS and 450 mS. The packet itself may be as long as 30 ms depending on the data sent. The longest time to conclude a supervisory transmission is then:

$$3 * 30 \text{ mS} + 2 * 450 \text{ mS} = 990 \text{ mS}$$

3.1.3 Duty Cycle Correction Factor [§15.231(b)(2) and §15.35(c)]

The transmitter employs amplitude modulation and transmits 80 bits. Each bit, except for one, has an “ON” time of 122 μ S. One bit has an on time of 366 μ S. The total on time of a single packet is:

$$79 * 122 \mu\text{S} + 366 \mu\text{S} = 10.00 \text{ mS}.$$

Only one packet is sent in any given 100 mS window for a duty cycle correction factor of:

$$20 * \text{LOG}(10.00/100) = -20.00 \text{ dB}$$

The maximum allowed correction factor is 20 dB.

The following plots show:

1. Single packet in 100 mS window.
2. Expanded view of a packet with a duration of 23.89 mS



GE Interlogix

08:27:47 OCT 1, 2002

RL 0.00 dBm

MKR #1 ΔSWT 23.89 msec

ATTEN 10 dB

37.10 dB


10.00 dB/DIV

MARKER

23.89 msec

37.10 dB

1



CENTER 319.508 000 MHz

SPAN 0 Hz

*RB 300 kHz

*VB 100 kHz

*ST 30.00 msec



GE Interlogix

(p) 08:19:40 OCT 1, 2002


RL 0.00 dBm

MKR #1 SWT 4.125 msec

ATTEN 10 dB

-18.15 dBm

10.00 dB/DIV



CENTER 319.508 000 MHz

SPAN 0 Hz

*RB 300 kHz

*VB 100 kHz

*ST 100.0 msec



Bandwidth Measurement [§15.231(c)]

Bandwidth Measurements were made in peak mode, using a Hewlett Packard Spectrum Analyzer, model number 70000.

The spectrum analyzer 20 dB skirt bandwidth is 3.4 KHz.

The allowed 20 dB bandwidth is 0.25% of center frequency.

Estimated signal bandwidth = Measured signal bandwidth - analyzer bandwidth.


Center Frequency MHz	Measured 20 dB Bandwidth in KHz	Estimated 20 dB signal Bandwidth in KHz	FCC allowed 20 dB Bandwidth in KHz
319.5	41.3	38.9	799

The following three plots show:

1. Bandwidth of carrier without modulation
2. Bandwidth of signal with modulation, 200 KHz span
3. Bandwidth of signal with modulation, 200 MHz span



GE Interlogix





GE Interlogix

08:51:31 OCT 1, 2002

RL 0.00 dBm

MKR #1 Δ FRQ 42.3 kHz

ATTEN 10 dB
10.00 dB/DIV


-0.31 dB

MARKER Δ

42.3 kHz

-0.31 dB

1



CENTER 319.508 0 MHz

SPAN 200.0 kHz


RB 2.15 kHz

VB 3.00 kHz

ST 141.9 msec



GE Interlogix



3.1.4 Emissions Measurements

3.1.4.1 Radiated Emissions Summary

The Telephone Interface Module passes FCC Rules Part 15, Subpart C, Paragraph 15.231. The highest fundamental radiated emission was .2 dB below the FCC limit at 319.42 MHz. The highest spurious emission measurement was 11.3 dB below the FCC limit at 638.92 MHz. The highest forbidden band emission was 4.78 dB below the FCC limit at 2875.52 MHz.

3.1.4.2 FCC Emissions Calculation

3.1.4.2.1 Terms

Term	Abbreviation	Units	Description
Analyzer Reading	AR	dB μ V	The power reading read directly from the analyzer without any correction for cabling or receive antenna.
Duty Cycle Correction	DC	dB	Correction for averaging measurement, see Duty Cycle Correction Factor [§15.231(b)(2) and §15.35(c)]
Antenna Factor	AF	dB	Calibration factor for measurement antenna which converts from dB μ V measured with antenna to the field strength received by the antenna in dB μ V/M.
Cable Loss	CL	dB	Amount of power lost in cable (and connectors, if any) between antenna and analyzer
Pre-Amp	PA	dB	Gain in pre-amp

3.1.4.2.2 Example Calculation

AR = 99.3 dBμV

AF = 13.9 dB

CL = 3.8 dB

DC = 20 dB

PA=26.2 dB

The field strength for comparison to FCC limits is found to be:

$$AR + AF + CL - DC - PA = 99.3 + 13.9 + 3.8 - 20 - 26.2 = 70.8 \text{ dB}\mu\text{V/M}$$

Alternatively, the AR + AF + CL - PA is compared to the FCC limit + DC. This number is often written to the right of measurement data on the test results. For example, the FCC limit for ITI transmitters at 319.5 MHz is approximately 95.8 dBμV/M. The limit from §15.231(b) with linear interpolation yields a limit, without consideration for duty cycle, of approximately 75.8 dBμV/M.

To convert to μV/M the following equation is used:

$$\mu\text{V/M} = \text{INVLOG}(\text{dB}\mu\text{V/M} / 20)$$

For the above example, 70.8 dBμV/M is 3,467.369μV/M

The average ON time field strength of each packet, as shown on page 11, has an upper level of 95.6dBuV/M and a lower level, which is 37.1db down, is 58.5dBuV/M.

Calculate the average Field Strength of each packet follows:

$$95.6\text{dBuV/M} = 60255.96\mu\text{V/M}$$

$$58.5\text{dBuV/M} = 841.3951\mu\text{V/M}$$

$$20 * \text{LOG}(60255.96\mu\text{V/M} + 841.3951\mu\text{V/M})$$

$$20 * \text{LOG}(61097.3551\mu\text{V/M}) = 95.7204482\text{dBuV/M}$$

$$\text{Average Field Strength} = 95.7\text{dBuV/M}$$



3.1.4.3 Radiated Emissions

The highest fundamental emission along with the three highest spurious and restricted band emissions are listed below as per ANSI C63.4 paragraph 10.1.8.2. Emissions from 0.009 MHz to the tenth harmonic were measured as per FCC Rules Part 15, Subpart C, Paragraph 15.33(a). Emission limits were derived from §15.231(b).

Frequency	Analyzer Reading	Duty Cycle Correction	Cable Loss	Antenna Factor	Pre-Amp	Field Strength	Field Strength	FCC Limit
MHz	dBuV	dB	dB	dB	dB	dBuV/M	uV/M	uV/M
319.42	80.40	20	1.6	13.6	0	75.60	6,026	6,229
638.92	70.00	20	2.3	19.8	27.6	44.50	168	623
425.92	56.80	20	1.8	16.2	27.7	27.10	23	623
2875.59	40.00	20	4.9	31.5	27.1	29.30	29	623

3.1.4.4 Forbidden Bands

Noise floor of spectrum analyzer with antenna factors and duty cycle correction converted to $\mu\text{V/M}$ at approximately one meter.

All measurements were taken with an HP 8566B Spectrum Analyzer. The bandwidth was 100 KHz for measurements below 1000 MHz. The bandwidth was 1 MHz for measurements above 1000 MHz. The video filter was off.

The noise floor measurements are summarized in the table below. See also the test data included in this report.



Frequency Range								
Low Limit	High Limit	Noise Floor Reading	Duty Cycle Corr	Field Strength	Field Strength	FCC Limit @ 3M	FCC Limit @ 1M	
MHz	MHz	dBuV	dB	dBuV/M	uV/M	uV/M	uV/M	
0.09000	0.11000	N/A	20	N/A	N/A	2400/F		
0.49500	0.50500	N/A	20	N/A	N/A	2400/F		
2.13750	2.19050	N/A	20	N/A	N/A	30	90	
4.12500	4.12800	N/A	20	N/A	N/A	30	90	
4.17725	4.17775	N/A	20	N/A	N/A	30	90	
4.20725	4.20775	N/A	20	N/A	N/A	30	90	
6.21500	6.21800	N/A	20	N/A	N/A	30	90	
6.26775	6.26825	N/A	20	N/A	N/A	30	90	
6.31175	6.31225	N/A	20	N/A	N/A	30	90	
8.29100	8.29400	N/A	20	N/A	N/A	30	90	
8.36200	8.36600	N/A	20	N/A	N/A	30	90	
8.37625	8.38675	N/A	20	N/A	N/A	30	90	
8.41425	8.41475	N/A	20	N/A	N/A	30	90	
12.29000	12.29300	N/A	20	N/A	N/A	30	90	
12.51975	12.52025	N/A	20	N/A	N/A	30	90	
12.57675	12.57725	N/A	20	N/A	N/A	30	90	
13.36000	13.41000	N/A	20	N/A	N/A	30	90	
16.42000	16.42300	N/A	20	N/A	N/A	30	90	
16.69475	16.69525	N/A	20	N/A	N/A	30	90	
16.80425	16.80475	N/A	20	N/A	N/A	30	90	
25.50000	25.67000	N/A	20	N/A	N/A	30	90	
37.50000	38.25000	23.00	20	3.0	1.4	100	300	
73.00000	74.60000	17.20	20	-2.8	0.7	100	300	
74.80000	75.20000	19.00	20	-1.0	0.9	100	300	
108.00000	121.94000	14.50	20	-5.5	0.5	150	450	
123.00000	138.00000	14.50	20	-5.5	0.5	150	450	
149.90000	150.05000	14.50	20	-5.5	0.5	150	450	
156.52475	156.52525	14.50	20	-5.5	0.5	150	450	
156.70000	156.90000	14.50	20	-5.5	0.5	150	450	
162.01250	167.17000	14.50	20	-5.5	0.5	150	450	
167.72000	173.20000	14.50	20	-5.5	0.5	150	450	
240.0	285.0	21.80	20	1.8	1.2	200	600	
322.0	335.4	21.80	20	1.8	1.2	200	600	
399.9	410.0	21.80	20	1.8	1.2	200	600	
608.0	614.0	21.80	20	1.8	1.2	200	600	
960.0	1240.0	21.80	20	1.8	1.2	500	1500	
1300.0	1427.0	36.80	20	16.8	6.9	500	1500	
1435.0	1626.5	38.00	20	18.0	7.9	500	1500	
1645.5	1646.5	40.90	20	20.9	11.1	500	1500	
1660.0	1710.0	40.90	20	20.9	11.1	500	1500	
1718.8	1722.2	43.70	20	23.7	15.3	500	1500	
2200.0	2300.0	41.60	20	21.6	12.0	500	1500	
2310.0	2390.0	41.60	20	21.6	12.0	500	1500	
2483.5	2500.0	41.60	20	21.6	12.0	500	1500	
2655.0	2900.0	41.60	20	21.6	12.0	500	1500	
3260.0	3267.0	41.60	20	21.6	12.0	500	1500	
3332.0	3339.0	41.60	20	21.6	12.0	500	1500	
3345.8	3358.0	41.60	20	21.6	12.0	500	1500	
3600.0	4400.0	41.60	20	21.6	12.0	500	1500	

The following 4 pages contain the test data:

Radiated Electromagnetic Emissions



Test Report #:	4981 Run 01	Test Area:	LTS 3m	
Test Method:	N/A	Test Date:	27-Sep-2002	
EUT Model #:	55-786E TELEPHONE INTERFACE MODULE	EUT Power:	3.6VDC	
EUT Serial #:		Temperature:	20	°C
Manufacturer:	GE INTERLOGIX	Relative Humidity:	60	%
EUT Description:	TELEPHONE INTERFACE MODULE	Air Pressure:	99	kPa
Notes:	TRANSMITTER SCAN		Page:	1 of 4

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
RBW = 100KHZ BELOW 1GHZ AND RBW = 1MHZ ABOVE 1GHZ.						
ALL READINGS MAXIMIZED IN PEAK.						
106.41	77.9 Pk	0.9 / 8.9 / 27.9	59.8	V / 1.0 / 0.0	N/A	N/A
319.42	80.4 Pk	1.6 / 13.6 / 0.0	95.6	V / 1.4 / 90.0	N/A	N/A
319.42	80.4 Pk	1.6 / 13.6 / 0.0	95.6	H / 1.0 / 0.0	N/A	N/A
212.92	53.8 Pk	1.4 / 10.9 / 0.0	66.0	V / 1.0 / 0.0	N/A	N/A
425.92	56.8 Pk	1.8 / 16.2 / 27.7	47.1	V / 1.0 / 0.0	N/A	N/A
532.42	52.4 Pk	2.0 / 17.9 / 27.6	44.7	V / 1.0 / 0.0	N/A	N/A
638.92	70.0 Pk	2.3 / 19.8 / 27.6	64.5	V / 1.0 / 0.0	N/A	N/A
745.42	39.9 Pk	2.4 / 21.1 / 27.5	35.9	V / 1.0 / 0.0	N/A	N/A
851.92	44.8 Pk	2.6 / 22.5 / 27.2	42.7	V / 1.0 / 0.0	N/A	N/A
958.42	64.1 Pk	2.9 / 23.2 / 27.2	63.0	H / 1.0 / 0.0	N/A	N/A
1065.00	34.0 Pk	2.9 / 22.4 / 27.2	32.1	H / 1.0 / 0.0	N/A	N/A
1171.50	34.2 Pk	3.2 / 23.5 / 27.1	33.8	H / 1.0 / 0.0	N/A	N/A
1278.00	43.7 Pk	3.4 / 24.8 / 27.5	44.4	H / 1.0 / 0.0	N/A	N/A
1384.50	34.8 Pk	3.4 / 25.1 / 27.5	35.8	H / 1.0 / 0.0	N/A	N/A
1491.00	33.5 Pk	3.4 / 26.1 / 27.3	35.8	V / 1.0 / 0.0	N/A	N/A
1597.50	39.8 Pk	3.5 / 26.5 / 27.4	42.4	H / 1.0 / 0.0	N/A	N/A
1704.00	34.0 Pk	3.7 / 28.0 / 27.0	38.7	V / 1.0 / 0.0	N/A	N/A
1810.50	35.9 Pk	3.8 / 27.8 / 27.2	40.3	H / 1.0 / 0.0	N/A	N/A
1917.00	44.0 Pk	4.1 / 28.3 / 26.9	49.5	H / 1.0 / 0.0	N/A	N/A
2023.50	34.6 Pk	4.1 / 29.7 / 27.2	41.2	H / 1.0 / 0.0	N/A	N/A
2130.00	34.6 Pk	4.1 / 29.9 / 27.3	41.4	H / 1.0 / 0.0	N/A	N/A
2236.50	38.0 Pk	4.3 / 30.1 / 26.9	45.5	H / 1.0 / 0.0	N/A	N/A
2343.00	35.6 Pk	4.4 / 30.4 / 26.8	43.6	H / 1.0 / 0.0	N/A	N/A
2449.50	33.8 Pk	4.5 / 30.6 / 26.8	42.0	H / 1.0 / 0.0	N/A	N/A
2556.00	36.4 Pk	4.5 / 30.8 / 27.0	44.8	H / 1.0 / 0.0	N/A	N/A

Tested by: RMJ Printed Signature

Reviewed by: Printed Signature

Radiated Electromagnetic Emissions



Test Report #:	<u>4981 Run 01</u>	Test Area:	<u>LTS 3m</u>	
Test Method:	<u>N/A</u>	Test Date:	<u>27-Sep-2002</u>	
EUT Model #:	<u>55-786E TELEPHONE INTERFACE MODULE</u>	EUT Power:	<u>3.6VDC</u>	
EUT Serial #:				Temperature: <u>20</u> °C
Manufacturer:	<u>GE INTERLOGIX</u>	Relative Humidity: <u>60</u> %		
EUT Description:	<u>TELEPHONE INTERFACE MODULE</u>	Air Pressure: <u>99</u> kPa		
Notes:	<u>TRANSMITTER SCAN</u>			Page: <u>2</u> of <u>4</u>

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
2662.50	33.7 Pk	4.7 / 31.0 / 27.0	42.4	H / 1.0 / 0.0	N/A	N/A
2769.00	34.2 Pk	4.8 / 31.2 / 27.0	43.2	H / 1.0 / 0.0	N/A	N/A
2875.52	40.0 Pk	4.9 / 31.5 / 27.1	49.2	H / 1.0 / 0.0	N/A	N/A
2982.02	33.6 Pk	5.0 / 31.7 / 27.5	42.9	H / 1.0 / 0.0	N/A	N/A
3088.52	33.6 Pk	5.2 / 31.9 / 28.2	42.5	H / 1.0 / 0.0	N/A	N/A
3195.02	33.7 Pk	5.4 / 32.1 / 28.2	43.0	H / 1.0 / 0.0	N/A	N/A
END OF SCAN.						

Tested by: RMJ
Printed Signature

Reviewed by:
Printed Signature

Radiated Electromagnetic Emissions



Test Report #:	4981 Run 01	Test Area:	LTS 3m	
Test Method:	N/A	Test Date:	27-Sep-2002	
EUT Model #:	55-786E TELEPHONE INTERFACE MODULE	EUT Power:	3.6VDC	
EUT Serial #:		Temperature:	20	°C
Manufacturer:	GE INTERLOGIX	Relative Humidity:	60	%
EUT Description:	TELEPHONE INTERFACE MODULE	Air Pressure:	99	kPa
Notes:	TRANSMITTER SCAN			Page: 3 of 4

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
---------------	-----------------	------------------------------	-----------------	-----------------------------	---------------	---------------

***** MEASUREMENT SUMMARY *****						
106.41	77.9 Pk	0.9 / 8.9 / 27.9	59.8	V / 1.0 / 0.0	N/A	N/A
212.92	53.8 Pk	1.4 / 10.9 / 0.0	66.0	V / 1.0 / 0.0	N/A	N/A
319.42	80.4 Pk	1.6 / 13.6 / 0.0	95.6	H / 1.0 / 0.0	N/A	N/A
425.92	56.8 Pk	1.8 / 16.2 / 27.7	47.1	V / 1.0 / 0.0	N/A	N/A
532.42	52.4 Pk	2.0 / 17.9 / 27.6	44.7	V / 1.0 / 0.0	N/A	N/A
638.92	70.0 Pk	2.3 / 19.8 / 27.6	64.5	V / 1.0 / 0.0	N/A	N/A
745.42	39.9 Pk	2.4 / 21.1 / 27.5	35.9	V / 1.0 / 0.0	N/A	N/A
851.92	44.8 Pk	2.6 / 22.5 / 27.2	42.7	V / 1.0 / 0.0	N/A	N/A
958.42	64.1 Pk	2.9 / 23.2 / 27.2	63.0	H / 1.0 / 0.0	N/A	N/A
1065.00	34.0 Pk	2.9 / 22.4 / 27.2	32.1	H / 1.0 / 0.0	N/A	N/A
1171.50	34.2 Pk	3.2 / 23.5 / 27.1	33.8	H / 1.0 / 0.0	N/A	N/A
1278.00	43.7 Pk	3.4 / 24.8 / 27.5	44.4	H / 1.0 / 0.0	N/A	N/A
1384.50	34.8 Pk	3.4 / 25.1 / 27.5	35.8	H / 1.0 / 0.0	N/A	N/A
1491.00	33.5 Pk	3.4 / 26.1 / 27.3	35.8	V / 1.0 / 0.0	N/A	N/A
1597.50	39.8 Pk	3.5 / 26.5 / 27.4	42.4	H / 1.0 / 0.0	N/A	N/A
1704.00	34.0 Pk	3.7 / 28.0 / 27.0	38.7	V / 1.0 / 0.0	N/A	N/A
1810.50	35.9 Pk	3.8 / 27.8 / 27.2	40.3	H / 1.0 / 0.0	N/A	N/A
1917.00	44.0 Pk	4.1 / 28.3 / 26.9	49.5	H / 1.0 / 0.0	N/A	N/A
2023.50	34.6 Pk	4.1 / 29.7 / 27.2	41.2	H / 1.0 / 0.0	N/A	N/A
2130.00	34.6 Pk	4.1 / 29.9 / 27.3	41.4	H / 1.0 / 0.0	N/A	N/A
2236.50	38.0 Pk	4.3 / 30.1 / 26.9	45.5	H / 1.0 / 0.0	N/A	N/A
2343.00	35.6 Pk	4.4 / 30.4 / 26.8	43.6	H / 1.0 / 0.0	N/A	N/A
2449.50	33.8 Pk	4.5 / 30.6 / 26.8	42.0	H / 1.0 / 0.0	N/A	N/A
2556.00	36.4 Pk	4.5 / 30.8 / 27.0	44.8	H / 1.0 / 0.0	N/A	N/A
2662.50	33.7 Pk	4.7 / 31.0 / 27.0	42.4	H / 1.0 / 0.0	N/A	N/A
2769.00	34.2 Pk	4.8 / 31.2 / 27.0	43.2	H / 1.0 / 0.0	N/A	N/A
2875.52	40.0 Pk	4.9 / 31.5 / 27.1	49.2	H / 1.0 / 0.0	N/A	N/A

Tested by: RMJ Printed Signature

Reviewed by: Printed Signature

TÜV
PRODUCT SERVICE

Temperature:	20	°C
Relative Humidity:	60	%
Air Pressure:	99	kPa
Page:	4 of 4	

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	DELTA1 N/A	DELTA2 N/A
2982.02	33.6 Pk	5.0 / 31.7 / 27.5	42.9	H / 1.0 / 0.0	N/A	N/A
3088.52	33.6 Pk	5.2 / 31.9 / 28.2	42.5	H / 1.0 / 0.0	N/A	N/A
3195.02	33.7 Pk	5.4 / 32.1 / 28.2	43.0	H / 1.0 / 0.0	N/A	N/A

Reviewed by: _____ Printed _____ Signature _____