

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. THE MINIMUM HEIGHT OF THE REGISTERED TRADEMARK SYMBOL SHALL BE 1/32 OF AN INCH. WHEN THE OVERALL DIAMETER OF THE UL MARK IS LESS THAN 3/8 OF AN INCH, THE TRADEMARK SYMBOL MAY BE OMITTED IF IT IS NOT LEGIBLE TO THE NAKED EYE. THE FONT FOR THE UL SYMBOL IS TO BE HELVETICA CONDENSED MEDIUM BLACK.
2. THE FONT FOR THE TRADEMARK SYMBOL IS TO BE HELVETICA CONDENSED MEDIUM.
3. BAR CODE SHOWN IS TO BE FOR APPROXIMATE SIZE AND POSITION ONLY.
4. LABEL MUST BE PRINTED USING AN APPROVED UL MARKING SYSTEM.

S/N: 123456789123AA

YEAR →

DAY OF YEAR →

SHIFT →

PLANT →

LINE →

MODEL ID →

FONT: 0.10" TALL ARIAL

FONT: 0.05" TALL ARIAL

FONT: 0.07" TALL ARIAL

FONT: 0.07" TALL ARIAL

OVERHEAD DOOR

Residential Door Operator

(MODEL NUMBER)

S/N: 123456789123AA

PAT www.overheaddoor.com/patents



1-800-929-3667 OR WWW.OVERHEADDOOR.COM

SEE NOTE 2

SEE NOTE 1



VOLTAGE (FONT: 0.07" TALL ARIAL)
(BOX FOR POSITION ONLY, DO NOT PRINT)

CURRENT (FONT: 0.07" TALL ARIAL)
(BOX FOR POSITION ONLY, DO NOT PRINT)

FCC: 889-BLEWMM
1C, 2133A-BLEWMM

ASSEMBLY LOCATION:
"ASSEMBLED IN MEXICO" OR "ASSEMBLED IN USA"
FONT: 0.07" TALL ARIAL
(BOX FOR POSITION ONLY, DO NOT PRINT)

FREQUENCY (FONT: 0.07" TALL ARIAL)
(BOX FOR POSITION ONLY, DO NOT PRINT)


PRINTED ON LABEL

MODEL NUMBER	VOLTAGE	FREQUENCY	CURRENT	DESCRIPTION (REF)
MODEL 9020H	120V	60Hz	4A	OHD 9020H - PRO RESIDENTIAL
MODEL 9120H	120V	60Hz	4A	OHD 9120H ICM/BBU - PRO RESIDENTIAL

P/N 39922-A

PLOTTED: 5/17/19

THE DRAWINGS AND ALL OTHER INFORMATION CONTAINED HEREIN ARE THE PROPERTY OF GENIE OVERHEAD DOOR CORPORATION. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF GENIE OVERHEAD DOOR CORPORATION. DISCLOSURE OF ANY INFORMATION IN WHOLE OR IN PART TO ANYONE WITHOUT PRIOR WRITTEN CONSENT OF GENIE OVERHEAD DOOR CORPORATION IS STRICTLY PROHIBITED. LICENSE OR AUTHORIZATION TO USE IT FOR QUALITY DESIGN PURPOSES ONLY. NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF GENIE OVERHEAD DOOR CORPORATION.		UNLESS OTHERWISE SPECIFIED INTERPRET DIMS & TOLS PER ASME Y14.5M ALL DIMS ARE IN INCHES DO NOT SCALE DIMS: DECIMAL WITH SYMBOL ARE CRITICAL TO QUALITY DESIGN. DIMS IN PARETHESIS ARE APPLICABLE INFERENCE.		UNLESS OTHERWISE SPECIFIED TOLERANCES: X = ±.1 XX = ±.01 XXX = ±.005 ANGULAR = ±1° HOLES: < Ø.251 = ±.003 Ø.251-Ø.500 = ±.003 > Ø.500 = ±.003 ALL GEOMETRY GOVERNED BY 3D CAD DATABASE		APPROVALS DATE DRAWN DANP 7/9/2012 CHECKED WDR 5/17/19 APPROVED RSM 5/20/19 MATERIAL FINISH		DESCRIPTION SPEC, PRINTING, JACKSHAFT MODEL LABEL, OHD		GENIE A SUBSIDIARY OF OVERHEAD DOOR CORPORATION MT. HOPE, OHIO	
SIZE DWG NO. C 39922				SCALE 3:1				SHEET 1 OF 1			



ENG F 20-11C (FORM 1RE) A

