

	Mode	Position	Distance (mm)	CH	Max. Rate Power + 1 Tolerance
			GSM850 (Head)		
			GSM850 (Body-Worn)		

Tested HSTNH-F606V SAR at the worst case position.

Mode	Position	Distance (mm)	CH	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Scaling	Averaged SAR over 1g (W/kg)		Plot page
								Measured	Reported	
GSM850 (Head)	Re Cheek	-	190	836.6	33.50	31.69	151.71%	0.229	0.347	-
GSM850 (Body-Worn)	Back side	10	190	836.6	33.50	31.69	151.71%	0.356	0.540	-
GPRS850 (Hotspot) (1Dn4UP)	Front side	10	251	848.8	27.50	26.65	121.62%	0.497	0.604	-



































































































































































































































































































































































































































































































































































































































































































































































































Report No. : EN/2017/10007
Page : 476 of 479

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at





