

FCC Test Report

(PART 24)

Report No.: RF180125C14-5

FCC ID: B94HNQ10CPD

Test Model: HSN-Q10C

Received Date: Feb. 05, 2018

Test Date: Mar. 21, 2018 ~ May 23, 2018

Issued Date: Jun. 01, 2018

Applicant: HP Inc.

Address: 3390 East Harmony Road, Fort Collins, Colorado 80528, United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C

**FCC Registration /
Designation Number:** 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Test Site And Instruments	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Configuration of System under Test	9
3.2.1 Description of Support Units	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	12
3.5 General Description of Applied Standards	12
4 Test Types and Results	13
4.1 Output Power Measurement	13
4.1.1 Limits of Output Power Measurement	13
4.1.2 Test Procedures	13
4.1.3 Test Setup	14
4.1.4 Test Results	15
4.2 Frequency Stability Measurement	20
4.2.1 Limits of Frequency Stability Measurement	20
4.2.2 Test Procedure	20
4.2.3 Test Setup	20
4.2.4 Test Results	21
4.3 Occupied Bandwidth Measurement	28
4.3.1 Test Procedure	28
4.3.2 Test Setup	28
4.3.3 Test Result	29
4.4 Band Edge Measurement	33
4.4.1 Limits of Band Edge Measurement	33
4.4.2 Test Setup	33
4.4.3 Test Procedures	33
4.4.4 Test Results	34
4.5 Peak to Average Ratio	41
4.5.1 Limits of Peak to Average Ratio Measurement	41
4.5.2 Test Setup	41
4.5.3 Test Procedures	41
4.5.4 Test Results	42
4.6 Conducted Spurious Emissions	46
4.6.1 Limits of Conducted Spurious Emissions Measurement	46
4.6.2 Test Setup	46
4.6.3 Test Procedure	46
4.6.4 Test Results	47
4.7 Radiated Emission Measurement	68
4.7.1 Limits of Radiated Emission Measurement	68
4.7.2 Test Procedure	68
4.7.3 Deviation from Test Standard	68
4.7.4 Test Setup	69
4.7.5 Test Results	70
5 Pictures of Test Arrangements	94
Appendix – Information on the Testing Laboratories	95

Release Control Record

Issue No.	Description	Date Issued
RF180125C14-5	Original Release	Jun. 01, 2018

1 Certificate of Conformity

Product: Notebook Computer

Brand: HP

Test Model: HSN-Q10C

Sample Status: Production Unit

Applicant: HP Inc.

Test Date: Mar. 21, 2018 ~ May 23, 2018

Standards: FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Evonne Liu, **Date:** Jun. 01, 2018
Evonne Liu / Specialist

Approved by : Dylan Chiou, **Date:** Jun. 01, 2018
Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1046 24.232(d)	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	Pass	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -26.67 dB at 5700 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site And Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
HORN Antenna ETS	3117	00034128	Dec. 14, 2017	Dec. 13, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 07, 2017	Jul. 06, 2018
Preamplifier Agilent	310N	187226	Jun. 23, 2017	Jun. 22, 2018
Preamplifier Agilent	83017A	MY39501357	Jun. 23, 2017	Jun. 22, 2018
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 23, 2017	Jun. 22, 2018
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 23, 2017	Jun. 22, 2018
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jun. 28, 2017	Jun. 27, 2019
Radio Communication Analyzer Anritsu	MT8820C	6201010284	Dec. 28, 2017	Dec. 27, 2018
Temperature & Humidity Chamber	GTH-120-40-CP-A R	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 30, 2017	Jun. 29, 2018

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Notebook Computer	
Brand	HP	
Test Model	HSN-Q10C	
Status of EUT	Production Unit	
Power Supply Rating	20 or 15 or 12 or 9 or 5 Vdc (Adapter)	
Modulation Type	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range	WCDMA	1852.4 ~ 1907.6 MHz
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz
Max. EIRP Power	WCDMA	56.89 mW
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	50.12 mW
	LTE Band 2 (Channel Bandwidth: 3 MHz)	50.35 mW
	LTE Band 2 (Channel Bandwidth: 5 MHz)	50.82 mW
	LTE Band 2 (Channel Bandwidth: 10 MHz)	51.17 mW
	LTE Band 2 (Channel Bandwidth: 15 MHz)	51.29 mW
	LTE Band 2 (Channel Bandwidth: 20 MHz)	52.24 mW
Emission Designator	WCDMA	4M08F9W
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1M10G7D
	LTE Band 2 (Channel Bandwidth: 3 MHz)	2M71W7D
	LTE Band 2 (Channel Bandwidth: 5 MHz)	4M50G7D
	LTE Band 2 (Channel Bandwidth: 10 MHz)	8M99G7D
	LTE Band 2 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 2 (Channel Bandwidth: 20 MHz)	18M0W7D
Antenna Type	Refer to Note as below	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:

1. The WWAN module (Brand: Fibocom, Model: L850-GL) was installed in the EUT.
2. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	hp	TPN-LA12	I/P: 100-240 Vac, 50-60 Hz, 1.6 A O/P: 20 Vdc, 3.25 A, 15 Vdc, 4.33 A, 12 Vdc, 5 A, 9 Vdc, 3 A, 5 Vdc, 3 A

3. The antenna information is listed as below.


Ant. Type	Manuf.	Parts Number	Antenna Gain							
			LTE 2 / LTE 25 / WCDMA Band II	LTE 4 / LTE 66 / WCDMA Band IV	LTE 5 / LTE 26 / WCDMA Band V	LTE 7	LTE 12 / LTE 17	LTE 13	LTE 30	LTE 41
PIFA	INPAQ	Main Ant.: DQ6LB020017 (WA-P-LTE8LTE12LBB-02-001) Aux Ant.: DQ6LB020017 (WA-P-LTE8LTE12LBB-02-001)	-6.19	-5.79	-5.86	-4.9	-5.21	-4.32	-3.68	-4.9

Antenna Type	Vendor	Part Number	Antenna Gain (dBi)			
			Laptop PC Mode			
			WLAN 2.4GHz	WLAN 5.2GHz	WLAN 5.5GHz	WLAN 5.8GHz
PIFA	INPAQ	WLAN Main Antenna: DQ6LB020509 (WA-P-LBB-02-059) WLAN Aux Antenna: DQ6LB020509 (WA-P-LBB-02-059)	1.66	0.54	0.56	-0.21
			Tablet PC Mode			
			WLAN 2.4GHz	WLAN 5.2GHz	WLAN 5.5GHz	WLAN 5.8GHz
			-0.36	3.36	2.21	3.08


4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below.

Band	EIRP	Radiated Emission
WCDMA	X-plane	NB-axis
LTE Band 2	X-plane	Z-axis

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
-	Frequency Stability	9262 to 9538	9262, 9538	WCDMA
-	Occupied Bandwidth	9262 to 9538	9262, 9400, 9538	WCDMA
-	Band Edge	9262 to 9538	9262, 9538	WCDMA
-	Peak to Average Ratio	9262 to 9538	9262, 9400, 9538	WCDMA
-	Conducted Emission	9262 to 9538	9262, 9400, 9538	WCDMA
-	Radiated Emission	9262 to 9538	9262, 9400, 9538	WCDMA

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	18607 to 19193	18607, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 19185	3 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 19150	10 MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 19125	15 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 19100	20 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	18607 to 19193	18607	1.4 MHz	QPSK	1 RB / 0 RB Offset
			19193	1.4 MHz	QPSK	6 RB / 0 RB Offset
		18615 to 19185	18615	3 MHz	QPSK	1 RB / 0 RB Offset
			19185	3 MHz	QPSK	15 RB / 0 RB Offset
		18625 to 19175	18625	5 MHz	QPSK	1 RB / 0 RB Offset
			19175	5 MHz	QPSK	25 RB / 0 RB Offset
		18650 to 19150	18650	10 MHz	QPSK	1 RB / 0 RB Offset
			19150	10 MHz	QPSK	50 RB / 0 RB Offset
		18675 to 19125	18675	15 MHz	QPSK	1 RB / 0 RB Offset
			19125	15 MHz	QPSK	75 RB / 0 RB Offset
		18700 to 19100	18700	20 MHz	QPSK	1 RB / 0 RB Offset
			19100	20 MHz	QPSK	100 RB / 0 RB Offset
		18607 to 19193	18607	1.4 MHz	QPSK	1 RB / 0 RB Offset
			19193	1.4 MHz	QPSK	6 RB / 0 RB Offset
		18615 to 19185	18615	3 MHz	QPSK	1 RB / 0 RB Offset
			19185	3 MHz	QPSK	15 RB / 0 RB Offset
		18625 to 19175	18625	5 MHz	QPSK	1 RB / 0 RB Offset
			19175	5 MHz	QPSK	25 RB / 0 RB Offset
		18650 to 19150	18650	10 MHz	QPSK	1 RB / 0 RB Offset
			19150	10 MHz	QPSK	50 RB / 0 RB Offset
		18675 to 19125	18675	15 MHz	QPSK	1 RB / 0 RB Offset
			19125	15 MHz	QPSK	75 RB / 0 RB Offset
		18700 to 19100	18700	20 MHz	QPSK	1 RB / 0 RB Offset
			19100	20 MHz	QPSK	100 RB / 0 RB Offset
-	Conducted	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset

	Emission	18615 to 19185	18615, 18900, 19185	3 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	26 deg. C, 58 % RH	6.54 Vdc	Karl Lee
Frequency Stability	26 deg. C, 58 % RH	6.54 Vdc	Wayne Lin
Occupied Bandwidth	26 deg. C, 58 % RH	6.54 Vdc	Wayne Lin
Band Edge	26 deg. C, 58 % RH	6.54 Vdc	Wayne Lin
Peak to Average Ratio	26 deg. C, 58 % RH	6.54 Vdc	Wayne Lin
Conducted Emission	26 deg. C, 58 % RH	6.54 Vdc	Wayne Lin
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1 MHz for GSM, GPRS & EDGE, 5 MHz for WCDMA and CDMA, and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.


Conducted Power Measurement:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA, CDMA, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

Band	WCDMA Band II			3GPP MPR (dB)
Channel	9262	9400	9538	
Frequency (MHz)	1852.4	1880.0	1907.6	
RMC 12.2K	23.69	23.76	23.70	-
HSDPA Subtest-1	23.67	23.74	23.68	0
HSDPA Subtest-2	22.75	22.82	22.76	0
HSDPA Subtest-3	22.27	22.34	22.28	0.5
HSDPA Subtest-4	22.01	22.08	22.02	0.5
HSUPA Subtest-1	22.77	22.84	22.78	0
HSUPA Subtest-2	20.55	20.62	20.56	2
HSUPA Subtest-3	21.25	21.32	21.26	1
HSUPA Subtest-4	20.79	20.86	20.80	2
HSUPA Subtest-5	22.83	22.90	22.84	0

LTE Band 2															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100				Channel		18675	18900	19125	
		Frequency (MHz)		1860.0	1880.0	1900.0				Frequency (MHz)		1857.5	1880.0	1902.5	
20M	QPSK	1	0	22.75	22.68	22.84	0	15M	QPSK	1	0	22.69	22.62	22.79	0
		1	50	22.40	22.63	22.65	0			1	37	22.32	22.56	22.59	0
		1	99	22.39	22.56	22.78	0			1	74	22.31	22.49	22.73	0
		50	0	21.61	21.63	21.75	1			36	0	21.51	21.53	21.67	1
		50	25	21.39	21.57	21.63	1			36	19	21.27	21.46	21.53	1
		50	50	21.31	21.59	21.64	1			36	39	21.17	21.48	21.54	1
		100	0	21.67	21.69	21.73	1			75	0	21.58	21.60	21.64	1
	16QAM	1	0	21.79	21.72	21.89	1		16QAM	1	0	21.73	21.65	21.84	1
		1	50	21.40	21.65	21.68	1			1	37	21.33	21.58	21.61	1
		1	99	21.38	21.57	21.83	1			1	74	21.30	21.50	21.77	1
		50	0	20.56	20.60	20.73	2			36	0	20.43	20.46	20.65	2
		50	25	20.34	20.52	20.60	2			36	19	20.19	20.37	20.46	2
		50	50	20.26	20.54	20.61	2			36	39	20.11	20.40	20.51	2
		100	0	20.64	20.66	20.71	2			75	0	20.55	20.57	20.63	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18650	18900	19150				Channel		18625	18900	19175	
		Frequency (MHz)		1855.0	1880.0	1905.0				Frequency (MHz)		1852.5	1880.0	1907.5	
10M	QPSK	1	0	22.63	22.53	22.74	0	5M	QPSK	1	0	22.57	22.48	22.69	0
		1	24	22.22	22.47	22.50	0			1	12	22.16	22.41	22.45	0
		1	49	22.21	22.40	22.66	0			1	24	22.15	22.32	22.61	0
		25	0	21.36	21.41	21.55	1			12	0	21.25	21.29	21.49	1
		25	12	21.10	21.29	21.41	1			12	6	20.96	21.14	21.29	1
		25	25	21.01	21.33	21.42	1			12	13	20.86	21.19	21.32	1
		50	0	21.47	21.49	21.53	1			25	0	21.37	21.41	21.46	1
	16QAM	1	0	21.68	21.59	21.79	1		16QAM	1	0	21.63	21.52	21.74	1
		1	24	21.24	21.50	21.53	1			1	12	21.18	21.45	21.48	1
		1	49	21.23	21.41	21.72	1			1	24	21.16	21.35	21.67	1
		25	0	20.33	20.38	20.58	2			12	0	20.19	20.24	20.45	2
		25	12	20.07	20.25	20.38	2			12	6	19.89	20.12	20.24	2
		25	25	19.97	20.29	20.40	2			12	13	19.81	20.15	20.28	2
		50	0	20.45	20.49	20.53	2			25	0	20.32	20.36	20.43	2
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18615	18900	19185				Channel		18607	18900	19193	
		Frequency (MHz)		1851.5	1880.0	1908.5				Frequency (MHz)		1850.7	1880.0	1909.3	
3M	QPSK	1	0	22.49	22.38	22.63	0	1.4M	QPSK	1	0	22.45	22.35	22.58	0
		1	7	22.02	22.30	22.35	0			1	2	21.97	22.24	22.29	0
		1	14	22.01	22.22	22.54	0			1	5	21.94	22.16	22.51	0
		8	0	21.07	21.12	21.33	1			3	0	21.46	21.53	21.27	0
		8	3	20.81	21.01	21.12	1			3	1	21.17	21.37	21.03	0
		8	7	20.71	21.04	21.15	1			3	3	21.07	21.40	21.06	0
		15	0	21.19	21.24	21.29	1			6	0	21.12	21.16	21.24	1
	16QAM	1	0	21.55	21.44	21.69	1		16QAM	1	0	21.49	21.37	21.63	1
		1	7	21.10	21.38	21.41	1			1	2	20.97	21.26	21.33	1
		1	14	21.06	21.27	21.60	1			1	5	20.95	21.15	21.54	1
		8	0	20.10	20.14	20.38	2			3	0	20.64	20.73	20.28	1
		8	3	19.74	19.96	20.14	2			3	1	20.33	20.52	20.03	1
		8	7	19.66	20.02	20.19	2			3	3	20.21	20.59	20.06	1
		15	0	20.22	20.27	20.34	2			6	0	20.12	20.18	20.25	2

EIRP Power (dBm)

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	9262	1852.4	-20.64	38.19	17.55	56.89	H
	9400	1880.0	-21.23	38.70	17.47	55.85	
	9538	1907.6	-21.86	39.35	17.49	56.10	
	9262	1852.4	-25.94	38.48	12.54	17.95	V
	9400	1880.0	-26.10	38.59	12.49	17.74	
	9538	1907.6	-26.43	38.87	12.44	17.54	

LTE Band 2							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	18607	1850.7	-27.70	44.70	17.00	50.12	H
	18900	1880.0	-27.76	44.70	16.94	49.43	
	19193	1909.3	-27.59	44.57	16.98	49.92	
	18607	1850.7	-32.26	44.27	12.01	15.89	V
	18900	1880.0	-32.90	44.87	11.97	15.74	
	19193	1909.3	-32.60	44.61	12.01	15.90	
Channel Bandwidth: 1.4 MHz / 16QAM							
X	18607	1850.7	-28.71	44.70	15.99	39.72	H
	18900	1880.0	-28.77	44.70	15.93	39.17	
	19193	1909.3	-28.63	44.57	15.94	39.29	
	18607	1850.7	-33.25	44.27	11.02	12.65	V
	18900	1880.0	-33.92	44.87	10.95	12.45	
	19193	1909.3	-33.61	44.61	11.00	12.60	

LTE Band 2							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	18615	1851.5	-27.68	44.70	17.02	50.35	H
	18900	1880.0	-27.69	44.70	17.01	50.23	
	19185	1908.5	-27.58	44.57	16.99	50.04	
	18615	1851.5	-32.25	44.27	12.02	15.92	V
	18900	1880.0	-32.87	44.87	12.00	15.85	
	19185	1908.5	-32.64	44.61	11.97	15.75	
Channel Bandwidth: 3 MHz / 16QAM							
X	18615	1851.5	-28.64	44.70	16.06	40.36	H
	18900	1880.0	-28.70	44.70	16.00	39.81	
	19185	1908.5	-28.53	44.57	16.04	40.21	
	18615	1851.5	-33.23	44.27	11.04	12.71	V
	18900	1880.0	-33.85	44.87	11.02	12.65	
	19185	1908.5	-33.66	44.61	10.95	12.45	

LTE Band 2							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	18625	1852.5	-27.64	44.70	17.06	50.82	H
	18900	1880.0	-27.66	44.70	17.04	50.58	
	19175	1907.5	-27.54	44.57	17.03	50.50	
	18625	1852.5	-32.21	44.27	12.06	16.07	V
	18900	1880.0	-32.82	44.87	12.05	16.03	
	19175	1907.5	-32.59	44.61	12.02	15.93	
Channel Bandwidth: 5 MHz / 16QAM							
X	18625	1852.5	-28.63	44.70	16.07	40.46	H
	18900	1880.0	-28.65	44.70	16.05	40.27	
	19175	1907.5	-28.53	44.57	16.04	40.21	
	18625	1852.5	-33.18	44.27	11.09	12.85	V
	18900	1880.0	-33.80	44.87	11.07	12.79	
	19175	1907.5	-33.54	44.61	11.07	12.80	

LTE Band 2							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	18650	1855.0	-27.61	44.70	17.09	51.17	H
	18900	1880.0	-27.63	44.70	17.07	50.93	
	19150	1905.0	-27.53	44.57	17.04	50.62	
	18650	1855.0	-32.20	44.27	12.07	16.11	V
	18900	1880.0	-32.83	44.87	12.04	16.00	
	19150	1905.0	-32.57	44.61	12.04	16.01	
Channel Bandwidth: 10 MHz / 16QAM							
X	18650	1855.0	-28.60	44.70	16.10	40.74	H
	18900	1880.0	-28.64	44.70	16.06	40.36	
	19150	1905.0	-28.53	44.57	16.04	40.21	
	18650	1855.0	-33.21	44.27	11.06	12.76	V
	18900	1880.0	-33.84	44.87	11.03	12.68	
	19150	1905.0	-33.60	44.61	11.01	12.63	

LTE Band 2							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	18675	1857.5	-27.60	44.70	17.10	51.29	H
	18900	1880.0	-27.62	44.70	17.08	51.05	
	19125	1902.5	-27.53	44.57	17.04	50.62	
	18675	1857.5	-32.16	44.27	12.11	16.26	V
	18900	1880.0	-32.80	44.87	12.07	16.11	
	19125	1902.5	-32.53	44.61	12.08	16.15	
Channel Bandwidth: 15 MHz / 16QAM							
X	18675	1857.5	-28.63	44.70	16.07	40.46	H
	18900	1880.0	-28.66	44.70	16.04	40.18	
	19125	1902.5	-28.52	44.57	16.05	40.30	
	18675	1857.5	-33.12	44.27	11.15	13.03	V
	18900	1880.0	-33.85	44.87	11.02	12.65	
	19125	1902.5	-33.53	44.61	11.08	12.83	

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	18700	1860.0	-27.52	44.70	17.18	52.24	H
	18900	1880.0	-27.56	44.70	17.14	51.76	
	19100	1900.0	-27.45	44.57	17.12	51.56	
	18700	1860.0	-32.12	44.27	12.15	16.41	V
	18900	1880.0	-32.74	44.87	12.13	16.33	
	19100	1900.0	-32.53	44.61	12.08	16.15	
Channel Bandwidth: 20 MHz / 16QAM							
X	18700	1860.0	-28.50	44.70	16.20	41.69	H
	18900	1880.0	-28.52	44.70	16.18	41.50	
	19100	1900.0	-28.43	44.57	16.14	41.14	
	18700	1860.0	-33.10	44.27	11.17	13.09	V
	18900	1880.0	-33.72	44.87	11.15	13.03	
	19100	1900.0	-33.52	44.61	11.09	12.86	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1852.400004	0.002	1907.600002	0.001	2.5
6.54	1852.400001	0.001	1907.600001	0.001	2.5
8.85	1852.400002	0.001	1907.600001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1852.400004	0.002	1907.600003	0.002	2.5
-20	1852.400004	0.002	1907.600004	0.002	2.5
-10	1852.400004	0.002	1907.600002	0.001	2.5
0	1852.400001	0.001	1907.600001	0.001	2.5
10	1852.400002	0.001	1907.600003	0.002	2.5
20	1852.399996	-0.002	1907.599998	-0.001	2.5
30	1852.399997	-0.002	1907.599998	-0.001	2.5
40	1852.399998	-0.001	1907.599999	-0.001	2.5
50	1852.399999	-0.001	1907.599997	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1850.700003	0.001	1909.300002	0.001	2.5
6.54	1850.700003	0.001	1909.300004	0.002	2.5
8.85	1850.700002	0.001	1909.300002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1850.700002	0.001	1909.300002	0.001	2.5
-20	1850.700002	0.001	1909.300001	0.001	2.5
-10	1850.700003	0.001	1909.300001	0.001	2.5
0	1850.700002	0.001	1909.300003	0.002	2.5
10	1850.700001	0.001	1909.300003	0.002	2.5
20	1850.699997	-0.002	1909.299997	-0.001	2.5
30	1850.699997	-0.002	1909.299998	-0.001	2.5
40	1850.699998	-0.001	1909.299998	-0.001	2.5
50	1850.699998	-0.001	1909.299997	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1851.500001	0.001	1908.500003	0.001	2.5
6.54	1851.500002	0.001	1908.500003	0.001	2.5
8.85	1851.500002	0.001	1908.500004	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1851.500002	0.001	1908.500001	0.001	2.5
-20	1851.500001	0.001	1908.500004	0.002	2.5
-10	1851.500001	0.001	1908.500002	0.001	2.5
0	1851.500003	0.001	1908.500002	0.001	2.5
10	1851.500003	0.002	1908.500003	0.002	2.5
20	1851.499996	-0.002	1908.499998	-0.001	2.5
30	1851.499999	-0.001	1908.499999	-0.001	2.5
40	1851.499999	-0.001	1908.499998	-0.001	2.5
50	1851.499998	-0.001	1908.499997	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1852.500002	0.001	1907.500002	0.001	2.5
6.54	1852.500004	0.002	1907.500003	0.002	2.5
8.85	1852.500004	0.002	1907.500004	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1852.500002	0.001	1907.500003	0.002	2.5
-20	1852.500003	0.001	1907.500003	0.002	2.5
-10	1852.500001	0.001	1907.500004	0.002	2.5
0	1852.500003	0.001	1907.500004	0.002	2.5
10	1852.500002	0.001	1907.500003	0.002	2.5
20	1852.499998	-0.001	1907.499999	-0.001	2.5
30	1852.499999	-0.001	1907.499997	-0.002	2.5
40	1852.499996	-0.002	1907.499998	-0.001	2.5
50	1852.499997	-0.001	1907.499999	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1855.000001	0.001	1905.000002	0.001	2.5
6.54	1855.000003	0.002	1905.000003	0.001	2.5
8.85	1855.000001	0.001	1905.000001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1855.000002	0.001	1905.000002	0.001	2.5
-20	1855.000003	0.002	1905.000002	0.001	2.5
-10	1855.000004	0.002	1905.000002	0.001	2.5
0	1855.000003	0.002	1905.000001	0.001	2.5
10	1855.000003	0.001	1905.000004	0.002	2.5
20	1854.999999	-0.001	1904.999998	-0.001	2.5
30	1854.999999	-0.001	1904.999999	-0.001	2.5
40	1854.999997	-0.002	1904.999999	-0.001	2.5
50	1854.999998	-0.001	1904.999997	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1857.500004	0.002	1902.500003	0.002	2.5
6.54	1857.500004	0.002	1902.500003	0.001	2.5
8.85	1857.500004	0.002	1902.500003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1857.500003	0.001	1902.500002	0.001	2.5
-20	1857.500002	0.001	1902.500001	0.001	2.5
-10	1857.500003	0.002	1902.500003	0.002	2.5
0	1857.500003	0.001	1902.500003	0.002	2.5
10	1857.500001	0.001	1902.500002	0.001	2.5
20	1857.499999	-0.001	1902.499997	-0.002	2.5
30	1857.499998	-0.001	1902.499996	-0.002	2.5
40	1857.499998	-0.001	1902.499997	-0.001	2.5
50	1857.499998	-0.001	1902.499998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
7.7	1860.000002	0.001	1900.000003	0.001	2.5
6.54	1860.000001	0.001	1900.000003	0.001	2.5
8.85	1860.000001	0.001	1900.000003	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 6.54 Vdc to 8.85 Vdc.

Frequency Error vs. Temperature


Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1860.000003	0.002	1900.000003	0.002	2.5
-20	1860.000001	0.001	1900.000002	0.001	2.5
-10	1860.000004	0.002	1900.000003	0.002	2.5
0	1860.000002	0.001	1900.000001	0.001	2.5
10	1860.000002	0.001	1900.000002	0.001	2.5
20	1859.999997	-0.002	1899.999998	-0.001	2.5
30	1859.999999	-0.001	1899.999998	-0.001	2.5
40	1859.999996	-0.002	1899.999996	-0.002	2.5
50	1859.999997	-0.001	1899.999999	-0.001	2.5

4.3 Occupied Bandwidth Measurement

4.3.1 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 Test Setup




4.3.3 Test Result


Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
		WCDMA
9262	1852.4	4.0807
9400	1880.0	4.0799
9538	1907.6	4.0775



LTE Band 2							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	1.0919	1.0942	18615	1851.5	2.7029	2.7061
18900	1880.0	1.0958	1.0936	18900	1880.0	2.7050	2.7057
19193	1909.3	1.0928	1.0926	19185	1908.5	2.7018	2.7003



LTE Band 2							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	4.4964	4.4943	18650	1855.0	8.9908	8.9797
18900	1880.0	4.4974	4.4965	18900	1880.0	8.9946	8.9847
19175	1907.5	4.4984	4.4931	19150	1905.0	8.9914	8.9789




LTE Band 2


Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	13.474	13.464	18700	1860.0	17.960	17.951
18900	1880.0	13.484	13.476	18900	1880.0	17.984	17.986
19125	1902.5	13.455	13.444	19100	1900.0	17.930	17.926

Spectrum Plot of Worst Value

15 MHz / QPSK



20 MHz / 16QAM




4.4 Band Edge Measurement

4.4.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


4.4.2 Test Setup





4.4.3 Test Procedures


- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 15 kHz and VB of the spectrum is 47 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 51 kHz and VB of the spectrum is 150 kHz (LTE Bandwidth 5 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 200 kHz and VB of the spectrum is 620 kHz (LTE Bandwidth 20 MHz).
- Record the max trace plot into the test report.


4.4.4 Test Results


















4.5 Peak to Average Ratio

4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Setup




4.5.3 Test Procedures


1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.5.4 Test Results


Channel	Frequency (MHz)	Peak to Average Ratio (dB)
		WCDMA
9262	1852.4	3.47
9400	1880.0	3.45
9538	1907.6	3.40




LTE Band 2							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	5.83	6.82	18615	1851.5	6.02	6.83
18900	1880.0	5.79	5.84	18900	1880.0	6.04	5.99
19193	1909.3	5.28	5.89	19185	1908.5	5.39	6.07



LTE Band 2							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	5.90	6.83	18650	1855.0	5.90	6.80
18900	1880.0	5.84	5.88	18900	1880.0	5.86	5.87
19175	1907.5	5.52	6.23	19150	1905.0	5.93	6.75



LTE Band 2							
Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	5.92	6.75	18700	1860.0	5.99	6.89
18900	1880.0	5.98	5.69	18900	1880.0	6.02	6.46
19125	1902.5	6.18	6.75	19100	1900.0	6.20	6.84




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.


4.6.2 Test Setup



4.6.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 26.5 GHz. 20 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz is used for conducted emission measurement.

4.6.4 Test Results




WCDMA Channel 9400


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




WCDMA Channel 9538


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 1.4 MHz

Channel 18900


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 1.4 MHz

Channel 19193


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 3 MHz

Channel 18615


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 3 MHz

Channel 18900


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 3 MHz

Channel 19185


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 5 MHz

Channel 18625


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 5 MHz

Channel 18900


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 5 MHz

Channel 19175


Frequency Range: 30 MHz ~ 1 GHz




Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz






LTE Band 2


Channel Bandwidth: 10 MHz

Channel 18900


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz



Channel 19150

Frequency Range: 1 GHz ~ 10 GHz




LTE Band 2


Channel Bandwidth: 15 MHz

Channel 18675


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz



Channel 18900

Frequency Range: 1 GHz ~ 10 GHz




LTE Band 2


Channel Bandwidth: 15 MHz

Channel 19125


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 20 MHz

Channel 18700


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 20 MHz

Channel 18900


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 20 MHz

Channel 19100


Frequency Range: 30 MHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13 dBm.

4.7.2 Test Procedure

- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}.$


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

4.7.3 Deviation from Test Standard


No deviation.

4.7.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

WCDMA:

Low Channel




Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 9

Date: 2018-03-21



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : Bnad II_Link_CH9262
Tested by: Karl Lee


		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3704.80	-51.31	-67.19	-13.00	-38.31	15.88	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Bnad II_Link_CH9262
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3704.80	-50.74	-66.62	-13.00	-37.74	15.88	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2018-03-21



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : Bnad II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	157.71	-46.85	-39.13	-13.00	-33.85	-7.72	Peak
2	220.35	-54.85	-48.94	-13.00	-41.85	-5.91	Peak
3	275.43	-55.62	-49.88	-13.00	-42.62	-5.74	Peak
4	312.60	-60.05	-54.24	-13.00	-47.05	-5.81	Peak
5	433.70	-64.77	-61.29	-13.00	-51.77	-3.48	Peak
6	531.70	-63.38	-60.37	-13.00	-50.38	-3.01	Peak
7	3760.00	-51.47	-67.61	-13.00	-38.47	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-03-21



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Bnad II_Link_CH9400
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	151.23	-54.82	-46.90	-13.00	-41.82	-7.92	Peak
2	216.84	-66.41	-60.46	-13.00	-53.41	-5.95	Peak
3	278.67	-64.60	-58.84	-13.00	-51.60	-5.76	Peak
4	533.10	-57.89	-55.02	-13.00	-44.89	-2.87	Peak
5	668.20	-60.54	-60.32	-13.00	-47.54	-0.22	Peak
6	727.00	-64.96	-64.07	-13.00	-51.96	-0.89	Peak
7	3760.00	-51.07	-67.21	-13.00	-38.07	16.14	Peak
8 pp	5640.00	-44.47	-64.94	-13.00	-31.47	20.47	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-21



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : Bnad II_Link_CH9538
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.20	-50.48	-66.89	-13.00	-37.48	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-21



Site : 966 chamber 1
 Condition: PART 22/24 Vertical
 Remark : Bnad II_Link_CH9538
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.20	-51.14	-67.55	-13.00	-38.14	16.41	Peak

LTE Band 2
Channel Bandwidth: 1.4 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18607
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3701.40	-50.70	-66.58	-13.00	-37.70	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18607
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3701.40	-50.94	-66.82	-13.00	-37.94	15.88	Peak
2 pp	5552.10	-43.23	-63.57	-13.00	-30.23	20.34	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.44	-67.58	-13.00	-38.44	16.14 Peak
2 pp	5640.00	-43.34	-63.81	-13.00	-30.34	20.47 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-50.87	-67.01	-13.00	-37.87	16.14	Peak
2 pp	5640.00	-40.47	-60.94	-13.00	-27.47	20.47	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : LTE_Band 2_Link_CH19193
 Tested by: Karl Lee

			Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	3818.60	-48.77	-65.27	-13.00	-35.77	16.50	Peak
2 pp	5727.90	-44.02	-64.36	-13.00	-31.02	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19193
Tested by: Karl Lee

			Read	Limit	Over		
Freq	Level	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dBm	dB	dB	
1	3818.60	-50.34	-66.84	-13.00	-37.34	16.50	Peak
2	5727.90	-42.91	-63.25	-13.00	-29.91	20.34	Peak

Channel Bandwidth: 5 MHz / QPSK

Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1

Condition: PART 22/24 Horizontal

Remark : LTE_Band 2_Link_CH18625

Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3705.00	-51.04	-66.92	-13.00	-38.04	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18625
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3705.00	-51.39	-67.27	-13.00	-38.39	15.88	Peak
2 pp	5557.50	-42.71	-63.05	-13.00	-29.71	20.34	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-50.64	-66.78	-13.00	-37.64	16.14	Peak
2 pp	5640.00	-44.94	-65.41	-13.00	-31.94	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	3760.00	-51.44	-67.58	-13.00	-38.44	16.14	Peak
2 pp	5640.00	-40.60	-61.07	-13.00	-27.60	20.47	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19175
Tested by: Karl Lee

			Read	Limit	Over		
Freq	Level	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB		
1	3815.00	-50.06	-66.47	-13.00	-37.06	16.41	Peak
2 pp	5722.50	-44.57	-64.84	-13.00	-31.57	20.27	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19175
Tested by: Karl Lee

			Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	3815.00	-50.39	-66.80	-13.00	-37.39	16.41	Peak
2 pp	5722.50	-43.84	-64.11	-13.00	-30.84	20.27	Peak

Channel Bandwidth: 20 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3720.00	-50.36	-66.33	-13.00	-37.36	15.97	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3720.00	-51.50	-67.47	-13.00	-38.50	15.97	Peak
2 pp	5580.00	-40.37	-60.74	-13.00	-27.37	20.37	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-50.64	-66.78	-13.00	-37.64	16.14	Peak
2 pp	5640.00	-41.67	-62.14	-13.00	-28.67	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

			Read	Limit	Over		
Freq	Level	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.36	-67.50	-13.00	-38.36	16.14	Peak
2 pp	5640.00	-41.88	-62.35	-13.00	-28.88	20.47	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2018-03-22



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee


			Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	157.98	-47.45	-39.73	-13.00	-34.45	-7.72	Peak
2	212.79	-52.38	-46.37	-13.00	-39.38	-6.01	Peak
3	273.27	-56.57	-50.85	-13.00	-43.57	-5.72	Peak
4	531.00	-64.90	-61.82	-13.00	-51.90	-3.08	Peak
5	739.60	-57.94	-56.81	-13.00	-44.94	-1.13	Peak
6	937.70	-56.55	-61.13	-13.00	-43.55	4.58	Peak
7	3800.00	-50.00	-66.41	-13.00	-37.00	16.41	Peak
8 pp	5700.00	-41.95	-62.16	-13.00	-28.95	20.21	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	151.77	-56.66	-48.77	-13.00	-43.66	-7.89	Peak
2	217.92	-65.38	-59.44	-13.00	-52.38	-5.94	Peak
3	276.24	-64.43	-58.68	-13.00	-51.43	-5.75	Peak
4	431.60	-61.22	-57.78	-13.00	-48.22	-3.44	Peak
5	533.10	-56.52	-53.65	-13.00	-43.52	-2.87	Peak
6	727.70	-59.67	-58.78	-13.00	-46.67	-0.89	Peak
7	3800.00	-50.43	-66.84	-13.00	-37.43	16.41	Peak
8 pp	5700.00	-39.67	-59.88	-13.00	-26.67	20.21	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---