

#01_WLAN2.4GHz_802.11b 1Mbps_Bottom Face_0cm_Ch6;Ant B

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1.01

Medium: MSL_2450_141105 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.985$ S/m; $\epsilon_r = 51.902$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3753; ConvF(7.31, 7.31, 7.31); Calibrated: 2014/3/26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2014/7/23
- Phantom: ELI_Left; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (6);SEMCAD X Version 14.6.9 (7117)

Configuration/Ch6/Area Scan (41x71x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 1.26 W/kg


Configuration/Ch6/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 23.539 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.86 W/kg

SAR(1 g) = 0.848 W/kg; SAR(10 g) = 0.372 W/kg

Maximum value of SAR (measured) = 1.35 W/kg



#02_WLAN5GHz_802.11a 6Mbps_Edge 3_0cm_Ch40;Ant B

Communication System: 802.11a ; Frequency: 5200 MHz;Duty Cycle: 1:1.048

Medium: MSL_5G_141106 Medium parameters used: $f = 5200$ MHz; $\sigma = 5.138$ S/m; $\epsilon_r = 47.493$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.67, 4.67, 4.67); Calibrated: 2014/3/26;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2014/7/23
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1127
- Measurement SW: DASY52, Version 52.8 (6);SEMCAD X Version 14.6.9 (7117)

Configuration/Ch40/Area Scan (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.38 W/kg


Configuration/Ch40/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 21.373 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 4.22 W/kg

SAR(1 g) = 0.979 W/kg; SAR(10 g) = 0.303 W/kg

Maximum value of SAR (measured) = 2.36 W/kg



0 dB = 2.36 W/kg = 3.73 dBW/kg

#03_WLAN5GHz_802.11a 6Mbps_Edge 3_0cm_Ch56;Ant B

Communication System: 802.11a ; Frequency: 5280 MHz;Duty Cycle: 1:1.048

Medium: MSL_5G_141106 Medium parameters used : $f = 5280$ MHz; $\sigma = 5.231$ S/m; $\epsilon_r = 47.294$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.42, 4.42, 4.42); Calibrated: 2014/3/26;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2014/7/23
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1127
- Measurement SW: DASY52, Version 52.8 (6);SEMCAD X Version 14.6.9 (7117)

Configuration/Ch56/Area Scan (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.97 W/kg


Configuration/Ch56/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 19.091 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 3.45 W/kg

SAR(1 g) = 0.824 W/kg; SAR(10 g) = 0.263 W/kg

Maximum value of SAR (measured) = 1.99 W/kg



0 dB = 1.99 W/kg = 2.99 dBW/kg

#04_WLAN5GHz_802.11a 6Mbps_Edge 3_0cm_Ch132;Ant B

Communication System: 802.11a; Frequency: 5660 MHz; Duty Cycle: 1:1.048

Medium: MSL_5G_141106 Medium parameters used: $f = 5660$ MHz; $\sigma = 5.764$ S/m; $\epsilon_r = 46.738$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(4.12, 4.12, 4.12); Calibrated: 2014/5/22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2014/5/19
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Ch132/Area Scan (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.613 W/kg


Configuration/Ch132/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 26.627 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 5.677 W/kg

SAR(1 g) = 1.12 W/kg; SAR(10 g) = 0.259 W/kg

Maximum value of SAR (measured) = 3.096 W/kg



0 dB = 3.096 W/kg = 4.91 dBW/kg

#05_WLAN5GHz_802.11a 6Mbps_Edge 3_0cm_Ch161;Ant B

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1.048

Medium: MSL_5G_141106 Medium parameters used: $f = 5805$ MHz; $\sigma = 6.004$ S/m; $\epsilon_r = 46.509$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(4.09, 4.09, 4.09); Calibrated: 2014/5/22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2014/5/19
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/Ch161/Area Scan (51x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.76 W/kg

Configuration/Ch161/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 24.46 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 4.94 W/kg

SAR(1 g) = 0.988 W/kg; SAR(10 g) = 0.242 W/kg

Maximum value of SAR (measured) = 2.64 W/kg

