

MPE/RF EXPOSURE TEST REPORT



Test of: HP Inc 0960-4025 and 0960-4034

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: MARS11_MPE Rev B FCC All Bands

This report supersedes: MARS11_MPE Rev A FCC All Bands

Applicant: HP Inc
1115 SE 164th Ave., Suite 210,
Vancouver,
Washington 98683,
USA

Product Function 802.11 a/b/g/n SDIO dual band
with BT/BLE

Issue Date: 20th December 2017

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC CFR 47 Part 1.1310
Serial #: MARS11_MPE FCC Rev B All Bands
Issue Date: 20th December 2017
Page: 2 of 4

1. PRODUCT DETAILS

Details	Description
Purpose:	Evaluation of the HP Inc 0960-4025 and 0960-4034 for compliance to FCC CFR 47 Part 1.1310
Applicant:	HP Inc 1115 SE 164th Ave., Suite 210, Vancouver, Washington 98683, USA
Manufacturer:	HP Inc
Laboratory performing the tests:	MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Product Family Name:	VCVRA-1712
Model(s):	Model: HP Inc.'s VCVRA-1712 Part numbers: 0960-4025 and 0960-4034
Equipment Dimensions:	37mm x 40mm
Weight:	0.3 oz
Hardware Rev:	V4
Software Rev:	P130

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



2. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Total Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
2400.0 - 2483.5 (BLE DTS GFSK))	2.5	1.78	7.55	5.69	0.002	1	0.90
2400.0 - 2483.5 (BLE FHSS)	2.5	1.78	7.25	5.31	0.002	1	0.90
2400.0 - 2483.5 WiFi	2.5	1.78	18.47	70.31	0.025	1	3.15
5725.0 - 5850.0 WiFi	3.8	2.40	17.48	55.98	0.027	1	3.27
5150.0 - 5250.0 WiFi	3.8	2.40	15.55	35.89	0.017	1	2.62
5470.0 - 5725.0 WiFi	3.8	2.40	15.90	38.90	0.019	1	2.73
5250.0 - 5350.0 WiFi	3.8	2.40	16.23	41.98	0.020	1	2.83

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits.

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com