


RADIO TEST REPORT

Test Report No. 14937633H-A-R1

Customer	DENSO TEN Limited
Description of EUT	Car Audio
Model Number of EUT	TN0046A
FCC ID	BABTN0046A
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	February 7, 2024
Remarks	-

Representative Test EngineerTetsuro Yoshida
Engineer**Approved By**Ryota Yamanaka
Engineer

CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
- ☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 22.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided from the customer for this report is identified in Section 1.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No.: 14937633H-A

This report is a revised version of 14937633H-A. 14937633H-A is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	14937633H-A	December 18, 2023	-
1	14937633H-A-R1	February 7, 2024	P.10 Table of Detail of Operating mode(s): Addition of "Conducted Spurious Emission" in Row 3 P.23, 24: Correction of wrong data : DH5: 2402 MHz and 2441 MHz P.36 Correction of Bottom of Vertical axis from 10 to 0 P.40 Correction of test mode from DH5 to 3DH5

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information	5
SECTION 2: Equipment Under Test (EUT).....	5
SECTION 3: Test Specification, Procedures & Results	6
SECTION 4: Operation of EUT during testing	9
SECTION 5: Radiated Spurious Emission.....	11
SECTION 6: Antenna Terminal Conducted Tests	13
APPENDIX 1: Test data	14
20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation	14
Number of Hopping Frequency.....	18
Dwell time	20
Maximum Peak Output Power	23
Average Output Power.....	24
Burst Rate Confirmation.....	25
Radiated Spurious Emission.....	26
Conducted Spurious Emission.....	37
Conducted Emission Band Edge compliance	43
APPENDIX 2: Test Instruments	45
APPENDIX 3: Photographs of test setup.....	46
Radiated Spurious Emission.....	46
Antenna Terminal Conducted Tests	47

SECTION 1: Customer Information

Company Name	DENSO TEN Limited
Address	2-28 Goshō-Dori 1-Chome, Hyogo-Ku Kobe 652-8510 Japan
Telephone Number	+81-78-682-2159
Contact Person	Kaoru Abe

The information provided from the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	Car Audio
Model Number	TN0046A
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	November 27, 2023
Test Date	November 27 and 28, 2023

2.2 Product Description

General Specification

Rating	DC 12 V
Operating temperature	-20 deg. C to 65 deg. C

Radio Specification

Bluetooth (BR / EDR)

Equipment Type	Transceiver
Frequency of Operation	2402 MHz to 2480 MHz
Type of Modulation	FHSS (GFSK, $\pi/4$ DQPSK, 8 DPSK)
Antenna Gain	-2.4 dBi

AM/FM

Equipment Type	Receiver
Frequency of Operation	AM: 530 kHz to 1710 kHz FM: 87.75 MHz to 107.9 MHz
Type of Modulation	AM FM
Antenna Connector Type	JASO
Impedance	75 ohm

SECTION 3: Test Specification, Procedures & Results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

3.2 Procedures and Results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	-	N/A	*1)
Carrier Frequency Separation	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1) ISED: RSS-247 5.1 (b)	See data.	Complied	Conducted
20dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1) ISED: RSS-247 5.1 (a)		Complied	Conducted
Number of Hopping Frequency	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied	Conducted
Dwell time	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section15.247(b)(1) ISED: RSS-247 5.4 (b)		Complied	Conducted
Spurious Emission & Band Edge Compliance	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	12.9 dB 4882.0 MHz, AV, Vertical / 4960.0 MHz, AV, Horizontal	Complied	Conducted/ Radiated (above 30 MHz) *2)
Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593. * In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred. *1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line. *2) Radiated test was selected over 30 MHz based on section 15.247(d).					

FCC Part 15.31 (e)

This EUT provides the stable voltage constantly to RF Module regardless of input voltage.
Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.
Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to Standard

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	3.3
10 m			dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	dB	4.8
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.1
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	4.8
		Vertical	dB	4.8
	200 MHz to 1000 MHz	Horizontal	dB	4.9
		Vertical	dB	5.0
3 m	1 GHz to 6 GHz	Test Receiver	dB	5.1
		Spectrum Analyzer	dB	4.9
	6 GHz to 18 GHz	Test Receiver	dB	5.4
		Spectrum Analyzer	dB	5.2
1 m	10 GHz to 18 GHz	Spectrum analyzer	dB	5.0
	18 GHz to 26.5 GHz	Spectrum analyzer	dB	5.6
	26.5 GHz to 40 GHz	Spectrum analyzer	dB	4.9
0.5 m	26.5 GHz to 40 GHz	Spectrum analyzer	dB	4.9
10 m	1 GHz to 18 GHz	Test Receiver	dB	5.4

Antenna Terminal Conducted

Item	Unit	Calculated Uncertainty (+/-)
Antenna terminated conducted emission / Power density / Burst power	dB	3.47
Adjacent channel power (ACP)	dB	2.28
Bandwidth (OBW)	%	0.96
Time readout (time span upto 100 msec)	%	0.11
Time readout (time span upto 1000 msec)	%	0.11
Time readout (time span upto 60 sec)	%	0.02
Power measurement (Power meter < 8 GHz)	dB	1.46
Power measurement (Call box < 6 GHz)	dB	1.69
Frequency readout (Frequency counter)	ppm	0.67
Frequency readout (Spectrum analyzer frequency readout function)	ppm	2.13
Temperature (constant temperature bath)	deg. C	0.69
Humidity (constant temperature bath)	%RH	2.98
Modulation characteristics	%	6.93
Frequency for mobile	ppm	0.08
Contention-based protocol	dB	2.26

3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)

Mode	Remarks*
Bluetooth (BT)	BR / EDR, Payload: PRBS9
*EUT has the power settings by the software as follows; Power Setting: 0 dBm Software: TN0046A Version: 1.0 (Date: October 6, 2023, Storage location: EUT memory) *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.	

Details of Operating Mode(s)

Test Item	Mode	Hopping	Tested Frequency
Radiated Spurious Emission (Below 1 GHz)	Tx DH5 *1)	Off	2480 MHz
Radiated Spurious Emission (Above 1 GHz), Conducted Spurious Emission	Tx DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Carrier Frequency Separation	Tx DH5 Tx 3DH5	On	2402 MHz 2441 MHz 2480 MHz
20dB Bandwidth	Tx DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Number of Hopping Frequency	Tx DH5 Tx 3DH5	On	-
Dwell time	Tx DH1, DH3, DH5 Tx 3DH1, 3DH3, 3DH5	On	-
Maximum Peak Output Power	Tx DH5 Tx 2DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Band Edge Compliance (Conducted)	Tx DH5 Tx 3DH5	On ----- Off	2402 MHz 2480 MHz
99% Occupied Bandwidth	Tx DH5 Tx 3DH5	On ----- Off	2402 MHz 2441 MHz 2480 MHz


*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test)

*2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative.

*It is considered that the non-tested packet type (e.g. inquiry) can be omitted as it is complied with above all the test items based on Bluetooth Core specification.

*1) Conducted emissions and Spurious emissions for frequencies below 1 GHz were limited to the channel that had the highest power during the antenna terminal test, as preliminary testing indicated that changing the operating frequency had no significant impact on the emissions in those frequency bands.

4.2 Configuration and Peripherals



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	Car Audio	TN0046A	BWB00050 *1) BWB00049 *2)	DENSO TEN Limited	EUT
B	Speaker	TS-F1600	- *2)	Pioneer Corporation	-
C	Speaker	-	- *2)	-	-
D	AM/FM Antenna	-	- *2)	-	-
E	Switch	-	- *2)	-	-
F	Android	SM-A510FD	R58H11M9Y8N *2)	Samsung	-
G	USB Memory	RUF3-K16GB	P10416 *2)	Buffalo	-

List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	1.1 *1) 3.0 *2)	Unshielded	Unshielded	-
2	Speaker Cable	1.2 *2)	Unshielded	Unshielded	-
3	Speaker Cable	1.2 *2)	Unshielded	Unshielded	-
4	FM/AM Cable	2.3 *2)	Shielded	Shielded	-
5	Signal Cable	2.4 *2)	Unshielded	Unshielded	-
6	Audio Cable	1.6 *2)	Shielded	Shielded	-
7	USB Cable	3.0 *2)	Shielded	Shielded	-

*1) Used for Antenna Terminal conducted test

*2) Used for Radiated Emission test

SECTION 5: Radiated Spurious Emission

Test Procedure

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane. Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating,


the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV *1)	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (RMS) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz

Figure 1: Test Setup


Below 1 GHz



× : Center of turn table

Test Distance: 3 m

1 GHz to 10 GHz




r : Radius of an outer periphery of EUT
× : Center of turn table

Distance Factor: $20 \times \log (3.65 \text{ m} / 3.0 \text{ m}) = 1.71 \text{ dB}$
* Test Distance: $(3 + \text{SVSWR Volume} / 2) - r = 3.65 \text{ m}$

SVSWR Volume : 1.5 m
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)
r = 0.1 m

10 GHz to 26.5 GHz



× : Center of turn table

Distance Factor: $20 \times \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$
*Test Distance: 1 m

The test was made on EUT at the normal use position.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement Range : 30 MHz to 26.5 GHz
Test Data : APPENDIX
Test Result : Pass

SECTION 6: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument Used
20dB Bandwidth	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak Average *2)	-	Power Meter (Sensor: 50MHz BW)
Carrier Frequency Separation	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Number of Hopping Frequency	30 MHz	200 kHz	620 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Dwell Time	Zero Span	100 kHz, 1 MHz	300 kHz, 3 MHz	As necessary capture the entire dwell time per hopping channel	Peak	Clear Write	Spectrum Analyzer
Conducted Spurious Emission *3) *4)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	10 kHz	30 kHz				
	30 MHz to 25 GHz	100 kHz	300 kHz				
Conducted Spurious Emission Band Edge compliance	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

*1) Peak hold was applied as Worst-case measurement.

*2) Reference data

*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was low enough as shown in the chart.
(9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 10 kHz).

*4) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

The test results and limit are rounded off to two decimals place, so some differences might be observed.
The equipment and cables were not used for factor 0 dB of the data sheets.

Test Data : APPENDIX

Test Result : Pass

APPENDIX 1: Test data

20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation


Test place	Ise EMC Lab. No.8 Measurement Room
Date	November 28, 2023
Temperature / Humidity	22 deg. C / 50 % RH
Engineer	Tetsuro Yoshida
Mode	Tx, Hopping Off, Tx, Hopping On

Mode	Freq. [MHz]	20 dB Bandwidth [MHz]	99 % Occupied Bandwidth [kHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency separation [MHz]
DH5	2402.0	0.940	857.646	1.000	≥ 0.627
DH5	2441.0	0.939	851.924	1.000	≥ 0.626
DH5	2480.0	0.940	854.808	1.000	≥ 0.627
DH5	Hopping On	-	78595.400	-	-
3DH5	2402.0	1.261	1152.000	1.000	≥ 0.841
3DH5	2441.0	1.256	1152.300	1.000	≥ 0.837
3DH5	2480.0	1.260	1151.700	1.000	≥ 0.840
3DH5	Hopping On	-	78647.300	-	-


Limit: Two-thirds of 20 dB Bandwidth or 25 kHz (whichever is greater).

No limit applies to 20 dB Bandwidth.


20dB Bandwidth and 99% Occupied Bandwidth



20dB Bandwidth and 99% Occupied Bandwidth



Carrier Frequency Separation




Number of Hopping Frequency

Test place	Ise EMC Lab. No.8 Measurement Room
Date	November 28, 2023
Temperature / Humidity	22 deg. C / 50 % RH
Engineer	Tetsuro Yoshida
Mode	Tx, Hopping On

Mode	Number of channel [channels]	Limit [channels]
DH5	79	>= 15
3DH5	79	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.

Number of Hopping Frequency



Dwell time

Test place	Ise EMC Lab. No.8 Measurement Room
Date	November 28, 2023
Temperature / Humidity	22 deg. C / 50 % RH
Engineer	Tetsuro Yoshida
Mode	Tx, Hopping On

Mode	Number of transmission in a 31.6 (79 Hopping x 0.4) / 12.8 (32 Hopping x 0.4) second period	Length of transmission [ms]	Result [ms]	Limit [ms]
DH1	101.2 times / 5 s x 31.6 s = 640 times	0.424	271	400
DH3	33.8 times / 5 s x 31.6 s = 214 times	1.687	361	400
DH5	20.4 times / 5 s x 31.6 s = 129 times	2.940	379	400
3DH1	101.6 times / 5 s x 31.6 s = 643 times	0.433	278	400
3DH3	34.0 times / 5 s x 31.6 s = 215 times	1.695	364	400
3DH5	20.2 times / 5 s x 31.6 s = 128 times	2.950	378	400

Sample Calculation

Result = Number of transmission x Length of transmission

*Average data of 5 tests.(except Inquiry)


Mode	Sampling [times]					Average [times]
	1	2	3	4	5	
DH1	101	101	102	101	101	101.2
DH3	34	34	33	34	34	33.8
DH5	21	21	20	20	20	20.4
3DH1	103	101	101	102	101	101.6
3DH3	34	34	33	34	35	34
3DH5	20	20	20	20	21	20.2

Sample Calculation


Average = Summation (Sampling 1 to 5) / 5

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in $N \times 0.4$ s, where N is the number of channels being used in the hopping sequence ($20 \leq N \leq 79$), is always less than 0.4 s regardless of packet size. This is confirmed in the test report for $N = 79$.

Dwell time



Dwell time



Maximum Peak Output Power

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx, Hopping Off

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Conducted Power					Antenna Gain [dBi]	e.i.r.p. for RSS-247				
					Result		Limit		Margin		Result		Limit		Margin
					[dBm]	[mW]	[dBm]	[mW]			[dB]	[dBm]	[mW]	[dBm]	
DH5	2402.0	-10.93	0.35	10.05	-0.53	0.88	20.96	125	21.49	-2.40	-2.93	0.51	36.02	4000	38.95
DH5	2441.0	-9.46	0.35	10.05	0.94	1.24	20.96	125	20.02	-2.40	-1.46	0.71	36.02	4000	37.48
DH5	2480.0	-8.80	0.35	10.05	1.60	1.44	20.96	125	19.36	-2.40	-0.80	0.83	36.02	4000	36.82
2DH5	2402.0	-11.36	0.35	10.05	-0.96	0.80	20.96	125	21.92	-2.40	-3.36	0.46	36.02	4000	39.38
2DH5	2441.0	-10.11	0.35	10.05	0.29	1.07	20.96	125	20.67	-2.40	-2.11	0.61	36.02	4000	38.13
2DH5	2480.0	-9.32	0.35	10.05	1.08	1.28	20.96	125	19.88	-2.40	-1.32	0.74	36.02	4000	37.34
3DH5	2402.0	-10.66	0.35	10.05	-0.26	0.94	20.96	125	21.22	-2.40	-2.66	0.54	36.02	4000	38.68
3DH5	2441.0	-9.21	0.35	10.05	1.19	1.31	20.96	125	19.77	-2.40	-1.21	0.76	36.02	4000	37.23
3DH5	2480.0	-8.87	0.35	10.05	1.53	1.42	20.96	125	19.43	-2.40	-0.87	0.82	36.02	4000	36.89

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss
e.i.r.p. Result = Conducted Power Result + Antenna Gain

Test was not performed at AFH mode, because the decrease of number of channel (min: 20 ch) at AFH mode does not influence on the output power and bandwidth of the EUT.
As this device had AFH mode and frequency separation could not meet the requirement of over 20 dB BW without 2/3 relaxation, 125 mW power limit was applied to it.

Average Output Power (Reference data for RF Exposure)

Test place	Ise EMC Lab. No.8 Measurement Room
Date	November 28, 2023
Temperature / Humidity	22 deg. C / 50 % RH
Engineer	Tetsuro Yoshida
Mode	Tx, Hopping Off

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
					[dBm]	[mW]		[dBm]	[mW]
DH5	2402.0	-11.65	0.35	10.05	-1.25	0.75	0.29	-0.96	0.80
DH5	2441.0	-10.45	0.35	10.05	-0.05	0.99	0.29	0.24	1.06
DH5	2480.0	-9.87	0.35	10.05	0.53	1.13	0.29	0.82	1.21
2DH5	2402.0	-14.82	0.35	10.05	-4.42	0.36	0.28	-4.14	0.39
2DH5	2441.0	-13.58	0.35	10.05	-3.18	0.48	0.28	-2.90	0.51
2DH5	2480.0	-13.00	0.35	10.05	-2.60	0.55	0.28	-2.32	0.59
3DH5	2402.0	-14.81	0.35	10.05	-4.41	0.36	0.28	-4.13	0.39
3DH5	2441.0	-13.65	0.35	10.05	-3.25	0.47	0.28	-2.97	0.50
3DH5	2480.0	-13.02	0.35	10.05	-2.62	0.55	0.28	-2.34	0.58

Sample Calculation:

Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss


Result (Burst power average) = Time average + Duty factor

*The equipment and cables were not used for factor 0 dB of the data sheets.


Burst Rate Confirmation

Test place	Ise EMC Lab. No.2 Semi Anechoic Chamber	Ise EMC Lab. No. 8 Measurement Room
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	22 deg. C / 50 % RH
Engineer	Tomoya Sone	Tetsuro Yoshida
Mode	Tx, Hopping Off	


DH5



2DH5



3DH5



Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone	Shousei Hamaguchi
	(1 GHz to 10 GHz)	(10 GHz to 26.5 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
Hori.	2390.0	44.9	33.3	27.7	4.7	34.9	0.3	42.3	31.0	73.9	53.9	31.6	22.9	*1)
Hori.	2558.1	44.8	35.8	27.6	4.8	34.9	-	42.4	33.3	73.9	53.9	31.5	20.6	
Hori.	4804.0	42.1	32.7	31.6	6.9	34.1	0.3	46.4	37.3	73.9	53.9	27.5	16.7	
Hori.	7206.0	42.5	32.3	36.0	8.0	34.0	-	52.4	42.2	73.9	53.9	21.5	11.7	Floor noise
Hori.	9608.0	43.5	33.5	38.9	8.9	34.7	-	56.6	46.5	73.9	53.9	17.3	7.4	Floor noise
Vert.	2390.0	44.6	33.1	27.7	4.7	34.9	0.3	42.0	30.8	73.9	53.9	31.9	23.1	*1)
Vert.	2558.1	46.8	40.6	27.6	4.8	34.9	-	44.4	38.2	73.9	53.9	29.5	15.7	
Vert.	4804.0	42.8	34.1	31.6	6.9	34.1	0.3	47.0	38.6	73.9	53.9	26.9	15.3	
Vert.	7206.0	43.1	32.5	36.0	8.0	34.0	-	53.0	42.4	73.9	53.9	20.9	11.5	Floor noise
Vert.	9608.0	42.9	33.2	38.9	8.9	34.7	-	55.9	46.3	73.9	53.9	18.0	7.6	Floor noise

$$\text{Result (QP / PK)} = \text{Reading} + \text{Ant Factor} + \text{Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz))} - \text{Gain(Amplifier)}$$

Result (AV) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

*QP detector was used up to 1GHz

*1) Not Out of Band emission(Leakage Power)

20dBc Data Sheet

Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	90.6	27.6	4.7	34.9	88.0	-	-	Carrier
Hori.	2400.0	39.1	27.6	4.7	34.9	36.5	68.0	31.5	
Vert.	2402.0	95.7	27.6	4.7	34.9	93.1	-	-	Carrier
Vert.	2400.0	46.4	27.6	4.7	34.9	43.9	73.1	29.2	



$$\text{Result} = \text{Reading} + \text{Ant Factor} + \text{Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz))} - \text{Gain(Amplifier)}$$

Distance factor: 1 GHz - 10 GHz $20\log(3.65\text{ m} / 3.0\text{ m}) = 1.71\text{ dB}$

$$10 \text{ GHz} - 26.5 \text{ GHz} \quad 20 \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$$

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.2
Date	November 27, 2023
Temperature / Humidity	21 deg. C / 44 % RH
Engineer	Tomoya Sone
	(1 GHz to 10 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge and authorized band edge were shown in tabular data.

Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone	Shousei Hamaguchi
	(1 GHz to 10 GHz)	(10 GHz to 26.5 GHz)
Mode	Tx, Hopping Off, DH5 2441 MHz	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
Hori.	4882.0	43.5	36.3	31.6	6.9	34.2	0.3	47.8	40.9	73.9	53.9	26.1	13.0	
Hori.	7323.0	43.4	32.7	36.2	8.1	34.1	-	53.6	42.8	73.9	53.9	20.3	11.1	Floor noise
Hori.	9764.0	42.2	34.3	39.3	8.9	34.7	-	55.7	47.8	73.9	53.9	18.2	6.1	Floor noise
Vert.	4882.0	43.8	36.4	31.6	6.9	34.2	0.3	48.1	41.0	73.9	53.9	25.8	12.9	
Vert.	7323.0	42.6	34.5	36.2	8.1	34.1	-	52.8	44.6	73.9	53.9	21.1	9.3	Floor noise
Vert.	9764.0	43.0	34.2	39.3	8.9	34.7	-	56.5	47.7	73.9	53.9	17.4	6.2	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

$$\text{Result (AV)} = \text{Reading} + \text{Ant Factor} + \text{Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz))} - \text{Gain(Amplifier)} + \text{Duty factor}$$

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

*QP detector was used up to 1GHz.

Distance factor:	1 GHz - 10 GHz	$20\log (3.65 \text{ m} / 3.0 \text{ m}) = 1.71 \text{ dB}$
	10 GHz - 26.5 GHz	$20\log (1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$

Radiated Spurious Emission

Test place	Ise EMC Lab.	No.2
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone (1 GHz to 10 GHz)	Shousei Hamaguchi (10 GHz to 26.5 GHz) (Below 1 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
Hori.	42.1	20.4	-	14.0	6.8	28.6	-	12.6	-	40.0	-	27.4	-	
Hori.	97.1	20.2	-	9.7	7.3	28.4	-	8.8	-	43.5	-	34.7	-	
Hori.	115.1	20.0	-	12.2	7.5	28.4	-	11.4	-	43.5	-	32.2	-	
Hori.	341.6	19.3	-	15.1	9.0	28.0	-	15.4	-	46.0	-	30.6	-	
Hori.	529.8	20.5	-	17.8	9.9	29.2	-	19.0	-	46.0	-	27.0	-	
Hori.	671.3	20.4	-	19.6	10.4	29.3	-	21.1	-	46.0	-	24.9	-	
Hori.	2483.5	44.7	33.6	27.5	4.8	34.9	0.3	42.1	31.3	73.9	53.9	31.8	22.6	*1)
Hori.	4960.0	43.4	36.3	31.7	6.9	34.2	0.3	47.8	41.0	73.9	53.9	26.1	12.9	
Hori.	7440.0	42.0	32.2	36.3	8.1	34.1	-	52.3	42.5	73.9	53.9	21.6	11.4	Floor noise
Hori.	9920.0	42.2	32.5	39.2	9.0	34.7	-	55.6	45.9	73.9	53.9	18.3	8.0	Floor noise
Vert.	42.1	20.4	-	14.0	6.8	28.6	-	12.6	-	40.0	-	27.4	-	
Vert.	97.1	20.2	-	9.7	7.3	28.4	-	8.8	-	43.5	-	34.7	-	
Vert.	115.1	20.0	-	12.2	7.5	28.4	-	11.4	-	43.5	-	32.2	-	
Vert.	341.6	19.3	-	15.1	9.0	28.0	-	15.4	-	46.0	-	30.6	-	
Vert.	529.8	20.5	-	17.8	9.9	29.2	-	19.0	-	46.0	-	27.0	-	
Vert.	671.3	20.4	-	19.6	10.4	29.3	-	21.1	-	46.0	-	24.9	-	
Vert.	2483.5	44.6	33.8	27.5	4.8	34.9	0.3	42.0	31.5	73.9	53.9	31.9	22.4	*1)
Vert.	4960.0	41.9	33.3	31.7	6.9	34.2	0.3	46.4	38.1	73.9	53.9	27.6	15.8	
Vert.	7440.0	43.0	31.9	36.3	8.1	34.1	-	53.3	42.3	73.9	53.9	20.6	11.6	Floor noise
Vert.	9920.0	41.9	33.1	39.2	9.0	34.7	-	55.4	46.5	73.9	53.9	18.5	7.4	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).



*QP detector was used up to 1GHz.

*1) Not Out of Band emission(Leakage Power)

Distance factor: 1 GHz - 10 GHz $20\log(3.65\text{ m} / 3.0\text{ m}) = 1.71\text{ dB}$
 10 GHz - 26.5 GHz $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

Radiated Spurious Emission
(Reference Plot for bandto edge)

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.2
Date	November 27, 2023
Temperature / Humidity	21 deg. C / 44 % RH
Engineer	Tomoya Sone
	(1 GHz to 10 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone	Shousei Hamaguchi
	(1 GHz to 10 GHz)	(10 GHz to 26.5 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
Hori.	2390.0	44.6	33.1	27.7	4.7	34.9	0.3	42.0	30.8	73.9	53.9	31.9	23.1	*1)
Hori.	4804.0	42.0	31.8	31.6	6.9	34.1	-	46.2	36.1	73.9	53.9	27.7	17.8	Floor noise
Hori.	7206.0	43.2	32.4	36.0	8.0	34.0	-	53.1	42.3	73.9	53.9	20.8	11.6	Floor noise
Hori.	9608.0	43.5	33.2	38.9	8.9	34.7	-	56.6	46.2	73.9	53.9	17.3	7.7	Floor noise
Vert.	2390.0	43.9	33.0	27.7	4.7	34.9	0.3	41.3	30.7	73.9	53.9	32.6	23.2	*1)
Vert.	4804.0	41.8	31.7	31.6	6.9	34.1	-	46.0	36.0	73.9	53.9	27.9	17.9	Floor noise
Vert.	7206.0	42.5	32.6	36.0	8.0	34.0	-	52.4	42.6	73.9	53.9	21.5	11.3	Floor noise
Vert.	9608.0	44.1	33.2	38.9	8.9	34.7	-	57.2	46.3	73.9	53.9	16.8	7.6	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).
*QP detector was used up to 1GHz.
*1) Not Out of Band emission(Leakage Power)

20dBc Data Sheet



Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	87.5	27.6	4.7	34.9	85.0	-	-	Carrier
Hori.	2400.0	46.9	27.6	4.7	34.9	44.3	65.0	20.6	
Vert.	2402.0	93.4	27.6	4.7	34.9	90.9	-	-	Carrier
Vert.	2400.0	52.5	27.6	4.7	34.9	49.9	70.9	20.9	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Distance factor:
1 GHz - 10 GHz 20log (3.65 m / 3.0 m) = 1.71 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.2
Date	November 27, 2023
Temperature / Humidity	21 deg. C / 44 % RH
Engineer	Tomoya Sone
	(1 GHz to 10 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge and authorized band edge were shown in tabular data.

Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone	Shousei Hamaguchi
	(1 GHz to 10 GHz)	(10 GHz to 26.5 GHz)
Mode	Tx, Hopping Off, 3DH5 2441 MHz	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
Hori.	4882.0	41.7	34.0	31.6	6.9	34.2	-	46.0	38.4	73.9	53.9	27.9	15.6	Floor noise
Hori.	7323.0	42.7	34.6	36.2	8.1	34.1	-	52.9	44.7	73.9	53.9	21.0	9.2	Floor noise
Hori.	9764.0	42.6	34.1	39.3	8.9	34.7	-	56.1	47.6	73.9	53.9	17.8	6.3	Floor noise
Vert.	4882.0	41.9	33.9	31.6	6.9	34.2	-	46.3	38.3	73.9	53.9	27.7	15.6	Floor noise
Vert.	7323.0	42.1	34.4	36.2	8.1	34.1	-	52.2	44.6	73.9	53.9	21.7	9.4	Floor noise
Vert.	9764.0	43.1	34.2	39.3	8.9	34.7	-	56.6	47.7	73.9	53.9	17.3	6.2	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

*QP detector was used up to 1GHz.

Distance factor:	1 GHz - 10 GHz	20log (3.65 m / 3.0 m) = 1.71 dB
	10 GHz - 26.5 GHz	20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone	Shousei Hamaguchi
	(1 GHz to 10 GHz)	(10 GHz to 26.5 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
Hori.	2483.5	44.2	33.4	27.5	4.8	34.9	0.3	41.6	31.1	73.9	53.9	32.3	22.8	*1)
Hori.	4960.0	41.5	31.4	31.7	6.9	34.2	-	46.0	35.8	73.9	53.9	27.9	18.1	Floor noise
Hori.	7440.0	42.0	32.2	36.3	8.1	34.1	-	52.4	42.5	73.9	53.9	21.5	11.4	Floor noise
Hori.	9920.0	42.1	32.5	39.2	9.0	34.7	-	55.5	45.9	73.9	53.9	18.4	8.0	Floor noise
Vert.	2483.5	44.3	34.0	27.5	4.8	34.9	0.3	41.7	31.7	73.9	53.9	32.2	22.2	*1)
Vert.	4960.0	41.1	31.8	31.7	6.9	34.2	-	45.5	36.3	73.9	53.9	28.4	17.6	Floor noise
Vert.	7440.0	42.1	32.1	36.3	8.1	34.1	-	52.4	42.4	73.9	53.9	21.5	11.5	Floor noise
Vert.	9920.0	43.0	32.5	39.2	9.0	34.7	-	56.4	46.0	73.9	53.9	17.5	7.9	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).



*QP detector was used up to 1GHz

*1) Not Out of Band emission(Leakage Power)

Distance factor: 1 GHz - 10 GHz $20\log(3.65\text{ m} / 3.0\text{ m}) = 1.71\text{ dB}$
 10 GHz - 26.5 GHz $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

Radiated Spurious Emission
(Reference Plot for band-edge)


Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.2
Date	November 27, 2023
Temperature / Humidity	21 deg. C / 44 % RH
Engineer	Tomoya Sone
	(1 GHz to 10 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.
Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission
(Plot data, Worst case mode for Maximum Peak Output Power)

Test place	Ise EMC Lab.	No.2
Semi Anechoic Chamber	No.2	No.2
Date	November 27, 2023	November 28, 2023
Temperature / Humidity	21 deg. C / 44 % RH	19 deg. C / 49 % RH
Engineer	Tomoya Sone (1 GHz to 10 GHz)	Shousei Hamaguchi (10 GHz to 26.5 GHz) (Below 1 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz	





*These plots data contain sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx, Hopping Off, DH5



2402 MHz



Conducted Spurious Emission

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx, Hopping Off, DH5

2441 MHz





Conducted Spurious Emission

Test place
Date
Temperature / Humidity
Engineer
Mode

Ise EMC Lab. No.8 Measurement Room
November 28, 2023
22 deg. C / 50 % RH
Tetsuro Yoshida
Tx, Hopping Off, DH5



2480 MHz



Conducted Spurious Emission

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx, Hopping Off, 3DH5



2402 MHz



Conducted Spurious Emission

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx, Hopping Off, 3DH5



2441 MHz



Conducted Spurious Emission

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx, Hopping Off, 3DH5


2480 MHz




Conducted Emission Band Edge compliance

Test place Ise EMC Lab. No.8 Measurement Room
Date November 28, 2023
Temperature / Humidity 22 deg. C / 50 % RH
Engineer Tetsuro Yoshida
Mode Tx DH5

Hopping On



Hopping Off



Conducted Emission Band Edge compliance

Test place

Date

Temperature / Humidity

Engineer

Mode

Ise EMC Lab. No.8 Measurement Room


November 28, 2023

22 deg. C / 50 % RH


Tetsuro Yoshida

Tx 3DH5

Hopping On



Hopping Off



APPENDIX 2: Test Instruments

Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	141244	Attenuator(10dB)	Weinschel - API Technologies Corp	WA8-10-34	A198	02/01/2023	12
AT	141333	Attenuator(10dB)	Suhner	6810.19. A	-	12/21/2022	12
AT	141395	Coaxial Cable	UL Japan	-	-	11/21/2023	12
AT	141414	Microwave Cable	Junkosha	MWX221	1207S407	08/01/2023	12
AT	141557	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	70900530	01/18/2023	12
AT	141567	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0008	01/13/2023	12
AT	141809	Power Meter	Anritsu Corporation	ML2495A	825002	05/26/2023	12
AT	141830	Power sensor	Anritsu Corporation	MA2411B	738285	05/26/2023	12
AT	141901	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY48250080	01/16/2023	12
RE	141265	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-190	07/11/2023	12
RE	141296	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	002	09/01/2023	12
RE	141317	Coaxial Cable	UL Japan	-	-	09/12/2023	12
RE	141427	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103B+BBA9106	08031	07/11/2023	12
RE	141503	Horn Antenna 18-26.5GHz	EMCO	3160-09	1265	06/23/2023	12
RE	141512	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	254	10/17/2023	12
RE	141542	Digital Tester	Fluke Corporation	FLUKE 26-3	78030611	08/01/2023	12
RE	141579	Pre Amplifier	Keysight Technologies Inc	8449B	3008A02142	02/14/2023	12
RE	141594	Pre Amplifier	Keysight Technologies Inc	8447D	2944A10150	02/02/2023	12
RE	141884	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY44020357	03/13/2023	12
RE	213780	EMI Test Receiver	Rohde & Schwarz	ESW8	103079	12/07/2023	12
RE	142004	AC2_Semi Anechoic Chamber (NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	05/30/2022	24
RE	142228	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	192300	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0013	12/17/2022	12
RE	220646	Attenuator	Huber+Suhner	6806_N-50-1	-	03/17/2023	12
RE	240023	Microwave Cable	Huber+Suhner	SF126E/11PC35/11PC35/1000MM,5000MM	537060/126E / 537075/126E	09/08/2023	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

AT: Antenna Terminal Conducted test

RE: Radiated Emission