

§1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

According to subpart 1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency Range (MHz)	Maximum Antenna Gain		Tune Up Conducted Power	MPE Limit (mW/cm ²)	Minimum Safe Distance (cm)
	(dBi)	(numeric)	(mW)		
26.965-27.405	0	1	4000	0.24	36.42

To maintain compliance with the FCC's RF exposure guidelines, please place the equipment at least 36.42cm from nearby persons.

Result: Compliance