

Test report

347785-5TRFWL

Date of issue: March 12, 2018

Applicant:

GN Netcom Inc.

Product:

DECT Base Station without Bluetooth

Model:

WHB051BS

FCC ID:

BCE-WHB051BS

IC Reg. Number:

2386C-WHB051BS

Specifications:

- ◆ **FCC 47 CFR Part 15, Subpart D**

Isochronous UPCS Device, 1920–1930 MHz

- ◆ **RSS-213, Issue 3, March 2015**

2 GHz Licence-Exempt Personal Communications Services (LE-PCS) Devices

Test location

Company name	Nemko Canada Inc.
Address	303 River Road
City	Ottawa
Province	Ontario
Postal code	K1V 1H2
Country	Canada
Telephone	+1 613 737 9680
Facsimile	+1 613 737 9691
Toll free	+1 800 563 6336
Website	www.nemko.com
Site number	FCC: CA2040; IC: 2040A-4 (3 m semi anechoic chamber)

Tested by	Frode Sveinsen, Senior Wireless Engineer
Reviewed by	Andrey Adelberg, Senior Wireless/EMC Specialist
Date	March 12, 2018
Signature of reviewer	

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

CONTENTS

1	INFORMATION	4
1.1	Applicant information	4
1.2	Tested Item	4
1.3	Testing dates	4
1.4	Description of Tested Device	4
1.5	Test Conditions	5
1.6	Test Engineer(s)	5
1.7	Digital Modulation Techniques	5
1.8	Labeling Requirements	5
1.9	Antenna Requirement	5
1.10	Channel Frequencies	6
1.11	Other Comments	6
2	TEST REPORT SUMMARY	7
2.1	General	7
2.2	Test Summary	8
3	TEST RESULTS	9
3.1	Power Line Conducted Emissions	9
3.2	Automatic Discontinuation of Transmission	13
3.3	Peak Power Output	14
3.4	Emission Bandwidth B	21
3.5	Power Spectral Density	28
3.6	In-Band Unwanted Emissions, Conducted	37
3.7	Out-of-band Emissions, Conducted	44
3.8	Carrier Frequency Stability	61
3.9	Frame Repetition Stability	62
3.10	Frame Period and Jitter	62
3.11	Monitoring Threshold, Least Interfered Channel	64
3.12	Threshold Monitoring Bandwidth	66
3.13	Reaction Time and Monitoring Interval	67
3.14	Time and Spectrum Window Access Procedure	69
3.15	Acknowledgements and Transmission Duration	72
3.16	Dual Access Criteria Check	73
3.17	Alternative Monitoring Interval	74
4	MEASUREMENT UNCERTAINTY	75
5	TEST SETUPS	76
5.1	Frequency Measurements	76
5.2	Timing Measurements	76
5.3	Conducted Emission Test	76
5.4	Power Line Conducted Emissions Test	76
5.5	Monitoring Tests	77
6	TEST EQUIPMENT USED	78

1 INFORMATION

1.1 Applicant information

Name :	GN Netcom Inc.
Address:	900 Chelmsford Street, Tower II, 8th Floor Lowell, 1851, MA, USA

1.2 Tested Item

Name:	Jabra
Model name:	WHB051BS
FCC ID:	BCE-WHB051BS
Industry Canada Registration Number:	2386C-WHB051BS
Serial number:	/
Trademark:	Jabra
Hardware identity and/or version:	28-04447
Software identity and/or version:	1.6.4
Tested to ISED Radio Standard (RSS):	RSS-213 Issue 3; RSS-Gen Issue 4
Frequency Band:	1920–1930 MHz
Frequency Range:	1921.536–1928.448 MHz
Number of Channels:	5 RF Channels, 5 × 12 = 60 TDMA Duplex Channels
Type of Modulation:	GFSK, $\pi/2$ -DBPSK, $\pi/4$ -DQPSK, $\pi/8$ -D8PSK
Conducted Output Power:	49.0 mW (GFSK) 45.7 mW ($\pi/2$ -DBPSK) 43.7 mW ($\pi/4$ -DQPSK) 42.7 mW ($\pi/8$ -D8PSK)
Antenna Connector:	None
Number of Antennas:	2
Antenna Diversity Supported:	Yes
Power Supply:	AC Adaptor Model: Phihong AM05E-075A
Interface:	USB, USB for connection to Computer, Phone connection, Phone handset connection, AUX
Companion Device:	Headset Model: WHB050HS (FCC ID: BCE-WHB050HS)

1.3 Testing dates

Tested in period:	February 12, 2018 to February 16, 2018
--------------------------	--

1.4 Description of Tested Device

The EUT is a DECT Base Station without Bluetooth, and is a responding device as described in ANSI C63.17 and is designed to operate together with a DECT Headset, which is the initiating device.

This model is identical to the model WHB050BS (FCC ID: BCE-WHB050BS) except that the BT chip is removed on this model. All tests have been performed on a WH050BS.

1.5 Test Conditions

Temperature:	15–30 °C
Relative humidity	20–75 %
Air pressure	860–1060 mbar
Normal test voltage	120 V _{AC}

All tests were performed with the EUT powered from the mains.

The values are the limit registered during the test period.

1.6 Test Engineer(s)

Frode Sveinsen

1.7 Digital Modulation Techniques

The EUT uses Multi Carrier / Time Division Multiple Access / Time Division Duplex and Digital GFSK modulation. For further details see the operational description provided by the applicant.

Requirement, FCC 15.319(b):

All transmissions must use only digital modulation techniques.

1.8 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

Requirements FCC 15.19

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

1.9 Antenna Requirement

Does the EUT have detachable antenna(s)?	☐ YES	☒ NO
If detachable, is the antenna connector(s) non-standard?	☐ YES	☐ NO
The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.		

Requirement: FCC 15.203, 15.204, 15.317.

1.10 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
Upper Band Edge	1930.000
0 (Highest)	1928.448
1	1926.720
2	1924.992
3	1923.264
4 (Lowest)	1921.536
Lower Band Edge	1920.000

Requirement: FCC 15.303

Within 1920–1930 MHz band for isochronous devices.

1.11 Other Comments

The Monitoring and Time and Spectrum Window Access tests were performed with Test Set-Up 6 (Ref. clause 5). A clock signal from the companion device was used to synchronize the Pulse Pattern Generator and the Spectrum Analyzer to the start of the DECT time window. The EUT was limited by administrative commands to operate on only two frequency carriers. For the tests where the EUT was required to operate on only one frequency carrier, one carrier was blocked by applying a CW interfering signal from RF Generator 3. The Pulse Pattern Generator was used to apply time synchronized interference to time windows where this was required.

Since the EUT was programmed to operate on only two RF carriers, it was only necessary with two RF generators for the monitoring tests, however a third generator was applied for the tests that required specific time slots to be blocked.

The tested EUT supports both normal DECT slot length and DECT Long slot. Long slot is an extended DECT slot that allows a higher data rate for bit rates higher than 32 kbps.

This EUT supports Least Interfered Channel procedure (LIC), the Monitoring and Time and Spectrum Window Access tests were conducted as specified for EUTs that support LIC procedure.

All tests except Power-Line Conducted Emissions were performed in conducted mode with a temporary antenna connector.

The Power-Line Conducted Emissions test was performed with all ports populated and operating.

2 TEST REPORT SUMMARY

2.1 General

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15 Subpart D for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 3 / RSS-Gen Issue 4 / RSP-100 Issue 11.

All tests were conducted in accordance with ANSI C63.4-2014 and ANSI C63.17-2013.

A description of the test facility is on file with the FCC and Industry Canada.

☒ New Submission

☒ Production Unit

☐ Class II Permissive Change

☐ Pre-production Unit

PUB Equipment Code

☐ Family Listing



THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

2.2 Test Summary

Name of test	FCC CFR 47 Paragraph #	IC RSS-213 Paragraph #	Verdict
Power Line Conducted Emission	15.107(a) 15.207(a)	5.4 RSS-GEN 8.8	Complies
Digital Modulation Techniques	15.319(b)	5.1	Complies
Labeling requirements	15.19(a)(3)	RSP-100 3.1	Complies
Antenna Requirement	15.317, 15.203	RSS-GEN 8.3	Complies
Channel Frequencies	15.303	5.1	Complies
Automatic discontinuation of transmission	15.319(f)	5.2 (4)	Complies
Emission Bandwidth	15.323(a)	5.5 RSS-GEN 6.6	Complies
In-band emissions	15.323(d)	5.8.2	Complies
Out-of-band emissions	15.323(d)	5.8.1	Complies
Peak Transmit Power and Antenna Gain	15.319(c)(e), 15.31(e)	5.6 RSS-GEN 8.3	Complies
Power Spectral Density	15.319(d)	5.7	Complies
Carrier frequency stability	15.323(f)	5.3	Complies
Frame repetition stability	15.323(e)	5.2 (13)	Complies
Frame period and jitter	15.323(e)	5.2 (13)	Complies
Monitoring threshold, Least interfered channel	15.323(c)(2)(5)(9)	5.2 (2)(5)(9)	Complies
Monitoring of intended transmit window and maximum reaction time	15.323(c)(1)	5.2 (1)	Complies
Threshold monitoring bandwidth	15.323(c)(7)	5.2 (7)	Complies
Reaction time and monitoring interval	15.323(c)(1)(5)(7)	5.2 (1)(5)(7)	Complies
Access criteria test interval	15.323(c)(4)(6)	5.2 (4)(6)	Complies
Access Criteria functional test	15.323(c)(4)(6)	5.2 (4)(6)	Complies
Acknowledgements	15.323(c)(4)	5.2 (4)	N/A ¹
Transmission duration	15.323(c)(3)	5.2 (3)	Complies
Dual access criteria	15.323(c)(10)	5.2 (10)	N/A ¹
Alterative monitoring interval	15.323(c)(11)(12)	5.2 (11)(12)	N/A ²
Spurious Emissions (Radiated)	15.319(g) 15.109(a), 15.209(a)	RSS-GEN 8.9	N/A ³

¹ Only applies for EUT that can be initiating device

² The client declares that the tested equipment does not implement this provision

³ Not required if the Conducted Out-of-Band Emissions test is Passed

3 TEST RESULTS

3.1 Power Line Conducted Emissions

FCC Part 15.207(a)


RSS-213 Clause 6.3, RSS-GEN Clause 8.8

Measurement procedure: ANSI C63.4-2014 using 50 μ H/50 ohms LISN.


Test Results: Complies

Measurement Data: See attached plots


Frequency (MHz)	Line	Detector	Measured (dB μ V)	Limit (dB μ V)	Margin (dB)
0.456000	N	AV	37.76	46.77	9.01
12.002500	N	QP	45.84	60	14.16
12.306250	N	QP	42.44	60	17.56
12.524500	L1	QP	43.11	60	16.89
12.569500	L1	QP	45.86	60	14.14
12.592000	L1	QP	42.44	60	17.56
12.922750	N	QP	42.84	60	17.16



120V 60Hz, WHB050HS Headset Charging, Phase N




120V 60Hz, WHB050HS Headset Charging, Phase L1




Jabra CE 120 Vac 60 Hz charging Neutral MN WHB051BS SN 030ABC6BF0
 Preview Result 2-AVG
 Preview Result 1-PK+
 CISPR 32 Mains Q-Peak Class B Limit
 CISPR 32 Mains Average Class B Limit
 Final_Result QPK
 Final_Result CAV

120V 60Hz, WHB051HS Headset Charging, Phase N



Jabra CE 120 Vac 60 Hz charging Phase MN WHB051BS SN 030ABC6BF0
 Preview Result 2-AVG
 Preview Result 1-PK+
 CISPR 32 Mains Q-Peak Class B Limit
 CISPR 32 Mains Average Class B Limit
 Final_Result QPK
 Final_Result CAV


120V 60Hz, WHB051HS Headset Charging, Phase L1



Jabra CE 120 Vac 60 Hz operational Neutral MN WHB051BS SN 030ABC6BF0

Preview Result 2-AVG
Preview Result 1-PK+
CISPR 32 Mains Q-Peak Class B Limit
CISPR 32 Mains Average Class B Limit
Final_Result QPK
Final_Result CAV

120V 60Hz, Off-Hook Mode, Phase N



Jabra CE 120 Vac 60 Hz operational Phase MN WHB051BS SN 030ABC6BF0

Preview Result 2-AVG
Preview Result 1-PK+
CISPR 32 Mains Q-Peak Class B Limit
CISPR 32 Mains Average Class B Limit
Final_Result QPK
Final_Result CAV

120V 60Hz, Off-Hook Mode, Phase L1

3.2 Automatic Discontinuation of Transmission

Does the EUT transmit Control and Signaling Information?	☒ YES	☐ NO
TYPE OF EUT :	☐ INITIATING DEVICE	☒ RESPONDING DEVICE

The following tests simulate the reaction of the EUT in case of either absence of information to transmit or operational failure after a connection with the companion device is established.

Number	Test	EUT Reaction	Verdict
1	Power removed from EUT	A	Pass
2	Switch Off EUT	N/A	Pass
3	Hook-On by EUT	N/A	Pass
4	Power Removed from Companion Device	B	Pass
5	Switch Off Companion Device	B	Pass
6	Hook-On by Companion Device	B	Pass

- A - Connection breakdown, Cease of all transmissions
B - Connection breakdown, EUT transmits control and signaling information
C - Connection breakdown, Companion Device transmits control and signaling information
N/A - Not Applicable (EUT does not have On/Off switch and cannot perform Hook-On)

Requirements, FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

3.3 Peak Power Output

Test Method:

ANSI C63.17, clause 6.1.2.

Test Results: Complies

Measurement Data:

Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power* (dBm)				Maximum Antenna Gain** (dBi)	Maximum Radiated Output Power (dBm)
		GFSK	$\pi/2$ -DBPSK	$\pi/4$ -DQPSK	$\pi/8$ -D8PSK		
4	1921.536	16.9	16.6	16.4	16.3	1.0	17.9
2	1924.992	16.8	16.5	16.3	16.1	1.0	17.8
0	1928.448	16.7	16.4	16.3	16.0	1.0	17.7

*Output Power value is Peak Power of DECT Burst

**Antenna Gain is value declared by manufacturer

For this test it was also checked that input voltage variation of 85 and 115% of nominal value did not have any effect on the measured output power.

Limit:

Conducted: $100 \mu\text{W} \times \text{SQRT}(B)$ where B is the measured Emission Bandwidth in Hz

FCC 15.319(c)(e) and RSS-213, Issue 3:

GFSK-Modulation: 20.7 dBm (118 mW)
PSK-Modulation: 21.1 dBm (130 mW)

The antenna gain is below 3 dBi, no reduction in transmit power is necessary.

Requirements, FCC 15.319(c)(e); RSS-213, Issue 3; RSS-GEN, Issue 4


Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.




Date: 13.FEB.2018 09:21:30

Conducted Peak Output Power, Lower Channel, GFSK




Date: 13.FEB.2018 09:23:24

Conducted Peak Output Power, Lower Channel, $\pi/2$ -DBPSK



Date: 13.FEB.2018 09:26:08

Conducted Peak Output Power, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 09:27:11

Conducted Peak Output Power, Lower Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 09:20:35

Conducted Peak Output Power, Middle Channel, GFSK




Date: 13.FEB.2018 09:23:53

Conducted Peak Output Power, Middle Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 09:25:33

Conducted Peak Output Power, Middle Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 09:27:39

Conducted Peak Output Power, Middle Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 09:21:05

Conducted Peak Output Power, Upper Channel, GFSK




Date: 13.FEB.2018 09:24:30

Conducted Peak Output Power, Upper Channel, $\pi/2$ -DBPSK



Date: 13.FEB.2018 09:25:04

Conducted Peak Output Power, Upper Channel, $\pi/4$ -DQPSK



Date: 13.FEB.2018 09:28:24

Conducted Peak Output Power, Upper Channel, $\pi/8$ -D8PSK

3.4 Emission Bandwidth B

Test Method:

ANSI C63.17, clause 6.1.3.

Test Results: Complies

Measurement Data:

Channel No.	Frequency (MHz)	Emission Bandwidth B (MHz)			
		GFSK	$\pi/2$ -DBPSK	$\pi/4$ -DQPSK	$\pi/8$ -D8PSK
4	1921.536	1.41	1.71	1.70	1.70
0	1928.448	1.40	1.71	1.74	1.71


Channel No.	Frequency (MHz)	Occupied Bandwidth (MHz)			
		GFSK	$\pi/2$ -DBPSK	$\pi/4$ -DQPSK	$\pi/8$ -D8PSK
2	1924.992	1.19	1.44	1.42	1.42

Requirements, FCC 15.323(a), RSS-213 Issue 3, clause 5.5

The Emission Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.


No requirements for 6 and 12 dB Bandwidth, these values are only used for testing Monitoring Bandwidth if the Simple Compliance test fails (ANSI C63.17, clause 7.4).

Occupied Bandwidth (99%) is measured according to RSS-GEN Issue 4, clause 6.6. This value is reported for information only.




Date: 13.FEB.2018 09:42:38

Emission Bandwidth B, Lower Channel, GFSK




Date: 13.FEB.2018 09:32:00

Emission Bandwidth B, Upper Channel, GFSK




Date: 13.FEB.2018 10:13:34

Emission Bandwidth B, Lower Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 10:11:29

Emission Bandwidth B, Upper Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 10:26:00

Emission Bandwidth B, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 09:59:44

Emission Bandwidth B, Upper Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 10:28:36

Emission Bandwidth B, Lower Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 09:57:54

Emission Bandwidth B, Upper Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 09:44:46

99% Bandwidth, Middle Channel, GFSK




Date: 13.FEB.2018 09:46:26

99% Bandwidth, Middle Channel, $\pi/2$ -DBPSK



Date: 13.FEB.2018 09:49:02

99% Bandwidth, Middle Channel, $\pi/4$ -DQPSK



Date: 13.FEB.2018 09:52:03

99% Bandwidth, Middle Channel, $\pi/8$ -D8PSK

3.5 Power Spectral Density

Test Method:

ANSI C63.17, clause 6.1.5.

Test Results: Complies


Measurement Data:

Channel No.	Frequency (MHz)	Power Spectral Density (dBm/3 kHz)			
		GFSK	$\pi/2$ -DBPSK	$\pi/4$ -DQPSK	$\pi/8$ -D8PSK
4	1921.536	-0.1	-3.8	-2.0	-4.5
0	1928.448	0.1	-4.4	-2.0	-4.6

Averaged over 1000 sweeps.


Requirements, FCC 15.319(d)

The Power Spectral Density shall be less than 3 mW (4.77 dBm/3 kHz) when averaged over at least 100 sweeps.




Date: 13.FEB.2018 11:17:56

PSD, Overview, Lower Channel, GFSK




Date: 13.FEB.2018 11:20:55

PSD, Averaged, 1000 Sweeps, Lower Channel, GFSK




Date: 13.FEB.2018 11:24:55

PSD, Overview. Upper Channel, GFSK, GFSK




Date: 13.FEB.2018 11:26:59

PSD, Averaged, 1000 Sweeps, Upper Channel, GFSK




Date: 13.FEB.2018 11:31:14

PSD, Overview, Lower Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 11:32:25

PSD, Averaged, 1000 Sweeps, Lower Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 11:28:55

PSD, Overview. Upper Channel, GFSK, $\pi/2$ -DBPSK




Date: 13.FEB.2018 11:29:53

PSD, Averaged, 1000 Sweeps, Upper Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 12:25:32

PSD, Overview, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 12:26:54

PSD, Averaged, 1000 Sweeps, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 12:33:35

PSD, Overview. Upper Channel, GFSK, $\pi/4$ -DQPSK




Date: 13.FEB.2018 12:34:36

PSD, Averaged, 1000 Sweeps, Upper Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 12:51:15

PSD, Overview, Lower Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 12:52:22

PSD, Averaged, 1000 Sweeps, Lower Channel, $\pi/8$ -D8PSK



Date: 13.FEB.2018 12:39:19

PSD, Overview. Upper Channel, GFSK, $\pi/8$ -D8PSK



Date: 13.FEB.2018 12:40:26

PSD, Averaged, 1000 Sweeps, Upper Channel, $\pi/8$ -D8PSK

3.6 In-Band Unwanted Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.1.

Test Results: Complies

Measurement Data:


See plots.

Requirements, FCC 15.323(d):

$B < f \leq 2B$: at least 30 dB below max. permitted peak power


$2B < f \leq 3B$: at least 50 dB below max. permitted peak power

$3B < f \leq$ UPCS Band Edge : at least 60 dB below max. permitted peak power




Date: 13.FEB.2018 11:15:05

In-Band Unwanted Emissions, Lower Channel, GFSK




Date: 13.FEB.2018 11:14:07

In-Band Unwanted Emissions, Middle Channel, GFSK




Date: 13.FEB.2018 11:08:18

In-Band Unwanted Emissions, Upper Channel, GFSK




Date: 13.FEB.2018 10:46:54

In-Band Unwanted Emissions, Lower Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 10:48:14

In-Band Unwanted Emissions, Middle Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 11:06:53

In-Band Unwanted Emissions, Upper Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 10:45:36

In-Band Unwanted Emissions, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 10:54:56

In-Band Unwanted Emissions, Middle Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 11:06:05

In-Band Unwanted Emissions, Upper Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 10:40:46

In-Band Unwanted Emissions, Lower Channel, $\pi/8$ -D8PSK



Date: 13.FEB.2018 10:56:05

In-Band Unwanted Emissions, Middle Channel, $\pi/8$ -D8PSK



Date: 13.FEB.2018 11:02:07

In-Band Unwanted Emissions, Upper Channel, $\pi/8$ -D8PSK

3.7 Out-of-band Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.2.


Test Results: Complies

Measurement Data:


See plots.

Requirements, FCC 15.323(d):

$f \leq 1.25$ MHz outside UPCS band :	≤ -9.5 dBm
$1.25 \text{ MHz} \leq f \leq 2.5$ MHz outside UPCS band :	≤ -29.5 dBm
$f \geq 2.5$ MHz outside UPCS band :	≤ -39.5 dBm




Date: 13.FEB.2018 15:00:17




Date: 13.FEB.2018 13:06:09

Out-of-Band Emissions, Lower Channel, GFSK




Date: 13.FEB.2018 13:04:59

Out-of-Band Emissions, Lower Channel, GFSK




Date: 13.FEB.2018 15:02:00

Out-of-Band Emissions, Upper Channel, GFSK




Date: 13.FEB.2018 15:04:28

Out-of-Band Emissions, Middle Channel, GFSK




Date: 13.FEB.2018 15:14:10




Date: 13.FEB.2018 15:15:12

Out-of-Band Emissions, Middle Channel, GFSK




Date: 13.FEB.2018 14:58:29




Date: 13.FEB.2018 13:10:55

Out-of-Band Emissions, Lower Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 12:59:36

Out-of-Band Emissions, Lower Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 15:20:38

Out-of-Band Emissions, Upper Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 15:31:02

Out-of-Band Emissions, Middle Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 15:32:39




Date: 13.FEB.2018 15:16:25

Out-of-Band Emissions, Middle Channel, $\pi/2$ -DBPSK




Date: 13.FEB.2018 14:56:32




Date: 13.FEB.2018 13:16:00

Out-of-Band Emissions, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 12:56:52

Out-of-Band Emissions, Lower Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 15:21:43

Out-of-Band Emissions, Upper Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 15:29:39

Out-of-Band Emissions, Middle Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 15:33:44




Date: 13.FEB.2018 15:17:28

Out-of-Band Emissions, Middle Channel, $\pi/4$ -DQPSK




Date: 13.FEB.2018 13:25:34




Date: 13.FEB.2018 13:17:07

Out-of-Band Emissions, Lower Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 12:55:42

Out-of-Band Emissions, Lower Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 15:23:03

Out-of-Band Emissions, Upper Channel, $\pi/8$ -D8PSK




Date: 13.FEB.2018 15:27:51

Out-of-Band Emissions, Middle Channel, $\pi/8$ -D8PSK



Date: 13.FEB.2018 15:35:12



Date: 13.FEB.2018 15:18:22

Out-of-Band Emissions, Middle Channel, $\pi/8$ -D8PSK

3.8 Carrier Frequency Stability

Test Method:

ANSI C63.17, clause 6.2.1.

Test Results: Complies

Measurement Data:

Long Term Frequency Stability is measured with the HP53310A Modulation Domain analyzer. The HP53310A is logged by a computer programmed to get new readings as fast as possible over the noted number of readings. The peak-to-peak difference was recorded and the mean value and deviation in ppm was calculated.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

Carrier Frequency Stability over Time at Nominal Temperature

Average Mean Carrier Frequency (MHz)	Max. Diff. (kHz)	Min. Diff. (kHz)	Max. Dev. (ppm)	Limit
1925.004171	14.092	10.867	1.0	±10 ppm

Deviation ppm = ((Diff. - Mean Diff) / Mean Carrier Freq.) x 10⁶

Deviation (ppm) is calculated from 3000 readings.

Frequency Stability over Power Supply Voltage at Nominal Temperature

Voltage	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
V _{nom}	1924.9864	0	0	±10 ppm
85% of V _{nom}	1924.9865	0.1	0.1	
115% of V _{nom}	1924.9864	0	0	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10⁶

This test does not apply for EUT that is powered from batteries.

Frequency Stability over Temperature

Temperature	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
T = +20 °C	1924.9864	0	0	±10 ppm
T = -20 °C	1924.9943	7.9	4.1	
T = +50 °C	1924.9809	-5.5	-2.9	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10⁶

3.9 Frame Repetition Stability

Test Method:

ANSI C63.17, clause 6.2.2.

Test Results: Complies

Measurement Data:

The envelope of the RF signal from the EUT is detected with a Crystal Detector and the mean and standard deviation of the frame repetition frequency is then gated over 100 frames and measured with a Frequency Domain Analyzer. The frame repetition stability is 3 times the standard deviation.

Carrier Frequency (MHz)	Mean (Hz)	Standard Deviation (μHz)	Frame Repetition Stability (ppm)
1924.992	100.000	1.276	0.038

Limit:

Frame Repetition Stability	±10 ppm (TDMA)
----------------------------	----------------

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.2

3.10 Frame Period and Jitter

Test Method:

ANSI C63.17, clause 6.2.3.

Test Results: Complies

Measurement Data:

The envelope of the RF signal from the EUT is detected with a Crystal Detector and the frame period and jitter is measured with a Frequency Domain Analyzer over at least 100.000 frames.

Carrier Frequency (MHz)	Frame Period (ms)	Max Jitter (μs)	3xStandard Deviation of Jitter (μs)
1924.992	10.000	-0.036	-0.033


Max Jitter = $(1 / (\text{Frame period} + \text{Pk-Pk}/2)) - (1 / \text{Frame Period})$, when Pk-Pk and Frame Period are in Hz

3xSt.Dev.Jitter = $3x (1 / (\text{Frame Period} + \text{St.Dev}) - 1 / \text{St.Dev}) \times 10^6$

Limit:


Frame Period	20 or 10 ms
Max Jitter	25 μs
3 times St.Dev of Jitter	12.5 μs

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.3



Mean	99.9999548009 Hz	1/Mean	10.000ms
Pk-Pk	7.13 μHz	Std Dev	1.2755 μHz

Frame Repetition Stability, Gated over 100 Frames



Mean	99.999948204 Hz	1/Mean	10.000ms
Pk-Pk	724 μHz	Std Dev	110.388 μHz

Frame Period and Jitter

3.11 Monitoring Threshold, Least Interfered Channel

Monitoring Threshold Limits:

Lower Threshold:

$$T_L = 15 \log B - 184 + 30 - P_{EUT} \quad (\text{dBm})$$

B is measured Emission Bandwidth in Hz
 P_{EUT} is measured Transmitter Power in dBm

Calculated values:

	FCC 15.323, RSS-213, Issue 3
Lower Threshold	-78.7 dBm

Least Interfered Channel Procedure (LIC) may only be used by systems with more than 20 duplex system access channels. Systems with less than 20 duplex system access channels are not allowed to transmit when interferer level is above Lower Threshold.

Measurement Procedure:

Least Interfered Channel Procedure NOT used:	
Lower Threshold	N/A The EUT uses LIC procedure

Least Interfered Channel (LIC) Procedure Test, FCC 15.323(b), (c)(2) and (c)(5)


ANSI C63.17 clause 7.3.2 ref.	Observation	Verdict
b) f_1 at $T_L + U_M + 7$ dB, f_2 at $T_L + U_M$	Transmission always on f_2	Pass
c) f_1 at $T_L + U_M$, f_2 at $T_L + U_M + 7$ dB	Transmission always on f_1	Pass
d) f_1 at $T_L + U_M + 1$ dB, f_2 at $T_L + U_M - 6$ dB	Transmission always on f_2	Pass
e) f_1 at $T_L + U_M - 6$ dB, f_2 at $T_L + U_M + 1$ dB	Transmission always on f_1	Pass

Selected Channel Confirmation, FCC 15.323(c)(1) and (5)

ANSI C63.17 clause 7.3.3	Observation	Verdict
b) Shall not transmit on f_1	EUT transmits on f_2	Pass
d) Shall not transmit on f_2	EUT transmits on f_1	Pass

Limits:

	FCC 15.323, RSS-213, Issue 3
Lower Threshold + 6 dB margin	-72.7 dBm



Date: 14.FEB.2018 15:07:14

7.3.4 Selected Channel Confirmation, Connection 2.1s After Interferer Removed

3.12 Threshold Monitoring Bandwidth

This test is only required if a dedicated monitoring receiver is used. However, if the test is not carried out the manufacturer shall declare and provide proper evidence that the monitoring is made through the radio receiver used for communication.

Measurement Procedure:

Simple Compliance Test, ANSI C63.17, clause 7.4.1

More Detailed Test, ANSI C63.17, clause 7.4.2

The test is passed if **either** the Simple Compliance Test or the More Detailed test is passed.

During this test the spectrum analyzer is observed visually to see if the EUT transmits or not.

Test Results:

Test performed	Observation	Verdict
Simple Compliance test, at $\pm 30\%$ of B	N/A	N/A
More Detailed Test, at -6 dB points	N/A	N/A
More Detailed Test, at -12 dB points	N/A	N/A

The more detailed test must be pass at both the -6 and -12 dB points if the Simple Compliance test fails.

Comment: The manufacturer declares that the tested EUT uses the same receiver for monitoring and communication, this test is therefore not required.

Limits, FCC 15.323(c)(7):

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission.

3.13 Reaction Time and Monitoring Interval

Measurement Procedure

ANSI C63.17, clause 7.5

Test results:

By administrative commands and out-of-operating region interference, the EUT is restricted to operate on two RF carrier frequencies.

A CW interferer signal at a level T_L is applied on f_i and time-synchronized pulsed interference at a level $T_L + U_M$ dB is applied on f_2 . The level on f_2 was raised 6 dB for part d) with 35 μ s pulses.

The pulses are synchronized with the EUT timeslots and applied centered within all timeslots.

For both tests the test is passed if the EUT transmits on f_i .


Pulse Width, ref. to ANSI C63.17 clause 7.5	Observation	Verdict
c) > largest of 50 μ s and $50 \times \text{SQRT}(1.25/B)$	EUT transmits on f_i	Pass
d) > largest of 35 μ s and $35 \times \text{SQRT}(1.25/B)$, and with interference level raised 6 dB	EUT transmits on f_i	Pass

Comment: Since B is larger than 1.25 MHz the test was performed with pulse lengths of 50 μ s and 35 μ s.

Limits, FCC 15.323(c)(1), (5) and (7)


The maximum reaction time must be less than $50 \times \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 μ s.

If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be $35 \times \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds but shall not be required to be less than 35 μ s.



Date: 14.FEB.2018 15:10:30

50 µs Pulses



Date: 14.FEB.2018 15:13:02

35 µs Pulses

3.14 Time and Spectrum Window Access Procedure

This requirement is only for EUTs which transmit unacknowledged control and signaling information.

Measurement Procedure:

Timing for EUTs using control and signaling channel type transmissions: ANSI C63.17, clause 8.1

Test results:

Access Criteria, ref. to ANSI C63.17 clause 8.1.1	Observation	Verdict
b) Check that the EUT transmits on the interference free time-slot	EUT transmits on the interference free time-slot	Pass
b) The EUT must terminate or pause in its repetitive transmission of the control and signalling channel on the open channel to repeat the access criteria not less frequently than every 30 s	Transmission paused every 1.28 s	Pass

If FCC 15.323(c)(6) option, **If Random Waiting Interval is NOT implemented**

Access Criteria, ref. to ANSI C63.17 clause 8.1.2	Observation	Verdict
b) Check that the EUT changes to an interference-free slot when interference is introduced on the time slot in use	EUT changes to the interference-free time-slot, and stays there	Pass

If FCC 15.323(c)(6) option, **Only if Random Waiting Interval is implemented**

Access Criteria, ref. to ANSI C63.17 clause 8.1.3	Observation	Verdict
b-d) Check that the EUT uses random waiting interval before continuing transmission on an interfered time slot	N/A	N/A

Comment: The tested EUT does not support the Random Waiting Interval option.

Limits:

FCC 15.323(c)(4):


Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

FCC 15.323(c)(6):

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available




Access Criteria Check




Date: 14.FEB.2018 15:17:57

8.1.1b) Access Criteria check Interval

Access Criteria Check



Date: 14.FEB.2018 15:16:24



Date: 14.FEB.2018 15:16:48

8.1.2 Access Criteria Functional Test, Before and After

3.15 Acknowledgements and Transmission Duration

Measurement Procedure:

Acknowledgements: ANSI C63.17, clause 8.2.1

Transmission Duration: ANSI C63.17, clause 8.2.2

During the test **Initial transmission without acknowledgements** the signal from the EUT to the companion device is blocked by circulators in addition to the tunable attenuator.

The test **Transmission time after loss of acknowledgements** is performed by cutting-off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

The **Transmission Duration** test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

Test Results:

Acknowledgements

Test ref. to ANSI C63.17 clause 8.2.1	Observation	Verdict
a) Initial transmission without acknowledgements	Not applicable for EUT that transmits control and signaling information	N/A
c) Transmission time after loss of acknowledgements	5.0 sec	Pass

Transmission Duration

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict
b) Transmission duration on same time and frequency window	Only for initiating device that controls which time slot is used	N/A

Comment: /

Limits, FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgements must be received at least every 30 seconds or transmission must cease.

Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

3.16 Dual Access Criteria Check

Measurement Procedure:

EUTs that does not implement the LIC procedure: ANSI C63.17, clause 8.3.1

EUTs that implement the LIC procedure: ANSI C63.17, clause 8.3.2

This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

Test Results:

EUTs that do NOT implements the LIC procedure:

Test ref. to ANSI C63.17 clause 8.3.1	Observation	Verdict
b) EUT is restricted to a single carrier f_i for TDMA systems. The Test is Pass if EUT can transmit	N/A	N/A
c) d) Interference at level $T_L + U_M$ on all timeslots except one receive slot where interference is at least 10 dB below T_L	N/A	N/A
e) f) Interference at level $T_L + U_M$ on all timeslots except one transmit slot where interference is at least 10 dB below T_L	N/A	N/A

EUTs that implements the LIC procedure:

Test ref. to ANSI C63.17 clause 8.3.2	Observation	Verdict
b) EUT is restricted to a single carrier f_i for TDMA systems. The Test is Pass if EUT can transmit	N/A	N/A
c) d) Transmission on interference-free receive time/spectrum window	N/A	N/A
e) f) Transmission on interference-free transmit time/spectrum window	N/A	N/A

Comment: This test is only applicable for EUT that can be initiating device.

Limits, FCC 15.323(c)(10)

An initiating device may attempt to establish a duplex connection by monitoring both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

3.17 Alternative Monitoring Interval

Test procedure described in ANSI C63.17 clause 8.4.

This test is required if the EUT implements the provisions of FCC 15.323(c)(11).

Test result:

Not Tested. The tested EUT does not implement this provision. See manufacturers' declaration.

4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item		Uncertainty
Output Power		±0.5 dB
Power Spectral Density		±0.5 dB
Out of Band Emissions, Conducted (RBW < 100 kHz)	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth		±4 %
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error		±0.6 ppm
Timing and Jitter Measurements		±2.0 ns
Frame Timing Measurements		±1.4 ppm
Receiver Blocking Levels		±1.0 dB
Temperature Uncertainty		±1 °C

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2

5 Test Setups


5.1 Frequency Measurements



Test Set-up 1

This setup is used for measuring Carrier frequency stability at normal and extreme temperatures.


5.2 Timing Measurements



Test Set-up 2

This setup is used for measuring Frame repetition stability, Frame period and Jitter.


5.3 Conducted Emission Test



Test Set-up 3


This setup is used for all conducted emission tests.

5.4 Power Line Conducted Emissions Test



Test Set-Up 5

5.5 Monitoring Tests



Test Set-Up 6

This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generators to the EUT is measured with a power meter before the testing is started.

The CLK100 is used to synchronize the Pulse-/ Pattern generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the CLK100 signal will come from the Companion Device.

The sync signal to the Spectrum Analyzer is the CLK100 signal that is regenerated in the Pulse-/ Pattern Generator, this is used to synchronize the Spectrum Analyzer to the DECT frame when in zero span. The Pulse-/ Pattern Generator is used for tests that require time synchronized pulses or blocking of specific time slots.

6 Test Equipment Used

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Testhouse.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSP30	Spectrum Analyzer	Rohde & Schwarz	LR 1551	2017.06	2019.06
2	SMIQ06B	Signal generator	Rohde & Schwarz	SN: 100481	2017.08	2018.08
3	SMIQ03E	Signal generator	Rohde & Schwarz	FA001269	2016.04	2018.04
4	SMR40	Signal generator	Rohde & Schwarz	FA001879	COU	
5	53310A	Modulation Domain Analyzer	Hewlett Packard	LR 1483	COU	
6	81110A	Pulse-/ Pattern Generator	Agilent	LR 1725	COU	
7	8470B	Crystal Detector	Hewlett Packard	LR 1207	N/A	
8	6810.17B	Attenuator	Suhner	LR 1669	COU	
9	745-69	Step Attenuator	Narda	LR 1442	N/A	
10	WE 1506A	Power Splitter	Weinchel	LR 244	COU	
11	WE 1506A	Power Splitter	Weinchel	LR 245	COU	
12	H-9	Hybrid	Anzac	LR 86	COU	
13	H-9	Hybrid	Anzac	LR 257	COU	
14	S212DS	RF Switch	Narda	LR 1244	N/A	
15	87H35-1	Circulator	Racal-MESL	s.no.: 140	N/A	
16	87H35-1	Circulator	Racal-MESL	s.no.: 141	N/A	
17	87H35-1	Circulator	Racal-MESL	s.no.: 142	N/A	
18	ESU 26	Receiver/spectrum analyzer	Rohde & Schwarz	FA002043	2018.01	2019.01
19	ENV216	LISN	Rohde & Schwarz	FA002023	2017.05	2018.05
20	ST18/SMA/N/36	RF Cable	Suhner	LR 1630	COU	

Note: COU – calibrate on use; N/A – Not Applicable

The software listed below has been used for one or more tests.

No.	Manufacturer	Name	Version	Comment
1	Agilent	Intuitlink Data Capture	2.1.0	Screenshots from HP 53310A
2	Rohde & Schwarz	EMC 32	9.26.01	Software for EMC Measurements of Power-Line Conducted Tests

Revision history

Version	Date	Comment	Sign
1.0	2017.11.14	First edition	FS