

## MEASUREMENT REPORT

### FCC PART 15.247 Bluetooth (Low Energy)

**Applicant Name:**  
Apple Inc.  
1 Infinite Loop  
Cupertino, CA 95014  
United States

**Date of Testing:**  
6/9-8/9/2017  
**Test Site/Location:**  
PCTEST Lab., Morgan Hill, CA, USA  
**Test Report Serial No.:**  
1C1706160002-58-03-R3.BCG

**FCC ID:** BCG-A1858

**APPLICANT:** Apple Inc.

**Application Type:** Certification  
**Model:** A1858, A1959  
**EUT Type:** Watch  
**Max. RF Output Power:** 87.096 mW (19.4 dBm) Peak Conducted  
**Frequency Range:** 2402 - 2480 MHz  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15.247  
**Test Procedure(s):** KDB 558074 D01 v04, KDB 648474 D03 v01r04,  
KDB 414788 D01 Radiated Test Site v01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01 v04. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1C1706160002-58-03-R3.BCG) supersedes and replaces the previously issued test report (S/N: 1C1706160002-58-03-R2.BCG) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortanez  
President




|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 1 of 57                           |

## T A B L E O F C O N T E N T S


|                                                                 |    |
|-----------------------------------------------------------------|----|
| FCC PART 15.247 MEASUREMENT REPORT .....                        | 3  |
| 1.0 INTRODUCTION.....                                           | 4  |
| 1.1 Scope .....                                                 | 4  |
| 1.2 PCTEST Test Location.....                                   | 4  |
| 2.0 PRODUCT INFORMATION .....                                   | 5  |
| 2.1 Equipment Description .....                                 | 5  |
| 2.2 Device Capabilities.....                                    | 5  |
| 2.3 Antenna Description .....                                   | 5  |
| 2.4 Test Support.....                                           | 5  |
| 2.5 Test Configuration .....                                    | 6  |
| 2.6 Software and Firmware .....                                 | 6  |
| 2.7 EMI Suppression Device(s)/Modifications .....               | 6  |
| 3.0 DESCRIPTION OF TESTS .....                                  | 7  |
| 3.1 Evaluation Procedure .....                                  | 7  |
| 3.2 AC Line Conducted Emissions .....                           | 7  |
| 3.3 Radiated Emissions.....                                     | 8  |
| 3.4 Environmental Conditions .....                              | 8  |
| 4.0 ANTENNA REQUIREMENTS .....                                  | 9  |
| 5.0 MEASUREMENT UNCERTAINTY .....                               | 10 |
| 6.0 TEST EQUIPMENT CALIBRATION DATA.....                        | 11 |
| 7.0 TEST RESULTS .....                                          | 12 |
| 7.1 Summary.....                                                | 12 |
| 7.2 6dB Bandwidth Measurement – Bluetooth (LE) .....            | 13 |
| 7.3 Output Power Measurement – Bluetooth (LE).....              | 18 |
| 7.3.1 Peak Output Power Measurement - Bluetooth (LE) .....      | 20 |
| 7.3.2 Average Output Power Measurement - Bluetooth (LE) .....   | 21 |
| 7.4 Power Spectral Density – Bluetooth (LE) .....               | 25 |
| 7.5 Conducted Emissions at the Band Edge .....                  | 30 |
| 7.6 Conducted Spurious Emissions.....                           | 33 |
| 7.7 Radiated Spurious Emission Measurements – Above 1GHz .....  | 38 |
| 7.8 Radiated Restricted Band Edge Measurements.....             | 45 |
| 7.9 Radiated Spurious Emissions Measurements – Below 1GHz ..... | 49 |
| 7.10 Line-Conducted Test Data .....                             | 53 |
| 8.0 CONCLUSION .....                                            | 57 |

|                                                      |                                                                                                                                                          |                           |                                        |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
| FCC ID: BCG-A1858                                    |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                           | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                                                                                       | <b>EUT Type:</b><br>Watch | Page 2 of 57                           |



## MEASUREMENT REPORT

### FCC Part 15.247



#### § 2.1033 General Information

**APPLICANT:** Apple Inc.  
**APPLICANT ADDRESS:** 1 Infinite Loop  
 Cupertino, CA 95014, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 18855 Adams Court, Morgan Hill, CA 95037 USA  
**FCC RULE PART(S):** Part 15.247  
**BASE MODEL:** A1858, A1959  
**FCC ID:** BCG-A1858  
**FCC CLASSIFICATION:** Digital Transmission System (DTS)  
**Test Device Serial No.:** FH7TX0HAJ880, ☐ Production ☒ Pre-Production ☐ Engineering  
 FH7V100FJ87X  
**DATE(S) OF TEST:** 6/9-8/9/2017  
**TEST REPORT S/N:** 1C1706160002-58-03-R3.BCG

#### Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab located in Morgan Hill, CA 95037, U.S.A.**

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 3 of 57                           |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science, and Economic Development Canada.

### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 18855 Adams Court, Morgan Hill, CA 95037.

|                                                      |                                                                                                                                                          |                           |                                        |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                           | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                                                                                       | <b>EUT Type:</b><br>Watch | Page 4 of 57                           |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID: BCG-A1858**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application. The EUT operates in two power schemes per modulation. The power schemes are Internal Pre Amplifier (iPA) and External Pre Amplifier (ePA). According to the manufacturer, models A1858 and A1959 are electrically identical. Model A1858 was used for final testing.

### 2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n WLAN, Bluetooth (1x, EDR, LE), NFC

### 2.3 Antenna Description

Following antenna was used for the testing.

| Frequency (GHz) | Antenna Gain (dBi) |
|-----------------|--------------------|
| 2.4             | -13.39             |

Table 2-1. Antenna Peak Gain

### 2.4 Test Support

|   |                             |        |                    |         |                     |
|---|-----------------------------|--------|--------------------|---------|---------------------|
| 1 | Apple MacBook               | Model: | A1502              | S/N:    | C02NQ01YG465        |
|   | w/ AC/DC Adapter            | Model: | A1435              | S/N:    | C04325505K1F288BG   |
| 2 | Apple USB Cable             | Model: | Kanzi              | S/N:    | 20153D              |
|   | w/ Charging Dock            | Model: | FAPS61             | S/N:    | 6304000736          |
|   | w/ Dock                     | Model: | X241               | S/N:    | SJH3002AP2AS        |
| 3 | USB Cable                   | Model: | N/A                | S/N:    | N/A                 |
|   |                             |        | Shielded USB Cable |         |                     |
| 4 | w/ AC Adapter               | Model: | B353               | S/N:    | N/A                 |
| 5 | Test Pathfinder Board       | Model: | X988               | S/N:    | FGH7648700BDHVMV323 |
| 6 | Wireless Charging Pad (WCP) | Model: | A1598              | FCC ID: | BCGA1598            |

Table 2-2. Test Support Equipment Used

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 5 of 57                    |

## 2.5 Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups. Additional radiated spurious emissions measurements were performed with the EUT on a certified wireless charging pad (WCP) while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

The worst case configuration was investigated for all combinations of the three materials, aluminum, ceramic, and stainless steel, and various types of wristbands, metal and non-metal wrist bands. The store display sample was investigated with the three types of EUTs. The EUT was also investigated with and without wireless charger.

The worst case configuration found was used for all testing. The worst case material was aluminum. The worst case accessory was metal wristband but no significant difference was found between various types of wrist bands.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report. The worst orientation was found to be X-orientation (flatbed).

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB cable with wireless charger
- EUT powered by host PC via USB cable with wireless charger

## 2.6 Software and Firmware

The test was conducted with firmware version 15R328 installed on the EUT.

For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance.

## 2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

|                                                      |                                                                                                                                                          |                           |                                        |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
| FCC ID: BCG-A1858                                    |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                           | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                                                                                       | <b>EUT Type:</b><br>Watch | Page 6 of 57                           |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v04 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.20.01.

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 7 of 57                    |

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm high Styrodur Plastic Test Table is placed on top of the turntable. For measurements above 1GHz, another Styrodur Plastic Test Table of 70cm height is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 8 of 57                    |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

### Conclusion:

The EUT complies with the requirement of §15.203.

|                                               |                                                                                                                                                  |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                      | EUT Type:<br>Watch | Page 9 of 57                    |

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                     | Expanded Uncertainty ( $\pm$ dB) |
|----------------------------------|----------------------------------|
| Conducted Bench Top Measurements | 1.13                             |
| Line Conducted Disturbance       | 3.09                             |
| Radiated Disturbance (<1GHz)     | 4.98                             |
| Radiated Disturbance (>1GHz)     | 5.07                             |
| Radiated Disturbance (>18GHz)    | 5.09                             |

|                                                      |                                                                                                                                                      |                           |                                        |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
| FCC ID: BCG-A1858                                    |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                           | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                                                                                   | <b>EUT Type:</b><br>Watch | Page 10 of 57                          |

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

| Manufacturer          | Model           | Description                    | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-----------------------|-----------------|--------------------------------|------------|--------------|------------|---------------|
| -                     | ACLC Conducted  | ACLC Emissions Cable Set       | 3/17/2017  | Biennial     | 10/1/2017  | CAACLC1       |
| -                     | AM WN25         | WLAN Cable Set                 | 3/17/2017  | Annual       | 3/17/2018  | AM WN25       |
| -                     | EMI 3117-ESW1   | Radiated Cable Set             | 3/1/2017   | Biennial     | 3/1/2018   | N/A           |
| -                     | EMI HL562E-ESW1 | Radiated Cable Set             | 2/28/2017  | Biennial     | 2/28/2018  | N/A           |
| Anritsu               | MA2411B         | Pulse Power Sensor             | 10/14/2015 | Biennial     | 10/14/2017 | 1027293       |
| Anritsu               | ML2495A         | Power Meter                    | 10/16/2015 | Biennial     | 10/16/2017 | 1039008       |
| Rohde & Schwarz       | 180-442AKF      | 20dB Nominal Gain Horn Antenna | 2/24/2017  | Annual       | 2/24/2018  | T058701-03    |
| COM-POWER             | LIN-120A        | LISN                           | 2/22/2017  | Annual       | 2/22/2018  | 241296        |
| Keysight Technologies | N9030A          | 3Hz-44Ghz PXA Signal Analyzer  | 3/13/2017  | Annual       | 3/13/2018  | MY49430244    |
| Rohde & Schwarz       | ERTS.2          | Loop Antenna Cable Set         | 3/17/2017  | Biennial     | 3/17/2018  | AM Loop1      |
| Rohde & Schwarz       | ESW26           | ESW26 EMI Test Receiver        | 1/20/2017  | Annual       | 1/20/2018  | 101299        |
| Rohde & Schwarz       | FSV40           | Signal Analyzer                | 12/23/2016 | Annual       | 12/23/2017 | 101619        |
| Rohde & Schwarz       | HL562E          | Bi-Log Antenna                 | 1/19/2017  | Annual       | 1/19/2018  | 100610        |
| Rohde & Schwarz       | OSP130          | Open Switch and Control Unit   | 1/18/2017  | Annual       | 1/18/2018  | 100970        |
| Rohde & Schwarz       | SFUNIT-RX       | TS-SFUNIT SHIELDED FILTER UNIT | 2/3/2017   | Annual       | 2/3/2018   | 102131        |
| Rohde & Schwarz       | TS-PR18         | Pre-Amplifier (1GHz - 18GHz)   | 2/3/2017   | Annual       | 2/3/2018   | 101639        |
| Rohde & Schwarz       | TS-PR1840       | Pre-Amplifier (18GHz - 40GHz)  | 2/3/2017   | Annual       | 2/3/2018   | 100052        |
| Rohde & Schwarz       | TS-PR8          | Pre-amplifier (30MHz - 8GHz)   | 2/3/2017   | Annual       | 2/3/2018   | 102325        |
| Rohde & Schwarz       | TC-TA18         | CROSS POL. VIVALDI ANT         | 11/8/2016  | Annual       | 11/8/2017  | 101056-AE     |
| UTIFlex               | TS9975/FSC40    | 40GHz Micro Coax Cable         | 4/1/2017   | Biennial     | 10/1/2017  | 200200        |

**Table 6-1. Annual Test Equipment Calibration Schedule**

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 11 of 57                   |

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Apple Inc.  
 FCC ID: BCG-A1858  
 FCC Classification: Digital Transmission System (DTS)  
 Number of Channels: 40

| FCC Part Section(s) | Test Description                                                              | Test Limit                                                                     | Test Condition | Test Result | Reference              |
|---------------------|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------|----------------|-------------|------------------------|
| 15.247(a)(2)        | 6dB Bandwidth                                                                 | > 500kHz                                                                       | CONDUCTED      | PASS        | Section 7.2            |
| 15.247(b)(3)        | Transmitter Output Power                                                      | < 1 Watt                                                                       |                | PASS        | Sections 7.3           |
| 15.247(e)           | Transmitter Power Spectral Density                                            | < 8dBm / 3kHz Band                                                             |                | PASS        | Section 7.4            |
| 15.247(d)           | Band Edge / Out-of-Band Emissions                                             | ≥ 20dBc                                                                        |                | PASS        | Sections 7.5, 7.6      |
| 15.205<br>15.209    | General Field Strength Limits (Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 | RADIATED       | PASS        | Sections 7.7, 7.8, 7.9 |
| 15.207              | AC Conducted Emissions 150kHz – 30MHz                                         | < FCC 15.207 limits                                                            | LINE CONDUCTED | PASS        | Section 7.10           |

**Table 7-1. Summary of Test Results**

#### Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Bluetooth LE Automation," Version 3.0.

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 12 of 57                   |

## 7.2 6dB Bandwidth Measurement – Bluetooth (LE)

### §15.247(a.2)

#### Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

**The minimum permissible 6dB bandwidth is 500 kHz.**

#### Test Procedure Used

KDB 558074 D01 v04 – Section 8.2 Option 2

#### Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

#### Test Notes


None

|                                               |                                                                                                                                                          |                    |                                 |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                              | EUT Type:<br>Watch | Page 13 of 57                   |


| Frequency [MHz] | Modulation | Power Scheme | Channel No. | Bluetooth Mode | Measured Bandwidth [kHz] | Minimum Bandwidth [kHz] | Pass / Fail |
|-----------------|------------|--------------|-------------|----------------|--------------------------|-------------------------|-------------|
| 2402            | GFSK       | ePA          | 0           | LE             | 714.1                    | 500                     | Pass        |
| 2440            | GFSK       | ePA          | 19          | LE             | 713.9                    | 500                     | Pass        |
| 2480            | GFSK       | ePA          | 39          | LE             | 715.4                    | 500                     | Pass        |
| 2402            | GFSK       | iPA          | 0           | LE             | 712.6                    | 500                     | Pass        |
| 2440            | GFSK       | iPA          | 19          | LE             | 716.9                    | 500                     | Pass        |
| 2480            | GFSK       | iPA          | 39          | LE             | 713.8                    | 500                     | Pass        |

**Table 7-2. Conducted Bandwidth Measurements**

|                                                      |                                                                                     |                                                                  |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                        | Page 14 of 57                          |




Plot 7-1. 6dB Bandwidth Plot (Bluetooth (LE), ePA – Ch. 0)




Plot 7-2. 6dB Bandwidth Plot (Bluetooth (LE), ePA – Ch. 19)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 15 of 57                   |




Plot 7-3. 6dB Bandwidth Plot (Bluetooth (LE), ePA – Ch. 39)



Plot 7-4. 6dB Bandwidth Plot (Bluetooth (LE), iPA – Ch. 0)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 16 of 57                   |



Plot 7-5. 6dB Bandwidth Plot (Bluetooth (LE), iPA – Ch. 19)



Plot 7-6. 6dB Bandwidth Plot (Bluetooth (LE), iPA – Ch. 39)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 17 of 57                   |

## 7.3 Output Power Measurement – Bluetooth (LE)

### §15.247(b.3)

#### Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

**The maximum permissible conducted output power is 1 Watt.**

#### Test Procedure Used

KDB 558074 D01 v04 – Section 9.1.1  
KDB 558074 D01 v04 – Section 9.2.3.2 Method AVGPM-G

#### Test Settings

##### Method 1 (Peak Power Measurement)

1. RBW = 3MHz
2. VBW = 28MHz
3. Span  $\geq 3 \times$  RBW
4. Sweep = auto couple
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

##### Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

|                                               |                                                                                                                                                          |                    |                                 |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                              | EUT Type:<br>Watch | Page 18 of 57                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-2. Test Instrument & Measurement Setup for Peak Power Measurement**



**Figure 7-3. Test Instrument & Measurement Setup for Average Power Measurement**

## Test Notes

None

|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 19 of 57                          |

### 7.3.1 Peak Output Power Measurement - Bluetooth (LE)

§15.247(b.3)

| Frequency<br>[MHz] | Modulation | Power<br>Scheme | Channel<br>No. | Peak Conducted<br>Power |        |
|--------------------|------------|-----------------|----------------|-------------------------|--------|
|                    |            |                 |                | [dBm]                   | [mW]   |
| 2402               | GFSK       | ePA             | 0              | 18.68                   | 73.790 |
| 2441               | GFSK       | ePA             | 19             | 19.40                   | 87.096 |
| 2480               | GFSK       | ePA             | 39             | 19.25                   | 84.140 |
| 2402               | GFSK       | iPA             | 0              | 12.92                   | 19.588 |
| 2441               | GFSK       | iPA             | 19             | 13.25                   | 21.135 |
| 2480               | GFSK       | iPA             | 39             | 12.93                   | 19.634 |

**Table 7-3. Peak Conducted Output Power Measurements (Bluetooth (LE))**

|                                                      |                                                                                                                                                          |                           |                                        |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                           | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                                                                                       | <b>EUT Type:</b><br>Watch | Page 20 of 57                          |


### 7.3.2 Average Output Power Measurement - Bluetooth (LE)

§15.247(b.3)


| Frequency<br>[MHz] | Modulation | Power<br>Scheme | Channel<br>No. | Ave Conducted<br>Power |        |
|--------------------|------------|-----------------|----------------|------------------------|--------|
|                    |            |                 |                | [dBm]                  | [mW]   |
| 2402               | GFSK       | ePA             | 0              | 18.00                  | 63.096 |
| 2441               | GFSK       | ePA             | 19             | 18.51                  | 70.958 |
| 2480               | GFSK       | ePA             | 39             | 18.30                  | 67.608 |
| 2402               | GFSK       | iPA             | 0              | 12.20                  | 16.596 |
| 2441               | GFSK       | iPA             | 19             | 12.42                  | 17.458 |
| 2480               | GFSK       | iPA             | 39             | 12.03                  | 15.959 |

Table 7-4. Average Conducted Output Power Measurements (Bluetooth (LE))

|                                               |                                                                                                                                                          |                    |                                 |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                              | EUT Type:<br>Watch | Page 21 of 57                   |




Plot 7-7. Peak Power Plot (Bluetooth (LE), ePA – Ch. 0)




Plot 7-8. Peak Power Plot (Bluetooth (LE), ePA – Ch. 19)

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 22 of 57                   |




Plot 7-9. Peak Power Plot (Bluetooth (LE), ePA – Ch. 39)




Plot 7-10. Peak Power Plot (Bluetooth (LE), iPA – Ch. 0)

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 23 of 57                   |



Plot 7-11. Peak Power Plot (Bluetooth (LE), iPA – Ch. 19)



Plot 7-12. Peak Power Plot (Bluetooth (LE), iPA – Ch. 39)

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 24 of 57                   |

## 7.4 Power Spectral Density – Bluetooth (LE)

### §15.247(e)

#### Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

**The maximum permissible power spectral density is 8 dBm in any 3 kHz band.**

#### Test Procedure Used

KDB 558074 D01 v04 – Section 10.2 Method PKPSD

#### Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3.  $RBW = 3\text{kHz} < RBW < 100\text{kHz}$
4.  $VBW = 1\text{MHz}$
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Test Instrument & Measurement Setup**

#### Test Notes


None

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 25 of 57                   |


| Frequency [MHz] | Modulation | Power Scheme | Channel No. | Bluetooth Mode | Measured Power Spectral Density [dBm] | Maximum Permissible Power Density [dBm / 3kHz] | Margin [dB] |
|-----------------|------------|--------------|-------------|----------------|---------------------------------------|------------------------------------------------|-------------|
| 2402            | GFSK       | ePA          | 0           | LE             | 4.71                                  | 8.0                                            | -3.29       |
| 2440            | GFSK       | ePA          | 19          | LE             | 5.97                                  | 8.0                                            | -2.03       |
| 2480            | GFSK       | ePA          | 39          | LE             | 6.08                                  | 8.0                                            | -1.92       |
| 2402            | GFSK       | iPA          | 0           | LE             | 3.14                                  | 8.0                                            | -4.86       |
| 2440            | GFSK       | iPA          | 19          | LE             | 3.13                                  | 8.0                                            | -4.87       |
| 2480            | GFSK       | iPA          | 39          | LE             | 3.30                                  | 8.0                                            | -4.71       |

**Table 7-5. Conducted Power Density Measurements**

|                                                      |                                                                                     |                                                                  |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                        | Page 26 of 57                          |




Plot 7-13. Power Spectral Density Plot (Bluetooth (LE), ePA – Ch. 0)



Plot 7-14. Power Spectral Density Plot (Bluetooth (LE), ePA – Ch. 19)

|                                               |                                                                                                                                                      |                    |                                 |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                          | EUT Type:<br>Watch | Page 27 of 57                   |



Plot 7-15. Power Spectral Density Plot (Bluetooth (LE), ePA – Ch. 39)



Plot 7-16. Power Spectral Density Plot (Bluetooth (LE), iPA – Ch. 0)

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 28 of 57                   |



Plot 7-17. Power Spectral Density Plot (Bluetooth (LE), iPA – Ch. 19)



Plot 7-18. Power Spectral Density Plot (Bluetooth (LE), iPA – Ch. 39)

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 29 of 57                   |

## 7.5 Conducted Emissions at the Band Edge

### §15.247(d)

#### Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

**The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.**

#### Test Procedure Used

KDB 558074 D01 v04 – Section 11.3

#### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-5. Test Instrument & Measurement Setup**


#### Test Notes

None

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 30 of 57                   |




Plot 7-19. Band Edge Plot (Bluetooth (LE), ePA - Ch. 0)




Plot 7-20. Band Edge Plot (Bluetooth (LE), ePA - Ch. 39)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 31 of 57                   |



Plot 7-21. Band Edge Plot (Bluetooth (LE), iPA – Ch. 0)



Plot 7-22. Band Edge Plot (Bluetooth (LE), iPA – Ch. 39)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 32 of 57                   |

## 7.6 Conducted Spurious Emissions

### §15.247(d)

#### Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.1 of KDB 558074 D01 v04.

#### Test Procedure Used

KDB 558074 D01 v04 – Section 11.3

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-6. Test Instrument & Measurement Setup**

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 33 of 57                   |


### **Test Notes**

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

|                                                      |                                                                                                                                                          |                           |                                        |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> |                           | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                                                                                       | <b>EUT Type:</b><br>Watch | Page 34 of 57                          |




Plot 7-23. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 0)




Plot 7-24. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 0)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 35 of 57                   |




Plot 7-25. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 19)




Plot 7-26. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 19)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 36 of 57                   |



Plot 7-27. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39)



Plot 7-28. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39)

|                                               |                                                              |                    |                                 |
|-----------------------------------------------|--------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                  | EUT Type:<br>Watch | Page 37 of 57                   |

## 7.7 Radiated Spurious Emission Measurements – Above 1GHz

§15.205 §15.209 §15.247(d)

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-6 per Section 15.209.

| Frequency       | Field Strength<br>[ $\mu\text{V/m}$ ] | Measured Distance<br>[Meters] |
|-----------------|---------------------------------------|-------------------------------|
| Above 960.0 MHz | 500                                   | 3                             |

**Table 7-6. Radiated Limits**

### Test Procedures Used

KDB 558074 D01 v04 – Section 12.1, 12.2.7

### Test Settings

#### Average Field Strength Measurements per Section 12.2.5.1 of KDB 558074 D01 v04

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times \text{span/RBW}$ )
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

#### Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 D01 v04

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 38 of 57                   |

| Frequency    | RBW          |
|--------------|--------------|
| 9 – 150kHz   | 200 – 300Hz  |
| 0.15 – 30MHz | 9 – 10kHz    |
| 30 – 1000MHz | 100 – 120kHz |
| > 1000MHz    | 1MHz         |

**Table 7-7. RBW as a Function of Frequency**

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Radiated Test Setup >1GHz**

|                                                      |                                               |                                                                      |                                        |
|------------------------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017            | <b>EUT Type:</b><br>Watch                                            | Page 39 of 57                          |

## Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v04 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-8.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. No significant radiated band edge emissions were found in the 2310 – 2390MHz restricted band.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

## Sample Calculations

### Determining Spurious Emissions Levels

- Field Strength Level  $_{[dB_{\mu V/m}]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB_{\mu V/m}]} - \text{Limit}_{[dB_{\mu V/m}]}$

### Radiated Band Edge Measurement Offset




- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 40 of 57                   |

## Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d)



|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 41 of 57                   |


## Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209



Date: 9.JUL.2017 03:31:50

Plot 7-32. Radiated Spurious Plot above 18GHz (GFSK ePA, Pol. H)



Date: 8.JUL.2017 21:37:33

Plot 7-33. Radiated Spurious Plot above 18GHz (GFSK ePA, Pol. V)

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 42 of 57                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.6  
06/06/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d)

Bluetooth Mode: LE  
 Modulation: GFSK  
 Power Scheme: ePA  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2402MHz  
 Channel: 0

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 4804.00         | Avg      | V               | -                   | -                          | -76.45               | 0.08        | 30.63                   | 53.98          | -23.34      |
| 4804.00         | Peak     | V               | -                   | -                          | -64.83               | 0.08        | 42.25                   | 73.98          | -31.72      |
| 12010.00        | Avg      | V               | -                   | -                          | -77.95               | 14.07       | 43.12                   | 53.98          | -10.86      |
| 12010.00        | Peak     | V               | -                   | -                          | -66.55               | 14.07       | 54.52                   | 73.98          | -19.46      |

**Table 7-9. Radiated Measurements @ 3 meters**

Bluetooth Mode: LE  
 Modulation: GFSK  
 Power Scheme: ePA  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2441MHz  
 Channel: 19

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 4882.00         | Avg      | V               | -                   | -                          | -76.69               | 0.73        | 31.04                   | 53.98          | -22.94      |
| 4882.00         | Peak     | V               | -                   | -                          | -65.18               | 0.73        | 42.55                   | 73.98          | -31.43      |
| 7323.00         | Avg      | V               | -                   | -                          | -77.89               | 5.54        | 34.65                   | 53.98          | -19.33      |
| 7323.00         | Peak     | V               | -                   | -                          | -66.40               | 5.54        | 46.14                   | 73.98          | -27.84      |
| 12205.00        | Avg      | V               | -                   | -                          | -78.08               | 14.29       | 43.21                   | 53.98          | -10.77      |
| 12205.00        | Peak     | V               | -                   | -                          | -66.93               | 14.29       | 54.36                   | 73.98          | -19.62      |

**Table 7-10. Radiated Measurements @ 3 meters**

|                                               |                                                                                                                                                      |                    |                                 |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                          | EUT Type:<br>Watch | Page 43 of 57                   |

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d)

|                           |          |
|---------------------------|----------|
| Bluetooth Mode:           | LE       |
| Modulation:               | GFSK     |
| Power Scheme:             | ePA      |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 2480MHz  |
| Channel:                  | 39       |

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 4960.00         | Avg      | V               | -                   | -                          | -76.22               | 0.39        | 31.17                   | 53.98          | -22.81      |
| 4960.00         | Peak     | V               | -                   | -                          | -65.13               | 0.39        | 42.26                   | 73.98          | -31.72      |
| 7440.00         | Avg      | V               | -                   | -                          | -77.91               | 5.67        | 34.76                   | 53.98          | -19.22      |
| 7440.00         | Peak     | V               | -                   | -                          | -66.46               | 5.67        | 46.21                   | 73.98          | -27.77      |
| 12400.00        | Avg      | V               | -                   | -                          | -78.05               | 14.85       | 43.80                   | 53.98          | -10.18      |
| 12400.00        | Peak     | V               | -                   | -                          | -66.96               | 14.85       | 54.89                   | 73.98          | -19.09      |

**Table 7-11. Radiated Measurements @ 3 meters**

|                                               |                                                                                                                                                      |                    |  |                                 |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                          | EUT Type:<br>Watch |  | Page 44 of 57                   |

## 7.8 Radiated Restricted Band Edge Measurements


\$15.205 \$15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

|                       |          |
|-----------------------|----------|
| Bluetooth Mode:       | LE       |
| Modulation:           | GFSK     |
| Power Scheme:         | ePA      |
| Measurement Distance: | 3 Meters |
| Operating Frequency:  | 2402MHz  |
| Channel:              | 0        |



Date: 17 JUL 2017 17:57:23

**Plot 7-34. Radiated Restricted Upper Band Edge Measurement (Average & Peak)**

|                                               |                                               |                                                              |  |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|--|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           |  | Page 45 of 57                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.6  
06/06/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

## Radiated Restricted Band Edge Measurements

### \$15.205 \$15.209

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Bluetooth Mode: LE


Modulation: GFSK

Power Scheme: iPA

Measurement Distance: 3 Meters

Operating Frequency: 2402MHz

Channel: 0



Date: 17 JUL 2017 18:44:16

**Plot 7-35. Radiated Restricted Upper Band Edge Measurement (Average & Peak)**

|                                               |                                                                  |                    |                                 |
|-----------------------------------------------|------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                      | EUT Type:<br>Watch | Page 46 of 57                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.6  
06/06/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

## Radiated Restricted Band Edge Measurements

### §15.205 §15.209

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Bluetooth Mode: LE


Modulation: GFSK

Power Scheme: ePA

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 39



Date: 17 JUL 2017 18:24:04

**Plot 7-36. Radiated Restricted Upper Band Edge Measurement (Average & Peak)**

|                                               |                                                                                                                                                      |                    |                                 |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                          | EUT Type:<br>Watch | Page 47 of 57                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.6  
06/06/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

## Radiated Restricted Band Edge Measurements

### §15.205 §15.209

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Bluetooth Mode: LE


Modulation: GFSK

Power Scheme: iPA

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 39



Date: 17 JUL 2017 19:00:42

**Plot 7-37. Radiated Restricted Upper Band Edge Measurement (Average & Peak)**

|                                               |                                                                                                                                                      |                    |                                 |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT (CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                                                                                          | EUT Type:<br>Watch | Page 48 of 57                   |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.6  
06/06/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

## 7.9 Radiated Spurious Emissions Measurements – Below 1GHz

### §15.209

#### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-12 per Section 15.209.

| Frequency         | Field Strength<br>[ $\mu\text{V/m}$ ] | Measured Distance<br>[Meters] |
|-------------------|---------------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                          | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                         | 30                            |
| 1.705 – 30.00 MHz | 30                                    | 30                            |
| 30.00 – 88.00 MHz | 100                                   | 3                             |
| 88.00 – 216.0 MHz | 150                                   | 3                             |
| 216.0 – 960.0 MHz | 200                                   | 3                             |
| Above 960.0 MHz   | 500                                   | 3                             |

**Table 7-12. Radiated Limits**

#### Test Procedures Used

ANSI C63.10-2013

#### Test Settings


##### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 49 of 57                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-8. Radiated Test Setup < 30Mhz**




**Figure 7-9. Radiated Test Setup < 1GHz**

|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 50 of 57                          |

## Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-12.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. The unit was tested with all possible mode and power schemes and only the highest emission is reported.

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 51 of 57                   |



**Plot 7-38. Radiated Spurious Plot below 1GHz (GFSK ePA, Pol. H & V)**

| Frequency [MHz] | Detector   | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 30.48           | Quasi-Peak | V               | -                   | -                          | -60.24               | -19.43      | 27.33                   | 40.00          | -12.67      |
| 48.90           | Quasi-Peak | V               | -                   | -                          | -62.44               | -24.87      | 19.69                   | 40.00          | -20.31      |
| 79.91           | Quasi-Peak | H               | -                   | -                          | -62.05               | -25.01      | 19.94                   | 40.00          | -20.06      |
| 100.25          | Quasi-Peak | H               | -                   | -                          | -63.16               | -24.02      | 19.82                   | 43.52          | -23.70      |
| 112.85          | Quasi-Peak | H               | -                   | -                          | -63.49               | -25.93      | 17.58                   | 43.52          | -25.94      |
| 248.52          | Quasi-Peak | V               | -                   | -                          | -65.05               | -24.76      | 17.19                   | 46.02          | -28.83      |

**Table 7-13. Radiated Spurious Emissions Below 1GHz**

|                                               |                                                                                     |                                                              |  |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|--|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           |  | Page 52 of 57                   |

## 7.10 Line-Conducted Test Data

### §15.207

#### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below, per 15.207.**

| Frequency of emission (MHz) | Conducted Limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15 – 0.5                  | 66 to 56*              | 56 to 46* |
| 0.5 – 5                     | 56                     | 46        |
| 5 – 30                      | 60                     | 50        |

**Table 7-14. Conducted Limits**

\*Decreases with the logarithm of the frequency.

#### Test Procedures Used

ANSI C63.10-2013, Section 6.2

#### Test Settings

##### Quasi-Peak Field Strength Measurements

- Analyzer center frequency was set to the frequency of the spurious emission of interest
- RBW = 9kHz (for emissions from 150kHz – 30MHz)
- Detector = quasi-peak
- Sweep time = auto couple
- Trace mode = max hold
- Trace was allowed to stabilize


##### Average Field Strength Measurements

- Analyzer center frequency was set to the frequency of the spurious emission of interest
- RBW = 9kHz (for emissions from 150kHz – 30MHz)
- Detector = RMS
- Sweep time = auto couple
- Trace mode = max hold
- Trace was allowed to stabilize

|                                               |                                                                                     |                                                              |                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             |  | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                                                         | EUT Type:<br>Watch                                           | Page 53 of 57                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-10. Test Instrument & Measurement Setup**

## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207.
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

|                                               |                                               |                                                              |                                 |
|-----------------------------------------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------------|
| FCC ID: BCG-A1858                             | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1706160002-58-03-R3.BCG | Test Dates:<br>6/9-8/9/2017                   | EUT Type:<br>Watch                                           | Page 54 of 57                   |




**Plot 7-39. Line Conducted Plot with Bluetooth LE (GFSK ePA, L1)**

| Frequency<br>MHz | Process State | QuasiPeak<br>dBμV | Average<br>dBμV | Limit<br>dBμV | Margin<br>dB | Bandwidth<br>kHz | Line | PE  |
|------------------|---------------|-------------------|-----------------|---------------|--------------|------------------|------|-----|
| 0.152250         | FINAL         | 46.20             | —               | 65.88         | 19.68        | 9.000            | L1   | GND |
| 0.152250         | FINAL         | —                 | 34.28           | 55.88         | 21.59        | 9.000            | L1   | GND |
| 0.251250         | FINAL         | 37.08             | —               | 61.72         | 24.63        | 9.000            | L1   | GND |
| 0.251250         | FINAL         | —                 | 29.29           | 51.72         | 22.42        | 9.000            | L1   | GND |
| 0.627000         | FINAL         | 35.02             | —               | 56.00         | 20.98        | 9.000            | L1   | GND |
| 0.631500         | FINAL         | —                 | 28.96           | 46.00         | 17.04        | 9.000            | L1   | GND |
| 1.959000         | FINAL         | —                 | 23.11           | 46.00         | 22.89        | 9.000            | L1   | GND |
| 1.959000         | FINAL         | 28.70             | —               | 56.00         | 27.30        | 9.000            | L1   | GND |
| 7.509750         | FINAL         | —                 | 24.21           | 50.00         | 25.79        | 9.000            | L1   | GND |
| 7.509750         | FINAL         | 27.77             | —               | 60.00         | 32.23        | 9.000            | L1   | GND |
| 26.774250        | FINAL         | 34.72             | —               | 60.00         | 25.28        | 9.000            | L1   | GND |
| 26.774250        | FINAL         | —                 | 33.07           | 50.00         | 16.93        | 9.000            | L1   | GND |

**Table 7-15. Line Conducted Table with Bluetooth LE (GFSK ePA, L1)**

|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 55 of 57                          |



**Plot 7-40. Line Conducted Plot with Bluetooth LE (GFSK ePA, N)**

| Frequency<br>MHz | Process State | QuasiPeak<br>dBμV | Average<br>dBμV | Limit<br>dBμV | Margin<br>dB | Bandwidth<br>kHz | Line | PE  |
|------------------|---------------|-------------------|-----------------|---------------|--------------|------------------|------|-----|
| 0.152250         | FINAL         | 46.20             | —               | 65.88         | 19.67        | 9.000            | N    | GND |
| 0.152250         | FINAL         | —                 | 33.47           | 55.88         | 22.41        | 9.000            | N    | GND |
| 0.303000         | FINAL         | 32.93             | —               | 60.16         | 27.23        | 9.000            | N    | GND |
| 0.303000         | FINAL         | —                 | 23.65           | 50.16         | 26.51        | 9.000            | N    | GND |
| 0.584250         | FINAL         | 31.09             | —               | 56.00         | 24.91        | 9.000            | N    | GND |
| 0.584250         | FINAL         | —                 | 23.33           | 46.00         | 22.67        | 9.000            | N    | GND |
| 2.028750         | FINAL         | 19.13             | —               | 56.00         | 36.87        | 9.000            | N    | GND |
| 2.037750         | FINAL         | —                 | 12.39           | 46.00         | 33.61        | 9.000            | N    | GND |
| 7.860750         | FINAL         | —                 | 19.05           | 50.00         | 30.95        | 9.000            | N    | GND |
| 8.038500         | FINAL         | 25.43             | —               | 60.00         | 34.57        | 9.000            | N    | GND |
| 24.490500        | FINAL         | 27.34             | —               | 60.00         | 32.66        | 9.000            | N    | GND |
| 24.490500        | FINAL         | —                 | 24.19           | 50.00         | 25.81        | 9.000            | N    | GND |

**Table 7-16. Line Conducted Table with Bluetooth LE (GFSK ePA, N)**

|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 56 of 57                          |

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Watch** **FCC ID: BCG-A1858** is in compliance with Part 15C of the FCC Rules.

|                                                      |                                                                                     |                                                                      |                                        |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BCG-A1858                             |  | <b>FCC Pt. 15.247 BLUETOOTH (LE) TEST REPORT<br/>(CERTIFICATION)</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1C1706160002-58-03-R3.BCG | <b>Test Dates:</b><br>6/9-8/9/2017                                                  | <b>EUT Type:</b><br>Watch                                            | Page 57 of 57                          |