TEST SETUP PHOTOS

Report Number: 14523771-EP1V1

TABLE OF CONTENTS

1. SCOPE 2
2. A2849 SETUP PHOTOS 3
2.1. 2.4GHz/5GHz /NB /6E TECHNOLOGIES 3
2.1.1. BT/BLE/HDR/DTS/UNII/NB/6E RADIATED RF MEASUREMENT SETUP 4
2.2. NFC TECHNOLOGY 6
2.2.1. RADIATED RF MEASUREMENT SETUP 7
2.3. WPT RADIATED AND AC LINE SETUP 8
2.4. WWAN TECHNOLOGIES 9
2.5. UWB TECHNOLOGIES SETUP 10
2.5.1. RADIATED RF MEASUREMENT SETUP 11
2.6. CBSD SETUP PHOTO 15
2.7. RF EXPOSURE SETUP PHOTO 16
2.7.1. RF Exposure 16
2.8. DYNAMIC FREQUENCY SELECTION MEASUREMENT SETUP 20
2.9. CONTENTION PROTOCOL MEASUREMENT SETUP 23

1. SCOPE

The purpose of this document is to show test setup diagrams and photos for the following reports;

Reports
14523771

2. A2849 SETUP PHOTOS

2.1. 2.4GHz/5GHz /NB /6E TECHNOLOGIES

ANTENNA PORT AND AC LINE CONDUCTED SETUP



RF ANTENNA PORT CONDUCTED



AC LINE CONDUCTED (FRONT)

AC LINE CONDUCTED (BACK)

AC LINE CONDUCTED WITH HOST (FRONT)

AC LINE CONDUCTED WITH HOST (BACK)

2.1.1. BT/BLE/HDR/DTS/UNII/NB/6E RADIATED RF MEASUREMENT SETUP



FCC BELOW 30MHz (FRONT)

FCC BELOW 30MHz (BACK)

FCC BELOW 1GHz (FRONT)

FCC BELOW 1GHz (BACK)



ABOVE 1GHz X-Axis Front

ABOVE 1GHz X-Axis Back



ABOVE 1GHz Y-Axis Front



ABOVE 1GHz Y-Axis Back



ABOVE 1GHz Z-Axis Front

ABOVE 1GHz Z-Axis Back

2.2. NFC TECHNOLOGY

FREQ TOLERANCE AND AC LINE CONDUCTED SETUP



AC LINE CONDUCTED (FRONT)

AC LINE CONDUCTED (BACK)

2.2.1. RADIATED RF MEASUREMENT SETUP



FCC BELOW 30MHz (FRONT)

FCC BELOW 30MHz (BACK)

FCC BELOW 1GHz (FRONT)

FCC BELOW 1GHz (BACK)

2.3. WPT RADIATED AND AC LINE SETUP



BELOW 30 MHz (FRONT)

BELOW 30 MHz (BACK)

BELOW 1GHz (FRONT)

BELOW 1GHz (BACK)



AC LINE CONDUCTED (FRONT)

AC LINE CONDUCTED (BACK)

2.4. WWAN TECHNOLOGIES

FREQUENCY STABILITY



RF ANTENNA PORT CONDUCTED



X-ORIENTATION



Y-ORIENTATION



Z-ORIENTATION

Zoom Out

2.5. UWB TECHNOLOGIES SETUP



AC LINE CONDUCTED (FRONT)

AC LINE CONDUCTED (BACK)

AC LINE WITH LAPTOP (FRONT)

AC LINE WITH LAPTOP (BACK)

2.5.1. RADIATED RF MEASUREMENT SETUP



BELOW 30 MHz (FRONT)

BELOW 30 MHz (BACK)

BELOW 0.96 GHz (FRONT)

BELOW 0.96 GHz (BACK)

ABOVE 1GHz X-Axis Front



ABOVE 1GHz X-Axis Back



ABOVE 1GHz Y-Axis Front



ABOVE 1GHz Y-Axis Back

ABOVE 1GHz Z-Axis Front



ABOVE 1GHz Z-Axis Back

Fundamental 6 – 9 GHz (FRONT)



Fundamental 6 – 9 GHz (BACK)

0.96 – 6 GHz (FRONT)



0.96 – 6 GHz (BACK)



9 - 18 GHz (FRONT)



9 – 18 GHz (BACK)

 **18 – 40GHz (FRONT)**	 **18 – 40GHz (BACK)**

2.6. CBSD SETUP PHOTO

B48

N48

2.7. RF EXPOSURE SETUP PHOTO

2.7.1. RF Exposure



2mm GAP

CONFIGURATION 1 Operating Mode

S1, RF Exposure Setup Photo



S2, RF Exposure Setup Photo

S3, RF Exposure Setup Photo

S4, RF Exposure Setup Photo

Top



Bottom,

CONFIGURATION 2 Operating Mode with 2mm gap



S1, RF Exposure Setup Photo



S2, RF Exposure Setup Photo

S3, RF Exposure Setup Photo



S4, RF Exposure Setup Photo

Top, With 2mm Gap



Bottom, With 2mm Gap

Probe side X

Probe side Y

Probe side Z

Model	Probe (EHP200)
X/Y/Z	8.5 cm

2.8. DYNAMIC FREQUENCY SELECTION MEASUREMENT SETUP

DFS FRONT PHOTO (EUT)

DFS BACK PHOTO (EUT)

DFS FULL SETUP PHOTO (CLIENT MODE SETUP)

DFS FULL SETUP PHOTO (CLIENT-TO-CLIENT COMMUNICATIONS MODE SETUP)

DFS FULL SETUP PHOTO (PEER TO PEER MODE SETUP / EUT)

DFS FULL SETUP PHOTO (PEER TO PEER MODE SETUP / PEER DEVICE)

2.9. CONTENTION PROTOCOL MEASUREMENT SETUP

CONTENTION PROTOCOL PHOTO (FRONT)

CONTENTION PROTOCOL PHOTO (BACK)

END OF REPORT