







5G NR n7 30MHz BPSK Middle Channel RB1-0, ID:12482




5G NR n7 30MHz BPSK High Channel RB1-0, ID:12482




5G NR n7 30MHz BPSK Middle Channel RB1-159, ID:12482




5G NR n7 30MHz BPSK High Channel RB1-159, ID:12482





5G NR n7 30MHz BPSK Middle Channel RB160-0, ID:12482




5G NR n7 30MHz BPSK High Channel RB160-0, ID:12482









5G NR n7 40MHz BPSK Middle Channel RB1-0, ID:12482




5G NR n7 40MHz BPSK High Channel RB1-0, ID:12482




5G NR n7 40MHz BPSK Middle Channel RB1-215, ID:12482



5G NR n7 40MHz BPSK High Channel RB1-215, ID:12482



5G NR n7 40MHz BPSK Middle Channel RB216-0, ID:12482



5G NR n7 40MHz BPSK High Channel RB216-0, ID:12482


9.2.2. LTE BAND 12 AND 5G NR n12


LIMITS

FCC: §27.53


(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

LTE BAND 12 EMISSION MASK







LTE B12 1.4MHz QPSK High Channel RB1-0




LTE B12 3MHz QPSK Low Channel RB1-0




LTE B12 1.4MHz QPSK High Channel RB1-5




LTE B12 3MHz QPSK Low Channel RB1-14




LTE B12 1.4MHz QPSK High Channel RB6-0




LTE B12 3MHz QPSK Low Channel RB15-0




LTE B12 3MHz QPSK Middle Channel RB1-0




LTE B12 3MHz QPSK High Channel RB1-0




LTE B12 3MHz QPSK Middle Channel RB1-14




LTE B12 3MHz QPSK High Channel RB1-14




LTE B12 3MHz QPSK Middle Channel RB15-0




LTE B12 3MHz QPSK High Channel RB15-0




LTE B12 5MHz QPSK Low Channel RB1-0




LTE B12 5MHz QPSK Middle Channel RB1-0




LTE B12 5MHz QPSK Low Channel RB1-24




LTE B12 5MHz QPSK Middle Channel RB1-24




LTE B12 5MHz QPSK Low Channel RB25-0




LTE B12 5MHz QPSK Middle Channel RB25-0




LTE B12 5MHz QPSK High Channel RB1-0




LTE B12 10MHz QPSK Low Channel RB1-0




LTE B12 5MHz QPSK High Channel RB1-24




LTE B12 10MHz QPSK Low Channel RB1-49




LTE B12 5MHz QPSK High Channel RB25-0




LTE B12 10MHz QPSK Low Channel RB50-0




LTE B12 10MHz QPSK Middle Channel RB1-0




LTE B12 10MHz QPSK High Channel RB1-0




LTE B12 10MHz QPSK Middle Channel RB1-49



LTE B12 10MHz QPSK High Channel RB1-49




LTE B12 10MHz QPSK Middle Channel RB50-0




LTE B12 10MHz QPSK High Channel RB50-0


5G NR n12 EMISSION MASK




5G NR n12 5MHz BPSK Low Channel RB1-0




5G NR n12 5MHz BPSK Middle Channel RB1-0




5G NR n12 5MHz BPSK Low Channel RB1-24




5G NR n12 5MHz BPSK Middle Channel RB1-24





5G NR n12 5MHz BPSK Low Channel RB25-0



5G NR n12 5MHz BPSK Middle Channel RB25-0









Intentionally Blank

9.2.3. LTE BAND 13

LIMITS

FCC: §27.53

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;


(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) Emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals. (-70 dBW/MHz = -40 dBm/MHz).





9.2.4. LTE BAND 14 AND 5G NR n14

LIMITS

FCC: §90.543 Emission Limitations.

(e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.


(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.


(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.


(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

LTE BAND 14 EMISSION MASK







5G NR n14 EMISSION MASK




5G NR n14 5MHz BPSK Low Channel RB1-0, ID: 28774




5G NR n14 5MHz BPSK High Channel RB1-24,




5G NR n14 5MHz BPSK Low Channel RB25-0




5G NR n14 5MHz BPSK High Channel RB25-0



5G NR n14 10MHz BPSK Middle Channel RB1-0



5G NR n14 10MHz BPSK Middle Channel RB1-51




9.2.5. LTE BAND 17


LIMITS

FCC: §27.53


(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.




LTE B17 5MHz QPSK Low Channel RB1-0




LTE B17 5MHz QPSK High Channel RB1-0




LTE B17 5MHz QPSK Low Channel RB1-24




LTE B17 5MHz QPSK High Channel RB1-24




LTE B17 5MHz QPSK Low Channel RB25-0




LTE B17 5MHz QPSK High Channel RB25-0




LTE B17 10MHz QPSK Low Channel RB1-0




LTE B17 10MHz QPSK High Channel RB1-0




LTE B17 10MHz QPSK Low Channel RB1-49



LTE B17 10MHz QPSK High Channel RB1-49



LTE B17 10MHz QPSK Low Channel RB50-0



LTE B17 10MHz QPSK High Channel RB50-0

9.2.6. LTE BAND 25 AND 5G NR n25

LIMITS

FCC: §24.238 (a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.