

TAS Validation Test Report

**FCC ID: BCG-E9188A
Model: A3447**

**Report Number: 16064952-S5V2
Issue Date: 2026/07/20**

**Prepared for:
APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014-2084**

**Prepared by:
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888**

Revision History

Rev.	Date	Revisions	Revised By
V1	2026/07/16	Initial Issue	--
V2	2026/07/20	1. Added SM1 Extremity designation in §3.1 (Tables 3-1 and 3-2)	Nathan Sousa

Table of Contents

1.	Test Specifications, Methods/Procedures, and Facilities	7
2.	Introduction.....	7
3.	Key TAS Parameters.....	8
3.1	Operating State Summary	8
3.2	TAS Parameter Definitions	8
3.3	Device Characterizations.....	9
4.	Test Sequences.....	9
4.1	Conducted	9
4.1.1	Start-up Test Sequences	9
4.1.1.1	Start-up Sequence A.....	9
4.1.1.2	Start-up Sequence B	9
4.1.2	Pseudo-random Sequence.....	9
4.1.3	Antenna Switching.....	10
4.1.4	Change in Operating State.....	10
4.1.5	Frequency Band Hand-off or Redirect.....	10
4.1.6	Technology Hand-off.....	10
4.1.6.1	Additional WWAN Test Coverage	10
4.1.7	Switching Between Time Division Duplexing and Frequency Division Duplexing	10
4.1.8	Change in Modulation Scheme within a Communication Technology	11
4.1.9	Dropped Connection.....	11
4.1.10	Test Sequence Validation	11
4.2	Radiated	12
4.2.1	Test Procedure and Validation.....	12
4.2.1.1	ANT 1	12
4.2.1.2	ANT 2.....	13
4.2.1.3	ANT 3.....	14
4.2.1.4	ANT 4.....	15
4.2.1.5	ANT 7	16
4.2.1.6	ANT 12.....	17
4.2.1.7	ANT 14.....	18
4.3	PD (mmW).....	19
4.3.1	SAR to MPE Switch.....	19
4.3.2	Beam Switch.....	19
5.	Test Cases.....	19
5.1	Sub-7.2 GHz	19
5.2	PD (mmWave)	22
5.2.1	Measurement Setup	22
5.2.1.1	Radiated Power	22
5.2.1.2	PD Measurements	23
6.	TAS Validation	24
6.1	Conducted	24

6.1.1	Start-up Sequence A	24
6.1.1.1	Test Case 1: FR-1 TDD Start-up Sequence A	24
6.1.2	Test Cases 2-10: Start-up Sequence B	26
6.1.2.1	Test Case 2: GSM Start-up Sequence B	26
6.1.2.2	Test Case 3: W-CDMA Start-up Sequence B	28
6.1.2.3	Test Case 4: LTE FDD Start-up Sequence B	30
6.1.2.4	Test Case 5: LTE TDD Start-up Sequence B	32
6.1.2.5	Test Case 6: FR-1 FDD Start-up Sequence B	34
6.1.2.6	Test Case 7: FR-1 TDD Start-up Sequence B	36
6.1.2.7	Test Case 8: Wi-Fi 5 GHz Start-up Sequence B	38
6.1.2.8	Test Case 9: Wi-Fi 6 GHz Start-up Sequence B	39
6.1.2.9	Test Case 10: Bluetooth 2.4 GHz Start-up Sequence B	40
6.1.3	Pseudo-random Sequence	41
6.1.3.1	Test Case 11: LTE FDD Pseudo-random Sequence	41
6.1.4	Test Case 12: Antenna Switching	44
6.1.5	Test Case 13: Change in Operating State and Antenna Switching	45
6.1.6	Test Case 14: Technology Hand-off ULCA	46
6.1.7	Test Case 15: Technology Hand-off EN-DC	48
6.1.8	Test Case 16: Switching Between Duplexes	50
6.1.9	Test Case 17: Dropped Connection	52
6.2	PD (mmWave)	54
6.2.1	SAR to MPE Switch	54
6.2.2	Beam Switch	55
7.	MSS	56
7.1	Conducted	56
7.1.1	Technology Hand-off MSS to Cellular to MSS	56
8.	Dynamic Budget Algorithm Validation	58
9.	Conclusion	60
	Appendices	61
	Appendix A: Test Setup Photos	61
	Appendix B: cSAR3D Calibration Certificate	61
	Appendix C: Dipole Certification Certificates	61
	Appendix D: Fast SAR Measurement System & Test Equipment	62
	D.1. Fast SAR Measurement System	62
	D.2. Test Equipment	63
	Appendix E: Fast SAR System Verification	64
	Appendix F: Measurement Uncertainty	66
	F.1. Fast SAR	66
	F.1.1 Fast SAR Combined Expanded Uncertainty	66
	F.2. Conducted	67

Table of Tables

Table 2-1: Time-averaging Duration	7
Table 3-1: DUT Supported Operating States for State A	8
Table 3-2: DUT Supported Operating States for State B	8
Table 4-1: ANT 1 SAR v. Requested Power.....	12
Table 4-2: ANT 2 SAR v. Requested Power.....	13
Table 4-3: ANT 3 SAR v. Requested Power.....	14
Table 4-4: ANT 4 SAR v. Requested Power.....	15
Table 4-5: ANT 7 SAR v. Requested Power.....	16
Table 4-6: ANT 8 SAR v. Requested Power.....	17
Table 4-7: ANT 14 SAR v. Requested Power.....	18
Table 5-1: Selected Test Cases for sub-7.2 GHz TAS Validation.....	19
Table 5-2: Selected Test Cases for PD TAS Validation	22
Table 6-1: LTE FDD T_{req} vs. P_{req} (Conducted).....	43
Table 8-1: Selected Technologies for Dynamic Budget Algorithm Validation.....	58
Table 9-1: Summary of Results for sub-7.2 GHz Conducted.....	60
Table 9-2: Summary of Results for PD.....	60
Table 9-3: Summary of Results for Dynamic Budget Algorithm Validation	60

Table of Figures

Figure 4-1: ANT 1 SAR v. Requested Power Linearity Validation.....	12
Figure 4-2: ANT 2 SAR v. Requested Power Linearity Validation.....	13
Figure 4-3: ANT 3 SAR v. Requested Power Linearity Validation.....	14
Figure 4-4: ANT 4 SAR v. Requested Power Linearity Validation.....	15
Figure 4-5: ANT 7 SAR v. Requested Power Linearity Validation.....	16
Figure 4-6: ANT 8 SAR v. Requested Power Linearity Validation.....	17
Figure 4-7: ANT 14 SAR v. Requested Power Linearity Validation.....	18
Figure 5-1: Time-varying, Change in Operating State, Change in Duplex/Modulation, and Dropped Connection	20
Figure 5-2: Antenna Switching and Frequency Band Hand-off or Redirect	20
Figure 5-3: Technology Hand-off.....	21
Figure 5-4: Dynamic Budget Algorithm Validation.....	21
Figure 5-5: mmW Radiated Power Measurement Setup	22
Figure 5-6: PD Measurement Setup	23
Figure 6-1: FR-1 TDD Start-up Sequence A (Conducted)	24
Figure 6-2: FR-1 TDD $P[n]$ vs. P_{Limit} Sequence A Validation (Conducted).....	25
Figure 6-3: GSM Start-up Sequence B (Conducted)	26
Figure 6-4: GSM $P[n]$ vs. P_{Limit} Sequence B Validation (Conducted).....	27
Figure 6-5: W-CDMA Start-up Sequence B (Conducted)	28
Figure 6-6: W-CDMA $P[n]$ vs. P_{Limit} Sequence B Validation (Conducted)	29
Figure 6-7: LTE FDD Start-up Sequence B (Conducted).....	30
Figure 6-8: LTE FDD $P[n]$ vs. P_{Limit} Sequence B Validation (Conducted)	31
Figure 6-9: LTE TDD Start-up Sequence B (Conducted).....	32
Figure 6-10: LTE TDD $P[n]$ vs. P_{Limit} Sequence B Validation (Conducted)	33
Figure 6-11: FR-1 FDD Start-up Sequence B (Conducted)	34
Figure 6-12: FR-1 FDD $P[n]$ vs. P_{Limit} Sequence B Validation (Conducted).....	35
Figure 6-13: FR-1 TDD Start-up Sequence B (Conducted).....	36
Figure 6-14: FR-1 TDD $P[n]$ vs. P_{Limit} Sequence B Validation (Conducted).....	37
Figure 6-15: Wi-Fi 5 GHz Start-up Sequence B and $P[n]$ vs. P_{Limit} (Conducted)	38
Figure 6-16: Wi-Fi 6 GHz Start-up Sequence B and $P[n]$ vs. P_{Limit} (Conducted)	39
Figure 6-17: Bluetooth 2.4 GHz Start-up Sequence B and $P[n]$ vs. P_{Limit} (Conducted)	40
Figure 6-18: LTE FDD Pseudo-random Sequence (Conducted)	41
Figure 6-19: LTE FDD $P[n]$ vs. P_{Limit} Pseudo-random Sequence Validation (Conducted).....	42
Figure 6-20: Antenna Switch Plot (Conducted).....	44
Figure 6-21: Antenna Switch Validation (Conducted)	44
Figure 6-22: Change in Operating State and Antenna Switching (Conducted)	45
Figure 6-23: Change in Operating State and Antenna Switching (Conducted)	45
Figure 6-24: Technology Hand-off ULCA Test Case (Conducted)	46
Figure 6-25: Technology Hand-off ULCA Test Case Validation (Conducted).....	47

Figure 6-26: Technology Hand-off EN-DC (Conducted)	48
Figure 6-27: Technology Hand-off EN-DC Validation (Conducted).....	49
Figure 6-28: Switching Between Duplexes Test Case (Conducted)	50
Figure 6-29: Switching Between Duplexes Test Case Validation (Conducted).....	51
Figure 6-30: Call Drop Plot (Conducted).....	52
Figure 6-31: Call Drop Validation (Conducted)	53
Figure 6-32: SAR to MPE Switch Validation	54
Figure 6-33: Beam Switch Validation	55
Figure 7-1: MSS to Cellular to MSS	56
Figure 7-2: MSS to Cellular to MSS Validation	57
Figure 8-1: Cellular + Wi-Fi to Cellular + Wi-Fi + Bluetooth to Cellular + Wi-Fi + Bluetooth + Static Radios	58
Figure 8-2: Cellular + Wi-Fi to Cellular + Wi-Fi + Bluetooth to Cellular + Wi-Fi + Bluetooth + Static Radios Validation	59
Figure D.1-1: cSAR3D System Block Diagram	62

Table of Equations

Equation 1: Power Level Equation	9
Equation 2: T_{req} Durations	9
Equation 3: Rolling Time-averaged Power (Constant P_{Limit})	11
Equation 4: Rolling Time-averaged Power (P_{Limit} not Constant)	11

1. Test Specifications, Methods/Procedures, and Facilities

The tests documented in this report were performed following the OEM's pre-approval guidance KDB 388624 D02 Pre-Approval Guidance List v18r06, PWRCNG).

The test sites and measurement facilities used to collect data are located at:

47173 Benicia Street	47266 Benicia Street
SAR Labs A to Q	SAR Labs 1 to 30

The Test Lab Conformity Assessment Body Identifier (CABID)

Location	CABID	Company Number
47173 Benicia Street, Fremont, CA, 94538 UNITED STATES	US0104	2324A
47266 Benicia Street, Fremont, CA, 94538 UNITED STATES		

2. Introduction

The modem is enabled with WWAN/WLAN/Bluetooth/NB U-NII/802.15.4/MSS TAS technology feature to control and manage transmitting power, in real time.

This DUT supports a time-average method of transmit power control for the aforementioned technologies. Consumed SAR from active radios is tracked and stored for the duration of the applicable regulatory averaging window. Rolling time-averaged SAR values are calculated from the consumed SAR reported from active radios. The time-averaged SAR is always maintained less than the applicable $SAR_{Reported}$.

The purpose of this document is to demonstrate the validity of the TAS feature(s) implemented within this product with a technology agnostic approach.

Table 2-1 defines the applicable time-averaging durations per regulatory body:

Table 2-1: Time-averaging Duration

FCC						
Frequency (GHz)	WWAN (s)	MSS (s)	WLAN (s)	Bluetooth (s)	NB U-NII (s)	802.15.4 (s)
< 3	100	99.84	100	100	N/A	100
3 - 6	60	N/A	60	N/A	60	N/A
6 - 10	N/A	N/A	30	N/A	30	N/A
24 - 42	4	N/A	N/A	N/A	N/A	N/A

3. Key TAS Parameters

This section defines the relevant power and RF Exposure parameters related to the TAS mechanism for this DUT.

3.1 Operating State Summary

Table 3-1 summarizes the operating states supported by the DUT:

Table 3-1: DUT Supported Operating States for State A

RF Exposure	Power/Index State	Description
Head	Mode A	Max permissible power relative to P_{Limit} when the device is used against the user's head
Body-worn	Mode B	Max permissible power relative to P_{Limit} when the device is used in a Body-worn configuration
Body-worn	SM1	Max permissible power relative to P_{Limit} when sensing conditions are satisfied and the device is used in a Body-worn configuration
Hotspot	Mode B	Max permissible power relative to P_{Limit} when the device is used in a Hotspot configuration
Hotspot	SM1	Max permissible power relative to P_{Limit} when sensing conditions are satisfied and the device is used in a Hotspot configuration
Extremity	Mode B	Max permissible power relative to P_{Limit} when the device is used in an Extremity configuration
Extremity	SM1	Max permissible power relative to P_{Limit} when sensing conditions are satisfied and the device is used in an Extremity configuration

Table 3-2: DUT Supported Operating States for State B

RF Exposure	Power/Index State	Description
Body-worn	Mode B	Max permissible power relative to P_{Limit} when the device is used in a Body-worn configuration
Body-worn	SM1	Max permissible power relative to P_{Limit} when sensing conditions are satisfied and the device is used in a Body-worn configuration
Hotspot	Mode B	Max permissible power relative to P_{Limit} when the device is used in a Hotspot configuration
Hotspot	SM1	Max permissible power relative to P_{Limit} when sensing conditions are satisfied and the device is used in a Hotspot configuration
Extremity	Mode B	Max permissible power relative to P_{Limit} when the device is used in an Extremity configuration
Extremity	SM1	Max permissible power relative to P_{Limit} when sensing conditions are satisfied and the device is used in an Extremity configuration

3.2 TAS Parameter Definitions

- P_{Max} : The maximum possible instantaneous power
- P_{Limit} : The maximum possible time-averaged power
- $P_{Limit, nom}$: The listed time-averaged target power, excluding total device uncertainty
- $P_{Max, nom}$: The maximum possible instantaneous power, excluding total device uncertainty
- $SAR_{Measured}$: The maximum spatial peak averaged SAR value corresponding to $P_{Limit, nom}$
- $SAR_{Reported}$: The maximum spatial peak averaged SAR value inclusive of total device uncertainty, corresponding to P_{Limit}
- $PD_{Reported}$: The maximum 4 cm² Square averaged PD value inclusive of total device uncertainty, corresponding to P_{Limit}

$P_{Limit, nom}$, P_{Limit} , $P_{Max, nom}$, and P_{Max} values are defined for all antennas, technologies, bands, power states, and operating states combinations supporting TAS on the DUT. Instantaneous power for the specified antenna/technology/band/operating state combinations is capped at P_{Max} .

3.3 Device Characterizations

The device characterizations can be found within the SAR Report 16064952-S1, Appendix G.

4. Test Sequences

4.1 Conducted

The TAS algorithm shall be validated when the base station requests different power levels to manage the link budget.

Conducted power measurements shall be performed for at least one band per technology. The P_{Limit} value associated with the chosen band should be several dB lower than the corresponding value of P_{Max} , e.g. 2 to 4 dB lower. Whenever possible, the same band should not be repeated for different technologies.

4.1.1 Start-up Test Sequences

4.1.1.1 Start-up Sequence A

- Upon start-up, request a power level of $P_{Max, nom}$ for a period of at least 1.5x of the Time-averaging Duration, followed by $0.5 \cdot P_{Limit, nom}$ for a period of at least 1.5x of the Time-averaging Duration.

4.1.1.2 Start-up Sequence B

- Upon start-up, request a power level of 1 mW (0 dBm) for a period of at least 1.5x of the Time-averaging Duration, followed by $P_{Max, nom}$ for a period of at least 1.5x of the Time-averaging Duration.

4.1.2 Pseudo-random Sequence

A pseudo-random sequence of power requests shall be applied to validate the dynamic behavior of the TAS algorithm. Each test shall be performed with a unique sequence of 150 independent power requests for WWAN and 40 independent power requests for WLAN. These power levels are calculated as follows (Equation 1):

Equation 1: Power Level Equation

$$P_{req} = P_{Max, nom} \left(\frac{P_{Limit, nom}}{P_{Max, nom}} \right)^x$$

where P_{req} is the requested power in watts and x is a random value drawn from the Weibull distribution with shape and scale parameters of 2.0 and 0.8, and 1.0 and 0.4, respectively, for WWAN and WLAN. These values were chosen to ensure that P_{req} exceeds $P_{Limit, nom}$ on average, while maintaining a reasonable likelihood that some P_{req} values will sometimes fall well below $P_{Limit, nom}$.

The corresponding request durations are given by (Equation 2):

Equation 2: T_{req} Durations

$$T_{req} = d * 2(1 + 2y)$$

where T_{req} is the duration of the power request in seconds, d is the extended duration (1 for WWAN and 4 for WLAN), and y is a uniformly distributed random value between 0 and 1.

4.1.3 Antenna Switching

Conducted power measurements shall be performed to validate the TAS algorithm in antenna switching scenarios. Maximum power shall be requested from the DUT throughout the test. The switch between antennas and duplexes shall occur once the TAS algorithm has reached steady state for the first antenna and duplex, and the test shall conclude once the algorithm has reached steady state for the second antenna and duplex.

When different P_{Limit} and P_{Max} values are associated with each transmitting antenna and duplex, consideration shall be given to the combinations of antennas/duplexes and operating state(s) for which the P_{Limit} values are below the corresponding P_{Max} values and where one of the largest differences between P_{Max} and P_{Limit} occurs. Of these combinations, the performance of the TAS algorithm shall be validated when the DUT switches from the antenna with the highest P_{Limit} value to the lowest.

4.1.4 Change in Operating State

Conducted power measurements shall be performed to validate the TAS algorithm when the DUT changes between operating states with different P_{Limit} values, e.g., when sensors or other mechanisms are used to change operating states. Maximum power shall be requested from the DUT throughout the test. The change in operating state shall occur once the TAS algorithm has reached steady state for the first operating state, and the test shall conclude once the algorithm has reached steady state for the second operating state.

4.1.5 Frequency Band Hand-off or Redirect

Conducted power measurements shall be performed to validate the TAS algorithm when the DUT switches between frequency bands with different P_{Limit} values. When the frequency band hand-off or redirect logic of the algorithm is the same regardless of the technology, only one test is required. Maximum power shall be requested from the DUT throughout the test. The change in frequency band shall occur once the TAS algorithm has reached steady state, and the test shall also conclude once the algorithm has reached steady state.

4.1.6 Technology Hand-off

Conducted power measurements shall be performed to validate the TAS algorithm when the DUT switches between technologies with different P_{Limit} values. Maximum power shall be requested from the DUT throughout the test. The technology hand-off shall occur once the TAS algorithm has reached steady state for the first technology(ies), and the test shall conclude once the algorithm has reached steady state for the second technology(ies). When there are more than two technologies that are supported by the TAS algorithm or the final product implementation, more than two technologies can be tested within one test as long as the TAS algorithm has reached steady state prior to commencing the next technology hand-off.

4.1.6.1 Additional WWAN Test Coverage

Intra-technology hand-off shall include the following test(s) for WWAN:

- Enhanced New Radio Dual Connectivity (EN-DC) with LTE and NR transmitting simultaneously

Note: If non-standalone (NSA) is supported, when power is requested for NR, LTE shall be set at low power.

- Uplink Carrier Aggregation (ULCA) transmitting simultaneously for two tests, one with two LTE Bands and the other with two NR bands

These test cases shall be performed in the following sequence: Standalone technology with one of the highest P_{Limit} , simultaneous transmission of technologies, and standalone technology with one of the lowest P_{Limit} .

4.1.7 Switching Between Time Division Duplexing and Frequency Division Duplexing

Conducted power measurements shall be performed to validate the TAS algorithm when the DUT switches between TDD and FDD configurations with different P_{Limit} values, both of which should be lower than the corresponding P_{Max} values and where one of the largest differences between P_{Max} and P_{Limit} occurs. Maximum power shall be requested from the DUT

throughout the test. The switch between configurations shall occur once the TAS algorithm has reached steady state and the test shall also conclude once the algorithms has reached steady state.

Note: This test case can be combined with frequency band hand-off or redirect.

4.1.8 Change in Modulation Scheme within a Communication Technology

Conducted power measurements shall be performed to validate the TAS algorithm for approval and final product implementations for WWAN and WLAN when the DUT changes between modulation schemes with different P_{Limit} values. For example, measurements would be required to validate a change from a higher order, for example, 64 QAM (quadrature amplitude modulation), to a lower order, such as QPSK (quadrature phase shift keying) and vice versa.

Only one test is required with the configurations where both P_{Limit} values are lower than the corresponding P_{Max} values and where one of the largest differences between P_{Max} and P_{Limit} occurs. Maximum power shall be requested from the DUT throughout the test. The switch between modulation schemes shall occur once the TAS algorithm has reached steady state and the test shall also conclude once the algorithm has reached steady state.

Note: This test case may be waived if the same P_{Limit} applies to all modulations for the technology under test.

4.1.9 Dropped Connection

Conducted power measurements shall be performed to validate the TAS algorithm during dropped connections to ensure the algorithm is able to account for previous connection states. When the dropped connection logic of the algorithm is the same regardless of the technology, only one test is required. Only one test is required with one of the configurations for which P_{Limit} is below P_{Max} and where one of the largest differences between P_{Max} and P_{Limit} occurs. Maximum power shall be requested from the DUT throughout the test. The dropped connection shall occur once the TAS algorithm has reached steady state, and the test shall conclude once steady state has been regained after the dropped connection.

4.1.10 Test Sequence Validation

Validation plots are included for the applicable test cases for this DUT. These plots serve to validate the operation of this TAS algorithm by ensuring that the measured power averaged over the applicable regulatory limit ($P[n]$) is always maintained below the defined P_{Limit} .

Conducted power measurements (P_{Meas}) are used to validate all TAS test cases. In test cases where P_{Limit} remains constant, the equation, Equation 3, below is used to calculate the rolling time-averaged power for the n^{th} time step ($P[n]$).

Equation 3: Rolling Time-averaged Power (Constant P_{Limit})

$$P[n] = \frac{1}{M} \sum_{m=0}^{M-1} P_{Meas}[n-m]$$

Where M is the total number of reporting periods per time-averaging window and m is the index of the time-averaging window. The TAS algorithm is validated when $P[n]$ is maintained less than or equal to P_{Limit} .

In test cases where P_{Limit} is not constant, the equation, Equation 4, below is used to calculate the normalized rolling time-averaged power ($p[n]$).

Equation 4: Rolling Time-averaged Power (P_{Limit} not Constant)

$$p[n] = \frac{1}{M} \sum_{m=0}^{M-1} \frac{P_{Meas}[n-m]}{P_{Limit}[n-m]}$$

Where M is the total number of reporting periods per time-averaging window and m is the index of the time-averaging window. The TAS algorithm is validated when $p[n]$ is maintained less than or equal to 1.

4.2 Radiated

4.2.1 Test Procedure and Validation

To validate linearity, point SAR measurements are performed with TAS operation turned off. Per antenna, the mode with the largest difference between P_{Limit} and P_{Max} will be selected for measurement. When possible, different frequency bands will be assessed per antenna.

Point SAR measurements are performed in 2 dB steps from P_{Max} to at least P_{Limit} minus 4 dB.

Linearity is sufficiently validated when the SAR versus requested power is within the defined device uncertainties.


4.2.1.1 ANT 1

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-1: ANT 1 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P_{Max}	P_{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 1	State A Body	W-CDMA B4	1.14	24.7	23.2	24	251.2	1.120	0.861	1.456
ANT 1	State A Body	W-CDMA B4	1.14	24.7	23.2	22	158.5	0.707	0.544	0.919
ANT 1	State A Body	W-CDMA B4	1.14	24.7	23.2	20	100.0	0.443	0.343	0.580
ANT 1	State A Body	W-CDMA B4	1.14	24.7	23.2	18	63.1	0.277	0.216	0.366

Figure 4-1: ANT 1 SAR v. Requested Power Linearity Validation




4.2.1.2 ANT 2

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-2: ANT 2 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P _{Max}	P _{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	24	251.2	2.270	1.744	2.955
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	22	158.5	1.430	1.100	1.865
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	20	100.0	0.905	0.694	1.177
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	18	63.1	0.566	0.438	0.742
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	16	39.8	0.354	0.276	0.468
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	14	25.1	0.224	0.174	0.296
ANT 2	State B Body	LTE FDD B25	1.146	25.7	17.0	12	15.8	0.142	0.110	0.186

Figure 4-2: ANT 2 SAR v. Requested Power Linearity Validation




4.2.1.3 ANT 3

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-3: ANT 3 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P _{Max}	P _{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 3	State A Body	FR-1 TDD n41	2.1	25.7	20.5	24	251.2	2.460	1.517	3.990
ANT 3	State A Body	FR-1 TDD n41	2.1	25.7	20.5	22	158.5	1.450	0.957	2.517
ANT 3	State A Body	FR-1 TDD n41	2.1	25.7	20.5	20	100.0	0.889	0.604	1.588
ANT 3	State A Body	FR-1 TDD n41	2.1	25.7	20.5	18	63.1	0.589	0.381	1.002
ANT 3	State A Body	FR-1 TDD n41	2.1	25.7	20.5	16	39.8	0.375	0.240	0.632
ANT 3	State A Body	FR-1 TDD n41	2.1	25.7	20.5	14	25.1	0.240	0.152	0.399

Figure 4-3: ANT 3 SAR v. Requested Power Linearity Validation




4.2.1.4 ANT 4

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-4: ANT 4 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P _{Max}	P _{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	26	398.1	4.560	3.699	5.622
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	24	251.2	2.770	2.334	3.547
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	22	158.5	1.750	1.473	2.238
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	20	100.0	1.090	0.929	1.412
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	18	63.1	0.690	0.586	0.891
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	16	39.8	0.438	0.370	0.562
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	14	25.1	0.278	0.233	0.355
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	12	15.8	0.174	0.147	0.224
ANT 4	State B Body	FR-1 TDD n77 (Block C)	0.909	26.0	14.9	10	10.0	0.106	0.093	0.141

Figure 4-4: ANT 4 SAR v. Requested Power Linearity Validation




4.2.1.5 ANT 7

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-5: ANT 7 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P _{Max}	P _{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 7	State A Body	FR-1 TDD n77 (Block A)	1.42	26.0	20.8	26	398.1	2.550	1.839	3.536
ANT 7	State A Body	FR-1 TDD n77 (Block A)	1.42	26.0	20.8	24	251.2	1.560	1.160	2.231
ANT 7	State A Body	FR-1 TDD n77 (Block A)	1.42	26.0	20.8	22	158.5	0.973	0.732	1.408
ANT 7	State A Body	FR-1 TDD n77 (Block A)	1.42	26.0	20.8	20	100.0	0.607	0.462	0.888
ANT 7	State A Body	FR-1 TDD n77 (Block A)	1.42	26.0	20.8	18	63.1	0.386	0.291	0.560
ANT 7	State A Body	FR-1 TDD n77 (Block A)	1.42	26.0	20.8	16	39.8	0.233	0.184	0.354

Figure 4-5: ANT 7 SAR v. Requested Power Linearity Validation




4.2.1.6 ANT 12

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-6: ANT 8 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P _{Max}	P _{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 12	State B Body	LTE FDD B5	0.853	25.1	25.1	24	251.2	0.798	0.656	0.971
ANT 12	State B Body	LTE FDD B5	0.853	25.1	25.1	22	158.5	0.503	0.414	0.613
ANT 12	State B Body	LTE FDD B5	0.853	25.1	25.1	20	100.0	0.295	0.261	0.387

Figure 4-6: ANT 8 SAR v. Requested Power Linearity Validation




4.2.1.7 ANT 14

The table and figure below demonstrate that the linearity is sufficiently validated as the SAR versus requested power is within the expected uncertainties.

Table 4-7: ANT 14 SAR v. Requested Power

Transmitter	RF Exposure Condition	Technology	Uncert. ($\pm$)	P _{Max}	P _{Limit}	Req. Power (dBm)	Req. Power (mW)	Meas. SAR (W/kg)	SAR Lower Bound	SAR Upper Bound
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	24	251.2	3.040	1.887	4.896
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	22	158.5	2.060	1.191	3.089
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	20	100.0	1.230	0.751	1.949
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	18	63.1	0.779	0.474	1.230
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	16	39.8	0.489	0.299	0.776
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	14	25.1	0.308	0.189	0.490
ANT 14	State A Body	FR-1 FDD n7	2.07	25.5	17.1	12	15.8	0.191	0.119	0.309

Figure 4-7: ANT 14 SAR v. Requested Power Linearity Validation



4.3 PD (mmW)

4.3.1 SAR to MPE Switch

LTE sub-6 GHz (P_{Max}) + FR-2 (all down bits/lowest power configuration) to LTE sub-6 GHz (P_{Max}) + FR-2 (P_{Max}) to LTE sub-6 GHz (all down bits/lowest power configuration) + FR2 (P_{Max})

- The test should be performed for a single test case. The test time will be sufficient to allow steady state to be reached for both connections.

Conducted power measurements will be used to validate the sub-6 GHz test configuration. Radiated power measurements will be used to validate the FR-2 test configuration.

4.3.2 Beam Switch

LTE sub-6 GHz (all down bits/lowest power configuration) + FR-2 beam 1 (P_{Max}) to LTE sub-6 GHz (all down bits/lowest power configuration) + FR-2 beam 2 (P_{Max})

- The test should be performed for a single test case. The test time will be sufficient to allow steady state to be reached for both connections.

Conducted power measurements will be used to validate the sub-6 GHz test configuration. Radiated power measurements will be used to validate the FR-2 test configuration.

5. Test Cases

5.1 Sub-7.2 GHz

The test cases are summarized in Table 5-1.

Table 5-1: Selected Test Cases for sub-7.2 GHz TAS Validation

Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Duty Cycle (%)	Port	Transmitter	RF Exposure Condition	P_{Max} (dBm)	P_{Max} Corr. (dBm)	P_{1000} (dBm)	P_{1000} Corr. (dBm)	P_{Max} (mW)	P_{Max} Corr. (mW)	P_{1000} (mW)	P_{1000} Corr. (mW)
1	Sequence A	FR-1 TDD	n41	DFT-s 1/2 BPSK	N/A	PC3	67.00%	Port A	ANT 2	State A Body	25.7	27.4	17.6	19.3	371.5	554.5	57.5	85.9
2	Sequence B	GSM	1900	GMSK	2 Slot(s)	N/A	25.00%	Port A	ANT 2	State B Body	31.0	31.0	23.5	23.5	1258.9	1258.9	223.9	223.9
3		W-CDMA	B4	QPSK	N/A	N/A	100.00%	Port B	ANT 1	State A Body	24.7	24.7	23.2	23.2	265.1	265.1	208.9	208.9
4		LTE FDD	B4	QPSK	N/A	N/A	100.00%	Port D	ANT 3	State B Body	25.2	25.2	21.5	21.5	331.1	331.1	141.3	141.3
5		LTE TDD	B48	QPSK	N/A	N/A	63.33%	Port C	ANT 4	State A Body	25.2	25.2	20.1	20.1	331.1	331.1	102.3	102.3
6		FR-1 FDD	n7	DFT-s 1/2 BPSK	N/A	N/A	91.00%	Port C	ANT 14	State B Body	25.5	25.9	18.4	18.8	354.8	389.9	69.2	76.0
7		FR-1 TDD	n77 (Block A)	DFT-s 1/2 BPSK	N/A	PC3	67.00%	Port B	ANT 7	State A Body	26.0	27.7	20.8	22.5	398.1	594.2	120.2	179.4
8		Wi-Fi	U-NII 5	BPSK	N/A	N/A	N/A	N/A	ANT 5	State B Body	20.4	20.4	14.8	14.8	109.6	109.6	29.9	29.9
9		Wi-Fi	U-NII 5	BPSK	N/A	N/A	N/A	N/A	ANT 5	State A Body	19.6	19.6	13.0	13.0	91.2	91.2	20.0	20.0
10		Bluetooth	2.4 GHz	LE	N/A	N/A	N/A	N/A	ANT 5	State B Body	21.0	21.0	19.8	19.8	125.9	125.9	94.4	94.4
11	Pseudo-random	LTE FDD	B30	QPSK	N/A	N/A	100.00%	Port D	ANT 3	State A Body	23.7	23.7	20.4	20.4	234.4	234.4	109.6	109.6
17	Dropped Connection	LTE FDD	B25	QPSK	N/A	N/A	100.00%	Port A	ANT 2	State A Body	25.7	25.7	17.7	17.7	371.5	371.5	58.9	58.9
Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Duty Cycle (%)	Port	Transmitter	RF Exposure Condition	P_{Max} (dBm)	P_{Max} Corr. (dBm)	P_{1000} (dBm)	P_{1000} Corr. (dBm)	P_{Max} (mW)	P_{Max} Corr. (mW)	P_{1000} (mW)	P_{1000} Corr. (mW)
12	Antenna Switching	Wi-Fi	2.4 GHz	SSSS	N/A	N/A	N/A	N/A	ANT 4	State B Body	21.2	21.2	19.0	19.0	131.8	131.8	79.4	79.4
		Wi-Fi	U-NII 8	BPSK	N/A	N/A	N/A	N/A	ANT 6	State B Body	18.7	18.7	13.0	13.0	74.1	74.1	20.0	20.0
13	Change in Operating State & Antenna Switching	Wi-Fi	U-NII 6	BPSK	N/A	N/A	N/A	N/A	ANT 6	State A Body	19.8	19.8	13.5	13.5	95.5	95.5	22.4	22.4
		Wi-Fi	U-NII 6	BPSK	N/A	N/A	N/A	N/A	ANT 5	State A Head	15.8	15.8	12.5	12.5	38.0	38.0	17.8	17.8
16	Switching Between Duplexes	LTE FDD	B30	QPSK	N/A	N/A	100.00%	Port C	ANT 14	State B Body	24.9	24.9	22.7	22.7	309.0	309.0	186.2	186.2
		LTE TDD	B41	QPSK	N/A	PC3	63.33%	Port C	ANT 14	State B Body	25.7	25.7	18.7	18.7	371.5	371.5	74.1	74.1
14	Technology Hand-off (ULCA)	LTE TDD	B12	QPSK	N/A	N/A	100.00%	Port B	ANT 1	State B Body	25.7	25.7	25.7	25.7	371.5	371.5	371.5	371.5
		LTE FDD	B66	QPSK	N/A	N/A	100.00%	Port D	ANT 3	State B Body	25.2	25.2	21.5	21.5	331.1	331.1	141.3	141.3
15	Technology Hand-off (ENDC)	LTE FDD	B12	QPSK	N/A	N/A	100.00%	Port C	ANT 12	State A Body	25.4	25.4	25.4	25.4	346.7	346.7	346.7	346.7
		FR-1 FDD	n30	DFT-s 1/2 BPSK	N/A	N/A	91.00%	Port A	ANT 2	State A Body	25.0	25.4	17.5	17.9	316.2	347.5	56.2	61.8
20	Technology Hand-off (MSS to Cellular to MSS)	MSS	L-Band	N/A	N/A	N/A	N/A	Port A	ANT 2	State A Body	28.7	28.7	22.5	22.5	741.3	741.3	177.8	177.8
		LTE FDD	B66	QPSK	N/A	N/A	100.00%	Port A	ANT 2	State A Body	25.7	25.7	17.8	17.8	371.5	371.5	60.3	60.3

The following figures outline the test setup for the applicable test cases:





Figure 5-1: Time-varying, Change in Operating State, Change in Duplex/Modulation, and Dropped Connection**Figure 5-2: Antenna Switching and Frequency Band Hand-off or Redirect**

Figure 5-3: Technology Hand-off**Figure 5-4: Dynamic Budget Algorithm Validation**

5.2 PD (mmWave)

The test cases are summarized in Table 5-2.

Table 5-2: Selected Test Cases for PD TAS Validation

Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Bandwidth (MHz)	Port	Transmitter	Polarity	Beam ID	RF Exposure Condition	P_{Max} (dBm)	P_{Limit} (dBm)	P_{Max} (mW)	P_{Limit} (mW)
18	SAR to MPE	LTE	B2	QPSK	N/A	N/A	20	Port A	ANT 2	N/A	N/A	State B Body	25.7	17.7	371.5	58.9
		FR-2	n258	QPSK	N/A	N/A	100	N/A	M1	Horizontal	6	State B Body	N/A	0.5	N/A	1.1
19	Beam Switch	LTE	B2	QPSK	N/A	N/A	20	Port A	ANT 2	N/A	N/A	State B Body	25.7	17.7	371.5	58.9
		FR-2	n258	QPSK	N/A	N/A	100	N/A	M1	Horizontal	6	State B Body	N/A	0.5	N/A	1.1
		FR-2	n258	QPSK	N/A	N/A	100	N/A	M1	Horizontal	9	State B Body	N/A	3.6	N/A	2.3


5.2.1 Measurement Setup

5.2.1.1 Radiated Power

A mmW capable call box is used in this test. The call box has two RF radio heads to up/down convert the IF to mmW frequencies, which, in turn, are connected to two horn antennas for V- and H-polarizations for downlink communication. In the uplink, a directional coupler is used in the path of one of the horn antennas to measure and record radiated power using an appropriate power sensor and meter.¹

The DUT is placed inside an anechoic chamber with V- and H-polarity horn antennas to establish the radio link as shown in Figure 5-5. The call box's anchor port is directly connected to the DUT's RF port via a directional coupler to measure the DUT's conducted transmission power using a power sensor and power meter. Additionally, the DUT is connected to the PC via USB connection for sending beam switch commands. Care is taken to route the USB and RF cable away from the DUT's mmW antenna module(s).

Figure 5-5: mmW Radiated Power Measurement Setup



Both the call box and power meter are connected to the PC using USB cables. Test scripts are custom made for automation, i.e., establishing an anchor + mmW call, conducted transmission power recording for the anchor, and radiated transmission power recording for mmW. These tests are manually stopped after the desired time duration. The test script is programmed to set the anchor transmission power to minimum power on the call box immediately after the mmW link is established and programmed to toggle between all up and minimum power depending on the transmission scenario being evaluated. Similarly, the test script is also programmed to send beam switching commands manually to the DUT via a USB connection. For all the tests, the call box is set to request maximum transmission power from the mmW radio.

In simultaneous transmission scenarios involving sub-7.2 GHz + mmW, for a given operating state, both sub-7.2 GHz exposure and mmW exposure will be evaluated at the operating state corresponding separation distance in the TER analysis; but in the same time, the compliance of mmW exposure at 2 mm is ensured for all operating states. Thus, the following steps are implemented:

¹ The isolation of the directional coupler may not be sufficient to attenuate the downlink signal from the call box, which will result in high noise floor masking the recording of the radiated power from the DUT. In that case, either lower the downlink signal strength emanating from the RF radio heads of the call box or add an attenuator between the call box radio heads and the directional coupler. Additionally, since the measurements performed in this validation are all relative, measurement of the DUT's radiated power in one polarization is sufficient.

- ### 5.2.1.2 PD Measurements

Worst-surface of the DUT (for the mmW beam being tested) is positioned facing up for PD measurements with the cDASY6/8 mmW probe as shown in Figure 5-6.

The diagram illustrates the experimental setup for measuring the E-field of an LTE signal. The setup includes a PC connected to a Callbox and a Power meter via GPIB. The Callbox is connected to a combiner. The Power meter is connected to a Directional coupler. The Directional coupler is connected to the LTE signal source. The E-field is measured by a probe connected to the DASY controller and PC. The measured E-field is labeled as $meas.E(t)$. The measured power is labeled as $meas.P(t)$. The conducted power is labeled as Conducted power LTE.

Power meter readings are periodically recorded every 10 milliseconds on the power sensor for sub-7.2 GHz conducted transmission power. Time-averaged E-field measurements are performed using the mmW probe at peak location of the measurement. The distance between the mmW probe tip to the DUT's surface is ~0.5 mm and the distance between the mmW probe sensor to the probe tip is 1.5 millimeters. cDASY6/8 records relative point E-field, i.e., ratio $\frac{[pointE(t)]^2}{[pointE_{P\_Limit}]^2}$ versus time for mmW transmission.


6. TAS Validation

6.1 Conducted

6.1.1 Start-up Sequence A


6.1.1.1 Test Case 1: FR-1 TDD Start-up Sequence A²

Figure 6-1: FR-1 TDD Start-up Sequence A (Conducted)



² P_{Max} and P_{Limit} were adjusted to an operating 67% duty cycle.

Figure 6-2: FR-1 TDD P[n] vs. P_{Limit} Sequence A Validation (Conducted)



P[n] was calculated using the 100 second time-averaging duration.

6.1.2 Test Cases 2-10: Start-up Sequence B

6.1.2.1 Test Case 2: GSM Start-up Sequence B

Figure 6-3: GSM Start-up Sequence B (Conducted)





Figure 6-4: GSM P[n] vs. P_{Limit} Sequence B Validation (Conducted)



P[n] was calculated using the 100 second time-averaging duration.

6.1.2.2 Test Case 3: W-CDMA Start-up Sequence B

Figure 6-5: W-CDMA Start-up Sequence B (Conducted)





Figure 6-6: W-CDMA P[n] vs. P_{Limit} Sequence B Validation (Conducted)



P[n] was calculated using the 100 second time-averaging duration.

6.1.2.3 Test Case 4: LTE FDD Start-up Sequence B

Figure 6-7: LTE FDD Start-up Sequence B (Conducted)





Figure 6-8: LTE FDD P[n] vs. P_{Limit} Sequence B Validation (Conducted)



P[n] was calculated using the 100 second time-averaging duration.

6.1.2.4 Test Case 5: LTE TDD Start-up Sequence B

Figure 6-9: LTE TDD Start-up Sequence B (Conducted)






Figure 6-10: LTE TDD P[n] vs. P_{Limit} Sequence B Validation (Conducted)



P[n] was calculated using the 60 second time-averaging duration.


6.1.2.5 Test Case 6: FR-1 FDD Start-up Sequence B³

Figure 6-11: FR-1 FDD Start-up Sequence B (Conducted)



³ P_{Max} and P_{Limit} were adjusted to an operating 91% duty cycle.


Figure 6-12: FR-1 FDD P[n] vs. P_{Limit} Sequence B Validation (Conducted)



P[n] was calculated using the 100 second time-averaging duration.


6.1.2.6 Test Case 7: FR-1 TDD Start-up Sequence B⁴

Figure 6-13: FR-1 TDD Start-up Sequence B (Conducted)



⁴ P_{Max} and P_{Limit} were adjusted to an operating 67% duty cycle.


Figure 6-14: FR-1 TDD P[n] vs. P_{Limit} Sequence B Validation (Conducted)



P[n] was calculated using the 60 second time-averaging duration.

6.1.2.7 Test Case 8: Wi-Fi 5 GHz Start-up Sequence B


Figure 6-15: Wi-Fi 5 GHz Start-up Sequence B and $P[n]$ vs. P_{Limit} (Conducted)



$P[n]$ was calculated using the 60 second time-averaging duration.

6.1.2.8 Test Case 9: Wi-Fi 6 GHz Start-up Sequence B


Figure 6-16: Wi-Fi 6 GHz Start-up Sequence B and $P[n]$ vs. P_{Limit} (Conducted)



$P[n]$ was calculated using the 30 second time-averaging duration.

6.1.2.9 Test Case 10: Bluetooth 2.4 GHz Start-up Sequence B

Figure 6-17: Bluetooth 2.4 GHz Start-up Sequence B and P[n] vs. P_{Limit} (Conducted)



P[n] was calculated using the 100 second time-averaging duration.

6.1.3 Pseudo-random Sequence

6.1.3.1 Test Case 11: LTE FDD Pseudo-random Sequence

Figure 6-18: LTE FDD Pseudo-random Sequence (Conducted)





Figure 6-19: LTE FDD P[n] vs. P_{Limit} Pseudo-random Sequence Validation (Conducted)



P[n] was calculated using the 100 second time-averaging duration.

Table 6-1: LTE FDD T_{req} vs. P_{req} (Conducted)

Time (s)	T_{Req} (s)	P_{Req} (dBm)	P_{Req} (mW)	Time (s)	T_{Req} (s)	P_{Req} (dBm)	P_{Req} (mW)	Time (s)	T_{Req} (s)	P_{Req} (dBm)	P_{Req} (mW)
0	3	23.0	199.5	210	5	19.5	89.1	416	5	22.5	177.8
3	5	21.5	141.3	215	2	22.0	158.5	421	4	20.0	100.0
8	4	21.5	141.3	217	4	21.0	125.9	425	4	20.0	100.0
12	4	19.5	89.1	221	5	21.0	125.9	429	5	22.0	158.5
16	3	20.5	112.2	226	4	20.0	100.0	434	5	22.5	177.8
19	3	22.0	158.5	230	5	21.0	125.9	439	2	21.5	141.3
22	4	23.0	199.5	235	4	20.0	100.0	441	3	21.0	125.9
26	5	18.0	63.1	239	3	21.0	125.9	444	5	23.5	223.9
31	3	20.5	112.2	242	4	21.0	125.9	449	5	21.5	141.3
34	5	22.5	177.8	246	4	22.5	177.8	454	2	23.0	199.5
39	5	21.5	141.3	250	4	22.0	158.5	456	4	20.5	112.2
44	6	21.5	141.3	254	5	22.5	177.8	460	4	22.5	177.8
50	5	22.0	158.5	259	5	21.0	125.9	464	3	21.5	141.3
55	4	23.0	199.5	264	2	19.0	79.4	467	5	19.5	89.1
59	6	23.5	223.9	266	3	23.0	199.5	472	6	20.5	112.2
65	5	21.5	141.3	269	2	20.0	100.0	478	6	18.5	70.8
70	6	20.5	112.2	271	6	21.5	141.3	484	2	22.0	158.5
76	6	22.0	158.5	277	4	22.5	177.8	486	4	18.0	63.1
82	4	22.5	177.8	281	3	22.5	177.8	490	3	23.0	199.5
86	5	21.0	125.9	284	5	22.0	158.5	493	2	22.0	158.5
91	3	22.5	177.8	289	2	20.5	112.2	495	4	23.0	199.5
94	2	22.0	158.5	291	3	22.5	177.8	499	2	22.0	158.5
96	5	20.5	112.2	294	4	21.0	125.9	501	3	22.5	177.8
101	4	22.5	177.8	298	5	19.0	79.4	504	2	20.5	112.2
105	6	20.0	100.0	303	2	21.5	141.3	506	4	21.5	141.3
111	5	21.0	125.9	305	4	21.0	125.9	510	3	20.5	112.2
116	4	20.0	100.0	309	6	21.0	125.9	513	3	21.5	141.3
120	3	22.0	158.5	315	3	21.5	141.3	516	5	23.0	199.5
123	3	22.0	158.5	318	2	22.5	177.8	521	6	23.5	223.9
126	4	19.0	79.4	320	6	22.5	177.8	527	6	20.0	100.0
130	2	20.5	112.2	326	5	20.5	112.2	533	3	21.0	125.9
132	5	20.0	100.0	331	4	23.5	223.9	536	2	20.5	112.2
137	4	21.5	141.3	335	3	18.5	70.8	538	4	21.0	125.9
141	3	20.5	112.2	338	5	19.5	89.1	542	3	20.5	112.2
144	5	21.0	125.9	343	5	19.5	89.1	545	4	21.0	125.9
149	5	21.5	141.3	348	4	23.0	199.5	549	6	22.5	177.8
154	5	22.5	177.8	352	2	21.5	141.3	555	4	21.5	141.3
159	3	20.0	100.0	354	3	19.5	89.1	559	4	22.5	177.8
162	5	20.5	112.2	357	5	22.0	158.5	563	4	22.5	177.8
167	3	20.5	112.2	362	6	21.0	125.9	567	4	23.5	223.9
170	4	22.5	177.8	368	6	22.0	158.5	571	3	22.5	177.8
174	3	22.0	158.5	374	5	22.5	177.8	574	6	22.0	158.5
177	5	22.5	177.8	379	4	19.5	89.1	580	3	20.0	100.0
182	3	21.5	141.3	383	5	22.0	158.5	583	3	23.5	223.9
185	5	22.0	158.5	388	5	21.0	125.9	586	3	23.0	199.5
190	6	20.5	112.2	393	3	20.5	112.2	589	2	22.5	177.8
196	4	20.0	100.0	396	3	22.5	177.8	591	5	19.5	89.1
200	4	19.0	79.4	399	5	21.0	125.9	596	3	20.5	112.2
204	2	19.0	79.4	404	6	19.5	89.1	599	6	22.0	158.5
206	4	18.5	70.8	410	6	23.0	199.5	605	2	23.0	199.5

6.1.4 Test Case 12: Antenna Switching

Figure 6-20: Antenna Switch Plot (Conducted)





Figure 6-21: Antenna Switch Validation (Conducted)



$p[n]$ was calculated using the sum of Wi-Fi 2.4 GHz's 100 second time-averaging duration and Wi-Fi 6 GHz's 30 second time-averaging duration.

6.1.5 Test Case 13: Change in Operating State and Antenna Switching

Figure 6-22: Change in Operating State and Antenna Switching (Conducted)





Figure 6-23: Change in Operating State and Antenna Switching (Conducted)



$p[n]$ was calculated using the sum of Wi-Fi's 30 second time-averaging duration.

6.1.6 Test Case 14: Technology Hand-off ULCA

Figure 6-24: Technology Hand-off ULCA Test Case (Conducted)





Figure 6-25: Technology Hand-off ULCA Test Case Validation (Conducted)

p[n] was calculated using the sum of LTE PCC's and LTE SCC's 100 second time-averaging duration.

6.1.7 Test Case 15: Technology Hand-off EN-DC

Figure 6-26: Technology Hand-off EN-DC (Conducted)





Figure 6-27: Technology Hand-off EN-DC Validation (Conducted)



p[n] was calculated using the sum of LTE's and FR-1's 100 second time-averaging duration.

6.1.8 Test Case 16: Switching Between Duplexes

Figure 6-28: Switching Between Duplexes Test Case (Conducted)





Figure 6-29: Switching Between Duplexes Test Case Validation (Conducted)

$p[n]$ was calculated using the sum of LTE TDD's and LTE FDD's 100 second time-averaging duration.

6.1.9 Test Case 17: Dropped Connection

Figure 6-30: Call Drop Plot (Conducted)





Figure 6-31: Call Drop Validation (Conducted)




P[n] was calculated using the 100 second time-averaging duration.

6.2 PD (mmWave)

6.2.1 SAR to MPE Switch


Figure 6-32: SAR to MPE Switch Validation



Combined TER was calculated using the 4 second time-averaging duration for FR-2 and 100 second time-averaging duration for Cellular.

6.2.2 Beam Switch

Figure 6-33: Beam Switch Validation




$p[n]$ normalized was calculated using the 4 second time-averaging duration.

7. MSS⁵


7.1 Conducted

7.1.1 Technology Hand-off MSS to Cellular to MSS

Figure 7-1: MSS to Cellular to MSS



⁵ Data in this section was collected and provided by the OEM; the test lab did not conduct any of these measurements within this section.

Figure 7-2: MSS to Cellular to MSS Validation

p[n] was calculated using the sum of MSS 99.84 second time-averaging duration and WWAN's 100 second time-averaging duration.

8. Dynamic Budget Algorithm Validation

This DUT supports dynamic budget sharing for Cellular, MSS, Wi-Fi, Bluetooth, NB U-NII, and 802.15.4 technologies. The budgeting algorithm dynamically controls the SAR and MPE budgets assigned to radios over time depending on use conditions and power demands.

This dynamic budgeting algorithm ensures simultaneous compliance through management of overall device TER. With this implementation, it is no longer relevant to assess simultaneous SAR, or TER, in a static manner using fixed simultaneous budgets. The validation of this dynamic budgeting algorithm is sufficient to prove simultaneous compliance.

To validate the dynamic budgeting algorithm, the following configurations will be assessed:


1. Cellular Standalone
2. Cellular + Wi-Fi
3. Cellular + Wi-Fi + Bluetooth
4. Cellular + Wi-Fi + Bluetooth + Static Budget Radios⁶

Table 8-1: Selected Technologies for Dynamic Budget Algorithm Validation


Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Bandwidth (MHz)	Channel	Port	Transmitter	RF Exposure Condition	P _{Max} (dBm)	P _{Limit} (dBm)	P _{Max} (mW)	P _{Limit} (mW)
21	Dynamic Budgeting	LTE FDD	B25	QPSK	N/A	N/A	20	Mid	Port A	ANT 2	State A Body	25.7	17.7	371.5	58.9
		Wi-Fi	U-NII 2C	BPSK	N/A	N/A	80	122	N/A	ANT 6	State A Body	20.6	15.3	114.8	33.5
		Bluetooth	2.4 GHz	GFSK	N/A	N/A	N/A	N/A	N/A	ANT 4	State A Body	21.0	19.3	125.9	85.1
		Static Budget Radios													

The test time per sequence will be sufficient to allow steady state to be reached. Static budget radios should capture the maximum transmission budget of any technology that does not have time-averaging or dynamic budgeting support.

Figure 8-1: Cellular + Wi-Fi to Cellular + Wi-Fi + Bluetooth to Cellular + Wi-Fi + Bluetooth + Static Radios



⁶ Static Budget Radios include: WPT, UWB, 802.15.4ab – NB (Narrow Band), and NFC.

Figure 8-2: Cellular + Wi-Fi to Cellular + Wi-Fi + Bluetooth to Cellular + Wi-Fi + Bluetooth + Static Radios Validation

9. Conclusion

Table 9-1: Summary of Results for sub-7.2 GHz Conducted

Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Duty Cycle (%)	Port	Transmitter	RF Exposure Condition	P_{Max} (dBm)	P_{Max} Corr. (dBm)	P_{Limit} (dBm)	P_{Limit} Corr. (dBm)	Validation (dBm)	P_{Max} (mW)	P_{Max} Corr. (mW)	P_{Limit} (mW)	P_{Limit} Corr. (mW)	Validation (mW)	
1	Sequence A	FR-1 TDD	n41	DFT-s 1/2 BPSK	N/A	PC3	67.00%	Port A	ANT 2	State A Body	25.7	27.4	17.6	19.3	18.3 < 19.3	371.5	554.5	57.5	85.9	67.9 < 85.9	
2		CSM	1900	GMSK	2 Slots	N/A	25.00%	Port A	ANT 2	State B Body	31.0	31.0	23.5	23.5	22.3 < 23.5	1258.9	1258.9	223.9	223.9	171.0 < 223.9	
3	Sequence B	W-CDMA	B4	QPSK	N/A	N/A	100.00%	Port B	ANT 1	State A Body	24.7	24.7	23.2	23.2	22.0 < 23.2	265.1	265.1	208.9	208.9	159.8 < 208.9	
4		LTE FDD	B4	QPSK	N/A	N/A	100.00%	Port D	ANT 3	State B Body	25.2	25.2	21.5	21.5	18.4 < 21.5	331.1	331.1	141.3	141.3	69.0 < 141.3	
5		LTE TDD	B48	QPSK	N/A	N/A	63.33%	Port C	ANT 4	State A Body	25.2	25.2	20.1	20.1	19.0 < 20.1	331.1	331.1	102.3	102.3	78.9 < 102.3	
6		FR-1 FDD	n7	DFT-s 1/2 BPSK	N/A	N/A	91.00%	Port C	ANT 14	State B Body	25.5	25.9	18.4	18.8	15.6 < 18.8	354.8	389.9	69.2	76.0	35.9 < 76.0	
7		FR-1 TDD	n77 (Block A)	DFT-s 1/2 BPSK	N/A	PC3	67.00%	Port B	ANT 7	State A Body	26.0	27.7	20.8	22.5	21.4 < 22.5	398.1	594.2	120.2	179.4	138.0 < 179.4	
8		Wi-Fi	U-NII 3	BPSK	N/A	N/A	N/A	N/A	ANT 5	State B Body	20.4	20.4	14.8	14.8	13.0 < 14.8	109.6	109.6	28.9	28.9	19.9 < 28.9	
9		Wi-Fi	U-NII 5	BPSK	N/A	N/A	N/A	N/A	ANT 5	State A Body	19.6	19.6	13.0	13.0	11.4 < 13.0	91.2	91.2	20.0	20.0	13.7 < 20.0	
10		Bluetooth	2.4 GHz	LE	N/A	N/A	N/A	N/A	ANT 4	State B Body	21.0	21.0	19.8	19.8	9.7 < 19.8	125.9	125.9	94.4	94.4	9.2 < 94.4	
11		Pseudorange	LTE FDD	B30	QPSK	N/A	N/A	100.00%	Port D	ANT 3	State A Body	23.7	23.7	20.4	20.4	19.2 < 20.4	234.4	234.4	109.6	109.6	83.0 < 109.6
17		Dropped Connection	LTE FDD	B35	QPSK	N/A	N/A	100.00%	Port A	ANT 2	State A Body	25.7	25.7	17.7	17.7	16.5 < 17.7	371.5	371.5	58.9	58.9	44.3 < 58.9
Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Duty Cycle (%)	Port	Transmitter	RF Exposure Condition	P_{Max} (dBm)	P_{Max} Corr. (dBm)	P_{Limit} (dBm)	P_{Limit} Corr. (dBm)	Validation (dBm)	P_{Max} (mW)	P_{Max} Corr. (mW)	P_{Limit} (mW)	P_{Limit} Corr. (mW)	Validation (mW)	
12	Antenna Switching	Wi-Fi	2.4 GHz	DSSS	N/A	N/A	N/A	N/A	ANT 4	State B Body	21.2	21.2	19.0	19.0	13.18	131.8	131.8	79.4	79.4	0.731 < 1.000	
13		Change in Operating State & Antenna Switching	Wi-Fi	U-NII 6	BPSK	N/A	N/A	N/A	N/A	ANT 6	State B Body	18.7	18.7	13.0	13.0	74.1	74.1	20.0	20.0	0.488 < 1.000	
16	Switching Between Duplexes	LTE FDD	B30	QPSK	N/A	N/A	100.00%	Port C	ANT 14	State B Body	24.9	24.9	22.7	22.7	309.0	309.0	186.2	186.2	0.572 < 1.000		
14		Technology Hand-off (ULCA)	LTE TDD	B41	QPSK	N/A	PC3	63.33%	Port C	ANT 14	State B Body	25.7	25.7	18.7	18.7	371.5	371.5	74.1	74.1	0.572 < 1.000	
15	Technology Hand-off (ENDC)	LTE FDD	B12	QPSK	N/A	N/A	100.00%	Port B	ANT 1	State B Body	25.7	25.7	25.7	25.7	371.5	371.5	371.5	371.5	0.922 < 1.000		
20		Technology Hand-off (MSS to Cellular to MSS)	LTE FDD	B66	QPSK	N/A	N/A	100.00%	Port D	ANT 3	State B Body	25.2	25.2	21.5	21.5	331.1	331.1	141.3	141.3	0.922 < 1.000	
15	Technology Hand-off (ENDC)	LTE FDD	B12	QPSK	N/A	N/A	100.00%	Port C	ANT 12	State A Body	25.4	25.4	25.4	25.4	346.7	346.7	346.7	346.7	0.984 < 1.000		
20		Technology Hand-off (MSS to Cellular to MSS)	SSA FDD	n41	DFT-s 1/2 BPSK	N/A	N/A	91.00%	Port A	ANT 7	State A Body	25.0	25.0	17.5	17.5	161.6	161.6	347.5	347.5	61.8	
20	Technology Hand-off (MSS to Cellular to MSS)	MSS	L-band	N/A	N/A	N/A	N/A	Port A	ANT 2	State A Body	28.7	28.7	22.5	22.5	741.3	741.3	177.8	177.8	0.796 < 1.000		
20		LTE FDD	B66	QPSK	N/A	N/A	100.00%	Port A	ANT 2	State A Body	25.7	25.7	17.8	17.8	371.5	371.5	60.3	60.3	60.3		

Table 9-2: Summary of Results for PD

Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Bandwidth (MHz)	Port	Transmitter	Polarity	Beam ID	RF Exposure Condition	P_{Max} (dBm)	P_{Limit} (dBm)	P_{Max} (mW)	P_{Limit} (mW)	Validation
18	SAR to MPE	LTE	B2	QPSK	N/A	N/A	20	Port A	ANT 2	N/A	N/A	State B Body	25.7	17.7	371.5	58.9	0.918 < 1.000
19	Beam Switch	FR-2	n258	QPSK	N/A	N/A	100	N/A	M1	Horizontal	6	State B Body	N/A	0.5	N/A	1.1	0.737 < 1.000
		LTE	B2	QPSK	N/A	N/A	20	Port A	ANT 2	N/A	N/A	State B Body	25.7	17.7	371.5	58.9	
		FR-2	n258	QPSK	N/A	N/A	100	N/A	M1	Horizontal	6	State B Body	N/A	0.5	N/A	1.1	
		FR-2	n258	QPSK	N/A	N/A	100	N/A	M1	Horizontal	9	State B Body	N/A	3.6	N/A	2.3	

Table 9-3: Summary of Results for Dynamic Budget Algorithm Validation

Test Case No.	Test Case	Technology	Band	Modulation	Slot	Power Class	Bandwidth (MHz)	Channel	Port	Transmitter	RF Exposure Condition	P _{Max} (dBm)	P _{Limit} (dBm)	P _{Max} (mW)	P _{Limit} (mW)	Validation
21	Dynamic Budgeting	LTE FDD	B25	QPSK	N/A	N/A	20	Mid	Port A	ANT 2	State A Body	25.7	17.7	371.5	58.9	0.840 < 1.000
		Wi-Fi	U-NII 2C	BPSK	N/A	N/A	80	122	N/A	ANT 6	State A Body	20.6	15.3	114.8	33.5	
		Bluetooth	2.4 GHz	GFSK	N/A	N/A	N/A	N/A	N/A	ANT 4	State A Body	21.0	19.3	125.9	85.1	
		Static Budget Radios														

The data collected herein is sufficient in displaying the validation of the TAS algorithm(s). As demonstrated, the power limiting enforcement is effective and the total normalized time-averaged conducted power does not exceed 1 nor does $P[n]$ exceed P_{Limit} .

Appendices

Appendix A: Test Setup Photos

Appendix B: cSAR3D Calibration Certificate

Appendix C: Dipole Certification Certificates

D.2. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations and is traceable to recognized national standards.

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
POWERSOURCE1	SPEAG	SE UMS 160 CC	4394	1/18/2026

Lab Equipment

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Fast SAR Measurement Platform - Flat	SPEAG	cSARDV2-FHSL	5014	10/28/2026
Fast SAR Measurement Platform - Flat	SPEAG	cSARDV2-FHSL	5279	3/10/2027
System Validation Dipole	SPEAG	D835V2	4d117	11/5/2026
System Validation Dipole	SPEAG	D1950V3	1136	4/14/2027
System Validation Dipole	SPEAG	D2450V2	706	1/9/2027
System Validation Dipole	SPEAG	D5GHz	1138	2/13/2027

Other

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Wideband Radio Communication Tester	R&S	CMW500	135384-PJ	3/31/2027
Wideband Radio Communication Tester	R&S	CMW500	171873-PW	2/11/2027
Wideband Radio Communication Tester	R&S	CMW500	137873-WG	3/31/2027
Radio Communication Tester	R&S	CMX500	103011	2/28/2027
Wideband Radio Communication Tester	Keysight	E7515B UXM 5G	MY58460103	1/31/2027
Wideband Radio Communication Tester	Keysight	E7515B UXM 5G	MY58291246	2/28/2027
Power Sensor	R&S	NRP8S	115089-GV	2/28/2027
Power Sensor	R&S	NRP8S	115090-HV	2/28/2027
Power Sensor	R&S	NRP8S	115095-QK	2/28/2027
Power Sensor	R&S	NRP18S	104134-bP	2/28/2027
Power Sensor	R&S	NRP18S	104136-JZ	2/28/2027
Power Sensor	R&S	NRP8S	115091-ZA	2/28/2027
Power Sensor	R&S	NRP8S	115093-GT	2/28/2027
Power Sensor	R&S	NRP8S	110667-vC	2/28/2027
Power Sensor	R&S	NRP8S	109115-nc	2/28/2027
Power Sensor	R&S	NRP8S	115094-Yy	2/28/2027
Power Sensor	R&S	NRP8S	115088-rq	2/28/2027
Power Sensor	R&S	NRP8S	115092-m	2/28/2027

Appendix E: Fast SAR System Verification

A system verification was performed weekly before measurements were made as defined in *cSAR3D Application Note: System Check or Verification, April 2024* per IEC 62209-3 standards.

cSAR3D Verification Test - Flat Phantom **Version date:** May 6, 2024

This spreadsheet is to be used for the System Verification Test described in the Application Note "System Check or Verification" that is part of the cSAR3D System Handbook. Please follow the Application Note "System Check or Verification" and fill the data in the yellow cells.

Date of Tests	12-Jul-2026
Software version	5.10.8.3621
Laboratory	OTA-A
Operator	Dominick Christmas
Ambient Temp.	21.1

- Notes**
- Location (Orientation) Antenna location and orientation as described in the cSAR3D System Handbook
- Reported uncertainty (k = 2) The expanded measurement uncertainty as reported by the cSAR3D software. In the cSAR3D Handbook, this is $\Delta SAR_{meas} = \sqrt{MM^2 + MN^2 + MD^2 + ME^2}$
- Total uncertainty (k = 2) The expanded uncertainty that combines the reported uncertainty with the uncertainty for system validation antenna. In the cSAR3D Handbook, this is $\Delta SAR_{syscheck} = \sqrt{(\Delta SAR_{meas}^2 + MV^2)} = \sqrt{MM^2 + MN^2 + MD^2 + ME^2 + MV^2}$
- Numerical target The absolute target values as tabulated in IEC 62209-3, known as SAR_1g.cal and SAR_10g.cal
- SAR from cSAR3D Certificate The cSAR3D measured SAR values reported by the SPEAG calibration lab, located in the cSAR3D calibration certificate. These are known in IEC 62209-3 as SAR_1g.sys and SAR_10g.sys
- Tolerance The allowable repeatability tolerance, which is stated as 10% in IEC 62209-3 for the same setup. For different positions and orientations, this is -20% to +10% as explained in the Application Note.

cSAR3D Type		Flat HSL																								
Serial Number		5279																								
Dipole Type	Dipole Serial Number	frequency (MHz)	Location (Orientation)	Power (dBm)	Measured SAR (W/kg)		Reported Uncertainty (k = 2) (dB)		Measured SAR Normalized to 1 W (W/kg)		Verification Against Absolute Targets				Verification Against Measured Reference Values											
											Numerical Target (W/kg)		Deviation from Target (dB)		Total Uncertainty (k = 2) (%) (dB)		Verified Against Numerical Targets?		SAR from cSAR3D Certificate (W/kg)		Deviation from Cal. Cert. (dB)		Tolerance (-dB) (+dB)		Verified Against Measured Values?	
					1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g	1g	10g
D835V2	4d117	835	A0 (0°)	17	0.433	0.273	1.01	1.01	8.64	5.45	9.56	6.22	-0.4	-0.6	30.7%	1.2	Yes	Yes	8.71	5.46	0.0	0.0	-1.0	0.4	Yes	Yes
D1950V3	1136	1950	A0 (0°)	17	2.000	1.000	1.01	1.01	39.91	19.95	40.5	20.9	-0.1	-0.2	30.7%	1.2	Yes	Yes	39.50	19.50	0.0	0.1	-1.0	0.4	Yes	Yes
D2450V2	748	2450	A0 (0°)	17	2.510	1.140	1.13	1.13	50.08	22.75	51.4	23.8	-0.1	-0.2	33.8%	1.3	Yes	Yes	51.80	23.10	-0.1	-0.1	-1.0	0.4	Yes	Yes
D5GHzV2	1003	5200	A0 (0°)	17	4.100	1.180	1.13	1.13	81.81	23.54	75.8	21.4	0.3	0.4	33.8%	1.3	Yes	Yes	86.40	24.00	-0.2	-0.1	-1.0	0.4	Yes	Yes
D5GHzV2	1003	5800	A0 (0°)	17	4.130	1.160	1.13	1.13	82.40	23.15	78.0	21.9	0.2	0.2	33.8%	1.3	Yes	Yes	86.50	23.70	-0.2	-0.1	-1.0	0.4	Yes	Yes

cSAR3D Verification Test - Flat Phantom

Version date: May 6, 2024

This spreadsheet is to be used for the System Verification Test described in the Application Note "System Check or Verification" that is part of the cSAR3D System Handbook
Please follow the Application Note "System Check or Verification" and fill the data in the yellow cells.

Date of Tests	12-Jul-2026
Software version	5.10.6.3469
Laboratory	OTA-B
Operator	Dominick Chistmas
Ambient Temp.	21.1

- Notes
- Location (Orientation)

Antenna location and orientation as described in the cSAR3D System Handbook
- Reported uncertainty (k = 2)

The expanded measurement uncertainty as reported by the cSAR3D software. In the cSAR3D Handbook, this is $\Delta SAR_{meas} = \sqrt{MM^2 + MN^2 + MD^2 + ME^2}$
- Total uncertainty (k = 2)

The expanded uncertainty that combines the reported uncertainty with the uncertainty for system validation antenna. In the cSAR3D Handbook, this is $\Delta SAR_{syscheck} = \sqrt{(\Delta SAR_{meas}^2 + MV^2)} = \sqrt{MM^2 + MN^2 + MD^2 + ME^2 + MV^2}$
- Numerical target

The absolute target values as tabulated in IEC 62209-3, known as SAR_1g.cal and SAR_10g.cal
- SAR from cSAR3D Certificate

The cSAR3D measured SAR values reported by the SPEAG calibration lab, located in the cSAR3D calibration certificate. These are known in IEC 62209-3 as SAR_1g.sys and SAR_10g.sys
- Tolerance

The allowable repeatability tolerance, which is stated as 10% in IEC 62209-3 for the same setup. For different positions and orientations, this is -20% to +10% as explained in the Application Note.

cSAR3D Type		Flat HSL																		Verification Against Absolute Targets								Verification Against Measured Reference Values							
Serial Number		5014																																	
Dipole Type	Dipole Serial Number	frequency (MHz)	Location (Orientation)	Power (dBm)	Measured SAR		Reported Uncertainty (k = 2)		Measured SAR Normalized to 1 W		Numerical Target		Deviation from Target		Total Uncertainty (k = 2)		Verified Against Numerical Targets?		SAR from cSAR3D Certificate		Deviation from Cal. Cert.		Tolerance		Verified Against Measured Values?										
					(W/kg)		(dB)		(W/kg)		(W/kg)		(dB)		(%)		1g	10g	(W/kg)		(dB)		-(dB)	+(dB)	1g	10g									
					1g	10g	1g	10g	1g	10g	1g	10g	1g	10g		(dB)			1g	10g	1g	10g													
D835V2	4d117	835	A0 (0°)	17	0.448	0.283	1.01	1.01	8.94	5.65	9.56	6.22	-0.3	-0.4	30.7%	1.2	Yes	Yes	8.71	5.46	0.1	0.1	-1.0	0.4	Yes	Yes									
D1950V3	1136	1950	A0 (0°)	17	1.990	1.000	1.01	1.01	39.71	19.95	40.5	20.9	-0.1	-0.2	30.7%	1.2	Yes	Yes	39.50	19.50	0.0	0.1	-1.0	0.4	Yes	Yes									
D2450V2	748	2450	A0 (0°)	17	2.550	1.160	1.13	1.13	50.88	23.15	51.4	23.8	0.0	-0.1	33.8%	1.3	Yes	Yes	51.80	23.10	-0.1	0.0	-1.0	0.4	Yes	Yes									
D5GHzv2	1003	5200	A0 (0°)	17	4.040	1.150	1.13	1.13	80.61	22.95	75.8	21.4	0.3	0.3	33.8%	1.3	Yes	Yes	86.40	24.00	-0.3	-0.2	-1.0	0.4	Yes	Yes									
D5GHzv2	1003	5800	A0 (0°)	17	3.950	1.120	1.13	1.13	78.81	22.35	78.0	21.9	0.0	0.1	33.8%	1.3	Yes	Yes	86.50	23.70	-0.4	-0.3	-1.0	0.4	Yes	Yes									

Appendix F: Measurement Uncertainty

F.1. Fast SAR

The cSAR3D Measurement Platform performs on-the-fly calculation of the uncertainty of each measurement from the measured SAR distribution and other parameters. The calculated uncertainties for each Fast SAR measurement performed is reported with the Fast SAR Test results.

The uncertainty calculations are performed in accordance with IEC 62209-3 and the draft IEC Technical Report for 5G NR FR-1.

The combined expanded uncertainties for *psSAR1g* and *psSAR10g* are calculated as follows:

$$U_{1g} = k \cdot u_{c,1g}$$

$$U_{10g} = k \cdot u_{c,10g}$$

A coverage factor of $k = 2$ is used, corresponding to a 95% confidence interval. The combined standard uncertainties, $u_{c,1g}$ [dB] and $u_{c,10g}$ [dB], having log normal distributions, are calculated as follows:

$$u_{c,1g} = \sqrt{\sum_{i=1}^N (a_{i,1g} \cdot c_i / q_i)^2} = \sqrt{\sum_{i=1}^N u_{i,1g}^2}$$

$$u_{c,10g} = \sqrt{\sum_{i=1}^N (a_{i,10g} \cdot c_i / q_i)^2} = \sqrt{\sum_{i=1}^N u_{i,10g}^2}$$

where

- $a_{i,1g}$ and $a_{i,10g}$ are the uncertainty values of the i^{th} uncertainty component having a probability density function PDF_i . These are determined from the measured SAR distribution, other measurement parameters, phantom type, and system characteristics
- q_i is the divisor corresponding to the probability density function PDF_i .
- c_i is the sensitivity coefficient associated with the i^{th} uncertainty component. It describes how the total uncertainty varies with small changes in the uncertainty component.
- $u_{i,1g} = a_{i,1g} \cdot c_i / q_i$ is standard uncertainty of the i^{th} uncertainty component. It is normalized so that it has a lognormal distribution.

F.1.1 Fast SAR Combined Expanded Uncertainty

The general combined expanded uncertainty declared by the Fast SAR system manufacturer is shown below in both percentages and decibel offsets.

Phantom Type	Distance (mm)	psSAR	$2 \cdot u_c (\pm\%)$				$2 \cdot u_c (\pm\text{dB})$			
			0.69 - 1 GHz	1 - 3 GHz	3 - 5 GHz	5 - 6 GHz	0.69 - 1 GHz	1 - 3 GHz	3 - 5 GHz	5 - 6 GHz
Flat	< 5	1g / 10g	27.5	27.5	29.0	29.0	1.5	1.5	1.6	1.6
Flat	≥ 5	1g / 10g	26.4	26.4	28.5	28.5	1.5	1.5	1.6	1.6
Head	≥ 0	1g / 10g	35.8	35.8	36.9	36.9	1.8	1.8	1.8	1.8

Note(s):

*: Measurement uncertainty declarations for Fast SAR systems are referenced from *Schmid & Partner Engineering AG, cSAR3D V5.10 Manual, October 2025*.

F.2. Conducted

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
RF Power Measurement Direct Method Using Power Meter	1.300 dB Peak 0.450 dB Avg

Uncertainty figures are valid to a confidence level of 95%.

END OF REPORT