



**FCC 47 CFR PART 15 SUBPART C
INDUSTRY CANADA RSS-247 ISSUE 1**

**CERTIFICATION TEST REPORT
CLASS II PERMISSIVE CHANGE**

FOR

PORTABLE COMPUTER

MODEL NUMBER: A1534

**FCC ID: BCGA1534
IC: 579C-A1534**

REPORT NUMBER: 16U22814-E3V3

ISSUE DATE: FEBRUARY 24, 2016

Prepared for
**APPLE, INC.
1 INFINITE LOOP
CUPERTINO, CA 95014, U.S.A.**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	02/19/2016	Initial Issue	M. Mekuria
V2	02/23/2016	Addressed TCB's Questions	E. Yu
V3	02/24/2016	Updated power CDD & BF	J. Vang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. SOFTWARE AND FIRMWARE.....	8
5.5. WORST-CASE CONFIGURATION AND MODE.....	9
5.6. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	15
7. MEASUREMENT METHODS	16
8. ANTENNA PORT TEST RESULTS	17
8.1. ON TIME AND DUTY CYCLE.....	17
8.2. 802.11b SISO MODE IN THE 2.4 GHz BAND, CHAIN 0.....	21
8.2.1. 6 dB BANDWIDTH.....	21
8.2.2. 99% BANDWIDTH.....	25
8.2.3. OUTPUT POWER	29
8.2.4. POWER SPECTRAL DENSITY	31
8.2.5. OUT-OF-BAND EMISSIONS	35
8.3. 802.11b SISO MODE IN THE 2.4 GHz BAND, CHAIN 1.....	42
8.3.1. 6 dB BANDWIDTH.....	42
8.3.2. 99% BANDWIDTH.....	46
8.3.3. OUTPUT POWER	50
8.3.4. POWER SPECTRAL DENSITY	52
8.3.5. OUT-OF-BAND EMISSIONS	56
8.4. 802.11b 2Tx MODE IN THE 2.4 GHz BAND	63
8.4.1. 6 dB BANDWIDTH.....	63
8.4.2. 99% BANDWIDTH.....	69
8.4.3. OUTPUT POWER	75
8.4.4. POWER SPECTRAL DENSITY	77
8.4.5. OUT-OF-BAND EMISSIONS	83
8.5. 802.11g SISO MODE IN THE 2.4 GHz BAND	96

8.6.	802.11n HT20 SISO MODE IN THE 2.4 GHz BAND, CHAIN 0.....	97
8.6.1.	6 dB BANDWIDTH.....	97
8.6.2.	99% BANDWIDTH.....	102
8.6.3.	OUTPUT POWER	107
8.6.4.	POWER SPECTRAL DENSITY	109
8.6.5.	OUT-OF-BAND EMISSIONS	114
8.7.	802.11n HT20 SISO MODE IN THE 2.4 GHz BAND, CHAIN 1.....	123
8.7.1.	6 dB BANDWIDTH.....	123
8.7.2.	99% BANDWIDTH.....	128
8.7.3.	OUTPUT POWER	133
8.7.4.	POWER SPECTRAL DENSITY	135
8.7.5.	OUT-OF-BAND EMISSIONS	140
8.8.	802.11g 2Tx CDD MODE IN THE 2.4 GHz BAND	149
8.9.	802.11n HT20 2Tx CDD MODE IN THE 2.4 GHz BAND.....	150
8.9.1.	6 dB BANDWIDTH.....	150
8.9.2.	99% BANDWIDTH.....	161
8.9.3.	OUTPUT POWER	172
8.9.4.	POWER SPECTRAL DENSITY	174
8.9.5.	OUT-OF-BAND EMISSIONS	185
8.10.	802.11ac VHT20 BEAM FORMING MODE IN THE 2.4 GHz BAND	206
8.10.1.	6 dB BANDWIDTH	206
8.10.2.	99% BANDWIDTH	217
8.10.3.	OUTPUT POWER	228
8.10.4.	POWER SPECTRAL DENSITY.....	230
8.10.5.	OUT-OF-BAND EMISSIONS.....	241
9.	RADIATED TEST RESULTS.....	262
9.1.	LIMITS AND PROCEDURE	262
9.2.	TRANSMITTER ABOVE 1 GHz.....	263
9.2.1.	802.11b 1Tx MODE IN THE 2.4 GHz BAND CHAIN 0	263
9.2.2.	802.11b 1Tx MODE IN THE 2.4 GHz BAND CHAIN 1	281
9.2.3.	802.11b 2Tx MODE IN THE 2.4 GHz BAND (CHAIN 0 + CHAIN 1).....	299
9.2.4.	802.11n HT20 1Tx MODE IN THE 2.4 GHz BAND CHAIN 0	317
9.2.5.	802.11n HT20 1Tx MODE IN THE 2.4 GHz BAND CHAIN 1	339
9.2.6.	802.11n HT20 2Tx MODE IN THE 2.4 GHz BAND (CHAIN 0 + CHAIN 1)	361
9.2.7.	802.11ac VHT20 BEAM FORMING MODE IN THE 2.4 GHz BAND (CHAIN 0 + CHAIN 1)	387
9.3.	WORST-CASE BELOW 1 GHz.....	415
9.4.	WORST-CASE 18 to 26 GHz.....	417
10.	AC POWER LINE CONDUCTED EMISSIONS	419
11.	SETUP PHOTOS	422

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE, INC.
1 INFINITE LOOP
CUPERTINO, CA 95014, U.S.A.

EUT DESCRIPTION: PORTABLE COMPUTER

MODEL: A1534

SERIAL NUMBER: C02R4002H501 (CONDUCTED); C02R400FH4W8 (RADIATED)


DATE TESTED: JANUARY 27-- FEBRUARY 24, 2016

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:



MENGISTU MEKURIA
PROJECT LEADER
UL VERIFICATION SERVICES INC.

Tested By:



ERIC YU
EMC ENGINEER
UL VERIFICATION SERVICES INC.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, KDB 558074 D01 v03r04, ANSI C63.10-2013, RSS-GEN Issue 4, and RSS-247 Issue 1.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A	☒ Chamber D
☐ Chamber B	☒ Chamber E
☐ Chamber C	☒ Chamber F
	☐ Chamber G
	☒ Chamber H

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers A through H are covered under Industry Canada company address code 2324B with site numbers 2324B -1 through 2324B-8, respectively.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	± 3.52 dB
Radiated Disturbance, 30 to 1000 MHz	± 4.94 dB
Radiated Disturbance, 1 to 6 GHz	± 3.86 dB
Radiated Disturbance, 6 to 18 GHz	± 4.23 dB
Radiated Disturbance, 18 to 26 GHz	± 5.30 dB
Radiated Disturbance, 26 to 40 GHz	± 5.23 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Laptop Device with Bluetooth and WLAN Radios (AC 80 MHZ Beam-Forming).

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2472	802.11b 1TX	19.47	88.51
2412 - 2472	802.11b 2TX	22.41	174.18
2412 - 2472	802.11g 1TX	Covered by HT20 1TX	
2412 - 2472	802.11g 2TX	Covered by HT20 2TX CDD	
2412 - 2472	802.11n HT20 1TX	18.99	79.25
2412 - 2472	802.11n HT20 2TX CDD	21.91	155.24
2412 - 2472	802.11ac VHT20 2TX Beam Forming	21.94	156.31

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency Band (GHz)	Antenna Gain (dBi)	
	Chain 0	Chain 1
2.4	2.24	3.40

5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was 7.21.94.152

The test utility software used during testing was 10.11.3 (15D2043)

5.5. WORST-CASE CONFIGURATION AND MODE

For below 1G radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

For g and HT20 modes, radiated harmonics spurious and power line conducted emissions were performed with the EUT set at the CDD mode at highest power setting among the CDD/STBC/SDM/Beamforming modes as worst-case scenario.

EUT was investigated with and without AC Charger and the worst case was determined to be with charger. Therefore, all testing was performed with AC charger in normal use orientation as described by the manufacturer.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20mode: MCS0

The following modes have the same target power and use the same modulation (OFDM). Therefore, 802.11g 1TX and 802.11g 2TX are covered by 802.11n HT20 1TX and 802.11n HT20 2TX CDD respectively.

- 802.11g and 802.11n HT20 1TX
- 802.11g 2TX and 802.11n HT20 2TX CDD

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC/ DC Adapter	Apple Inc.	A1540	N/A	N/A

I/O CABLES (CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	2	SMA	Un-Shielded	0.2	To Spectrum Analyzer
2	DC	1	Lightning	Un-Shielded	2	N/A

I/O CABLES (ABOVE 1G RADIATED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC	1	Lightning	Un-Shielded	2	N/A


I/O CABLES (BELOW 1G RADIATED AND AC POWER CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
2	DC	1	Lightning	Un-Shielded	2	NA
3	Audio	1	Jack	Un-Shielded	0.5	NA

TEST SETUP- CONDUCTED PORT

The EUT was tested connected to spectrum analyzer via antenna port. Test software exercised the EUT.


SETUP DIAGRAM



TEST SETUP- RADIATED- ABOVE 1 GHz

The EUT was powered by AC/DC adapter. Test software exercised the EUT.


SETUP DIAGRAM



TEST SETUP- RADIATED- BELOW 1 GHz

The EUT was powered by AC/DC adapter and with earphone plugged in. Test software exercised the EUT.


SETUP DIAGRAM



TEST SETUP- AC LINE CONDUCTED TESTS

The EUT was powered by AC/DC adapter and with earphone plugged in. Test software exercised the EUT.

SETUP DIAGRAM



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Horn 1-18GHz	ETS Lindgren	3117	165318	4/10/2016
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB3	A022813-1	10/28/2016
Amplifier, 1 - 18GHz	Miteq	AFS42-00101800-25-S-42	1782153	6/2/2016
Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	323561	6/8/2016
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent	N9030A	US51350187	6/1/2016
Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	185623	6/9/2016
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent	N9030A	MY51380911	10/15/2016
Power Meter, P-series single channel	Agilent	N1911A	GB45100212	9/25/2016
Power Sensor, P - series, 50MHz to 18GHz, Wideband	Agilent	N1921A	MY53260010	7/8/2016
Antenna, Horn 18 to 26.5GHz	ARA	MWH-1826	209336	5/12/2016
Spectrum Analyzer, 40 GHz	Agilent	8564E	3943A01643	8/14/2016
Amplifier, 1 to 26.5GHz, 23.5dB Gain minimum	Agilent	8449B	3008A04710	6/29/2016
AC Line Conducted				
EMI Test Receiver 9KHz-7GHz	Rohde & Schwarz	ESCI7	100935	9/16/2016
LISN for Conducted Emissions CISPR-16	Fischer	50/250-25-2	161124	9/16/2016
Power Cable, Line Conducted Emissions	UL	PG1	N/A	7/28/2016
UL SOFTWARE				
* Radiated Software	UL	UL EMC	Ver 9.5, June 24, 2015	
* Conducted Software	UL	UL EMC	Ver 4.0, January 11, 2016	
* AC Line Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015	

Note: * indicates automation software version used in the compliance certification testing

7. MEASUREMENT METHODS

6 dB BW: KDB 558074 D01 v03r04, Section 8.1.

Output Power: KDB 558074 D01 v03r02, Section 9.2.3.1

Power Spectral Density: KDB 558074 D01 v03r04, Section 10.2.

Out-of-band emissions in non-restricted bands: KDB 558074 D01 v03r04, Section 11.0.

Out-of-band emissions in restricted bands: KDB 558074 D01 v03r04, Section 12.1.

Band-edge: KDB 558074 D01 v03r04, Section 12.1.

8. ANTENNA PORT TEST RESULTS

8.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.



PROCEDURE



KDB 558074 Zero-Span Spectrum Analyzer Method.


ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
2.4GHz Band						
802.11b 1TX	5.000	5.000	1.000	100.00%	0.00	0.010
802.11b CDD	5.000	5.000	1.000	100.00%	0.00	0.010
802.11n HT20 1TX	1.920	1.941	0.989	98.92%	0.00	0.010
802.11n HT20 CDD	1.914	1.938	0.988	98.76%	0.00	0.010
802.11ac VHT20 Beam Forming	3.904	4.544	0.859	85.92%	0.66	0.256

DUTY CYCLE PLOTS







8.2. 802.11b SISO MODE IN THE 2.4 GHz BAND, CHAIN 0

8.2.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)



IC RSS-247 (5.2) (1)



The minimum 6 dB bandwidth shall be at least 500 kHz.


RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	8.580	0.5
Mid	2437	8.554	0.5
High_11	2462	8.567	0.5
High_12	2467	8.073	0.5
High_13	2472	8.960	0.5

6 dB BANDWIDTH







8.2.2. 99% BANDWIDTH



LIMITS



None; for reporting purposes only.


RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	11.632
Mid	2437	11.729
High_11	2462	11.557
High_12	2467	11.369
High_13	2472	11.826

99% BANDWIDTH







8.2.3. OUTPUT POWER

LIMITS

FCC §15.247

IC RSS-247 (5.4) (4)

For systems using digital modulation in the 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

RESULTS

Limits

Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	2.24	30.00	30	36	30.00
Mid	2437	2.24	30.00	30	36	30.00
High_11	2462	2.24	30.00	30	36	30.00
High_12	2467	2.24	30.00	30	36	30.00
High_13	2472	2.24	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	19.45	19.45	30.00	-10.55
Mid	2437	19.47	19.47	30.00	-10.53
High_11	2462	19.34	19.34	30.00	-10.66
High_12	2467	17.48	17.48	30.00	-12.52
High_13	2472	14.99	14.99	30.00	-15.01

8.2.4. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247

IC RSS-247 (5.2) (2)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 KHz band during any time interval of continuous transmissions.



RESULTS



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd PSD
---------------------------	------	---


PSD Results

Channel	Frequency (MHz)	Meas (dBm)	Total Corr'd PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-2.04	-2.04	8.0	-10.0
Mid	2437	-2.17	-2.17	8.0	-10.2
High_11	2462	-2.50	-2.50	8.0	-10.5
High_12	2467	-4.16	-4.16	8.0	-12.2
High_13	2472	-6.95	-6.95	8.0	-15.0

PSD







8.2.5. OUT-OF-BAND EMISSIONS

LIMITS


FCC §15.247 (d)

IC RSS-247 (5.5)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

RESULTS



LOW CHANNEL BANDEDGE




MID CHANNEL REFERENCE







HIGH CHANNEL BANDEDGE






OUT-OF-BAND EMISSIONS







8.3. 802.11b SISO MODE IN THE 2.4 GHz BAND, CHAIN 1

8.3.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)



IC RSS-247 (5.2) (1)



The minimum 6 dB bandwidth shall be at least 500 kHz.


RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	8.047	0.5
Mid	2437	9.072	0.5
High_11	2462	8.580	0.5
High_12	2467	8.580	0.5
High_13	2472	8.554	0.5

6 dB BANDWIDTH







8.3.2. 99% BANDWIDTH



LIMITS



None; for reporting purposes only.


RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	11.928
Mid	2437	11.251
High_11	2462	12.078
High_12	2467	11.850
High_13	2472	11.718

99% BANDWIDTH







8.3.3. OUTPUT POWER

LIMITS

FCC §15.247

IC RSS-247 (5.4) (4)

For systems using digital modulation in the 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

RESULTS

Limits

Channel	Frequency (MHz)	Directional Gain (dBi)	FCC Power Limit (dBm)	IC Power Limit (dBm)	IC EIRP Limit (dBm)	Max Power (dBm)
Low	2412	3.40	30.00	30	36	30.00
Mid	2437	3.40	30.00	30	36	30.00
High_11	2462	3.40	30.00	30	36	30.00
High_12	2467	3.40	30.00	30	36	30.00
High_13	2472	3.40	30.00	30	36	30.00

Results

Channel	Frequency (MHz)	Meas Power (dBm)	Total Corr'd Power (dBm)	Power Limit (dBm)	Margin (dB)
Low	2412	19.37	19.37	30.00	-10.63
Mid	2437	19.42	19.42	30.00	-10.58
High_11	2462	19.39	19.39	30.00	-10.61
High_12	2467	17.44	17.44	30.00	-12.56
High_13	2472	14.82	14.82	30.00	-15.18

8.3.4. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247

IC RSS-247 (5.2) (2)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 KHz band during any time interval of continuous transmissions.



RESULTS



Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd PSD
---------------------------	------	---


PSD Results

Channel	Frequency (MHz)	Meas (dBm)	Total Corr'd PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-2.23	-2.23	8.0	-10.2
Mid	2437	-2.26	-2.26	8.0	-10.3
High_11	2462	-2.36	-2.36	8.0	-10.4
High_12	2467	-4.53	-4.53	8.0	-12.5
High_13	2472	-6.78	-6.78	8.0	-14.8

PSD







8.3.5. OUT-OF-BAND EMISSIONS

LIMITS


FCC §15.247 (d)

IC RSS-247 (5.5)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

RESULTS



LOW CHANNEL BANDEDGE




MID CHANNEL REFERENCE







HIGH CHANNEL BANDEDGE






OUT-OF-BAND EMISSIONS







8.4. 802.11b 2Tx MODE IN THE 2.4 GHz BAND

8.4.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)



IC RSS-247 (5.2) (1)



The minimum 6 dB bandwidth shall be at least 500 kHz.


RESULTS

Channel	Frequency (MHz)	6 dB BW Chain 0 (MHz)	6 dB BW Chain 1 (MHz)	Minimum Limit (MHz)
Low	2412	8.10	8.61	0.5
Mid	2437	8.07	8.57	0.5
High_11	2462	8.07	8.57	0.5
High_12	2467	8.05	8.58	0.5
High_13	2472	8.07	8.54	0.5


6 dB BANDWIDTH, Chain 0











6 dB BANDWIDTH, Chain 1







8.4.2. 99% BANDWIDTH



LIMITS



None; for reporting purposes only.


RESULTS

Channel	Frequency (MHz)	99% BW Chain 0 (MHz)	99% BW Chain 1 (MHz)
Low	2412	11.136	11.402
Mid	2437	11.669	11.807
High_11	2462	11.048	12.009
High_12	2467	11.731	11.733
High_13	2472	11.746	11.360

99% BANDWIDTH, Chain 0







99% BANDWIDTH, Chain 1

