






Plot 7-83. Band Edge Plot SISO CORE0 (802.11g- Ch. 1)




Plot 7-84. Band Edge Plot SISO CORE0 (802.11g - Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 69 of 142




Plot 7-85. Band Edge Plot SISO CORE0 (802.11g – Ch. 12)




Plot 7-86. Band Edge Plot SISO CORE0 (802.11g – Ch. 13)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 70 of 142




Plot 7-87. Band Edge Plot SISO CORE0 (802.11n (2.4GHz) – Ch. 1)




Plot 7-88. Band Edge Plot SISO CORE0 (802.11n (2.4GHz) – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 71 of 142




Plot 7-89. Band Edge Plot SISO CORE0 (802.11n – Ch. 12)




Plot 7-90. Band Edge Plot SISO CORE0 (802.11n – Ch. 13)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 72 of 142

SISO Core 1 Primary Conducted Emissions at the Band Edge




Plot 7-91. Band Edge Plot SISO CORE1 PRIMARY (802.11b – Ch. 1)




Plot 7-92. Band Edge Plot SISO CORE1 PRIMARY (802.11b – Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 73 of 142




Plot 7-93. Band Edge Plot SISO CORE1 PRIMARY (802.11b – Ch. 12)




Plot 7-94. Band Edge Plot SISO CORE1 PRIMARY (802.11b – Ch. 13)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC. MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 74 of 142




Plot 7-95. Band Edge Plot SISO CORE1 PRIMARY (802.11g– Ch. 1)




Plot 7-96. Band Edge Plot SISO CORE1 PRIMARY (802.11g – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 75 of 142




Plot 7-97. Band Edge Plot SISO CORE1 PRIMARY (802.11g – Ch. 12)




Plot 7-98. Band Edge Plot SISO CORE1 PRIMARY (802.11g – Ch. 13)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 76 of 142




Plot 7-99. Band Edge Plot SISO CORE1 PRIMARY (802.11n (2.4GHz) – Ch. 1)




Plot 7-100. Band Edge Plot SISO CORE1 PRIMARY (802.11n (2.4GHz) – Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 77 of 142



Plot 7-101. Band Edge Plot SISO CORE1 PRIMARY (802.11n – Ch. 12)




Plot 7-102. Band Edge Plot SISO CORE1 PRIMARY (802.11n – Ch. 13)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 78 of 142

SISO Core 1 Diversity Conducted Emissions at the Band Edge




Plot 7-103. Band Edge Plot SISO CORE1 DIVERSITY (802.11b – Ch. 1)




Plot 7-104. Band Edge Plot SISO CORE1 DIVERSITY (802.11b – Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 79 of 142



Plot 7-105. Band Edge Plot SISO CORE1 DIVERSITY (802.11b – Ch. 12)




Plot 7-106. Band Edge Plot SISO CORE1 DIVERSITY (802.11b – Ch. 13)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 80 of 142




Plot 7-107. Band Edge Plot SISO CORE1 DIVERSITY (802.11g- Ch. 1)




Plot 7-108. Band Edge Plot SISO CORE1 DIVERSITY (802.11g - Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 81 of 142




Plot 7-109. Band Edge Plot SISO CORE1 DIVERSITY (802.11g- Ch. 12)




Plot 7-110. Band Edge Plot SISO CORE1 DIVERSITY (802.11g - Ch. 13)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 82 of 142




Plot 7-111. Band Edge Plot SISO CORE1 DIVERSITY (802.11n (2.4GHz) – Ch. 1)




Plot 7-112. Band Edge Plot SISO CORE1 DIVERSITY (802.11n (2.4GHz) – Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 83 of 142



Plot 7-113. Band Edge Plot SISO CORE1 DIVERSITY (802.11n- Ch. 12)



Plot 7-114. Band Edge Plot SISO CORE1 DIVERSITY (802.11n - Ch. 13)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 84 of 142

7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots, the EUT was investigated in all available data rates for “b”, “g”, and “n” modes. The worst case spurious emissions for the 2.4GHz band were found while transmitting in “b” mode at 1 Mbps and are shown in the plots below.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.1 of ANSI C63.10-2013 and KDB 558074 D01 v05.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05 – Section 8.5
ANSI C63.10-2013 – Section 14.3.3
KDB 662911 D01 v02r01 – Section E)3)b)

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 85 of 142


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. The conducted spurious emissions were measured to relative limits. Therefore, in accordance with ANSI C63.10-2013 and KDB 662911 D01 v02r01 Section E)3)b), it was unnecessary to show compliance through the summation of test results of the individual outputs.


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 86 of 142



© 2018 PCTEST Engineering Laboratory, Inc. V 8.3 07/10/2018
All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.




Plot 7-117. Conducted Spurious Plot SISO CORE0 (802.11b – Ch. 6)




Plot 7-118. Conducted Spurious Plot SISO CORE0 (802.11b – Ch. 6)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 88 of 142




Plot 7-119. Conducted Spurious Plot SISO CORE0 (802.11b – Ch. 11)




Plot 7-120. Conducted Spurious Plot SISO CORE0 (802.11b – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 89 of 142

SISO Core 1 Primary Conducted Spurious Emissions




Plot 7-121. Conducted Spurious Plot SISO CORE1 PRIMARY (802.11b – Ch. 1)




Plot 7-122. Conducted Spurious Plot SISO CORE1 PRIMARY (802.11b – Ch. 1)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 90 of 142




Plot 7-123. Conducted Spurious Plot SISO CORE1 PRIMARY (802.11b – Ch. 6)




Plot 7-124. Conducted Spurious Plot SISO CORE1 PRIMARY (802.11b – Ch. 6)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 91 of 142




Plot 7-125. Conducted Spurious Plot SISO CORE1 PRIMARY (802.11b – Ch. 11)




Plot 7-126. Conducted Spurious Plot SISO CORE1 PRIMARY (802.11b – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 92 of 142

SISO Core 1 Diversity Conducted Spurious Emissions




Plot 7-127. Conducted Spurious Plot SISO CORE1 DIVERSITY (802.11b – Ch. 1)




Plot 7-128. Conducted Spurious Plot SISO CORE1 DIVERSITY (802.11b – Ch. 1)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 93 of 142




Plot 7-129. Conducted Spurious Plot SISO CORE1 DIVERSITY (802.11b – Ch. 6)




Plot 7-130. Conducted Spurious Plot SISO CORE1 DIVERSITY (802.11b – Ch. 6)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 94 of 142



Plot 7-131. Conducted Spurious Plot SISO CORE1 DIVERSITY (802.11b – Ch. 11)



Plot 7-132. Conducted Spurious Plot SISO CORE1 DIVERSITY (802.11b – Ch. 11)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 95 of 142

7.7 Radiated Spurious Emission Measurements – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-24 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-24. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3
KDB 558074 D01 v05 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 96 of 142

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-24.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 97 of 142

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 98 of 142

7.7.1 SISO Core0 Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-133. Radiated Spurious Plot above 1GHz SISO CORE0 (802.11b – Ch. 1)



Plot 7-134. Radiated Spurious Plot above 1GHz SISO CORE0 (802.11b – Ch. 6)



Plot 7-135. Radiated Spurious Plot above 1GHz SISO CORE0 (802.11b – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 99 of 142

SISO Core 0 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	H	-	-	-79.62	4.73	32.11	53.98	-21.87
4824.00	Peak	H	-	-	-67.88	4.73	43.85	73.98	-30.13
12060.00	Avg	H	-	-	-83.12	19.97	43.85	53.98	-10.13
12060.00	Peak	H	-	-	-73.71	19.97	53.26	73.98	-20.72

Table 7-25. SISO CORE0 Radiated Measurements

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-80.42	4.99	31.57	53.98	-22.41
4874.00	Peak	H	-	-	-67.93	4.99	44.06	73.98	-29.92
7311.00	Avg	H	-	-	-80.70	11.96	38.26	53.98	-15.72
7311.00	Peak	H	-	-	-70.00	11.96	48.96	73.98	-25.02
12185.00	Avg	H	-	-	-82.77	19.24	43.47	53.98	-10.51
12185.00	Peak	H	-	-	-73.21	19.24	53.03	73.98	-20.95

Table 7-26. SISO CORE0 Radiated Measurements

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 100 of 142

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	-	-	-79.44	4.75	32.31	53.98	-21.67
4924.00	Peak	H	-	-	-68.56	4.75	43.19	73.98	-30.79
7386.00	Avg	H	-	-	-79.53	12.14	39.61	53.98	-14.37
7386.00	Peak	H	-	-	-69.69	12.14	49.45	73.98	-24.53
12310.00	Avg	H	-	-	-81.99	20.29	45.30	53.98	-8.68
12310.00	Peak	H	-	-	-73.05	20.29	54.24	73.98	-19.74

Table 7-27. SISO CORE0 Radiated Measurements


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 101 of 142

7.7.2 SISO Core 1 Primary Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-136. Radiated Spurious Plot above 1GHz SISO CORE1 PRIMARY (802.11b – Ch. 1)



Plot 7-137. Radiated Spurious Plot above 1GHz SISO CORE1 PRIMARY (802.11b – Ch. 6)



Plot 7-138. Radiated Spurious Plot above 1GHz SISO CORE1 PRIMARY (802.11b – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 102 of 142

SISO Core 1 Primary Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	H	113	333	-74.00	4.73	37.73	53.98	-16.25
4824.00	Peak	H	113	333	-65.98	4.73	45.75	73.98	-28.23
12060.00	Avg	H	-	-	-81.57	19.97	45.40	53.98	-8.58
12060.00	Peak	H	-	-	-69.86	19.97	57.11	73.98	-16.87

Table 7-28. SISO CORE1 PRIMARY Radiated Measurements

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	107	337	-74.72	4.99	37.27	53.98	-16.71
4874.00	Peak	H	107	337	-66.03	4.99	45.96	73.98	-28.02
7311.00	Avg	H	-	-	-79.07	11.96	39.89	53.98	-14.09
7311.00	Peak	H	-	-	-68.46	11.96	50.50	73.98	-23.48
12185.00	Avg	H	-	-	-81.34	19.24	44.90	53.98	-9.08
12185.00	Peak	H	-	-	-70.32	19.24	55.92	73.98	-18.06

Table 7-29. SISO CORE1 PRIMARY Radiated Measurements

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 103 of 142

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	105	344	-77.25	4.75	34.50	53.98	-19.48
4924.00	Peak	H	105	344	-67.60	4.75	44.15	73.98	-29.83
7386.00	Avg	H	-	-	-79.19	12.14	39.95	53.98	-14.03
7386.00	Peak	H	-	-	-67.55	12.14	51.59	73.98	-22.39
12310.00	Avg	H	-	-	-81.75	20.29	45.54	53.98	-8.44
12310.00	Peak	H	-	-	-70.64	20.29	56.65	73.98	-17.33

Table 7-30. SISO CORE1 PRIMARY Radiated Measurements


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 104 of 142

7.7.3 SISO Core 1 Diversity Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-139. Radiated Spurious Plot above 1GHz SISO CORE1 DIVERSITY (802.11b – Ch. 1)



Plot 7-140. Radiated Spurious Plot above 1GHz SISO CORE1 DIVERSITY (802.11b – Ch. 6)



Plot 7-141. Radiated Spurious Plot above 1GHz SISO CORE1 DIVERSITY (802.11b – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 105 of 142

SISO Core 1 Diversity Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	H	143	329	-78.82	4.77	32.95	53.98	-21.03
4824.00	Peak	H	143	329	-66.34	4.77	45.43	73.98	-28.55
12060.00	Avg	H	-	-	-82.98	19.71	43.73	53.98	-10.25
12060.00	Peak	H	-	-	-73.54	19.71	53.17	73.98	-20.81

Table 7-31. SISO CORE1 DIVERSITY Radiated Measurements

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	291	108	-79.04	5.12	33.08	53.98	-20.90
4874.00	Peak	H	291	108	-67.44	5.12	44.68	73.98	-29.30
7311.00	Avg	H	-	-	-80.61	12.30	38.69	53.98	-15.29
7311.00	Peak	H	-	-	-70.21	12.30	49.09	73.98	-24.89
12185.00	Avg	H	-	-	-82.91	19.31	43.40	53.98	-10.58
12185.00	Peak	H	-	-	-73.39	19.31	52.92	73.98	-21.06

Table 7-32. SISO CORE1 DIVERSITY Radiated Measurements

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 106 of 142

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	293	307	-78.68	4.68	33.00	53.98	-20.98
4924.00	Peak	H	293	307	-68.44	4.68	43.24	73.98	-30.74
7386.00	Avg	H	-	-	-80.05	12.17	39.12	53.98	-14.86
7386.00	Peak	H	-	-	-70.31	12.17	48.86	73.98	-25.12
12310.00	Avg	H	-	-	-83.34	19.75	43.41	53.98	-10.57
12310.00	Peak	H	-	-	-73.12	19.75	53.63	73.98	-20.35

Table 7-33. SISO CORE1 DIVERSITY Radiated Measurements


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 107 of 142

7.7.4 CDD Primary Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-142. Radiated Spurious Plot above 1GHz CDD PRIMARY (802.11n – Ch. 1)



Plot 7-143. Radiated Spurious Plot above 1GHz CDD PRIMARY (802.11n – Ch. 6)



Plot 7-144. Radiated Spurious Plot above 1GHz CDD PRIMARY (802.11n – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 108 of 142

CDD Primary Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	H	-	-	-79.17	6.79	0.00	34.62	53.98	-19.36
4824.00	Peak	H	-	-	-69.17	6.79	0.00	44.62	73.98	-29.36
12060.00	Avg	H	-	-	-81.79	17.97	0.00	43.18	53.98	-10.80
12060.00	Peak	H	-	-	-67.95	17.97	0.00	57.02	73.98	-16.96

Table 7-34. Radiated Measurements CDD PRIMARY

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-79.22	6.82	0.00	34.60	53.98	-19.38
4874.00	Peak	H	-	-	-67.87	6.82	0.00	45.95	73.98	-28.03
7311.00	Avg	H	-	-	-81.06	11.09	0.00	37.03	53.98	-16.95
7311.00	Peak	H	-	-	-69.07	11.09	0.00	49.02	73.98	-24.96
12185.00	Avg	H	-	-	-81.50	18.19	0.00	43.69	53.98	-10.29
12185.00	Peak	H	-	-	-70.03	18.19	0.00	55.16	73.98	-18.82

Table 7-35. Radiated Measurements CDD PRIMARY

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 109 of 142

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	-	-	-79.40	7.54	0.00	35.14	53.98	-18.84
4924.00	Peak	H	-	-	-67.46	7.54	0.00	47.08	73.98	-26.90
7386.00	Avg	H	-	-	-80.97	11.75	0.00	37.78	53.98	-16.20
7386.00	Peak	H	-	-	-69.90	11.75	0.00	48.85	73.98	-25.13
12310.00	Avg	H	-	-	-82.34	18.41	0.00	43.07	53.98	-10.91
12310.00	Peak	H	-	-	-71.41	18.41	0.00	54.00	73.98	-19.98

Table 7-36. Radiated Measurements CDD PRIMARY


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 110 of 142

7.7.5 CDD Diversity Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-145. Radiated Spurious Plot above 1GHz CDD DIVERSITY (802.11n – Ch. 1)



Plot 7-146. Radiated Spurious Plot above 1GHz CDD DIVERSITY (802.11n – Ch. 6)



Plot 7-147. Radiated Spurious Plot above 1GHz CDD DIVERSITY (802.11n – Ch. 11)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 111 of 142

CDD Diversity Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	H	-	-	-79.40	6.79	0.00	34.39	53.98	-19.59
4824.00	Peak	H	-	-	-68.08	6.79	0.00	45.71	73.98	-28.27
12060.00	Avg	H	-	-	-81.89	17.97	0.00	43.08	53.98	-10.90
12060.00	Peak	H	-	-	-71.25	17.97	0.00	53.72	73.98	-20.26

Table 7-37. Radiated Measurements CDD DIVERSITY

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	H	-	-	-79.28	6.82	0.00	34.54	53.98	-19.44
4874.00	Peak	H	-	-	-68.34	6.82	0.00	45.48	73.98	-28.50
7311.00	Avg	H	-	-	-81.12	11.09	0.00	36.97	53.98	-17.01
7311.00	Peak	H	-	-	-69.57	11.09	0.00	48.52	73.98	-25.46
12185.00	Avg	H	-	-	-81.51	18.19	0.00	43.68	53.98	-10.30
12185.00	Peak	H	-	-	-70.63	18.19	0.00	54.56	73.98	-19.42

Table 7-38. Radiated Measurements CDD DIVERSITY

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 112 of 142

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	-	-	-79.37	7.54	0.00	35.17	53.98	-18.81
4924.00	Peak	H	-	-	-67.79	7.54	0.00	46.75	73.98	-27.23
7386.00	Avg	H	-	-	-81.04	11.75	0.00	37.71	53.98	-16.27
7386.00	Peak	H	-	-	-69.36	11.75	0.00	49.39	73.98	-24.59
12310.00	Avg	H	-	-	-82.61	18.41	0.00	42.80	53.98	-11.18
12310.00	Peak	H	-	-	-71.52	18.41	0.00	53.89	73.98	-20.09

Table 7-39. Radiated Measurements CDD DIVERSITY


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 113 of 142

CDD Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-148. Radiated Spurious Plot above 18GHz CDD Primary (802.11b – Ch. 6, Ant. Pol. H)



Plot 7-149. Radiated Spurious Plot above 18GHz CDD Primary (802.11b – Ch. 6, Ant. Pol. V)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 114 of 142

7.7.6 SISO Core0 Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11b
Worst Case Transfer Rate:	1Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1



Plot 7-150. Radiated Restricted Lower Band Edge Measurement SISO CORE0 (Average & Peak)


Worst Case Mode:	802.11b
Worst Case Transfer Rate:	1Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2467MHz
Channel:	12



Plot 7-151. Radiated Restricted Upper Band Edge Measurement SISO CORE0 (Average & Peak)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 115 of 142

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-152. Radiated Restricted Upper Band Edge Measurement SISO CORE0 (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-153. Radiated Restricted Lower Band Edge Measurement SISO CORE0 (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 116 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-154. Radiated Restricted Upper Band Edge Measurement SISO CORE0 (Average & Peak)

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-155. Radiated Restricted Upper Band Edge Measurement SISO CORE0 (Average & Peak)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 117 of 142