



Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5510MHz
Channel: 102



Plot 7-248. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5550MHz
Channel: 110



Plot 7-249. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 180 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5670 MHz
Channel: 134



Plot 7-250. Radiated Upper Band Edge Plot SISO CORE 1 (Peak - UNII Band 2C)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5755MHz
Channel: 151



Plot 7-251. Radiated Lower Band Edge Plot SISO CORE 1 (Peak - UNII Band 3)

FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 181 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5795MHz
Channel: 159




Plot 7-252. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 182 of 208

7.6.10 SISO CORE-1 Radiated Band Edge Measurements (80MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5210MHz
Channel: 42



Plot 7-253. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 1)


Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5290MHz
Channel: 58



Plot 7-254. Radiated Upper Band Edge Plot SISO CORE 1 (UNII Band 2A)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 183 of 208

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5530MHz
Channel: 106



Plot 7-255. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5775MHz
Channel: 155



Plot 7-256. Radiated Lower Band Edge Plot SISO CORE 1 (Peak - UNII Band 3)

FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 184 of 208

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5775MHz
Channel: 155




Plot 7-257. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 185 of 208

7.6.11 CDD/SDM Radiated Band Edge Measurements (20MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5180MHz
Channel: 36



Plot 7-258. Radiated Lower Band Edge Plot CDD (UNII Band 1)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5200MHz
Channel: 40



Plot 7-259. Radiated Lower Band Edge Plot CDD (UNII Band 1)


FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 186 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS8
Distance of Measurements: 3 Meters
Operating Frequency: 5300MHz
Channel: 60



Plot 7-260. Radiated Upper Band Edge Plot SDM (UNII Band 2A)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64



Plot 7-261. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 187 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100



Plot 7-262. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS8
Distance of Measurements: 3 Meters
Operating Frequency: 5520MHz
Channel: 104



Plot 7-263. Radiated Lower Band Edge Plot SDM (UNII Band 2C)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 188 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS8
Distance of Measurements: 3 Meters
Operating Frequency: 5680MHz
Channel: 136



Plot 7-264. Radiated Lower Band Edge Plot SDM (UNII Band 2C)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5700MHz
Channel: 140



Plot 7-265. Radiated Upper Band Edge Plot CDD (Peak - UNII Band 2C)


FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 189 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5745MHz
Channel: 149



Plot 7-266. Radiated Lower Band Edge Plot CDD (Peak - UNII Band 3)

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5825MHz
Channel: 165




Plot 7-267. Radiated Upper Band Edge Plot CDD (Peak - UNII Band 3)

FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 190 of 208

7.6.12 CDD Radiated Band Edge Measurements (40MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5190MHz
Channel: 38



Plot 7-268. Radiated Lower Band Edge Plot CDD (UNII Band 1)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5230MHz
Channel: 46



Plot 7-269. Radiated Lower Band Edge Plot CDD (UNII Band 1)


FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 191 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5270MHz
Channel: 54



Plot 7-270. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5310MHz
Channel: 62



Plot 7-271. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 192 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5510MHz
Channel: 102



Plot 7-272. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5550MHz
Channel: 110



Plot 7-273. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 193 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5670 MHz
Channel: 134



Plot 7-274. Radiated Upper Band Edge Plot CDD (Peak - UNII Band 2C)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5755MHz
Channel: 151



Plot 7-275. Radiated Lower Band Edge Plot CDD (Peak - UNII Band 3)

FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 194 of 208

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5795MHz
Channel: 159




Plot 7-276. Radiated Upper Band Edge Plot CDD (Peak – UNII Band 3)

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 195 of 208

7.6.13 CDD Radiated Band Edge Measurements (80MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5210MHz
Channel: 42



Plot 7-277. Radiated Lower Band Edge Plot CDD (UNII Band 1)


Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5290MHz
Channel: 58



Plot 7-278. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 196 of 208

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5530MHz
Channel: 106



Plot 7-279. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5775MHz
Channel: 155



Plot 7-280. Radiated Lower Band Edge Plot CDD (Peak - UNII Band 3)

FCC ID: BCGA2198	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device		Page 197 of 208

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5775MHz
Channel: 155



Plot 7-281. Radiated Upper Band Edge Plot CDD (Peak – UNII Band 3)

FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 198 of 208

7.7 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-74 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-74. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 199 of 208

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 200 of 208


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-74.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions within 6dB of the limit. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 201 of 208

CDD Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-282. Radiated Spurious Plot below 1GHz CDD- Ch.36 with AC/DC Adapter


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.83	Max-Peak	V	100	104	-68.01	-9.26	29.73	40.00	-10.27
60.46	Max-Peak	V	250	252	-63.22	-22.15	21.63	40.00	-18.37
131.51	Max-Peak	H	250	127	-68.83	-17.96	20.21	43.52	-23.31
146.26	Max-Peak	H	250	132	-62.62	-19.05	25.33	43.52	-18.19
320.95	Max-Peak	H	100	201	-75.28	-14.85	16.87	46.02	-29.15
944.03	Max-Peak	V	100	288	-78.70	-3.91	24.39	46.02	-21.63

Table 7-75. Radiated Spurious Emissions below 1GHz CDD- Ch. 36 with AC/DC Adapter

FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 202 of 208

Simultaneous Tx Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-283. Radiated Spurious Plot below 1GHz (2.4GHz – 5GHz), with Laptop

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
46.54	Max-Peak	V	100	267	38.94	-18.96	19.98	40.00	-20.02
110.95	Max-Peak	V	100	162	50.12	-17.27	32.85	43.52	-10.67
133.69	Max-Peak	H	250	276	50.17	-18.17	32.00	43.52	-11.52
221.19	Max-Peak	H	100	159	54.96	-17.75	37.21	46.02	-8.81
309.75	Max-Peak	H	100	132	50.17	-14.91	35.26	46.02	-10.76
318.53	Max-Peak	V	100	104	45.72	-14.44	31.28	46.02	-14.74
478.29	Max-Peak	H	100	154	40.79	-10.30	30.49	46.02	-15.53

Table 7-76. Radiated Spurious Plot below 1GHz (2.4GHz – 5GHz), with Laptop

FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 203 of 208

7.8 AC Line-Conducted Test Data

§15.407; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-77. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 204 of 208

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. The traces on the plots were measured with a quasi-peak and average detectors.
7. Deviations to the Specifications: None.

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 205 of 208




Plot 7-284. AC Line Conducted Plot with 802.11n UNII Band 1 – Ch.36 (L1), with Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.314	FINAL	—	32.72	49.86	-17.14	L1	GND
0.314	FINAL	41.2	—	59.86	-18.65	L1	GND
0.632	FINAL	—	29.47	46.00	-16.53	L1	GND
0.632	FINAL	31.7	—	56.00	-24.26	L1	GND
1.577	FINAL	—	27.14	46.00	-18.87	L1	GND
1.581	FINAL	31.1	—	56.00	-24.94	L1	GND
2.202	FINAL	30.5	—	56.00	-25.55	L1	GND
2.207	FINAL	—	25.21	46.00	-20.80	L1	GND
2.524	FINAL	—	22.29	46.00	-23.71	L1	GND
2.531	FINAL	29.0	—	56.00	-26.97	L1	GND
2.868	FINAL	27.6	—	56.00	-28.41	L1	GND
2.870	FINAL	—	20.86	46.00	-25.14	L1	GND

Table 7-78. AC Line Conducted Table with 802.11n UNII Band 1 – Ch.36 (L1), with Adapter

FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 206 of 208



Plot 7-285. AC Line Conducted Plot with 802.11n UNII Band 1 – Ch.36 (N), with Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.152	FINAL	—	24.72	55.88	-31.16	N	GND
0.152	FINAL	47.7	—	65.88	-18.20	N	GND
0.314	FINAL	—	34.41	49.86	-15.45	N	GND
0.314	FINAL	40.1	—	59.86	-19.77	N	GND
0.350	FINAL	—	25.33	48.96	-23.62	N	GND
0.353	FINAL	32.2	—	58.90	-26.76	N	GND
1.257	FINAL	29.6	—	56.00	-26.37	N	GND
1.262	FINAL	—	24.20	46.00	-21.80	N	GND
3.820	FINAL	—	23.17	46.00	-22.83	N	GND
3.824	FINAL	30.3	—	56.00	-25.67	N	GND
19.129	FINAL	29.5	—	60.00	-30.54	N	GND
19.246	FINAL	—	22.63	50.00	-27.37	N	GND

Table 7-79. AC Line Conducted Table with 802.11n UNII Band 1 – Ch.36 (N), with Adapter

FCC ID: BCGA2198	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 207 of 208

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA2198** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2198	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1901280004-09.BCG	Test Dates: 05/01/2019-08/08/2019	EUT Type: Tablet Device	Page 208 of 208