

FCC and ISED Test Report

Apple Inc
Model: A2873

In accordance with FCC 47 CFR Part 15B and
ICES-003 and ISED RSS-GEN (Transmitters Idle)

Prepared for: Apple Inc
One Apple Park Way
Cupertino
California
95014
USA

FCC ID: BCGA2873

IC: 579C-A2873

COMMERCIAL-IN-CONFIDENCE

Document 75957630-07 Issue 01



Add value.
Inspire trust.

TUV
SUD

Digitally signed
by TUV SUD
Date: 2023.03.30
15:44:37 +01'00'

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Andrew Lawson	Chief Engineer	Authorised Signatory	30 March 2023

Signatures in this approval box have checked this document in line with the requirements of TUV SUD document control rules.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15B and ICES-003 and ISED RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	James Cumming	30 March 2023	

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory

ISED Accreditation
12669A Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15B, ICES-003 and ISED RSS-GEN: 2021, Issue 7: 2020 and Issue 5 and A2 (2021-02) for the tests detailed in section 1.3.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2023 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom

TÜV SÜD

TÜV®



Contents

1 Report Summary2

1.1 Report Modification Record.....2

1.2 Introduction.....2

1.3 Brief Summary of Results3

1.4 Product Information4

1.5 Deviations from the Standard.....4

1.6 EUT Modification Record5

1.7 Test Location5

2 Test Details6

2.1 Conducted Disturbance at Mains Terminals6

2.2 Radiated Disturbance..... 11

3 Test Equipment Information 19

3.1 General Test Equipment Used..... 19

4 Incident Reports 20

5 Measurement Uncertainty 21



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	30-March-2023

Table 1

1.2 Introduction

Applicant	Apple Inc
Manufacturer	Apple Inc
Model Number(s)	A2873
Serial Number(s)	WR39R2H474 and N32Y4Q42KC
Hardware Version(s)	REV1.0
Software Version(s)	22E217 and 22E202
Number of Samples Tested	2
Test Specification/Issue/Date	FCC 47 CFR Part 15B, ICES-003 and ISED RSS-GEN: 2021, Issue 7: 2020 and Issue 5 and A2 (2021-02)
Start of Test	23-February-2023
Finish of Test	24-February-2023
Name of Engineer(s)	James Cumming and Connor Lee
Related Document(s)	ANSI C63.4: 2014



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15B and ICES-003 and ISED RSS-GEN is shown below.

Section	Specification Clause	Test Description	Result	Comments/Base Standard
Configuration and Mode: AC Powered - Transmitters Idle				
2.1	15.107, 3.1 and 8.8	Conducted Disturbance at Mains Terminals	Pass	ANSI C63.4: 2014
2.2	15.109, 3.2 and 7.1	Radiated Disturbance	Pass	ANSI C63.4: 2014

Table 2



1.4 Product Information

1.4.1 Technical Description

The equipment under test (EUT) was an Apple desktop computer with Bluetooth® Low Energy, Thread and IEEE 802.11 a/b/g/n/ac/ax Wi-Fi capabilities in the 2.4 GHz, 5 GHz and 6 GHz bands.

1.4.2 EUT Port/Cable Identification

Port	Max Cable Length specified	Usage	Type	Screened
Configuration and Mode: AC Powered - Transmitters Idle				
AC Power Port	2 m	Power	AC to DC Power Adapter with USB-C output.	Yes
USB-C Port 1	2 m	Data	USB-C	Yes
USB-C Port 2	2 m	Data	USB-C	Yes
USB-C Port 3	2 m	Data	USB-C	Yes
Headphone Port	2 m	Audio	Headphone Jack	No

Table 3

1.4.3 Test Configuration

Configuration	Description
AC Powered	The EUT was powered from a 120 V 60 Hz AC mains supply through an AC to DC adapter with a USB-C output connected to USB-C Port 1. The EUT had the following connections made: A set of headphones was used to terminate the EUT's 3.5 mm audio jack port. A USB to USB-C adapter and a mouse was used to terminate USB-C Port 2. A keyboard was used to terminate the EUT's USB-C Port 3.

Table 4

1.4.4 Modes of Operation

Mode	Description
Transmitters Idle	The EUT was powered and operational with the EUT's intentional transmitters turned off. The EUT was configured to display video on its screen whilst playing audio through the headphones. The display was set to maximum brightness and sleep mode was disabled.

Table 5

1.5 Deviations from the Standard

No deviations from the applicable test standard were made during testing.



1.6 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Model: A2873, Serial Number: N32Y4Q42KC			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: A2873, Serial Number: WR39R2H474			
0	As supplied by the customer	Not Applicable	Not Applicable

Table 6

1.7 Test Location

TÜV SÜD conducted the following tests at our Octagon House Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: AC Powered - Transmitters Idle		
Conducted Disturbance at Mains Terminals	James Cumming	UKAS
Radiated Disturbance	James Cumming	UKAS

Table 7

Office Address:

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire
PO15 5RL
United Kingdom



2 Test Details

2.1 Conducted Disturbance at Mains Terminals

2.1.1 Specification Reference

FCC 47 CFR Part 15B, ICES-003 and ISSED RSS-GEN, Clause 15.107, 3.1 and 8.8

2.1.2 Equipment Under Test and Modification State

A2873, S/N: N32Y4Q42KC - Modification State 0

2.1.3 Date of Test

23-February-2023

2.1.4 Test Method

The EUT was setup according to ANSI C63.4, clause 5.2.

The EUT was placed on a non-conductive table 0.8 m above a reference ground plane. A vertical coupling plane was placed 0.4 m from the EUT boundary.

A Line Impedance Stabilisation Network (LISN) was directly bonded to the ground-plane. The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN was 0.8 m.

Interconnecting cables that hanged closer than 0.4 m to the ground plane were folded back and forth in the centre forming a bundle 0.3 m to 0.4 m long.

Input and output cables were terminated with equipment or loads representative of real usage conditions.

The EUT was configured to give the highest level of emissions within reason of a typical installation as described by the manufacturer.

2.1.5 Example Calculation

Quasi-Peak level (dB μ V) = Receiver level (dB μ V) + Correction Factor (dB)
Margin (dB) = Quasi-Peak level (dB μ V) - Limit (dB μ V)

CISPR Average level (dB μ V) = Receiver level (dB μ V) + Correction Factor (dB)
Margin (dB) = CISPR Average level (dB μ V) - Limit (dB μ V)

2.1.6 Example Test Setup Diagram




Figure 1 - Conducted Disturbance

2.1.7 Environmental Conditions

Ambient Temperature	19.1 °C
Relative Humidity	53.5 %
Atmospheric Pressure	996.0 mbar

2.1.8 Specification Limits

Required Specification Limits - Class B			
Line Under Test	Frequency Range (MHz)	Quasi-Peak Test Limit (dB μ V)	CISPR Average Test Limit (dB μ V)
AC Power Port	0.15 to 0.5	66 to 56 ⁽¹⁾	56 to 46 ⁽¹⁾
	0.5 to 5	56	46
	5 to 30	60	50
Supplementary information: Note 1. Decreases with the logarithm of the frequency.			

Table 8

2.1.9 Test Results

Results for Configuration and Mode: AC Powered - Transmitters Idle.

This test was performed to the requirements of the Class B limits.

Performance assessment of the EUT made during this test: Pass.

Detailed results are shown below.




Figure 2 - Graphical Results - AC Power Port Live Line

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector
0.156	44.58	65.70	-21.12	Q-Peak
0.156	39.84	55.70	-15.86	CISPR Avg
0.184	43.94	64.30	-20.36	Q-Peak
0.184	38.83	54.30	-15.47	CISPR Avg
0.218	34.94	62.90	-27.96	Q-Peak
0.218	30.10	52.90	-22.80	CISPR Avg
0.246	38.25	61.90	-23.65	Q-Peak
0.246	35.29	51.90	-16.61	CISPR Avg
0.369	29.56	58.50	-28.94	Q-Peak
0.369	25.90	48.50	-22.60	CISPR Avg
0.399	27.21	57.90	-30.69	Q-Peak
0.399	22.49	47.90	-25.41	CISPR Avg
13.558	37.50	60.00	-22.50	Q-Peak
13.558	32.77	50.00	-17.23	CISPR Avg

Table 9




Figure 3 - Graphical Results - AC Power Port Neutral Line

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector
0.156	43.16	65.70	-22.54	Q-Peak
0.156	36.24	55.70	-19.46	CISPR Avg
0.182	41.23	64.40	-23.17	Q-Peak
0.182	34.30	54.40	-20.10	CISPR Avg
0.215	35.64	63.00	-27.36	Q-Peak
0.215	31.91	53.00	-21.09	CISPR Avg
0.246	37.74	61.90	-24.16	Q-Peak
0.246	32.36	51.90	-19.54	CISPR Avg
0.405	29.71	57.80	-28.09	Q-Peak
0.405	15.75	47.80	-32.05	CISPR Avg
12.001	35.27	60.00	-24.73	Q-Peak
12.001	21.35	50.00	-28.65	CISPR Avg
13.558	38.37	60.00	-21.63	Q-Peak
13.558	33.79	50.00	-16.21	CISPR Avg

Table 10



2.1.10 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Screened Room (12)	MVG	EMC-3	5621	36	11-Aug-2023
Emissions Software	TUV SUD	EmX V3.1.10	5125	-	Software
Test Receiver	Rohde & Schwarz	ESW44	5382	12	01-Jun-2023
Test Receiver	Rohde & Schwarz	ESU40	3506	12	25-Mar-2023
Transient Limiter	Hewlett Packard	11947A	2378	12	25-Oct-2023
Cable (N-Type to N-Type, 8 m)	Teledyne	PR90-088-8MTR	5450	6	23-Apr-2023
Cable (SMA to N-Type, 2 m)	Junkosha	MWX241/B	5817	6	04-Aug-2023
LISN (CISPR 16, Single Phase)	Chase	MN 2050	336	12	04-Jul-2023
LISN (CISPR 16, Single Phase)	Rohde & Schwarz	ESH3-Z5	1390	12	02-Feb-2024

Table 11



2.2 Radiated Disturbance

2.2.1 Specification Reference

FCC 47 CFR Part 15B, ICES-003 and ISSED RSS-GEN, Clause 15.109, 3.2 and 7.1

2.2.2 Equipment Under Test and Modification State

A2873, S/N: WR39R2H474 - Modification State 0

2.2.3 Date of Test

24-February-2023

2.2.4 Test Method

The EUT was set up on a non-conductive table 0.8 m above a reference ground plane within a semi-anechoic chamber on a remotely controlled turntable.

A pre-scan of the EUT emissions profile using a peak detector was made at a 3 m antenna distance whilst varying the antenna-to-EUT azimuth and polarisation.

For an EUT which could reasonably be used in multiple planes, pre-scans were performed with the EUT orientated in X, Y and Z planes with reference to the ground plane.

Using a list of the highest emissions detected during the pre-scan along with their bearing and associated antenna polarisation, the EUT was then formally measured using a Quasi-Peak, Peak or CISPR Average detector as appropriate.

The readings were maximised by adjusting the antenna height, polarisation and turntable azimuth, in accordance with the specification.

2.2.5 Example Calculation

Below 1 GHz:


$$\begin{aligned}\text{Quasi-Peak level (dB}\mu\text{V/m)} &= \text{Receiver level (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ \text{Margin (dB)} &= \text{Quasi-Peak level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}\end{aligned}$$

Above 1 GHz:

$$\begin{aligned}\text{CISPR Average level (dB}\mu\text{V/m)} &= \text{Receiver level (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ \text{Margin (dB)} &= \text{CISPR Average level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}\end{aligned}$$

$$\begin{aligned}\text{Peak level (dB}\mu\text{V/m)} &= \text{Receiver level (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ \text{Margin (dB)} &= \text{Peak level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}\end{aligned}$$

2.2.6 Example Test Setup Diagram



2.2.7 Environmental Conditions

Ambient Temperature	23.9 °C
Relative Humidity	30.3 %
Atmospheric Pressure	1005.0 mbar



2.2.8 Specification Limits

Required Specification Limits, Field Strength - Class B Test Limit at a 3 m Measurement Distance		
Frequency Range (MHz)	Test Limit ($\mu\text{V/m}$)	Test Limit ($\text{dB}\mu\text{V/m}$)
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0
Supplementary information: Note 1. A Quasi-peak detector is to be used for measurements below 1 GHz. Note 2. A CISPR Average detector is to be used for measurements above 1 GHz. Note 3. The Peak test limit above 1 GHz is 20 dB higher than the CISPR Average test limit.		

Table 12

2.2.9 Test Results

Results for Configuration and Mode: AC Powered - Transmitters Idle.

This test was performed to the requirements of the Class B limits.

Performance assessment of the EUT made during this test: Pass.

Detailed results are shown below.

Highest frequency generated or used within the EUT: 6 GHz
Which necessitates an upper frequency test limit of: 30 GHz (Tested to 36 GHz)




Figure 5 - 30 MHz to 1 GHz, Horizontal

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
88.799	10.01	43.50	-33.49	Q-Peak	327	188	Horizontal
104.187	14.03	43.50	-29.47	Q-Peak	338	200	Horizontal

Table 13

No other final measurements were made as all other peak emissions seen above the measurement system noise floor during the pre-scan were greater than 10 dB below the test limit.




Figure 6 - 30 MHz to 1 GHz, Vertical

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
31.096	23.41	40.00	-16.59	Q-Peak	211	100	Vertical
37.485	26.77	40.00	-13.23	Q-Peak	255	109	Vertical
38.982	32.17	40.00	-7.83	Q-Peak	0	101	Vertical
76.883	11.99	40.00	-28.01	Q-Peak	282	100	Vertical
83.410	12.45	40.00	-27.55	Q-Peak	222	100	Vertical
331.358	18.18	46.00	-27.82	Q-Peak	224	143	Vertical

Table 14




Figure 7 - 1 GHz to 36 GHz, Horizontal

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
34465.922	57.03	83.50	-26.47	Peak	350	100	Horizontal
34465.922	44.03	63.50	-19.47	CISPR Avg	350	100	Horizontal
34974.493	57.50	83.50	-26.00	Peak	12	100	Horizontal
34974.493	44.35	63.50	-19.15	CISPR Avg	12	100	Horizontal
35850.496	59.42	83.50	-24.08	Peak	352	100	Horizontal
35850.496	45.90	63.50	-17.60	CISPR Avg	352	100	Horizontal

Table 15

No other final measurements were made as all other peak emissions seen above the measurement system noise floor during the pre-scan were greater than 10 dB below the test limit.




Figure 8 - 1 GHz to 36 GHz, Vertical

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
34415.171	44.09	63.50	-19.41	CISPR Avg	351	100	Vertical
34415.171	57.23	83.50	-26.27	Peak	351	100	Vertical
35859.998	58.49	83.50	-25.01	Peak	316	100	Vertical
35859.998	45.82	63.50	-17.68	CISPR Avg	316	100	Vertical

Table 16

No other final measurements were made as all other peak emissions seen above the measurement system noise floor during the pre-scan were greater than 10 dB below the test limit.



2.2.10 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Screened Room (12)	MVG	EMC-3	5621	36	11-Aug-2023
Emissions Software	TUV SUD	EmX V3.1.10	5125	-	Software
Test Receiver	Rohde & Schwarz	ESU40	3506	12	25-Mar-2023
Turntable & Mast Controller	Maturo Gmbh	NCD/498/2799.01	5612	-	TU
Tilt Antenna Mast	Maturo Gmbh	TAM 4.0-P	5613	-	TU
Cable (N-Type to N-Type, 8 m)	Teledyne	PR90-088-8MTR	5450	6	23-Apr-2023
Cable (K-Type to K-Type, 2 m)	Junkosha	MWX241/B	5909	12	14-Apr-2023
Cable (N-Type to N-Type, 2 m)	Teledyne	PR90-088-2MTR	5196	12	11-Aug-2023
Pre-Amplifier (1 GHz to 18 GHz)	Schwarzbeck	BBV 9718 C	5350	12	20-Oct-2023
Pre-Amplifier (8 GHz to 18 GHz)	Phase One	PS04-0086	1533	12	21-Feb-2023
Pre-Amplifier (18 GHz to 40 GHz)	Phase One	PSO4-0087	1534	12	23-Sep-2023
Antenna with attenuator (Bilog, 30 MHz to 3 GHz)	Schaffner	CBL6143	287	24	02-Dec-2024
Antenna (DRG, 1 GHz to 10.5 GHz)	Schwarzbeck	BBHA9120B	5611	12	16-Oct-2023
Antenna (DRG, 7.5 GHz to 18 GHz)	Schwarzbeck	HWRD750	5348	12	16-Oct-2023
Antenna (DRG, 18 GHz to 40 GHz)	Link Microtek Ltd	AM180HA-K-TU2	230	24	23-Sep-2024

Table 17

TU - Traceability Unscheduled



3 Test Equipment Information

3.1 General Test Equipment Used

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5471	12	06-Apr-2023

Table 18



4 Incident Reports

No incidents reports were raised.



5 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

Test Name	Measurement Uncertainty
Conducted Disturbance at Mains Terminals	150 kHz to 30 MHz, LISN, ± 3.7 dB
Radiated Disturbance	30 MHz to 1 GHz, Bilog Antenna, ± 5.2 dB 1 GHz to 40 GHz, Horn Antenna, ± 6.3 dB

Table 19

Worst case error for both Time and Frequency measurement 12 parts in 10^6 .

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115:2021, Clause 4.4.3 (Procedure 2). The measurement results are directly compared with the test limit to determine conformance with the requirements of the standard.

Risk: The uncertainty of measurement about the measured result is negligible with regard to the final pass/fail decision. The measurement result can be directly compared with the test limit to determine conformance with the requirement (compare IEC Guide 115). The level of risk to falsely accept and falsely reject items is further described in ILAC-G8.